HUPTLE HR TECHNOLOGIES

Partner Integration Specification & 1-Click SSO Protocol

Technical Guide for Mentorlee Engineering Team | Production Release v1.0 | October 2026

1. Overview & Architecture

I have prepared this technical specification to establish a direct, zero-friction bridge between Mentorlee's platform and Huptle's Job Portal (**apply.huptle.com**). Our integration is architected around two primary pillars:

1. Real-Time Job Syndication: A secure REST API allowing your backend or client application to query active, verified job openings hosted on Huptle, complete with metadata, screening parameters, and direct apply links.
2. Cryptographic 1-Click Single Sign-On (SSO): An industry-standard tokenized handoff using HMAC-SHA256 signatures. When an authenticated candidate on Mentorlee clicks to apply, they are redirected to Huptle and automatically logged in. Their verified email and name are injected seamlessly without requiring a separate password, registration form, or credential re-entry.

Step 1: Discover Jobs	Mentorlee backend queries GET /api/partner/jobs with partner key to fetch active roles.
Step 2: Candidate Handoff	Candidate clicks 'Apply'. Mentorlee creates an HMAC-SHA256 JWT containing candidate identity.
Step 3: Secure Session	Candidate is redirected to https://apply.huptle.com/auth/partner?token=....
Step 4: Immediate Apply	Huptle verifies the signature in constant-time, sets secure HTTP-only cookies, and routes to target job.

2. Credentials & Production Environment

I have provisioned dedicated production credentials for your application. Please store these securely in your production secrets manager (e.g., AWS Secrets Manager, Vault, or GCP Secret Manager). Never expose the SSO Secret in client-side bundles.

Parameter	Assigned Production Value	Scope & Purpose
Production Base URL	`https://apply.huptle.com`	Public portal gateway
Partner API Key	`vBDyubhdP5xSsSzgOR3OVFX41kFfllO4TiWdGdKY1EA=`	Job syndication endpoint authentication
Partner SSO Secret	`vBDyubhdP5xSsSzgOR3OVFX41kFfllO4TiWdGdKY1EA=`	HMAC-SHA256 signature generation
Token Validity (TTL)	`300 seconds (5 minutes)`	Replay attack protection window

3. Job Syndication REST API

To sync active Huptle job postings into your portal, issue authenticated GET requests to our jobs endpoint. Responses are cached for 60 seconds with stale-while-revalidate headers for optimal edge latency.

Method & URL:	`GET https://apply.huptle.com/api/partner/jobs`
Required Headers:	X-Partner-Key: <YOUR_PARTNER_API_KEY> *(or Authorization: Bearer <YOUR_PARTNER_API_KEY>)*

Response Schema (`200 OK` JSON):

4. 1-Click Single Sign-On (SSO) Protocol

When a logged-in user on Mentorlee interacts with an integrated job opening, your application initiates a browser redirect. The candidate passes through our authentication route and lands on the designated job page with a fully hydrated profile and active session.

Redirect URL Pattern:

```
https://apply.huptle.com/auth/partner?token=<SIGNED_HMAC_JWT>&redirect;=/apply/<JOB_ID>
```

Token Specification & Required Claims:

Claim	Type	Required	Description & Example
`iss`	string	Optional	Issuer identifier. Set to "mentorlee".
`sub`	string	**Yes**	Unique user identifier in your database (e.g. "usr_12345").
`email`	string	**Yes**	Candidate's verified email address.
`name`	string	Recommended	Full display name used to pre-fill their candidate application.
`redirect`	string	Recommended	Target landing path on Huptle (e.g. "/apply/<jobId>").
`iat`	integer	Recommended	Unix timestamp in seconds when the token was minted.
`exp`	integer	**Yes**	Expiration timestamp. Maximum allowed window is 300 seconds (5 min).
`jti`	string	Recommended	Unique nonce / UUID to protect against replay attacks.

5. Implementation Code (Ready-to-Use)

You can drop either of the following production snippets directly into your codebase:

TypeScript / Node.js Implementation:

Python (FastAPI / Django / Flask) Implementation:

6. Security Guarantees & Error Handling

Our integration adheres strictly to modern web security guidelines to safeguard candidate privacy and prevent unauthorized access:

• **Zero Password Transmission:** Neither platform transmits candidate credentials or passwords. Authentication is purely cryptographic.
• **Timing Attack Immunity:** All HMAC signatures are evaluated on our servers using constant-time byte comparisons (crypto.timingSafeEqual).
• **Replay Immunity:** Expired tokens or duplicate nonces are blocked immediately.
• **Secure Session Hardening:** Successful handoffs establish HttpOnly, Secure, SameSite=Lax session cookies.

Status Code Reference:

HTTP Code	Scenario	Recommended Resolution
`200 OK`	Successful verification / Jobs retrieved	Normal operation. User redirected to job application.
`400 Bad Request`	Missing token parameter or missing email	Ensure the query parameter is passed as ?token=....
`401 Unauthorized`	Invalid HMAC signature or missing API key	Verify that the secret string matches the assigned production secret.
`401 Unauthorized`	Token expired (exceeded 5 min TTL)	Generate a fresh token immediately prior to user redirection.

7. Pre-Launch Verification Checklist

Before announcing the integration to your users, please complete the following verification steps:
[ ] Execute a test request to GET /api/partner/jobs with your key to confirm job feed ingestion.
[ ] Generate a test token for a staging candidate and verify that clicking the generated URL opens the job with their email pre-filled.
[ ] Confirm your token expiration timestamp (exp) is set to 300 seconds from generation.
[ ] Ensure the shared secret is stored as a secret environment variable and not compiled into client-side web bundles.

8. Engineering Support & Escalation

I am personally available to assist your development team with any questions, testing, or end-to-end sandbox validation. Please feel free to reach out directly if you need us to review your token generation logic or provision additional webhook hooks.

Huptle Engineering Team
Portal: https://apply.huptle.com
Technical Escalations: engineering@huptle.com