

ROTO F Series



HURRICANE
ROTAVATORS



WE
RESPECT
FARMERS

FOCUS

MANUFACTURING COMPANY

A Product by Focus Manufacturing Company

Head Office: 2419, St.no. 14, S.K.S Nagar, Gill Road, Ludhiana- 141006, Punjab IN.
T: 998877 9566
E: [hurricanerotawtors@gmail.com](mailto:hurricanerotawators@gmail.com)
W: focusmanufacturing.co/hurricane

Scan To visit FB Page



ROTO F Series

MODEL	Roto F-6	Roto F-7	Roto F-8
Overall Length (in mm)	2026	2259	2481
Overall Width (in mm)		845	
Overall Height (in mm)		1139	
Tilling Width (mm/inch)	1881/74	2114/83.2	2336/92
Tractor power (HP/KW)	50-65/37-48	60-75/45-56	65-75/48-56
3-Point Hitch Type		CAT-II	
Frame Off-set (mm/inch)	30/1.2	50.8/2	58.42/2.3
No. of Tines (L/C -80/7)	42	48	54
Standard tine Construction		Curved	
Transmission Type		Gear	
Max. Working Depth (mm/inch)		178/7	
Rotor Tube Dia (mm/inch)		90/3.54	
Rotor Swing Dia (mm/inch)		450/17.7	
Driveline Safety Device		Shear Bolt/Slip Clutch	
Weight (KG/lbs)	447/987	484/1068	561/1237

Series	Input RPM	Gear Box	Spur Gear 1	Spur Gear 2	Rotor Speed
ROTO-F	540	Multi Speed	16	19	184
			17	18	206
			18	17	231
	1000	Multi Speed	13	22	239

ADVANTAGES:

- Suitable for hard soil.
- It helps in retaining moisture of the soil and increases soil porosity and aeration which enhances germination and growth of crops.
- Its specially designed blade rotor reduces load on tractor as well as diesel consumption and avoids tyre slippage