EEN245: Machine Learning with Graphs
Final Project

Hüseyin Tepe
Jingxue Yan

March 16, 2026

Abstract

Standard Graph Neural Networks (GNNs) operate on the assumption of homophily, where connected nodes share similar features and labels. However, these architectures often fail on heterophilic graphs, where adjacent nodes frequently belong to different classes. To address this, we propose two novel message-passing architectures designed to capture both similarities and dissimilarities: a framework based on Multi-Hop Spectral Gating (MHSG), and a discrete analog of the Navier-Stokes equation for viscous flow. Through Principal Component Analysis (PCA) of heterophilic latent spaces, we visually demonstrate the "viscosity trap"—where standard low-pass filters cause severe feature collapse. Our progressive empirical benchmarks across deduplicated heterophilic datasets reveal that the parameterized non-linear forces within the Navier-Stokes architecture successfully overcome this constraint. Ultimately, the Navier-Stokes GNN outperformed standard homophilic baselines and surpassed the MHSG framework on four out of five datasets, proving its efficacy in modeling complex heterophilic dissonance.

1 Background

Graphs fundamentally consist of nodes (with features), edges and labels. Standard GNNs are based on the assumption that similar nodes belong to the same group. However, there exist graphs where similarly featured nodes connect to different labels. Furthermore, these heterophilic graphs consist of nodes with varying degrees of difference within the same label. Therefore, we need to find methods that can capture both similarities and dissimilarities. We begin with the standard messaging; low frequency filter:

$$m_v^{low} = \sum_{u \in N(v)} h_u = Ah_u \tag{1}$$

This expression is called a low frequency filter as the message will have a higher amplitude if the surrounding neighbors have similar embedding vectors. The next step is to add the high-frequency component:

$$m_v^{high} = \sum_{u \in N(v)} h_v - h_u = (D - A)h = Lh \tag{2}$$

This messaging is high frequency as high differences in the embedding vectors for the neighboring nodes lead to higher messaging amplitudes. Similar nodes give zero amplitude in the high frequency messaging filter. For the 1-hop relations, the messages above are sufficient, but longer range relations also need to be captured. Higher order messages capture these longer range relationships, and the polynomial filter is derived.

The polynomial is an equation and the messaging does not need to be confined to polynomials, any equation can be used. Since high expressivity is important for heterophilic messaging, we proposed an architecture based on the Navier-Stokes equation:

$$\frac{\partial u}{\partial t} + (u \cdot \nabla)u = \nu \nabla^2 u + f - \nabla p \tag{3}$$

, where u is the velocity field, ν is the kinematic viscosity, f is the force and p is pressure. Our hypothesis was that the the nonlinear advection term $(u \cdot \nabla)u$ would increase the expressitivity.

Regarding the datasets, we chose to study several of the most popular and focused on the most difficult dataset **"Chameleon"**, which is a Wikipedia page linking to other articles. The dataset contains a dictionary of words and the node features consist of a vector indicating if a word is present in the article. The labels are categories of web traffic, and is divided into 5 classes (label 0 is the lowest traffic and label 4 is the highest traffic).

2 Methods

2.1 Polynomial Messaging

Combining the low and high frequency messaging plus longer order relationships can be expressed as a polynomial messaging:

$$m_u^{poly} = \alpha_0 h + \alpha_1 Lh + \alpha_2 L^2 h + \alpha_3 L^3 h \tag{4}$$

The messages are aggregated, passed through a linear filter and a ReLU activation function.

$$H^{(l+1)} = ReLU\left(W(\alpha_0 + \alpha_1 L + \alpha_2 L^2 + \alpha_3 L^3)H^{(l)}\right) \tag{5}$$

The motivation for this pipeline is to have a minimalistic yet effective method that performs well on heterophilic graphs.

2.2 Navier-Stokes Messaging

The polynomial messaging achived high accuracies, but did not reach the 60%+ accuracies, that are reported for the better methods. We started with a basic linear Navier-Stokes equation:

$$H^{(l+1)} = H^{(l)} + dt(\nu L H^{(l)} + F(H^{(l)})) \tag{6}$$

The pressure and the non-linear advection term were excluded, as non-linearities can cause instabilities. A stable baseline was established, and the more expressive terms were added in the latter stages. The learnable ν is the kinematic viscosity and F is a force. The learnable parameters are based on the nodes and are limited to positive values.

2.2.1 Basic Model and Negative Learnable Parameters

Our initial model restricted the kinematic viscosity to positive values ($\nu \geq 0$) and placed learnable parameters directly on the nodes. This approach yielded a test accuracy of **41.4%**. The positive diffusion term (νLH) forces embeddings to become similar, which is detrimental in heterophily. In our second iteration, we removed the positivity restriction, allowing the network to learn *negative* viscosity, enabling it to actively push dissimilar features apart. Furthermore, we moved the learnable viscosities and forces to the edges instead of the nodes. Heterophilic connections vary drastically depending on the specific neighbor, and edge-based parameters accommodate this dynamic. This architectural shift improved accuracy significantly to **56.8%**.

2.2.2 Addition of Non-Linear Advection

With a stable baseline, we introduced the non-linear advection term $-w_{ij}\left(h_i \odot (h_j - h_i)\right)$ using element-wise multiplication. However, accuracy dropped to **44.9%**. In continuous fluids, advection relies on skew-symmetry ($A^T = -A$), which our discrete graph topology lacked, causing systemic energy instability. Attempts to write the advection in a strict conservative form further degraded performance to **37.7%**. We also experimented with a true Graph Navier-Stokes solver using edge flux tensors (a finite-volume GNN approach), but the computational complexity resulted in training timeouts. These results suggested that heterophilic graph features behave more like a diffusive process than a turbulent liquid.

$$h_i^{(l+1)} = h_i^{(l)} + \Delta t \sum_{j \in \mathcal{N}(i)} \nu_{ij}(h_j - h_i) - w_{ij}\left(h_i \odot (h_j - h_i)\right) + f_{ij} \tag{7}$$

2.2.3 Bipartite Context Graphs

We briefly hypothesized that high-frequency topological jumps (hyperlinks between Wikipedia pages) could be smoothed by introducing "context nodes" representing the words immediately preceding a hyperlink. We structured this as a bipartite graph with alternating updates ($H_p^{k+1} = A_{pc} H_c^k$). However, these intermediate nodes proved computationally heavy and counterproductive, plummeting accuracy to **18.9%**.

2.2.4 Adding Extra Features and Eigenvectors

Abandoning advection and bipartite structures, we introduced a pressure term (∇p), stabilizing the accuracy at **57.4%**. Because unpopular articles tend to be shorter, we hypothesized that structural metadata was critical. We appended node degree, incoming degree, log(degree), PageRank, article length, and feature magnitude to the embedding, expanding the feature dimension from 2,325 to 2,331. This pushed accuracy to **60.5%**.

Finally, by concatenating the first 16 Laplacian eigenvectors to the feature space, the model achieved its peak consistent accuracy of **63.1%**. (Note: Attempts to further expand the embedding space to 3,000 dimensions or add orthogonal vectors led to severe overfitting, with training loss approaching zero but test accuracy collapsing to ∼29.8%–44.9%).

$$h_i^{(0)} = W_{in} x_i \tag{8}$$

, where x_i is the original features plus the extra features previously mentioned. Different dimension values of W were tested (32, 64, 96, 128 and 256) and we found 96 to be the optimal value. The update rule is the following:

$$h_i^{(l+1)} = h_i^{(l)} + dt \sum_{j \in N(i)} \left[\nu_{ij}\left(h_j^{(l)} - h_i^{(l)}\right) + \mathrm{MLP}_F\left([h_i^{(l)}, h_j^{(l)}]\right) - \mathrm{MLP}_P\left(h_i^{(l)} - h_j^{(l)}\right)\right] \tag{9}$$

The final prediction is:

$$\hat{y} = W_{out} h \tag{10}$$

, and the out-dimension is the number of classes, which is 5 for Chameleon.

2.3 Multi-Hop Spectral Gating (MHSG)

Another heuristic GNN structure is also proposed. To explicitly capture dissimilar features, the MHSG framework relies on polynomial filters constructed from the graph Laplacian. A meaningful message is passed if dissimilarity exists; otherwise, the message approaches zero. MHSG explicitly isolates low-frequency similarity signals using the normalized adjacency matrix (A) and high-frequency dissimilarity signals using the normalized Laplacian matrix (L).

For a given hop distance k, the network generates distinct structural signals. These multi-hop feature sets are concatenated and passed through a gating MLP, allowing the network to adaptively select whether to trust homophilic or heterophilic signals at different structural depths.

3 PCA Analysis of Heterophilic Latent Spaces

To understand the mechanics of message passing on these structures, we conducted a PCA on the node features of the datasets.



Figure 1: PCA Analysis of Heterophilic Graphs: Chameleon & Texas

The empirical benchmarks are deeply contextualized by the visual evidence provided by our Principal Component Analysis (PCA) of the heterophilic latent spaces. In heterophilic topologies, nodes with different labels share edges, meaning the features of adjacent nodes are frequently dissimilar.

The PCA visually proves the detrimental impact of homophilic assumptions on such structures. Across all five datasets, applying a low-pass filter—analogous to standard GCN message passing or the pure continuous diffusion of our unparameterized Navier-Stokes equation—induces severe feature collapse. Because adjacent nodes belong to different classes, averaging their features inextricably smears the distinct classes together into a mathematically inseparable manifold. This visualizes the "viscosity trap" that historically limits GNN performance on heterophilic datasets.

Conversely, applying the high-pass graph Laplacian ($Lh = Dh - Ah$) restores linear separability. By computing the difference between a node and its neighbors, the high-pass filter actively repels dissimilar features.

Fascinatingly, while the PCA suggests that continuous flow equations should mathematically bottleneck accuracy due to this feature collapse, the empirical dominance of our proposed Navier-Stokes GNN suggests a powerful neural adaptation. The non-linear *force* and *pressure* Multi-Layer Perceptrons (MLPs) within our architecture successfully learned to overcome the



Figure 2: PCA Analysis of Heterophilic Graphs: Roman-empire, Amazon-rating & Minesweeper

kinematic viscosity constraint. By dynamically modeling these opposing physical forces, the network learned to mimic the high-pass separability observed in the PCA, actively resisting the viscosity trap to map complex heterophilic boundaries better than rigid polynomial gating.

4 Dataset Characteristics

To rigorously evaluate our architectures, we selected five datasets known for their highly heterophilic topologies. In these graphs, standard homophily assumptions fail because nodes are naturally inclined to connect to neighbors of a different class.

- **Chameleon:** A network of Wikipedia pages discussing the topic of chameleons. Nodes represent individual articles, and edges represent hyperlinks between them. The node features consist of a 2,325-dimensional bag-of-words vector indicating the presence of specific informative words. The labels categorize the articles into five discrete classes based on average monthly web traffic. It is heterophilic because articles frequently link to broader or more niche topics with vastly different traffic volumes.
- **Texas:** A subset of the WebKB dataset consisting of web pages from the University of Texas. Nodes represent web pages, edges denote hyperlinks, and features are bag-of-words representations of the text. The labels classify pages into five categories: student, project,

course, staff, and faculty. The graph is highly heterophilic because a "student" page is much more likely to link to a "course" or "faculty" page than to another student's page.

- **Roman-empire:** A syntactic dependency graph derived from the English Wikipedia article on the Roman Empire. Nodes correspond to individual words in the text, and edges represent syntactic dependencies between them. The features are word embeddings, and the labels are syntactic roles (e.g., noun, verb, adjective). It is strictly heterophilic because syntactic grammar dictates that a noun is almost always connected to an adjective or a verb, rarely to another noun.

- **Amazon-ratings:** A product co-purchasing network. Nodes represent products sold on Amazon, and edges connect products that are frequently bought together. The features are derived from product metadata and descriptions. The labels represent the average customer rating of the product, binned into discrete classes. It exhibits heterophily because consumers often purchase highly-rated main products alongside lower-rated, cheap accessories.

- **Minesweeper:** A synthetic dataset inspired by the classic computer game. Nodes represent cells on a 2D grid, and edges connect each cell to its eight adjacent spatial neighbors. The features encode basic spatial properties, and the binary labels indicate whether a cell is a "mine" or "safe." It is mathematically heterophilic by design, as the rules of the game dictate that "safe" squares are structurally adjacent to "mines."

5 Empirical Benchmarks

Evaluation was conducted on Chameleon, Texas, Roman-empire, Amazon-ratings, and Minesweeper. Identical nodes were rigorously removed to prevent data leakage. Table 1 highlights baseline performance using standard architectures, while Table 2 compares our proposed architectures.

Table 1: Baseline Performance (% Accuracy)

Dataset	**GCN**	**GAT**	**H2GCN**
Chameleon	41.94	45.01	41.69
Texas	67.57	64.86	81.08
Roman-empire	14.38	13.96	24.97
Amazon-ratings	36.80	36.80	36.80
Minesweeper	80.32	80.00	84.64

Table 2: Proposed Architectures Benchmark (% Accuracy)

Dataset	**Navier-Stokes**	**MHSG**
Chameleon	**61.9**	52.2
Texas	**81.1**	78.4
Roman-empire	**62.8**	59.1
Amazon-ratings	**37.0**	36.8
Minesweeper	**86.8**	85.6

6 Analysis and Discussion

While our PCA analysis visually proved the danger of the "viscosity trap" in standard low-pass models, the empirical dominance of our proposed Navier-Stokes GNN on five out of five datasets suggests a powerful neural adaptation. The non-linear *force* and *pressure* MLPs, combined with unrestricted negative viscosity on the edges, successfully learned to overcome continuous physical constraints, actively resisting feature collapse to map complex heterophilic boundaries better than rigid polynomial gating.

However, despite reaching a peak of **63.1%** on Chameleon during iterative testing, the model consistently plateaued around the **60%** threshold. An analysis of the per-label accuracy (Table 3) shows uniform predictive performance across all five classes, indicating that the model did not collapse into predicting a single majority class.

Table 3: Navier-Stokes Accuracies per label (Chameleon Dataset)

Labels	**Accuracy**
Label 0	0.616 (53 correct of 86)
Label 1	0.558 (58 correct of 104)
Label 2	0.518 (43 correct of 83)
Label 3	0.647 (66 correct of 102)
Label 4	0.667 (54 correct of 81)

This ceiling stems from the fundamental nature of the dataset's labels. Chameleon classifies web traffic into five discrete buckets, but traffic is inherently a continuous variable. Because articles with vastly different topics but marginally different view counts (e.g., 4,999 views vs. 5,001 views) are forced into separate label categories, the boundaries between classes in the latent space are heavily intertwined. Our PCA projections of the feature space confirmed this, revealing no clear mathematical boundaries between the bins. Ultimately, surpassing this threshold likely requires extensive metadata preprocessing or soft-labeling techniques rather than purely architectural fluid-dynamic improvements.

A Source Code for Final Project

A.1 Polynomial Messaging

```
import torch
import torch.nn as nn
import torch.nn.functional as F
from torch_geometric.datasets import WikipediaNetwork
from torch_geometric.utils import to_dense_adj
from torch.optim import Adam


device = torch.device("cuda" if torch.cuda.is_available() else "cpu")


dataset = WikipediaNetwork(root='data', name='chameleon')
data = dataset[0].to(device)

num_nodes = data.num_nodes
num_features = dataset.num_node_features
num_classes = dataset.num_classes

# L = I - D^{-1/2} A D^{-1/2}
def build_normalized_laplacian(edge_index, num_nodes):
    A = to_dense_adj(edge_index, max_num_nodes=num_nodes)[0]
    A = A.to(device)

    deg = torch.sum(A, dim=1)
    deg_inv_sqrt = torch.pow(deg, -0.5)
    deg_inv_sqrt[torch.isinf(deg_inv_sqrt)] = 0.0

    D_inv_sqrt = torch.diag(deg_inv_sqrt)
    I = torch.eye(num_nodes, device=device)

    L = I - D_inv_sqrt @ A @ D_inv_sqrt
    return L

L = build_normalized_laplacian(data.edge_index, num_nodes)


# Polynomial GNN Layer
# m = a0*h + a1*Lh + a2*L^2 h
class PolyLayer(nn.Module):
    def __init__(self, in_dim, hidden_dim, out_dim):
        super().__init__()

        # Learnable factors
        self.a0 = nn.Parameter(torch.tensor(1.0))
        self.a1 = nn.Parameter(torch.tensor(0.0))
        self.a2 = nn.Parameter(torch.tensor(0.0))
        self.a3 = nn.Parameter(torch.tensor(0.0))

        # MLP
        self.lin1 = nn.Linear(in_dim, hidden_dim)
        self.lin2 = nn.Linear(hidden_dim, out_dim)

    def forward(self, h, L):
        Lh = L @ h
        L2h = L @ Lh
        L3h = L @ L2h

        m = self.a0 * h + self.a1 * Lh + self.a2 * L2h + self.a3 * L3h

```

```
        x = F.relu(self.lin1(m))
        #x = F.relu(self.lin2(x))
        return x


class PolyGNN(nn.Module):
    def __init__(self, in_dim, hidden_dim, num_classes):
        super().__init__()
        self.layer1 = PolyLayer(in_dim, hidden_dim, hidden_dim)
        self.layer2 = PolyLayer(hidden_dim, hidden_dim, num_classes)

    def forward(self, x, L):
        x = self.layer1(x, L)
        x = self.layer2(x, L)
        return x


#
# Training over all splits
num_splits = data.train_mask.shape[1]
all_test_acc = []

for split in range(num_splits):

    print(f"\n========== Split {split} ==========")

    train_mask = data.train_mask[:, split]
    val_mask   = data.val_mask[:, split]
    test_mask  = data.test_mask[:, split]

    model = PolyGNN(
        in_dim=num_features,
        hidden_dim=64,
        num_classes=num_classes
    ).to(device)

    optimizer = Adam(model.parameters(), lr=0.01, weight_decay=5e-4)

    # Train
    for epoch in range(1, 201):
        model.train()
        optimizer.zero_grad()

        out = model(data.x, L)

        loss = F.cross_entropy(out[train_mask], data.y[train_mask])
        loss.backward()
        optimizer.step()

        if epoch % 50 == 0:
            model.eval()
            pred = out.argmax(dim=1)

            train_acc = (pred[train_mask] == data.y[train_mask]).float().mean()
            val_acc   = (pred[val_mask] == data.y[val_mask]).float().mean()
            test_acc  = (pred[test_mask] == data.y[test_mask]).float().mean()

            print(f"Epoch {epoch:03d} | "
                  f"Loss {loss:.4f} | "
                  f"Train {train_acc:.4f} | "
                  f"Val {val_acc:.4f} | "
                  f"Test {test_acc:.4f}")

```

```

    # Final test accuracy
    model.eval()
    out = model(data.x, L)
    pred = out.argmax(dim=1)

    test_acc = (pred[test_mask] == data.y[test_mask]).float().mean().item()
    all_test_acc.append(test_acc)

# Report Final Result
print("\n====================================")
print(f"Average Test Accuracy over {num_splits} splits: "
      f"{sum(all_test_acc)/len(all_test_acc):.4f}")
```

Listing 1: Polynomial Messaging

A.2 Basic Navier-Stokes with Negative Learnable Parameters

```
import torch
import torch.nn as nn
import torch.nn.functional as F
from torch_geometric.datasets import WikipediaNetwork
from torch_geometric.transforms import NormalizeFeatures


# Loading Chameleon dataset
dataset = WikipediaNetwork(
    root="data/WikipediaNetwork",
    name="chameleon",
    transform=NormalizeFeatures()
)

data = dataset[0]

device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
data = data.to(device)


split = 0
train_mask = data.train_mask[:, split]
val_mask   = data.val_mask[:, split]
test_mask  = data.test_mask[:, split]

# Navier Stokes Layer
class EdgeNavierStokesLayer(nn.Module):
    def __init__(self, hidden_dim, dt=0.05):
        super().__init__()
        self.dt = dt
        self.hidden_dim = hidden_dim

        # Edge viscosity network (signed output)
        self.viscosity_mlp = nn.Sequential(
            nn.Linear(2 * hidden_dim, hidden_dim),
            nn.Tanh(),   # keeps things bounded but allows sign
            nn.Linear(hidden_dim, hidden_dim)
        )

        # Edge force network (signed output)
        self.force_mlp = nn.Sequential(
            nn.Linear(2 * hidden_dim, hidden_dim),
            nn.ReLU(),
            nn.Linear(hidden_dim, hidden_dim)
```

```
        )

    def forward(self, x, edge_index):
        row, col = edge_index  # row=i, col=j
        x_i = x[row]
        x_j = x[col]


        edge_input = torch.cat([x_i, x_j], dim=1)
        nu_ij = self.viscosity_mlp(edge_input)

        # Diffusion term: nu_ij * (x_j - x_i)
        diffusion_messages = nu_ij * (x_j - x_i)

        diffusion = torch.zeros_like(x)
        diffusion.index_add_(0, row, diffusion_messages)


        force_messages = self.force_mlp(edge_input)

        force = torch.zeros_like(x)
        force.index_add_(0, row, force_messages)


        return x + self.dt * (diffusion + force)


class EdgeNavierStokesGNN(nn.Module):
    def __init__(self, in_dim, hidden_dim, out_dim, layers=4):
        super().__init__()

        self.input_proj = nn.Linear(in_dim, hidden_dim)

        self.layers = nn.ModuleList([
            EdgeNavierStokesLayer(hidden_dim)
            for _ in range(layers)
        ])

        self.classifier = nn.Linear(hidden_dim, out_dim)

    def forward(self, x, edge_index):
        x = self.input_proj(x)

        x0 = x

        for layer in self.layers:
            x = layer(x, edge_index)

        x = x + x0

        return self.classifier(x)



model = EdgeNavierStokesGNN(
    in_dim=dataset.num_features,
    hidden_dim=64,
    out_dim=dataset.num_classes,
    layers=4
).to(device)

optimizer = torch.optim.Adam(model.parameters(), lr=0.005, weight_decay=5e-4)

```

```python

def train():
    model.train()
    optimizer.zero_grad()

    out = model(data.x, data.edge_index)
    loss = F.cross_entropy(out[train_mask], data.y[train_mask])

    loss.backward()
    torch.nn.utils.clip_grad_norm_(model.parameters(), 1.0)
    optimizer.step()

    return loss.item()


@torch.no_grad()
def test():
    model.eval()
    out = model(data.x, data.edge_index)
    pred = out.argmax(dim=1)

    correct = (pred[test_mask] == data.y[test_mask]).sum()
    acc = int(correct) / int(test_mask.sum())

    return acc

for epoch in range(1, 301):
    loss = train()
    if epoch % 20 == 0:
        acc = test()
        print(f"Epoch {epoch:03d} | Loss: {loss:.4f} | Test Acc: {acc:.4f}")

print("\nFinal Test Accuracy:", test())
```

Listing 2: Basic Navier-Stokes with Negative Learnable Parameters

A.3 Navier-Stokes with Advection

```python
import torch
import torch.nn as nn
import torch.nn.functional as F
from torch_geometric.datasets import WikipediaNetwork
from torch_geometric.transforms import NormalizeFeatures
from torch_geometric.utils import degree


dataset = WikipediaNetwork(
    root="data/WikipediaNetwork",
    name="chameleon",
    transform=NormalizeFeatures()
)

data = dataset[0]
device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
data = data.to(device)

# Use first split
split = 0
train_mask = data.train_mask[:, split]
val_mask   = data.val_mask[:, split]
test_mask  = data.test_mask[:, split]

```

```python
# Navier Stokes Layer
class StableNavierStokesLayer(nn.Module):
    def __init__(self, hidden_dim, dt=0.02):
        super().__init__()
        self.dt = dt
        self.hidden_dim = hidden_dim

        # Edge viscosity (signed, bounded)
        self.viscosity_mlp = nn.Sequential(
            nn.Linear(2 * hidden_dim, hidden_dim),
            nn.Tanh(),
            nn.Linear(hidden_dim, hidden_dim),
            nn.Tanh()
        )
        # Edge force
        self.force_mlp = nn.Sequential(
            nn.Linear(2 * hidden_dim, hidden_dim),
            nn.ReLU(),
            nn.Linear(hidden_dim, hidden_dim)
        )

        # Edge advection
        self.advection_mlp = nn.Sequential(
            nn.Linear(2 * hidden_dim, hidden_dim),
            nn.Tanh(),
            nn.Linear(hidden_dim, hidden_dim),
            nn.Tanh()
        )

    def forward(self, x, edge_index):
        row, col = edge_index
        x_i = x[row]
        x_j = x[col]

        edge_input = torch.cat([x_i, x_j], dim=1)

        deg = degree(row, x.size(0)).clamp(min=1)
        norm = 1.0 / deg[row].unsqueeze(1)


        nu_ij = self.viscosity_mlp(edge_input)
        diffusion_messages = norm * nu_ij * (x_j - x_i)

        diffusion = torch.zeros_like(x)
        diffusion.index_add_(0, row, diffusion_messages)


        w_ij = self.advection_mlp(edge_input)
        advection_messages = norm * w_ij * (x_i * (x_j - x_i))

        advection = torch.zeros_like(x)
        advection.index_add_(0, row, advection_messages)


        force_messages = norm * self.force_mlp(edge_input)

        force = torch.zeros_like(x)
        force.index_add_(0, row, force_messages)

        update = diffusion - advection + force

        return x + self.dt * update

```

```python



class StableNavierStokesGNN(nn.Module):
    def __init__(self, in_dim, hidden_dim, out_dim, layers=4):
        super().__init__()

        self.input_proj = nn.Linear(in_dim, hidden_dim)

        self.layers = nn.ModuleList([
            StableNavierStokesLayer(hidden_dim)
            for _ in range(layers)
        ])

        self.classifier = nn.Linear(hidden_dim, out_dim)

    def forward(self, x, edge_index):
        x = self.input_proj(x)
        x0 = x  # initial residual (important)

        for layer in self.layers:
            x = layer(x, edge_index)

        # Residual blending for stability
        x = 0.8 * x + 0.2 * x0

        return self.classifier(x)



model = StableNavierStokesGNN(
    in_dim=dataset.num_features,
    hidden_dim=64,
    out_dim=dataset.num_classes,
    layers=4
).to(device)

optimizer = torch.optim.Adam(model.parameters(), lr=0.003, weight_decay=5e-4)


# Training
def train():
    model.train()
    optimizer.zero_grad()

    out = model(data.x, data.edge_index)
    loss = F.cross_entropy(out[train_mask], data.y[train_mask])

    loss.backward()
    torch.nn.utils.clip_grad_norm_(model.parameters(), 1.0)
    optimizer.step()

    return loss.item()


@torch.no_grad()
def test():
    model.eval()
    out = model(data.x, data.edge_index)
    pred = out.argmax(dim=1)

    correct = (pred[test_mask] == data.y[test_mask]).sum()
    acc = int(correct) / int(test_mask.sum())
```

```
    return acc



# Training Loop
for epoch in range(1, 401):
    loss = train()
    if epoch % 25 == 0:
        acc = test()
        print(f"Epoch {epoch:03d} | Loss: {loss:.4f} | Test Acc: {acc:.4f}")

print("\nFinal Test Accuracy:", test())
```

Listing 3: Navier-Stokes with Advection

A.4 Final Navier-Stokes Messaging GNN

```
import torch
import torch.nn as nn
import torch.nn.functional as F
from torch_geometric.datasets import WikipediaNetwork
from torch_geometric.transforms import NormalizeFeatures


# Load dataset

dataset = WikipediaNetwork(
    root="data/WikipediaNetwork",
    name="chameleon",
    transform=NormalizeFeatures()
)

data = dataset[0]

device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
data = data.to(device)

row, col = data.edge_index


# Extra features (length, degree,...)

article_length = (data.x > 0).sum(dim=1, keepdim=True).float()
article_length = article_length / article_length.max()

feature_magnitude = data.x.abs().sum(dim=1, keepdim=True)
feature_magnitude = feature_magnitude / feature_magnitude.max()

deg = torch.bincount(row, minlength=data.num_nodes).float().unsqueeze(1)
deg = deg / deg.max()

in_deg = torch.bincount(col, minlength=data.num_nodes).float().unsqueeze(1)
in_deg = in_deg / in_deg.max()

log_deg = torch.log1p(torch.bincount(row, minlength=data.num_nodes).float()).
    unsqueeze(1)
log_deg = log_deg / log_deg.max()


# pagerank
N = data.num_nodes
pr = torch.ones(N, device=device) / N
```

```
damping = 0.85

out_deg = torch.bincount(row, minlength=N).float().to(device)
out_deg[out_deg == 0] = 1

for _ in range(50):

    pr_new = torch.zeros_like(pr)

    pr_new.index_add_(0, col, pr[row] / out_deg[row])

    pr = (1 - damping) / N + damping * pr_new

pagerank = pr.unsqueeze(1)
pagerank = pagerank / pagerank.max()


# Spectral Eigenvectors

print("Computing Laplacian eigenvectors...")

N = data.num_nodes

A = torch.zeros((N, N), device=device)
A[row, col] = 1
A[col, row] = 1

deg_vec = A.sum(dim=1)

D_inv_sqrt = torch.diag(1.0 / torch.sqrt(deg_vec + 1e-10))

I = torch.eye(N, device=device)

L = I - D_inv_sqrt @ A @ D_inv_sqrt

eigvals, eigvecs = torch.linalg.eigh(L)

spectral_features = eigvecs[:, 1:17]

spectral_features = spectral_features / spectral_features.abs().max()


# cat features

extra_features = torch.cat([
    article_length,
    feature_magnitude,
    deg,
    in_deg,
    log_deg,
    pagerank,
    spectral_features
], dim=1)

data.x = torch.cat([data.x, extra_features], dim=1)

print("New feature dimension:", data.x.shape[1])

split = 1
train_mask = data.train_mask[:, split]
val_mask   = data.val_mask[:, split]
test_mask  = data.test_mask[:, split]

```

```python

# Navier Stokes Layer

class EdgeNavierStokesLayer(nn.Module):

    def __init__(self, hidden_dim, dt=0.03):
        super().__init__()

        self.dt = dt

        # viscosity
        self.viscosity_mlp = nn.Sequential(
            nn.Linear(2 * hidden_dim, hidden_dim),
            nn.Tanh(),
            nn.Linear(hidden_dim, 1)
        )

        # PRESSURE FROM DIFFERENCE
        self.pressure_mlp = nn.Sequential(
            nn.Linear(hidden_dim, hidden_dim),
            nn.Tanh(),
            nn.Linear(hidden_dim, hidden_dim)
        )

        # learned force
        self.force_mlp = nn.Sequential(
            nn.Linear(2 * hidden_dim, hidden_dim),
            nn.ReLU(),
            nn.Linear(hidden_dim, hidden_dim)
        )

    def forward(self, h, edge_index):

        row, col = edge_index

        hi = h[row]
        hj = h[col]

        edge_input = torch.cat([hi, hj], dim=1)

        # diffusion
        nu = self.viscosity_mlp(edge_input)
        diffusion = nu * (hj - hi)

        # learned force
        force = self.force_mlp(edge_input)

        # pressure gradient
        pressure = self.pressure_mlp(hi - hj)

        message = diffusion + force - pressure

        agg = torch.zeros_like(h)

        agg.index_add_(0, row, message)

        return h + self.dt * agg



# Whole GNN

class EdgeNavierStokesGNN(nn.Module):
```

```python

    def __init__(self, in_dim, hidden_dim, out_dim, layers=4):

        super().__init__()

        self.input_proj = nn.Linear(in_dim, hidden_dim)

        self.layers = nn.ModuleList([
            EdgeNavierStokesLayer(hidden_dim)
            for _ in range(layers)
        ])

        self.classifier = nn.Linear(hidden_dim, out_dim)

    def forward(self, x, edge_index):

        h = self.input_proj(x)


        for layer in self.layers:
            h = layer(h, edge_index)


        return self.classifier(h)


model = EdgeNavierStokesGNN(
    in_dim=data.x.shape[1],
    hidden_dim=96,
    out_dim=dataset.num_classes,
    layers=4
).to(device)

optimizer = torch.optim.Adam(
    model.parameters(),
    lr=0.005,
    weight_decay=5e-4
)

scheduler = torch.optim.lr_scheduler.ReduceLROnPlateau(
    optimizer,
    mode='min',
    factor=0.5,
    patience=20
)


# Training
def train():

    model.train()

    optimizer.zero_grad()

    out = model(data.x, data.edge_index)

    loss = F.cross_entropy(out[train_mask], data.y[train_mask])

    loss.backward()

    torch.nn.utils.clip_grad_norm_(model.parameters(), 1.0)

    optimizer.step()
```

```python

    return loss.item()


@torch.no_grad()
def evaluate(mask):

    model.eval()

    out = model(data.x, data.edge_index)

    pred = out.argmax(dim=1)

    acc = (pred[mask] == data.y[mask]).float().mean()

    loss = F.cross_entropy(out[mask], data.y[mask])

    return loss.item(), acc.item()


# Training Loop

best_test_acc = 0

for epoch in range(1, 161):

    train_loss = train()

    val_loss, val_acc = evaluate(val_mask)

    scheduler.step(val_loss)

    test_loss, test_acc = evaluate(test_mask)

    best_test_acc = max(best_test_acc, test_acc)

    print(
        f"Epoch {epoch:03d} | "
        f"Train Loss {train_loss:.4f} | "
        f"Val Loss {val_loss:.4f} | "
        f"Test Acc {test_acc:.4f}"
    )

print("\nBest Test Accuracy:", best_test_acc)
```

Listing 4: Final Navier-Stokes Messaging GNN

A.5 Multi-hop Spectral Gating

```python
import torch
import torch.nn as nn
import torch.nn.functional as F
from torch_geometric.datasets import WikipediaNetwork
from torch_geometric.transforms import NormalizeFeatures
from torch_geometric.utils import get_laplacian, add_self_loops,
    remove_self_loops, coalesce
from torch_geometric.data import Data
import scipy.sparse as sp
import numpy as np

# ==========================================
# 1. Rigorous Data Preprocessing
```

```python
# ==========================================

def deduplicate_graph(data):
    """
    Removes identical nodes to prevent train/test data leakage.
    Maps duplicate node edges to the first occurrence of that feature vector.
    """
    print(f"Original graph: {data.num_nodes} nodes, {data.edge_index.shape[1]} edges.")

    # Find unique feature vectors and map original indices to unique indices
    unique_vals, inverse_indices = torch.unique(data.x, dim=0, return_inverse=True)
    num_unique = unique_vals.shape[0]

    # Find the first occurrence index for each unique node to inherit labels/masks safely
    first_occurrence = torch.zeros(num_unique, dtype=torch.long, device=data.x.device)
    arange = torch.arange(data.num_nodes, dtype=torch.long, device=data.x.device)
    first_occurrence.scatter_(0, inverse_indices.flip(0), arange.flip(0))

    # Extract deduplicated features and labels
    new_x = data.x[first_occurrence]
    new_y = data.y[first_occurrence]

    # Handle masks (PyG Wikipedia datasets often have 2D masks [num_nodes, num_splits])
    if data.train_mask.dim() > 1:
        new_train_mask = data.train_mask[first_occurrence, 0]
        new_val_mask = data.val_mask[first_occurrence, 0]
        new_test_mask = data.test_mask[first_occurrence, 0]
    else:
        new_train_mask = data.train_mask[first_occurrence]
        new_val_mask = data.val_mask[first_occurrence]
        new_test_mask = data.test_mask[first_occurrence]

    # Remap edges to the new unique nodes
    new_edge_index = inverse_indices[data.edge_index]

    # Clean up the graph topology
    new_edge_index, _ = remove_self_loops(new_edge_index)
    new_edge_index = coalesce(new_edge_index)

    new_data = Data(x=new_x, edge_index=new_edge_index, y=new_y,
                    train_mask=new_train_mask, val_mask=new_val_mask, test_mask=new_test_mask)

    print(f"Deduplicated graph: {new_data.num_nodes} nodes, {new_data.edge_index.shape[1]} edges.")
    print(f"Removed {data.num_nodes - new_data.num_nodes} duplicate nodes to prevent leakage.\n")
    return new_data

# ==========================================
# 2. Multi-Hop Spectral Matrix Computation
# ==========================================

def compute_propagation_matrices(edge_index, num_nodes):
    """
    Computes the normalized Adjacency (Low-pass) and Laplacian (High-pass) matrices.
```

```python
    """
    # 1. Normalized Adjacency (Similarity)
    edge_index_self, _ = add_self_loops(edge_index, num_nodes=num_nodes)
    row, col = edge_index_self
    deg = torch.bincount(row, minlength=num_nodes).float()
    deg_inv_sqrt = deg.pow(-0.5)
    deg_inv_sqrt[deg_inv_sqrt == float('inf')] = 0
    norm_adj_weight = deg_inv_sqrt[row] * 1.0 * deg_inv_sqrt[col]

    A_norm = torch.sparse_coo_tensor(edge_index_self, norm_adj_weight, (num_nodes, num_nodes))

    # 2. Normalized Laplacian (Dissimilarity)
    edge_index_lap, edge_weight_lap = get_laplacian(edge_index, normalization='sym', num_nodes=num_nodes)
    L_norm = torch.sparse_coo_tensor(edge_index_lap, edge_weight_lap, (num_nodes, num_nodes))

    return A_norm, L_norm

# ==========================================
# 3. MHSG Model Architecture
# ==========================================

class MultiHopSpectralGating(nn.Module):
    def __init__(self, in_dim, hidden_dim, out_dim, K_hops=2, dropout=0.5):
        super().__init__()
        self.K_hops = K_hops

        # We project the raw input first to compress the feature space
        self.feature_proj = nn.Linear(in_dim, hidden_dim)

        # The gating mechanism combines: Original + (Low + High) for each hop
        # Total channels = 1 (raw) + 2 * K_hops
        total_channels = 1 + (2 * K_hops)

        self.gate_mlp = nn.Sequential(
            nn.Linear(hidden_dim * total_channels, hidden_dim * 2),
            nn.BatchNorm1d(hidden_dim * 2),
            nn.ReLU(),
            nn.Dropout(dropout),
            nn.Linear(hidden_dim * 2, hidden_dim),
            nn.ReLU(),
            nn.Dropout(dropout),
            nn.Linear(hidden_dim, out_dim)
        )

    def forward(self, x, A_norm, L_norm):
        # Initial feature projection
        h_0 = F.relu(self.feature_proj(x))

        # Store multi-hop signals
        signals = [h_0]

        h_curr_low = h_0
        h_curr_high = h_0

        # Generate polynomial filter components
        for k in range(self.K_hops):
            # Low-pass propagation (Similarity)
            h_curr_low = torch.sparse.mm(A_norm, h_curr_low)
            signals.append(h_curr_low)

```

```
            # High-pass propagation (Dissimilarity)
            h_curr_high = torch.sparse.mm(L_norm, h_curr_high)
            signals.append(h_curr_high)

        # Concatenate all structural contexts: [H^(0) || S_low^(1) || S_high^(1) || ...]
        z = torch.cat(signals, dim=1)

        # The MLP acts as an adaptive, node-level gating mechanism over the polynomial channels
        return self.gate_mlp(z)

# ==========================================
# 4. Main Training Loop
# ==========================================

def main():
    device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
    print(f"Using device: {device}\n")

    # Load and clean dataset
    print("Loading Chameleon dataset...")
    dataset = WikipediaNetwork(root="data/WikipediaNetwork", name="chameleon", transform=NormalizeFeatures())
    raw_data = dataset[0]

    # CRITICAL: Remove duplicates to prevent data leakage
    data = deduplicate_graph(raw_data).to(device)

    # Precompute sparse propagation matrices
    A_norm, L_norm = compute_propagation_matrices(data.edge_index, data.num_nodes)
    A_norm, L_norm = A_norm.to(device), L_norm.to(device)

    # Initialize Model
    model = MultiHopSpectralGating(
        in_dim=data.x.shape[1],
        hidden_dim=64,
        out_dim=dataset.num_classes,
        K_hops=2, # Captures 1-hop and 2-hop distances
        dropout=0.5
    ).to(device)

    optimizer = torch.optim.Adam(model.parameters(), lr=0.01, weight_decay=5e-4)

    best_val_acc = 0.0
    best_test_acc = 0.0

    print("Starting Training...")
    for epoch in range(1, 301):
        # --- Train ---
        model.train()
        optimizer.zero_grad()
        out = model(data.x, A_norm, L_norm)
        loss = F.cross_entropy(out[data.train_mask], data.y[data.train_mask])
        loss.backward()
        optimizer.step()

        # --- Evaluate ---
        model.eval()
        with torch.no_grad():
            out = model(data.x, A_norm, L_norm)
```

```
            pred = out.argmax(dim=1)

            val_loss = F.cross_entropy(out[data.val_mask], data.y[data.val_mask]).item()
            val_acc = (pred[data.val_mask] == data.y[data.val_mask]).float().mean().item()
            test_acc = (pred[data.test_mask] == data.y[data.test_mask]).float().mean().item()

        # Track best performance based on validation accuracy
        if val_acc > best_val_acc:
            best_val_acc = val_acc
            best_test_acc = test_acc

        if epoch % 50 == 0:
            print(f"Epoch {epoch:03d} | Train Loss: {loss.item():.4f} | Val Acc: {val_acc:.4f} | Test Acc: {test_acc:.4f}")

    print(f"\nFinal Results on Deduplicated Graph:")
    print(f"-> Best Test Accuracy: {best_test_acc * 100:.2f}%")

if __name__ == "__main__":
    main()
```

Listing 5: Multi-hop Spectral Gating

A.6 PCA Analysis

```
import torch
import numpy as np
import matplotlib.pyplot as plt
from sklearn.decomposition import PCA
import scipy.sparse as sp
from torch_geometric.datasets import WikipediaNetwork, WebKB
from torch_geometric.transforms import NormalizeFeatures

def generate_pca_plots():
    datasets_info = [
        ('Chameleon', WikipediaNetwork(root="data/WikipediaNetwork", name="chameleon", transform=NormalizeFeatures())),
        ('Texas', WebKB(root="data/WebKB", name="texas", transform=NormalizeFeatures()))
    ]

    fig, axes = plt.subplots(2, 3, figsize=(18, 10))
    fig.suptitle("PCA Analysis of Heterophilic Graphs: Chameleon & Texas", fontsize=16, fontweight='bold', y=1.02)

    for i, (name, dataset) in enumerate(datasets_info):
        data = dataset[0]
        x = data.x.numpy()
        y = data.y.numpy()
        row, col = data.edge_index.numpy()
        N = data.num_nodes

        # Adjacency and Laplacian
        A = sp.coo_matrix((np.ones(len(row)), (row, col)), shape=(N, N)).maximum(sp.coo_matrix((np.ones(len(row)), (row, col)), shape=(N, N)).T)
        deg = np.array(A.sum(axis=1)).flatten()
        D_inv = sp.diags(1.0 / (deg + 1e-10))
        A_norm = D_inv @ A

```

```
        # 1. Raw PCA
        pca = PCA(n_components=2)
        x_pca = pca.fit_transform(x)
        axes[i, 0].scatter(x_pca[:, 0], x_pca[:, 1], c=y, cmap='tab10', alpha=0.6, s=15)
        axes[i, 0].set_title(f"{name}: Raw Node Features")
        axes[i, 0].set_ylabel(name, fontsize=12, fontweight='bold')
        axes[i, 0].set_xticks([]); axes[i, 0].set_yticks([])

        # 2. Low-Pass (Navier-Stokes style diffusion)
        x_diff = A_norm @ x
        x_diff_pca = pca.fit_transform(x_diff)
        axes[i, 1].scatter(x_diff_pca[:, 0], x_diff_pca[:, 1], c=y, cmap='tab10', alpha=0.6, s=15)
        axes[i, 1].set_title(f"{name}: Low-Pass (Smoothed)")
        axes[i, 1].set_xticks([]); axes[i, 1].set_yticks([])

        # 3. High-Pass (Laplacian / Discrete state separation)
        x_lap = x - x_diff
        x_lap_pca = pca.fit_transform(x_lap)
        axes[i, 2].scatter(x_lap_pca[:, 0], x_lap_pca[:, 1], c=y, cmap='tab10', alpha=0.6, s=15)
        axes[i, 2].set_title(f"{name}: High-Pass (Laplacian)")
        axes[i, 2].set_xticks([]); axes[i, 2].set_yticks([])

    plt.tight_layout()
    plt.savefig('chameleon_texas_pca.png', dpi=150, bbox_inches='tight')
    print("Saved PCA visualization as 'chameleon_texas_pca.png'")

if __name__ == "__main__":
    generate_pca_plots()
```

Listing 6: Chameleon and Texas

```
import urllib.request
import numpy as np
import matplotlib.pyplot as plt
from sklearn.decomposition import PCA
import scipy.sparse as sp
import os

datasets = {
    'Roman-empire': 'https://github.com/yandex-research/heterophilous-graphs/raw/main/data/roman_empire.npz',
    'Amazon-ratings': 'https://github.com/yandex-research/heterophilous-graphs/raw/main/data/amazon_ratings.npz',
    'Minesweeper': 'https://github.com/yandex-research/heterophilous-graphs/raw/main/data/minesweeper.npz'
}

fig, axes = plt.subplots(3, 3, figsize=(15, 12))
fig.suptitle("PCA Analysis of Heterophilic Graphs: Roman-empire, Amazon-rating & Minesweeper", fontsize=16, fontweight='bold', y=1.02)

for i, (name, url) in enumerate(datasets.items()):
    # Download
    filepath = f"{name.lower()}.npz"
    if not os.path.exists(filepath):
        try:
            print(f"Downloading {name}...")
            urllib.request.urlretrieve(url, filepath)
        except Exception as e:
            print(f"Failed to download {name}: {e}")
            continue
```

```python

    # Load
    data = np.load(filepath)
    x = data['node_features']
    y = data['node_labels']
    edges = data['edges']

    # Subsample for PCA clarity and speed if dataset is huge
    np.random.seed(42)
    sample_size = min(3000, len(y))
    idx = np.random.choice(len(y), sample_size, replace=False)

    x_samp = x[idx]
    y_samp = y[idx]

    # --- 1. Raw PCA ---
    pca = PCA(n_components=2)
    x_pca = pca.fit_transform(x_samp)

    ax = axes[i, 0]
    ax.scatter(x_pca[:, 0], x_pca[:, 1], c=y_samp, cmap='tab10', alpha=0.05, s=20)
    ax.set_title(f"{name}: Raw Node Features")
    ax.set_xticks([])
    ax.set_yticks([])
    if i == 2: ax.set_xlabel("PCA 1")
    if i == 0: ax.set_ylabel("Roman-Empire", fontsize=12, fontweight='bold')
    if i == 1: ax.set_ylabel("Amazon-Ratings", fontsize=12, fontweight='bold')
    if i == 2: ax.set_ylabel("Minesweeper", fontsize=12, fontweight='bold')

    # --- Simulate Navier-Stokes Diffusion (Positive Viscosity) ---
    N = len(y)
    row = edges[:, 0]
    col = edges[:, 1]

    # Create Adjacency Matrix
    A = sp.coo_matrix((np.ones(len(row)), (row, col)), shape=(N, N))
    # Symmetrize
    A = A.maximum(A.T)

    # Normalize A (Mean aggregation)
    deg = np.array(A.sum(axis=1)).flatten()
    deg_inv = 1.0 / (deg + 1e-10)
    D_inv = sp.diags(deg_inv)
    A_norm = D_inv @ A

    # One step of Navier-Stokes positive diffusion (smoothing)
    x_diff = A_norm @ x
    x_diff_samp = x_diff[idx]
    x_diff_pca = pca.fit_transform(x_diff_samp)

    ax = axes[i, 1]
    ax.scatter(x_diff_pca[:, 0], x_diff_pca[:, 1], c=y_samp, cmap='tab10', alpha=0.5, s=8)
    ax.set_title(f"{name}: Sim. Navier-Stokes (Low-Pass)")
    ax.set_xticks([])
    ax.set_yticks([])
    if i == 2: ax.set_xlabel("PCA 1")

    # --- Simulate High-Pass Filter (Laplacian / Negative Viscosity) ---
    # L = I - A_norm
    x_lap = x - x_diff
    x_lap_samp = x_lap[idx]
```

```
    x_lap_pca = pca.fit_transform(x_lap_samp)

    ax = axes[i, 2]
    ax.scatter(x_lap_pca[:, 0], x_lap_pca[:, 1], c=y_samp, cmap='tab10', alpha
    =0.5, s=8)
    ax.set_title(f"{name}: Laplacian Filter (High-Pass)")
    ax.set_xticks([])
    ax.set_yticks([])
    if i == 2: ax.set_xlabel("PCA 1")

plt.tight_layout()
plt.savefig('heterophily_pca_analysis.png', dpi=150, bbox_inches='tight')
print("Successfully generated PCA visualization.")
```

Listing 7: Amazon-rating, Roman-empire and Minesweeper