## EVVO 20000TLG23P / 25000TLG23P / 30000TLG23P / 33000TLG23P

## Three Phase Inverter Dual MPPT

Data Sheets	20000W	25000W	30000M	33000W			
nput(DC)							
Max. Input power	26000W	32500W	39000W	42900W			
Max DC power for single MPPT	13000W	16000W	18000W	20000W			
lumber of independent MPPT	2						
lumber of DC inputs	2 for each MPPT 3 for each MPPT						
Max. input voltage	1100V						
tart-up input voltage	250V(+/-1V)						
ated input voltage	620V	620V	620V	620V			
MPPT voltage range	230V-960V						
ull load DC voltage range	480V-850V	460V-850V	520V-850V	580V-850V			
Max. input MPPT current	24A/24A	28A/28A	30A/30A	30A/30A			
Output(AC)							
ated power(@230V,50Hz)	20000W	25000W	30000W	33000W			
Max. AC power	22000VA	27500VA	33000VA	36300VA			
Max. output current	32A	40A	48A	53A			
Iominal Grid Voltage	3/N/PE, 230/400Vac						
Grid Voltage Range	310Vac - 480Vac						
Nominal Frequency	50/60Hz						
Grid frequency range	4	5~55Hz/55~65Hz(Acco					
Active power adjustable range	0~100%						
THDI		<	3%				
Power factor	1(Adjustable +/-0.8)						
Performance							
Max efficiency	98.2%	98.4%	98.4%	98.6%			
European weighted efficiency	98.0%	98.2%	98.2%	98.2%			
elf-consumption at night	<1W						
eed-in start power	45W						
APPT efficiency	>99.9%						
rotection							
C reverse polarity protection		Yes					
OC switch	Yes						
rotection class /overvoltage category	1/111						
afety protection	Anti islanding, RCMU, Ground fault monitoring						
Certification	IEC 62116,IEC 61727,IEC 61683,IEC 60068(1,2,14,30),IEC62109-1/2 CE,CGC,ZVRT,AS4777,AS3100,VDE4105,C10-C11,G59(more available on request)						
ARPC	Anti Reverse Power Controller(optional)						

## Communication

Standard Communication Mode RS485, Wifi,GPRS(optional), SD card, Multi-function is				
Operation Data Storage	25 years			
General data				
Ambient temperature range	35% .60%			

Ambient temperature range	-25°C+60°C				
Topology	Transformerless				
Degree of protection	IP65				
Allowable relative humidity range	0100% no condensing				
Max.operating altitude	<2000M				
Noise	<30dB	<45dB	<45dB	<45dB	
Weight	37kg				
Cooling	Natural	Fan	Fan	Fan	
Dimension	666*512*254mm				
Display	LCD display				
Warranty	10 years				