EVVO 4000TLG2 / 5000TLG2 / 6000TLG2

Single Phase Inverter Dual MPPT

Data Sheet	4000W	5000W	6000W	
Input(DC)				
	440014	EFOOW	660014	
Max. Input power	4400W	5500W	6600W	
Max DC power for single MPPT	2600(200V-500V)	3000(200V-500V)	3150(250V-520V)	
Number of independent MPPT		2		
Number of DC inputs		1 for each MPPT		
Max. input voltage		600V		
Start-up input voltage		120V		
Rated input voltage		360V		
MPPT voltage range		100V-580V		
Full load DC voltage range	165V-520V	175V-520V	250V-520V	
Max. input current per MPPT	13A/13A	15A/15A		
Input short circuit current for each MPPT	16A	18A		
Output(AC)				
Rated power	4000W	5000W	6000W	
Max. AC power	4000VA	5000VA	6000VA	
Max. output current	17.5A	22A	26A	
Nominal Grid Voltage		230V		
Grid Voltage Range	180~270	(According to local	standard)	
Nominal Frequency	50/60Hz			
Grid frequency range	47~53 / 57~63Hz (According to local standard)			
Active power adjustable range		0~100%		
THDi		<3%		
Power factor	1 (adjustable +/-0.8)			
Power Limit export	Zero export	or adjustable pov	ver limit export	
Performance				
Max.efficiency		97.6%		
Weighted eff. (EU/CEC)	97.1%/97.3%			
Self-consumption at night	<1W			
Feed-in start power		20W		
MPPT efficiency		>99.9%		
Protection				
DC reverse polarity protection		Yes		
DC switch		Yes		
Protection class /overvoltage category		1/111		
Input / output MOV (III)		Yes		
Safety protection	Anti islanding, RCMU, Ground fault monitoring			
Certification	IEC 62116,IEC 61727,IEC 61683,IEC 60068(1,2,14,30),IEC62109-1/2 CE, CGC, AS4777,AS3100,VDE4105,C10-C11,G83/G59(more available on request)			
SPD	N	IOV : Type III standar	d	
Communication				
Standard Communication Mode	WiFi , RS485、GPRS、SD card(optional)			
Operation Data Storage	25 years			
General data				
Ambient temperature range		-25°C+60°C		
Topology	Transformerless			
Degree of protection	IP65			
Allowable relative humidity range	0100% no condensing			
Max.operating altitude	2000m			
Noise		<25dB		
Weight	18kg		19kg	
Cooling		Natural		
Dimension	344 * 478 * 170mm			
Display		LCD display		
Warranty		10 years		