



K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

Roll No.: 1911027

Experiment No. 6

Grade: AA / AB / BB / BC / CC / CD / DD

Signature of the Staff In-charge with date

Problem Statement:

Demonstrate the use of GUI Widgets to create Scientific Calculator
(Min. 10 functionalities).

AIM: Use concepts of tkinter GUI widgets

Expected OUTCOME of Experiment:

CO1: Describe the Numbers, Math functions, Strings, List, Tuples and Dictionaries in Python.

CO2: Interpret different Decision Making statements, Functions, Object oriented programming in Python.

CO4: Explain how to design GUI Applications in Python and evaluate different database operations.

Books/ Journals/ Websites referred:


- 1) https://www.tutorialspoint.com/python/python_gui_programming
 - 2) <https://docs.python.org/3/library/tkinter.html>
 - 3) <https://www.geeksforgeeks.org/python-gui-tkinter/>
 - 4) <https://www.datacamp.com/community/tutorials/gui-tkinter-python>
-



Pre Lab/ Prior Concepts:

Tkinter:

Tkinter is the standard GUI library for Python. Python when combined with Tkinter provides a fast and easy way to create GUI applications. Tkinter provides a powerful object-oriented interface to the Tk GUI toolkit. Both Tk and tkinter are available on most Unix platforms, as well as on Windows systems. (Tk itself is not part of Python; it is maintained at ActiveState). Most of the time, tkinter is all you really need, but a number of additional modules are available as well. The Tk interface is located in a binary module named `_tkinter`. This module contains the low-level interface to Tk, and should never be used directly by application programmers. It is usually a shared library (or DLL), but might in some cases be statically linked with the Python interpreter. In addition to the Tk interface module, tkinter includes a number of Python modules, `tkinter.constants` being one of the most important. Importing tkinter will automatically import `tkinter.constants`



Flow Diagram for Rendering a Basic GUI

Creating a GUI application using Tkinter is an easy task. All you need to do is perform the following steps –

- Import the Tkinter module.
- Create the GUI application main window.
- Add one or more of the above-mentioned widgets to the GUI application.
- Enter the main event loop to take action against each event triggered by the user.



K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

Example:


```
import tkinter
```

```
top = tkinter.Tk()
```

```
# Code to add widgets will go here...
```

```
top.mainloop()
```

This would create a following window –



Tkinter Widgets:

Tkinter provides various controls, such as buttons, labels and text boxes used in a GUI application. These controls are commonly called widgets. There are currently 15 types of widgets in Tkinter. We present these widgets as well as a brief description in the following table –

Sr No.	Operator & Description
1	Button: The Button widget is used to display buttons in your application.



K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

2	<p>Canvas:</p> <p>The Canvas widget is used to draw shapes, such as lines, ovals, polygons and rectangles, in your application.</p>
3	<p>Checkbutton:</p> <p>The Checkbutton widget is used to display a number of options as checkboxes. The user can select multiple options at a time.</p>
4	<p>Entry:</p> <p>The Entry widget is used to display a single-line text field for accepting values from a user.</p>
5	<p>Frame:</p> <p>The Frame widget is used as a container widget to organize other widgets.</p>
6	<p>Label:</p> <p>The Label widget is used to provide a single-line caption for other widgets. It can also contain images.</p>
7	<p>Listbox:</p> <p>The Listbox widget is used to provide a list of options to a user.</p>
8	<p>Menubutton:</p> <p>The Menubutton widget is used to display menus in your application.</p>
9	<p>Menu:</p> <p>The Menu widget is used to provide various commands to a user. These commands are contained inside Menubutton.</p>
10	<p>Message:</p> <p>The Message widget is used to display multiline text fields for</p>



K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

	accepting values from a user.
11	Radiobutton: The Radiobutton widget is used to display a number of options as radio buttons. The user can select only one option at a time.
12	Scale: The Scale widget is used to provide a slider widget.
13	Scrollbar: The Scrollbar widget is used to add scrolling capability to various widgets, such as list boxes.
14	Text: The Text widget is used to display text in multiple lines.
15	Toplevel: The Toplevel widget is used to provide a separate window container.
16	Spinbox: The Spinbox widget is a variant of the standard Tkinter Entry widget, which can be used to select from a fixed number of values.
17	PanedWindow: A PanedWindow is a container widget that may contain any number of panes, arranged horizontally or vertically.
18	LabelFrame: A labelframe is a simple container widget. Its primary purpose is to act as a spacer or container for complex window layouts.



K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

19	tkMessageBox: This module is used to display message boxes in your applications.
----	--

Standard attributes:

Let us take a look at how some of their common attributes such as sizes, colours and fonts are specified.

Dimensions: 1) Colours 2) Fonts 3) Anchors 4) Relief styles 5) Bitmaps 6) Cursors

Geometry Management:

All Tkinter widgets have access to specific geometry management methods, which have the purpose of organizing widgets throughout the parent widget area. Tkinter exposes the following geometry manager classes: pack, grid, and place.

The pack() Method – This geometry manager organizes widgets in blocks before placing them in the parent widget.

The grid() Method – This geometry manager organizes widgets in a table-like structure in the parent widget.

The place() Method – This geometry manager organizes widgets by placing them in a specific position in the parent widget.

Examples:

1) Check Button: To select any number of options by displaying a number of options to a user as toggle buttons. The general syntax is:

w = CheckButton(master, option=value)



K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

There are number of options which are used to change the format of this widget. Number of options can be passed as parameters separated by commas. Some of them are listed below.

Title: To set the title of the widget.


activebackground: to set the background colour when widget is under the cursor.

activeforeground: to set the foreground colour when widget is under the cursor.

Code:

```
from tkinter import *  
  
master = Tk()  
  
var1 = IntVar()  
  
Checkbutton(master, text='male', variable=var1).grid(row=0, sticky=W)  
  
var2 = IntVar()  
  
Checkbutton(master, text='female', variable=var2).grid(row=1, sticky=W)  
  
mainloop()
```

Output:





K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

2) Entry: It is used to input the single line text entry from the user.. For multi-line text input, Text widget is used. The general syntax is:

`w=Entry(master, option=value)`

master is the parameter used to represent the parent window.

There are number of options which are used to change the format of the widget. Number of options can be passed as parameters separated by commas. Some of them are listed below.

bd: to set the border width in pixels.

bg: to set the normal background colour.

cursor: to set the cursor used.

command: to call a function.

Program:

```
from tkinter import *
import math
import re
def preced(sym):
    if(sym=='^'):
        return 3
    elif(sym=='*' or sym=='/'):
        return 2
    elif(sym=='+' or sym=='-'):
        return 1
    else:
```




K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

```
return 0
```

```
def cal(str1):
    flag=0
    flag1=0
    str1=str1+"")
    stack=list()
    stack=[None]*100
    stack[0]="("
    post=list()
    post=[None]*100
    j=0
    k=0
    i=0
    while(i<len(str1)):
        match=re.search(r'[0-9]',str1[i])
        if(match):
            tem=""
            for t in range(i,len(str1)):
                match1=re.search(r'[0-9]|[\.]',str1[t])
                if(match1):
                    tem=tem+str1[t]
                    i=i+1
            else:
                break
            post[j]=tem
            j=j+1
        elif(str1[i]=='('):
            k=k+1
```



K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

```
stack[k]=str1[i]
i=i+1
elif(str1[i]=='^' or str1[i]=='+' or str1[i]=='-' or str1[i]=='/' or str1[i]=='*'):
    temp=stack[k]
    k=k-1
    while(preced(temp)>=preced(str1[i]) and (temp=='^' or temp=='+' or
temp=='-' or temp=='*' or temp=='/')):
        post[j]=temp
        j=j+1
        temp=stack[k]
        k=k-1
    k=k+1
    stack[k]=temp
    k=k+1
    stack[k]=str1[i]
    i=i+1
elif(str1[i]==')'):
    temp=stack[k]
    k=k-1
    while(temp!='('):
        post[j]=temp
        j=j+1
        temp=stack[k]
        k=k-1
    i=i+1
elif(re.search(r'[a-z]',str1[i])):
    exp=""
    temp=""
    for j in range(i,len(str1)):
```



K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

```
if(re.search(r'[a-z]',str1[j])):
    temp=temp+str1[j]
    i=i+1
else:
    break
for m in range(i,len(str1)):
    if(str1[m]=='('):
        i=i+1
        continue
    elif(str1[m]!='")"):
        exp=exp+str1[m]
        i=i+1
    elif(str1[m]==")"):
        i=i+1
        break
if(temp=="sin"):
    cal1=float(exp)*math.pi/180
    calans=math.sin(cal1)
elif(temp=="cos"):
    cal1=float(exp)*math.pi/180
    calans=math.cos(cal1)
elif(temp=="tan"):
    if(float(exp)!=90.0):
        cal1=float(exp)*math.pi/180
        calans=math.tan(cal1)
    else:
        e.delete(0,END)
        e.insert(0,"Invalid Operation")
    flag1=1
```



K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

```
        break
    elif(temp=="log"):
        calans=math.log(float(exp))
    elif(temp=="rot"):
        calans=math.sqrt(float(exp))
    elif(temp=="sinh"):
        calans=math.asin(float(exp))*180/math.pi
    elif(temp=="cosh"):
        calans=math.acos(float(exp))*180/math.pi
    elif(temp=="tanh"):
        calans=math.atan(float(exp))*180/math.pi
    elif(temp=="e"):
        calans=math.pow(2.718,float(exp))
    post[j]=calans
    j=j+1
if(flag1!=1):
    calcupo(post)

def calcupo(post):
    stack=list()
    stack=[None]*100
    k=-1
    flag=0
    for i in range(0,len(post)):
        if(post[i]!=None):
            match=re.search(r'[0-9][0-9]*[.][0-9]*',str(post[i]))
            if(match):
                k=k+1
                stack[k]=float(post[i])
```



K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

```
else:
    num1=float(stack[k])
    k=k-1
    num2=float(stack[k])
    k=k-1
    if(post[i]=='/'):
        if(num1==0):
            e.delete(0,END)
            e.insert(0,"Division by zero occurred")
            flag=1
            break
        ans=num2/num1
    elif(post[i]=='*'):
        ans=num2*num1
    elif(post[i]=='+'):
        ans=num2+num1
    elif(post[i]=='-'):
        ans=num2-num1
    else:
        ans=num2**num1
    k=k+1
    stack[k]=ans
if(flag==0):
    e.delete(0,END)
    e.insert(0,str(stack[k]))
```

```
def cleartex():
    e.delete('0', END)
```



K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

```
def setTextInput(text):
    cur=e.get()
    e.delete(0,END)
    e.insert(0,str(cur)+str(text))

def gettext():
    str1=e.get()
    if(not re.search(r'[0-9]',str1)):
        e.delete(0,END)
        e.insert(0,"Invalid Operation")
    elif(re.search(r'[\!]',str1)):
        if(re.search(r'[.]',str1)):
            e.delete(0,END)
            e.insert(0,"Factorial Not Possible")
        else:
            sum=1
            act=int(str1[:-1])
            for i in range(1,act+1):
                sum=sum*i
            e.delete(0,END)
            e.insert(0,str(sum))
    else:
        cal(str1)

root=Tk()
root.title('Scientific Caclulator')
root.geometry('680x350')
```



K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

```
e=Entry(root,borderwidth=5,width=85)
e.grid(row=0,column=0,columnspan=9,padx=20,pady=20)
b0=Button(root,text='0',padx=30,pady=20,borderwidth=2,command=lambda:set
TextInput("0"))
b1=Button(root,text='1',padx=30,pady=20,borderwidth=2,command=lambda:set
TextInput("1"))
b2=Button(root,text='2',padx=30,pady=20,borderwidth=2,command=lambda:set
TextInput("2"))
b3=Button(root,text='3',padx=30,pady=20,borderwidth=2,command=lambda:set
TextInput("3"))
b4=Button(root,text='4',padx=30,pady=20,borderwidth=2,command=lambda:set
TextInput("4"))
b5=Button(root,text='5',padx=30,pady=20,borderwidth=2,command=lambda:set
TextInput("5"))
b6=Button(root,text='6',padx=30,pady=20,borderwidth=2,command=lambda:set
TextInput("6"))
b7=Button(root,text='7',padx=30,pady=20,borderwidth=2,command=lambda:set
TextInput("7"))
b8=Button(root,text='8',padx=30,pady=20,borderwidth=2,command=lambda:set
TextInput("8"))
b9=Button(root,text='9',padx=30,pady=20,borderwidth=2,command=lambda:set
TextInput("9"))

equal=Button(root,text='=',padx=30,pady=20,borderwidth=2,command=gettext)
clear=Button(root,text='Clear',padx=60,pady=20,borderwidth=2,command=clear
tex)
decimal=Button(root,text='.',padx=30,pady=20,borderwidth=2,command=lambd
a:setTextInput("."))
```



K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

```
plus=Button(root,text='+',padx=30,pady=20,borderwidth=2,command=lambda:s
etTextInput("+"))
subtract=Button(root,text='-
',padx=30,pady=20,borderwidth=2,command=lambda:setTextInput("-"))
divide=Button(root,text='/',padx=30,pady=20,borderwidth=2,command=lambda:
setTextInput("/"))
multiply=Button(root,text='X',padx=30,pady=20,borderwidth=2,command=lambd
a:setTextInput("*"))
sin=Button(root,text='sin',padx=30,pady=20,borderwidth=2,command=lambda:s
etTextInput("sin()"))
cos=Button(root,text='cos',padx=30,pady=20,borderwidth=2,command=lambda:
setTextInput("cos()"))
tan=Button(root,text='tan',padx=30,pady=20,borderwidth=2,command=lambda:s
etTextInput("tan()"))
log=Button(root,text='ln',padx=30,pady=20,borderwidth=2,command=lambda:se
tTextInput("log()"))
sinh=Button(root,text='sinh',padx=30,pady=20,borderwidth=2,command=lambd
a:setTextInput("sinh()"))
cosh=Button(root,text='cosh',padx=30,pady=20,borderwidth=2,command=lambd
a:setTextInput("cosh()"))
tanh=Button(root,text='tanh',padx=30,pady=20,borderwidth=2,command=lambd
a:setTextInput("tanh()"))
eraise=Button(root,text='e^',padx=30,pady=20,borderwidth=2,command=lambd
a:setTextInput("e()"))
x_y=Button(root,text=' ^
',padx=30,pady=20,borderwidth=2,command=lambda:setTextInput("^"))
sqrt=Button(root,text='Sqrt',padx=65,pady=20,borderwidth=2,command=lambda
:setTextInput("rot()"))
```




K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

```
fact=Button(root,text='fact',padx=30,pady=20,borderwidth=2,command=lambda  
:setTextInput("!"))
```

```
brack_ope=Button(root,text='(',padx=30,pady=20,borderwidth=2,command=lam  
bda:setTextInput("("))
```

```
brack_clo=Button(root,text=')',padx=30,pady=20,borderwidth=2,command=lam  
bda:setTextInput(")"))
```

```
b1.grid(row=3,column=0,sticky='nesw')
```

```
b2.grid(row=3,column=1,sticky='nesw')
```

```
b3.grid(row=3,column=2,sticky='nesw')
```

```
b4.grid(row=2,column=0,sticky='nesw')
```

```
b5.grid(row=2,column=1,sticky='nesw')
```

```
b6.grid(row=2,column=2,sticky='nesw')
```

```
b7.grid(row=1,column=0,sticky='nesw')
```

```
b8.grid(row=1,column=1,sticky='nesw')
```

```
b9.grid(row=1,column=2,sticky='nesw')
```

```
equal.grid(row=4,column=2,sticky='nesw')
```

```
b0.grid(row=4,column=1,sticky='nesw')
```

```
plus.grid(row=1,column=4,sticky='nesw')
```

```
subtract.grid(row=2,column=4,sticky='nesw')
```

```
divide.grid(row=3,column=4,sticky='nesw')
```

```
multiply.grid(row=4,column=4,sticky='nesw')
```

```
sin.grid(row=1,column=5,sticky='nesw')
```

```
cos.grid(row=2,column=5,sticky='nesw')
```

```
tan.grid(row=3,column=5,sticky='nesw')
```

```
log.grid(row=4,column=5,sticky='nesw')
```



K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

```
sinh.grid(row=1,column=6,sticky='nesw')  
cosh.grid(row=2,column=6,sticky='nesw')  
tanh.grid(row=3,column=6,sticky='nesw')  
eraise.grid(row=4,column=6,sticky='nesw')
```

```
fact.grid(row=1,column=7,sticky='nesw')  
x_y.grid(row=2,column=7,sticky='nesw')  
sqrt.grid(row=3,column=7,columnspan=10)  
decimal.grid(row=4,column=0,sticky='nesw')  
clear.grid(row=4,column=7,columnspan=10)  
brack_ope.grid(row=1,column=8,sticky='nesw')  
brack_clo.grid(row=2,column=8,sticky='nesw')  
root.mainloop()
```




K. J. Somaiya College of Engineering, Mumbai-77


Department of Computer Engineering

Output:

Basic Math operations:



Result:






K. J. Somaiya College of Engineering, Mumbai-77


Department of Computer Engineering

Trigonometric Functions:

1) Sine function:



Result:







K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

2) Cosine function:



Result:







K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

3) Cosine inverse function:



Result:







K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

4) Tangent inverse function:



Result:







K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

Logarithmic function:



Result:







K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

Factorial function:



Result:







K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

Invalid factorial operation:



Result:






K. J. Somaiya College of Engineering, Mumbai-77


Department of Computer Engineering

Exponential functions:

1) x^y :



Result:







K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

2) e^x :



Result:







K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

Square root function:



Result:







K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

Complex operation 1:



Result:







K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

Complex operation 2:



Result:







K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

Invalid operation:



Result:





K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

Conclusion: By performing this experiment completely understood how to make a GUI application using tkinter. Also gained knowledge about how calculators internally work. Used many functionalities of tkinter and made a scientific calculator.

Date: 15 / 4 / 2021

Signature of faculty in-charge

Post Lab Descriptive Questions

1. Config() in Python Tkinter are used for

- (A) destroy the widget
- (B) place the widget
- (C) change property of the widget
- (D) configure the widget

ANS) (C) change property of the widget

2. Correct way to draw a line in canvas tkinter ?

- (A) line()
- (B) canvas.create_line()
- (C) create_line(canvas)
- (D) None of the above

ANS) (B) canvas.create_line()

3. Essential thing to create a window screen using tkinter python?

- (A) call tk() function
- (B) create a button
- (C) To define a geometry
- (D) All of the above



K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

ANS) (A) call tk() function

4. fg in tkinter widget is stands for ?

- (A) foreground
- (B) background
- (C) forgap
- (D) None of the above

ANS) (A) foreground

5. For user Entry data, which widget we use in tkinter ?

- (A) Entry
- (B) Text
- (C) Both of the above
- (D) None of the above

ANS) (B) Text

6. How pack() function works on tkinter widget ?

- (A) According to x,y coordinate
- (B) According to row and column wise
- (C) According to left,right,up,down
- (D) None of the above

ANS) (C) According to left,right,up,down

7. How the grid() function put the widget on the screen ?

- (A) According to x,y coordinate
- (B) According to row and column wise
- (C) According to left,right,up,down
- (D) None of the above



K. J. Somaiya College of Engineering, Mumbai-77

Department of Computer Engineering

ANS) (B) According to row and column wise

8. Minimum number of argument we pass in a function to create a rectangle using canvas tkinter ?

(A) 2

(B) 4

(C) 6

(D) 5

ANS) (A) 2

9. Which of the following is clickable in GUI programming ?

(A) Button

(B) Checkbutton

(C) Lable

(D) 1 and 2

ANS) (D) 1 and 2

10. How we import a tkinter in python program ?

(A) import tkinter

(B) import tkinter as t

(C) from tkinter import *

(D) All of the above

ANS) (D) All of the above