

A Beamer Template for Huazhong University of Science and Technology: the hustbeamer class *

Xu Cheng
xucheng@me.com

2013/07/01

Contents

I	Introduction	3
II	中文使用说明	4
1	使用必要条件	4
2	安装	4
2.1	安装到本地	4
2.2	免安装使用	5
3	基本用法	5
3.1	文档类型选项	5
3.2	基本字段设置	5
3.3	其它基本命令	6
4	简单示例	6
5	预设宏包介绍	7
6	高级设置	7
6.1	切换字体	7
III	English Version Instruction	8

*This document corresponds to hustbeamer.cls v1.0, dated 2013/07/01.

1 Requirement	8
2 Installation	8
2.1 Install into local	8
2.2 Use without installation	8
3 Usage	9
3.1 Option	10
3.2 Variables setting	10
3.3 Other commands	10
4 Simple example	11
5 Introduction to some packages used in the template	11
 IV Implementation	 13
1 Process Options	13
2 Check Engine	13
3 Font Setting	14
4 Basic Format	17
5 Load Packages	17
6 Variables Setting	18
7 Localization	19
8 Style Setting	21
8.1 Beamer Style	21
8.2 Equation Style	22
8.3 Theorem Style	23
8.4 Floating Objects Style	24
8.5 Table Style	24
8.6 Caption Style	24
8.7 Code Highlight Style	25
8.8 Bibliography Style	25
9 Specical Page	26
10 Other Command	27
 V Index	 28

I Introduction

This is a beamer template for [Huazhong University of Science & Technology](#). This template is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

The whole project is published under LPPL v1.3 License at [GitHub](#).

中文使用说明见 [Part II](#)。

English version instruction is in [Part III](#).

II 中文使用说明

1 使用必要条件

1. 安装最新版本的 **TeXLive** (推荐) 或 **MiKTeX**。因为未及时更新的宏包可能存在未修复的 **bug**，请确保所有宏包都更新至最新。
2. 安装如下中文字体¹:
 - a) AdobeSongStd-Light
 - b) AdobeKaitiStd-Regular
 - c) AdobeHeitiStd-Regular
 - d) AdobeFangsongStd-Regular



如果使用 LuaTeX，安装字体之后需运行命令 `mkluatexfontdb` 生成字体索引。

2 安装

2.1 安装到本地

使用如下命令即可安装本模板到本地：

```
make install
```

如需卸载，则使用如下命令：

```
make uninstall
```

对于没有安装 **Make** 的 **Windows** 系统用户，可以使用如下命令安装：

```
makewin32.bat install
```

如需卸载，则使用如下命令：

```
makewin32.bat uninstall
```

虽然 `makewin32.bat` 表现与 **Makefile** 极其相似，但是还是强烈建议你安装 **Make**，对于 **Windows** 用户可以在[这里](#)下载。

¹本模板所用到的英文字体 **Tex Gyre Termes**，**Droid Sans** 和 **CMU Typewriter Text** 均默认安装于 **TeXLive** 和 **MiKTeX** 中。

2.2 免安装使用

如果你希望临时使用本模板，而非安装到本地供长期使用。使用如下命令解压模板文件：

```
make unpack
```

对于没有安装 Make 的 Windows 系统用户，则使用如下命令解压：

```
makewin32.bat unpack
```

再将 `hustbeamer` 目录下的如下文件拷贝到你 $\text{T}_{\text{E}}\text{X}$ 工程根目录下即可：

- `hustbeamer.cls`
- `hust-header.png`

3 基本用法



本文档只能使用 $\text{X}_{\text{L}}\text{A}_{\text{T}}\text{E}_{\text{X}}$ 或 $\text{Lua}_{\text{L}}\text{A}_{\text{T}}\text{E}_{\text{X}}$ （推荐）编译。

在源文件开头处选择加载本文档类型，即可使用本模板，如下所示：

```
\documentclass[language=chinese]{hustbeamer}
```

3.1 文档类型选项

加载本文档类型时，有如下选项提供选择。

`language` `language = <chinese | english>`

指定模板语言。如果不指定，默认设置为 `chinese`。

3.2 基本字段设置

模板中定义一些命令用于设置文档中的字段。

`\title` `\title{<the title>}`
 `\title[<short title>]{<long title>}`

设置标题。

`\author` `\author{<the author>}`
 `\author[<short author>]{<long author>}`

设置作者名。

```
\date{} % remove date field.
```

```
\date{<content>} % put whatever you want.
```

```
\date{<Year>}{<Month>}
```

```
\date{<Year>}{<Month>}{<Day>}
```

设置日期。

3.3 其它基本命令

下面来介绍其它基本命令

```
\maketitle
```

```
\makecover
```

```
\PrintTOC
```

`\maketitle` 和 `\makecover` 作用相同，用于生成封面。

`\PrintTOC` 用于生成总目录。

```
\EnableTOCAtBeginSection
```

```
\DisableTOCAtBeginSection
```

本模板会自动在每个小节开头处加入当前索引，使用这两个命令可以开启或关闭该功能。

```
\email{<Email Address>}
```

用于生成邮箱地址。如 `\email{name@example.com}` 会生成如下效果的地址：
`name@example.com`。

4 简单示例

如下为一个使用本模板的简单示例。更完整的例子请见 `hustbeamer-example.tex` 文件，其效果见 `hustbeamer-example.pdf`。

```
1 \documentclass[language=chinese]{hustbeamer}
2
3 \title[短标题]{长标题}
4 \author{作者名}
5 \institute{作者信息}
6 \date{2013}{7}{1}
7
8 \begin{document}
9
10 \maketitle
11 \PrintTOC
12
13 %% 正文
```

5 预设宏包介绍

本模板中预设了一些宏包，下面对其进行简单介绍。

- **algorithm2e** 算法环境。
- **fancynum** 用于将大数每三位断开。
- **listings** 代码环境。如需更好的代码高亮可以使用 **minted** 宏包。
- **multirow** 用于表格中合并行。
- **overpic** 用于在图片上层叠其他内容。
- **tabularx** 扩展到表格环境。
- **xy-pic** 用于绘制简单图形。如需更高级功能可以使用 **tikz** 宏包。
- **zhnumber** 用于生成中文数字。

6 高级设置

6.1 切换字体

模板正文字体为宋体 (AdobeSongStd-Light)，同时我们提供如下命令切换中文字体：

```
\HEI {\HEI <content>}
```

```
\hei {\hei{<content>}}
```

切换字体为黑体 (AdobeHeitiStd-Regular)。

```
\KAI {\KAI <content>}
```

```
\kai {\kai{<content>}}
```

切换字体为楷体 (AdobeKaitiStd-Regular)。

```
\FANGSONG {\FANGSONG <content>}
```

```
\fangsong {\fangsong{<content>}}
```

切换字体为仿宋 (AdobeFangsongStd-Regular)。

如果需要加载其他字体，请参阅宏包 **fontspec**，宏包 **xeCJK** (对于 Xe_{La}TeX) 和宏包 **luatex-jaf** (对于 Lua_{La}TeX) 的文档。

III English Version Instruction

1 Requirement

Install the latest version of **TeXLive**(Recommend) or **MiKTeX**. Please ensure that all the packages are up-to-date.

2 Installation

2.1 Install into local

Use the command below to install this template into local.

```
make install
```

If you need uninstall it, use the command below.

```
make uninstall
```

For Windows User who don't install Make, use the command below to install.

```
makewin32.bat install
```

If you need uninstall it, use the command below.

```
makewin32.bat uninstall
```

Although `makewin32.bat` behaves much like `Makefile`, I still recommend you install Make into your Windows. You can download it from [here](#).

2.2 Use without installation

If you want to use this template temporary rather than installing it into local for long term use. Run below command to unpack the package.

```
make unpack
```

For Windows User who don't install Make, use the command below to unpack the package.

```
makewin32.bat unpack
```

Then copy the following files from directory `hustbeamer` into your \TeX project root directory.

- `hustbeamer.cls`
- `hust-header.png`

3 Usage



This template can only be compiled by
Xe_{La}TeX or Lua_{La}TeX (Recommend).

Insert below code in the top of source code to use this template:

```
\documentclass[language=english]{hustbeamer}
```

3.1 Option

There's one option available when use this template.

<code>language</code>	<code>language = <chinese english></code>
-----------------------	---

Set what language is used in the document. The default value is chinese.

3.2 Variables setting

There're some commands which are used to set the variables for the thesis.

<code>\title</code>	<code>\title{<the title>}</code>
<code>\title</code>	<code>\title[<short title>]{<long title>}</code>

Set title.

<code>\author</code>	<code>\author{<the author>}</code>
<code>\author</code>	<code>\author[<short author>]{<long author>}</code>

Set author.

<code>\date</code>	<code>\date{} % remove date field.</code>
<code>\date</code>	<code>\date{<content>} % put whatever you want.</code>
<code>\date</code>	<code>\date{<Year>}{<Month>}</code>
<code>\date</code>	<code>\date{<Year>}{<Month>}{<Day>}</code>

Set date.

3.3 Other commands

<code>\maketitle</code>	<code>\maketitle</code> and <code>\makecover</code> are the same. Used to create the title page.
<code>\makecover</code>	

<code>\PrintTOC</code>	<code>\PrintTOC</code> is used to insert the table of contents.
------------------------	---

`\EnableTOCAtBeginSection`
`\DisableTOCAtBeginSection`

This template will automatically insert current table of contents in every beginning of section. Use these two commands to enable or disable this feature.

`\email` `\email{\textit{Email Address}}`

A command to display email address. For example, `\email{name@example.com}` would look like this: `name@example.com`.

4 Simple example

Below is a simple example of using this template. For a complete example see `hustbeamer-example.tex` which will generate `hustbeamer-example.pdf`.

```
1 \documentclass[language=english]{hustbeamer}
2
3 \title[short title]{long title}
4 \author{your name}
5 \institute{your info}
6 \date{2013}{7}{1}
7
8 \begin{document}
9
10 \maketitle
11 \PrintTOC
12
13 %% main body
14
15 \end{document}
```

5 Introduction to some packages used in the template

Here's a list of some packages used in the template.

- `algorithm2e` For display algorithm.
- `fancynum` Display the really big number.
- `listings` For display the highlighted code. If you need better quality, use the package `minted`.
- `multirow` Combine multi-rows in table.

- `overpic` Put something over a picture,
- `tabularx` A better table environment.
- `xy-pic` To draw some picture. If you need more advanced features, use the package `tikz`.

IV Implementation

```
1 <*class>
2 \RequirePackage{ifthen}
```

1 Process Options

Use **xkeyval** to process options.

```
3 \RequirePackage{xkeyval}
4
5 Option language.
6
7 \gdef\HUST@language{chinese}
8 \DeclareOptionX{language}[chinese]{
9   \ifthenelse{\equal{#1}{chinese} \OR \equal{#1}{english}}{
10     \gdef\HUST@language{#1}
11   }{
12     \ClassError{hustbeamer}
13     {Option language can only be 'chinese' or 'english'}
14     {Try to remove option language^^J}
15   }
16 }
```

Process options and load class beamer.

```
14 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{beamer}}
15 \ProcessOptionsX
16 \LoadClass[12pt,utf8,compress,mathserif,noamsthm,xcolor=table]{beamer}
```

2 Check Engine

Check engine, only Xe^LA^TE^X and Lua^LA^TE^X are supported.

```
17 \RequirePackage{iftex}
18 \ifXeTeX\else
19   \ifLuaTeX\else
20     \begingroup
21       \errorcontextlines=-1\relax
22       \newlinechar=10\relax
23       \errmessage{^^J
24         *****^^J
25         * XeTeX or LuaTeX is required to compile this document.^^J
26         * Sorry!^^J}
```

```

27      *****~J
28      }%
29      \endgroup
30      \fi
31      \fi

```

3 Font Setting

Set font used in document. Firstly, it's font setting for English font under english mode. We use **fontspec** package to handle font. We choose Tex Gyre Termes, Droid Sans and CMU Typewriter Text as document main font, sans font and mono font.

```

32 \ifthenelse{\equal{\HUST@language}{english}}{
33     \RequirePackage{fontspec}
34     \setmainfont[
35         Ligatures={Common,TeX},
36         Extension=.otf,
37         UprightFont=*-regular,
38         BoldFont=*-bold,
39         ItalicFont=*-italic,
40         BoldItalicFont=*-bolditalic]{texgyretermes}
41     \setsansfont[Ligatures={Common,TeX}]{Droid Sans}
42     \setmonofont{CMU Typewriter Text}
43     \defaultfontfeatures{Mapping=tex-text}

```

Now let's set the Chinese font commands into empty, when document is under english mode.

```

44     \let\HEI\relax
45     \let\KAI\relax
46     \let\FANGSONG\relax
47     \newcommand{\hei}[1]{#1}
48     \newcommand{\kai}[1]{#1}
49     \newcommand{\fangsong}[1]{#1}
50 }{}

```

Below is the font setting under chinese mode. We chooses the same English font as under english mode. We use **xecjk** package (for X_YLA_TE_X) or **luatex-jafont** package (for Lua_YLA_TE_X, recommend) to handle Chinese font. We will use font: AdobeSongStd-Light, AdobeKaitiStd-Regular, AdobeHeitiStd-Regular and AdobeFangsongStd-Regular.

```

51 \ifthenelse{\equal{\HUST@language}{chinese}}{

```

```

52 \ifXeTeX % XeTeX 下使用 fontspec + xeCJK 处理字体
53 % 英文字体
54 \RequirePackage{fontspec}
55 \RequirePackage{xunicode}
56 \setmainfont[
57     Ligatures={Common,TeX},
58     Extension=.otf,
59     UprightFont=*-regular,
60     BoldFont=*-bold,
61     ItalicFont=*-italic,
62     BoldItalicFont=*-bolditalic]{texgyretermes}
63 \setsansfont[Ligatures={Common,TeX}]{Droid Sans}
64 \setmonofont{CMU Typewriter Text}
65 \defaultfontfeatures{Mapping=tex-text}
66 % 中文字体
67 \RequirePackage[CJKmath]{xeCJK}
68 \setCJKmainfont[
69     BoldFont={Adobe Heiti Std},
70     ItalicFont={Adobe Kaiti Std}]{Adobe Song Std}
71 \setCJKsansfont{Adobe Kaiti Std}
72 \setCJKmonofont{Adobe Fangsong Std}
73 \xeCJKsetup{PunctStyle=kaiming}
74
75 \newcommand\ziju[2]{\renewcommand{\CJKglue}{\hskip #1} #2}}

\HEI
76 \newCJKfontfamily\HEI{Adobe Heiti Std}

\KAI
77 \newCJKfontfamily\KAI{Adobe Kaiti Std}

\FANGSONG
78 \newCJKfontfamily\FANGSONG{Adobe Fangsong Std}

\hei
79 \newcommand{\hei}[1]{\HEI #1}}

\kai
80 \newcommand{\kai}[1]{\KAI #1}}

\fangsong
81 \newcommand{\fangsong}[1]{\FANGSONG #1}}

```

```

82 \else\fi
83 \ifLuaTeX % LuaTeX 下使用 luatex-jan 处理字体 [推荐]
84 \RequirePackage{luatexja-fontspec}
85 % 英文字体
86 \setmainfont[Ligatures={Common,TeX}]{Tex Gyre Termes}
87 \setsansfont[Ligatures={Common,TeX}]{Droid Sans}
88 \setmonofont{CMU Typewriter Text}
89 \defaultfontfeatures{Mapping=tex-text,Scale=MatchLowercase}
90 % 中文字体
91 \setmainfont[
92 BoldFont={AdobeHeitiStd-Regular},
93 ItalicFont={AdobeKaitiStd-Regular}]{AdobeSongStd-Light}
94 \setsansfont{AdobeKaitiStd-Regular}
95 \defaultjfontfeatures{JFM=kaiming}
96
97 \newcommand\ziju[2]{\vbox{\ltjsetparameter{kanjiskip=#1} #2}}

\HEI
98 \newjfontfamily\HEI{AdobeHeitiStd-Regular}

\KAI
99 \newjfontfamily\KAI{AdobeKaitiStd-Regular}

\FANGSONG
100 \newjfontfamily\FANGSONG{AdobeFangsongStd-Regular}

\hei
101 \newcommand{\hei}[1]{\jfontspec{AdobeHeitiStd-Regular} #1}

\kai
102 \newcommand{\kai}[1]{\jfontspec{AdobeKaitiStd-Regular} #1}

\fangsong
103 \newcommand{\fangsong}[1]{\jfontspec{AdobeFangsongStd-Regular} #1}
104 \else\fi

Generate Chinese number using zhnumber.

105 \RequirePackage{zhnumber}
106 \def\CJKnumber#1{\zhnumber{#1}} % 兼容 CJKnumb
107 }{}

```


4 Basic Format

Use **interfaces** package to handle font size and line spread. We set global line spread to 1.2.

```
108 \RequirePackage{interfaces-Latex}
109 \changefont{linespread=1.2}
```

Papaer setting.

```
110 \pdfpagewidth=\paperwidth
111 \pdfpageheight=\paperheight
```

Indent of paragraph and skip between paragraphs.

```
112 \RequirePackage[indentfirst]
113 \setlength{\parindent}{2em}
114 \setlength{\parskip}{0pt plus 2pt minus 1pt}
```

Use **hyperref** package to generate cross-reference link.

```
115 \RequirePackage[unicode]{hyperref}
116 \definecolor{HUST@hyperreflinkred}{RGB}{128,23,31}
117 \hypersetup{
118   bookmarksnumbered=true,
119   bookmarksopen=true,
120   bookmarksopenlevel=3,
121   colorlinks=true,
122   allcolors=HUST@hyperreflinkred,
123   pdfpagemode={FullScreen},
124   pdfinfo={Template.Info={hustbeamer.cls v1.0 2013/07/01, Copyright (C) 2013 by Xu C
125 }
```

5 Load Packages

Load packages for math.

```
126 \RequirePackage{amsmath,amssymb,amsfonts}
127 \RequirePackage[amsmath,amsthm,hyperref,thref]{ntheorem}
128 \RequirePackage{fancynum}
129 \setfnumgsym{\,,}
130 \RequirePackage[lined,boxed,linesnumbered,ruled,vlined,algorithsection]{algorithm2e}
```

Load packages for picture.

```
131 \RequirePackage[all]{xy}
132 \RequirePackage{overpic}
133 \RequirePackage{graphicx,caption,subcaption}
134 \RequirePackage{pgf,pgfarrows,pgfnodes,pgfautomata,pgfheaps,pgfshade}
```

Load packages for table.

```
135 \RequirePackage{array,tabu}
```

```
136 \RequirePackage{multirow}
```

Load package for code highlight. Here we use **listings** to highlight the code. But if you need more features, use **minted**.

```
137 \RequirePackage{listings}
```

Load package for bibliography cite style.

```
138 \RequirePackage[numbers,square,comma,super,sort&compress]{natbib}
```

Other packages for style setting.

```
139 \RequirePackage{datenumner}
```

```
140 \RequirePackage{etoolbox}
```

6 Variables Setting

\title A command to set the title.

```
141 \let\HUST@oldtitle\title
```

```
142 \DeclareDocumentCommand\title{o m}
```

```
143 {
```

```
144   \IfNoValueTF{#1}{
```

```
145     \HUST@oldtitle{#2}
```

```
146   }{
```

```
147     \HUST@oldtitle[#1]{#2}
```

```
148   }
```

```
149   \hypersetup{pdftitle={#2}}
```

```
150 }
```

```
151 \title{}
```

\author A command to set the author.

```
152 \let\HUST@oldauthor\author
```

```
153 \DeclareDocumentCommand\author{o m}
```

```
154 {
```

```
155   \IfNoValueTF{#1}{
```

```
156     \HUST@oldauthor{#2}
```

```
157   }{
```

```
158     \HUST@oldauthor[#1]{#2}
```

```
159   }
```

```
160   \hypersetup{pdfauthor={#2}}
```

```
161 }
```

```
162 \author{}
```

`\date` A command to set the date.

```
163 \let\HUST@olddate\date
164 \DeclareDocumentCommand\date{m g g}
165 {
166   \IfNoValueTF{#2}{
167     \HUST@olddate{#1} % only one argument
168   }{
169     \IfNoValueTF{#3}{ % two arguments
170       \setdate{#1}{#2}{1}
171       \ifthenelse{\equal{\HUST@language}{chinese}}{
172         \HUST@olddate{~\thedateyear~年~\thedatemonth~月}
173       }{
174         \HUST@olddate{\datemonthname~\thedateyear}
175       }
176     }{ % three arguments
177       \setdate{#1}{#2}{#3}
178       \ifthenelse{\equal{\HUST@language}{chinese}}{
179         \HUST@olddate{~\thedateyear~年~\thedatemonth~月~\thededay~
180           日}
181       }{
182         \HUST@olddate{\datedate}
183       }
184     }
185   }
186   \setdatetoday
187   \date{\thedateyear}{\thedatemonth}{\thededay}
```

7 Localization

Chinese localization. ²

```
188 \ifthenelse{\equal{\HUST@language}{chinese}}{
189   \def\indexname{索引}
190   \def\figurename{图}
191   \def\tablename{表}
192   \AtBeginDocument{\def\listingscaption{代码}}
193   \def\refname{参考文献}
194   \def\contentsname{目录}
```

²The `\autorefname` Reference:<http://tex.stackexchange.com/questions/52410/how-to-use-the-command-autoref-to-implement-the-same-effect-when-use-the-command>

```

195 \def\equationautorefname{公式}
196 \def\footnoteautorefname{脚注}
197 \def\itemautorefname~#1\null{第~#1~项\null}
198 \def\figureautorefname{图}
199 \def\tableautorefname{表}
200 \def\sectionautorefname~#1\null{#1~小节\null}
201 \def\subsectionautorefname~#1\null{#1~小节\null}
202 \def\subsubsectionautorefname~#1\null{#1~小节\null}
203 \def\FancyVerbLineautorefname~#1\null{第~#1~行\null}
204 \def\pageautorefname~#1\null{第~#1~页\null}
205 \def\lstlistingautorefname{代码}
206 \def\definitionautorefname{定义}
207 \def\propositionautorefname{命题}
208 \def\lemmaautorefname{引理}
209 \def\theoremautorefname{定理}
210 \def\axiomautorefname{公理}
211 \def\corollaryautorefname{推论}
212 \def\exerciseautorefname{练习}
213 \def\exampleautorefname{例}
214 \def\proofautorefname{证明}
215 \SetAlgorithmName{算法}{算法}{算法索引}
216 \SetAlgoProcName{过程}{过程}
217 \SetAlgoFuncName{函数}{函数}
218 \def\AlgoLineautorefname~#1\null{第~#1~行\null}
219 }{}

```

English localization.

```

220 \ifthenelse{\equal{\HUST@language}{english}}{
221 \def\contentsname{Contents}
222 \def\equationautorefname{Equation}
223 \def\footnoteautorefname{Footnote}
224 \def\itemautorefname{Item}
225 \def\figureautorefname{Figure}
226 \def\tableautorefname{Table}
227 \def\sectionautorefname{Section}
228 \def\subsectionautorefname{Subsection}
229 \def\subsubsectionautorefname{Sub-subsection}
230 \def\FancyVerbLineautorefname{Line}
231 \def\pageautorefname{Page}
232 \def\lstlistingautorefname{Code Fragment}
233 \def\definitionautorefname{Definition}
234 \def\propositionautorefname{Proposition}

```

```

235 \def\lemmaautorefname{Lemma}
236 \def\theoremautorefname{Theorem}
237 \def\axiomautorefname{Axiom}
238 \def\corollaryautorefname{Corollary}
239 \def\exerciseautorefname{Exercise}
240 \def\exampleautorefname{Example}
241 \def\proofautorefname{Proof}
242 \SetAlgorithmName{Algorithm}{Algorithm}{List of Algorithms}
243 \SetAlgoProcName{Procedure}{Procedure}
244 \SetAlgoFuncName{Function}{Function}
245 \def\AlgoLineautorefname{Line}
246 }{}

```

8 Style Setting

8.1 Beamer Style

```

247 \usetheme{Rochester}
248 \pgfdeclareimage[width=1.0\paperwidth]{hust-header}{hust-header.png}
249 \setbeamertemplate{itemize items}[circle]
250 \setbeamertemplate{enumerate items}[default]
251 \setbeamertemplate{blocks}[rounded][shadow=true]
252 \setbeamercovered{transparent}
253 \beamer@headheight=0.13\paperwidth
254 \definecolor{HUST@orange}{rgb}{0.96,0.5,0.04}
255 \definecolor{HUST@gray}{rgb}{0.40625,0.40625,0.40625}
256 \definecolor{HUST@lightgray}{rgb}{0.93,0.93,0.93}
257 \definecolor{HUST@blue}{rgb}{0.137,0.43,0.684}
258 \setbeamercolor*{Title bar}{fg=white}
259 \setbeamercolor*{Location bar}{fg=HUST@orange,bg=HUST@lightgray}
260 \setbeamercolor*{frametitle}{parent=Title bar}
261 \setbeamercolor*{block title}{bg=HUST@blue,fg=white}
262 \setbeamercolor*{block body}{bg=HUST@lightgray,fg=HUST@gray}
263 \setbeamercolor*{normal text}{bg=white,fg=HUST@gray}
264 \setbeamercolor*{section in head/footer}{bg=HUST@blue,fg=white}
265 \usecolortheme[named=HUST@orange]{structure}
266 \setbeamerfont{date}{size=\scriptsize,parent=structure}
267 \setbeamerfont{section in head/footer}{size=\tiny,series=\normalfont}
268 \setbeamerfont{frametitle}{size=\Large,series=\bfseries\HEI}
269 \setbeamertemplate{section in toc}[sections numbered]
270 \setbeamertemplate{subsection in toc}[subsections numbered]

```

```

271 \setbeamertemplate{navigation symbols}{}
272 \setbeamertemplate{frametitle}
273 {
274   \vskip-0.25\beamer@headheight
275   \vskip-\baselineskip
276   \vskip-0.2cm
277   \hskip0.7cm\usebeamerfont*{frametitle}\insertframetitle
278   \vskip-0.10em
279   \hskip0.7cm\usebeamerfont*{framesubtitle}\insertframesubtitle
280 }
281 \setbeamertemplate{headline}
282 {
283   \pgfuseimage{hust-header}
284   \vskip -1.95cm
285   \linethickness{0pt}
286
287   \framelatex{
288     \begin{beamercolorbox}[wd=\paperwidth,ht=0.3\beamer@headheight]{Title bar}
289       \usebeamerfont{section in head/foot}%
290       \hskip 1.2cm\insertsectionnavigationhorizontal{0pt}{\hskip0.22cm}{}%
291     \end{beamercolorbox}}
292
293   \framelatex{
294     \begin{beamercolorbox}[wd=\paperwidth,ht=0.7\beamer@headheight]{Title bar}
295     \end{beamercolorbox}}
296 }
297 \setbeamertemplate{footline}
298 {
299   \linethickness{0pt}
300   \framelatex{
301     \begin{beamercolorbox}[leftskip=.3cm,wd=\paperwidth,ht=0.3\beamer@headheight,sep=0
302       \usebeamerfont{section in head/foot}%
303       \insertshortauthor~|~\insertshorttitle
304       \hfill
305       \insertframenum/\inserttotalframenum
306     \end{beamercolorbox}}
307 }

```

8.2 Equation Style

Allow long equation breaking between lines or pages.

```

308 \allowdisplaybreaks[4]

```

Set skip between equation and context.

```
309 \abovedisplayskip=10bp plus 2bp minus 2bp
310 \abovedisplayshortskip=10bp plus 2bp minus 2bp
311 \belowdisplayskip=\abovedisplayskip
312 \belowdisplayshortskip=\abovedisplayshortskip

Set equation numbering style.
313 \numberwithin{equation}{section}
```

8.3 Theorem Style

We use `amsthm` to handle the proof environment and use `ntheorem` to handle other theorem environments.

```
314 \theoremnumbering{arabic}
315 \ifthenelse{\equal{\HUST@language}{chinese}}{
316   \theoremseparator{: }
317 }{
318   \theoremseparator{:}
319 }
320 \theorempreskip{1.2ex plus 0ex minus 1ex}
321 \theorempostskip{1.2ex plus 0ex minus 1ex}
322 \theoremheaderfont{\normalfont\bfseries\HEI}
323 \theoremsymbol{}
324
325 \theoremstyle{definition}
326 \theorembodyfont{\normalfont}
327 \ifthenelse{\equal{\HUST@language}{chinese}}{
328   \newtheorem{definition}{定义}[section]
329 }{
330   \newtheorem{definition}{Definition}[section]
331 }
332
333 \theoremstyle{plain}
334 \theorembodyfont{\itshape}
335 \ifthenelse{\equal{\HUST@language}{chinese}}{
336   \newtheorem{proposition}{命题}[section]
337   \newtheorem{lemma}{引理}[section]
338   \newtheorem{theorem}{定理}[section]
339   \newtheorem{axiom}{公理}[section]
340   \newtheorem{corollary}{推论}[section]
341   \newtheorem{exercise}{练习}[section]
342   \newtheorem{example}{例}[section]}
```

```

343 \def\proofname{\hei{证明}}
344 }{
345 \newtheorem{proposition}{Proposition}[section]
346 \newtheorem{lemma}{Lemma}[section]
347 \newtheorem{theorem}{Theorem}[section]
348 \newtheorem{axiom}{Axiom}[section]
349 \newtheorem{corollary}{Corollary}[section]
350 \newtheorem{exercise}{Exercise}[section]
351 \newtheorem{example}{Example}[section]
352 \def\proofname{\textbf{Proof}}
353 }

```

8.4 Floating Objects Style

Set the skip to the context for floating object with argument ‘h’.

```

354 \setlength{\intextsep}{0.7\baselineskip plus 0.1\baselineskip minus 0.1\baselineskip}

```

Set the skip to the context for top or bottom floating object.

```

355 \setlength{\textfloatsep}{0.8\baselineskip plus 0.1\baselineskip minus 0.2\baselineskip}

```

Set the fraction of floating object. Make the fraction less crowded than default value to prevent floating object occupying too much space.

```

356 \renewcommand{\textfraction}{0.15}
357 \renewcommand{\topfraction}{0.85}
358 \renewcommand{\bottomfraction}{0.65}
359 \renewcommand{\floatpagefraction}{0.60}

```

8.5 Table Style

`\tabincell` A command make it easier to insert a new table into an existing cell.

```

360 \newcommand{\tabincell}[2]{\begin{tabular}{@{}#1@{}}#2\end{tabular}}

```

8.6 Caption Style

Set caption font size as 11pt, use hang format, remove ‘:’ after number and set the skip between context as 12pt.

```

361 \DeclareCaptionFont{HUST@captionfont}{\changeont{size=11pt}}
362 \DeclareCaptionLabelFormat{HUST@caplabel}{#1~#2}
363 \captionsetup{
364   font=HUST@captionfont,

```



```

365   labelformat=HUST@caplabel,
366   format=hang,
367   labelsep=quad,
368   skip=12pt
369 }

```

8.7 Code Highlight Style

```

370 \definecolor{HUST@lstgreen}{rgb}{0,0.6,0}
371 \definecolor{HUST@lstmauve}{rgb}{0.58,0,0.82}
372
373 \lstset{
374   basicstyle=\footnotesize\ttfamily\changeont{linespread=1}\FANGSONG,
375   keywordstyle=\color{blue}\bfseries,
376   commentstyle=\color{HUST@lstgreen}\itshape\KAI,
377   stringstyle=\color{HUST@lstmauve},
378   showspaces=false,
379   showstringspaces=false,
380   showtabs=false,
381   numbers=left,
382   numberstyle=\tiny\color{black},
383   frame=lines,
384   rulecolor=\color{black},
385   breaklines=true
386 }

```

8.8 Bibliography Style

We use thubib.bst in **thuthesis** to typeset bibliography in Chinese language mode. And use **IEEEtran** in English language mode.

```

387 \ifthenelse{\equal{\HUST@language}{chinese}}{
388   \def\thudot{\unskip.}
389   \def\thumasterbib{[Master Thesis]}
390   \def\thuphdbib{[Doctor Thesis]}
391   \bibliographystyle{thubib}
392 }{
393   \bibliographystyle{IEEEtran}
394   \let\HUST@bibliography\bibliography
395   \def\bibliography#1{\HUST@bibliography{IEEEabrv,#1}}
396 }

```

9 Specical Page

\maketitle Commands to generate title page.

```
\makecover 397 \def\maketitle{
398   \let\HUST@oldthepage\thepage
399   \ifthenelse{\equal{\HUST@language}{chinese}}
400   {\def\thepage{封面}}
401   {\def\thepage{Titlepage}}
402   \begingroup
403   \setbeamertemplate{headline}{\pgfuseimage{hust-header}}
404   \setbeamertemplate{footline}
405   {
406     \linethickness{0pt}
407     \framelatex{
408       \begin{beamercolorbox}[leftskip=.3cm,wd=\paperwidth,ht=0.3\beamer@headheight,sep
409       \usebeamerfont{section in head/foot}%
410       \insertshortauthor~|~\insertshorttitle
411       \hfill
412       \end{beamercolorbox}}
413   }
414   \frame{\titlepage}
415   \endgroup
416   \let\thepage\HUST@oldthepage
417   \setcounter{framenum}{0}
418 }
419 \let\makecover\maketitle
```

\PrintTOC A command to generate table of contents.

```
420 \def\PrintTOC{
421   \section*{}
422   \begin{frame}{\contentsname}
423   \pdfbookmark{\contentsname}{\contentsname}
424   \tableofcontents[subsubsectionstyle=hide]
425   \end{frame}
426 }
```

Here we set whether insert current table of contents at beginning of section.

```
427 \newif\ifHUST@TOCAtBeginSection
428 \HUST@TOCAtBeginSectiontrue
```

TOCAtBeginSection Use `\EnableTOCAtBeginSection` to enable insert current table of contents at beginning of section.

```
429 \def\EnableTOCAtBeginSection{\HUST@TOCAtBeginSectiontrue}
```

TOCAtBeginSection Use `\DisableTOCAtBeginSection` to disable insert current table of contents at beginning of section.

```
430 \def\DisableTOCAtBeginSection{\HUST@TOCAtBeginSectionfalse}
```

Insert current table of contents at beginning of section.

```
431
```

```
432 \AtBeginSection[] {
```

```
433 \ifHUST@TOCAtBeginSection
```

```
434 \begin{frame}{\secname}
```

```
435 \tableofcontents[sectionstyle=show/shaded,subsectionstyle=hide]
```

```
436 \end{frame}
```

```
437 \else\fi
```

```
438 }
```

```
439 \AtBeginSubsection[] {
```

```
440 \ifHUST@TOCAtBeginSection
```

```
441 \begin{frame}{\secname}{\subsecname}
```

```
442 \tableofcontents[sectionstyle=show/hide,subsectionstyle=show/shaded/hide,subsubsec
```

```
443 \end{frame}
```

```
444 \else\fi
```

```
445 }
```

10 Other Command

\email

```
446 \def\email#1{
```

```
447 \href{mailto:#1}{\texttt{#1}}
```

```
448 }
```

```
449 \</class>
```

V Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

A		<code>\CurrentOption</code> 14
<code>\abovedisplayshortskip</code> .. 310, 312		
<code>\abovedisplayskip</code> 309, 311		D
<code>\AlgoLineautorefname</code> 218, 245		<code>\date</code> 5, 9, <u>163</u> , 163, 164, 187
<code>\allowdisplaybreaks</code> 308		<code>\datedate</code> 181
language 4, 9		<code>\datemonthname</code> 174
<code>\AtBeginDocument</code> 192		<code>\DeclareCaptionFont</code> 361
<code>\AtBeginSection</code> 432		<code>\DeclareCaptionLabelFormat</code> .. 362
<code>\AtBeginSubsection</code> 439		<code>\DeclareDocumentCommand</code>
<code>\author</code> 4, 9, <u>152</u> , 152, 153, 162	 142, 153, 164
<code>\axiomautorefname</code> 210, 237		<code>\DeclareOption</code> 14
		<code>\DeclareOptionX</code> 5
B		<code>\defaultfontfeatures</code> ... 43, 65, 89
<code>\baselineskip</code> 275, 354, 355		<code>\defaultjfontfeatures</code> 95
<code>\beamer@headheight</code>		<code>\definecolor</code>
..... 253, 274, 288, 294, 301, 408		. 116, 254, 255, 256, 257, 370, 371
<code>\begin</code> 288,		<code>\definitionautorefname</code> .. 206, 233
294, 301, 360, 408, 422, 434, 441		<code>\DisableTOCAtBeginSection</code> ...
<code>\belowdisplayshortskip</code> 312	 5, 10, <u>430</u> , 430
<code>\belowdisplayskip</code> 311		
<code>\bfseries</code> 268, 322, 375		E
<code>\bibliography</code> 394, 395		<code>\email</code> 5, 10, <u>446</u> , 446
<code>\bibliographystyle</code> 391, 393		<code>\EnableTOCAtBeginSection</code>
<code>\bottomfraction</code> 358	 5, 10, <u>429</u> , 429
C		<code>\end</code> 291,
<code>\captionsetup</code> 363		295, 306, 360, 412, 425, 436, 443
<code>\changeont</code> 109, 361, 374		<code>\equal</code> 6, 32, 51, 171, 178,
<code>\CJKglue</code> 75		188, 220, 315, 327, 335, 387, 399
<code>\CJKnumber</code> 106		<code>\equationautorefname</code> 195, 222
<code>\ClassError</code> 9		<code>\errmessage</code> 23
<code>\color</code> 375, 376, 377, 382, 384		<code>\errorcontextlines</code> 21
<code>\contentsname</code> 194, 221, 422, 423		<code>\exampleautorefname</code> 213, 240
<code>\corollaryautorefname</code> ... 211, 238		<code>\exerciseautorefname</code> 212, 239

F	
<code>\FancyVerbLineautorefname</code>	203, 230
<code>\FANGSONG</code>	6, 46, 78, 78, 81, 100, 100, 374
<code>\fangsong</code>	6, 49, 81, 81, 103, 103
<code>\figureautorefname</code>	198, 225
<code>\figurename</code>	190
<code>\floatpagefraction</code>	359
<code>\footnoteautorefname</code>	196, 223
<code>\footnotesize</code>	374
<code>\frame</code>	414
<code>\framelatex</code>	287, 293, 300, 407
<code>\insertframesubtitle</code>	279
<code>\insertframetitle</code>	277
<code>\insertsectionnavigationhorizontal</code>	290
<code>\insertshortauthor</code>	303, 410
<code>\insertshorttitle</code>	303, 410
<code>\inserttotalframenumbers</code>	305
<code>\intextsep</code>	354
<code>\itemautorefname</code>	197, 224
<code>\itshape</code>	334, 376
J	
<code>\jfontspec</code>	101, 102, 103
K	
<code>\KAI</code>	6, 45, 77, 77, 80, 99, 99, 376
<code>\kai</code>	6, 48, 80, 80, 102, 102
L	
<code>\Large</code>	268
<code>\lemmaautorefname</code>	208, 235
<code>\linethickness</code>	285, 299, 406
<code>\listingscaption</code>	192
<code>\LoadClass</code>	16
<code>\lstlistingautorefname</code>	205, 232
<code>\lstset</code>	373
<code>\ltjsetparameter</code>	97
M	
<code>\makecover</code>	5, 9, 397, 419
<code>\maketitle</code>	5, 9, 397, 397, 419
N	
<code>\newCJKfontfamily</code>	76, 77, 78
<code>\newif</code>	427
<code>\newjfontfamily</code>	98, 99, 100
<code>\newlinechar</code>	22
<code>\newtheorem</code>	328, 330, 336, 337, 338, 339, 340, 341, 342, 345, 346, 347, 348, 349, 350, 351
<code>\normalfont</code>	267, 322, 326
<code>\null</code>	197, 200, 201, 202, 203, 204, 218
<code>\numberwithin</code>	313
I	
<code>\ifHUST@TOCAtBeginSection</code>	427, 433, 440
<code>\ifLuaTeX</code>	19, 83
<code>\IfNoValueTF</code>	144, 155, 166, 169
<code>\ifthenelse</code>	6, 32, 51, 171, 178, 188, 220, 315, 327, 335, 387, 399
<code>\ifXeTeX</code>	18, 52
<code>\indexname</code>	189
<code>\insertframenumbers</code>	305
H	
<code>\HEI</code>	6, 44, 76, 76, 79, 98, 98, 268, 322
<code>\hei</code>	6, 47, 79, 79, 101, 101, 343
<code>\hfill</code>	304, 411
<code>\href</code>	447
<code>\hskip</code>	75, 277, 279, 290
<code>\HUST@bibliography</code>	394, 395
<code>\HUST@language</code>	4, 7, 32, 51, 171, 178, 188, 220, 315, 327, 335, 387, 399
<code>\HUST@oldauthor</code>	152, 156, 158
<code>\HUST@olddate</code>	163, 167, 172, 174, 179, 181
<code>\HUST@oldthepage</code>	398, 416
<code>\HUST@oldtitle</code>	141, 145, 147
<code>\HUST@TOCAtBeginSectionfalse</code>	430
<code>\HUST@TOCAtBeginSectiontrue</code>	428, 429
<code>\hypersetup</code>	117, 149, 160

O	
\OR	6
P	
\pageautorefname	204, 231
\paperheight	111
\paperwidth	110, 248, 253, 288, 294, 301, 408
\parindent	113
\parskip	114
\PassOptionsToClass	14
\pdfbookmark	423
\pdfpageheight	111
\pdfpagewidth	110
\pgfdeclareimage	248
\pgfuseimage	283, 403
\PrintTOC	5, 9, 420, 420
\ProcessOptionsX	15
\proofautorefname	214, 241
\proofname	343, 352
\propositionautorefname ..	207, 234
R	
\refname	193
\relax	21, 22, 44, 45, 46
S	
\scriptsize	266
\secname	434, 441
\section	421
\sectionautorefname	200, 227
\SetAlgoFuncName	217, 244
\SetAlgoProcName	216, 243
\SetAlgorithmName	215, 242
\setbeamercolor	258, 259, 260, 261, 262, 263, 264
\setbeamercovered	252
\setbeamerfont	266, 267, 268
\setbeamertemplate	249, 250, 251, 269, 270, 271, 272, 281, 297, 403, 404
\setCJKmainfont	68
\setCJKmonofont	72
\setCJKsansfont	71
\setcounter	417
\setdate	170, 177
\setdatetoday	186
\setfnungsym	129
\setlength	113, 114, 354, 355
\setmainfont	34, 56, 86
\setmainjfont	91
\setmonofont	42, 64, 88
\setsansfont	41, 63, 87
\setsansjfont	94
\subsecname	441
\subsectionautorefname ..	201, 228
\subsubsectionautorefname	202, 229
T	
\tabincell	360, 360
\tableautorefname	199, 226
\tablename	191
\tableofcontents	424, 435, 442
\textbf	352
\textfloatsep	355
\textfraction	356
\texttt	447
\theday	179, 187
\thedate	172, 179, 187
\theday	172, 174, 179, 187
\theoremautorefname	209, 236
\theorembodyfont	326, 334
\theoremheaderfont	322
\theoremnumbering	314
\theorempostskip	321
\theoremprskip	320
\theoremseparator	316, 318
\theoremstyle	325, 333
\theoremsymbol	323
\thepage	398, 400, 401, 416
\thudot	388
\thumasterbib	389
\thuphdbib	390

<code>\tiny</code>	267, 382	V	
<code>\title</code>	4, 9, <u>141</u> , 141, 142, 151	<code>\vbox</code>	97
<code>\titlepage</code>	414	<code>\vskip</code>	274, 275, 276, 278, 284
<code>\topfraction</code>	357		
<code>\ttfamily</code>	374	X	
U		<code>\xeCJKsetup</code>	73
<code>\unskip</code>	388		
<code>\usebeamerfont</code>	277, 279, 289, 302, 409	Z	
<code>\usecolortheme</code>	265	<code>\zhnumber</code>	106
<code>\usetheme</code>	247	<code>\ziju</code>	75, 97