SHELF & SOUL — PROJECT FILE INVENTORY

40 files listed | Generated 19 October 2026 | Paths relative to project root

Data protection: This is not a data backup. Prototype data is held in browser Local Storage; production records are held in Supabase PostgreSQL, including member contact details and operational history. Sample source data is in lib/demo-data.ts and prisma/seed.ts. Manager JSON exports are unencrypted; encrypted PostgreSQL backup files contain the full database. Keep connection credentials, personal data and backups private. Supabase is database-only; custom application authentication is used.

Dependency/build/cache folders (node_modules, .next, .git, coverage, dist, build and .turbo) are excluded because they are generated or third-party files.

FILE NAME (PROJECT-RELATIVE)	WHAT IT DOES	DATA / SENSITIVITY NOTE
.env.example	Supabase PostgreSQL URLs and environment-variable template for auth, reset email and backups.	Placeholders only. Never commit real credentials.
.gitattributes	Git file handling rules, including PDF binary treatment.	Repository metadata only.
.gitignore	Excludes environment secrets, generated outputs and backups from Git.	Ensures .env and backup artifacts are not tracked.
app/api/admin/backup/route.ts	Manager-only library JSON export and validated restore API.	Contains sensitive library/member records in exported JSON; export is not encrypted.
app/api/auth/login/route.ts	Production login/password verification and signed session issuance.	Processes account email and password; DB stores hash, not plaintext.
app/api/auth/logout/route.ts	Clears session cookie.	Session handling.
app/api/auth/password-reset/complete/route.ts	Validates one-time token and updates account password.	Password and token hashes are handled server-side.
app/api/auth/password-reset/request/route.ts	Creates expiring reset token and invokes configured email endpoint.	Processes email; sends raw token by email but stores token hash.
app/api/auth/register/route.ts	Creates customer account and membership.	Stores personal profile and password hash.
app/api/auth/session/route.ts	Checks current session and active account.	Returns user profile fields.
app/api/library/route.ts	Validates/authorizes application library actions and persists changes.	Handles personal, circulation, sales, fine and audit data.
app/api/public/catalog/route.ts	Public catalog and configured contact data endpoint.	Exposes intended public book/contact details.
app/api/staff/route.ts	Manager-only staff CRUD endpoint and audit records.	Stores staff profiles, roles, permissions and password hashes.
app/globals.css	Global responsive styling and print layout.	Presentation only.
app/layout.tsx	Root page layout and metadata.	Presentation metadata.
app/page.tsx	Main client application, auth UI, visitor views, dashboards and workflows.	Displays/submits operational and personal data.
lib/api-auth.ts	Production active-user/session/role helper.	Reads identity/role and permission data.
lib/auth-validation.ts	Shared account/password validation schemas.	Validation rules only.
lib/demo-data.ts	Sample books and library data plus state normalization.	Contains demo data; not actual customer data.
lib/library-service.ts	Core library operations, role rules, stock handling and audit creation.	Processes member, loan, inventory, sales and fine records.
lib/prisma.ts	Creates shared Prisma database client.	Uses server-side DATABASE_URL/DIRECT_URL.
lib/prototype-storage.ts	Prototype auth, session and library persistence in browser storage.	Stores demo account hashes and library/member data in Local Storage.
lib/session.ts	Signs/verifies session tokens and cookie settings.	Session contains identity; signing key comes from AUTH_SECRET.
lib/types.ts	Shared TypeScript models for domain entities and library state.	Defines operational/personal data shapes.

FILE NAME (PROJECT-RELATIVE)	WHAT IT DOES	DATA / SENSITIVITY NOTE
next-env.d.ts	Next.js generated type references.	Generated metadata.
next.config.ts	Next.js configuration.	Build/runtime configuration.
package-lock.json	Locks npm dependency versions.	Package names/versions.
package.json	Project scripts and dependencies, including db:backup.	Build/runtime configuration.
prisma/migrations/20261019170000_initial/migration.sql	Initial PostgreSQL tables/enums for users and library snapshot.	Schema only; no user rows.
prisma/migrations/20261019225000_auth_recovery/migration.sql	Adds auth version and reset-token table.	Schema only; no token rows.
prisma/migrations/migration_lock.toml	Declares PostgreSQL Prisma migration provider.	Migration metadata.
prisma/schema.prisma	Prisma model definitions for User, AuthToken and LibrarySnapshot.	Database schema; no records.
prisma/seed.ts	Creates initial snapshot, manager and optional demo accounts.	Writes demo data/accounts; passwords read from environment.
README.md	Run, setup, Supabase connection, backup and scope documentation.	Configuration guidance; no secrets should be added.
scripts/backup-postgres.mjs	pg_dump stream encryption with AES-GCM and retention cleanup.	Creates encrypted full database backups; encryption key is secret.
Shelf_and_Soul_File_Inventory.pdf	Inventory of filenames, purposes and data-handling notes.	Documentation only; not a backup.
Shelf_and_Soul_Project_Report.pdf	Current implementation/status report.	Project status; no credentials intended.
Shelf_and_Soul_Technical_Report.pdf	Supabase/PostgreSQL technical report.	Technical status; no credentials intended.
tsconfig.json	TypeScript compiler settings and path aliases.	Configuration only.
tsconfig.tsbuildinfo	Generated TypeScript incremental build cache.	Generated compiler data.