# SHELF & SOUL — PROJECT FILE INVENTORY

39 files listed | Generated 19 October 2026 | Paths are relative to the project root

**Important data note:** This is a filename/purpose guide, not a data backup. Live library data is stored in the browser Local Storage during prototype use, or in MySQL in production (including member contact information, loans, sales, fines, and audit history). Source files such as **lib/demo-data.ts** and **prisma/seed.ts** contain sample/demo values. Manager JSON exports contain library records and are unencrypted; scheduled MySQL backup output is encrypted. Keep credentials and personal data private.

Scope: includes project files outside dependency/build/cache folders. Excluded: node_modules, .next, .git, coverage, dist, build, and .turbo. Those contain installed dependencies or generated outputs and can be regenerated; this inventory does not claim to list every third-party dependency file.

| FILE NAME (PROJECT-RELATIVE) | WHAT IT DOES | DATA / SENSITIVITY NOTE |
|---|---|---|
| .env.example | Environment-variable template for database, authentication, email reset, and encrypted backup configuration. | Placeholder configuration only; never put real passwords/API keys here. |
| .gitignore | Lists files and folders Git should leave untracked. | May exclude .env, dependencies, builds, and local backups; those excluded files are not listed. |
| app/api/admin/backup/route.ts | Manager-only library snapshot JSON export and validated restore API. | Exports/imports member, catalog, loans, sales, fines, and other snapshot data; exported JSON is not encrypted. |
| app/api/auth/login/route.ts | Production login endpoint; checks password hash and issues a signed session. | Reads account email/password and account profile fields; password is not stored as plain text. |
| app/api/auth/logout/route.ts | Clears the signed-in session cookie. | Session/cookie handling; no library record storage. |
| app/api/auth/password-reset/complete/route.ts | Validates one-time reset token and changes the account password. | Processes reset token and new password; token hash/password hash stored in MySQL. |
| app/api/auth/password-reset/request/route.ts | Creates an expiring reset token and sends reset email via configured mail endpoint. | Processes email; raw token is emailed, only token hash stored in database; requires provider secrets. |
| app/api/auth/register/route.ts | Registers a customer account and links/creates its membership record. | Processes name, email, phone, membership details and password hash. |
| app/api/auth/session/route.ts | Verifies current session and returns active account profile. | Returns account profile fields; checks session version and active status. |
| app/api/library/route.ts | Validates, authorizes, executes, and persists library actions through the API. | Handles member details, loans, sales, fines, inventory, reviews, settings, and audit entries. |
| app/api/public/catalog/route.ts | Provides public catalog and configured library contact information. | Exposes public book metadata and contact settings; no account secrets. |
| app/api/staff/route.ts | Manager-only staff account list/create/update API and staff audit logging. | Processes staff contact details, role/permissions, and password hashes. |
| app/globals.css | Global responsive UI styles, components, and print styles. | Presentation only; no records. |
| app/layout.tsx | Root HTML layout and page metadata wrapper. | Application metadata; no customer records. |
| app/page.tsx | Main client UI: sign-in, visitor pages, staff/customer screens, reports and workflows. | Displays and submits account, member, circulation, inventory, sales, fine and contact data. |
| lib/api-auth.ts | Loads the active production user and checks current session/version. | Reads account role, permissions, and identity from MySQL/session. |
| lib/auth-validation.ts | Shared Zod schemas for login, registration, and password requirements. | Defines validation rules; no stored user data. |
| lib/demo-data.ts | Default prototype catalog, sample members, loans and normalization of library state. | Contains demo/example books and sample library/member records; not intended as real customer data. |

| FILE NAME (PROJECT-RELATIVE) | WHAT IT DOES | DATA / SENSITIVITY NOTE |
|---|---|---|
| lib/library-service.ts | Core library business rules, permissions, workflows, stock changes and audit generation. | Processes and transforms operational data including members, loans, sales, fines and audit history. |
| lib/prisma.ts | Creates/reuses the Prisma database client. | Database connection access; credentials come from environment configuration. |
| lib/prototype-storage.ts | Prototype Local Storage account, session, library data, and demo actions. | Stores prototype account hashes and library/member records in the current browser Local Storage. |
| lib/session.ts | Signs/verifies session JWT and defines secure cookie options. | Contains session identity/role in signed token; secret is read from AUTH_SECRET environment variable. |
| lib/types.ts | TypeScript models for books, members, loans, sales, settings, audit and other data. | Defines schemas/shapes of operational and personal data; no records stored here. |
| next-env.d.ts | Next.js generated TypeScript environment declarations. | Generated framework declarations; no business records. |
| next.config.ts | Next.js project configuration. | Configuration only; no records. |
| package-lock.json | Locks exact npm dependency versions for reproducible installs. | Dependency names and versions; no customer records or secrets. |
| package.json | Project metadata, npm scripts, and dependency declarations. | Build/dependency configuration; no customer records. |
| prisma/migrations/20261019170000_initial/migration.sql | Initial MySQL schema migration for user accounts and library snapshot. | Defines database structures and constraints; does not contain customer rows. |
| prisma/migrations/20261019225000_auth_recovery/migration.sql | Adds authentication versioning and expiring auth-token table. | Defines token/password-reset metadata structures; no actual token rows. |
| prisma/migrations/migration_lock.toml | Records Prisma migration provider selection. | Database provider metadata only. |
| prisma/schema.prisma | Prisma data model for User, AuthToken, and LibrarySnapshot. | Defines where account/authentication and library data are stored; not the data rows themselves. |
| prisma/seed.ts | Initializes the library snapshot and creates the bootstrap manager; optional demo staff/customer accounts. | Writes demo catalog/member records and accounts to the configured database; reads passwords from environment variables. |
| README.md | Project run/setup guide, current scope, payment flow, password reset and backups documentation. | Operational guidance; do not paste real secrets into documentation. |
| scripts/backup-mysql.mjs | Streams mysqldump into AES-256-GCM encrypted backup and prunes old matching backups. | Reads DB credentials and encryption key from environment; output contains full database data in encrypted form. |
| Shelf_and_Soul_File_Inventory.pdf | This file: project filename inventory, purpose and data/sensitivity notes. | Explains where data is handled; not a database export. |
| Shelf_and_Soul_Project_Report.pdf | Existing project report document. | May include project information; review its contents before sharing externally. |
| Shelf_and_Soul_Technical_Report.pdf | Technical status report created for the project. | Contains technical summaries and production-readiness notes; no credentials intended. |
| tsconfig.json | TypeScript compiler settings and source include/exclude rules. | Compiler configuration only. |
| tsconfig.tsbuildinfo | Generated TypeScript incremental build cache. | Build metadata, not library/member records; regenerable. |