



## XP-T230L

### Thermal Receipt Printer

- Water proof, oil proof, dust proof design
- Wifi, Bluetooth option
- Led light and sound alarm
- Wall mountable design

### APPLICATIONS



Shopping



Mart



Hospital



Coffee Shop



Restaurant




Ticketing



Express



Factory

[illegible]



## XP-T300L

### Thermal Receipt Printer

- Water proof, oil proof, dust proof design
- ESC/POS compatible(including code page)
- Led light and sound alarm
- Wall mountable design

### APPLICATIONS



Shopping



Mart



Hospital



Coffee Shop



Restaurant



Ticketing



Express



Factory

# XF

Ther



| MODEL                 |  |
|-----------------------|--|
| Printing Method       | Direct thermal                         |
| Printing Speed        | 300mm/s                                |
| Paper Width           | 79.5±0.5 mm                            |
| Print Range           | 72mm(adjustable by commands)           |
| Maxi Paper Dia        | Φ80 mm                                 |
| Paper Thickness       | 0.06-0.08mm                            |
| Color                 | 576 dots/line 512 dots/line            |
| Line Spacing          | 3.75mm(Changeable by commands)         |
| Compatible            | Compatible with ESC/POS                |
| Interface             | USB+Serial+Lan                         |
| Dimension             | 198×148×138mm (D×W×H)                  |
| Gross weight          | 1.78 kg                                |
| Barcode               |  |
| 2-dimensional code    |  |
| Code page             |  |
| Cutter                | Partial                                |
| Cutter Capacity       | 1.5 million cuts                       |
| Print head            | 100KM                                  |
| Input buffer          | 2048 Kbytes                            |
| Memory Flash          | 256 Kbytes                             |
| Power adapter         | AC110V/220V, 50~60Hz                   |
| Power supply          | DC 24V/2.5A                            |
| Input voltage         | 24V/2.5A                               |
| Cash drawer           |  |
| Work environment      | Temperature: 10~40℃ Humidity: 10~80RH% |
| Storage environment   | Temperature -10~60℃ Humidity: 1~90RH%  |
| Operating environment |  |