ATP-H58 Thermal Receipt Printer

Product Introduction:

ATP-H58 is a well-designed economic printer for common thermal bill printing ,this mold is with solid material,Exquisite workmanship.Transparent cover design, simple

-H58 adopt

built-in power supply,not only can save space,but also easy for users to configure

choice for economical printing.

Product Features：

Simple and fashion,With solid material,exquisite workmanship. Easy paper install structure,simple and convenient to operate

Built-in power supply design, to save space and more convenient to configure;

Transparent cover design, the user can know the paper

Support GB18030 big font, easy to print uncommon characters

Support multi language print, suitable for users all over the world; Support download and print LOGO&graphics ;

Support Windows, Linux, Android and IOS system printing

Application Area：

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal

Parameters：

Items		Parameters
Print parameters	Printing Method	Thermal Line
	Printing Method	48MM
	Resolution	384dots/Line（8dots/mm，203dpi）
	Printing Speed	130mm/Second
	Interface Type	USB，USB+Bluetooth(1 to 1),USB+Bluetooth(1 to many)
	Line Spacing	3.75 mm（Can adjust line spacing by command）
	Line No.	Font A:32 character /Line Font B:42 character/Line Simple,traditional Chinese-16 lines
	Character	Standard GB18030 simplified / traditional Chinese Fonts

	Character Size	ANKcharacter，Font A：1.5×3.0mm（12×24 点）Font B：1.1×2.1mm（9×17 点）Simplified/Traditional Chinese：3.0×3.0mm(24×24 Dots）
Bar code Character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/ Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/P C858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/T haiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	1D bar code： UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128 2D bar code：QRCODE
Graphics printing	Graphics printing	Supports bitmap download and print
Paper	Type	Thermal Roll
	Width	57.5±0.5mm

	Diameter	
	Feed Method	Easy feed(Clameshell feed)
Print	Commands	ESC/POS
Power	Power Adaptor	Input：AC 100V-240V,50-60Hz Output：DC 12V/2A
	Casher Drawer	DC 12V/1A
Buffer	Input Buffer	4K
	NV Flash	40K
physical characteristics	Weight	590g
	Dimension	185*130*112(MM)
Environment	Working	Temp：5～45℃，Humidity：10～80%
	Storage	Temp：-10～50℃，Humidity：10～90%（No dew）
Reliability parameter	Print Head Life	100KM（print ）
	Cutter Life	1000,000times