e-ID Card Reader and Biometric Authentication Device

A612

MK Vision's M6 Biometric e-ID Card Authentication Device is an e-ID card reader that performs identity verification through fingerprint and facial matching (MOC) in accordance with Public Security Ministry protocols, and is capable of integration with access control management software developed by MK Vision. The product supports enterprises and organizations in security control, enhancing protection, identity verification, and access management across multiple sectors including: E-government; Smart cities; Online Payment Banking; Healthcare; Transportation; Education; Telecommunications.



FINGERPRINT
FAP 20 OPTICAL

WIFI
WI-FI 802.11 B/G/N
(2.4 GHZ)

INTEGRATED FILL LIGHT
WHITE LED LIGHT


NFC COMMUNICATION

DISPLAY
5-INCH TOUCHSCREEN

WIRED CONNECTIVITY
LAN (POE)







Headquarters: The Vista, No. 4, Lane 15
Duy Tan Street,Cau Giay District, Hanoi

Website: http://mkvision.com
Email: contact@mkvision.com

Phone: (+84 24) 7100 6785
(+84 24) 3813 4646

Access Control Device for Gate Entry

A612





Camera	
Image Sensor	Sony 1/ 2.8" CMOS
Lens	Fixed focal length, 2.8 mm, F2.2, 140° field of view
Night Mode	Automatic Switching
Minimum Illumination	Color Mode: 0.001 lux at 50 IRE, F2.2 Infrared Mode: 0 lux
Configuration	
Processor	Quad-core Arm® Cortex®-A53 1 GHz
Memory	1025 MB DDR4
Processing Performance	Ambarella image signal processor and video encoding Edge vision analysis CVflow®
Video	
Resolution	2MP
Compression Standard	H.264
Frame Rate	Up to 30 frames per second at Full HD resolution
Signal-to-Noise Ratio	≥ 50dB
Wide Dynamic Range (WDR)	≥ 120dB
Image Adjustment	Automatic White Balance, Automatic Backlight Compensation, Automatic Gain Adjustment, HDR
Audio	
Audio Input	Microphone*1
Audio Output	Speaker*1
Connectivity	
Wired Connection	1*USB-C, 1*Relay port, 1*Alarm, 1*RJ45
Wireless connectivity	WiFi: 802.11 b/g/n, 2.4 GHz & 5 GHz Bluetooth: BLE 4.2 NFC: Supports reading of ISO/IEC 14443 contactless card protocol
Protocol	MK Vision SDK
Information security	Firmware digital signature; Video digital signature; Event digital signature; One-time password (OTP); True random number generator (TRNG); Password encryption; Secure boot TrustZone®; Memory encryption; DRAM scrambling
System Integration	
Application Programming Interface	Open API service for software integration: metadata, events, reports
Video Surveillance System	Compatible with MK Vision video management system
Analytics	
Intelligent Features	[IDVision] Supports up to 20,000 facial profiles in the database. Facial recognition rate ≥90%. Supports facial template library encryption. Fingerprint recognition supported by FAP20 optical fingerprint module, compatible with chipembedded ID card fingerprint data, featuring automatic live fingerprint detection.
Certification	
ISO	ISO 9001:2016
Overview	
Housing	ABS Plastic, PC
Power Supply	12VDC; PoE IEEE 802.3af
Display	5-inch Touchscreen, 480x854 px
Illumination	White LED: 0.5 m
Storage	64 GB EMMC Flash
Security Module	Supports 2 SAM Slot
Operating Conditions	-10°C to 50°C, humidity 90% and non-condensing
Storage Conditions	-10°C to 50°C, humidity 90% and non-condensing
Dimensions	185 x 79 x 27 mm
Weight	130 g
Accessories	Desktop Stand, Wall-Mounted Stand, Relay Cable, Alarm Cable
Supported Languages	English, Vietnamese
CO	Manufactured in Vietnam
CQ	MK Vision CQ, Quatest

Headquarters: The Vista, No. 4, Lane 15
Duy Tan Street,Cau Giay District, Hanoi

Website: http://mkvision.com
Email: contact@mkvision.com

Phone: (+84 24) 7100 6785
(+84 24) 3813 4646