PRODUCT
CATALOG
YEAR 2024



pavana

Smart Security Camera

HTTPS://PAVANA.TECH/EN/ | ADDRESS : THE VISTA 4/15 DUY TAN, HA NOI

pavana
Smart Security Camera

MODEL NO
PVN CH222M6ND 2812PW-A



- High quality imaging with progressive scan CMOS
- Support SMART H.265/H.264 coding
- Up to 45M IR distance
- motorized 4X zoom lens
- 3D DNR,BLC
- Built-in micro SD card slot, up to 256GB
- 1CH audio input; 1CH audio output
- DC12V/PoE power supply
- IP67
- P2P function optional
- Support Multiple streams
- Support mobile surveillance by smart phones

pavana
Smart Security Camera

MODEL NO
PVN CH222M6ND 2812PW-A

Video	
Imaging Device	1/2.7"
Effective Pixels	2MP 1920(H)×1080(V)
Scanning System	Progressive CMOS
Min.Illumination	Color 0.006lux @F1.6(AGC ON) ; B/W 0 lux @ IR ON
Lens Type	
Focal Length (Zoom Ratio)	2.8-12mm
Max. Aperture Ratio	F No. 1.8 (W) ~3.3(T)
Angular Field of View	H:107° (W) -35° (T) V:54° (W) -20° (T) D:133° (W) -40° (T)
Min. Object Distance	1.2m (W/T)
Lens Type	Manual(Ø14)
Operational	
IR Viewable Length	Up to 45m
Camera Title	On/Off
Day &Night	IR cut filter with auto switch (Day/Night/Auto/Image/Schedule)
Backlight Compensation	Off/On (5 Zone)
Wide Dynamic Range	DWDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Privacy Masking	Off/On (4 Zone, Rectangle)
Gain Control	Auto
White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
Mirror	Flip/Rotation
On-Board Storage	Micro SD slot, up to 256GB
Alarm	NA
Audio	1 input (RCA), 1 output (RCA)
Hardware Reset	Yes
Smart Feature	NA

pavana
Smart Security Camera

MODEL NO
PVN CH222M6ND 2812PW-A

Network	
Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264
Resolution	Main Stream &30fps 1080P(1920x1080) Sub Steam &20fps VGA(640x480)
Video Quality Ajustment	256Kbps ~ 4Mbps
Bitrate control method	CBR/VBR
Streaming Capability	Dual-Stream(Main/Sub)
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP
Web browser	IE10/11
Security	complicated password;Authenticated username and password
Streaming Method	Unicast/Multicast
Application Programming Interface	ONVIF
Environmental	
Operating Conditions	-35 ~ +60°C/less than ≤ 90% RH
Ingress Protection	IP67
Electrical	
Input Voltage/ Current	D12V/POE(IEEE802.3af)
Power Consumption (IR OFF)	1.5W-2.5W
Power Consumption (IR ON)	5.5W-7.5W
Mechanical	
Material	Metal
Dimensions (HxWxD)	242*87.4*83.88mm
Weight	782g

pavana
Smart Security Camera

MODEL NO
PVN-CH322M6MCA-2812PW-A



- High quality imaging with progressive scan CMOS
- Support SMART H.265/H.264 coding
- Up to 45M IR distance
- Motorized 4X zoom lens
- 3D DNR,BLC
- Built-in micro SD card slot, up to 256GB
- DC12V/PoE power supply
- IP67
- P2P function optional
- Support Multiple streams
- Support mobile surveillance by smart phones

pavana
Smart Security Camera

MODEL NO
PVN-CH322M6MCA-2812PW-A

Video	
Imaging Device	1/2.7"
Effective Pixels	2MP 1920(H)×1080(V)
Scanning System	Progressive CMOS
Min.Illumination	Color 0.006lux @F1.6(AGC ON) ; B/W 0 lux @ IR ON
Lens Type	
Focal Length (Zoom Ratio)	2.8-12mm
Max. Aperture Ratio	F No. 1.8 (W) ~3.3(T)
Angular Field of View	H:107° (W) -35° (T) V:54° (W) -20° (T) D:133° (W) -40° (T)
Min. Object Distance	1.2m (W/T)
Lens Type	Manual(Ø14)
Operational	
IR Viewable Length	Up to 45m
Camera Title	On/Off
Day &Night	IR cut filter with auto switch (Day/Night/Auto/Image/Schedule)
Backlight Compensation	Off/On (5 Zone)
Wide Dynamic Range	DWDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Privacy Masking	Off/On (4 Zone, Rectangle)
Gain Control	Auto
White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
Mirror	Flip/Rotation
On-Board Storage	Micro SD slot, up to 256GB
Alarm	NA
Audio	1 input (RCA), 1 output (RCA)
Hardware Reset	Yes
Smart Feature	NA

pavana
Smart Security Camera

MODEL NO
PVN-CH322M6MCA-2812PW-A

Network	
Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264
Resolution	Main Stream &30fps 1080P(1920x1080) Sub Steam &20fps VGA(640x480)
Video Quality Ajustment	256Kbps ~ 4Mbps
Bitrate control method	CBR/VBR
Streaming Capability	Dual-Stream(Main/Sub)
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP
Web browser	IE10/11
Security	complicated password;Authenticated username and password
Streaming Method	Unicast/Multicast
Application Programming Interface	ONVIF
Environmental	
Operating Conditions	-35 ~ +60°C/less than ≤ 90% RH
Ingress Protection	IP67
Electrical	
Input Voltage/ Current	D12V/POE(IEEE802.3af)
Power Consumption (IR OFF)	1.5W-2.5W
Power Consumption (IR ON)	5.5W-7.5W
Mechanical	
Material	Metal
Dimensions (HxWxD)	135.56*135.56*127mm
Weight	821g

pavana
Smart Security Camera

MODEL NO
PVN-N1064OD-E4HL



Video	Resolution	12MP,8MP,5MP, 3MP, 2MP(1080P), 1.3MP(960P), 1.0MP(720P)
Recording Bandwidth	Inputs	640M
	Out	640M

pavana
Smart Security Camera

MODEL NO
PVN-N1064OD-E4HL

Performance		
Live/Playback	Compression	Audio: G.711A/G.711U
		Video :H.264/H.265/H.264+/H.265+
	Frame rate	4K:240fps 4MP:480fps 2MP:960fps
	Event	MD(Sensitivity Level 1~8)
		Videlo loss
		Beep,Email
		Push notification to Mobile APP
	Playback function	Fast forward / backward (2x, 4x, 8x,16x)
		Slow forward (1/2x, 1/4x, 1/8x,1/16x)
	Playback	Max 16CH playback
RAID	RAID Type	RAID0, RAID1, RAID5, RAID6, RAID10
	Fisheye	Support
UI/Monitoring	Local	UI5.0
	WEB	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above
	Mobile viewer	Rxcamview
AI		Face Detection
		Pedestrian Detection
		Vehicle Detection
		Cross Counting
		Heat Map
		Crowd Density Detection
		PerimeterIntrusion Detection
		Line Crossing Detection
		Queue Legth Detection
		License Plate Detection
		Rare Sound Detection

pavana
Smart Security Camera

MODEL NO
PVN-N1064OD-E4HL

Interface		
P/W Reset		YES
Monitors	HDMI	3（1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 , 1920*1080,1600*1200，1920*1200, 3840*2160/7680*4320/EDID）Async out *If the output resolution of HDMI 1 is set to 8K, the maximum output resolution of HDMI 3 and 4 will be limited to 1080P, and HDMI 2 will be disabled.
		1（1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 /EDID）Async out
	Ethernet	2 RJ45 1000 Base-T
	USB	USB2.0*1(front)　USB3.0*2(rear)
	Audio out	1
	E-sata	1
	HDD	16 SATA HDD, up to 18TB (Enterprise-Class)
	Line in	1
	RS232	1*RJ45
	RS485	1
	Alarm Input/out	16 in /4 out
General		
OSD Language		English/French/Spanish/Portuguese/German /Ialian/Greek/Danish/Finnish/Russia/Hebrew/ Turkish/Bulgarian/Arabc/Korean/Japanese/Thai /Hindi/Romanian/Dutch/Polish
Mechanical design	Dimension (WxDxH)	440*460*149mm
Electrical	Input Voltage/Current	ATX 250W
	Power consumption (excluding hard disk)	8W
Environmental	Operating Temperature/Humidity	Temperature : -10°C~+50°C (14°F ~ 122°F)
		Humidity: Less than 90%RH

pavana
Smart Security Camera

MODEL NO
SC609E



Video	
Imaging Device	1/2.7"
Effective Pixels	5MP 2592(H)×1944(V)
Scanning System	Progressive CMOS
Min. Illumination	Color 0.003lux @ F1.6(AGC ON) ; B/W 0 lux @ IR ON

pavana
Smart Security Camera

MODEL NO
SC609E

Lens Type	
Focal Length (Zoom Ratio)	2.7-13.5mm
Max. Aperture Ratio	F No. 1.8 (W) ~ 3.3(T)
Angular Field of View	Horizontal: 31 ~102°, Vertical: 23 ~ 73°, Diagonal: 38 ~ 138°
Min. Object Distance	0.3m~INF
Lens Type	Motorized(Ø14)
Operational	
IR Viewable Length	Up to 45m
Camera Title	On/Off
Day & Night	IR cut filter with auto switch（Day/Night/Auto/Image/Schedule）
Backlight Compensation	Off/On (5 Zone)
Wide Dynamic Range	WDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Privacy Masking	Off/On (4 Zone, Rectangle)
Gain Control	Auto
White Balance	Auto/Manual
Electronic Shutter Speed	1/5~ 1/20000s
On-Board Storage	Micro SD slot, up to 256GB
Alarm	1 input, 1 output
Audio	1 input (RCA), 1 output (RCA)
Hardware Reset	Yes
Smart Feature	Face Recognition（FR） Human&Vehicle Detection（PD&VD） Perimeter Intrusion Detection（PID) Line Crossing Detection（LCD） Cross Counting（CC） Stationary Object Detection（SOD) Heat Map（HM） Crowd Density Detection（CD） Queue Lenght Detection（QD） license Plate Recognition（LPR） Rare Sound Detection（RSD）

pavana
Smart Security Camera

MODEL NO
SC609E

Network	
Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264
Resolution	Main Stream @30fps 5MP(2592x1944),4MP(2592x1520),3MP(2304x1296), 1080P(1920x1080), 960P(1280*960) Sub Steam @30fps 1080P(1920x1080)，720P(1280x720),VGA(640x480) Mobile Stream @30fps VGA(640x480), QVGA（320x240）
Video Quality Ajustment	256Kbps ~ 8Mbps
Bitrate control method	CBR/VBR
Streaming Capability	Triple-Stream(Main/Sub/Moile)
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP
Web browser	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above
Security	IP address filter;complicated password;Authenticated username and password
Streaming Method	Unicast/Multicast
Application Programming Interface	ONVIF(Profile S/G/T)
Environmental	
Operating Conditions	-35～+60°C/less than ≤ 95% RH
Ingress Protection	IP67
Electrical	
Input Voltage / Current	D12V/POE(IEEE802.3af)
Power Consumption（IR OFF）	3.5W-4.5W
Power Consumption（IR ON）	7.5W-9.5W
Mechanical	
Material	Metal
Dimensions (HxWxD)	242*87.4*83.88mm
Weight	811g

pavana

CATALOG