VA50FA0V

AI Outdoor Dome Camera

Ambarella CVflow

QCVN 135:2024/BTTTT



- **Video content analysis**
- **Extended long-range infrared distance**
- **HDR Engine Gen3**
- **Impact resistance IK10**
- **Dust and water protection IP67**

The 5MP AI Outdoor Dome Camera is an AI camera product "Made in Vietnam" by MK Vision, offering a comprehensive surveillance solution that combines advanced image processing technology with Edge AI (AI on Edge). The camera integrates HDR Engine Gen3 to deliver outstanding image sharpness even in low-light conditions, along with intelligent video content analysis powered by Ambarella CVflow. The camera is designed for reliable operation in all environments, meeting IK10 impact resistance and IP67 dust and water protection standards. In addition, the product fully complies with ONVIF Profile S/G/T/M compatibility standards and the information security standard, confirming it as an optimal choice in terms of performance and security.

Headquarters: The Vista, No. 4, Lane 15
Duy Tan Street,Cau Giay District, Hanoi

Website: http://mkvision.com
Email: contact@mkvision.com

Phone: (+84 24) 7100 6785
(+84 24) 3813 4646

Specification

Configuration	
SoC	Ambarella CV25
Processor	Quad-core ARM® Cortex® A53 1GHz
ROM memory	NAND Flash
Memory	1GB DDR4
Processing performance	CVflow® Computer Vision Engine @588MHz DNN Accelerated Engine
Smart features	AI Video Motion Detection, AI People Detection, AI Vehicle Detection, AI Face Detection, AI Face Recognition, AI License Plate Recognition, ...
Camera	
Sensor	OmniVision 5M (1/2.7" Progressive CMOS)
FOV	Horizontal: 102.1(W) - 31.5(T) ° Vertical: 70.3(W) - 22.7(T)°
Lens	Auto focus: 2.8-12mm
Detection range 25 ppm	56m(W) - 240m(T)
Observation range 62.5 ppm	22,4m(W) - 96m(T)
Recognition range 125ppm	11,2m(W) - 48m(T)
Identification range 250 ppm	5,6m(W) - 24m(T)
Night mode	Automatic IR-cut filter Automatic switching
Minimum lighting	Infrared mode: 0 lux Infrared: ≥ 50m
Shutter speed	1 ~ 1/10.000 s
Video	
Resolution	5 Megapixels (2592H x 1944V)
Compression standard	H.265 / H.264 / Motion JPEG
Frame rate	5MP @30fps
Signal-to-Noise Ratio (SNR)	≥ 50dB
Exposure balance	HDR Engine Gen3, WDR 120dB
Adjust the image	Automatic White Balance (AWB), Backlight Compensation (BLC), Automatic Gain Control (AGC), Auto Iris, Auto Focus
Connect	
Connection ports	RJ45, 10/100Mbps
Supports protocols	ARP, PPPoE, IPv4/v6, ICMP, IGMP, QoS, TCP, UDP, DHCP, UPnP, SNMP, SMTP, RTP, RTSP, HTTP, HTTPS, FTP, NTP, DDNS
ONVIF®	Profile S, G, T, M
Certification	
ISO	ISO 9001:2015
Protection standard	IP67 - TCVN 4255:2025 (IEC 60529:2013) IK10 - TCVN 14227:2025 (IEC 62262:2021)
Electrical safety	TCVN 73126-1:2003 (IEC 60950-1:2001)
Information safety	NDAA, FIPS 140-2 Level 3
Overview	
Case	Metal
Power supply	12VDC; PoE IEEE 802.3af
Storage	Support microSD / microSDHC / microSDXC
Operating conditions	-5 ~ +60°C/ humidity ≤ 95% RH
Storage conditions	-15 ~ +65°C/ humidity ≤ 95% RH
Dimensions	Ø 133.8x117.4 mm
Weight	760 g
Supported languages	English, Vietnamese
Certificate of origin	Made in Vietnam