VB50FB1V

5MP AI Outdoor Bullet Camera

Ambarella CVflow

QCVN 135:2024/BTTTT



- Sony Sensor IMX-415
- Extended long-range infrared distance
- Impact resistance IK10
- HDR Engine Gen3
- Video content analysis
- Dust and water protection IP67

The 5MP AI Outdoor Bullet Camera is a “Made in Vietnam” AI camera by MK Vision, providing a comprehensive surveillance solution that integrates advanced image processing technology with Edge AI. The camera is equipped with a Sony IMX-335 sensor and HDR Engine Gen3, delivering outstanding image clarity even in low-light conditions, while intelligent video content analysis is powered by Ambarella CVflow. Designed for reliable operation in all environments, it meets IK10 impact resistance and IP67 dust and water protection standards. Notably, the product fully complies with ONVIF Profile S/G/T/M interoperability requirements and the Vietnamese Information Security Regulation QCVN 135:2024/BTTTT, confirming it as an optimal choice in terms of both performance and security.

Headquarters: The Vista, No. 4, Lane 15
Duy Tan Street,Cau Giay District, Hanoi

Website: http://mkvision.com
Email: contact@mkvision.com

Phone: (+84 24) 7100 6785
(+84 24) 3813 4646

Specification

Configuration	
SoC	Ambarella CV25
Processor	Quad-core ARM® Cortex® A53 1GHz
ROM memory	64GB eMMC
Memory	1GB DDR4
Processing performance	CVflow® Vision Processor 588MHz DNN Accelerated Engine
Smart features	AI Video Motion Detection, AI People Detection, AI Vehicle Detection, AI Face Detection, AI Face Recognition, AI License Plate Recognition, ...
Camera	
Sensor	Sony IMX-335 (1/2.7" Progressive CMOS)
FOV	Horizontal: 101(W) - 30(T) ° Vertical: 72(W) - 23(T)°,
Lens	Auto focus 2.8-12mm
Detection range 25 ppm	56m(W) - 240m(T)
Observation range 62.5 ppm	22,4m(W) - 96m(T)
Recognition range 125ppm	11,2m(W) - 48m(T)
Identification range 250 ppm	5,6m(W) - 24m(T)
Night mode	Automatic IR-cut filter Automatic switching
Minimum lighting	Infrared mode: 0 lux Infrared: ≥ 50m
Shutter speed	1 ~ 1/10.000 s
Video	
Resolution	5 Megapixels (2592H x 1944V)
Compression standard	H.265 / H.264 / Motion JPEG
Frame rate	5MP @30fps
Signal-to-Noise Ratio (SNR)	≥ 50dB
Exposure balance	HDR Engine Gen3, WDR 120dB
Adjust the image	Automatic White Balance (AWB), Backlight Compensation (BLC), Automatic Gain Control (AGC), Auto Iris, Auto Focus
Connect	
Connection ports	RJ45, 10/100Mbps
Supports protocols	ARP, PPPoE, IPv4/v6, ICMP, IGMP, QoS, TCP, UDP, DHCP, UPnP, SNMP, SMTP, RTP, RTSP, HTTP, HTTPS, FTP, NTP, DDNS
ONVIF®	Profile S, G, T, M
Certification	
ISO	ISO 9001:2015
Protection standard	IP67 - TCVN 4255:2025 (IEC 60529:2013) IK10 - TCVN 14227:2025 (IEC 62262:2021)
Electrical safety	TCVN 73126-1:2003 (IEC 60950-1:2001)
Information safety	NDAA, FIPS 140-2 Level 3
Overview	
Case	Metal
Power supply	12VDC; PoE IEEE 802.3af
Storage	64GB EMMC Flash
Operating conditions	-5 ~ +60°C/ humidity ≤ 95% RH
Storage conditions	-15 ~ +65°C/ humidity ≤ 95% RH
Dimensions	Ø 90x350 mm
Weight	1,5kg
Supported languages	English, Vietnamese
Certificate of origin	Made in Vietnam