

Automated Programming Verdict Classification from Submission Metadata: Comparing Machine Learning and Large Language Models in Competitive Programming

WENBIN HU, School of Computer Science, Xijing University, China

Context: Automated verdict classification is valuable for computing-education platforms, yet most approaches require source-code access or costly LLM inference. Competitive programming platforms return both a structured verdict and rich execution metadata for every submission, making it possible to ask: what verdict information is recoverable from metadata alone, and where does metadata become insufficient?

Objective: We systematically compare traditional ML and LLMs for metadata-based verdict classification to characterize the platform-encoding boundary—the point at which verdict information is deterministically recoverable from execution metadata alone.

Method: 13,360 Codeforces submissions across five verdict types. Processed metadata features extracted via the Codeforces REST API; raw submission payloads are retained locally and are not redistributed per platform Terms of Service—see Section 7 for ethics details. We evaluate Random Forest, Gradient Boosting, and Logistic Regression (seven metadata features) plus two LLM configurations (DeepSeek-V3 and Qwen2.5:3B, using five metadata fields as text input), under identical zero-shot protocols. Significance is assessed with McNemar's test with Bonferroni correction. For a fair ML–LLM comparison, we also report Gradient Boosting trained on the same five features available to the LLMs.

Results: Three verdict types are platform-encoded: CE (compile-time = 0 ms), TLE (execution time = limit), and MLE (memory = limit) are deterministically recoverable from execution metadata ($F1 \geq 0.89$) because these values are defined by the platform's own measurement thresholds. These three verdict types account for 18.4% of all submissions in our dataset, meaning automated classification can immediately deliver actionable feedback for these platform-encoded verdicts without requiring instructors' manual review, where GB achieves 95.02% overall accuracy (BAcc=0.89). The WA↔RE boundary is not separable from metadata alone (RE $F1 = 0.52$; all models fail here). DeepSeek-V3 reaches 76.65% on valid predictions (0.8% invalid) but collapses on RE ($F1 = 0.03$), while Qwen2.5:3B achieves only 35.50% (10.1% invalid). This comparison is asymmetric: ML models were trained on 10,688 labeled samples while LLMs received no task-specific training. Supervised ML outperforms DeepSeek-V3 zero-shot (76.65%) by 18.4 pp; a fair-feature comparison using GB trained on the same five features as the LLMs (92.0%) still outperforms DeepSeek-V3 by 15.4 pp.

Conclusions: We characterize the platform-encoding boundary for verdict classification from submission metadata. CE, TLE, and MLE are directly recoverable from platform thresholds ($F1 \geq 0.89$), while WA↔RE is not metadata-separable (RE $F1 = 0.52$). These findings delineate where metadata alone becomes insufficient, motivating source-code analysis as the natural next step, and provide empirical grounding for lightweight metadata-based verdict screening—classroom

Author's Contact Information: Wenbin Hu, School of Computer Science, Xijing University, Xi'an, China, wenbin.hu2026@outlook.com.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

© 2026 Copyright held by the owner/author(s). Publication rights licensed to ACM.

ACM 1946-6226/2026/7-ART1

<https://doi.org/10.1145/nnnnnnn.nnnnnnn>

validation required before drawing conclusions about learning impact. From a pedagogical perspective, the three platform-encoded verdicts (CE, TLE, MLE) are precisely those where immediate, specific feedback is most actionable; we hypothesize that a student receiving a CE verdict would benefit from syntax guidance rather than algorithmic review—a claim that remains to be validated in a classroom study. We release the dataset, pipeline, and deployment guidelines at <https://github.com/huwenbin123huwenbin/programming-error-classification>.

CCS Concepts: • **Social and professional topics** → **Computing education**.

Additional Key Words and Phrases: programming verdict classification, machine learning, large language models, competitive programming, Codeforces, metadata-based classification

ACM Reference Format:

Wenbin Hu. 2026. Automated Programming Verdict Classification from Submission Metadata: Comparing Machine Learning and Large Language Models in Competitive Programming. *ACM Trans. Comput. Educ.* 1, 1, Article 1 (July 2026), 30 pages. <https://doi.org/10.1145/nnnnnnn.nnnnnnn>

1 Introduction

Introductory programming courses report 30–40% dropout rates [10, 45], with debugging difficulty as a primary obstacle [42, 45]. Prior work analyzed compilation behavior [24] and scaled to large populations via Blackbox [12], revealing systematic debugging differences between student groups. Competitive programming platforms such as Codeforces and LeetCode provide structured metadata (execution time, memory consumption, precise error verdicts, test cases passed) for every submission, making them valuable environments for studying programming error patterns at scale.

A central methodological consideration motivates this work. Competitive programming platforms return structured verdicts for every submission, but the specific metadata available and the granularity of verdict taxonomies vary across platforms. For three of the five verdict types, the platform’s execution environment creates distinctive metadata signatures: a Compilation Error executes in near-zero time (the compiler does not run), a Time Limit Exceeded submission runs to the time limit, and a Memory Limit Exceeded submission exhausts the memory limit. These three verdict types therefore produce predictable metadata patterns that a classifier can learn: CE is associated with `time_consumed` ≈ 0 , TLE with `time_consumed` $\approx \text{limit}$, and MLE with `memory_consumed` $\approx \text{limit}$. Critically, this framing serves cross-platform applicability: if CE/TLE/MLE can be reliably classified from metadata, a single model trained on one platform’s data could transfer to another platform with a different verdict taxonomy, providing consistent error categorization without source-code access.

The question then becomes: *what verdict information is genuinely recoverable from metadata beyond these platform-encoded cases?* We define the **platform-encoding boundary** as the point at which verdict information is deterministically recoverable from submission metadata alone, without requiring source-code access. This framing serves cross-platform applicability: if a classifier trained on one platform’s data can classify CE, TLE, and MLE on another platform’s submissions, the approach generalizes beyond platform-specific code analysis. The WA $\leftrightarrow$ RE boundary represents the residual uncertainty where neither error type produces distinctive execution signatures, and where source-code analysis may become necessary. Our study is organized around this decomposition.

Caveat on population generalizability: Our dataset comes from competitive programmers on Codeforces (rating 800–3,500). Error patterns in CS1/CS2 student populations differ substantially: novices produce more syntax errors and fewer complex runtime errors, and the competitive programming context (time pressure, algorithmic challenge) may not

map directly to classroom learning goals. We evaluate generalizability via a skill-tier analysis (Section 4.7), but validation on student datasets (CS1QA[30], Blackbox) is needed before drawing conclusions for novice programming education contexts [4, 41]. Furthermore, we note that competitive programmers on Codeforces differ from novices in submission behavior: competitive submissions are made under time pressure with strategic test-case optimization, whereas students iteratively submit during learning. The skill-tier analysis in Section 4.7 partially addresses this by demonstrating consistent performance across programmer experience levels (novice: 96.0%, advanced: 88.5%); however, validation on student datasets remains necessary.

Prior work has studied LLM-based programming feedback [19, 39] and source-code analysis for programming error classification [18]; we review this literature in Section 2.

We investigate three research questions:

- **RQ1:** What are the prevalent programming error patterns in competitive programming submissions, and how do they distribute across error categories?
- **RQ2:** How do traditional ML classifiers perform on metadata-based verdict classification, which features are most predictive, and how stable are predictions?
- **RQ3:** Where does the platform-encoding boundary lie—can ML or LLMs distinguish Wrong Answer from Runtime Error—and what are the accuracy–cost tradeoffs?

Our contributions are:

- (1) **Controlled comparative study** of ML and LLM methods for verdict classification from submission metadata under identical evaluation protocols, spanning three ML models and two LLM configurations.
- (2) **Characterization of the platform-encoding boundary:** The $WA \leftrightarrow RE$ boundary is not metadata-separable ($RE\ F1 \leq 0.52$ for all models) because neither error type produces distinctive execution signatures; CE, TLE, and MLE are reliably recoverable ($F1 \geq 0.89$) from execution metadata, establishing cross-platform applicability of the metadata-based approach; source-code analysis is hypothesized (not demonstrated) as the next step for the $WA \leftrightarrow RE$ boundary.
- (3) **Quantitative deployment guidelines:** execution time and memory are the dominant predictors (8.8 pp accuracy drop when removed), with statistical analysis (McNemar tests, ablation, Gini importance) quantifying accuracy–cost–latency tradeoffs across six deployment contexts. Dataset and code: <https://github.com/huwenbin123huwenbin/programming-error-classification>.

Student-population disclaimer. Our dataset comes from competitive programmers (Codeforces rating 800–3,500), a population with substantially different error profiles from CS1/CS2 students. Prior work (Altadmri & Brown, 2015) reports 42 LLM (no task-specific training). This reflects realistic deployment conditions: ML requires labeled data and training time, while LLMs deploy out-of-the-box. We do not claim this comparison is symmetric; it quantifies the *labeled-data advantage* ML models carry in practice (Section 4.6). Future work should compare fine-tuned LLMs, few-shot LLMs, and active-learning ML under controlled data budgets.

2 Related Work

2.1 Programming Error Analysis

The study of programming errors has a history spanning over four decades in computing education research [46]. This psychological perspective on programming pedagogy highlights

the cognitive demands debugging places on novices [46]. McCauley et al. [32] conducted a comprehensive review of the novice programmer literature, identifying syntax errors, logical errors, and conceptual misunderstandings as the three dominant error categories. Their meta-analysis revealed that novices spend approximately 25% of their programming time on debugging activities, yet novice debugging effectiveness improves only modestly over a semester of instruction. This finding underscores the need for automated tools that can accelerate the development of debugging proficiency. Cognitive Load Theory [43] posits that debugging simultaneously taxes working memory across error diagnosis, code comprehension, and solution planning, creating intrinsic overload that constrains novice self-correction [28]. Jadud

Jadud [24] pioneered compilation event analysis using the BlueJ IDE, establishing compilation behavior as a data source for educational mining. The Blackbox project [12] scaled this to 200,000+ users, revealing that compilation errors cluster early in programming episodes and that high-performing students compile more strategically.

Large-scale analyses [1, 31] established that runtime errors persist across cohorts and resist standard interventions [4], motivating automated diagnostic tools [7].

Spohrer and Soloway [42] provided an influential early theoretical framework distinguishing between plan composition errors (faulty algorithm design or implementation strategy) and plan comprehension errors (misunderstanding of specific language constructs). Their controlled studies with novice LISP programmers demonstrated that many seemingly simple errors have deeper cognitive roots than syntax misunderstanding, indicating that effective automated feedback must identify the underlying error pattern. Students' self-efficacy beliefs compound this challenge. Structured self-evaluation interventions in CS1 have been shown to improve both self-efficacy and programming performance. Gorson and O'Rourke [21] found that CS1 students systematically overestimate their error severity, often attributing correct execution to luck rather than understanding—a metacognitive gap that automated tools could help correct.

Busjahn et al. [13] further revealed through eye-tracking studies that even expert programmers do not process code linearly, complicating error diagnosis and self-correction across all skill levels.

2.2 Machine Learning in Computing Education

Machine learning has been increasingly applied to computing education challenges over the past fifteen years. Educational data mining has identified programming education as a key application domain [5, 40], with prediction tasks dominating the literature. Metadata-based approaches achieve strong performance [4, 24], while deep learning enables knowledge tracing in code-based learning [37].

Behavioral features from early assignments—compilation frequency, error diversity, time-on-task—can predict course outcomes [12, 24], enabling early intervention through instructor-facing dashboards [25, 44].

Robust behavioral modeling distinguishes productive from unproductive debugging [17], aligning with cognitive load principles [43]. Analyzing interaction sequences rather than aggregated statistics has been shown to improve predictive accuracy for programming behavior.

Prior work on verdict classification from submission data has shown that metadata features can achieve strong performance when combined with source-code analysis. Yet the computational cost of extracting code-level features (ASTs, cyclomatic complexity, token diversity) limits scalability for platform-level deployment. Our approach demonstrates that

metadata-only features—without source code access—can achieve competitive accuracy, offering a practical alternative for large-scale deployment. Allamanis et al. [2] demonstrated that graph-based representations of program structure capture semantically meaningful features for code-related prediction tasks, motivating the incorporation of such learned representations into verdict classification.

Alnahhas and Mourtada [3] predicted the performance of competitive programming contestants using account-level metadata (rating, participation frequency, problem-difficulty distribution), demonstrating that non-code features carry substantial signal for programming behavior analysis. While their focus was on performance prediction rather than verdict classification, their work demonstrates the continued relevance of simple, interpretable models in educational contexts.

Automated program repair (APR) methods [35] address similar diagnostic challenges at the source-code level, automatically localizing bugs and suggesting fixes. While effective, APR requires full code access and substantial computational resources, limiting deployment at platform scale. Our metadata-based approach complements APR by providing lightweight error-type inference without code access, serving as a screening layer to determine when deeper source-code analysis is warranted.

2.3 Large Language Models in Programming

Large language models have rapidly transformed expectations for automated code understanding and generation [8, 9]. Barke et al. demonstrated that programmer interaction with code-generating models differs fundamentally from traditional IDE usage. Finnie-Ansley et al. found that GPT-3 answered only 56% of CS1 examination questions correctly but produced plausible yet often incorrect explanations, raising over-reliance concerns. Sarsa et al. demonstrated that LLM-based feedback generation achieves expert-level quality [41], and Leinonen et al. showed that LLM-enhanced error messages measurably improve novice self-correction rates. Padiyar et al. showed that prompt engineering substantially improves LLM accuracy on competitive programming tasks, motivating controlled evaluation protocols.

Feng et al. showed that CodeBERT achieves state-of-the-art performance on code-level benchmarks including defect detection, but is primarily evaluated on source code features; its effectiveness on submission metadata alone remains unclear. Messeri et al. reported significant performance degradation on error identification compared to code generation, indicating that current LLMs are better suited as code generators than error diagnosticians [38]. Leerentveld et al. found that LLM-generated programming error messages were “ineffective in practice” in a controlled classroom study, aligning with our finding that RE remains the most challenging category. Lee et al. found that LLM explanations of compiler errors often contained hallucinated details for runtime errors, directly relevant to our metadata-only setting where Qwen2.5:3B also struggled with RE classification.

Recent work has explored hybrid approaches combining ML classification with LLM explanation generation [19, 26], but these have been evaluated primarily on synthetic datasets. Our work extends this line by providing the first comprehensive ML–LLM comparison on real-world competitive programming data. Keuning et al. provide a systematic review of AI for programming education [27].

2.4 Metadata-Based Classification in Educational Contexts

While source-code analysis (ASTs, token sequences, code embeddings) has received considerable attention in computing education research, a parallel line of work has demonstrated that *submission metadata alone* can achieve strong predictive performance for a range of

educational outcomes. Jadud [24] showed that compilation frequency and error persistence patterns extracted from IDE interaction logs can predict course outcomes with moderate accuracy ($R^2 \approx 0.3$). The Blackbox project [12] scaled this approach to over 200,000 students worldwide, demonstrating that behavioral metadata (compilation sequences, time-on-task, submission frequency) constitute a rich and continuously available signal for educational data mining.

Prior work has shown that features derived from early programming submissions—including compilation frequency, error diversity, and time-on-task—can predict final course grades using only metadata, without accessing student source code [4]. Altadmri and Brown [4] further classified 37M Java submissions, finding that approximately 42% of novice errors are compile-time errors, with runtime errors and wrong-answer errors accounting for most of the remainder. This distribution differs substantially from competitive programming, motivating cross-population validation of automated classification tools. [12, 24]. This established that *behavioral signals* from the first four weeks of a semester are sufficient to identify students at risk of failure, enabling early intervention without privacy-invasive code monitoring.

In the context of competitive programming platforms, Alnahhas and Mourtada [3] used account-level metadata (contestant rating, participation frequency, problem difficulty distribution) to predict overall competitive programming performance, reporting 78% accuracy using only non-code features. Their findings indicate that metadata alone carries substantial signal for programming behavior analysis, motivating our focus on metadata-based verdict classification.

The advantages of metadata-based classification are both practical and privacy-preserving: (1) no source code access is required, avoiding potential concerns about student code being processed by third-party APIs; (2) computational cost is orders of magnitude lower than code-based approaches (no tokenization, AST parsing, or GPU inference); and (3) deployment at platform scale (millions of daily submissions) becomes feasible with modest computational resources. A central open question is whether metadata alone can achieve competitive accuracy against code-based approaches—a question our work is, to our knowledge, the first to systematically address for the verdict classification task.

Contribution boundary: Prior work on metadata-based prediction has focused primarily on *grade prediction* and *at-risk identification*. We are not aware of any prior study that has applied metadata-based classification to the more granular task of *verdict classification* across five error categories, nor has any work systematically compared metadata-based ML against LLM-based approaches on the same task.

No prior study has systematically compared traditional ML and LLM approaches on the same programming verdict classification task using the same dataset and evaluation protocol. We identify three specific gaps:

- (1) **Metadata-based classification:** Existing verdict classification studies focus on source code analysis, neglecting the rich diagnostic signals in submission metadata (execution time, memory usage, test cases passed).
- (2) **ML–LLM comparison:** No work systematically compares traditional ML (RF, GB, LR) and two LLM configurations (DeepSeek-V3, Qwen2.5:3B) on identical verdict classification tasks.
- (3) **Feature importance quantification:** While execution time has been hypothesized as important, no study quantifies feature importance through systematic ablation with statistical significance testing.

Our work addresses all three gaps by providing the first comprehensive comparison of ML and LLM methods for metadata-based verdict classification, with systematic feature ablation and McNemar significance testing.

3 Methodology

3.1 Dataset Collection

We collected submission data from Codeforces, a competitive programming platform widely used for algorithmic training and education [34, 48] (<https://codeforces.com/>) via the official public REST API. The Codeforces platform was selected for three reasons: (1) it provides structured, rich metadata for every submission including precise execution time, memory usage, and error verdict; (2) it represents an ecologically valid competitive programming environment with high participant engagement; and (3) it has a large, diverse problem set covering a wide range of algorithmic domains and difficulty levels.

Submissions were retrieved from competitive programmers with Codeforces ratings spanning 800 to 3500 (corresponding to Newbie through Legendary Grandmaster levels). This range was deliberately chosen to represent proficient programmers who produce a variety of error types and for whom submission metadata is meaningfully differentiated. Data collection was completed in June 2026, covering submissions from November 2020 to June 2026, providing approximately 5.5 years of programming activity.

Collection Pipeline. The data collection and preparation proceeded as follows (details in Data Cleaning below):

- (1) Raw collection: error submissions retrieved from the Codeforces public REST API (Nov 2020–Jun 2026).
- (2) Filtering: submissions with missing execution time, memory, or verdict fields were removed.
- (3) Deduplication: duplicate entries were removed and only the final submission per (user, problem) pair was retained to prevent train–test leakage.
- (4) Final dataset: **13,360** error samples from competitive programmers across hundreds of Codeforces contests

Data Cleaning. Data cleaning was performed in three stages. First, submissions with incomplete metadata (missing execution time, memory, or verdict fields) were removed. Second, duplicate entries (identical submission timestamps and verdicts) were deduplicated. Third, to prevent data leakage between training and test sets, only the final submission per (user, problem) pair was retained—this ensures that no two submissions in the dataset are from the same user solving the same problem. This does not prevent user-level leakage: a given user can appear in both training and test sets on different problems, potentially allowing the model to exploit user-specific patterns. The `user_success_rate` feature (19.4% Gini importance) is the primary channel for this effect. Stratified sampling ensures no single user dominates any fold (maximum 0.8% of any fold). We additionally re-ran McNemar tests on a user-level deduplicated subset ($n=3,241$ unique user-problem pairs), finding consistent significance patterns (GB vs. DeepSeek: $p < 0.001$). Full results are in the Supplementary Materials.

Caveat on `user_success_rate`. This feature captures competitive programmers’ historical success rates across all submissions to a given platform. Because WA and RE submissions are classified as unsuccessful, high-WA or high-RE users will have systematically lower

success rates. This creates a conditional dependency: `user_success_rate` encodes information partially redundant with the target verdict. We retain it for three reasons: (1) ablation confirms it provides 3.6 pp accuracy (complementary to execution-time features); (2) it represents a distinct dimension of programmer proficiency not reducible to per-submission metadata; and (3) in formative assessment settings, historical performance is a legitimate proxy for instructor judgment of student progress. Furthermore, `user_success_rate` is a historical aggregate unavailable for new students in early-semester deployment; its predictive power may not transfer to populations with no prior submission history. Future work should examine whether this feature generalizes across different student populations or introduces demographic biases.

The final dataset comprises 13,360 error submissions from competitive programmers across hundreds of Codeforces contests. Table 1 summarizes the error type distribution. The language distribution is predominantly C++ (C++23 41.1%, C++17 22.0%, C++20 18.6%), with Python (7.1%), Java (5.5%), and other languages representing smaller fractions. This linguistic skew reflects the competitive programming community’s preference for C++ due to its performance advantages in time-constrained problems.




Fig. 1. Feature correlation matrix showing relationships between submission metadata. Time and memory show moderate positive correlation ($r=0.32$), while language choice weakly correlates with memory consumption ($r=0.17$), reflecting language-specific memory management patterns.

Table 1. Error type distribution in the 13,360-sample Codeforces dataset. Note: CE, TLE, and MLE produce near-deterministic metadata signatures (compile-time ≈ 0 , execution time $\approx$ limit, memory $\approx$ limit), while WA and RE do not. This asymmetry motivates the platform-encoding boundary analysis in Section 5.1. Note: CE, TLE, and MLE produce near-deterministic metadata signatures (compile-time = 0, execution time *approx* limit, memory *approx* limit), while WA and RE do not. This asymmetry motivates the platform-encoding boundary analysis in Section refsec:platform-encoding. [†]MLE and TLE mean execution times reflect platform threshold effects: MLE mean (2,048 ms) approximates the memory-limit boundary, and TLE mean (2,000 ms) equals the problem-specific time limit; these are platform-encoding boundary artifacts (see Section 5.1), not run-time execution signatures.

Error Type	Count	Percentage	Avg. Exec. Time (ms)
Wrong Answer (WA)	10,234	76.6%	46
Time Limit Exceeded (TLE)	1,288	9.6%	2,000
Runtime Error (RE)	656	4.9%	187
Compilation Error (CE)	980	7.3%	0
Memory Limit Exceeded (MLE) [†]	202	1.5%	2,048
Total	13,360	100%	—




Fig. 2. Error type distribution across problem difficulty levels. Novice problems (rating ≤ 800) show highest WA rates (79.0%), while Expert problems (>2000) exhibit more diverse errors: WA drops to 41.0%, with RE (26.5%), TLE (14.3%), and MLE (11.7%) substantially higher, reflecting the increasing algorithmic and memory complexity of harder problems.

3.2 Feature Engineering

Seven features were extracted from each submission, spanning problem characteristics, execution metrics, submission behavior, and user history:

- (1) **problem_rating**: integer difficulty rating (800–3500), indicating the algorithmic complexity of the problem.
- (2) **language**: programming language used (C++/Python/Java), capturing potential language-specific error patterns.
- (3) **time_consumed_ms**: execution time in milliseconds, capturing runtime performance characteristics.
- (4) **memory_kb**: memory consumption in kilobytes, reflecting the program’s memory footprint.
- (5) **problem_type**: problem index prefix (e.g., A/B/C/D), encoding structural information about the contest problem.
- (6) **hour**: submission hour within the contest window, capturing temporal submission behavior.
- (7) **user_success_rate**: historical success rate of the submitting user, reflecting individual competitive programming experience.

These features were selected based on the following criteria: availability in the Codeforces API without requiring source code access, coverage of different aspects of the programming process (problem difficulty, execution behavior, and partial correctness), and prior evidence of predictive relevance from educational data mining literature.

Theoretical Framework: Feedback and Self-Efficacy. This study is grounded in two complementary theories from computing education research. First, Hattie and Timperley’s model of effective feedback [22] identifies four levels of feedback: task level, process level, self-regulation level, and self level. Accurate error classification enables *task-level feedback* (correcting specific misconceptions) and *process-level feedback* (addressing algorithmic inefficiencies), which Hattie ranks as the most impactful for learning. Automated formative feedback at the task level has been shown to consistently improve student learning outcomes across multiple educational contexts. Feedback that identifies a runtime error versus a logic error is more actionable than a generic “incorrect output” message because it narrows the student’s search space from the full program to a specific error class.

Second, Bandura’s self-efficacy theory [6] posits that accurate performance feedback is a primary driver of self-efficacy beliefs. When students receive vague or misleading error messages, they cannot form accurate self-assessments, leading to frustration and disengagement. An automated system that correctly distinguishes a WA from a RE enables the student to attribute the failure to a specific root cause (logic error vs. runtime hazard), which supports accurate self-efficacy calibration and sustained engagement.

The present study operationalizes these theories by asking: *How much error-type information is recoverable from submission metadata alone, without source-code access?* The answer determines the granularity of feedback that can be delivered automatically at scale. We test two specific theoretical predictions: (1) Hattie and Timperley’s model predicts that *task-level feedback* (precise error class) is more actionable than *process-level feedback* (general guidance); our finding that WA $\leftrightarrow$ RE is not metadata-separable confirms that the finest-grained automated feedback (distinguishing logic errors from runtime failures) might require source-code analysis, consistent with their ranking of feedback levels. (2) Bandura’s theory predicts that accurate self-assessment requires attributing failure to a specific cause;

our results show that metadata cannot support this attribution for RE versus WA, suggesting that students will receive vague feedback that impedes self-efficacy calibration—a hypothesis requiring longitudinal validation. These theoretical predictions are *consistent with* our empirical findings; causal validation would require a controlled study measuring student self-efficacy and learning outcomes, which is beyond the scope of this work.

Feature Selection Rationale. The features were selected based on: (1) availability in online judge platform APIs without source code access; (2) theoretical relevance—each captures a distinct aspect (difficulty, execution behavior, partial correctness); and (3) complementarity—features span problem-level, submission-level, and runtime-level characteristics.

Numeric features were z-score standardized; categorical features (language) were one-hot encoded. No a priori feature selection was applied to preserve the ablation study’s validity. Pairwise Pearson correlations confirmed no multicollinearity among numeric features (max $\rho = 0.31$ between time and memory, well below the $\rho = 0.7$ threshold).

passed_test_count and verdict collinearity: The passed_test_count feature exhibits partial collinearity with certain verdicts. Point-biserial correlations reveal: CE ($r = -0.107$, $p < 10^{-35}$), where 100% of CE submissions have passed_test_count = 0 (compilation prevents execution); TLE ($r = 0.322$, $p < 10^{-300}$) and MLE ($r = 0.206$, $p < 10^{-120}$), where submissions hitting limits tend to pass test cases before failing. WA shows moderate negative correlation ($r = -0.233$, $p < 10^{-160}$), but 69.7% of WA submissions have passed_test_count > 0 (mean = 1.31), confirming this feature does *not* deterministically encode WA. A separate check (passed_test_count is provided to the LLMs but not to the ML models) shows adding then removing it yields only a 0.5 pp accuracy drop, far less than time_consumed_ms (8.8 pp), confirming the model does not rely on it as primary signal.

3.3 Sample Size Justification

For the primary research question (detecting a 15 pp difference between GB at 95.02% and DeepSeek-V3 at 76.65% on 2,672 test samples), post-hoc a retrospective power analysis confirms sufficient statistical power: the minimum detectable effect (MDE) with $n=2,672$ at $\alpha = 0.05$ is approximately 2.5 pp, far smaller than the 18.4 pp gap observed between GB and DeepSeek-V3, and 12.4 pp gap between GB and RF—far smaller than the 18.4 pp gap we report. Bootstrap validation yields 95% CI [94.2%, 95.9%] for GB, excluding random chance. Table 2 shows accuracy stability across training set sizes, confirming sample adequacy.

Table 2. Sensitivity analysis: Random Forest balanced accuracy (BAcc) and accuracy across training set sizes (test set $n = 2,672$; values from a single-seed run; the 10,688 training point corresponds to the full training split and its test accuracy (94.24%) matches the RF result in Table 3)

N (Training)	Test Accuracy	Drop from Full
400	86.26%	−7.98 pp
600	87.95%	−6.29 pp
800	88.06%	−6.18 pp
1,600	87.61%	−6.63 pp
2,800	88.92%	−5.32 pp
10,688	94.24%	—

3.4 Experimental Models

We selected three traditional ML classifiers and two LLM-based approaches representing different paradigms in automated code analysis. The selection was designed to span the spectrum from simple, interpretable models (LR) to ensemble methods (RF, GB), enabling a comprehensive comparison between traditional ML and LLM approaches.

Traditional ML Classifiers.

- **Random Forest (RF):** An ensemble of 100 decision trees using Gini impurity for splitting [11], with unlimited max depth, minimum samples split of 2, and minimum samples leaf of 1. Random Forest was selected for its well-documented ability to handle mixed-type data (numeric and categorical), capture non-linear feature interactions, and provide inherent feature importance measures.
- **Gradient Boosting (GB):** An ensemble of 100 staged decision trees using gradient descent optimization [20], with max depth of 3 (shallow trees to prevent overfitting), learning rate of 0.1, and subsample of 1.0. GB was selected as a complementary ensemble method that typically performs well on structured educational data.
- **Logistic Regression (LR):** Multinomial logistic regression with L2 regularization [23], using the L-BFGS solver and maximum 1,000 iterations. LR was included as an interpretable linear baseline; its coefficients can be directly inspected to understand the direction and magnitude of each feature's influence on each error class.

All traditional ML models were implemented using scikit-learn 1.3.0 [36] with default parameters unless otherwise specified. Hyperparameter tuning was initially explored using grid search with 3-fold cross-validation on a 10% held-out validation set, but the performance gains were marginal (< 1% for tuned vs. default RF), so default parameters were retained to mitigate overfitting and improve reproducibility. The random state was set to 42 for reproducibility. All classifiers used default class-weight=None (no SMOTE or cost-sensitive reweighting) with stratified splitting. This means the model is not reweighted toward minority classes; this is a deliberate design choice prioritizing aggregate accuracy over balanced class performance. Future work should evaluate class-weight=balanced or SMOTE to improve RE F1 at the cost of aggregate accuracy.

LLM-Based Approaches. Two LLM configurations were evaluated under an identical zero-shot protocol, both receiving the same five metadata fields (problem_rating, language, time_consumed_ms, memory_kb, passed_test_count) and asked to output a single verdict acronym (WA/TLE/RE/CE/MLE) in JSON:

- **DeepSeek-V3 [15] (online, evaluated):** A frontier online model accessed via the DeepSeek API, representing a strong, general-purpose LLM available without local compute.
- **Qwen2.5:3B (local, evaluated):** A 3-billion-parameter model run on-device via Ollama v0.30.7 at no API cost, representing a small local LLM suitable for privacy-sensitive educational deployment.

Inference used temperature=0 and grammar-constrained JSON output to ensure parsable responses; both models were evaluated on the same 2,672-sample test set as the ML models.

3.5 Evaluation Protocol

All experiments followed a consistent evaluation protocol to ensure fair comparison between ML and LLM approaches. The dataset of 13,360 samples was partitioned using stratified

80/20 train-test splitting, yielding 10,688 training samples and 2,672 test samples, preserving class proportions across both sets.

For traditional ML models, five-fold stratified cross-validation was performed on the training set (10,688 training per fold) to assess stability, and final test-set accuracy was reported. For LLM-based methods, the test set of 2,672 samples was classified directly using zero-shot prompting without any fine-tuning or few-shot demonstrations. Unlike ML models, LLMs do not have a training phase in our protocol; we therefore do not apply cross-validation to LLM results. A single fixed test-set evaluation is reported for each LLM configuration, consistent with standard LLM benchmarking. Multiple random-seed repetitions would provide variance estimates; DeepSeek-V3 was evaluated with temperature=0 (deterministic API), so within-run variance is negligible and cross-run variance reflects only model-level non-determinism, which is minimal under this configuration. Future work should report confidence intervals from multiple evaluation runs or use Bayesian methods for LLM performance estimation. Both DeepSeek-V3 (API) and Qwen2.5:3B (local Ollama) were evaluated under the identical protocol.

Statistical significance of pairwise model comparisons was assessed using McNemar's test [33] ($\alpha = 0.05$), a non-parametric test for paired nominal data appropriate for comparing classifiers on the same test set. Feature ablation was conducted by systematically removing each feature, retraining GB on the remaining six features, and measuring the accuracy drop on the test set. Feature ablation was conducted by systematically removing each feature, retraining GB on the remaining six features, and measuring the accuracy drop on the test set. Seven features were ablated; no multiple-comparison correction was applied to the ablation study. All reported ablation p-values ($p < 0.001$) are reported as-is. The Bonferroni-corrected threshold ($\alpha' = 0.05/7 \approx 0.007$) is noted: all ablation p-values satisfy this threshold. Ablation results are exploratory; the primary multiple-comparison correction is applied to the 10 pairwise model comparisons in Table 7 (Bonferroni $\alpha' = 0.005$).

Classification performance is reported as overall accuracy, per-class precision, recall, and F1-score. Confusion matrices are provided for the best-performing model to reveal class-wise error patterns. Confidence intervals (95%) for LLM performance are computed using the Wilson score interval for binomial proportions.

4 Results

4.1 Experimental Setup

All experiments were conducted on a MacBook Pro (macOS 13.7, Intel i7, 16GB RAM) using Python 3.9.6 with scikit-learn 1.3.0. Random seeds were fixed to 42 for reproducibility. Hyperparameters were set to defaults (RF: 100 trees; GB: 100 trees, depth=3, $\eta=0.1$; LR: L2 regularization, L-BFGS solver) after grid search yielded $< 1\%$ improvement.

LLM experiments used two configurations: DeepSeek-V3 via the DeepSeek API and Qwen2.5:3B via local Ollama (temperature=0, max_tokens=50). Both were evaluated zero-shot on the same stratified 80/20 test set (2,672 samples); no cross-validation was applied to the LLMs (inference-only). Statistical significance was assessed via McNemar's test ($\alpha = 0.05$) with 95% confidence intervals computed via Wilson score. Per-class performance metrics (precision, recall, per-class F1) with Wilson score confidence intervals are reported in the Supplementary Materials. Balanced Accuracy is reported alongside overall accuracy to address class-imbalance effects. All code and processed analysis scripts are publicly available at: <https://github.com/huwenbin123huwenbin/programming-error-classification>

4.2 Traditional ML Performance

Table 3 presents the performance of the three traditional ML classifiers on both the held-out test set and via 5-fold cross-validation.

Table 3. Traditional ML model performance on 13,360-sample dataset (5-fold stratified cross-validation)

Model	Test Acc	CV Mean ($\pm$ SD)	Macro F1	Train (s)	Infer (ms)
Random Forest	94.24%	94.39% (± 0.65)	0.8543	—	—
Gradient Boosting	95.02%	95.13% (± 0.39)	0.8711	—	—
Logistic Regression	73.91%	74.31% (± 3.26)	0.6738	—	—

Note: Logistic Regression shows $5\times$ higher CV variance (\$3.26pp) than RF (\$0.65 pp) or GB (\$0.39pp); included as a baseline for interpretability, not as a preferred method.

Note: 80/20 stratified split: 10,688 training, 2,672 test. 5-fold CV on training set. Random state fixed at 42.

Balanced Accuracy (BAcc): GB=0.89, RF=0.87, LR=0.62 (average of per-class recall, reported in Supplementary Materials).

The Gradient Boosting achieves balanced accuracy (BAcc) of 0.89 and 95.02% overall accuracy, representing an 12.4 pp lift in BAcc over the majority-class baseline (0.89 vs. 0.20) (and 15.4 pp for the fair 5-feature GB variant) over the majority-class baseline (76.6%); overall accuracy is dominated by WA (76.6% of test set, F1=0.97), while RE (4.9% of test set) has F1=0.52 consistent with three verdicts being near-deterministically encoded in execution metrics while the WA $\leftrightarrow$ RE boundary is not metadata-separable. The perfect ROC-AUC for MLE/TLE (1.000) reflects this deterministic relationship; the critical challenge lies in the WA and RE boundary (AUC 0.778), where execution metadata provides only partial signal.

The 21 pp gap between ensemble methods and linear regression confirms that error classification benefits from models capturing non-linear feature interactions. Prior work [4, 31] established that runtime errors are persistently difficult to classify, consistent with our findings.

Class-Wise Analysis (Random Forest). To better understand the strengths and limitations of the best-performing model, we conducted a detailed class-wise analysis of Random Forest's predictions.

Confusion Matrix Analysis (Random Forest). Table 4 presents the confusion matrix for Random Forest on the test set of 2,672 samples. Figure 4 shows the corresponding feature importance profile.

The confusion matrix reveals a clear performance gradient across error

categories. Compilation Error (CE) achieves strong classification accuracy (F1 = 0.89) because CE submissions consistently exhibit zero execution time, forming a perfectly separable region in the feature space. Wrong Answer (WA) achieves an F1 score of 0.97 due to its dominance in the dataset (76.6%) and distinct metadata signature—WA submissions typically execute within normal time bounds but fail on correctness tests. Time Limit Exceeded (TLE) is well-classified (F1 = 0.98), as TLE submissions systematically exhibit execution times at or near the problem's time limit.

The most challenging category is Runtime Error (F1 = 0.52). This substantially exceeds the random baseline for a five-class problem (expected F1 $\approx$ 0.02 per class), indicating that

Table 4. Random Forest confusion matrix and class-wise F1 (test set, $n = 2,672$)

Actual	Predicted					F1
	CE	MLE	RE	TLE	WA	
CE (196)	185	0	2	0	9	0.89
MLE (40)	0	36	2	2	0	0.91
RE (131)	5	2	58	1	65	0.52
TLE (258)	0	0	0	258	0	0.98
WA (2047)	29	1	31	5	1981	0.97




Fig. 3. Class-wise F1 scores (Random Forest, test set $n = 2,672$). Four error types—Compilation Error, Memory Limit Exceeded, Time Limit Exceeded, and Wrong Answer—achieve strong F1 (≥ 0.89), whereas Runtime Error (RE) is markedly weaker ($F1 = 0.52$). This asymmetry reflects the *platform-encoding boundary*: CE/TLE/MLE are cleanly separable by execution time and memory, while RE submissions share no distinctive metadata signature.

metadata provides predictive signal for RE. Of 131 actual RE samples, 58 were correctly identified (44.3%) while 65 were misclassified as WA (49.6%). The $WA \leftrightarrow RE$ boundary thus accounts for the majority of residual errors. This stems from the heterogeneous nature of RE: the Codeforces RE verdict encompasses segmentation faults, division by zero, assertion failures, and signal termination, each producing distinct metadata signatures that overlap with WA behavior. For pedagogical purposes, where distinguishing logic errors (WA) from runtime failures (RE) is essential, the 49.6% $RE \rightarrow WA$ error rate indicates that metadata-only classification is insufficient—this is the “platform-encoding boundary” for verdict classification.

Memory Limit Exceeded (MLE, $F1 = 0.91$) benefits from distinct memory consumption signatures that clearly separate it from other categories in the test set.

4.3 Feature Importance

Figure 4 presents the Gini importance scores computed from the Random Forest model, which quantify each feature’s contribution to the model’s predictive accuracy across all decision trees.




Fig. 4. Feature importance (Gini importance) from the Random Forest model (7 features). Execution time (`time_consumed_ms`) shows the highest importance (42.5%), followed by memory consumption (24.2%), user success rate (19.4%), problem difficulty (5.7%), programming language (5.0%), problem type (3.2%), and submission hour (0.0%).

Feature importance reveals a pronounced hierarchy: execution time (42.5%), memory consumption (24.2%), user success rate (19.4%), problem difficulty (5.7%), language (5.0%), and problem type (3.2%). Submission hour contributes negligibly. The Gini ranking aligns with ablation results: `time_consumed_ms` causes an 8.8pp accuracy drop when removed, confirming its dominant role. Problem difficulty and language provide modest discriminatory power.

Submission hour (`hour`, 0.0%) contributes the least importance, which is expected because submission timing within a contest window carries little information about verdict type.

4.4 Error Analysis

The confusion matrix (Table 4) reveals a clear performance gradient: CE and MLE achieve strong classification ($F1=0.89$ and 0.91) due to distinct metadata signatures (zero execution time and high memory consumption, respectively). WA achieves $F1=0.97$, while TLE is well-classified ($F1=0.98$) due to execution times at the problem’s time limit. RE ($F1=0.52$) is the most challenging category, attributable to its heterogeneous nature (segfault, division by zero, etc.) that metadata alone cannot distinguish. Qualitative analysis of 20 misclassified cases identified three main failure modes: (1) RE with partial output misclassified as WA (40%), (2) borderline TLE/WA cases (30%), and (3) outlier problem ratings (20%). These findings motivate incorporating source-code-level features for improved RE classification.

4.5 Ablation Study

To rigorously quantify each feature’s contribution and assess the model’s robustness, we conducted a systematic feature ablation study. Table 4.5 reports uncorrected ablation p-values; the Holm-Bonferroni correction (Section ??) applies to the primary ML–LLM McNemar comparisons. Each of the seven features was removed individually from the feature set, the Gradient Boosting model was retrained on the remaining six features, and performance was measured on the same held-out test set of 2,672 samples.

Table 5. Ablation study: accuracy drop when removing each feature (Gradient Boosting, test set $n = 2,672$)

). Seven ablated comparisons; Bonferroni-corrected threshold $\alpha' = 0.05/7 \approx 0.007$. All reported p-values (< 0.001) satisfy α' . Ablation p-values are uncorrected; this note is for reference only. Primary multiple-comparison correction: Table 7 ($\alpha' = 0.005$).

Removed Feature	Accuracy (%)	Drop (pp)	p-value
None (full model)	95.02	—	—
problem_rating	94.95	0.10	$< 0.001^{***}$
language_encoded	94.76	0.30	$< 0.001^{***}$
time_consumed_ms	86.19	8.80	$< 0.001^{***}$
memory_kb	93.64	1.40	$< 0.001^{***}$
problem_type	94.87	0.10	$< 0.001^{***}$
hour	95.02	0.00	n.s.
user_success_rate	91.39	3.60	$< 0.001^{***}$

Execution time is the dominant predictor (8.8pp accuracy drop when removed): this reflects that CE submissions produce near-zero execution times, while TLE and MLE submissions cluster near platform threshold boundaries. The WA↔RE boundary remains indistinguishable from execution metadata alone, as neither error type produces distinctive runtime signatures—this is where source-code analysis might be required, a hypothesis to be tested in future work. Note: ablation accuracy drops are point estimates without confidence intervals; bootstrap CI estimation would clarify whether feature contributions are statistically distinguishable from each other. We retain all features in the final model because they provide complementary information that supports robust classification.; bootstrap CI estimation would clarify whether feature contributions are statistically distinguishable from each other.




Fig. 5. ROC curves for Random Forest (One-vs-Rest, test set $n = 2,672$). AUC values: CE = 0.984, MLE = 1.000, TLE = 1.000, WA = 0.935, RE = 0.778




Fig. 6. Precision-Recall curves for Random Forest (One-vs-Rest, test set $n = 2,672$)

4.6 LLM Performance Comparison

Table 4.6 presents the performance of LLM-based approaches on the same test set of 2,672 samples, reporting our own experiments with two LLM configurations under an identical zero-shot protocol: a strong online model (DeepSeek-V3, accessed via API) and a small local model (Qwen2.5:3B, run on-device via Ollama). Both receive the same five metadata fields as the ML models. (We deliberately omit prior-work LLM accuracy figures whose underlying error-classification setup is not publicly reproducible.)

Table 6. Model performance: ML baselines vs. two LLM configurations (test set $n = 2,672$)

). ML per-class F1 (RF/GB): WA ≥ 0.97 , TLE ≥ 0.98 , CE ≥ 0.89 , MLE ≥ 0.91 , RE ≤ 0.52 ; balanced accuracy: GB=0.89, RF=0.87. DeepSeek-V3: Macro F1=0.5447; Qwen2.5:3B: Macro F1=0.2311 (see Table 8).

Model	Test Acc	95% CI	Macro F1	Cost/1k
Random Forest (ML)	94.24%	[93.3, 95.0]	0.8543	\$0.01
Gradient Boosting (ML)	95.02%	[94.2, 95.9]	0.8711	\$0.01
Logistic Regression (ML)	73.91%	[72.4, 75.4]	0.6738	\$0.01
<i>LLM — Our Experiments (test set, $n=2,672$)</i>				
DeepSeek-V3 Zero-Shot (online, all)	76.05%	[74.3, 77.8]	—	\$0.10
DeepSeek-V3 Zero-Shot (online, valid)	76.65%	[75.0, 78.2]	0.5447	\$0.10
Qwen2.5:3B Zero-Shot (local, all)	31.92%	[30.0, 33.9]	—	\$0.00
Qwen2.5:3B Zero-Shot (local, valid)	35.50%	[33.6, 37.4]	0.2311	\$0.00
*ML models (7-feature): trained on 10,688 samples, evaluated on 2,672 test.				
[†] LLMs use 5 metadata features. For a fair ML–LLM McNemar comparison (Table 7) we use a 5-feature GB variant (92.0%).				
[‡] DeepSeek-V3: 21/2,672 (0.8%) invalid; Qwen2.5:3B: 269/2,672 (10.1%) UNKNOWN (model did not return a valid verdict).				

Key Finding 1: Supervised ML models substantially outperform zero-shot LLM configurations, but the gap varies sharply by LLM capability.

On the asymmetry of the ML–LLM comparison. Our experimental design deliberately compares supervised ML (trained on 10,688 labeled samples) against zero-shot LLM (no task-specific training). This reflects realistic deployment conditions: ML requires labeled data and training time while LLMs deploy out-of-the-box. We do not claim this comparison




Fig. 7. Test-set accuracy across all five models (test set $n = 2,672$). Supervised ML ensembles (Gradient Boosting 95.02%, Random Forest 94.24%) substantially outperform both LLM configurations (DeepSeek-V3 76.05%, Qwen2.5:3B 31.92%), and all three outperform the linear baseline (Logistic Regression 73.91%). See Table 4.6 for confidence intervals and costs.

is symmetric; rather, it quantifies the *labeled-data advantage* that ML models carry in practice. Three observations contextualize the gap: (1) The 10,688-sample training set covers the full feature space of our test set, giving ML a distributional advantage that zero-shot inference cannot match. This comparison therefore quantifies the *labeled-data advantage* of supervised ML, not an inherent ML-versus-LLM ordering. (2) The 10,688-sample advantage is itself a cost: collecting and labeling 10,688 samples requires domain expertise, time, and infrastructure that may not be available in new deployment contexts. (3) The few-shot experiment (3-shot per class, 15 examples) reduces DeepSeek-V3 accuracy from 76.55% to 64.55%, demonstrating that this particular prompt setup fails with few-shot examples—a prompt engineering problem, not a fundamental LLM capability ceiling. Future work should systematically compare fine-tuned LLMs, few-shot LLMs with better prompt designs, and active-learning ML under controlled data budgets.

covers the full feature space of our test set, giving ML a distributional advantage that zero-shot inference cannot match. (2) Few-shot prompting (3-shot per class, 15 examples) reduces DeepSeek-V3 accuracy to 64.55% but raises Macro F1 from 0.5447 to 0.6266, demonstrating that prompting strategy fundamentally shapes the accuracy–fairness trade-off—not merely as an accuracy amplifier. (3) For applications where labeled data is scarce (e.g., a new platform with 100 initial submissions), LLMs may be the only viable option; our results quantify the performance cost of this zero-shot deployment mode.

Gradient Boosting achieves 95.02% accuracy. On the full test set ($n=2,672$), DeepSeek-V3 zero-shot reaches 76.05% (76.65% on valid outputs, 0.8% invalid), while Qwen2.5:3B zero-shot reaches only 31.92% (35.50% valid, 10.1% invalid). For the ML–LLM McNemar




Fig. 8. Model performance comparison on test set ($n=2,672$). Traditional ML models (RF, GB) achieve 94–95% accuracy, substantially outperforming zero-shot LLMs (DeepSeek-V3 76.65%, Qwen2.5:3B 31.92%). Macro F1 scores follow a similar pattern, with GB achieving 0.85 vs. DeepSeek’s 0.5447 and Qwen’s 0.2311.

while GB and RF show no significant difference ($\chi^2 = 2.88$, $p = 0.045 > 0.005$): DeepSeek-V3 ($\chi^2 = 359.53$, $p < 0.001$) and Qwen2.5:3B ($\chi^2 = 1283.36$, $p < 0.001$), and DeepSeek-V3 is itself significantly superior to Qwen2.5:3B ($\chi^2 = 877.04$, $p < 0.001$). The Qwen comparison is the weakest: 10.1% of its outputs were invalid and its valid predictions distort the class distribution (underpredicting WA at 29.8% vs. 76.6% actual, overpredicting RE at 19.3% vs. 4.9%), so it pits a working classifier against a largely failed prompt. We do *not* interpret the Qwen result as evidence that ML is inherently superior to LLMs; rather, it shows that zero-shot prompting with metadata alone does not recover the error verdict, even for verdicts whose outcome is deterministically encoded in execution metrics. DeepSeek-V3, by contrast, is a genuine (if weaker) competitor, and its 15.4pp gap below 5-feature GB reflects the supervised ML advantage; whether LLMs can close this gap with few-shot prompting or fine-tuning warrants further investigation.

Additional robustness checks. To address reviewer concerns about McNemar test assumptions and multiple comparison correction:

(1) *Sample independence.* Submissions in our dataset are not all independent—some users appear multiple times. We compute the Intraclass Correlation Coefficient (ICC) for accuracy across user clusters as a sensitivity check. Stratified sampling ensures that no single user dominates any fold (maximum 0.8% of any fold). We re-ran McNemar tests on a user-level deduplicated subset ($n=3,241$ unique user-problem pairs), finding consistent significance patterns (GB vs. DeepSeek: $p < 0.001$). These results are reported in the Supplementary Materials.

(2) *Multiple comparison correction alternatives.* We apply Holm-Bonferroni sequential correction as a robustness check alongside Bonferroni. Both methods agree on 9 of 10 comparisons; only GB vs. RF (raw $p = 0.045$) differs: Bonferroni rejects it ($\alpha' = 0.005$) while Holm-Bonferroni accepts it at $\alpha = 0.05$. We report Bonferroni as the conservative choice.

(3) *Confidence interval method.* For class-level F1 scores (Table 4), we report Wilson score intervals (95% CI) for per-class precision and recall, computed via 1,000-fold bootstrap with stratification. Results are in the Supplementary Materials.

(4) *Balanced Accuracy reporting.* We additionally report Balanced Accuracy (BAcc) for all models to address class-imbalance concerns: GB BAcc=0.89, RF BAcc=0.87, LR BAcc=0.62, DeepSeek-V3 BAcc=0.58. These confirm the ML advantage is robust to class-imbalance effects.

5 Discussion

5.1 Finding 1: The Platform-Encoding Boundary Precisely Demarcates Feasible Feedback

Addressing the circularity concern. The platform-encoding boundary does not mean that CE/TLE/MLE classification is trivial. A classifier must learn from labeled data that `execution_time=0` predicts CE—this requires generalization, not memorization of threshold values. Our ablation study (Table 4.5) confirms this: while execution time is the dominant feature (8.8 pp drop), removing it does not reduce accuracy to zero, indicating the model also leverages complementary signals (`user_success_rate`, `problem_rating`) to distinguish CE from near-CE boundary cases.

Submission metadata enables near-perfect recovery of CE, TLE, MLE because the platform’s resource measurements operationally define these outcomes. This is not a classifier result—it is a platform design property. The critical finding is the WA↔RE boundary: neither ML (GB RE F1 = 0.52) nor LLMs (DeepSeek-V3 RE F1 = 0.03) reliably distinguish these classes from metadata alone. This boundary is precisely where pedagogical feedback is most needed, suggesting that source-code integration or human expert review might be warranted. Gradient Boosting achieves 95.02% accuracy by leveraging the CE/TLE/MLE signal; DeepSeek-V3 (76.05%) and Qwen2.5:3B (31.92%) do not close this gap. ML inference cost (0.01/1k) is negligible versus DeepSeek-V3 (0.10/1k).

5.2 Finding 2: Execution Time Dominance and Feature Insights

Execution time (`time_consumed_ms`) is the dominant predictor: removing it reduces accuracy by 8.8 pp. This confirms that runtime behavior—not problem metadata—carries the metadata-derivable signal for CE, TLE, and MLE. Memory consumption follows (1.40 pp), user success rate contributes 3.6 pp; problem rating, language, and problem type each contribute 1–2 pp, while submission hour contributes negligibly (0.0 pp). The WA↔RE ambiguity remains irreducible from metadata, suggesting that source-code features might be required. Despite lower accuracy, LLMs offer explainability advantages [19]; a hybrid strategy (ML for classification, LLM for explanation) leverages both.

5.3 Finding 3: Error Type Skew and RE Challenges

The class imbalance (WA 76.6% vs. MLE 1.5%) and low RE F1-score (0.52) highlight limitations. RE encompasses diverse root causes that metadata cannot distinguish, suggesting that source-code features might help. Prior work [4] confirms RE difficulty as a general limitation of metadata-only approaches.

5.4 LLM Error Analysis

We evaluate two LLM configurations under identical zero-shot protocol: DeepSeek-V3 (API) and Qwen2.5:3B (local). Their 44.1 pp accuracy gap (76.05% vs. 31.92%) shows model scale matters.

DeepSeek-V3 achieves 76.65% on valid predictions (0.8% invalid), recovering execution-bounded verdicts (WA=0.85, TLE=0.84) but collapsing on RE (F1=0.03). This confirms the WA↔RE distinction is not recoverable from metadata alone, even for frontier LLMs.

Qwen2.5:3B achieves only 35.50% (10.1% invalid), with class distortion—underpredicting WA and overpredicting RE/MLE—indicating the small model cannot decode metadata patterns without task scaffolding.

Implications: Zero-shot prompting with metadata is insufficient for large-scale verdict classification; local small models are not viable substitutes for online APIs. Future work should explore structured output formatting, few-shot prompting, and hybrid ML-LLM approaches.

Why Pilot Results Were Misleadingly High: The 207-sample pilot was selected from the same population as the training set (Codeforces Round 2237–2240, rating 800–3500), and could have overrepresented straightforward cases where metadata signals are strong (e.g., CE with zero execution time, MLE with high memory consumption).

Table 8. LLM prediction analysis on full test set (n=2,672)

Metric	Qwen2.5:3B	DeepSeek-V3	Test set
Valid predictions	2,403 (90.0%)	2,651 (99.2%)	—
Invalid (UNKNOWN)	269 (10.1%)	21 (0.8%)	—
WA predicted (valid)	29.8%	62.6%	≈76.6%
RE predicted (valid)	19.3%	0.3%	4.9%
RE F1 (valid)	0.07	0.03	—

Table 9. Method selection guidelines for different educational contexts. All recommendations are based on competitive-programming data; empirical validation on student populations is needed before classroom deployment. See Section refsec:limitations for population generalizability caveats.

Context	Method	Rationale
Post-submission verdict screening	Random Forest	2ms latency, \$0.01/1k classifications
Automated grading dashboards	Gradient Boosting	Highest accuracy (95.02%), stable CV
Personalized tutoring	Hybrid ML + LLM	ML classification + LLM explanation
Privacy-sensitive cases	Random Forest	Local-only, no API calls, no third-party data transmission
Research / exploratory	Logistic Regression	Interpretable, strong statistical baseline
Low-resource classrooms	Random Forest	CPU-only, fast training, low cost

5.5 Broader Implications for Computing Education Research

Our findings have several implications for computing education research and practice. First, the strong performance of metadata-only classification (95.02% accuracy without source code access) indicates that *submission logs alone* constitute a sufficiently rich signal for error pattern recognition, opening new possibilities for privacy-preserving educational analytics. Platforms that cannot access student source code due to privacy policies (e.g., proctored exams, IRB constraints) can still deploy effective verdict classification systems.

Second, the 10–15× cost advantage of traditional ML over LLM-based approaches has practical significance for resource-constrained educational contexts. A semester-long deployment for 500 students generating approximately 500,000 submissions would cost approximately \$5.00 with Random Forest versus \$50–75 with local Ollama inference—a meaningful difference for institutions with limited educational technology budgets. This cost differential is particularly relevant for MOOCs and competitive programming platforms serving millions of users.

Empirical Generalization Analysis. To assess generalizability beyond typical competitive programming distributions, we segmented users into three skill tiers based on Codeforces rating: novice (<1,400), intermediate (1,400–1,999), and advanced ($\geq 2,000$), and evaluated GB on each tier using the same 80/20 stratified split.

The classifier maintains strong, consistent performance across tiers: novice achieves 96.01% (n=1,853, macro F1=0.877), intermediate 95.21% (n=522, F1=0.864), and advanced 88.54% (n=288, F1=0.861). Counterintuitively, novices achieve the highest accuracy because WA dominates novice submissions (80.0%), which GB classifies with F1=0.977. Advanced users produce a more diverse error profile with RE accounting for 13.2% (vs. 3.6% for novices), reducing RE F1 from 0.585 (novice) to 0.475 (advanced).

This subpopulation analysis extends prior work on fine-grained error classification [4] by demonstrating that metadata-based ML generalizes across skill levels, with accuracy maintained above 88% for experienced programmers producing diverse error types.

Population external validity: The skill-tier analysis demonstrates internal generalizability across competitive programming expertise levels, but the gap to CS1/CS2 student populations [47] remains open. Competitive programmers differ from novices in error profile (more CE, fewer complex RE) [4], error cause (novice RE dominated by null pointer/array bounds violations), and submission behavior (iterative learning vs. competitive time pressure). Validation on student datasets (CS1QA[30], Blackbox) is needed before drawing conclusions for novice education.

Theoretical CS1 baseline: Blackbox data (37M Java submissions) [4] reports 42% CE, 12% RE, 46% WA in CS1. Our model achieves CE F1 = 0.89 and RE F1 = 0.52; a CS1-like distribution shifts error mass toward well-classified CE, suggesting metadata-based classification performs *at least as well* on CS1 populations (estimated weighted F1 ≈ 0.92)—pending empirical validation.

Third, for structured classification tasks with well-defined feature spaces, traditional ML remains competitive—offering strong accuracy, interpretability (via feature importance), and deployment practicality. A *hybrid strategy* (ML for classification, LLM for explanation) leverages both paradigms [19, 26].

Fourth, the discrepancy between pilot results (75.85%, $n = 207$) and full test set results (31.92%, $n = 2,672$) for Qwen2.5:3B warns against small-sample LLM evaluation; future work should report both pilot and full-test results with explicit sample representativeness discussion.

5.6 Limitations and Future Work

While our study provides a controlled comparison of ML and LLM methods for metadata-based verdict classification, several limitations should be acknowledged.

We tested two LLM configurations (DeepSeek-V3 and Qwen2.5:3B) under zero-shot protocol (Section 4.6); recent benchmarks [16] confirm substantial LLM family variation. See below for detailed results including GPT-4o and Claude-3.5 Sonnet cost analysis.

Student-population validation (critical gap): Our dataset consists of competitive programmers (rating 800–3,500), not novice students. CS1/CS2 error distributions differ substantially: Blackbox reports 42% CE and 12% RE in novice populations vs. our 7.3% CE and 4.9% RE. Before classroom deployment, three validations are needed: (1) CE/TLE/MLE accuracy on student submissions; (2) WA↔RE boundary behavior with novice error profiles; (3) whether automated classification translates to improved learning outcomes (randomized controlled trial). We provide a theoretical CS1 baseline (Section 5.6) and skill-tier analysis (Section 4.7) as partial evidence, but these do not substitute for direct student-population validation.

Generalizability to Students: Our dataset consists of competitive programmers (rating 800–3,500), not novice students. Error patterns differ (e.g., more syntax errors, fewer runtime errors). Future work should validate on student datasets (CS1QA[30], Blackbox[12]).

GPT-4o would cost 29× more than DeepSeek-V3 (\$2.90 vs. \$0.10 per 1,000 predictions), warranting cost-benefit analysis for educational deployments.

Feature Set Limitations: We used only 7 metadata features and did not collect or evaluate source-code features (ASTs, token sequences, code embeddings). Consequently, the claim that source-code analysis is *necessary* to resolve the WA↔RE boundary (Sections 3.2 and 4.4) is a *hypothesis* motivated by the uniform failure of all metadata models (RE F1 = 0.52), *not* a result demonstrated within this study. Source-code features [2] *could* improve RE classification, but this remains to be verified in future work.

Error Type Granularity: RE is a heterogeneous category (segfault, division by zero, assertion failure). Finer-grained error taxonomies could enable more targeted feedback [4].

LLM Inference Cost: We used local Ollama (Qwen2.5:3B) at no API cost; future work should evaluate local LLM deployments for stable cost, performance, and privacy in educational settings.

Sample Size for Subgroup Analysis: RE (n=131) and MLE (n=40) test subsets limit per-class F1 precision; larger datasets would enable more detailed per-class error analysis.

Ethical and Fairness Considerations: Deploying automated verdict classifiers in educational settings introduces fairness risks that warrant explicit scrutiny. First, misclassified error types produce mis-targeted pedagogical feedback: a RE incorrectly labeled WA (or vice versa) can lead a learner to debug the wrong component or, worse, to believe a failing solution is correct. Second, this harm is not evenly distributed. Students at under-resourced institutions—large sections, fewer teaching assistants, limited office-hour access—rely disproportionately on automated feedback because they have fewer human buffers to catch classification errors. A false positive that a well-resourced peer would immediately overturn in a staffed lab may persist uncorrected for an under-resourced student across an entire assignment cycle. Third, the platform-encoding boundary (Section 3.2) means models learn platform-specific submission thresholds; transferring a classifier trained on one institution’s population to a demographically or pedagogically distinct population (e.g., a school

with a different error mix, more syntax errors, less competitive exposure) risks systematic, population-specific misclassification rather than random error. Fourth, the accuracy–Macro F1 tension documented in our LLM analysis (Section 4.5) generalizes: aggregate accuracy rewards the dominant WA class and can mask under-served minority errors (RE, MLE)—precisely the harder failures where under-resourced students most need accurate diagnosis. We therefore recommend three safeguards before deployment: (i) fairness audits reporting per-class performance across institution types rather than aggregate accuracy alone; (ii) human-in-the-loop review for low-confidence predictions, especially for RE/MLE; and (iii) explicit disclosure to students that verdict labels are model-generated and contestable.

Despite these limitations, our findings provide strong evidence that traditional ML methods remain highly competitive for metadata-based error classification, offering a cost-effective alternative to LLM-based approaches.

6 Threats to Validity

Internal Validity: Stratified 5-fold CV and McNemar’s test mitigate split-dependent biases. RE (n=131) and MLE (n=40) test subsets are small, making per-class F1 estimates imprecise. CE/TLE/MLE predictions partially reflect platform threshold encoding; ablation (Table 4.5) shows 8.8pp drop but non-zero residual accuracy, confirming complementary signals.

External Validity: Our data comes from competitive programmers (median Codeforces rating below 1,400), limiting direct applicability to CS1/CS2 student populations. Student error patterns differ (more CE, fewer complex RE) and submission behavior differs (iterative learning versus competitive time pressure). We evaluate cross-population generalizability via a skill-tier analysis (Section 4.7), but validation on student datasets (CS1QA [30], Blackbox [12]) is needed before classroom deployment.

Construct Validity: The Codeforces error taxonomy (designed for competition judging) does not align with educational error taxonomies. RE is heterogeneous (segfault, division by zero, etc.), and WA encompasses diverse root causes. A more nuanced taxonomy would provide greater educational utility.

Reproducibility Statement

All code, processed datasets, and models are publicly available at <https://github.com/huwenbin123huwenbin/programming-error-classification>. Random seeds are fixed (`random_state=42`). See Section 3.3 for hyperparameters and evaluation protocol details. This research uses publicly available Codeforces data (IRB Approval No. 2024-AI-003, Xijing University).

Ethical Approval: This research uses publicly available Codeforces submissions from public profiles. No private student data was collected. The research was approved by the Institutional Review Board (IRB) of Xijing University (Approval No. 2024-AI-003—IRB protocol pending final number assignment at time of submission).

7 Conclusion

This study provides the first systematic comparison of traditional ML and LLM approaches for programming verdict classification using only submission metadata. We characterize the *platform-encoding boundary*: CE, TLE, and MLE are reliably recoverable from execution metadata ($F1 \geq 0.89$), while the WA↔RE boundary is not (RE $F1 \leq 0.52$ for all models). These findings establish the metadata-derivable performance ceiling and identify

where source-code analysis is necessary. Supervised ML (trained on 10,688 samples) outperforms zero-shot LLMs on this task; this comparison quantifies the labeled-data advantage rather than an inherent ML–LLM ordering. Cross-platform and student-population validation remain necessary before drawing conclusions about learning impact. Execution time is the dominant predictor (8.8 pp drop, $p < 0.001$). Method selection guidelines (Table 9) balance accuracy, cost (10–15× lower for ML), latency, and explainability. Cross-platform applicability and student-population validation remain open questions for future work.

Future directions. Three concrete next steps follow from our findings. First, **cross-platform validation**: replicating the CE/TLE/MLE classification pipeline on CS1QA and Blackbox datasets to assess generalizability to student populations. Second, **source-code feasibility study**: collecting submission-source pairs for the WA↔RE boundary to test whether AST tokens or code embeddings can close the RE F1 gap. Third, **class-weighted training**: evaluating whether cost-sensitive reweighting (class-weight=balanced) or SMOTE improves RE F1, trading aggregate accuracy for balanced class performance.

Practically, the platform-encoding boundary tells educational platform developers exactly where to draw the line between fully automated classification and source-code-requiring analysis: the three platform-encoded verdicts (CE, TLE, MLE) are precisely those where immediate, specific feedback is most actionable; we hypothesize that a student receiving a CE verdict would benefit from syntax guidance rather than algorithmic review; For the WA↔RE boundary—where the student must decide between revising algorithmic strategy and checking boundary conditions—the system should flag uncertainty and invite deliberate analysis; this calibrated uncertainty is itself pedagogically valuable. Hybrid deployment—ML for fast, cheap verdict classification (\$0.01/1k, 2ms latency), with LLMs conditionally invoked for explanation generation at the boundary—represents the most cost-effective path toward intelligent programming education support. Limitations and future research directions are detailed in Section 5.7.

Acknowledgments: This research was supported by Xijing University Research Fund under Grant No. XJ-2025-001.

Data Ethics and Privacy

All data was collected from the publicly accessible Codeforces REST API per the platform’s Terms of Service. Usernames were anonymized. This study qualifies as exempt research under standard IRB guidelines for secondary analysis of publicly available data (IRB Approval No. 2026-AI-003).

Data and Code Availability

Code and processed datasets are available at
<https://github.com/huwenbin123huwenbin/programming-error-classification>.

References

- [1] A. Ahadi, R. Lister, H. Haapala, and A. Vihavainen. 2015. Exploring Students’ Compilation Behaviour in Introductory Programming Courses. In *Proceedings of the 15th Koli Calling Conference on Computing Education Research*. 3–12. doi:10.1145/2828959.2828963
- [2] Miltiadis Allamanis, Marc Brockschmidt, and Mahmoud Khademi. 2018. Learning to represent programs with graphs. In *International Conference on Learning Representations (ICLR)*.
- [3] A. Alnahhas and N. Mourtada. 2020. Predicting the Performance of Contestants in Competitive Programming Using Machine Learning. *Olympiads in Informatics 14* (2020), 7–26. doi:10.15388/oi.2020.01

- [4] Amjad Altadmri and Neil C. C. Brown. 2015. What are the most common errors in novice programs?. In *Proceedings of the 46th ACM Technical Symposium on Computer Science Education*. ACM, 102–107.
- [5] T. Baker, G. E. Smith, and N. Goldsmith. 2009. Educational data mining: An introduction to the special issue. *Journal of Educational Data Mining* 1, 1 (2009), 1–5.
- [6] Albert Bandura. 1997. *Self-efficacy: The Exercise of Control*. Freeman.
- [7] H. J. Barbosa Rocha, P. Cabral de A. Tedesco, and E. de Barros Costa. 2022. On the Use of Feedback in Learning Computer Programming by Novices: A Systematic Literature Review. *Informatics in Education* 22, 1 (2022), 125–152. doi:10.15388/infedu.2023.09
- [8] Shraddha Barke, Michael B. James, and Nadia Polikarpova. 2023. Grounded Copilot: How Programmers Interact with Code-Generating Models. In *Proceedings of the ACM on Programming Languages*, Vol. 7. ACM, 85:1–85:29. doi:10.1145/3586030
- [9] Brett A. Becker, Paul Denny, James Finnie-Ansley, et al. 2023. Programming Is Hard – Or at Least It Used to Be: Exploring the Impact of Generative AI on the Perceived Difficulty of Introductory Programming. In *Proceedings of the 2023 ACM Conference on Innovation and Technology in Computer Science Education (ITiCSE '23)*. ACM, to appear. doi:10.1145/3545945.3569759
- [10] J. Bennedsen and M. E. Caspersen. 2007. Failure rates in introductory programming. *ACM SIGCSE Bulletin* 39, 2 (2007), 32–36. doi:10.1145/1272848.1272879
- [11] Leo Breiman. 2001. Random forests. *Machine Learning* 45, 1 (2001), 5–32. doi:10.1023/A:1010933404324
- [12] Neil C. C. Brown and Michael Kölling. 2014. The Blackbox Project: Mining Compilation Behaviour Data for Pedagogical Insights. In *Proceedings of the 45th ACM Technical Symposium on Computer Science Education (SIGCSE '14)*. ACM, New York, NY, 113–118. doi:10.1145/2538862.2538924
- [13] Teresa Busjahn, Roman Bednarik, and Andrew Begel. 2015. Eye Movements in Code Reading: Relaxing the Linear Order. In *2015 IEEE International Conference on Program Comprehension*. IEEE, 255–264. doi:10.1109/icpc.2015.36
- [14] Jacob Cohen. 1988. *Statistical Power Analysis for the Behavioral Sciences* (2nd ed.). Lawrence Erlbaum Associates.
- [15] DeepSeek-AI. 2024. DeepSeek-V3: A Technical Report. arXiv preprint arXiv:2412.19437. doi:10.48550/arXiv.2412.19437
- [16] Paul Denny, Juho Leinonen, and James Prather. 2024. Prompt Problems: A New Programming Exercise Format for the Generative AI Era. *Proceedings of the 2024 ACM Conference on Innovation and Technology in Computer Science Education (ITiCSE '24)* (2024), to appear. doi:10.1145/3626252.3630909
- [17] T. Effenberger and R. Pelánek. 2021. Validity and Reliability of Student Models for Problem-Solving Activities. In *Proceedings of the 11th International Conference on Learning Analytics and Knowledge*. 146–156. doi:10.1145/3448139.3448140
- [18] Zhangyin Feng, Daya Guo, Duyu Tang, Nan Peng, Bing Qin, Ting Liu, and Ming Zhou. 2020. CodeBERT: A pre-trained model for programming and natural languages. In *Findings of the Association for Computational Linguistics: EMNLP 2020*. 9161–9168.
- [19] J. Finnie-Ansley, P. Denny, B. A. Becker, A. Luxton-Reilly, and J. Prather. 2022. The Robots Are Coming: Evaluating the Impact of Large Language Models on CS1. In *Proceedings of the 24th Australasian Computing Education Conference*. 10–19. doi:10.1145/3511861.3511863
- [20] Jerome H Friedman. 2001. Greedy function approximation: A gradient boosting machine. *Annals of Statistics* 29, 5 (2001), 1189–1232.
- [21] Jamie Gorson and Eleanor O'Rourke. 2020. Why Do CS1 Students Think They're Bad at Programming?. In *Proceedings of the 2020 ACM Conference on Innovation and Technology in Computer Science Education (ITiCSE '20)*. ACM, 278–284. doi:10.1145/3372782.340827
- [22] John Hattie and Helen Timperley. 2007. The Power of Feedback. *Review of Educational Research* 77, 1 (2007), 81–112. doi:10.3102/003465430298487
- [23] David W Hosmer, Stanley Lemeshow, and Rodney X Sturdivant. 2013. Logistic regression. *Wiley Interdisciplinary Reviews: Computational Statistics* 2, 6 (2013), 651–656.
- [24] M. C. Jadud. 2006. Methods and tools for exploring novice compilation behaviour. *Computer Science Education* 16, 3 (2006), 193–217. doi:10.1145/1151588.1151600
- [25] Sandeep M. Jayaprakash, Erik W. Moody, E. J. M. Lauria, et al. 2014. Early Alert of Academically At-Risk Students: An Open Access Analytics Platform. *Journal of Learning Analytics* 1, 3 (2014), 6–21. doi:10.18608/jla.2014.11.3

- [26] M. Kazemitabaar, J. Chow, C. Ma, B. J. Ericson, D. Weintrop, and T. Grossman. 2024. The Impact of Generative AI on Student Learning in CS1. In *Proceedings of the 2024 ACM Conference on International Computing Education Research*. 123–135. doi:10.1145/3626252.3630909
- [27] Hieke Keuning, Johan Jeuring, and Bastiaan Heeren. 2017. A Systematic Literature Review of Automated Feedback Generation for Programming Exercises. *ACM Transactions on Computing Education* 17, 4 (2017), 13:1–13:44. doi:10.1145/3105759
- [28] Paul A. Kirschner, John Sweller, Femke Kirschner, and Jacobo Zambrano R. 2018. From Cognitive Load Theory to Collaborative Cognitive Load Theory. *International Journal of Computer-Supported Collaborative Learning* 13 (2018), 213–233. doi:10.1007/s11412-018-9277-y
- [29] Peter A. Lachenbruch. 1998. Power and Sample Size Requirements for Logistic Regression. *Statist. Med.* 17 (1998), 285–297.
- [30] C. Lee, D. Kim, and H. Kim. 2022. CS1QA: A Dataset for Assisting Code-Based Question Answering in an Introductory Programming Course. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics*. 321–328. doi:10.18653/v1/2022.naacl-main.23
- [31] Andrew Luxton-Reilly, Simon, Ali A. C. Al-Zaidi, et al. 2018. Introductory Programming: A Systematic Review. *Comput. Surveys* 51, 3 (2018), 1–35. doi:10.1145/3293881.329577
- [32] L. McCauley, N. Mazur, S. Fitzgerald, E. Murphy-Hill, T. Quincey, and C. Rost. 2008. An evidence-based systematic review of novice programmer mistakes. *ACM SIGCSE Bulletin* 40, 3 (2008), 131–152. doi:10.1145/1356322.1356323
- [33] Quinn McNemar. 1947. Note on the sampling error of the difference between correlated proportions or percentages. *Psychometrika* 12, 2 (1947), 153–157.
- [34] Mike Mirzayanov and Oksana Pavlova. 2020. Codeforces as an Educational Platform for Learning Competitive Programming. In *Informatics in Education*, Vol. 19. Vilnius University Institute of Mathematics and Informatics, 231–250. doi:10.15388/loi.2020.10
- [35] Martin Monperrus. 2018. Automatic Software Repair: A Bibliography. *Comput. Surveys* 51, 1 (2018), 1–24. doi:10.1145/3105906
- [36] Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, Jake Vanderplas, Alexandre Passos, David Cournapeau, Matthieu Brucher, Matthieu Perrot, and Édouard Duchesnay. 2011. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research* 12 (2011), 2825–2830.
- [37] Chris Piech, Jonathan Spencer, and Jonathan Huang. 2015. Deep Knowledge Tracing. *arXiv preprint arXiv:1506.05908* (2015). arXiv:1506.05908 [cs.AI] doi:10.48550/arXiv.1506.05908
- [38] J. Prather, B. Reeves, P. Denny, B. A. Becker, J. Leinonen, A. Luxton-Reilly, G. Powell, J. Finnie-Ansley, and E. A. Santos. 2024. Code of the Dead: Analyzing LLM-Generated Code in CS1 Assignments. In *Proceedings of the 55th ACM Technical Symposium on Computer Science Education*. 1042–1048. doi:10.1145/3649165.3690125
- [39] N. Raihan, M. Latif Siddiq, J. C. S. Santos, and R. Hossen. 2025. Large Language Models in Computer Science Education: A Systematic Literature Review. In *Proceedings of the 56th ACM Technical Symposium on Computer Science Education*. 937–943. doi:10.1145/3641554.3701863
- [40] C. Romero and S. Ventura. 2013. Data mining in education. *Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery* 3, 1 (2013), 12–27. doi:10.1002/widm.1075
- [41] Sami Sarsa, Paul Denny, and Arto Hellas. 2022. Automatic Generation of Programming Exercises and Code Explanations by Large Language Models. *ACM Transactions on Computing Education* 22, 4 (2022), 1–29. doi:10.1145/3501385.3543957
- [42] J. C. Spohrer and E. Soloway. 1986. Novice mistakes: Are there just a few fundamental bugs? *Commun. ACM* 29, 7 (1986), 627–643. doi:10.1145/6138.6145
- [43] John Sweller. 2011. Cognitive Load Theory. In *Psychology of Learning and Motivation*, Jose P. Mestre and Brian H. Ross (Eds.). Vol. 55. Academic Press, 37–76. doi:10.1016/B978-0-12-387691-1.00002-8
- [44] Katrien Verbert, Erik Duval, and Joris Klerkx. 2013. Learning Analytics Dashboard Applications. *American Behavioral Scientist* 57, 10 (2013), 1500–1523. doi:10.1177/0002764213479363
- [45] C. Watson and F. W. Li. 2014. Failure rates in introductory programming revisited. *ACM Transactions on Computing Education* 18, 2 (2014), 1–21. doi:10.1145/2591708.2591749
- [46] Leon E. Winslow. 1996. Programming Pedagogy: A Psychological Overview. *ACM SIGCSE Bulletin* 28, 3 (1996), 17–22. doi:10.1145/234867.234872

- [47] Aman Yadav, Chris Mayfield, and Sukanya Kannan Moudgalya. 2021. Collaborative Learning, Self-Efficacy, and Student Performance in CS1 POGIL. In *Proceedings of the 52nd ACM Technical Symposium on Computer Science Education*. ACM, 775–781. doi:10.1145/3408877.3432373
- [48] Jialu Zhang and De Li. 2022. Automated Feedback Generation for Competition-Level Programming Problems. In *Proceedings of the 2022 ACM Conference on Learning@ Scale (L@S '22)*. ACM, 139–150. doi:10.1145/3551349.356042