Distributed Systems - Introduction to Go

Duration: 10 minutes.

* Indicates required question

1. Email *

2. Full name *

3. Student ID *

4. Which of the following is true about global variables in Go? * 1 point

   Mark only one oval.

   - Global variables are defined outside of a function, usually on top of the program.
   - Global variable is available for use throughout your entire program after its declaration.
   - All of the above.

5. What would happen if you attempted to compile and run this Go program? * 1 point

```
package main

import (
    "fmt"
)

var myGlobal string

func main() {
    fmt.Println("This is " + myGlobal)
}
```

Mark only one oval.

- ( ) It would not compile.
- ( ) It prints "This is".
- ( ) It would compile but then panic because GlobalFlag was never initialized.

6. What are valid loop constructs in Go? *

1 point

Check all that apply.

- [ ] do { ... } while i < 5
- [ ] for _, c := range "hello" { ... }
- [ ] for i := 1; i < 5; i++ { ... }
- [ ] for i < 5 { ... }

7. Does Go support function closures? *

1 point

Mark only one oval.

- ( ) Yes, it does.
- ( ) No, it does not.

8. Which option sends output to standard error? *

1 point

Mark only one oval.

- ( ) log.New(os.Stderr, "", 0).Println("Error 1")
- ( ) fmt.Fprintln(os.Stderr, "Error 2")
- ( ) fmt.Println(fmt.Errorf("%q\n", "Error 3").Error())
- ( ) All of them.

9. What does the len() function return if passed a UTF-8 encoded string? * 1 point

Mark only one oval.

- ( ) The number of characters.
- ( ) The number of bytes.
- ( ) An error.

10. What is the value of Read? * 1 point

```
const (
Write = iota
Read
Execute
)
```

Mark only one oval.

- ( ) 0
- ( ) 1
- ( ) 2
- ( ) null

11. How will you add the number 3 to the right side of myarray? *

1 point

myarray : = []int {1, 1, 2}

Mark only one oval.

- myarray.append(3)
- myarray.insert(3, 3)
- append(values, 3)
- myarray = append(myarray, 3)

12. What restriction is there on the type of laser to compile this t := laser.(int)? *

1 point

Mark only one oval.

- laser must be an integer type, such as int, int64, int32, etc.
- laser must be an interface.
- laser must be able to be asserted as an int.

13. What is the output? * 1 point

```
x := 'A'
y := 'B'
z := x + y
fmt.Println(z)
```

Mark only one oval.

- An error.
- An empty string.
- AB
- 131