

Comment	Description	Designator	Footprint	LibRef	Quantity
Button 3x4x2.5		B1	Button 3x4x2.5	Button 3x4x2.5	1
		C1, C2, C3, C9, C10,			
1005	0	C11, C13, C14, C17,	040 0005	O CMD	10
100nF	Capacitor	C19	CAP_0805	CapSMD	10
4.7uF	Capacitor	C4	CAP_0805	CapSMD	1
0.1uF	Capacitor	C5	CAP_0805	CapSMD	1
1uF	Capacitor	C6	CAP_0805	CapSMD	1
22pF	Capacitor	C7, C8	CAP_0805	CapSMD	2
10uF	Capacitor	C12, C15, C18	CAP_0805	CapSMD	3
	Header IDC, 2 x 1				
	Pin Vertical 2.54mm Pitch (Non-Boxed,				
Header2	Male)	C16	HEAD2P-1.25	Header2	1
	LED Single colour				
GREEN	Green and Red	D1	LED-0805-Green	LED	1
	LED Single colour				
RED	Green and Red	D2	LED-0805-Red	LED	1
BLUE	LED Single colour Green and Red	D3	LED-0805-Blue	LED	1
BEGE	LED Single colour	D3	EED-0003-Bide	LLD	'
BLUE	Green and Red	D4	LED-0805-Red	LED	1
	LED Single colour				
RED	Green and Red	D5	LED-0805-Green	LED	1
	LED Single colour		l		
GREEN	Green and Red	D6	LED-0805-Yellow	LED	1
YELLOW	LED Single colour Green and Red	D7, D10	LED-0805-Yellow	LED	2
TELEOW	LED Single colour	<i>D1</i> , <i>D10</i>	EED-0003-Tellow	LLD	
BLUE	Green and Red	D8	LED-0805-Yellow	LED	1
	LED Single colour				
RED	Green and Red	D9	LED-0805-Yellow	LED	1
JP4	Connector 4	JP1	HEADER4P-1.25	Con4	1
10K	Resistor	R1, R2, R6, R12	RES-SMD-0805	Resistor - SMD	4
1K	Resistor	R3, R5, R16	RES-SMD-0805	Resistor - SMD	3
	L	R4, R8, R9, R10, R13,			
330R	Resistor	R14, R15, R17	RES-SMD-0805	Resistor - SMD	8
1.2K	Resistor	R7	RES-SMD-0805	Resistor - SMD	1
100R	Resistor	R11	RES-SMD-0805	Resistor - SMD	1
30K	Resistor	R18	RES-SMD-0805	Resistor - SMD	1
100K	Resistor	R19	RES-SMD-0805	Resistor - SMD	1
Switch 3x1	Switch 3x1	SW1	SLIDE_SW	SW3x1	1
	Mainstream				
	Performance line, ARM Cortex-M3				
	MCU with 64 Kbytes				
	Flash, 72 MHz CPU,				
	motor control, USB				
STM32F103C8T6	and CAN	U1	STM32F103C8T6	STM32F103C8T6	1
	Decawave's DW1000				
	Ultra Wideband (UWB)				
DWM1000	transceiver IC	U2	DW1000	DWM1000	1
544441666	Complete single cell	01	5111000	541111000	
	Li-lon battery with a				
	constant current /				
	constant voltage			TD 405 /	
TP4056	linear charger	U3	TP4056	TP4056	1
RT9013	One Call Little	U4, U6	RT9013	RT9013	2
	One Cell Lithium- ion/Polymer Battery				
DW01A	Protection IC	U5	SOT23-6	DW01A	1
CH340C		U7	SO16	CH340C	1
FS8205A		U8	FS8205A	FS8205A	1
	LISP Type P				1
USB Micro 5p DIP	USB Type B CRYSTAL 16MHZ	USB1	USB Micro 5p DIP	USB Micro 5p DIP ABM7-16.000MHZ-	
8MHz	18PF SMD	Y1	ABM7_v1_1_BIG	D2Y-T	1
	•				·