CC120(LED)-C vertical sample table (transmission &reflection)



1. Comply with ISO3664 international standard, CC120(LED)-C has three modes option(single or double or triple light sources).
2. Use with high color-rendering index lamps, and with timer for the using time of lamp on display screen.
3. CC120(LED)-C is fine made with metal material, large size and good work manship, easy to use.
4. Equipped with frequently-used light sources in printing industry, can meet the needs of ISO3664:2009.
5. CC120(LED)-C is widely used in printing shop and sampling centers.
6. It also can check reflection file, and be used in the industry of offset print, flexography,gravure

ISO9001 CE RoHS

PRODUCT FEATURES

Light Sources: can meet the international standard of ISO 3664
Lamps type: equipped with special Graphic lamps for import printing machine
Color-rendering index: CRI=98
Worktable material: metal plate desk, firm & durable
Operation desk: is incorporated with an intake ramp designed to meet the human visual observation
Hanging light sources: aluminium alloy stuff and streamline from design, fashion, style. Import reflector, uniform light cover will ensure the illuminating uniformity

APPLICATION INDUSTRY

CC120(LED) series vertical sample table is equipped with frequently-used light sources in printing industry, can meet the needs of ISO 3664:2009.It isalso widely used for color checking in the field of printing and dyeing, textiles, plastics, hardware etc, which willprovide standard environment forquality checking in the process of sample comparison, production, quality inspection, acceptance etc. That is to say, it can help user improve theproduct quality and market competition.


Printing Shop


Printing & Dyeing


Textiles


Plastics


Hardware

Others

PRODUCT PARAMETERS

Upper light source					
The upper configured with 3 groups of light	Model and specification	standard light source	Color Temperature	Power	Quantity
	CC120(LED)-C-1	D65 Single light source, without drawer	6500K	20W	1x4 pcs
	CC120(LED)-C-2	D65 D50 dual light source, without drawer	6500 5000K	20W	2x4 pcs
	CC120(LED)-C-3	D65 D50 TL84 three light sources, without drawer	6500 5000 4000K	20W	3x4 pcs
Lower light source without drawer					
Optional standard light source	CC120(LED)-C	D65 D50 TL84 single light source	6500 5000 4000K	20W	1x6 pcs

Basic Parameters	
Power Supply	AC220V 50HZ
Worktable size(mm)	1350*900(L*W)
Vertical size(mm)	1350*2174(L*W)
External size(mm)	1350*900*2174(L*W*H)