

IT5427


Tích hợp và xử lý dữ liệu lớn

IT5427

Spring 2020  
Thanh-Chung Dao Ph.D.


1

From where to learn Spark ?

<http://spark.apache.org/><http://shop.oreilly.com/product/0636920028512.do>

2

## Spark architecture



3

## Easy ways to run Spark ?

- ★ your IDE (ex. Eclipse or IDEA)
- ★ [Standalone Deploy Mode](#): simplest way to deploy Spark on a single machine
- ★ [Docker & Zeppelin](#)
- ★ [EMR](#)
- ★ Hadoop vendors ([Cloudera](#), [Hortonworks](#))
- Digital Ocean (Kuberneste cluster)

4


## Supported languages



5

## RDD

An RDD is simply an immutable distributed collection of objects!



The Spark logo, which consists of the word 'Spark' in a black sans-serif font followed by a small orange star icon.

6

## RDD (Resilient Distributed Dataset)

### RDD (Resilient Distributed Dataset)

- Resilient: If data in memory is lost, it can be recreated
  - Distributed: Processed across the cluster
  - Dataset: Initial data can come from a source such as a file, or it can be created programmatically
- **RDDs are the fundamental unit of data in Spark**
  - **Most Spark programming consists of performing operations on RDDs**

7

## Creating RDD (I)

Python

```
lines = sc.parallelize(["workshop", "spark"])
```

Scala

```
val lines = sc.parallelize(List("workshop", "spark"))
```

Java

```
JavaRDD<String> lines = sc.parallelize(Arrays.asList("workshop", "spark"))
```

8

## Creating RDD (II)

Python

```
lines = sc.textFile("/path/to/file.txt")
```

Scala

```
val lines = sc.textFile("/path/to/file.txt")
```

Java

```
JavaRDD<String> lines = sc.textFile("/path/to/file.txt")
```

9

## RDD persistence

```
MEMORY_ONLY  
MEMORY_AND_DISK  
MEMORY_ONLY_SER  
MEMORY_AND_DISK_SER  
DISK_ONLY  
MEMORY_ONLY_2  
MEMORY_AND_DISK_2  
OFF_HEAP
```

10

## Working with RDDs

11

## RDDs

### **RDDs can hold any serializable type of element**

- Primitive types such as integers, characters, and booleans
- Sequence types such as strings, lists, arrays, tuples, and dicts (including nested data types)
- Scala/Java Objects (if serializable)
- Mixed types

### **§ Some RDDs are specialized and have additional functionality**

- Pair RDDs
- RDDs consisting of key-value pairs
- Double RDDs
- RDDs consisting of numeric data

12

## Creating RDDs from Collections

**You can create RDDs from collections instead of files**  
**–sc.parallelize(*collection*)**

```
myData = ["Alice", "Carlos", "Frank", "Barbara"]
> myRdd = sc.parallelize(myData)
> myRdd.take(2) ['Alice', 'Carlos']
```

13

## Creating RDDs from Text Files (1)

**For file-based RDDs, use SparkContext.textFile**

– Accepts a single file, a directory of files, a wildcard list of files, or a comma-separated list of files. Examples:

```
–sc.textFile("myfile.txt")
–sc.textFile("mydata/")
–sc.textFile("mydata/*.log")
–sc.textFile("myfile1.txt,myfile2.txt")
```


– Each line in each file is a separate record in the RDD

**Files are referenced by absolute or relative URI**

```
–Absolute URI:
–file:/home/training/myfile.txt
–hdfs://nnhost/loudacre/myfile.txt
```


14

## Examples: Multi-RDD Transformations (1)



15

## Examples: Multi-RDD Transformations (2)



16



## Some Other General RDD Operations

### Other RDD operations

- first* returns the first element of the RDD
- foreach* applies a function to each element in an RDD
- top(n)* returns the largest  $n$  elements using natural ordering

### Sampling operations

- sample* creates a new RDD with a sampling of elements
- take Sample* returns an array of sampled elements

17


## Other data structures in Spark

- ★ Paired RDD
- ★ DataFrame
- ★ DataSet

18

## Paired RDD

Paired RDD = an RDD of key/value pairs



19

Pair RDDs

20

## Pair RDDs

### § Pair RDDs are a special form of RDD

- Each element must be a key-value pair (a two-element *tuple*)
- Keys and values can be any type

Pair RDD

(key1, value1)
(key2, value2)
(key3, value3)
...

### § Why?

- Use with map-reduce algorithms
- Many additional functions are available for common data processing needs
- Such as sorting, joining, grouping, and counting

21

## Creating Pair RDDs

**The first step in most workflows is to get the data into key/value form**

- What should the RDD should be keyed on?
- What is the value?

**Commonly used functions to create pair RDDs**

- map**
- flatMap / flatMapValues**
- keyBy**

22

## Example: A Simple Pair RDD

**Example: Create a pair RDD from a tab-separated file**

```
> val users = sc.textFile(file).
  map(line => line.split('\t')).
  map(fields => (fields(0),fields(1)))
```

```
user001\tFred Flintstone
user090\tBugs Bunny
user111\tHarry Potter
...
```



(user001,Fred Flintstone)
(user090,Bugs Bunny)
(user111,Harry Potter)
...

23

## Example: Keying Web Logs by User ID

```
> sc.textFile(logfile).
  keyBy(line => line.split(' ')[2])
```

User ID

```
56.38.234.188 - 99788 "GET /KBD0C-00157.html HTTP/1.0" ...
56.38.234.188 - 99788 "GET /theme.css HTTP/1.0" ...
203.146.17.59 - 25254 "GET /KBD0C-00230.html HTTP/1.0" ...
...
```




(99788,56.38.234.188 - 99788 "GET /KBD0C-00157.html...)
(99788,56.38.234.188 - 99788 "GET /theme.css...)
(25254,203.146.17.59 - 25254 "GET /KBD0C-00230.html...)
...

24

## Mapping Single Rows to Multiple Pairs

### How would you do this?


- Input: order numbers with a list of SKUs in the order
- Output: **order** (key) and **sku** (value)



25

## Answer : Mapping Single Rows to Multiple Pairs

```
> sc.textFile(file) \
  .map(lambda line: line.split('\t')) \
  .map(lambda fields: (fields[0], fields[1])) \
  .flatMapValues(lambda skus: skus.split(':'))
```



26

## Map-Reduce

- § **Map-reduce is a common programming model**
  - Easily applicable to distributed processing of large data sets
- § **Hadoop MapReduce is the major implementation**
  - Somewhat limited
  - Each job has one map phase, one reduce phase
  - Job output is saved to files
- § **Spark implements map-reduce with much greater flexibility**
  - Map and reduce functions can be interspersed
  - Results can be stored in memory
  - Operations can easily be chained


27

## Map-Reduce in Spark

- § **Map-reduce in Spark works on pair RDDs**
- § **Map phase**
  - Operates on one record at a time
  - “Maps” each record to zero or more new records
  - Examples: **map**, **flatMap**, **filter**, **keyBy**
- § **Reduce phase**
  - Works on map output
  - Consolidates multiple records
  - Examples: **reduceByKey**, **sortByKey**, **mean**

28

## Example: Word Count




29

## reduceByKey

The function passed to `reduceByKey` combines values from two keys

– Function must be binary



30

```
> val counts = sc.textFile (file) . flat.Map
  (line => line.split (' ')) . map (word => (word
    ,1)) . reduceByKey ((v1,v2) => v1+v2)
```

OR

```
> val counts = sc.textFile (file) . flat.Map
  (_.split (' ')) .
  map ((_,1)) .
  reduceByKey (_+_)
```

31

## Pair RDD Operations

§ In addition to map and reduceByKey operations, Spark has several operations specific to pair RDDs


### § Examples

- countByKey** returns a map with the count of occurrences of each key
- groupByKey** groups all the values for each key in an RDD
- sortByKey** sorts in ascending or descending order
- join** returns an RDD containing all pairs with matching keys from two RDD

32




## Example: Pair RDD Operations



33

## Example: Joining by Key

```
> movies = moviegross.join(movieyear)
```



34

## Other Pair Operations

### § Some other pair operations

- keys** returns an RDD of just the keys, without the values
- values** returns an RDD of just the values, without keys
- lookup(key)** returns the value(s) for a key
- leftOuterJoin**, **rightOuterJoin** , **fullOuterJoin** join two RDDs, including keys defined in the left, right or either RDD respectively
- mapValues**, **flatMapValues** execute a function on just the values, keeping the key the same

35

DataFrames and Apache Spark SQL

36

## What is Spark SQL?

### § What is Spark SQL?

- Spark module for structured data processing
- Replaces Shark (a prior Spark module, now deprecated)
- Built on top of core Spark

### § What does Spark SQL provide?

- The DataFrame API—a library for working with data as tables
- Defines DataFrames containing rows and columns
- DataFrames are the focus of this chapter!
- Catalyst Optimizer—an extensible optimization framework
- A SQL engine and command line interface

37

## SQL Context

### § The main Spark SQL entry point is a SQL context object

- Requires a **SparkContext** object
- The SQL context in Spark SQL is similar to Spark context in core Spark

### § There are two implementations

- SQLContext**
- Basic implementation
- HiveContext**
- Reads and writes Hive/HCatalog tables directly
- Supports full HiveQL language
- Requires the Spark application be linked with Hive libraries
- Cloudera recommends using **HiveContext**

38

## Creating a SQL Context

§ **The Spark shell creates a HiveContext instance automatically**

- Call **sqlContext**
- You will need to create one when writing a Spark application
- Having multiple SQL context objects *is* allowed

§ **A SQL context object is created based on the Spark context**

```
import org.apache.spark.sql.hive.HiveContext
val sqlContext = new HiveContext(sc)
import sqlContext.implicits._
```

Language: Scala

39

## DataFrames

§ **DataFrames are the main abstraction in Spark SQL**

- Analogous to RDDs in core Spark
- A distributed collection of structured data organized into Named columns
- Built on a *base RDD* containing **Row** objects

40

## Creating a DataFrame from a Data Source

§ `sqlContext.read` returns a `DataFrameReader` object

§ `DataFrameReader` provides the functionality to load data into a `DataFrame`

§ Convenience functions

- `json(filename)`
- `parquet(filename)`
- `orc(filename)`
- `table(hive-tablename)`
- `jdbc(url,table,options)`

41

## Example: Creating a DataFrame from a JSON File

```
val sqlContext = new HiveContext(sc)
import sqlContext.implicits._
val peopleDF = sqlContext.read.json("people.json")
```

Language: Scala

File: people.json

```
{ "name": "Alice", "pcode": "94304" }
{ "name": "Brayden", "age": 30, "pcode": "94304" }
{ "name": "Carla", "age": 19, "pcode": "10036" }
{ "name": "Diana", "age": 46 }
{ "name": "Étienne", "pcode": "94104" }
```

age	name	pcode
null	Alice	94304
30	Brayden	94304
19	Carla	10036
46	Diana	null
null	Étienne	94104

42

## Example: Creating a DataFrame from a Hive/Impala Table

```
val sqlContext = new HiveContext(sc)
import sqlContext.implicits._
val customerDF = sqlContext.read.table("customers")
```

Language: Scala

Table: customers

cust_id	name	country
001	Ani	us
002	Bob	ca
003	Carlos	mx
...	...	...



cust_id	name	country
001	Ani	us
002	Bob	ca
003	Carlos	mx
...	...	...

43

## Loading from a Data Source Manually

§ You can specify settings for the **DataFrameReader**

–**format**: Specify a data source type

–**option**: A key/value setting for the underlying data source

–**schema**: Specify a schema instead of inferring from the data source

§ Then call the generic base function **load**

```
sqlContext.read.
  format("com.databricks.spark.avro").
  load("/loudacre/accounts_avro")
```

```
sqlContext.read.
  format("jdbc").
  option("url", "jdbc:mysql://localhost/loudacre").
  option("dbtable", "accounts").
  option("user", "training").
  option("password", "training").
  load()
```

44

## Data Sources

### § Spark SQL 1.6 built-in data source types

- table
- json
- parquet
- jdbc
- orc

### § You can also use third party data source libraries, such as

- Avro (included in CDH)
- HBase
- CSV
- MySQL
- and more being added all the time

45

## DataFrame Basic Operations

- § Basic operations deal with DataFrame metadata (rather than its data)
- § Some examples
  - –schema returns a schema object describing the data
  - –printSchema displays the schema as a visual tree
  - –cache / persist persists the DataFrame to disk or memory
  - –columns returns an array containing the names of the columns
  - –dtypes returns an array of (column name,type) pairs
  - –explain prints debug information about the DataFrame to the console

46

## DataFrame Basic Operations

Language: Scala

```
> val peopleDF = sqlContext.read.json("people.json")
> peopleDF.dtypes.foreach(println)
(age, LongType)
(name, StringType)
(pcode, StringType)
```

47

## DataFrame Actions

§ Some DataFrame actions

- collect returns all rows as an array of Row objects
- take(*n*) returns the first *n* rows as an array of Row objects
- count returns the number of rows
- show(*n*) displays the first *n* rows (default=20)

Language: Scala

```
> peopleDF.count()
res7: Long = 5

> peopleDF.show(3)
age  name  pcode
null Alice  94304
30   Brayden 94304
19   Carla   10036
```

48



## DataFrame Queries

### § DataFrame query methods return new DataFrames

- Queries can be chained like transformations

### § Some query methods

- **distinct** returns a new DataFrame with distinct elements of this DF
- **join** joins this DataFrame with a second DataFrame
- Variants for inside, outside, left, and right joins
- **limit** returns a new DataFrame with the first **n** rows of this DF
- **select** returns a new DataFrame with data from one or more columns of the base DataFrame
- **where** returns a new DataFrame with rows meeting specified query criteria (alias for **filter**)

49

## DataFrame Query Strings

- Some query operations take strings containing simple query expressions

- Such as `select` and `where`

- Example: `select`

age	name	pcode
null	Alice	94304
30	Brayden	94304
19	Carla	10036
46	Diana	null
null	Étienne	94104

`peopleDF.  
select("age")`

age
null
30
19
46
null

`peopleDF.  
select("name", "age")`

name	age
Alice	null
Brayden	30
Carla	19
Diana	46
Étienne	null

50

## Querying DataFrames using Columns


§ Columns can be referenced in multiple ways

■ Scala

```
val ageDF = peopleDF.select(peopleDF("age"))
```

```
val ageDF = peopleDF.select($"age")
```

age	name	pcode
null	Alice	94304
30	Brayden	94304
19	Carla	10036
46	Diana	null
null	Étienne	94104



age
null
30
19
46
null

51

## Joining DataFrames


§ A basic inner join when join column is in both DataFrames

age	name	pcode
null	Alice	94304
30	Brayden	94304
19	Carla	10036
46	Diana	null
null	Étienne	94104

pcode	city	state
10036	New York	NY
87501	Santa Fe	NM
94304	Palo Alto	CA
94104	San Francisco	CA

Language: Python/Scala

```
peopleDF.join(pcodesDF, "pcode")
```



pcode	age	name	city	state
94304	null	Alice	Palo Alto	CA
94304	30	Brayden	Palo Alto	CA
10036	19	Carla	New York	NY
94104	null	Étienne	San Francisco	CA

52

## Joining DataFrames

- Specify type of join as inner (default), outer, left\_outer, right\_outer, or leftsemi

age	name	pcode
null	Alice	94304
30	Brayden	94304
19	Carla	10036
46	Diana	null
null	Étienne	94104

Language: Python  
`peopleDF.join(pcodesDF, "pcode", "left_outer")`

Language: Scala  
`peopleDF.join(pcodesDF, Array("pcode"), "left_outer")`

pcode	city	state
10036	New York	NY
87501	Santa Fe	NM
94304	Palo Alto	CA
94104	San Francisco	CA

pcode	age	name	city	state
94304	null	Alice	Palo Alto	CA
94304	30	Brayden	Palo Alto	CA
10036	19	Carla	New York	NY
null	46	Diana	null	null
94104	null	Étienne	San Francisco	CA

53

## SQL Queries

§ When using HiveContext, you can query Hive/Impala tables using HiveQL

– Returns a DataFrame

Language: Python/Scala  
`sqlContext.sql("""SELECT * FROM customers WHERE name LIKE "A%" """)`

Table: customers

cust_id	name	country
001	Ani	us
002	Bob	ca
003	Carlos	mx
...	...	...



cust_id	name	country
001	Ani	us

54

## Saving DataFrames

- § **Data in DataFrames can be saved to a data source**
- § **Use DataFrame.write to create a DataFrameWriter**
- § **DataFrameWriter provides convenience functions to externally save the data represented by a DataFrame**
- jdbc** inserts into a new or existing table in a database
- json** saves as a JSON file
- parquet** saves as a Parquet file
- orc** saves as an ORC file
- text** saves as a text file (string data in a single column only)
- saveAsTable** saves as a Hive/Impala table (**HiveContext** only)

Language: Python/Scala

```
peopleDF.write.saveAsTable("people")
```

55

## Options for Saving DataFrames

- § **DataFrameWriter option methods**
- format** specifies a data source type
- mode** determines the behavior if file or table already exists:  
overwrite, append, ignore or error (default is error)
- partitionBy** stores data in partitioned directories in the form  
*column=value* (as with Hive/Impala partitioning)
- options** specifies properties for the target data source
- save** is the generic base function to write the data

Language: Python/Scala

```
peopleDF.write.  
  format("parquet").  
  mode("append").  
  partitionBy("age").  
  saveAsTable("people")
```

56

## DataFrames and RDDs

### § DataFrames are built on RDDs

- Base RDDs contain **Row** objects
- Use **rdd** to get the underlying RDD

```
peopleRDD = peopleDF.rdd
```

peopleDF

age	name	pcode
null	Alice	94304
30	Brayden	94304
19	Carla	10036
46	Diana	null
null	Étienne	94104

peopleRDD

Row[null,Alice,94304]
Row[30,Brayden,94304]
Row[19,Carla,10036]
Row[46,Diana,null]
Row[null,Étienne,94104]

57

## DataFrames and RDDs

### § Row RDDs have all the standard Spark actions and transformations

- Actions: **collect**, **take**, **count**, and so on
- Transformations: **map**, **flatMap**, **filter**, and so on

### § Row RDDs can be transformed into pair RDDs to use map-reduce methods

### § DataFrames also provide convenience methods (such as **map**, **flatMap**, and **foreach**) for converting to RDDs

58

## Working with Row Objects

- Use **Array**-like syntax to return values with type **Any**
- row(*n*)** returns element in the *n*th column
- row.fieldIndex("age")** returns index of the **age** column
- Use methods to get correctly typed values
- row.getAs[Long]("age")**
- Use type-specific **get** methods to return typed values
- row.getString(*n*)** returns *n*th column as a string
- row.getInt(*n*)** returns *n*th column as an integer
- And so on

59

## Example: Extracting Data from Row Objects

### ■ Extract data from Row objects

Language: Python

```
peopleRDD = peopleDF \
    .map(lambda row: (row.pcode, row.name))
peopleByPCode = peopleRDD \
    .groupByKey()
```

Language: Scala

```
val peopleRDD = peopleDF.
  map(row =>
    (row(row.fieldIndex("pcode")),
     row(row.fieldIndex("name"))))
val peopleByPCode = peopleRDD.
  groupByKey()
```

Row[null,Alice,94304]
Row[30,Brayden,94304]
Row[19,Carla,10036]
Row[46,Diana,null]
Row[null,Étienne,94104]

(94304,Alice)
(94304,Brayden)
(10036,Carla)
(null,Diana)
(94104,Étienne)

(null,[Diana])
(94304,[Alice,Brayden])
(10036,[Carla])
(94104,[Étienne])

60

## Converting RDDs to DataFrames

§ You can also create a DF from an RDD using `createDataFrame`

```
import org.apache.spark.sql.types._
import org.apache.spark.sql.Row
val schema = StructType(Array(
  StructField("age", IntegerType, true),
  StructField("name", StringType, true),
  StructField("pcode", StringType, true)))
val rowRDD = sc.parallelize(Array(Row(40, "Abram", "01601"),
                                   Row(16, "Lucia", "87501")))
val myDF = sqlContext.createDataFrame(rowRDD, schema)
```

Language: Scala

61

## Working with Spark RDDs, Pair-RDDs

62

## RDD Operations

### Transformations

map()  
 flatMap()  
 filter()  
 union()  
 intersection()  
 distinct()  
 groupByKey()  
 reduceByKey()  
 sortByKey()  
 join()  
 ...

### Actions

count()  
 collect()  
 first(), top(n)  
 take(n), takeOrdered(n)  
 countByValue()  
 reduce()  
 foreach()  
 ...

Hanoi University of Science and Technology

© 2019 Binh Minh  
 Nguyen  
 63

63

## Lambda Expression

### PySpark WordCount example:

```
input_file = sc.textFile("/path/to/text/file")
map = input_file.flatMap(lambda line: line.split(" ")) \
    .map(lambda word: (word, 1))
counts = map.reduceByKey(lambda a, b: a + b)
counts.saveAsTextFile("/path/to/output/")
```

**lambda arguments: expression**

Hanoi University of Science and Technology

© 2019 Binh Minh  
 Nguyen  
 64

64



## PySpark RDD API

<https://spark.apache.org/docs/latest/api/python/pyspark.html#pyspark.RDD>

`map(f, preservesPartitioning=False)` [\[source\]](#)

Return a new RDD by applying a function to each element of this RDD.

```
>>> rdd = sc.parallelize(["b", "a", "c"])
>>> sorted(rdd.map(lambda x: (x, 1)).collect())
[('a', 1), ('b', 1), ('c', 1)]
```

`flatMap(f, preservesPartitioning=False)` [\[source\]](#)

Return a new RDD by first applying a function to all elements of this RDD, and then flattening the results.

```
>>> rdd = sc.parallelize([2, 3, 4])
>>> sorted(rdd.flatMap(lambda x: range(1, x)).collect())
[1, 1, 1, 2, 2, 3]
>>> sorted(rdd.flatMap(lambda x: [(x, x), (x, x)]).collect())
[(2, 2), (2, 2), (3, 3), (3, 3), (4, 4), (4, 4)]
```

© 2019 Binh Minh  
Nguyen

Hanoi University of Science and Technology

65

65

## Practice with flight data (1)

Data: **airports.dat** (<https://openflights.org/data.html>)

[Airport ID, Name, City, Country, IATA, ICAO, Latitude, Longitude, Altitude, Timezone, DST, Tz database, Type, Source]

**Try to do somethings:**

- Create RDD from textfile
- Count the number of airports
- Filter by country
- Group by country
- Count the number of airports in each country

© 2019 Binh Minh  
Nguyen

Hanoi University of Science and Technology

66

66

## Practice with flight data (2)

- Data: **airports.dat** (<https://openflights.org/data.html>)

*[Airport ID, Name, City, Country, IATA, ICAO, Latitude, Longitude, Altitude, Timezone, DST, Tz database, Type, Source]*

- Data: **routes.dat**

*[Airline, Airline ID, Source airport, Source airport ID, Destination airport, Destination airport ID, Codeshare, Stops, Equipment]*

### Try to do somethings:

- Join 2 RDD
- Count the number of flights arriving in each country

© 2019 Binh Minh  
Nguyen

67

Hanoi University of Science and Technology

67

## Working with DataFrame and Spark SQL

© 2019 Binh Minh  
Nguyen

68

Hanoi University of Science and Technology

68

## Creating a DataFrame(1)

```
%pyspark
from pyspark.sql import *

Employee = Row("firstName", "lastName", "email", "salary")

employee1 = Employee('Basher', 'armbrust', 'bash@edureka.co', 100000)
employee2 = Employee('Daniel', 'meng', 'daniel@stanford.edu', 120000)
employee3 = Employee('Muriel', None, 'muriel@waterloo.edu', 140000)
employee4 = Employee('Rachel', 'wendell', 'rach_3@edureka.co', 160000)
employee5 = Employee('Zach', 'galifianakis', 'zach_g@edureka.co', 160000)

employees = [employee1, employee2, employee3, employee4, employee5]

print(Employee[0])

print(employees)

dframe = spark.createDataFrame(employees)
dframe.show()
```

© 2019 Binh Minh  
Nguyen

Hanoi University of Science and Technology

69

69

## Creating a DataFrame

### From CSV file:

```
%pyspark
flightData2015 = spark\
    .read\
    .option("inferSchema", "true")\
    .option("header", "true")\
    .csv("/usr/zeppelin/module9/2015-summary.csv")

flightData2015.show()
```

### From RDD:

```
%pyspark
from pyspark.sql import *
list = [('Ankit', 25), ('Jalfaizy', 22), ('saurabh', 20), ('Bala', 26)]
rdd = sc.parallelize(list)
people = rdd.map(lambda x: Row(name=x[0], age=int(x[1])))
df = spark.createDataFrame(people)

df.show()
```

© 2019 Binh Minh  
Nguyen

70

70

## DataFrame APIs

- **DataFrame**: show(), collect(), createOrReplaceTempView(), distinct(), filter(), select(), count(), groupBy(), join()...
- **Column**: like()
- **Row**: row.key, row[key]
- **GroupedData**: count(), max(), min(), sum(), ...

<https://spark.apache.org/docs/latest/api/python/pyspark.sql.html>

© 2019 Binh Minh  
Nguyen

Hanoi University of Science and Technology

71

71

## Spark SQL

- Create a temporary view
- Query using SQL syntax

```
%pyspark
flightData2015.createOrReplaceTempView("flight_data_2015")

maxSql = spark.sql("""
SELECT DEST_COUNTRY_NAME, sum(count) as destination_total
FROM flight_data_2015
GROUP BY DEST_COUNTRY_NAME
ORDER BY sum(count) DESC
LIMIT 5
""")

maxSql.show()
```

© 2019 Binh Minh  
Nguyen

Hanoi University of Science and Technology

72

72