

- Morita. 6 kW Bidirectional, Insulated On-board Charger With GaN Gate Injection Transistors. In PCIM Europe, p. Nuremberg, Germany, 2017.
- [44] Zhu, Ke; O'Grady, Matt; Dodge, Jonathan; Bendel, John; "1.5 kW single phase CCM totem-pole PFC using 650V GaN MOSFETs," *IEEE 2016 IEEE 4th Workshop on Wide Bandgap Power Semiconductor Applications (WiPDA)* - Fayetteville, AR, USA (2016.11.7-2016.11.9), pp. 1-4, Nov. 2016.
- [45] L. Huber, B. T. Irving, and M. M. Jovanovic, "Effect of voltage and switching-frequency limitation on line-current distortion in boundary boost PFC converters," *IEEE Trans. Power Electron.*, vol. 24, no. 2, pp. 339–347, Feb. 2009.
- [46] C. Marxgut, J. Biela, and J. W. Kolar, "Interleaved triangular current mode (TCM) resonant transition, single phase PFC rectifier with high power density," in *Proc. Int. Power Electron. Conf. (IPEC)*, pp. 1725–1732, 2010.
- [47] B. Su, J. Zhang, and Z. Lu, "Totem-Pole boost bridgeless PFC with simple zero-current detection and full-range ZVS operating in DCM/CCM," *IEEE Trans. Power Electron.*, vol. 26, no. 2, pp. 339–347, Feb. 2011.
- [48] E. Firmansyah, S. Tomioka, S. Abe, M. Shoyama, and T. Ueda, "A critical-conduction-mode bridgeless interleaved boost converter with current correction," in *Proc. 31st Int. Telecommun. Energy Conf.*, Oct. 2010, pp. 1–4.
- [49] C. Marxgut, F. Krismer, D. Bortis and J. W. Kolar, "Ultra-High Power Density Triangular Current Mode (TCM) Single-Phase PFC Rectifier," *Power Electron.*, vol. 29, no. 2, pp. 873–882, Feb. 2014.