

# Team notebook

HCMUS-IdentityImbalance

February 19, 2022

## Contents

<b>1 Algorithms</b>	<b>1</b>	<b>5 Graphs</b>	<b>11</b>	9.7 miller rabin . . . . .	20
1.1 Mo's algorithm on trees . . . . .	1	5.1 bridges . . . . .	11	9.8 mod integer . . . . .	21
1.2 Mo's algorithm . . . . .	1	5.2 delete on dsu . . . . .	12	9.9 mod inv . . . . .	21
1.3 parallel binary search . . . . .	1	5.3 euler path . . . . .	12	9.10 mod mul . . . . .	21
<b>2 DP Optimizations</b>	<b>2</b>	5.4 karp min mean cycle . . . . .	13	9.11 mod pow . . . . .	21
2.1 convex hull trick . . . . .	2	5.5 konig's theorem . . . . .	13	9.12 number theoretic transform . . . . .	21
2.2 divide and conquer . . . . .	2	5.6 matching . . . . .	13	9.13 pollard rho factorize . . . . .	21
<b>3 Data structures</b>	<b>3</b>	5.7 max flow min cost . . . . .	14	9.14 primes . . . . .	22
3.1 dsu . . . . .	3	5.8 minimum path cover in DAG . . . . .	15	9.15 totient sieve . . . . .	22
3.2 fake update . . . . .	3	5.9 planar graph (euler) . . . . .	15	9.16 totient . . . . .	22
3.3 fenwick tree . . . . .	3	5.10 two sat . . . . .	15	<b>10 Strings</b>	<b>22</b>
3.4 hash table . . . . .	4	<b>6 Math</b>	<b>16</b>	10.1 Incremental Aho Corasick . . . . .	22
3.5 heavy light decomposition . . . . .	4	6.1 Lucas theorem . . . . .	16	10.2 minimal string rotation . . . . .	23
3.6 persistent array . . . . .	5	6.2 cumulative sum of divisors . . . . .	16	10.3 suffix array . . . . .	23
3.7 persistent seg tree . . . . .	5	6.3 fft . . . . .	16	10.4 suffix automaton . . . . .	24
3.8 persistent segment (v2) . . . . .	6	6.4 fibonacci properties . . . . .	17	10.5 z algorithm . . . . .	24
3.9 persistent trie . . . . .	6	6.5 gauss . . . . .	17	<b>1 Algorithms</b>	
3.10 segment tree . . . . .	7	6.6 others . . . . .	17	<b>1.1 Mo's algorithm on trees</b>	
3.11 sparse table . . . . .	7	6.7 polynomials . . . . .	17		
3.12 trie . . . . .	8	6.8 sigma function . . . . .	18		
<b>4 Geometry</b>	<b>8</b>	6.9 system different constraints . . . . .	18		
4.1 center 2 points + radius . . . . .	8	<b>7 Matrix</b>	<b>18</b>		
4.2 closest pair problem . . . . .	8	7.1 matrix . . . . .	18		
4.3 convex diameter . . . . .	9	<b>8 Misc</b>	<b>19</b>		
4.4 pick theorem . . . . .	9	8.1 dates . . . . .	19		
4.5 squares . . . . .	10	<b>9 Number theory</b>	<b>19</b>		
4.6 template . . . . .	10	9.1 convolution . . . . .	19		
4.7 triangles . . . . .	11	9.2 crt . . . . .	19		
		9.3 diophantine equations . . . . .	20		
		9.4 discrete logarithm . . . . .	20		
		9.5 ext euclidean . . . . .	20		
		9.6 highest exponent factorial . . . . .	20		

```
/*
-----
Problem:
-----
https://www.spoj.com/problems/COT2/
Given a tree with N nodes and Q queries. Each node
has an integer weight.
Each query provides two numbers u and v, ask for
how many different integers weight of nodes
there are on path from u to v.

-----
Modify DFS:
-----
```

For each node  $u$ , maintain the start and the end DFS time. Let's call them  $ST(u)$  and  $EN(u)$ .  
 $\Rightarrow$  For each query, a node is considered if its occurrence count is one.

-----  
 Query solving:  
 -----

Let's query be  $(u, v)$ . Assume that  $ST(u) \leq ST(v)$ .  
 Denotes  $P$  as  $LCA(u, v)$ .

Case 1:  $P = u$   
 Our query would be in range  $[ST(u), ST(v)]$ .

Case 2:  $P \neq u$   
 Our query would be in range  $[EN(u), ST(v)] + [ST(p), ST(p)]$   
 \*/

```
void update(int &L, int &R, int qL, int qR){
    while (L > qL) add(--L);
    while (R < qR) add(++R);

    while (L < qL) del(L++);
    while (R > qR) del(R--);
}
```

```
vector<int> MoQueries(int n, vector<query> Q){
    block_size = sqrt((int)nodes.size());
    sort(Q.begin(), Q.end(), [](const query &A,
        const query &B){
        return (ST[A.l]/block_size !=
            ST[B.l]/block_size)?
            (ST[A.l]/block_size <
                ST[B.l]/block_size) : (ST[A.r] <
                ST[B.r]);
    });
    vector<int> res;
    res.resize((int)Q.size());

    LCA lca;
    lca.initialize(n);

    int L = 1, R = 0;
    for(query q: Q){
        int u = q.l, v = q.r;
        if(ST[u] > ST[v]) swap(u, v); // assume that
            S[u] <= S[v]
        int parent = lca.get(u, v);

        if(parent == u){
            int qL = ST[u], qR = ST[v];
            update(L, R, qL, qR);
        }else{
            int qL = EN[u], qR = ST[v];
```

```
        update(L, R, qL, qR);
        if(cnt_val[a[parent]] == 0)
            res[q.pos] += 1;
    }

    res[q.pos] += cur_ans;
}
return res;
}
```

## 1.2 Mo's algorithm

```
/*
https://www.spoj.com/problems/FREQ2/
*/
vector<int> MoQueries(int n, vector<query> Q){
    block_size = sqrt(n);
    sort(Q.begin(), Q.end(), [](const query &A,
        const query &B){
        return (A.l/block_size != B.l/block_size)?
            (A.l/block_size < B.l/block_size) :
            (A.r < B.r);
    });
    vector<int> res;
    res.resize((int)Q.size());

    int L = 1, R = 0;
    for(query q: Q){
        while (L > q.l) add(--L);
        while (R < q.r) add(++R);

        while (L < q.l) del(L++);
        while (R > q.r) del(R--);

        res[q.pos] = calc(1, R-L+1);
    }
    return res;
}
```

## 1.3 parallel binary search

```
int lo[N], mid[N], hi[N];
vector<int> vec[N];

void clear() //Reset
{
    memset(bit, 0, sizeof(bit));
}
```

```
void apply(int idx) //Apply ith update/query
{
    if(ql[idx] <= qr[idx])
        update(ql[idx], qa[idx]),
        update(qr[idx]+1, -qa[idx]);
    else
    {
        update(1, qa[idx]);
        update(qr[idx]+1, -qa[idx]);
        update(ql[idx], qa[idx]);
    }
}

bool check(int idx) //Check if the condition is
    satisfied
{
    int req=reqd[idx];
    for(auto &it:owns[idx])
    {
        req-=pref(it);
        if(req<0)
            break;
    }
    if(req<=0)
        return 1;
    return 0;
}

void work()
{
    for(int i=1;i<=q;i++)
        vec[i].clear();
    for(int i=1;i<=n;i++)
        if(mid[i]>0)
            vec[mid[i]].push_back(i);
    clear();
    for(int i=1;i<=q;i++)
    {
        apply(i);
        for(auto &it:vec[i]) //Add
            appropriate check conditions
        {
            if(check(it))
                hi[it]=i;
            else
                lo[it]=i+1;
        }
    }
}

void parallel_binary()
{
    for(int i=1;i<=n;i++)
        lo[i]=1, hi[i]=q+1;
    bool changed = 1;
```

```

while(changed)
{
    changed=0;
    for(int i=1;i<=n;i++)
    {
        if(lo[i]<hi[i])
        {
            changed=1;
            mid[i]=(lo[i] +
                    hi[i])/2;
        }
        else
            mid[i]=-1;
    }
    work();
}

```

---

## 2 DP Optimizations

### 2.1 convex hull trick

```

#define long long long
#define pll pair <long, long>
#define all(c) c.begin(), c.end()
#define fastio ios_base::sync_with_stdio(false);
cin.tie(0)

struct line{
    long a, b;
    line() {};
    line(long a, long b) : a(a), b(b) {};
    bool operator < (const line &A) const {
        return pll(a,b) < pll(A.a,A.b);
    }
};

bool bad(line A, line B, line C){
    return (C.b - B.b) * (A.a - B.a) <= (B.b - A.b)
        * (B.a - C.a);
}

void addLine(vector<line> &memo, line cur){
    int k = memo.size();
    while (k >= 2 && bad(memo[k - 2], memo[k - 1],
        cur)){
        memo.pop_back();
        k--;
    }
    memo.push_back(cur);
}

```

```

long Fn(line A, long x){
    return A.a * x + A.b;
}

long query(vector<line> &memo, long x){
    int lo = 0, hi = memo.size() - 1;
    while (lo != hi){
        int mi = (lo + hi) / 2;
        if (Fn(memo[mi], x) > Fn(memo[mi + 1], x)){
            lo = mi + 1;
        }
        else hi = mi;
    }
    return Fn(memo[lo], x);
}

const int N = 1e6 + 1;
long dp[N];

int main()
{
    fastio;
    int n, c; cin >> n >> c;
    vector<line> memo;
    for (int i = 1; i <= n; i++){
        long val; cin >> val;
        addLine(memo, {-2 * val, val * val + dp[i -
            1]});
        dp[i] = query(memo, val) + val * val + c;
    }
    cout << dp[n] << '\n';
    return 0;
}

```

---

### 2.2 divide and conquer

```

/**
 * recurrence:
 *   dp[k][i] = min dp[k-1][j] + c[i][j - 1], for
 *   all j > i;
 *
 * "comp" computes dp[k][i] for all i in 0(n log n)
 *   (k is fixed)
 *
 * Problems:
 *   https://icpc.kattis.com/problems/branch
 *   http://codeforces.com/contest/321/problem/E
 */

void comp(int l, int r, int le, int re) {
    if (l > r) return;

```

```

int mid = (l + r) >> 1;

int best = max(mid + 1, le);
dp[cur][mid] = dp[cur ^ 1][best] + cost(mid, best
    - 1);
for (int i = best; i <= re; i++) {
    if (dp[cur][mid] > dp[cur ^ 1][i] + cost(mid, i
        - 1)) {
        best = i;
        dp[cur][mid] = dp[cur ^ 1][i] + cost(mid, i -
            1);
    }
}

comp(l, mid - 1, le, best);
comp(mid + 1, r, best, re);
}

```

---

## 3 Data structures

### 3.1 dsu

```

class DSU{
public:
    vector <int> parent;
    void initialize(int n){
        parent.resize(n+1, -1);
    }

    int findSet(int u){
        while(parent[u] > 0)
            u = parent[u];
        return u;
    }

    void Union(int u, int v){
        int x = parent[u] + parent[v];
        if(parent[u] > parent[v]){
            parent[v] = x;
            parent[u] = v;
        }else{
            parent[u] = x;
            parent[v] = u;
        }
    }
};

```

---

### 3.2 fake update

```

vector<int> fake_bit[MAXN];

void fake_update(int x, int y, int limit_x){
    for(int i = x; i < limit_x; i += i&(-i))
        fake_bit[i].pb(y);
}

void fake_get(int x, int y){
    for(int i = x; i >= 1; i -= i&(-i))
        fake_bit[i].pb(y);
}

vector<int> bit[MAXN];

void update(int x, int y, int limit_x, int val){
    for(int i = x; i < limit_x; i += i&(-i)){
        for(int j = lower_bound(fake_bit[i].begin(),
            fake_bit[i].end(), y) -
            fake_bit[i].begin(); j <
            fake_bit[i].size(); j += j&(-j))
            bit[i][j] = max(bit[i][j], val);
    }
}

int get(int x, int y){
    int ans = 0;
    for(int i = x; i >= 1; i -= i&(-i)){
        for(int j = lower_bound(fake_bit[i].begin(),
            fake_bit[i].end(), y) -
            fake_bit[i].begin(); j >= 1; j -=
            j&(-j))
            ans = max(ans, bit[i][j]);
    }
    return ans;
}

int main(){
    _io
    int n; cin >> n;
    vector<int> Sx, Sy;
    for(int i = 1; i <= n; i++){
        cin >> a[i].fi >> a[i].se;
        Sx.pb(a[i].fi);
        Sy.pb(a[i].se);
    }
    unique_arr(Sx);
    unique_arr(Sy);
    // unique all value
    for(int i = 1; i <= n; i++){
        a[i].fi = lower_bound(Sx.begin(), Sx.end(),
            a[i].fi) - Sx.begin();
        a[i].se = lower_bound(Sy.begin(), Sy.end(),
            a[i].se) - Sy.begin();
    }
}

```

```

// do fake BIT update and get operator
for(int i = 1; i <= n; i++){
    fake_get(a[i].fi-1, a[i].se-1);
    fake_update(a[i].fi, a[i].se,
        (int)Sx.size());
}

for(int i = 0; i < Sx.size(); i++){
    fake_bit[i].pb(INT_MIN); // avoid zero
    sort(fake_bit[i].begin(), fake_bit[i].end());
    fake_bit[i].resize(unique(fake_bit[i].begin(),
        fake_bit[i].end()) -
        fake_bit[i].begin());
    bit[i].resize((int)fake_bit[i].size(), 0);
}

// real update, get operator
int res = 0;
for(int i = 1; i <= n; i++){
    int maxCurLen = get(a[i].fi-1, a[i].se-1) +
        1;
    res = max(res, maxCurLen);
    update(a[i].fi, a[i].se, (int)Sx.size(),
        maxCurLen);
}
}

```

### 3.3 fenwick tree

```

template<typename T>
class FenwickTree{
    vector<T> fenw;
    int n;
public:
    void initialize(int _n){
        this->n = _n;
        fenw.resize(n+1);
    }

    void update(int id, T val) {
        while (id <= n) {
            fenw[id] += val;
            id += id&(-id);
        }
    }

    T get(int id){
        T ans{};
        while(id >= 1){
            ans += fenw[id];
            id -= id&(-id);
        }
    }
}

```

```

    return ans;
}
};

```

### 3.4 hash table

```

/*
 * Micro hash table, can be used as a set.
 * Very efficient vs std::set
 */

const int MN = 1001;
struct ht {
    int _s[(MN + 10) >> 5];
    int len;
    void set(int id) {
        len++;
        _s[id >> 5] |= (1LL << (id & 31));
    }
    bool is_set(int id) {
        return _s[id >> 5] & (1LL << (id & 31));
    }
};

```

### 3.5 heavy light decomposition

```

#include <bits/stdc++.h>
using namespace std;
using pii = pair<int, int>;
using pll = pair<int64_t, int64_t>;
using ld = long double;

#define long int64_t
#define all(c) c.begin(), c.end()
#define fastio ios_base::sync_with_stdio(false);
cin.tie(0)

template<class T> inline void chmin(T &a, const T&
    val) { if (a > val) a = val; }
template<class T> inline void chmax(T &a, const T&
    val) { if (a < val) a = val; }
template<class T> long sqr(T a) { return 1ll * a *
    a; }
template<class T> void compress(T &a) {
    sort(all(a)); a.resize(unique(all(a)) -
    a.begin()); }
template<class T> T power(T x, long n){
    T res = 1;
    for (; n; x *= x, n >>= 1){

```



```
int main()
{
    fastio;
    int T = 1; //cin >> T;
    while (T--){
        solve();
    }
    return 0;
}
```

### 3.6 persistent array

```
struct node {
    node *l, *r;
    int val;

    node (int x) : l(NULL), r(NULL), val(x) {}
    node () : l(NULL), r(NULL), val(-1) {}
};

typedef node* pnode;

pnode update(pnode cur, int l, int r, int at, int
    what) {
    pnode ans = new node();

    if (cur != NULL) {
        *ans = *cur;
    }
    if (l == r) {
        ans->val = what;
        return ans;
    }
    int m = (l + r) >> 1;
    if (at <= m) ans->l = update(ans->l, l, m, at,
        what);
    else ans->r = update(ans->r, m + 1, r, at,
        what);
    return ans;
}

int get(pnode cur, int l, int r, int at) {
    if (cur == NULL) return 0;
    if (l == r) return cur->val;
    int m = (l + r) >> 1;
    if (at <= m) return get(cur->l, l, m, at);
    else return get(cur->r, m + 1, r, at);
}
```

### 3.7 persistent seg tree

*/\* Problem: <https://cses.fi/problemset/task/1737/>  
 \* Your task is to maintain a list of arrays which  
 initially has a single array. You have to  
 process the following types of queries:  
 \* Query 1: Set the value a in array k to x.  
 \* Query 2: Calculate the sum of values in range  
 [a,b] in array k.  
 \* Query 3: Create a copy of array k and add it to  
 the end of the list.  
 \* Idea to create a persistent segment tree to save  
 all version of array.  
 \*/*

```
vector <int> a;
```

```
struct Node{
    int val;
    Node *left, *right;
    Node(){
        left = right = NULL;
        val = 0;
    }
    Node(Node* l, Node *r, int v){
        left = l;
        right = r;
        val = v;
    }
};
```

```
void build(Node* &cur, int l, int r){
    if(l == r){
        cur->val = a[l];
        return;
    }
    int mid = (l+r) >> 1;
    cur->left = new Node();
    cur->right = new Node();
    build(cur->left, l, mid);
    build(cur->right, mid+1, r);
    cur->val = cur->left->val + cur->right->val;
}
```

```
void update(Node* prev, Node* &cur, int l, int r,
    int i, int val){
    if(i < l || r < i)
        return;
    if(l == r && l == i){
        cur->val = val;
        return;
    }
    int mid = (l+r) >> 1;
    if(i <= mid){
```

```
        cur->right = prev->right;
        cur->left = new Node();
        update(prev->left, cur->left, l, mid, i,
            val);
    }else{
        cur->left = prev->left;
        cur->right = new Node();
        update(prev->right, cur->right, mid+1, r, i,
            val);
    }
    cur->val = cur->left->val + cur->right->val;
}

int get(Node* cur, int l, int r, int u, int v){
    if(v < l || r < u)
        return 0;
    if(u <= l && r <= v){
        return cur->val;
    }
    int mid = (l+r) >> 1;
    int L = get(cur->left, l, mid, u, v);
    int R = get(cur->right, mid+1, r, u, v);
    return L + R;
}

Node* ver[MAXN];
```

### 3.8 persistent segment (v2)

```
/*  

    Find distinct numbers in a range (online query  

    with persistent array)  

    */
struct Node{
    int lnode, rnode;
    int sum;
    Node(){
        lnode = rnode = sum = 0;
    }
}ver[MAXN * 120];
int sz = 0;

int build_new_node(int l, int r){
    int next = ++sz;
    if(l != r){
        int mid = (l+r) >> 1;
        ver[next].lnode = build_new_node(l, mid);
        ver[next].rnode = build_new_node(mid+1, r);
    }
    return next;
}
```

```

int update(int cur, int l, int r, int pos, int val){
    int next = ++sz;
    ver[next] = ver[cur];
    if(l == r){
        ver[next].sum = val;
        return next;
    }
    else{
        int mid = (l+r) >> 1;
        if(pos <= mid)
            ver[next].lnode = update(ver[cur].lnode,
                                     l, mid, pos, val);
        else
            ver[next].rnode = update(ver[cur].rnode,
                                     mid+1, r, pos, val);
    }
    ver[next].sum = ver[ver[next].lnode].sum +
                  ver[ver[next].rnode].sum;
    //cout << l << ' ' << r << ' ' << ver[next].sum
    << '\n';
    return next;
}

int get(int cur, int l, int r, int u, int v){
    if(r < u || l < v)
        return 0;
    if(u <= l && r <= v){
        return ver[cur].sum;
    }
    int mid = (l+r) >> 1;
    return get(ver[cur].lnode, l, mid, u, v) +
           get(ver[cur].rnode, mid+1, r, u, v);
}

```

### 3.9 persistent trie

```

// both tries can be tested with the problem:
// http://codeforces.com/problemset/problem/916/D

// Persistent binary trie (BST for integers)
const int MD = 31;

struct node_bin {
    node_bin *child[2];
    int val;

    node_bin() : val(0) {
        child[0] = child[1] = NULL;
    }
};

typedef node_bin* pnode_bin;

```

```

pnode_bin copy_node(pnode_bin cur) {
    pnode_bin ans = new node_bin();
    if (cur) *ans = *cur;
    return ans;
}

pnode_bin modify(pnode_bin cur, int key, int inc,
                 int id = MD) {
    pnode_bin ans = copy_node(cur);
    ans->val += inc;
    if (id >= 0) {
        int to = (key >> id) & 1;
        ans->child[to] = modify(ans->child[to], key,
                               inc, id - 1);
    }
    return ans;
}

int sum_smaller(pnode_bin cur, int key, int id =
                MD) {
    if (cur == NULL) return 0;
    if (id < 0) return 0; // strictly smaller
    // if (id == - 1) return cur->val; // smaller or
    // equal

    int ans = 0;
    int to = (key >> id) & 1;
    if (to) {
        if (cur->child[0]) ans += cur->child[0]->val;
        ans += sum_smaller(cur->child[1], key, id - 1);
    } else {
        ans = sum_smaller(cur->child[0], key, id - 1);
    }
    return ans;
}

// Persistent trie for strings.
const int MAX_CHILD = 26;
struct node {
    node *child[MAX_CHILD];
    int val;
    node() : val(-1) {
        for (int i = 0; i < MAX_CHILD; i++) {
            child[i] = NULL;
        }
    }
};

```

```

typedef node* pnode;

pnode copy_node(pnode cur) {
    pnode ans = new node();
    if (cur) *ans = *cur;

```

```

    return ans;
}

pnode set_val(pnode cur, string &key, int val, int
              id = 0) {
    pnode ans = copy_node(cur);
    if (id >= int(key.size())) {
        ans->val = val;
    } else {
        int t = key[id] - 'a';
        ans->child[t] = set_val(ans->child[t], key,
                               val, id + 1);
    }
    return ans;
}

pnode get(pnode cur, string &key, int id = 0) {
    if (id >= int(key.size()) || !cur)
        return cur;
    int t = key[id] - 'a';
    return get(cur->child[t], key, id + 1);
}

```

### 3.10 segment tree

```

// Problem:
// https://codeforces.com/edu/course/2/lesson/4/1/practice
struct SegmentTree {
    #define m ((l + r) >> 1)
    #define lc (i << 1)
    #define rc (i << 1 | 1)
    vector<int> mn;
    int n;

    SegmentTree(int n = 0) : n(n){
        mn.resize(4 * n + 1, 0);
    }

    SegmentTree(const vector<int> &a) : n(a.size())
    {
        mn.resize(4 * n + 1, 0);
        function<void(int, int, int)> build =
            [&](int i, int l, int r){
                if (l == r){
                    mn[i] = a[l - 1];
                    return;
                }
                build(lc, l, m); build(rc, m + 1, r);
                mn[i] = min(mn[lc], mn[rc]);
            };
        build(1, 1, n);
    }
}

```

```

void update(int i, int l, int r, int p, long
val){
    if (l == r){
        mn[i] = val;
        return;
    }
    if (p <= m) update(lc, l, m, p, val);
    else update(rc, m + 1, r, p, val);
    mn[i] = min(mn[lc], mn[rc]);
}

int get(int i, int l, int r, int u, int v){
    if (v < l || r < u) return INF;
    if (u <= l && r <= v) return mn[i];
    return min(get(lc, l, m, u, v), get(rc, m +
1, r, u, v));
}

void update(int p, long val){
    update(1, 1, n, p, val);
}

int get(int l, int r){
    return get(1, 1, n, l, r);
}

#undef m
#undef lc
#undef rc
};

```

```

// Problem: There are two operations:
// 1 l r val: add the value val to the segment from
// 1 to r
// 2 l v: calculate the minimum of elements from l
// to r

```

```

struct LazySegmentTree {
#define m ((l + r) >> 1)
#define lc (i << 1)
#define rc (i << 1 | 1)
    vector<int> mn, lazy;
    int n;

    LazySegmentTree(int n = 0) : n(n){
        mn.resize(4 * n + 1, 0);
        lazy.resize(4 * n + 1, 0);
    }

```

```

    void push(int i, int l, int r){
        if (lazy[i] == 0) return;
        mn[i] += lazy[i];
        if (l != r){
            lazy[lc] += lazy[i];
            lazy[rc] += lazy[i];
        }
    }

```

```

    }
    lazy[i] = 0;
}

void update(int i, int l, int r, int u, int v,
int val){
    push(i, l, r);
    if (v < l || r < u) return;
    if (u <= l && r <= v){
        lazy[i] += val;
        push(i, l, r);
        return;
    }
    update(lc, l, m, u, v, val); update(rc, m +
1, r, u, v, val);
    mn[i] = min(mn[lc], mn[rc]);
}

int get(int i, int l, int r, int u, int v){
    push(i, l, r);
    if (v < l || r < u) return INF;
    if (u <= l && r <= v) return mn[i];
    return min(get(lc, l, m, u, v), get(rc, m +
1, r, u, v));
}

void update(int l, int r, int val){
    update(1, 1, n, l, r, val);
}

int get(int l, int r){
    return get(1, 1, n, l, r);
}

#undef m
#undef lc
#undef rc
};

```

### 3.11 sparse table

```

template <typename T, typename func =
    function<T(const T, const T)>>
struct SparseTable {
    func calc;
    int n;
    vector<vector<T>> ans;

    SparseTable() {}

    SparseTable(const vector<T>& a, const func& f)
        : n(a.size()), calc(f) {}

```

```

    int last = trunc(log2(n)) + 1;
    ans.resize(n);
    for (int i = 0; i < n; i++){
        ans[i].resize(last);
    }
    for (int i = 0; i < n; i++){
        ans[i][0] = a[i];
    }
    for (int j = 1; j < last; j++){
        for (int i = 0; i <= n - (1 << j); i++){
            ans[i][j] = calc(ans[i][j - 1],
                ans[i + (1 << (j - 1))][j - 1]);
        }
    }

    T query(int l, int r){
        assert(0 <= l && l <= r && r < n);
        int k = trunc(log2(r - l + 1));
        return calc(ans[l][k], ans[r - (1 << k) +
1][k]);
    }
};

```

### 3.12 trie

```

const int MN = 26; // size of alphabet
const int MS = 100010; // Number of states.

```

```

struct trie{
    struct node{
        int c;
        int a[MN];
    };

    node tree[MS];
    int nodes;

    void clear(){
        tree[nodes].c = 0;
        memset(tree[nodes].a, -1, sizeof tree[nodes].a);
        nodes++;
    }

    void init(){
        nodes = 0;
        clear();
    }

    int add(const string &s, bool query = 0){
        int cur_node = 0;
        for(int i = 0; i < s.size(); ++i){

```



```

int id = gid(s[i]);
if(tree[cur_node].a[id] == -1){
    if(query) return 0;
    tree[cur_node].a[id] = nodes;
    clear();
}
cur_node = tree[cur_node].a[id];
}
if(!query) tree[cur_node].c++;
return tree[cur_node].c;
}
};

```

## 4 Geometry

### 4.1 center 2 points + radius

```

vector<point> find_center(point a, point b, long
double r) {
    point d = (a - b) * 0.5;
    if (d.dot(d) > r * r) {
        return vector<point> ();
    }
    point e = b + d;
    long double fac = sqrt(r * r - d.dot(d));
    vector<point> ans;
    point x = point(-d.y, d.x);
    long double l = sqrt(x.dot(x));
    x = x * (fac / l);
    ans.push_back(e + x);
    x = point(d.y, -d.x);
    x = x * (fac / l);
    ans.push_back(e + x);
    return ans;
}

```

### 4.2 closest pair problem

```

struct point {
    double x, y;
    int id;
    point() {}
    point(double a, double b) : x(a), y(b) {}
};

double dist(const point &o, const point &p) {
    double a = p.x - o.x, b = p.y - o.y;
    return sqrt(a * a + b * b);
}

```

```

}

double cp(vector<point> &p, vector<point> &x,
vector<point> &y) {
    if (p.size() < 4) {
        double best = 1e100;
        for (int i = 0; i < p.size(); ++i)
            for (int j = i + 1; j < p.size(); ++j)
                best = min(best, dist(p[i], p[j]));
        return best;
    }

    int ls = (p.size() + 1) >> 1;
    double l = (p[ls - 1].x + p[ls].x) * 0.5;
    vector<point> xl(ls), xr(p.size() - ls);
    unordered_set<int> left;
    for (int i = 0; i < ls; ++i) {
        xl[i] = x[i];
        left.insert(x[i].id);
    }
    for (int i = ls; i < p.size(); ++i) {
        xr[i - ls] = x[i];
    }

    vector<point> yl, yr;
    vector<point> pl, pr;
    yl.reserve(ls); yr.reserve(p.size() - ls);
    pl.reserve(ls); pr.reserve(p.size() - ls);
    for (int i = 0; i < p.size(); ++i) {
        if (left.count(y[i].id))
            yl.push_back(y[i]);
        else
            yr.push_back(y[i]);

        if (left.count(p[i].id))
            pl.push_back(p[i]);
        else
            pr.push_back(p[i]);
    }

    double dl = cp(pl, xl, yl);
    double dr = cp(pr, xr, yr);
    double d = min(dl, dr);
    vector<point> yp; yp.reserve(p.size());
    for (int i = 0; i < p.size(); ++i) {
        if (fabs(y[i].x - l) < d)
            yp.push_back(y[i]);
    }
    for (int i = 0; i < yp.size(); ++i) {
        for (int j = i + 1; j < yp.size() && j < i + 7; ++j) {
            d = min(d, dist(yp[i], yp[j]));
        }
    }
    return d;
}

```

```

}

double closest_pair(vector<point> &p) {
    vector<point> x(p.begin(), p.end());
    sort(x.begin(), x.end(), [](const point &a, const
point &b) {
        return a.x < b.x;
    });
    vector<point> y(p.begin(), p.end());
    sort(y.begin(), y.end(), [](const point &a, const
point &b) {
        return a.y < b.y;
    });
    return cp(p, x, y);
}

```

### 4.3 convex diameter

```

struct point{
    int x, y;
};

struct vec{
    int x, y;
};

vec operator - (const point &A, const point &B){
    return vec{A.x - B.x, A.y - B.y};
}

int cross(vec A, vec B){
    return A.x*B.y - A.y*B.x;
}

int cross(point A, point B, point C){
    int val = A.x*(B.y - C.y) + B.x*(C.y - A.y) +
C.x*(A.y - B.y);
    if(val == 0)
        return 0; // coline
    if(val < 0)
        return 1; // clockwise
    return -1; //counter clockwise
}

vector <point> findConvexHull(vector <point>
points){
    vector <point> convex;
    sort(points.begin(), points.end(), [](const
point &A, const point &B){
        return (A.x == B.x)? (A.y < B.y): (A.x <
B.x);
    });
}

```

```

vector <point> Up, Down;
point A = points[0], B = points.back();
Up.push_back(A);
Down.push_back(A);

for(int i = 0; i < points.size(); i++){
    if(i == points.size()-1 || cross(A,
        points[i], B) > 0){
        while(Up.size() > 2 &&
            cross(Up[Up.size()-2],
                Up[Up.size()-1], points[i]) <= 0)
            Up.pop_back();
        Up.push_back(points[i]);
    }
    if(i == points.size()-1 || cross(A,
        points[i], B) < 0){
        while(Down.size() > 2 &&
            cross(Down[Down.size()-2],
                Down[Down.size()-1], points[i]) >= 0)
            Down.pop_back();
        Down.push_back(points[i]);
    }
}

for(int i = 0; i < Up.size(); i++)
    convex.push_back(Up[i]);
for(int i = Down.size()-2; i > 0; i--)
    convex.push_back(Down[i]);
return convex;
}

int dist(point A, point B){
    return (A.x - B.x)*(A.x - B.x) + (A.y -
        B.y)*(A.y - B.y);
}

double findConvexDiameter(vector <point>
    convexHull){
    int n = convexHull.size();

    int is = 0, js = 0;
    for(int i = 1; i < n; i++){
        if(convexHull[i].y > convexHull[is].y)
            is = i;
        if(convexHull[js].y > convexHull[i].y)
            js = i;
    }

    int maxd = dist(convexHull[is], convexHull[js]);
    int i, maxi, j, maxj;
    i = maxi = is;
    j = maxj = js;
    do{
        int ni = (i+1)%n, nj = (j+1)%n;

```

```

        if(cross(convexHull[ni] - convexHull[i],
            convexHull[nj] - convexHull[j]) <= 0){
            j = nj;
        }else{
            i = ni;
        }
        int d = dist(convexHull[i], convexHull[j]);
        if(d > maxd){
            maxd = d;
            maxi = i;
            maxj = j;
        }
    }while(i != is || j != js);
    return sqrt(maxd);
}

```

#### 4.4 pick theorem

```

struct point{
    ll x, y;
};

//Pick: S = I + B/2 - 1

ld polygonArea(vector <point> &points){
    int n = (int)points.size();
    ld area = 0.0;
    int j = n-1;
    for(int i = 0; i < n; i++){
        area += (points[j].x + points[i].x) *
            (points[j].y - points[i].y);
        j = i;
    }

    return abs(area/2.0);
}

ll boundary(vector <point> points){
    int n = (int)points.size();
    ll num_bound = 0;
    for(int i = 0; i < n; i++){
        ll dx = (points[i].x - points[(i+1)%n].x);
        ll dy = (points[i].y - points[(i+1)%n].y);
        num_bound += abs(__gcd(dx, dy)) - 1;
    }
    return num_bound;
}

```

#### 4.5 squares

```

typedef long double ld;

const ld eps = 1e-12;
int cmp(ld x, ld y = 0, ld tol = eps) {
    return (x <= y + tol) ? (x + tol < y) ? -1 : 0
        : 1;
}

struct point{
    ld x, y;
    point(ld a, ld b) : x(a), y(b) {}
    point() {}
};

struct square{
    ld x1, x2, y1, y2,
        a, b, c;
    point edges[4];
    square(ld _a, ld _b, ld _c) {
        a = _a, b = _b, c = _c;
        x1 = a - c * 0.5;
        x2 = a + c * 0.5;
        y1 = b - c * 0.5;
        y2 = b + c * 0.5;
        edges[0] = point(x1, y1);
        edges[1] = point(x2, y1);
        edges[2] = point(x2, y2);
        edges[3] = point(x1, y2);
    }
};

ld min_dist(point &a, point &b) {
    ld x = a.x - b.x,
        y = a.y - b.y;
    return sqrt(x * x + y * y);
}

bool point_in_box(square s1, point p) {
    if (cmp(s1.x1, p.x) != 1 && cmp(s1.x2, p.x) != -1
        &&
        cmp(s1.y1, p.y) != 1 && cmp(s1.y2, p.y) != -1)
        return true;
    return false;
}

bool inside(square &s1, square &s2) {
    for (int i = 0; i < 4; ++i)
        if (point_in_box(s2, s1.edges[i]))
            return true;

    return false;
}

```

```

bool inside_vert(square &s1, square &s2) {
    if ((cmp(s1.y1, s2.y1) != -1 && cmp(s1.y1, s2.y2)
        != 1) ||
        (cmp(s1.y2, s2.y1) != -1 && cmp(s1.y2, s2.y2)
        != 1))
        return true;
    return false;
}

bool inside_hori(square &s1, square &s2) {
    if ((cmp(s1.x1, s2.x1) != -1 && cmp(s1.x1, s2.x2)
        != 1) ||
        (cmp(s1.x2, s2.x1) != -1 && cmp(s1.x2, s2.x2)
        != 1))
        return true;
    return false;
}

ld min_dist(square &s1, square &s2) {
    if (inside(s1, s2) || inside(s2, s1))
        return 0;

    ld ans = 1e100;
    for (int i = 0; i < 4; ++i)
        for (int j = 0; j < 4; ++j)
            ans = min(ans, min_dist(s1.edges[i],
                                    s2.edges[j]));

    if (inside_hori(s1, s2) || inside_hori(s2, s1)) {
        if (cmp(s1.y1, s2.y2) != -1)
            ans = min(ans, s1.y1 - s2.y2);
        else
            if (cmp(s2.y1, s1.y2) != -1)
                ans = min(ans, s2.y1 - s1.y2);
    }

    if (inside_vert(s1, s2) || inside_vert(s2, s1)) {
        if (cmp(s1.x1, s2.x2) != -1)
            ans = min(ans, s1.x1 - s2.x2);
        else
            if (cmp(s2.x1, s1.x2) != -1)
                ans = min(ans, s2.x1 - s1.x2);
    }

    return ans;
}

```

## 4.6 template

```

#define EPS 1e-6
const double PI = acos(-1.0);

```

```

double DEG_TO_RAD(double d) { return d * PI /
    180.0; }
double RAD_TO_DEG(double r) { return r * 180.0 /
    PI; }

inline int cmp(double a, double b) {
    return (a < b - EPS) ? -1 : ((a > b + EPS) ? 1
        : 0);
}

struct Point{
    double x, y;
    Point(){
        x = y = 0.0;
    }
    Point(double x, double y): x(x), y(y) {}

    Point operator + (const Point& a) const {
        return Point(x+a.x, y+a.y); }
    Point operator - (const Point& a) const {
        return Point(x-a.x, y-a.y); }
    Point operator * (double k) const { return
        Point(x*k, y*k); }
    Point operator / (double k) const { return
        Point(x/k, y/k); }

    double dot(const Point& a) const { return x*a.x
        + y*a.y; } // dot product
    double cross(const Point& a) const { return
        x*a.y - y*a.x; } // cross product

    int cmp(const Point& q) const {
        if (x != q.x) return ::cmp(x, q.x);
        return ::cmp(y, q.y);
    }

#define Comp(x) bool operator x (Point q) const
    { return cmp(q) x 0; }
    Comp(>) Comp(<) Comp(==) Comp(>=) Comp(<=)
    Comp(!=)
#undef Comp

    double norm() { return x*x + y*y; }
    double len() { return sqrt(norm()); }

    // Rotate vector
    Point rotate(double alpha) {
        double cosa = cos(alpha), sina = sin(alpha);
        return Point(x * cosa - y * sina, x * sina +
            y * cosa);
    }
};

istream& operator >> (istream& cin, Point& p) {

```

```

    cin >> p.x >> p.y;
    return cin;
}

ostream& operator << (ostream& cout, Point& p) {
    cout << p.x << ' ' << p.y;
    return cout;
}

struct Line{
    double a, b, c;
    Point A, B;

    Line(double a, double b, double c): a(a), b(b),
        c(c) {}

    Line(Point A, Point B): A(A), B(B) {
        a = B.y - A.y;
        b = A.x - B.x;
        c = -(a * A.x + b * A.y);
    }

    // initialize a line with slope k
    Line(Point P, double k) {
        a = -k;
        b = 1;
        c = k * P.x - P.y;
    }

    double f(Point A){
        return a * A.x + b * A.y + c;
    }
};

bool areParallel(Line l1, Line l2) {
    return cmp(l1.a*l2.b, l1.b*l2.a) == 0;
}

bool areSame(Line l1, Line l2) {
    return areParallel(l1, l2) && cmp(l1.c*l2.a,
        l2.c*l1.a) == 0
        && cmp(l1.c*l2.b, l1.b*l2.c) == 0;
}

bool areIntersect(Line l1, Line l2, Point &p) {
    if (areParallel(l1, l2))
        return false;
    double dx = l1.b*l2.c - l2.b*l1.c;
    double dy = l1.c*l2.a - l2.c*l1.a;
    double d = l1.a*l2.b - l2.a*l1.b;
    p = Point(dx / d, dy / d);
    return true;
}

// distance from p to line ab

```

```

double distToLine(Point p, Point a, Point b, Point
&c) {
    Point ap = p - a, ab = b - a;
    double k = ap.dot(ab) / ab.norm();
    c = a + (ab * k);
    return (p - c).len();
}

// closest point from p in line l.
void closestPoint(Line l, Point p, Point &ans) {
    if (fabs(l.b) < EPS) {
        ans.x = -(l.c) / l.a; ans.y = p.y;
        return;
    }
    if (fabs(l.a) < EPS) {
        ans.x = p.x; ans.y = -(l.c) / l.b;
        return;
    }
    Line perp(l.b, -l.a, - (l.b*p.x - l.a*p.y));
    areIntersect(l, perp, ans);
}

// reflect point p over line l
void reflectionPoint(Line l, Point p, Point &ans) {
    Point b;
    closestPoint(l, p, b);
    ans = p + (b - p) * 2;
}

```

## 4.7 triangles

Let a, b, c be length of the three sides of a triangle.

$$p = (a + b + c) * 0.5$$

The inradius is defined by:

$$iR = \sqrt{\frac{(p-a)(p-b)(p-c)}{p}}$$

The radius of its circumcircle is given by the formula:

$$cR = \frac{abc}{\sqrt{(a+b+c)(a+b-c)(a+c-b)(b+c-a)}}$$

## 5 Graphs

### 5.1 bridges

```

struct Graph {
    vector<vector<Edge>> g;
    vector<int> vi, low, d, pi, is_b;
    int bridges_computed;

    int ticks, edges;

    Graph(int n, int m) {
        g.assign(n, vector<Edge>());
        is_b.assign(m, 0);
        vi.resize(n);
        low.resize(n);
        d.resize(n);
        pi.resize(n);
        edges = 0;
        bridges_computed = 0;
    }

    void AddEdge(int u, int v) {
        g[u].push_back(Edge(v, edges));
        g[v].push_back(Edge(u, edges));
        edges++;
    }

    void Dfs(int u) {
        vi[u] = true;
        d[u] = low[u] = ticks++;
        for (int i = 0; i < (int)g[u].size(); ++i) {
            int v = g[u][i].to;
            if (v == pi[u]) continue;
            if (!vi[v]) {
                pi[v] = u;
                Dfs(v);
                if (d[u] < low[v]) is_b[g[u][i].id] = true;

                low[u] = min(low[u], low[v]);
            } else {
                low[u] = min(low[u], d[v]);
            }
        }
    }

    // Multiple edges from a to b are not allowed.
    // (they could be detected as a bridge).
    // If you need to handle this, just count
    // how many edges there are from a to b.
    void CompBridges() {
        fill(pi.begin(), pi.end(), -1);
        fill(vi.begin(), vi.end(), 0);
        fill(low.begin(), low.end(), 0);
        fill(d.begin(), d.end(), 0);
        ticks = 0;
        for (int i = 0; i < (int)g.size(); ++i)
            if (!vi[i]) Dfs(i);
    }
}

```

```

    bridges_computed = true;
}

map<int, vector<Edge>> BridgesTree() {
    if (!bridges_computed) CompBridges();
    int n = g.size();
    Dsu dsu(g.size());
    for (int i = 0; i < n; i++)
        for (auto e : g[i])
            if (!is_b[e.id]) dsu.Join(i, e.to);

    map<int, vector<Edge>> tree;
    for (int i = 0; i < n; i++)
        for (auto e : g[i])
            if (is_b[e.id])
                tree[dsu.Find(i)].emplace_back(dsu.Find(e.to),
                    e.id);

    return tree;
}
};

```

### 5.2 delete on dsu

```

struct dsu_save{
    int u, v;
    int par_u, par_v;

    dsu_save(){}

    dsu_save(int _v, int _par_v, int _u, int _par_u)
        : v(_v), par_v(_par_v), u(_u), par_u(_par_u)
        {}
};

class dsu_rollback{
public:
    vector<int> parent;
    int comps;
    stack<dsu_save> st_op;

    dsu_rollback(){};

    dsu_rollback(int n){
        parent.resize(n+1, -1);
        comps = n;
    }

    int find_set(int u){
        while(parent[u] > 0)
            u = parent[u];
        return u;
    }
}

```

```

}

bool Union(int u, int v){
    int U = find_set(u);
    int V = find_set(v);
    if(U == V)
        return false;
    comps--;
    st_op.push(dsu_save(U, parent[U], V,
        parent[V]));
    int x = parent[U] + parent[V];
    if(parent[U] > parent[V]){
        parent[U] = V;
        parent[V] = x;
    }else{
        parent[U] = x;
        parent[V] = U;
    }
    return true;
}

void rollback(){
    if(st_op.empty())
        return;
    dsu_save x = st_op.top();
    st_op.pop();
    comps++;
    parent[x.u] = x.par_u;
    parent[x.v] = x.par_v;
}

};

struct query{
    int u, v;
    bool united;
};

class QueryTree{
    vector <vector <query>> t;
    dsu_rollback dsu;
    int T;
public:
    QueryTree(int _T, int n){
        this->T = _T;
        this->dsu = dsu_rollback(n);
        t.resize(4*T + 4);
    }

    void add_to_tree(int id, int l, int r, int
        u, int v, query q){
        if(v < l || r < u || u > v)
            return;
        if(u <= l && r <= v){
            t[id].push_back(q);
            return;
        }
    }
};

```

```

}

int mid = (l+r) >> 1;
add_to_tree(2*id, l, mid, u, v, q);
add_to_tree(2*id+1, mid+1, r, u, v, q);
}

void add_query(query q, int l, int r){
    add_to_tree(1, 0, T-1, l, r, q);
}

void DFS(int id, int l, int r, vector <int>
    &ans){
    for(query &q: t[id])
        q.united = dsu.Union(q.u, q.v);

    if(l == r){
        ans[l] = dsu.comps;
    }else{
        int mid = (l+r) >> 1;
        DFS(2*id, l, mid, ans);
        DFS(2*id+1, mid+1, r, ans);
    }

    for(query &q: t[id])
        if(q.united)
            dsu.rollback();
    }

vector <int> compute(){
    vector <int> ans(T); // T query
    DFS(1, 0, T-1, ans);
    return ans;
}

};

```

### 5.3 euler path

```

struct DirectedEulerPath
{
    int n;
    vector<vector<int> > g;
    vector<int> path;

    void init(int _n){
        n = _n;
        g = vector<vector<int> > (n + 1,
            vector<int> ());
        path.clear();
    }

    void add_edge(int u, int v){
        g[u].push_back(v);
    }
};

```

```

}

void dfs(int u)
{
    while(g[u].size())
    {
        int v = g[u].back();
        g[u].pop_back();
        dfs(v);
    }
    path.push_back(u);
}

bool getPath(){
    int ctEdges = 0;
    vector<int> outDeg, inDeg;
    outDeg = inDeg = vector<int> (n + 1,
        0);
    for(int i = 1; i <= n; i++)
    {
        ctEdges += g[i].size();
        outDeg[i] += g[i].size();
        for(auto &u: g[i])
            inDeg[u]++;
    }
    int ctMiddle = 0, src = 1;
    for(int i = 1; i <= n; i++)
    {
        if(abs(inDeg[i] - outDeg[i])
            > 1)
            return 0;
        if(inDeg[i] == outDeg[i])
            ctMiddle++;
        if(outDeg[i] > inDeg[i])
            src = i;
    }
    if(ctMiddle != n && ctMiddle + 2 !=
        n)
        return 0;
    dfs(src);
    reverse(path.begin(), path.end());
    return (path.size() == ctEdges + 1);
}

};

```

### 5.4 karp min mean cycle

```

/**
 * Finds the min mean cycle, if you need the max
 * mean cycle
 * just add all the edges with negative cost and
 * print
 */

```

```

* ans * -1
*
* test: uva, 11090 - Going in Cycle!!
* */

const int MN = 1000;
struct edge{
    int v;
    long long w;
    edge(){} edge(int v, int w) : v(v), w(w) {}
};

long long d[MN][MN];
// This is a copy of g because increments the size
// pass as reference if this does not matter.
int karp(vector<vector<edge> > g) {
    int n = g.size();

    g.resize(n + 1); // this is important

    for (int i = 0; i < n; ++i)
        if (!g[i].empty())
            g[n].push_back(edge(i, 0));
    ++n;

    for(int i = 0; i < n; ++i)
        fill(d[i], d[i] + (n + 1), INT_MAX);

    d[n - 1][0] = 0;

    for (int k = 1; k <= n; ++k) for (int u = 0; u <
        n; ++u) {
        if (d[u][k - 1] == INT_MAX) continue;
        for (int i = g[u].size() - 1; i >= 0; --i)
            d[g[u][i].v][k] = min(d[g[u][i].v][k], d[u][k
                - 1] + g[u][i].w);
    }

    bool flag = true;

    for (int i = 0; i < n && flag; ++i)
        if (d[i][n] != INT_MAX)
            flag = false;

    if (flag) {
        return true; // return true if there is no a
            cycle.
    }

    double ans = 1e15;

    for (int u = 0; u + 1 < n; ++u) {
        if (d[u][n] == INT_MAX) continue;
        double W = -1e15;

```

```

        for (int k = 0; k < n; ++k)
            if (d[u][k] != INT_MAX)
                W = max(W, (double)(d[u][n] - d[u][k]) / (n
                    - k));

        ans = min(ans, W);
    }

    // printf("%.2lf\n", ans);
    cout << fixed << setprecision(2) << ans << endl;

    return false;
}

```

## 5.5 konig's theorem

In any bipartite graph, the number of edges in a maximum matching equals the number of vertices in a minimum vertex cover

## 5.6 matching

```

struct Hopcroft_Karp
{
    static const int inf = 1e9;

    int n;
    vector<int> matchL, matchR, dist;
    vector<vector<int> > g;

    Hopcroft_Karp(int n) :
        n(n), matchL(n + 1), matchR(n + 1),
        dist(n + 1), g(n + 1) {}

    void addEdge(int u, int v)
    {
        g[u].push_back(v);
    }

    bool bfs()
    {
        queue<int> q;
        for(int u = 1; u <= n; u++)
        {
            if (!matchL[u])
            {
                dist[u] = 0;
                q.push(u);
            }
            else
                dist[u] = inf;
        }
    }

```

```

}
dist[0] = inf;

while (!q.empty())
{
    int u = q.front();
    q.pop();
    for (auto v : g[u])
    {
        if (dist[matchR[v]] ==
            inf)
        {
            dist[matchR[v]]
                = dist[u]
                + 1;
            q.push(matchR[v]);
        }
    }

    return (dist[0] != inf);
}

bool dfs(int u)
{
    if (!u)
        return true;
    for (auto v : g[u])
    {
        if (dist[matchR[v]] ==
            dist[u] + 1
            && dfs(matchR[v]))
        {
            matchL[u] = v;
            matchR[v] = u;
            return true;
        }
    }
    dist[u] = inf;
    return false;
}

int max_matching()
{
    int matching = 0;
    while (bfs())
    {
        for (int u = 1; u <= n; u++)
        {
            if (!matchL[u])
                if (dfs(u))
                    matching++;
        }
    }
    return matching;
}

```

```

    }
};

```

## 5.7 max flow min cost

```

struct edge
{
    long long x, y, cap, flow, cost;
};

struct MinCostMaxFlow
{
    long long n, S, T;
    vector < vector <long long> > a;
    vector <long long> dist, prev, done, pot;
    vector <edge> e;

    MinCostMaxFlow() {}
    MinCostMaxFlow(long long _n, long long _S,
        long long _T)
    {
        n = _n; S = _S; T = _T;
        a = vector < vector <long long> >(n
            + 1);
        dist = vector <long long>(n + 1);
        prev = vector <long long>(n + 1);
        done = vector <long long>(n + 1);
        pot = vector <long long>(n + 1, 0);
    }

    void addEdge(long long x, long long y, long
        long _cap, long long _cost)
    {
        edge e1 = {x, y, _cap, 0, _cost};
        edge e2 = {y, x, 0, 0, -_cost};
        a[x].push_back(e.size());
        e.push_back(e1);
        a[y].push_back(e.size());
        e.push_back(e2);
    }

    pair <long long, long long> dijkstra()
    {
        long long flow = 0, cost = 0;
        for (long long i = 1; i <= n; i++)
            done[i] = 0, dist[i] = oo;
        priority_queue < pair<long long, long
            long> > q;
        dist[S] = 0; prev[S] = -1;
        q.push(make_pair(0, S));
        while (!q.empty())
        {

```

```

            long long x = q.top().second;
            q.pop();
            if (done[x]) continue;
            done[x] = 1;
            for (int i = 0; i <
                int(a[x].size()); i++)
            {
                long long id =
                    a[x][i], y =
                    e[id].y;
                if (e[id].flow <
                    e[id].cap)
                {
                    long long D =
                        dist[x] +
                        e[id].cost
                        + pot[x] -
                        pot[y];
                    if (!done[y] &&
                        D <
                        dist[y])
                    {
                        dist[y]
                            =
                            D;
                        prev[y]
                            =
                            id;
                        q.push(make_pair(-D,
                            y));
                    }
                }
            }
        }

        for (long long i = 1; i <= n; i++)
            pot[i] += dist[i];

        if (done[T])
        {
            flow = oo;
            for (long long id = prev[T];
                id >= 0; id =
                prev[e[id].x])
                flow = min(flow,
                    e[id].cap -
                    e[id].flow);
            for (long long id = prev[T];
                id >= 0; id =
                prev[e[id].x])
            {
                cost += e[id].cost *
                    flow;
                e[id].flow += flow;
                e[id ^ 1].flow -= flow;

```

```

            }
        }

        return make_pair(flow, cost);
    }

    pair <long long, long long> minCostMaxFlow()
    {
        long long totalFlow = 0, totalCost =
            0;
        while (1)
        {
            pair <long long, long long> u
                = dijkstra();
            if (!done[T]) break;
            totalFlow += u.first;
            totalCost += u.second;
        }
        return make_pair(totalFlow,
            totalCost);
    }
};

```

## 5.8 minimum path cover in DAG

Given a directed acyclic graph  $G = (V, E)$ , we are to find the minimum number of vertex-disjoint paths to cover each vertex in  $V$ .

We can construct a bipartite graph  $G' = (V_{out} \cup V_{in}, E')$  from  $G$ , where :

$$V_{out} = \{v \in V : v \text{ has positive out-degree}\}$$

$$V_{in} = \{v \in V : v \text{ has positive in-degree}\}$$

$$E' = \{(u, v) \in V_{out} \times V_{in} : (u, v) \in E\}$$

Then it can be shown, via König's theorem, that  $G'$  has a matching of size  $m$  if and only if there exists  $n - m$  vertex-disjoint paths that cover each vertex in  $G$ , where  $n$  is the number of vertices in  $G$  and  $m$  is the maximum cardinality bipartite matching in  $G'$ .

Therefore, the problem can be solved by finding the maximum cardinality matching in  $G'$  instead.

**NOTE:** If the paths are not necessarily disjoint, find the transitive closure and solve the problem for disjoint paths.

## 5.9 planar graph (euler)

Euler's formula states that if a finite, connected, planar graph is drawn in the plane without any edge intersections, and  $v$  is the number of vertices,  $e$  is the number of edges and  $f$  is the number of faces (regions bounded by edges, including the outer, infinitely large region), then:

$$f + v = e + 2$$

It can be extended to non connected planar graphs with  $c$  connected components:

$$f + v = e + c + 1$$

## 5.10 two sat

```
/**
 * Given a set of clauses (a1 v a2)^(a2 v a3)....
 * this algorithm find a solution to it set of
 * clauses.
 * test:
 * http://lightoj.com/volume_showproblem.php?problem=1251
 */

vector <int> G[MAXN];
vector <int> Gv2[MAXN];

int low[MAXN], num[MAXN];
int cntTime = 0, cntSCC = 0, SCC[MAXN];
vector <int> inSCC[MAXN];
stack <int> st;
queue <int> q;
// storing topo order with queue instead of stack
// because we need to go from back to begin of topo
// order

void DFS(int u){
    low[u] = num[u] = ++cntTime;
    st.push(u);
    for(int v: G[u])
        if(num[v])
            low[u] = min(low[u], num[v]);
        else{
            DFS(v);
            low[u] = min(low[u], low[v]);
        }
    if(low[u] == num[u]){
        int v;
        cntSCC++;
        do{
```

```
        v = st.top();
        st.pop();
        SCC[v] = cntSCC;
        inSCC[cntSCC].push_back(v);
        low[v] = num[v] = INT_MAX;
    }while(u != v);
}

void DFS_topo(int u){
    num[u] = 1;
    for(int v: Gv2[u])
        if(!num[v])
            DFS_topo(v);
    q.push(u);
}

int main(){
    io
    // freopen("test.inp", "r", stdin);
    // freopen("test.out", "w", stdout);
    int n, m;
    cin >> m >> n;

    auto getNot = [&](int u)->int{
        if(u > n)
            return u - n;
        return u + n;
    };

    while(m--){
        char c1, c2;
        int u, v;
        cin >> c1 >> u >> c2 >> v;
        if(c1 == '-' ) u += n;
        if(c2 == '-' ) v += n;
        // add (-v -> u) and (-u -> v)
        G[getNot(u)].push_back(v);
        G[getNot(v)].push_back(u);
    }

    // using tarjan's algorithm to find SCC.
    for(int i = 1; i <= 2*n; i++)
        if(!num[i])
            DFS(i);

    vector <int> notSCC(2*n+1);

    // check if exist u and -u are in the same
    // component
    for(int i = 1; i <= n; i++)
        if(SCC[i] == SCC[i+n])
            return cout << "IMPOSSIBLE", 0;
        else{
            // store the opposite component.
```

```
        notSCC[SCC[i]] = SCC[i+n];
        notSCC[SCC[i+n]] = SCC[i];
    }

    // build new graph
    for(int i = 1; i <= 2*n; i++)
        for(int v: G[i])
            if(SCC[i] != SCC[v]){
                Gv2[SCC[i]].push_back(SCC[v]);
            }

    // topological sort
    fill(num+1, num+1+2*n, 0);
    for(int i = 1; i <= cntSCC; i++)
        if(!num[i])
            DFS_topo(i);

    vector <int> ansSCC(2*n+1, -1);
    vector <int> ans(2*n+1, 0);
    while(!q.empty()){
        int u = q.front();
        q.pop();
        if(ansSCC[u] == -1){ // not pick
            // if u = 1 then -u must be 0
            ansSCC[u] = 1;
            ansSCC[notSCC[u]] = 0;
        }

        // set value of all nodes in the current SCC
        for(int v: inSCC[u]){
            ans[v] = ansSCC[u];
        }
    }

    for(int i = 1; i <= n; i++)
        cout << ((ans[i])? '+' : '-') << ' ';
    }
```

## 6 Math

### 6.1 Lucas theorem

For non-negative integers  $m$  and  $n$  and a prime  $p$ , the following congruence relation holds :

$$\binom{m}{n} \equiv \prod_{i=0}^k \binom{m_i}{n_i} \pmod{p},$$

where :

$$m = m_k p^k + m_{k-1} p^{k-1} + \dots + m_1 p + m_0,$$



and :

$$n = n_k p^k + n_{k-1} p^{k-1} + \dots + n_1 p + n_0$$

are the base  $p$  expansions of  $m$  and  $n$  respectively. This uses the convention that  $\binom{m}{n} = 0$  if  $m \leq n$ .

## 6.2 cumulative sum of divisors

---

/\*  
The function SOD(n) (sum of divisors) is defined as the summation of all the actual divisors of an integer number n. For example,

$$\text{SOD}(24) = 2+3+4+6+8+12 = 35.$$

The function CSOD(n) (cumulative SOD) of an integer n, is defined as below:

$$\text{csod}(n) = \sum_{i=1}^n \text{sod}(i)$$

It can be computed in  $O(\sqrt{n})$ :

```
*/
long long csod(long long n) {
    long long ans = 0;
    for (long long i = 2; i * i <= n; ++i) {
        long long j = n / i;
        ans += (i + j) * (j - i + 1) / 2;
        ans += i * (j - i);
    }
    return ans;
}
```

---

## 6.3 fft

---

/\*\*  
\* Fast Fourier Transform.  
\* Useful to compute convolutions.  
\* computes:  
\*  $C(f \star g)[n] = \sum_m (f[m] * g[n - m])$   
\* for all n.  
\* test: icpc live archive, 6886 - Golf Bot  
\* \*/

```
using namespace std;
#include <bits/stdc++.h>
#define D(x) cout << #x " = " << (x) << endl
#define endl '\n'
```

```
const int MN = 262144 << 1;
int d[MN + 10], d2[MN + 10];

const double PI = acos(-1.0);

struct cpx {
    double real, image;
    cpx(double _real, double _image) {
        real = _real;
        image = _image;
    }
    cpx(){}
};

cpx operator + (const cpx &c1, const cpx &c2) {
    return cpx(c1.real + c2.real, c1.image + c2.image);
}

cpx operator - (const cpx &c1, const cpx &c2) {
    return cpx(c1.real - c2.real, c1.image - c2.image);
}

cpx operator * (const cpx &c1, const cpx &c2) {
    return cpx(c1.real*c2.real - c1.image*c2.image, c1.real*c2.image + c1.image*c2.real);
}

int rev(int id, int len) {
    int ret = 0;
    for (int i = 0; (1 << i) < len; i++) {
        ret <<= 1;
        if (id & (1 << i)) ret |= 1;
    }
    return ret;
}

cpx A[1 << 20];

void FFT(cpx *a, int len, int DFT) {
    for (int i = 0; i < len; i++)
        A[rev(i, len)] = a[i];
    for (int s = 1; (1 << s) <= len; s++) {
        int m = (1 << s);
        cpx wm = cpx(cos( DFT * 2 * PI / m), sin(DFT * 2 * PI / m));
        for(int k = 0; k < len; k += m) {
            cpx w = cpx(1, 0);
            for(int j = 0; j < (m >> 1); j++) {
                cpx t = w * A[k + j + (m >> 1)];
                cpx u = A[k + j];
                A[k + j] = u + t;
                A[k + j + (m >> 1)] = u - t;
```

```
                w = w * wm;
            }
        }
    }
    if (DFT == -1) for (int i = 0; i < len; i++)
        A[i].real /= len, A[i].image /= len;
    for (int i = 0; i < len; i++) a[i] = A[i];
    return;
}

cpx in[1 << 20];

void solve(int n) {
    memset(d, 0, sizeof d);
    int t;
    for (int i = 0; i < n; ++i) {
        cin >> t;
        d[t] = true;
    }
    int m;
    cin >> m;
    vector<int> q(m);
    for (int i = 0; i < m; ++i)
        cin >> q[i];

    for (int i = 0; i < MN; ++i) {
        if (d[i])
            in[i] = cpx(1, 0);
        else
            in[i] = cpx(0, 0);
    }

    FFT(in, MN, 1);
    for (int i = 0; i < MN; ++i) {
        in[i] = in[i] * in[i];
    }
    FFT(in, MN, -1);

    int ans = 0;
    for (int i = 0; i < q.size(); ++i) {
        if (in[q[i]].real > 0.5 || d[q[i]]) {
            ans++;
        }
    }
    cout << ans << endl;
}

int main() {
    ios_base::sync_with_stdio(false); cin.tie(NULL);
    int n;
    while (cin >> n)
        solve(n);
    return 0;
}
```

---

## 6.4 fibonacci properties

Let A, B and n be integer numbers.

$$k = A - B \quad (1)$$

$$F_A F_B = F_{k+1} F_A^2 + F_k F_A F_{A-1} \quad (2)$$

$$\sum_{i=0}^n F_i^2 = F_{n+1} F_n \quad (3)$$

$ev(n)$  = returns 1 if n is even.

$$\sum_{i=0}^n F_i F_{i+1} = F_{n+1}^2 - ev(n) \quad (4)$$

$$\sum_{i=0}^n F_i F_{i-1} = \sum_{i=0}^{n-1} F_i F_{i+1} \quad (5)$$

## 6.5 gauss

---

```
const int inf = 1e9;
const double eps = 1e-6;

/*
 * Input:
 *   a: the coefficients of the system
 *   ans: storing answer
 * Output:
 *   The number of roots
 */
int gauss(vector<vector<double>>> a, vector<double> &ans){
    int n = (int)a.size();
    int m = (int)a[0].size() - 1;

    vector<int> where(m, -1);

    for(int col = 0, row = 0; col < m && row < n; col++){
        // Choosing the pivot row is done with heuristic:
        // choosing maximum value in the current column
        int pivot = row;
        for(int i = row; i < n; i++)
            if(abs(a[i][col]) > abs(a[pivot][col]))
                pivot = i;

        for(int i = col; i <= m; i++)
```

```
        swap(a[pivot][i], a[row][i]);
        where[col] = row;

        for(int i = 0; i < n; i++){
            if(i != row){
                double c = a[i][col] / a[row][col];
                for(int j = col; j <= m; j++){
                    a[i][j] -= a[row][j] * c;
                }
                row++;
            }
        }

        ans.assign(m, 0);
        for(int i = 0; i < m; i++){
            if(where[i] != -1)
                ans[i] = a[where[i]][m] / a[where[i]][i];

            // calculate the number of roots by re-checking
            // the system of equations.
            for(int i = 0; i < n; i++){
                double sum = 0;
                for(int j = 0; j < m; j++){
                    sum += ans[j] * a[i][j];
                }
                if(abs(sum - a[i][m]) > eps)
                    return 0;
            }

            for(int i = 0; i < m; i++){
                if(where[i] == -1)
                    return inf;
            }

            return 1;
        }
    }
}
```

---

## 6.6 others

Approximate factorial

$$n! = \sqrt{2\pi n} \left(\frac{n}{e}\right)^n \quad (6)$$

## 6.7 polynomials

---

```
// TODO: what's this ?
const double pi = acos(-1);
struct poly {
    deque<double> coef;
    double x_lo, x_hi;

    double evaluate(double x) {
        double ans = 0;
        for (auto it : coef)
```

```
            ans = (ans * x + it);
        }
        return ans;
    }

double volume(double x, double dx=1e-6) {
    dx = (x_hi - x_lo) / 1000000.0;
    double ans = 0;
    for (double ix = x_lo; ix <= x; ix += dx) {
        double rad = evaluate(ix);
        ans += pi * rad * rad * dx;
    }
    return ans;
}
};
```

---

## 6.8 sigma function

the sigma function is defined as:

$$\sigma_x(n) = \sum_{d|n} d^x$$

when  $x = 0$  is called the divisor function, that counts the number of positive divisors of n.

Now, we are interested in find

$$\sum_{d|n} \sigma_0(d)$$

if  $n$  is written as prime factorization:

$$n = \prod_{i=1}^k P_i^{e_k}$$

we can demonstrate that:

$$\sum_{d|n} \sigma_0(d) = \prod_{i=1}^k g(e_k + 1)$$

where  $g(x)$  is the sum of the first x positive numbers:

$$g(x) = (x * (x + 1)) / 2$$

## 6.9 system different constraints

```

/* http://poj.org/problem?id=2983 */
/*
## Problem
Given a system of inequations of the form  $x_j - x_i \leq w_{ij}$ .
Find any solution  $x_1, x_2, \dots, x_n$  or show that
the system has no solution.

## Solution
We construct a n-vertex graph (vertex i represents
variable  $x_i$ ). For each inequation  $x_j - x_i \leq w_{ij}$ ,
we add an edge from i to j with weight  $w_{ij}$ .

If the graph has negative cycle, there's no
solution.
Else, create a virtual vertex s, add edge with
weight 0 from s to every  $x_i$ ,
the solution is the shortest path from s to n
vertices.
*/
typedef long long ll;

struct edge{
    int u, v, c;
};

/*
check if negative cycle
*/
bool bellman_ford(int n, vector<edge> edges){
    int m = (int)edges.size();
    vector<ll> dist(n+1);
    for(int i = 1; i < n; i++){
        for(int j = 0; j < m; j++){
            int u = edges[j].u;
            int v = edges[j].v;
            int c = edges[j].c;
            if(dist[v] > dist[u] + c)
                dist[v] = dist[u] + c;
        }

        for(int j = 0; j < m; j++){
            int u = edges[j].u;
            int v = edges[j].v;
            int c = edges[j].c;
            if(dist[v] > dist[u] + c)
                return true;
        }
        return false;
    }
}

```

```

void solve(int n, int m){
    vector<edge> edges;
    while(m--){
        char t;
        cin >> t;
        if(t == 'P'){
            int u, v, c;
            cin >> u >> v >> c;
            edges.push_back({u, v, c});
            edges.push_back({v, u, -c});
        }else{
            int u, v; cin >> u >> v;
            edges.push_back({v, u, -1});
        }
    }
    if(bellman_ford(n, edges))
        cout << "Unreliable" << '\n';
    else cout << "Reliable" << '\n';
}

```

## 7 Matrix

### 7.1 matrix

```

const int dim = 10;

struct matrix{
    vector<vector<long long>> a;
    matrix(){
        a.resize(dim);
        for(int i = 1; i < dim; i++)
            a[i].resize(dim, 0);
    }
};

matrix Identity(){
    matrix A;
    for(int i = 1; i < dim; i++)
        A.a[i][i] = 1;
    return A;
}

matrix operator* (const matrix &A, const matrix &B){
    matrix mul;
    for(int k = 1; k < dim; k++)
        for(int i = 1; i < dim; i++)
            for(int j = 1; j < dim; j++)
                mul.a[i][j] += A.a[i][k]*B.a[k][j];
    return mul;
}

matrix fastPow(matrix A, long long b){

```

```

    if(b == 0)
        return Identity();
    if(b == 1)
        return A;
    matrix t = fastPow(A, b/2);
    t = t*t;
    if(b%2 == 1)
        t = t*A;
    return t;
}

```

## 8 Misc

### 8.1 dates

```

//
// Time - Leap years
//

// A[i] has the accumulated number of days from
// months previous to i
const int A[13] = { 0, 0, 31, 59, 90, 120, 151,
    181, 212, 243, 273, 304, 334 };
// same as A, but for a leap year
const int B[13] = { 0, 0, 31, 60, 91, 121, 152,
    182, 213, 244, 274, 305, 335 };
// returns number of leap years up to, and
// including, y
int leap_years(int y) { return y / 4 - y / 100 + y / 400; }
bool is_leap(int y) { return y % 400 == 0 || (y % 4 == 0 && y % 100 != 0); }
// number of days in blocks of years
const int p400 = 400*365 + leap_years(400);
const int p100 = 100*365 + leap_years(100);
const int p4 = 4*365 + 1;
const int p1 = 365;
int date_to_days(int d, int m, int y)
{
    return (y - 1) * 365 + leap_years(y - 1) +
        (is_leap(y) ? B[m] : A[m]) + d;
}

void days_to_date(int days, int &d, int &m, int &y)
{
    bool top100; // are we in the top 100 years of a
    400 block?
    bool top4; // are we in the top 4 years of a
    100 block?
    bool top1; // are we in the top year of a 4
    block?

    y = 1;

```

```

top100 = top4 = top1 = false;

y += ((days-1) / p400) * 400;
d = (days-1) % p400 + 1;

if (d > p100*3) top100 = true, d -= 3*p100, y += 300;
else y += ((d-1) / p100) * 100, d = (d-1) % p100 + 1;

if (d > p4*24) top4 = true, d -= 24*p4, y += 24*4;
else y += ((d-1) / p4) * 4, d = (d-1) % p4 + 1;

if (d > p1*3) top1 = true, d -= p1*3, y += 3;
else y += (d-1) / p1, d = (d-1) % p1 + 1;

const int *ac = top1 && (!top4 || top100) ? B : A;
for (m = 1; m < 12; ++m) if (d <= ac[m + 1])
    break;
d -= ac[m];
}

```

## 9 Number theory

### 9.1 convolution

```

typedef long long int LL;
typedef pair<LL, LL> PLL;

inline bool is_pow2(LL x) {
    return (x & (x-1)) == 0;
}

inline int ceil_log2(LL x) {
    int ans = 0;
    --x;
    while (x != 0) {
        x >>= 1;
        ans++;
    }
    return ans;
}

/* Returns the convolution of the two given vectors
   in time proportional to n*log(n).
* The number of roots of unity to use nroots_unity
   must be set so that the product of the first
* nroots_unity primes of the vector
   nth_roots_unity is greater than the maximum
   value of the
* convolution. Never use sizes of vectors bigger
   than 2^24, if you need to change the values of

```

```

* the nth roots of unity to appropriate primes for
   those sizes.
*/
vector<LL> convolve(const vector<LL> &a, const
    vector<LL> &b, int nroots_unity = 2) {
    int N = 1 << ceil_log2(a.size() + b.size());
    vector<LL> ans(N,0), fA(N), fB(N), fC(N);
    LL modulo = 1;
    for (int times = 0; times < nroots_unity;
        times++) {
        fill(fA.begin(), fA.end(), 0);
        fill(fB.begin(), fB.end(), 0);
        for (int i = 0; i < a.size(); i++) fA[i] = a[i];
        for (int i = 0; i < b.size(); i++) fB[i] = b[i];
        LL prime = nth_roots_unity[times].first;
        LL inv_modulo = mod_inv(modulo % prime, prime);
        LL normalize = mod_inv(N, prime);
        ntfft(fA, 1, nth_roots_unity[times]);
        ntfft(fB, 1, nth_roots_unity[times]);
        for (int i = 0; i < N; i++) fC[i] = (fA[i] *
            fB[i]) % prime;
        ntfft(fC, -1, nth_roots_unity[times]);
        for (int i = 0; i < N; i++) {
            LL curr = (fC[i] * normalize) % prime;
            LL k = (curr - (ans[i] % prime) + prime) %
                prime;
            k = (k * inv_modulo) % prime;
            ans[i] += modulo * k;
        }
        modulo *= prime;
    }
    return ans;
}

```

### 9.2 crt

```

/**
* Chinese remainder theorem.
* Find z such that z % x[i] = a[i] for all i.
*/
long long crt(vector<long long> &a, vector<long
    long> &x) {
    long long z = 0;
    long long n = 1;
    for (int i = 0; i < x.size(); ++i)
        n *= x[i];

    for (int i = 0; i < a.size(); ++i) {
        long long tmp = (a[i] * (n / x[i])) % n;
        tmp = (tmp * mod_inv(n / x[i], x[i])) % n;
        z = (z + tmp) % n;
    }
}

```

```

    return (z + n) % n;
}

```

### 9.3 diophantine equations

```

long long gcd(long long a, long long b, long long
    &x, long long &y) {
    if (a == 0) {
        x = 0;
        y = 1;
        return b;
    }
    long long x1, y1;
    long long d = gcd(b % a, a, x1, y1);
    x = y1 - (b / a) * x1;
    y = x1;
    return d;
}

bool find_any_solution(long long a, long long b,
    long long c, long long &x0,
    long long &y0, long long &g) {
    g = gcd(abs(a), abs(b), x0, y0);
    if (c % g) {
        return false;
    }

    x0 *= c / g;
    y0 *= c / g;
    if (a < 0) x0 = -x0;
    if (b < 0) y0 = -y0;
    return true;
}

void shift_solution(long long &x, long long &y,
    long long a, long long b,
    long long cnt) {
    x += cnt * b;
    y -= cnt * a;
}

long long find_all_solutions(long long a, long long
    b, long long c,
    long long minx, long long maxx, long long miny,
    long long maxy) {
    long long x, y, g;
    if (!find_any_solution(a, b, c, x, y, g)) return
        0;
    a /= g;
    b /= g;

```

## 9.4 discrete logarithm

```
long long d_log(long long a, long long b, long long
n) {
    long long m = ceil(sqrt(n));
    long long aj = 1;
    map<long long, long long> M;
    for (int i = 0; i < m; ++i) {
        if (!M.count(aj))
            M[aj] = i;
        aj = (aj * a) % n;
    }

    long long coef = mod_pow(a, n - 2, n);
    coef = mod_pow(coef, m, n);
    // coef = a ^ (-m)
    long long gamma = b;
    for (int i = 0; i < m; ++i) {
        if (M.count(gamma)) {
            return i * m + M[gamma];
        }
    }
}
```

## 9.5 ext euclidean

## 9.6 highest exponent factorial

## 9.7 miller rabin

```
// checks whether a is a witness that n is not
// prime,  $1 < a < n$ 
bool witness(long long a, long long n) {
    // check as in Miller Rabin Primality Test
    // described
    long long u = n - 1;
    int t = 0;
    while (u % 2 == 0) {
        t++;
        u >>= 1;
    }
}
```

## 9.8 mod integer

```
template<class T, T mod>
struct mint_t {
    T val;
    mint_t() : val(0) {}
    mint_t(T v) : val(v % mod) {}

    mint_t operator + (const mint_t& o) const {
        return (val + o.val) % mod;
    }
    mint_t operator - (const mint_t& o) const {
        return (val - o.val) % mod;
    }
    mint_t operator * (const mint_t& o) const {
        return (val * o.val) % mod;
    }
};
```

```
typedef mint_t<long long, 998244353> mint;
```

## 9.9 mod inv

```
long long mod_inv(long long n, long long m) {
    long long x, y, gcd;
    ext_euclid(n, m, x, y, gcd);
    if (gcd != 1)
        return 0;
    return (x + m) % m;
}
```

## 9.10 mod mul

```
// Computes (a * b) % mod
long long mod_mul(long long a, long long b, long
    long mod) {
    long long x = 0, y = a % mod;
    while (b > 0) {
        if (b & 1)
            x = (x + y) % mod;
        y = (y * 2) % mod;
        b /= 2;
    }
    return x % mod;
}
```

## 9.11 mod pow

```
// Computes (a ^ exp) % mod.
long long mod_pow(long long a, long long exp, long
    long mod) {
    long long ans = 1;
    while (exp > 0) {
        if (exp & 1)
            ans = mod_mul(ans, a, mod);
        a = mod_mul(a, a, mod);
        exp >>= 1;
    }
    return ans;
}
```

## 9.12 number theoretic transform

```
typedef long long int LL;
typedef pair<LL, LL> PLL;

/* The following vector of pairs contains pairs
   (prime, generator)
   * where the prime has an Nth root of unity for N
     being a power of two.
   * The generator is a number g s.t g^(p-1)=1 (mod p)
   * but is different from 1 for all smaller powers */
vector<PLL> nth_roots_unity {
    {1224736769, 330732430}, {1711276033, 927759239}, {167772161, 167489322},
    {469762049, 343261969}, {754974721, 643797295}, {1107296257, 883865065}
};

PLL ext_euclid(LL a, LL b) {
    if (b == 0)
        return make_pair(1, 0);
    pair<LL, LL> rc = ext_euclid(b, a % b);
    return make_pair(rc.second, rc.first - (a / b) *
        rc.second);
}

//returns -1 if there is no unique modular inverse
LL mod_inv(LL x, LL modulo) {
    PLL p = ext_euclid(x, modulo);
    if ((p.first * x + p.second * modulo) != 1)
        return -1;
    return (p.first + modulo) % modulo;
}

//Number theory fft. The size of a must be a power
  of 2
void ntfft(vector<LL> &a, int dir, const PLL
    &root_unity) {
    int n = a.size();
    LL prime = root_unity.first;
    LL basew = mod_pow(root_unity.second, (prime-1) /
        n, prime);
    if (dir < 0) basew = mod_inv(basew, prime);
    for (int m = n; m >= 2; m >>= 1) {
        int mh = m >> 1;
        LL w = 1;
        for (int i = 0; i < mh; i++) {
            for (int j = i; j < n; j += m) {
                int k = j + mh;
                LL x = (a[j] - a[k] + prime) % prime;
                a[j] = (a[j] + a[k]) % prime;
                a[k] = (w * x) % prime;
            }
            w = (w * basew) % prime;
        }
        basew = (basew * basew) % prime;
    }
    int i = 0;
```

```
for (int j = 1; j < n - 1; j++) {
    for (int k = n >> 1; k > (i ^= k); k >>= 1);
    if (j < i) swap(a[i], a[j]);
}
}
```

## 9.13 pollard rho factorize

```
long long pollard_rho(long long n) {
    long long x, y, i = 1, k = 2, d;
    x = y = rand() % n;
    while (1) {
        ++i;
        x = mod_mul(x, x, n);
        x += 2;
        if (x >= n) x -= n;
        if (x == y) return 1;
        d = __gcd(abs(x - y), n);
        if (d != 1) return d;
        if (i == k) {
            y = x;
            k *= 2;
        }
    }
    return 1;
}
```

```
// Returns a list with the prime divisors of n
vector<long long> factorize(long long n) {
    vector<long long> ans;
    if (n == 1)
        return ans;
    if (miller_rabin(n)) {
        ans.push_back(n);
    } else {
        long long d = 1;
        while (d == 1)
            d = pollard_rho(n);
        vector<long long> dd = factorize(d);
        ans = factorize(n / d);
        for (int i = 0; i < dd.size(); ++i)
            ans.push_back(dd[i]);
    }
    return ans;
}
```

## 9.14 primes

```
namespace primes {
```

```

const int MP = 100001;
bool sieve[MP];
long long primes[MP];
int num_p;
void fill_sieve() {
    num_p = 0;
    sieve[0] = sieve[1] = true;
    for (long long i = 2; i < MP; ++i) {
        if (!sieve[i]) {
            primes[num_p++] = i;
            for (long long j = i * i; j < MP; j += i)
                sieve[j] = true;
        }
    }
}

// Finds prime numbers between a and b, using
// basic primes up to sqrt(b)
// a must be greater than 1.
vector<long long> seg_sieve(long long a, long
    long b) {
    long long ant = a;
    a = max(a, 3LL);
    vector<bool> pmap(b - a + 1);
    long long sqrt_b = sqrt(b);
    for (int i = 0; i < num_p; ++i) {
        long long p = primes[i];
        if (p > sqrt_b) break;
        long long j = (a + p - 1) / p;
        for (long long v = (j == 1) ? p + p : j * p;
            v <= b; v += p) {
            pmap[v - a] = true;
        }
    }
    vector<long long> ans;
    if (ant == 2) ans.push_back(2);
    int start = a % 2 ? 0 : 1;
    for (int i = start, I = b - a + 1; i < I; i +=
        2)
        if (pmap[i] == false)
            ans.push_back(a + i);
    return ans;
}

vector<pair<int, int>> factor(int n) {
    vector<pair<int, int>> ans;
    if (n == 0) return ans;
    for (int i = 0; primes[i] * primes[i] <= n;
        ++i) {
        if ((n % primes[i]) == 0) {
            int expo = 0;
            while ((n % primes[i]) == 0) {
                expo++;
                n /= primes[i];
            }
        }
    }
}

```

```

        ans.emplace_back(primes[i], expo);
    }
}

if (n > 1) {
    ans.emplace_back(n, 1);
}
return ans;
}
}

```

## 9.15 totient sieve

```

for (int i = 1; i < MN; i++)
    phi[i] = i;

for (int i = 1; i < MN; i++)
    if (!sieve[i]) // is prime
        for (int j = i; j < MN; j += i)
            phi[j] -= phi[j] / i;

```

## 9.16 totient

```

long long totient(long long n) {
    if (n == 1) return 0;
    long long ans = n;
    for (int i = 0; primes[i] * primes[i] <= n; ++i) {
        if ((n % primes[i]) == 0) {
            while ((n % primes[i]) == 0) n /= primes[i];
            ans -= ans / primes[i];
        }
    }
    if (n > 1) {
        ans -= ans / n;
    }
    return ans;
}

```

## 10 Strings

### 10.1 Incremental Aho Corasick

```

class IncrementalAhoCorasick {
    static const int Alphabets = 26;
    static const int AlphabetBase = 'a';
    struct Node {

```

```

        Node *fail;
        Node *next[Alphabets];
        int sum;
        Node() : fail(NULL), next{}, sum(0) {}
    };

```

```

struct String {
    string str;
    int sign;
};

```

public:

```

//totalLen = sum of (len + 1)
void init(int totalLen) {
    nodes.resize(totalLen);
    nNodes = 0;
    strings.clear();
    roots.clear();
    sizes.clear();
    que.resize(totalLen);
}

```

```

void insert(const string &str, int sign) {
    strings.push_back(String{ str, sign });
    roots.push_back(nodes.data() + nNodes);
    sizes.push_back(1);
    nNodes += (int)str.size() + 1;
    auto check = [&]() { return sizes.size() > 1 &&
        sizes.end()[-1] == sizes.end()[-2]; };
    if(!check())
        makePMA(strings.end() - 1, strings.end(),
            roots.back(), que);
    while(check()) {
        int m = sizes.back();
        roots.pop_back();
        sizes.pop_back();
        sizes.back() += m;
        if(!check())
            makePMA(strings.end() - m * 2,
                strings.end(), roots.back(), que);
    }
}

```

```

int match(const string &str) const {
    int res = 0;
    for(const Node *t : roots)
        res += matchPMA(t, str);
    return res;
}

```

private:

```

static void
makePMA(vector<String>::const_iterator
    begin, vector<String>::const_iterator end,
    Node *nodes, vector<Node*> &que) {

```

```

int nNodes = 0;
Node *root = new(&nodes[nNodes++]) Node();
for(auto it = begin; it != end; ++ it) {
    Node *t = root;
    for(char c : it->str) {
        Node *&n = t->next[c - AlphabetBase];
        if(n == nullptr)
            n = new(&nodes[nNodes++]) Node();
        t = n;
    }
    t->sum += it->sign;
}
int qt = 0;
for(Node *&n : root->next) {
    if(n != nullptr) {
        n->fail = root;
        que[qt++] = n;
    } else {
        n = root;
    }
}
for(int qh = 0; qh != qt; ++ qh) {
    Node *t = que[qh];
    int a = 0;
    for(Node *n : t->next) {
        if(n != nullptr) {
            que[qt++] = n;
            Node *r = t->fail;
            while(r->next[a] == nullptr)
                r = r->fail;
            n->fail = r->next[a];
            n->sum += r->next[a]->sum;
        }
        ++ a;
    }
}

static int matchPMA(const Node *t, const string
    &str) {
    int res = 0;
    for(char c : str) {
        int a = c - AlphabetBase;
        while(t->next[a] == nullptr)
            t = t->fail;
        t = t->next[a];
        res += t->sum;
    }
    return res;
}

vector<Node> nodes;
int nNodes;
vector<String> strings;

```

```

vector<Node*> roots;
vector<int> sizes;
vector<Node*> que;
};

int main() {
    int m;
    while(~scanf("%d", &m)) {
        IncrementalAhoCorasic iac;
        iac.init(600000);
        rep(i, m) {
            int ty;
            char s[300001];
            scanf("%d%s", &ty, s);
            if(ty == 1) {
                iac.insert(s, +1);
            } else if(ty == 2) {
                iac.insert(s, -1);
            } else if(ty == 3) {
                int ans = iac.match(s);
                printf("%d\n", ans);
                fflush(stdout);
            } else {
                abort();
            }
        }
    }
    return 0;
}

```

## 10.2 minimal string rotation

```

// Lexicographically minimal string rotation
int lmsr() {
    string s;
    cin >> s;
    int n = s.size();
    s += s;
    vector<int> f(s.size(), -1);
    int k = 0;
    for (int j = 1; j < 2 * n; ++j) {
        int i = f[j - k - 1];
        while (i != -1 && s[j] != s[k + i + 1]) {
            if (s[j] < s[k + i + 1])
                k = j - i - 1;
            i = f[i];
        }
        if (i == -1 && s[j] != s[k + i + 1]) {
            if (s[j] < s[k + i + 1]) {
                k = j;
            }
            f[j - k] = -1;
        }
    }
}

```

```

    } else {
        f[j - k] = i + 1;
    }
}
return k;
}

```

## 10.3 suffix array

```

const int MAXN = 200005;

const int MAX_DIGIT = 256;
void countingSort(vector<int>& SA, vector<int>& RA,
    int k = 0) {
    int n = SA.size();
    vector<int> cnt(max(MAX_DIGIT, n), 0);
    for (int i = 0; i < n; i++)
        if (i + k < n)
            cnt[RA[i + k]]++;
    else
        cnt[0]++;
    for (int i = 1; i < cnt.size(); i++)
        cnt[i] += cnt[i - 1];
    vector<int> tempSA(n);
    for (int i = n - 1; i >= 0; i--)
        if (SA[i] + k < n)
            tempSA[--cnt[RA[SA[i] + k]]] = SA[i];
        else
            tempSA[--cnt[0]] = SA[i];
    SA = tempSA;
}

vector<int> constructSA(string s) {
    int n = s.length();
    vector<int> SA(n);
    vector<int> RA(n);
    vector<int> tempRA(n);
    for (int i = 0; i < n; i++) {
        RA[i] = s[i];
        SA[i] = i;
    }
    for (int step = 1; step < n; step <= 1) {
        countingSort(SA, RA, step);
        countingSort(SA, RA, 0);
        int c = 0;
        tempRA[SA[0]] = c;
        for (int i = 1; i < n; i++) {
            if (RA[SA[i]] == RA[SA[i - 1]] &&
                RA[SA[i] + step] == RA[SA[i - 1] +
                    step])
                tempRA[SA[i]] = tempRA[SA[i - 1]];
            else
                tempRA[SA[i]] = tempRA[SA[i - 1]] + 1;
        }
    }
}

```



```

        tempRA[SA[i]] = tempRA[SA[i - 1]] +
            1;
    }
    RA = tempRA;
    if (RA[SA[n - 1]] == n - 1) break;
}
return SA;
}

```

```

vector<int> computeLCP(const string& s, const
    vector<int>& SA) {
    int n = SA.size();
    vector<int> LCP(n), PLCP(n), c(n, 0);
    for (int i = 0; i < n; i++)
        c[SA[i]] = i;
    int k = 0;
    for (int j, i = 0; i < n-1; i++) {
        if(c[i] - 1 < 0)
            continue;
        j = SA[c[i] - 1];
        k = max(k - 1, 0);
        while (i+k < n && j+k < n && s[i + k] == s[j
            + k])
            k++;
        PLCP[i] = k;
    }
    for (int i = 0; i < n; i++)
        LCP[i] = PLCP[SA[i]];
    return LCP;
}

```

## 10.4 suffix automaton

```

/*
 * Suffix automaton:
 * This implementation was extended to maintain
 * (online) the
 * number of different substrings. This is
 * equivalent to compute
 * the number of paths from the initial state to
 * all the other
 * states.
 *
 * The overall complexity is O(n)
 * can be tested here:
 * https://www.urionlinejudge.com.br/judge/en/problems/view/1530
 */

struct state {
    int len, link;

```

```

    long long num_paths;
    map<int, int> next;
};

const int MN = 200011;
state sa[MN << 1];
int sz, last;
long long tot_paths;

void sa_init() {
    sz = 1;
    last = 0;
    sa[0].len = 0;
    sa[0].link = -1;
    sa[0].next.clear();
    sa[0].num_paths = 1;
    tot_paths = 0;
}

void sa_extend(int c) {
    int cur = sz++;
    sa[cur].len = sa[last].len + 1;
    sa[cur].next.clear();
    sa[cur].num_paths = 0;
    int p;
    for (p = last; p != -1 && !sa[p].next.count(c); p
        = sa[p].link) {
        sa[p].next[c] = cur;
        sa[cur].num_paths += sa[p].num_paths;
        tot_paths += sa[p].num_paths;
    }

    if (p == -1) {
        sa[cur].link = 0;
    } else {
        int q = sa[p].next[c];
        if (sa[p].len + 1 == sa[q].len) {
            sa[cur].link = q;
        } else {
            int clone = sz++;
            sa[clone].len = sa[p].len + 1;
            sa[clone].next = sa[q].next;
            sa[clone].num_paths = 0;
            sa[clone].link = sa[q].link;
            for (; p != -1 && sa[p].next[c] == q; p =
                sa[p].link) {
                sa[p].next[c] = clone;
                sa[q].num_paths -= sa[p].num_paths;
                sa[clone].num_paths += sa[p].num_paths;
            }
            sa[q].link = sa[cur].link = clone;
        }
    }
}

```

```

    }
    last = cur;
}

```

## 10.5 z algorithm

```

using namespace std;
#include<bits/stdc++.h>

vector<int> compute_z(const string &s){
    int n = s.size();
    vector<int> z(n,0);
    int l,r;
    r = l = 0;
    for(int i = 1; i < n; ++i){
        if(i > r) {
            l = r = i;
            while(r < n and s[r - 1] == s[r])r++;
            z[i] = r - l;r--;
        }else{
            int k = i-l;
            if(z[k] < r - i + 1) z[i] = z[k];
            else {
                l = i;
                while(r < n and s[r - l] == s[r])r++;
                z[i] = r - l;r--;
            }
        }
    }
    return z;
}

int main(){
    //string line;cin>>line;
    string line = "alfalfa";
    vector<int> z = compute_z(line);

    for(int i = 0; i < z.size(); ++i ){
        if(i)cout<<" ";
        cout<<z[i];
    }
    cout<<endl;

    // must print "0 0 0 4 0 0 1"

    return 0;
}

```