

# Checking the information of OS

```
lap@lap-vm:~$ uname -a
Linux lap-vm 4.4.0-31-generic #50-Ubuntu SMP Wed Jul 13 00
:07:12 UTC 2016 x86_64 x86_64 x86_64 GNU/Linux
lap@lap-vm:~$ cat /etc/lsb-release
DISTRIB_ID=Ubuntu
DISTRIB_RELEASE=16.04
DISTRIB_CODENAME=xenial
DISTRIB_DESCRIPTION="Ubuntu 16.04.1 LTS"
lap@lap-vm:~$
```

## Compile the kernel

Before starting to compile you need to install a few packages. Type the following commands in your terminal:

```
sudo apt-get install gcc
sudo apt-get install libncurses5-dev
sudo apt-get install bison
sudo apt-get install flex
sudo apt-get install libssl-dev
sudo apt-get install libelf-dev
sudo apt-get update
```

or

```
apt-get install gcc libncurses5-dev bison flex libssl-dev  
libelf-dev update -y
```

## Get kernel

```
lap@lap-vm:~$ pwd  
/home/lap  
lap@lap-vm:~$ wget http://cdn.kernel.org/pub/linux/kernel/  
v4.x/linux-4.4.2.tar.gz
```

## Extract the kernel source code

```
root@lap-vm:~# tar -xzf linux-4.4.2.tar.gz
```

## Define a new system call pidtoname

```
root@lap-vm:~# cd linux-4.4.2/  
root@lap-vm:~/linux-4.4.2# mkdir pnameid  
root@lap-vm:~/linux-4.4.2# cd pnameid/  
root@lap-vm:~/linux-4.4.2/pnameid# touch pnameid.c pnameid  
.h Makefile
```

## Content pnameid.h file

```
root@lap-vm:~/linux-4.4.2/pnameid# cat pnameid.h
asmlinkage long sys_pnametoid(char* name);
```

## Content pnameid.c file

```
root@lap-vm:~/linux-4.4.2/pnameid# cat pnameid.c
#include <linux/syscalls.h>
#include <linux/kernel.h>
#include <linux/sched.h>
#include <linux/init.h>
#include <linux/string.h>
#include "pnameid.h"
asmlinkage long sys_pnametoid(char* name){
    char buf[32];
    strncpy_from_user(buf, name, sizeof(buf));
    printk("DEBUG: %s", buf);
    struct task_struct *task;
    int pid = -1;
    for_each_process(task){
        if(strcmp(task->comm,buf) == 0){
            pid = task->pid;
        }
    }
    return (long)pid;
}
```

# Content Makefile file

```
root@lap-vm:~/linux-4.4.2/pnameid# cat Makefile
obj-y := pnameid.o
```

## Update Makefile to build Kernel

```
root@lap-vm:~/linux-4.4.2/pnameid# cd ..
root@lap-vm:~/linux-4.4.2# vim Makefile
root@lap-vm:~/linux-4.4.2# cat Makefile | grep "core-y"
core-y      := usr/
core-y      += kernel/ certs/ mm/ fs/ ipc/ security/ crypt
o/ block/ pnameid/
              $(core-y) $(core-m) $(drivers-y) $(drivers-m)
\
root@lap-vm:~/linux-4.4.2# vim arch/x86/entry/syscalls/sys
call_64.tbl
root@lap-vm:~/linux-4.4.2#
root@lap-vm:~/linux-4.4.2# cat arch/x86/entry/syscalls/sys
call_64.tbl | grep pnametoid -C 3
323 common  userfaultfd      sys_userfaultfd
324 common  membarrier       sys_membarrier
325 common  mlock2           sys_mlock2
326 64      pnametoid        sys_pnametoid
#
# x32-specific system call numbers start at 512 to avoid c
ache impact
```

```
# for native 64-bit operation.
```

```
root@lap-vm:~/linux-4.4.2# cat include/linux/syscalls.h |  
grep pnametoid -C 3  
asmlinkage long sys_membarrier(int cmd, int flags);  
  
asmlinkage long sys_mlock2(unsigned long start, size_t len  
, int flags);  
asmlinkage long sys_pnametoid(char* name);  
#endif  
root@lap-vm:~/linux-4.4.2#
```

## Compile and install the kernel:

```
root@lap-vm:~/linux-4.4.2# make menuconfig  
root@lap-vm:~/linux-4.4.2# make -j4  
root@lap-vm:~/linux-4.4.2# make modules_install install
```

## Checking new kernel

```
lap@lap-vm:~$ uname -a  
Linux lap-vm 4.4.2 #1 SMP Tue Apr 30 07:32:43 ICT 2019 x86  
_64 x86_64 x86_64 GNU/Linux
```

## Test the pnameid system call

```
lap@lap-vm:~$ pwd
```

```
/home/lap
```

```
lap@lap-vm:~$ cat test.c
```

```
#include<stdio.h>
```

```
#include<linux/kernel.h>
```

```
#include<sys/syscall.h>
```

```
#include<unistd.h>
```

```
#include<string.h>
```

```
#define MAX_SIZE 32
```

```
int main()
```

```
{
```

```
    // Test syscall pnametoid
```

```
    char name[32];
```

```
    puts("Enter process to find");
```

```
    scanf("%s",name);
```

```
    long int status = syscall(326, name);
```

```
    printf("sys_pnametoid returned %ld\n", status);
```

```
    return 0;
```

```
}
```

```
lap@lap-vm:~$ gcc test.c
```

```
lap@lap-vm:~$ ps -ef | grep compiz
```

```
lap          6138    5700  6 08:03 ?           00:00:26 compiz
```

```
lap          6964    6814  0 08:10 pts/3     00:00:00 grep --c
```

```
olor=auto compiz
```

```
lap@lap-vm:~$
```

```
lap@lap-vm:~$ ./a.out
```

```
Enter process to find  
compiz  
sys_pnametoid returned 6138
```

```
lap@lap-vm:~$ ps -ef | grep perf  
root          28      2  0 08:02 ?          00:00:00 [perf]  
lap          6974   6814  0 08:12 pts/3    00:00:00 grep --c  
olor=auto perf
```

```
lap@lap-vm:~$
```

```
lap@lap-vm:~$ ./a.out
```

```
Enter process to find  
perf  
sys_pnametoid returned 28
```

```
lap@lap-vm:~$
```

```
lap@lap-vm:~$ dmesg | grep "DEBUG"
```

```
[ 285.082165] DEBUG: ssh  
[ 293.566342] DEBUG: bash  
[ 437.508873] DEBUG: sshDEBUG: compiz  
[ 609.100889] DEBUG: perf
```