



Specification Sheet

Relieving Pressure Regulators 5/32" PI Input Port

Performance Data

Temperature Range	Media
-20° to 160° F	Compatible w/ seals

Product Number	Operating Pressure	Cv	Flow (scfm)	
			50 psi	125 psi
R0-RK-7	30 to 125 psi	.27	9.8	22
R11-RK-74	30 to 125 psi	.27	9.8	22
R11-RK-76	30 to 125 psi	.27	9.8	22
R11-RK-77	30 to 125 psi	.27	9.8	22
R11-RK-74-G	30 to 125 psi	.27	9.8	22
R11-RK-76-G	30 to 125 psi	.27	9.8	22
R11-RK-77-G	30 to 125 psi	.27	9.8	22
R0-RP-7	30 to 125 psi	.27	9.8	22
R11-RP-74	30 to 125 psi	.27	9.8	22
R11-RP-76	30 to 125 psi	.27	9.8	22
R11-RP-77	30 to 125 psi	.27	9.8	22
R11-RP-74-G	30 to 125 psi	.27	9.8	22
R11-RP-76-G	30 to 125 psi	.27	9.8	22
R11-RP-77-G	30 to 125 psi	.27	9.8	22

When design makes data critical- contact factory for confirmation. All published information is based on usual manufacturing standards and product applications and is for general reference purposes. Supplied information is in no way a representation of a warranty for product.

Materials

Pressure Regulators
Anodized Aluminum and Electroless Nickel Plated Brass
Body, Buna-N Seals, Stainless Steel Stem , Stainless
Steel Spring