

QRadar & Splunk Deep-Dive MCQs

Q1. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q2. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q3. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q4. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q5. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q6. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q7. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds

- c Network topology only
- d Manual analyst action

Q8. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q9. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q10. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q11. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q12. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q13. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q14. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only

d Manual analyst action

Q15. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q16. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q17. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q18. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q19. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q20. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q21. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q22. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q23. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q24. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q25. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q26. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q27. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q28. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q29. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q30. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q31. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q32. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q33. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q34. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q35. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q36. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q37. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q38. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q39. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q40. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q41. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q42. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q43. In QRadar, offenses are generated based on:

- a Log source availability

- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q44. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q45. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q46. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q47. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q48. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q49. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q50. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds

- c Network topology only
- d Manual analyst action

Q51. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q52. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q53. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q54. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q55. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q56. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q57. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only

d Manual analyst action

Q58. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q59. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q60. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q61. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q62. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q63. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q64. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q65. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q66. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q67. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q68. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q69. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q70. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q71. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q72. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q73. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q74. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q75. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q76. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q77. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q78. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q79. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action

Q80. In QRadar, offenses are generated based on:

- a Log source availability
- b Correlation rules and thresholds
- c Network topology only
- d Manual analyst action