



CS6107 – COMPUTER ARCHITECTURE

Module – 7 INSTRUCTION LEVEL PARALLELISM

Presented By
Dr. S. Muthurajkumar,
Assistant Professor,
Dept. of CT, MIT Campus,
Anna University, Chennai.

MODULE - 7

- Instruction Level Parallelism
- Pipelining
- Overview of pipelining
- Performance
- Pipeline Hazards
- Pipelined datapath and control
- Handling data hazards and control hazards
- Exceptions
- Introduction to advanced ILP

INSTRUCTION LEVEL PARALLELISM

- Simple pipeline checked structural, data hazards in Instruction Decode (Instruction Issue)
- Instead, split ID stage in two:
 - Issue—Decode instructions, check for structural hazards
 - Read operands—Wait until no data hazards, then read operands


TOMASULO

- Avoids WAR, WAW hazards
- Allows loop unrolling in Hard Ware
- Not limited to basic blocks
- Lasting Contributions
 - Dynamic scheduling
 - Register renaming
- 360/91 descendants are PowerPC 604, 620; MIPS R10000; HP-PA 8000; Intel Pentium Pro

TOMASULO ALGORITHM (DATA FLOW)

- Data fed to FU from RS, not through registers
- All data travels over Common Data Bus
 - Broadcasts results to all waiting FUs
 - Also back to registers
 - Avoids RAW hazards by executing an instruction only when its operands are available
- Load and Stores treated as FUs
 - Have own RSs

TOMASULO ORGANIZATION



REGISTER RESULT STATUS

Op: Operation to perform in the unit (e.g., + or −)

Vj, Vk: Value of Source operands

Store buffer has V field, result to be stored

Qj, Qk: Reservation stations producing source registers (value to be written)

Note: $Q_j, Q_k = 0 \Rightarrow$ ready

Store buffers only have Qi for RS producing result

Busy: Indicates reservation station or FU is busy

RESERVATION STATION COMPONENTS

- One entry for each register
- Indicates which functional unit will write
- Blank if no pending instructions will write
- If WAW, lists last to write

THE COMMON DATA BUS

- Normal bus is “Go To”
 - Put data on bus
 - Specify destination
- CDB is “Come From”
 - Put data on bus (64 bits)
 - Specify who is producing it (4 bits, on 360/91)
 - Destination says “I’m waiting for that” and grabs
 - Broadcast: multiple destinations can receive data
 - Destinations can also ignore

Three Stages of Tomasulo's Algorithm

1. Issue—get instruction from FP Op Queue
 - If reservation station free (no structural hazard), control issues instructions & sends operands
 - Picking RS has effect of renaming registers
2. Execute—operate on operands (EX)
 - Watch Common Data Bus to pick up operands from prior instructions
 - When both operands ready, can execute
3. Write result—finish execution (WB)
 - Write to all waiting units via Common Data Bus
 - Mark reservation station available

LATENCIES FOR TOMASULO EXAMPLE

- Floating add: 3 clocks
- Multiply: 10 clocks
- Divide: 40 clocks

Instruction stream

Exec Write

3 Load/Buffers

$$S1 \quad S2 \quad RS \quad RS$$

3 FP Adder R.S.
2 FP Mult R.S.

Clock

	$F0$	$F2$	$F4$	$F6$	$F8$	$F10$	$F12$	\dots	$F30$
FU									

Tomasulo Example Cycle 1

Instruction status:

				Exec	Write
Instruction	<i>j</i>	<i>k</i>	Issue	Comp	Result
LD	F6	34+	R2	1	
LD	F2	45+	R3		
MULTD	F0	F2	F4		
SUBD	F8	F6	F2		
DIVD	F10	F0	F6		
ADDD	F6	F8	F2		

	Busy	Address
Load1	Yes	34+R2
Load2	No	
Load3	No	

Reservation Stations:

				<i>S1</i>	<i>S2</i>	<i>RS</i>	<i>RS</i>
Time	Name	Busy	Op	<i>Vj</i>	<i>Vk</i>	<i>Qj</i>	<i>Qk</i>
	Add1	No					
	Add2	No					
	Add3	No					
	Mult1	No					
	Mult2	No					

Register result status:

Clock

1

	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
FU				Load1					

Tomasulo Example Cycle 2

Instruction status:

				<i>Exec</i> <i>Write</i>			
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Comp</i>	<i>Result</i>	Busy	Address
LD	F6	34+	R2	1		Load1	Yes 34+R2
LD	F2	45+	R3	2		Load2	Yes 45+R3
MULTD	F0	F2	F4			Load3	No
SUBD	F8	F6	F2				
DIVD	F10	F0	F6				
ADDD	F6	F8	F2				

Reservation Stations:

				<i>S1</i>	<i>S2</i>	<i>RS</i>	<i>RS</i>
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Vj</i>	<i>Vk</i>	<i>Qj</i>	<i>Qk</i>
	Add1	No					
	Add2	No					
	Add3	No					
	Mult1	No					
	Mult2	No					

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
2	<i>FU</i>		Load2		Load1					

Note: Can have multiple loads outstanding

Tomasulo Example Cycle 3

Instruction status:

				Exec Write			
Instruction	<i>j</i>	<i>k</i>	Issue	Comp	Result	Busy	Address
LD	F6	34+	R2	1	3	Load1	Yes 34+R2
LD	F2	45+	R3	2		Load2	Yes 45+R3
MULTD	F0	F2	F4	3		Load3	No
SUBD	F8	F6	F2				
DIVD	F10	F0	F6				
ADDD	F6	F8	F2				

Reservation Stations:

				<i>S1</i>	<i>S2</i>	<i>RS</i>	<i>RS</i>
Time	Name	Busy	Op	<i>Vj</i>	<i>Vk</i>	<i>Qj</i>	<i>Qk</i>
	Add1	No					
	Add2	No					
	Add3	No					
	Mult1	Yes	MULTD		R(F4)	Load2	
	Mult2	No					

Register result status:

Clock	F0	F2	F4	F6	F8	F10	F12	...	F30
3	FU	Mult1	Load2		Load1				

- Note: register names are removed (“renamed”) in Reservation Stations; MULT issued
- Load1 completing; what is waiting for Load1?

Tomasulo Example Cycle 4

Instruction status:

				Exec		Write		
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Comp</i>	<i>Result</i>		Busy	Address
LD	F6	34+	R2	1	3	4	Load1	No
LD	F2	45+	R3	2	4		Load2	Yes 45+R3
MULTD	F0	F2	F4	3			Load3	No
SUBD	F8	F6	F2	4				
DIVD	F10	F0	F6					
ADDD	F6	F8	F2					

Reservation Stations:

		<i>S1</i>		<i>S2</i>	<i>RS</i>		<i>RS</i>
Time	Name	Busy	<i>Op</i>	<i>Vi</i>	<i>Vk</i>	<i>Oi</i>	<i>Ok</i>
	Add1	Yes	SUBD	M(A1)			Load2
	Add2	No					
	Add3	No					
	Mult1	Yes	MULTD		R(F4)		Load2
	Mult2	No					

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
4	FU Mult1 Load2 M(A1) Add1								

- Load2 completing; what is waiting for Load2?

Tomasulo Example Cycle 5

Instruction status:

				Exec		Write		
Instruction		<i>j</i>	<i>k</i>	Issue	Comp	Result	Busy	Address
LD	F6	34+	R2	1	3	4	Load1	No
LD	F2	45+	R3	2	4	5	Load2	No
MULTD	F0	F2	F4	3			Load3	No
SUBD	F8	F6	F2	4				
DIVD	F10	F0	F6	5				
ADDD	F6	F8	F2					

Reservation Stations:

				<i>S1</i>	<i>S2</i>	<i>RS</i>	<i>RS</i>
Time	Name	Busy	Op	<i>Vj</i>	<i>Vk</i>	<i>Qj</i>	<i>Qk</i>
2	Add1	Yes	SUBD	M(A1)	M(A2)		
	Add2	No					
	Add3	No					
10	Mult1	Yes	MULTD	M(A2)	R(F4)		
	Mult2	Yes	DIVD		M(A1)	Mult1	

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
5	FU	Mult1	M(A2)		M(A1)	Add1	Mult2			

- Timer starts down for Add1, Mult1

Tomasulo Example Cycle 6

Instruction status:

				Exec Write			
Instruction	<i>j</i>	<i>k</i>	Issue	Comp	Result	Busy	Address
LD	F6	34+	R2	1	3	4	Load1
LD	F2	45+	R3	2	4	5	Load2
MULTD	F0	F2	F4	3			Load3
SUBD	F8	F6	F2	4			
DIVD	F10	F0	F6	5			
ADDD	F6	F8	F2	6			

Reservation Stations:

				<i>S1</i>	<i>S2</i>	<i>RS</i>	<i>RS</i>
Time	Name	Busy	Op	<i>Vj</i>	<i>Vk</i>	<i>Qj</i>	<i>Qk</i>
1	Add1	Yes	SUBD	M(A1)	M(A2)		
	Add2	Yes	ADDD		M(A2)	Add1	
	Add3	No					
9	Mult1	Yes	MULTD	M(A2)	R(F4)		
	Mult2	Yes	DIVD		M(A1)	Mult1	

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
6	FU								
	Mult1	M(A2)		Add2	Add1	Mult2			

- Issue ADDD here despite name dependency on F6?

Tomasulo Example Cycle 7

Instruction status:

				Exec Write			
Instruction	<i>j</i>	<i>k</i>	Issue	Comp	Result	Busy	Address
LD	F6	34+	R2	1	3	4	Load1
LD	F2	45+	R3	2	4	5	Load2
MULTD	F0	F2	F4	3			Load3
SUBD	F8	F6	F2	4	7		
DIVD	F10	F0	F6	5			
ADDD	F6	F8	F2	6			

Reservation Stations:

				<i>S1</i>	<i>S2</i>	<i>RS</i>	<i>RS</i>
Time	Name	Busy	Op	<i>Vj</i>	<i>Vk</i>	<i>Qj</i>	<i>Qk</i>
0	Add1	Yes	SUBD	M(A1)	M(A2)		
	Add2	Yes	ADDD		M(A2)	Add1	
	Add3	No					
8	Mult1	Yes	MULTD	M(A2)	R(F4)		
	Mult2	Yes	DIVD		M(A1)	Mult1	

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
7	FU	Mult1	M(A2)		Add2	Add1	Mult2		

- Add1 (SUBD) completing; what is waiting for it?

Tomasulo Example Cycle 8

Instruction status:

				<i>Exec</i> <i>Write</i>			
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Comp</i>	<i>Result</i>	Busy	Address
LD	F6	34+	R2	1	3	4	Load1
LD	F2	45+	R3	2	4	5	Load2
MULTD	F0	F2	F4	3			Load3
SUBD	F8	F6	F2	4	7	8	
DIVD	F10	F0	F6	5			
ADDD	F6	F8	F2	6			

Reservation Stations:

				<i>S1</i>	<i>S2</i>	<i>RS</i>	<i>RS</i>
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Vj</i>	<i>Vk</i>	<i>Qj</i>	<i>Qk</i>
	Add1	No					
2	Add2	Yes	ADDD	(M-M)	M(A2)		
	Add3	No					
7	Mult1	Yes	MULTD	M(A2)	R(F4)		
	Mult2	Yes	DIVD		M(A1)	Mult1	

Register result status:

		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
Clock	8									
	FU	Mult1	M(A2)		Add2	(M-M)	Mult2			

Tomasulo Example Cycle 9

Instruction status:

				Exec Write			
Instruction	<i>j</i>	<i>k</i>	Issue	Comp	Result	Busy	Address
LD	F6	34+	R2	1	3	4	Load1
LD	F2	45+	R3	2	4	5	Load2
MULTD	F0	F2	F4	3			Load3
SUBD	F8	F6	F2	4	7	8	
DIVD	F10	F0	F6	5			
ADDD	F6	F8	F2	6			

Reservation Stations:

				<i>S1</i>	<i>S2</i>	<i>RS</i>	<i>RS</i>
Time	Name	Busy	Op	<i>Vj</i>	<i>Vk</i>	<i>Qj</i>	<i>Qk</i>
	Add1	No					
1	Add2	Yes	ADDD	(M-M)	M(A2)		
	Add3	No					
6	Mult1	Yes	MULTD	M(A2)	R(F4)		
	Mult2	Yes	DIVD		M(A1)	Mult1	

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
9	FU	Mult1	M(A2)		Add2	(M-M)	Mult2		

Tomasulo Example Cycle 10

Instruction status:

				<i>Exec</i>		<i>Write</i>		
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Comp</i>	<i>Result</i>		Busy	Address
LD	F6	34+	R2	1	3	4	Load1	No
LD	F2	45+	R3	2	4	5	Load2	No
MULTD	F0	F2	F4	3			Load3	No
SUBD	F8	F6	F2	4	7	8		
DIVD	F10	F0	F6	5				
ADDD	F6	F8	F2	6	10			

Reservation Stations:

				<i>S1</i>	<i>S2</i>	<i>RS</i>	<i>RS</i>
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Vj</i>	<i>Vk</i>	<i>Qj</i>	<i>Qk</i>
	Add1	No					
0	Add2	Yes	ADDD	(M-M)	M(A2)		
	Add3	No					
5	Mult1	Yes	MULTD	M(A2)	R(F4)		
	Mult2	Yes	DIVD		M(A1)	Mult1	

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
10	FU								
	Mult1	M(A2)		Add2	(M-M)	Mult2			

- Add2 (ADDD) completing; what is waiting for it?

Tomasulo Example Cycle 11

Instruction status:

				<i>Exec Write</i>			
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Comp</i>	<i>Result</i>	Busy	Address
LD	F6	34+	R2	1	3	4	Load1
LD	F2	45+	R3	2	4	5	Load2
MULTD	F0	F2	F4	3			Load3
SUBD	F8	F6	F2	4	7	8	
DIVD	F10	F0	F6	5			
ADDD	F6	F8	F2	6	10	11	

Reservation Stations:

				<i>S1</i>	<i>S2</i>	<i>RS</i>	<i>RS</i>
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Vj</i>	<i>Vk</i>	<i>Qj</i>	<i>Qk</i>
	Add1	No					
	Add2	No					
	Add3	No					
4	Mult1	Yes	MULTD	M(A2)	R(F4)		
	Mult2	Yes	DIVD		M(A1)	Mult1	

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
11	FU	Mult1	M(A2)	(M-M+M)	(M-M)	Mult2			

- Write result of ADDD here?
- All quick instructions have finished by this cycle

Tomasulo Example Cycle 12

Instruction status:

				<i>Exec Write</i>			
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Comp</i>	<i>Result</i>	Busy	Address
LD	F6	34+	R2	1	3	4	Load1
LD	F2	45+	R3	2	4	5	Load2
MULTD	F0	F2	F4	3			Load3
SUBD	F8	F6	F2	4	7	8	
DIVD	F10	F0	F6	5			
ADDD	F6	F8	F2	6	10	11	

Reservation Stations:

				<i>S1</i>	<i>S2</i>	<i>RS</i>	<i>RS</i>
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Vj</i>	<i>Vk</i>	<i>Qj</i>	<i>Qk</i>
	Add1	No					
	Add2	No					
	Add3	No					
3	Mult1	Yes	MULTD	M(A2)	R(F4)		
	Mult2	Yes	DIVD		M(A1)	Mult1	

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
12	FU	Mult1	M(A2)		(M-M+N)	(M-M)	Mult2		

Tomasulo Example Cycle 13

Instruction status:

				Exec Write			
Instruction	<i>j</i>	<i>k</i>	Issue	Comp	Result	Busy	Address
LD	F6	34+	R2	1	3	4	Load1
LD	F2	45+	R3	2	4	5	Load2
MULTD	F0	F2	F4	3			Load3
SUBD	F8	F6	F2	4	7	8	
DIVD	F10	F0	F6	5			
ADDD	F6	F8	F2	6	10	11	

Reservation Stations:

				<i>S1</i>	<i>S2</i>	<i>RS</i>	<i>RS</i>
Time	Name	Busy	Op	<i>Vj</i>	<i>Vk</i>	<i>Qj</i>	<i>Qk</i>
	Add1	No					
	Add2	No					
	Add3	No					
2	Mult1	Yes	MULTD	M(A2)	R(F4)		
	Mult2	Yes	DIVD		M(A1)	Mult1	

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
13	FU	Mult1	M(A2)		(M-M+N)	(M-M)	Mult2		

Tomasulo Example Cycle 14

Instruction status:

Exec Write

Instruction	<i>j</i>	<i>k</i>	Issue	Comp	Result	Busy	Address
LD	F6	34+	R2	1	3	4	Load1
LD	F2	45+	R3	2	4	5	Load2
MULTD	F0	F2	F4	3			Load3
SUBD	F8	F6	F2	4	7	8	
DIVD	F10	F0	F6	5			
ADDD	F6	F8	F2	6	10	11	

Reservation Stations:

S1 S2 RS RS

Time	Name	Busy	Op	Vj	Vk	Qj	Qk
	Add1	No					
	Add2	No					
	Add3	No					
1	Mult1	Yes	MULTD	M(A2)	R(F4)		
	Mult2	Yes	DIVD		M(A1)	Mult1	

Register result status:

Clock

14

	F0	F2	F4	F6	F8	F10	F12	...	F30
FU	Mult1	M(A2)		(M-M+N	(M-M)	Mult2			

Tomasulo Example Cycle 15

Instruction status:

				<i>Exec Write</i>			
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Comp</i>	<i>Result</i>	Busy	Address
LD	F6	34+	R2	1	3	4	Load1
LD	F2	45+	R3	2	4	5	Load2
MULTD	F0	F2	F4	3	15		Load3
SUBD	F8	F6	F2	4	7	8	
DIVD	F10	F0	F6	5			
ADDD	F6	F8	F2	6	10	11	

Reservation Stations:

				<i>S1</i>	<i>S2</i>	<i>RS</i>	<i>RS</i>
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Vj</i>	<i>Vk</i>	<i>Qj</i>	<i>Qk</i>
	Add1	No					
	Add2	No					
	Add3	No					
0	Mult1	Yes	MULTD	M(A2)	R(F4)		
	Mult2	Yes	DIVD		M(A1)	Mult1	

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
15	FU	Mult1	M(A2)		(M-M+N)	(M-M)	Mult2		

- Mult1 (MULTD) completing; what is waiting for it?

Tomasulo Example Cycle 16

Instruction status:

				Exec Write			
Instruction	<i>j</i>	<i>k</i>	Issue	Comp	Result	Busy	Address
LD	F6	34+	R2	1	3	4	Load1
LD	F2	45+	R3	2	4	5	Load2
MULTD	F0	F2	F4	3	15	16	Load3
SUBD	F8	F6	F2	4	7	8	
DIVD	F10	F0	F6	5			
ADDD	F6	F8	F2	6	10	11	

Reservation Stations:

				<i>S1</i>	<i>S2</i>	<i>RS</i>	<i>RS</i>
Time	Name	Busy	Op	<i>Vj</i>	<i>Vk</i>	<i>Qj</i>	<i>Qk</i>
	Add1	No					
	Add2	No					
	Add3	No					
	Mult1	No					
40	Mult2	Yes	DIVD	M*F4	M(A1)		

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
16	FU	M*F4	M(A2)	(M-M+N	(M-M)	Mult2			

- Just waiting for Mult2 (DIVD) to complete

Faster-than-light computation
(skip a couple of cycles)

Tomasulo Example Cycle 55

Instruction status:

				Exec Write			
Instruction	<i>j</i>	<i>k</i>	Issue	Comp	Result	Busy	Address
LD	F6	34+	R2	1	3	4	Load1
LD	F2	45+	R3	2	4	5	Load2
MULTD	F0	F2	F4	3	15	16	Load3
SUBD	F8	F6	F2	4	7	8	
DIVD	F10	F0	F6	5			
ADDD	F6	F8	F2	6	10	11	

Reservation Stations:

				<i>S1</i>	<i>S2</i>	<i>RS</i>	<i>RS</i>
Time	Name	Busy	Op	<i>Vj</i>	<i>Vk</i>	<i>Qj</i>	<i>Qk</i>
	Add1	No					
	Add2	No					
	Add3	No					
	Mult1	No					
1	Mult2	Yes	DIVD	M*F4	M(A1)		

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
55	FU	M*F4	M(A2)	(M-M+N	(M-M)	Mult2			

Tomasulo Example Cycle 56

Instruction status:

				<i>Exec Write</i>			
Instruction	<i>j</i>	<i>k</i>	<i>Issue</i>	<i>Comp</i>	<i>Result</i>	Busy	Address
LD	F6	34+	R2	1	3	4	Load1
LD	F2	45+	R3	2	4	5	Load2
MULTD	F0	F2	F4	3	15	16	Load3
SUBD	F8	F6	F2	4	7	8	
DIVD	F10	F0	F6	5	56		
ADDD	F6	F8	F2	6	10	11	

Reservation Stations:

				<i>S1</i>	<i>S2</i>	<i>RS</i>	<i>RS</i>
<i>Time</i>	<i>Name</i>	<i>Busy</i>	<i>Op</i>	<i>Vj</i>	<i>Vk</i>	<i>Qj</i>	<i>Qk</i>
	Add1	No					
	Add2	No					
	Add3	No					
	Mult1	No					
0	Mult2	Yes	DIVD	M*F4	M(A1)		

Register result status:

Clock	<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
56	FU	M*F4	M(A2)		(M-M+N	(M-M)	Mult2		

- Mult2 (DIVD) is completing; what is waiting for it?

Tomasulo Example Cycle 57

Instruction status:

				Exec		Write		
Instruction		<i>j</i>	<i>k</i>	Issue	Comp	Result	Busy	Address
LD	F6	34+	R2	1	3	4	Load1	No
LD	F2	45+	R3	2	4	5	Load2	No
MULTD	F0	F2	F4	3	15	16	Load3	No
SUBD	F8	F6	F2	4	7	8		
DIVD	F10	F0	F6	5	56	57		
ADDD	F6	F8	F2	6	10	11		

Reservation Stations:

				<i>S1</i>	<i>S2</i>	<i>RS</i>	<i>RS</i>
Time	Name	Busy	Op	<i>Vj</i>	<i>Vk</i>	<i>Qj</i>	<i>Qk</i>
	Add1	No					
	Add2	No					
	Add3	No					
	Mult1	No					
	Mult2	Yes	DIVD	M*F4	M(A1)		

Register result status:

Clock		<i>F0</i>	<i>F2</i>	<i>F4</i>	<i>F6</i>	<i>F8</i>	<i>F10</i>	<i>F12</i>	...	<i>F30</i>
56	FU	M*F4	M(A2)		(M-M+N	(M-M)	Result			

- Once again: In-order issue, out-of-order execution, and out-of-order completion.

WHY CAN TOMASULO OVERLAP LOOP ITERATIONS?

- Register renaming
 - Multiple iterations use different physical destinations for registers (dynamic loop unrolling).
- Reservation stations
 - Permit instruction issue to advance past integer control-flow operations
 - Also buffer old values of registers
 - Totally avoids WAR stalls
- Another perspective:
 - Tomasulo builds data flow dependency graph on the fly

TWO MAJOR ADVANTAGES OF TOMASULO'S SCHEME

- Distributed hazard-detection logic
 - Distributed reservation stations
 - CDB
 - If multiple instructions waiting on single result, all simultaneously released by CDB broadcast
 - With centralized register file used instead,
 - Units have to read results from registers
 - Means waiting for register bus availability
- Eliminates stalls for WAW and WAR hazards

TOMASULO DRAWBACKS

- Complexity
 - Delays of 360/91, MIPS 10000, Alpha 21264, IBM PPC 620 in CA:AQA 2/e
 - But not in silicon!
- Many associative stores (CDB) at high speed
- Performance limited by Common Data Bus
 - Each CDB must go to multiple functional units
⇒ High capacitance, high wiring density
 - Only one functional unit can complete per cycle
 - Multiple CDBs ⇒ more FU logic for parallel assoc stores
- Non-precise interrupts!
 - We will address this later

REFERENCE

1. David A. Patterson and John L. Hennessy, “Computer Organization and Design: The Hardware/Software Interface”, Fifth Edition, Morgan Kaufmann / Elsevier, 2013.
2. Carl Hamacher, Zvonko Vranesic, Safwat Zaky and Naraig Manjikian, “Computer Organization and Embedded Systems”, Sixth Edition, Tata McGraw Hill, 2012.
3. William Stallings, “Computer Organization and Architecture – Designing for Performance”, Sixth Edition, Pearson Education, 2003.
4. John P. Hayes, “Computer Architecture and Organization”, Third Edition, Tata McGraw Hill, 1998.
5. V.P. Heuring, H.F. Jordan, “Computer Systems Design and Architecture”, Second Edition, Pearson Education, 2004.
6. Behrooz Parhami, “Computer Architecture”, Oxford University Press, 2007.

