


Brooks' theorem

In graph theory, **Brooks' theorem** states a relationship between the maximum degree of a graph and its chromatic number. According to the theorem, in a connected graph in which every vertex has at most Δ neighbors, the vertices can be colored with only Δ colors, except for two cases, complete graphs and cycle graphs of odd length, which require $\Delta + 1$ colors.

The theorem is named after R. Leonard Brooks, who published a proof of it in 1941. A coloring with the number of colors described by Brooks' theorem is sometimes called a *Brooks coloring* or a Δ -coloring.



Complete graphs need one more color than their maximum degree. They and the odd cycles are the only exceptions to Brooks' theorem.

Contents

- Formal statement
- Proof
- Extensions
- Algorithms
- Notes
- References
- External links

Formal statement

For any connected undirected graph G with maximum degree Δ , the chromatic number of G is at most Δ unless G is a complete graph or an odd cycle, in which case the chromatic number is $\Delta + 1$.

Proof

László Lovász (1975) gives a simplified proof of Brooks' theorem. If the graph is not biconnected, its biconnected components may be colored separately and then the colorings combined. If the graph has a vertex v with degree less than Δ , then a greedy coloring algorithm that colors vertices farther from v before closer ones uses at most Δ colors. Therefore, the most difficult case of the proof concerns biconnected Δ -regular graphs with $\Delta \geq 3$. In this case, Lovász shows that one can find a spanning tree such that two nonadjacent neighbors u and w of the root v are leaves in the tree. A greedy coloring starting from u and w and processing the remaining vertices of the spanning tree in bottom-up order, ending at v , uses at most Δ colors. For, when every vertex other than v is colored, it has an uncolored parent, so its already-colored neighbors cannot use up all the free colors, while at v the two neighbors u and w have equal colors so again a free color remains for v itself.

Extensions

A more general version of the theorem applies to list coloring: given any connected undirected graph with maximum degree Δ that is neither a clique nor an odd cycle, and a list of Δ colors for each vertex, it is possible to choose a color for each vertex from its list so that no two adjacent vertices have the same color. In other words, the list chromatic number of a connected undirected graph G never exceeds Δ , unless G is a clique or an odd cycle. This has been proved by Vadim Vizing (1976).

For certain graphs, even fewer than Δ colors may be needed. Bruce Reed (1999) shows that $\Delta - 1$ colors suffice if and only if the given graph has no Δ -clique, *provided* Δ is large enough. For triangle-free graphs, or more generally graphs in which the neighborhood of every vertex is sufficiently sparse, $O(\Delta/\log \Delta)$ colors suffice.^[1]

The degree of a graph also appears in upper bounds for other types of coloring; for edge coloring, the result that the chromatic index is at most $\Delta + 1$ is Vizing's theorem. An extension of Brooks' theorem to total coloring, stating that the total chromatic number is at most $\Delta + 2$, has been conjectured by Mehdi Behzad and Vizing. The Hajnal–Szemerédi theorem on equitable coloring states that any graph has a $(\Delta + 1)$ -coloring in which the sizes of any two color classes differ by at most one.

Algorithms

A Δ -coloring, or even a Δ -list-coloring, of a degree- Δ graph may be found in linear time.^[2] Efficient algorithms are also known for finding Brooks colorings in parallel and distributed models of computation.^[3]

Notes

- Alon, Krivelevich & Sudakov (1999).
- Skulrattanakulchai (2006).
- Karloff (1989); Hajnal & Szemerédi (1990); Panconesi & Srinivasan (1995); Grable & Panconesi (2000).

References

- Alon, Noga; Krivelevich, Michael; Sudakov, Benny (1999), "Coloring graphs with sparse neighborhoods", *Journal of Combinatorial Theory, Series B*, **77** (1): 73–82, doi:10.1006/jctb.1999.1910 (https://doi.org/10.1006%2Fjctb.1999.1910)

- Brooks, R. L. (1941), "On colouring the nodes of a network", *Mathematical Proceedings of the Cambridge Philosophical Society*, **37**: 194–197, doi:10.1017/S030500410002168X (https://doi.org/10.1017%2FS030500410002168X).
- Grable, David A.; Panconesi, Alessandro (2000), "Fast distributed algorithms for Brooks–Vizing colourings", *Journal of Algorithms*, **37**: 85–120, doi:10.1006/jagm.2000.1097 (https://doi.org/10.1006%2Fjagm.2000.1097).
- Hajnal, Péter; Szemerédi, Endre (1990), "Brooks coloring in parallel", *SIAM Journal on Discrete Mathematics*, **3** (1): 74–80, doi:10.1137/0403008 (https://doi.org/10.1137%2F0403008).
- Karloff, H. J. (1989), "An NC algorithm for Brooks' theorem", *Theoretical Computer Science*, **68** (1): 89–103, doi:10.1016/0304-3975(89)90121-7 (https://doi.org/10.1016%2F0304-3975%2889%2990121-7).
- Lovász, L. (1975), "Three short proofs in graph theory", *Journal of Combinatorial Theory, Series B*, **19**: 269–271, doi:10.1016/0095-8956(75)90089-1 (https://doi.org/10.1016%2F0095-8956%2875%2990089-1).
- Panconesi, Alessandro; Srinivasan, Aravind (1995), "The local nature of Δ -coloring and its algorithmic applications", *Combinatorica*, **15** (2): 255–280, doi:10.1007/BF01200759 (https://doi.org/10.1007%2FBF01200759).
- Reed, Bruce (1999), "A strengthening of Brooks' theorem", *Journal of Combinatorial Theory, Series B*, **76** (2): 136–149, doi:10.1006/jctb.1998.1891 (https://doi.org/10.1006%2Fjctb.1998.1891).
- Skulrattanakulchai, San (2006), " Δ -List vertex coloring in linear time", *Information Processing Letters*, **98** (3): 101–106, doi:10.1016/j.ipl.2005.12.007 (https://doi.org/10.1016%2Fj.ipl.2005.12.007).
- Vizing, V. G. (1976), "Vertex colorings with given colors", *Diskret. Analiz.* (in Russian), **29**: 3–10.

External links

- Weisstein, Eric W. "Brooks' Theorem" (http://mathworld.wolfram.com/BrooksTheorem.html). *MathWorld*.

Retrieved from "https://en.wikipedia.org/w/index.php?title=Brooks%27_theorem&oldid=899250201"

This page was last edited on 28 May 2019, at 19:58 (UTC).

Text is available under the Creative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.