

1 Thread API

Vocabularies

1. Void Pointer

- Is a pointer in C that has no associated data type with it
 - Can hold address of any type and can be typecasted to any type

2. Procedure Call

- Is synonymous to void function in C
- Is a statement without return value

Example

```
procedure printSquare(i: Integer) is
begin
    put(i * i);
end printSquare;
...
j := j + 1;
printSquare(j);
do_something_else();
```

3. Function call

- Is synonymous to non-void function in C
- Is a statement with return value

```
function square(i: Integer) return Natural is
begin
    return i * i;
end square;
...
int j = 5;

put(j);

put(square(j));

put(square(j) + 1);
```

4. Locks

- Is also called **mutex**
- Is a **synchronization primitive** used to prevent multiple threads from accessing a shared resource at the same time

5. Critical Section

- Is a piece of code that accesses a shared resource, usually a variable or data structure

1.1 Thread Creation

- Is done using `pthread_create`

1.2 Thread Completion

- Is done using `pthread_join`
 - Suspends the execution of the calling thread until the target thread (that's in `pthread_join`) terminates

1.3 Locks

- Ensures only one thread can enter **critical section** at a time
- Use
 1. Properly initialize lock

Example

```
pthread_mutex_t lock = PTHREAD_MUTEX_INITIALIZER;
```

OR

```
pthread_mutex_t lock;  
int rc = pthread_mutex_init(&lock, NULL);  
assert(rc == 0); // always check success!
```

2. Wrap lock and unlock around **critical section**

Example

```
Lock → [ pthread_mutex_lock(&lock);  
        x = x + 1; // or whatever your critical section is  
        pthread_mutex_unlock(&lock);  
Unlock → ]  
Critical Section
```

3. Destroy lock after use

Example

```
pthread_mutex_destroy(&lock);
```

1.4 Conditional Variable

- Is a queue that threads can put themselves on when it's execution is not desired
 - Queue is FIFO
- Forces thread(s) to wait until another thread does something (a signal) before it can continue
- Use
 - Properly initialize lock and conditional variable

Example

```
pthread_mutex_t lock = PTHREAD_MUTEX_INITIALIZER;  
pthread_cond_t cond = PTHREAD_COND_INITIALIZER;
```

- Put calling thread to sleep using `cond_wait()`

Example

```
Pthread_mutex_lock(&lock);  
while (ready == 0)  
    Pthread_cond_wait(&cond, &lock);  
Pthread_mutex_unlock(&lock);
```

- Wait until some other thread signals it using `cond_signal()`

Example

```
Pthread_mutex_lock(&lock);  
ready = 1;  
Pthread_cond_signal(&cond);  
Pthread_mutex_unlock(&lock);
```

1.5 Compiling and Running

- Requires a `-pthread` tag

```
prompt> gcc -o main main.c -Wall -pthread
```



Required Flag