

1 Address Space

Vocabularies

1. Multiprogramming

- Is a computer running more than one program at a time (like running Excel and Firefox simultaneously).

2. Time Sharing

- Is a basic technique used by an OS to share a resource
- Allows an entity to use the resource for a little while, and then a little while by another, and so forth

Example

CPU

3. Interactivity


- Is the ability of a computer to respond to a user's input

4. Easy to Use

- Is a basic concept in design that describes how easily users can use a product

5. Address Space

- Is a range of discrete addresses where each corresponds to a memory cell



6. Stack

- Is also called **runtime stack**, **automatic memory**
- Is a special region in computer's memory that temporarily stores local variables, function parameters, and return addresses
- Is managed by compiler

7. Heap

- Is a user-managed region in computer memory
- Is used for dynamically-allocated data structures such as linked list, hash-tables, and trees
- Is allocated using `malloc`, `calloc`, and `realloc`

8. Thread

- Is the unit of execution within a process.
 - A process can have anywhere from one thread to many threads

9. Abstraction

- the process of removing physical, spatial, or temporal details or attributes in the study of objects or systems to focus attention on details of greater importance; it is similar in nature to the process of generalization

10. Virtualizing Memory

- Is the process of turning a single storage space in RAM into seemingly infinite number of the single storage space used by multiple programs

11. Virtual Address

- Is the identification of a location in virtual storage that is mapped by the operating system into a location in real storage

Example

Pointer in C (i.e. `&variable_name`)

12. Transparency

- (In OS) is an illusion provided by the OS that should not be visible to applications

13. Efficiency

- the ratio of the useful work performed by a machine or in a process to the total energy

14. Mechanism

- Is a low-level method or protocol that implement a needed piece of functionality.

Example

Context Switching

15. Policies


- Is an algorithm for making some kinds of decision within the OS

Example

Scheduling Policy. That is, what kind of program should the OS run?

1.1 Address Space: Early Systems


- Was really simple



1.2 Multiprogramming and Time Sharing




- **Multiprogramming** was born from the need of many people wanting to run program on expensive computer (early days)



- **Time Sharing** was born from the limitation of batch computing, and programmers feeling tired of long program-debug cycle
- **Interactivity** was born from the need for timely response for each user
- **Protection** Was born from the need to prevent a process from reading or writing other processes' memory

1.3 The Address Space

- Is an easy to use abstraction of physical memory
- Has
 1. Code
 2. **Stack**
 - Grows upward
 3. **Heap**
 - Starts after code
 - Grows downward



1.4 Goal

- **Transparency**
 - A program shouldn't be aware that memory is virtualized
- **Efficiency**
 - **Virtual Memory** must be **efficient** in both time and space
 - * **time** - not making programs to run slow
 - * **space** - not taking too much memory to support structures of virtualization
- **Protection**
 - **Virtual Memory** of a process must be protected from other processes and OS
 - * One process cannot access or affect memory of other processes