Prepare one frozen trial safely

Maintainer preparation workflow using reviewed synthetic Store cases and the existing evaluator. Screenshots are browser-rendered actual CLI summaries, not terminal screenshots or model execution. Requires Python 3.11+, a reviewed frozen experiment, exact trial and supervisor attempt IDs; keep full envelopes outside executor mounts.

1. Select and bind one trial

Invoke trial_dispatch.py prepare with experiment, current_spec, trial_id and attempt_id. Keep the full returned envelope with the trusted supervisor. Release only executor_input (the selected request and files) to the assigned executor after its own path/materialization checks. Runtime and budget digests are declarations, not execution proof.



Prepare one exact frozen trial

Browser rendering of structural fields from actual public CLI output. This is not a terminal screenshot.

Output kind	development_trial_dispatch
Executor receives only	files, request
Supervisor-only binding	attempt_id, experiment_budget_digest, experiment_digest, source_digest, trial
Requested model	offline-v1 (declaration only)
Shared budget	Digest reference only; no per-trial reset
Execution / receipt admission	Not performed / not implemented
Cross-call attempt reservation	Supervisor responsibility

2026-10-18 | Sanitized actual CLI results | No model inference

Actual CLI structural output: selected payload fields and supervisor-owned binding, with no private identifiers or case text.

Expected result: Stale or tampered inputs are refused. Grading criteria, expected answers, other-arm payload and aggregate budget are not included in executor_input.

Prepare one frozen trial safely

Maintainer preparation workflow using reviewed synthetic Store cases and the existing evaluator. Screenshots are browser-rendered actual CLI summaries, not terminal screenshots or model execution. Requires Python 3.11+, a reviewed frozen experiment, exact trial and supervisor attempt IDs; keep full envelopes outside executor mounts.

2. Inspect the preparation journey and limits

Retain the frozen inventory and every attempted outcome with the supervisor. This example used the existing Store export and freeze commands, then prepared all eight scheduled development inputs. Check the stale/unknown-trial refusals and cleanup separately. Preparation does not reserve attempts across calls, launch models, admit receipts or authorize promotion.



Store export -> freeze -> prepare

Actual synthetic CLI workflow. Eight selected inputs were prepared; trials were not executed.

Actual CLI calls	23
Scheduled / prepared	8 / 8
Coverage	English + Korean; both arms and variants
Refusals observed	Stale spec: 1; unknown trial: 1
Owned workspace unchanged	True
Task removed after revoke	True
Temporary root removed	True
Model inference / operational admission	False / false

2026-10-18 | Sanitized actual CLI results | No model inference

Actual synthetic CLI journey: 23 commands, eight preparations, two expected refusals, revoke and owned temporary cleanup.

Expected result: Only preparation is established. The shared experiment budget, actual execution provenance, failed/missing attempt accounting and live admission remain supervisor/evaluator responsibilities.