
Opt in to Codex observations

Scenario: native-observation / workflow-map. 2026-10-18. A committed source, Python 3.11+, Codex and an explicitly authorized disposable project are required. Collection is off by default. Native trust and model access are separate prerequisites.

1. Choose one client and review trust

Open the map: Anytime > Self-improvement and eval > 1. Observe. Follow the native guide to create one exact-project Codex grant and preview its installer registration. Review the four observer definitions in native /hooks before activation; existing planning trust is separate.



Actual current map dialog. Follow its source guide for the authoritative commands and limits.


Expected result: One selected client receives observation delivery. Default installations collect nothing; preview and discovery alone do not prove callbacks executed.

Opt in to Codex observations

Scenario: native-observation / workflow-map. 2026-10-18. A committed source, Python 3.11+, Codex and an explicitly authorized disposable project are required. Collection is off by default. Native trust and model access are separate prerequisites.

2. Check actual callback evidence

In an authorized disposable session, exercise a synthetic read/write and an intentional failure. Inspect native records and planning context separately. Retain exact runtime identity and counts; then revoke the grant and remove owned test delivery.



Browser-rendered selected results from an actual macOS Codex 0.163.0 / GPT-6-Luna run; not a terminal screenshot.


Expected result: All four kinds occurred in this fixture. Codex tool-end status remains unknown even after a nonzero shell result. Revoked no-op was checked through a direct dispatcher, not another native model turn.

Opt in to Codex observations

Scenario: native-observation / workflow-map. 2026-10-18. A committed source, Python 3.11+, Codex and an explicitly authorized disposable project are required. Collection is off by default. Native trust and model access are separate prerequisites.

3. Keep platform blockers visible

Before relying on another host, compare its evidence with the native guide matrix. Treat observed callbacks, usable tools and authenticated model behavior as separate checks. Preserve a blocked result instead of weakening sandbox or authentication boundaries.



Browser rendering of actual Linux results: Codex callbacks/planning passed but tools were blocked; Claude proves initialization/SessionStart only.

Expected result: A partial Linux result does not qualify the complete fixture. Without usable Claude authentication, a model run was not attempted. No WSL, parent lineage, complete delivery or model-effectiveness claim follows.