Application.QueryDocumentSave

Event **QueryDocumentSave(**Doc As Document**,** *Cancel As Boolean***)**

Description

Member of Application

Parameter	Description
Doc	Specifies the document
Cancel	

Copyright 2014 Corel Corporation. All rights reserved.

Application.QueryQuit

Event **QueryQuit(***Cancel As Boolean***)**

Description

Member of Application

Parameter	Description
Cancel	

Copyright 2014 Corel Corporation. All rights reserved.

Application.Quit

Event **Quit()**

Description

Member of Application

The **Quit** event is triggered when the application is closed.

Copyright 2014 Corel Corporation. All rights reserved.

Application.SelectionChange

Event **SelectionChange()**

Description

Member of Application

The **SelectionChange** event is triggered when a selection is changed.

Copyright 2014 Corel Corporation. All rights reserved.

Application.Start

Event **Start()**

Description

Member of Application

The **Start** event is triggered when the application is started.

Copyright 2014 Corel Corporation. All rights reserved.

Application.WindowActivate

Event **WindowActivate(**Doc As Document**,** Window As Window**)**

Description

Member of Application

The **WindowActivate** event is triggered when a window is activated.

Parameter	Description
Doc	Specifies the document
Window	Specifies the window

Copyright 2014 Corel Corporation. All rights reserved.

Application.WindowDeactivate

Event **WindowDeactivate(**Doc As Document**,** Window As Window**)**

Description

Member of Application

The **WindowDeactivate** event is triggered when a window is deactivated.

Parameter	Description
Doc	Specifies the document
Window	Specifies the window

Copyright 2014 Corel Corporation. All rights reserved.

Document.AfterExport

Event AfterExport(*FileName As String*, *Filter As* cdrFilter, *SaveBitmap As Boolean*)

Description

Member of Document

The **AfterExport** event is triggered when a document is exported (that is, when the **Export** dialog box closes).

Parameter	Description
FileName	Specifies the filename
Filter	Specifies the filter
SaveBitmap	

Copyright 2014 Corel Corporation. All rights reserved.

Document.AfterPrint

Event **AfterPrint()**

Description

Member of Document

The **AfterPrint** event is triggered when a document is printed (that is, when the **Print** dialog box closes).

Copyright 2014 Corel Corporation. All rights reserved.

Document.AfterSave

Event **AfterSave(***SaveAs As Boolean***,** *FileName As String***)**

Description

Member of Document

The **AfterSave** event is triggered when a document is saved (that is, when the **Save** dialog box closes).

Parameter	Description
SaveAs	
FileName	Specifies the filename

Copyright 2014 Corel Corporation. All rights reserved.

Document.BeforeExport

Event **BeforeExport(***FileName As String***,** Filter As cdrFilter**,** *SaveBitmap As Boolean***)**

Description

Member of Document

The **BeforeExport** event is triggered when the **Export** dialog box opens.

Parameter	Description
FileName	Specifies the filename
Filter	Specifies the filter
SaveBitmap	

Copyright 2014 Corel Corporation. All rights reserved.

Document.BeforePrint

Event **BeforePrint()**

Description

Member of Document

The **BeforePrint** event is triggered when the **Print** dialog box opens, before printing begins.

Copyright 2014 Corel Corporation. All rights reserved.

Document.BeforeSave

Event **BeforeSave(***SaveAs As Boolean***,** *FileName As String***)**

Description

Member of Document

The **BeforeSave** event is triggered when the **Save** dialog box opens.

Copyright 2014 Corel Corporation. All rights reserved.

Document.Close

Event **Close()**

Description

Member of Document

The **Close** event is triggered when a document is closed.

Copyright 2014 Corel Corporation. All rights reserved.

Document.LayerActivate

Event **LayerActivate(**Layer As Layer**)**

Description

Member of Document

The **LayerActivate** event is triggered when a layer is activated.

Parameter	Description
Layer	Specifies the layer

Copyright 2014 Corel Corporation. All rights reserved.

Document.LayerChange

Event **LayerChange(**Layer As Layer**)**

Description

Member of Document

The **LayerChange** event is triggered when a layer is deactivated.

Parameter	Description
Layer	Specifies the layer

Copyright 2014 Corel Corporation. All rights reserved.

Document.LayerCreate

Event **LayerCreate(**Layer As Layer**)**

Description

Member of Document

The **LayerCreate** event is triggered when a layer is created.

Parameter	Description
Layer	Specifies the layer

Copyright 2014 Corel Corporation. All rights reserved.

Document.LayerDelete

Event **LayerDelete**(*Count As Long*)

Description

Member of Document

The **LayerCreate** event is triggered when a layer is deleted.

Parameter	Description
Count	

Copyright 2014 Corel Corporation. All rights reserved.

Document.Open

Event **Open()**

Description

Member of Document

The **Open** event is triggered when a document is opened.

Copyright 2014 Corel Corporation. All rights reserved.

Document.PageActivate

Event **PageActivate(**Page As Page**)**

Description

Member of Document

The **PageActivate** event is triggered when a page is activated.

Parameter	Description
Page	Specifies the page

Copyright 2014 Corel Corporation. All rights reserved.

Document.PageChange

Event **PageChange(**Page As Page**)**

Description

Member of Document

The **PageDeactivate** event is triggered when a page is deactivated.

Parameter	Description
Page	Specifies the page

Copyright 2014 Corel Corporation. All rights reserved.

Document.PageCreate

Event **PageCreate(**Page As Page**)**

Description

Member of Document

The **PageCreate** event is triggered when a page is created.

Parameter	Description
Page	Specifies the page

Copyright 2014 Corel Corporation. All rights reserved.

Document.PageDelete

Event **PageDelete(***Count As Long***)**

Description

Member of Document

The **PageDelete** event is triggered when a page is deleted.

Parameter	Description
Count	

Copyright 2014 Corel Corporation. All rights reserved.

Document.QueryClose

Event **QueryClose(***Cancel As Boolean***)**

Description

Member of Document

Parameter	Description
Cancel	

Copyright 2014 Corel Corporation. All rights reserved.

Document.QueryExport

Event **QueryExport(***Cancel As Boolean***)**

Description

Member of Document

Parameter	Description
Cancel	

Copyright 2014 Corel Corporation. All rights reserved.

Document.QueryPrint

Event **QueryPrint(***Cancel As Boolean***)**

Description

Member of Document

Parameter	Description
Cancel	

Copyright 2014 Corel Corporation. All rights reserved.

Document.QuerySave

Event **QuerySave**(*Cancel As Boolean*)

Description

Member of Document

Parameter	Description
Cancel	

Copyright 2014 Corel Corporation. All rights reserved.

Document.SelectionChange

Event **SelectionChange()**

Description

Member of Document

The **SelectionChange** event is triggered when a selection is changed.

Copyright 2014 Corel Corporation. All rights reserved.

Document.ShapeChange

Event **ShapeChange(**Shape As Shape**)**

Description

Member of Document

The **ShapeChange** event is triggered when a shape is deactivated.

Parameter	Description
Shape	Specifies the shape

Copyright 2014 Corel Corporation. All rights reserved.

Document.ShapeCreate

Event **ShapeCreate(**Shape As Shape**)**

Description

Member of Document

The **ShapeCreate** event is triggered when a shape is created.

Parameter	Description
Shape	Specifies the shape

Copyright 2014 Corel Corporation. All rights reserved.

Document.ShapeDelete

Event **ShapeDelete(***Count As Long***)**

Description

Member of Document

The **ShapeDelete** event is triggered when a shape is deleted.

Parameter	Description
Count	

Copyright 2014 Corel Corporation. All rights reserved.

Document.ShapeDistort

Event **ShapeDistort(**Shape As Shape**)**

Description

Member of Document

The **ShapeChange** event is triggered when a shape is distorted.

Parameter	Description
Shape	Specifies the shape

Copyright 2014 Corel Corporation. All rights reserved.

Document.ShapeMove

Event **ShapeMove(**Shape As Shape**)**

Description

Member of Document

The **ShapeMove** event is triggered when a shape is moved.

Parameter	Description
Shape	Specifies the shape

Copyright 2014 Corel Corporation. All rights reserved.

Document.ShapeTransform

Event **ShapeTransform(**Shape As Shape**)**

Description

Member of Document

The **ShapeTransform** event is triggered when a shape is transformed.

Parameter	Description
Shape	Specifies the shape

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.DocumentAfterExport

Event **DocumentAfterExport(**Doc As Document**,** *FileName As String*, Filter As cdrFilter**,** *SaveBitmap As Boolean***)**

Description

Member of GlobalMacroStorage

The **DocumentAfterExport** event is triggered when a document is exported (that is, when the **Export** dialog box closes).

Parameter	Description
Doc	Specifies the document
FileName	Specifies the filename
Filter	Specifies the filter
SaveBitmap	

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.DocumentAfterPrint

Event **DocumentAfterPrint(**Doc As Document**)**

Description

Member of GlobalMacroStorage

The **DocumentAfterPrint** event is triggered when a document is printed (that is, when the **Print** dialog box closes).

Parameter	Description
Doc	Specifies the document

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.DocumentAfterSave

Event **DocumentAfterSave(**Doc As Document**,** *SaveAs As Boolean***,** *FileName As String***)**

Description

Member of GlobalMacroStorage

The **DocumentAfterSave** event is triggered when a document is saved (that is, when the **Save** dialog box closes).

Parameter	Description
Doc	Specifies the document
SaveAs	
FileName	Specifies the filename

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.DocumentBeforeExport

Event **DocumentBeforeExport(**Doc As Document**,** *FileName As String*, Filter As cdrFilter**,** *SaveBitmap As Boolean***)**

Description

Member of GlobalMacroStorage

The **DocumentBeforeExport** event is triggered when the **Export** dialog box opens.

Parameter	Description
Doc	Specifies the document
FileName	Specifies the filename
Filter	Specifies the filter
SaveBitmap	

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.DocumentBeforePrint

Event **DocumentBeforePrint(**Doc As Document**)**

Description

Member of GlobalMacroStorage

The **DocumentBeforePrint** event is triggered when the **Print** dialog box opens, before printing begins.

Parameter	Description
Doc	Specifies the document

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.DocumentBeforeSave

Event **DocumentBeforeSave(**Doc As Document**,** *SaveAs As Boolean*, *FileName As String***)**

Description

Member of GlobalMacroStorage

The **DocumentBeforeSave** event is triggered when the **Save** dialog box opens.

Parameter	Description
Doc	Specifies the document
SaveAs	
FileName	Specifies the filename

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.DocumentClose

Event **DocumentClose**(Doc As Document)

Description

Member of GlobalMacroStorage

The **DocumentClose** event is triggered when a document is closed.

Parameter	Description
Doc	Specifies the document

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.DocumentNew

Event **DocumentNew(**Doc As Document, *FromTemplate As Boolean*, *Template As String*, *IncludeGraphics As Boolean***)**

Description

Member of GlobalMacroStorage

The **DocumentNew** event is triggered when a document is created.

Parameter	Description
Doc	Specifies the document
FromTemplate	Specifies whether to create the document from a template
Template	Specifies the template to use
IncludeGraphics	Specifies whether to include graphics

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.DocumentOpen

Event **DocumentOpen(**Doc As Document**,** *FileName As String***)**

Description

Member of GlobalMacroStorage

The **DocumentOpen** event is triggered when a document is opened.

Parameter	Description
Doc	Specifies the document
FileName	Specifies the filename

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.OnPluginCommand

Event **OnPluginCommand(***CommandID As String***)**

Description

Member of GlobalMacroStorage

Parameter	Description
CommandID	Specifies the ID of the plugin command

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.OnUpdatePluginCommand

Event **OnUpdatePluginCommand(***CommandID As String*, *Enabled As Boolean*, Checked As cdrCommandCheckState**)**

Description

Member of GlobalMacroStorage

Parameter	Description
CommandID	Specifies the ID of the plugin command
Enabled	
Checked	

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.QueryDocumentClose

Event **QueryDocumentClose(**Doc As Document**,** *Cancel As Boolean***)**

Description

Member of GlobalMacroStorage

Parameter	Description
Doc	Specifies the document
Cancel	

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.QueryDocumentExport

Event **QueryDocumentExport(**Doc As Document**,** *Cancel As Boolean***)**

Description

Member of GlobalMacroStorage

Parameter	Description
Doc	Specifies the document
Cancel	

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.QueryDocumentPrint

Event **QueryDocumentPrint(**Doc As Document**,** *Cancel As Boolean***)**

Description

Member of GlobalMacroStorage

Parameter	Description
Doc	Specifies the document
Cancel	

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.QueryDocumentSave

Event **QueryDocumentSave(**Doc As Document**,** *Cancel As Boolean***)**

Description

Member of GlobalMacroStorage

Parameter	Description
Doc	Specifies the document
Cancel	

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.QueryQuit

Event **QueryQuit(***Cancel As Boolean***)**

Description

Member of GlobalMacroStorage

Parameter	Description
Cancel	

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.Quit

Event **Quit()**

Description

Member of GlobalMacroStorage

The **Quit** event is triggered when the application is closed.

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.SelectionChange

Event **SelectionChange()**

Description

Member of GlobalMacroStorage

The **SelectionChanged** event is triggered when a selection is changed.

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.Start

Event **Start()**

Description

Member of GlobalMacroStorage

The **Start** event is triggered when the application is started.

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.WindowActivate

Event **WindowActivate(**Doc As Document**,** Window As Window**)**

Description

Member of GlobalMacroStorage

The **WindowActivate** event is triggered when a window is activated.

Parameter	Description
Doc	Specifies the document
Window	Specifies the window

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage.WindowDeactivate

Event **WindowDeactivate(**Doc As Document**,** Window As Window**)**

Description

Member of GlobalMacroStorage

The **WindowDeactivate** event is triggered when a window is deactivated.

Parameter	Description
Doc	Specifies the document
Window	Specifies the window

Copyright 2014 Corel Corporation. All rights reserved.

EdgeSnapPoint

Properties

Description

The **EdgeSnapPoint** class represents edge snap points.

Copyright 2014 Corel Corporation. All rights reserved.

EdgeSnapPoint.SegmentIndex

Property **SegmentIndex** As Long

Description

Member of EdgeSnapPoint

The **SegmentIndex** property returns a read-only value that is associated with the segment index number that is referenced by an edge snap point.

Copyright 2014 Corel Corporation. All rights reserved.

EdgeSnapPoint.SegmentOffset

Property **SegmentOffset** As Double

Description

Member of EdgeSnapPoint

The **SegmentIndex** property returns a read-only value that is associated with the time parameter (or offset) along a segment.

Copyright 2014 Corel Corporation. All rights reserved.

Effect

Properties Methods

Description

The **Effect** class represents the settings for an effect in CorelDRAW.

Copyright 2014 Corel Corporation. All rights reserved.

Effect.Application

Property **Application** As Application

Description

Member of Effect

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Effect.Blend

Property **Blend** As EffectBlend

Description

Member of Effect

The **Blend** property returns the EffectBlend object for the blend effect.

The **Blend** property returns a read-only value.

VBA example

The following VBA example determines whether a blend effect has been applied to the selected shape. If so, it changes the number of blend steps to three.

```
Sub Test()
 Dim e As Effect
 For Each e In ActiveShape.Effects
  If e.Type = cdrBlend Then
   e.Blend.Steps = 3
   Exit For
  End If
 Next e
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Effect.Clear

Sub **Clear()**

Description

Member of Effect

The **Clear** method removes the current effect from an object.

VBA example

The following VBA example clears all effects applied to the active shape.

```
Sub Test()
 Dim e As Effect
 For Each e In ActiveShape.Effects
  e.Clear
 Next e
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Effect.CloneParent

Property **CloneParent** As Effect

Description

Member of Effect

The **CloneParent** property points to the effect object from which the current effect is cloned. Any changes to the clone parent effect are automatically reflected in the cloned effect (or effects).

In order for this property to be effective, there must be a clone-master relationship between objects in the active document and the cloned object must be the active object.

The **CloneParent** property returns a read-only value.

Example

Here is a code example:

```
Sub Test()
 ActiveShape.Effects(1).CloneParent.Blend.Steps = 5
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Effect.Clones

Property **Clones** As Effects

Description

Member of Effect

The **Clones** property returns a collection of effect objects comprised of clones of the current effect.

The **Clones** property returns a read-only value.

VBA example

The following VBA example shows the number of effects cloned from the current effect.

```
Sub Test()
 MsgBox ActiveShape.Effects(1).Clones.Count
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Effect.Contour

Property **Contour** As EffectContour

Description

Member of Effect

The **Contour** property returns the EffectContour object for the contour effect.

The **Contour** property returns a read-only value.

VBA example

The following VBA example determines if a contour effect is applied to the selected shape. If so, it changes the type of color blend and the direction of the contour.

```
Sub Test()
 Dim e As Effect
 For Each e In ActiveShape.Effects
  If e.Type = cdrContour Then
   e.Contour.Direction = cdrContourOutside
   e.Contour.ColorBlendType = cdrRainbowCWFountainFillBlend
   Exit For
  End If
 Next e
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Effect.ControlPath

Property **ControlPath** As EffectControlPath

Description

Member of Effect

The **ControlPath** property returns an EffectControlPath object.

The **ControlPath** property returns a read-only value.

VBA example

The following VBA example checks whether there are any blends or text attached to the currently selected path. All blends are changed so that the object's transition in color from yellow to blue, and all text objects become filled with red.

```
Sub Test()
 Dim e1 As Effect, e2 As Effect
 For Each e1 In ActiveShape.Effects
  If e1.Type = cdrControlPath Then
   MsgBox "There are " & e1.ControlPath.Effects.Count & " effect objects on this path"
   For Each e2 In e1.ControlPath.Effects
    Select Case e2.Type
     Case cdrTextOnPath
      e2.TextOnPath.Text.Fill.UniformColor.RGBAssign 255, 0, 0
     Case cdrBlend
      e2.Blend.StartShape.Fill.UniformColor.RGBAssign 255, 255, 0
      e2.Blend.EndShape.Fill.UniformColor.RGBAssign 0, 0, 255
    End Select
   Next e2
   Exit For
  End If
 Next e1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Effect.Custom

Property **Custom** As CustomEffect

Description

Member of Effect

The **Custom** property returns properties of a custom effect.

The **Custom** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Effect.Distortion

Property **Distortion** As EffectDistortion

Description

Member of Effect

The **Distortion** property returns the EffectDistortion object for the distortion effect.

The **Distortion** property returns a read-only value.

VBA example

The following VBA example changes properties of the distortion effect for the active shape.

```
Sub Test()
 Dim e As Effect
 For Each e In ActiveShape.Effects
  If e.Type = cdrDistortion Then
   Select Case e.Distortion.Type
    Case cdrDistortionZipper
     e.Distortion.Zipper.Amplitude = 50
    Case cdrDistortionTwister
     e.Distortion.Twister.Angle = 120
    Case cdrDistortionPushPull
     e.Distortion.PushPull.Amplitude = 70
   End Select
  End If
 Next e
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Effect.DropShadow

Property **DropShadow** As EffectDropShadow

Description

Member of Effect

The **DropShadow** property returns EffectDropShadow for the drop-shadow effect.

The **DropShadow** property returns a read-only value.

VBA example

The following VBA example changes properties of the drop shadow applied to the active shape.

```
Sub Test()
 Dim e As Effect
 For Each e In ActiveShape.Effects
  If e.Type = cdrDropShadow Then
   e.DropShadow.Color.RGBAssign 255, 0, 0
   e.DropShadow.Feather = 30
  End If
 Next e
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Effect.Envelope

Property **Envelope** As EffectEnvelope

Description

Member of Effect

The **Envelope** property returns the EffectEnvelope object for the envelope effect.

The **Envelope** property returns a read-only value.

VBA example

The following VBA example selects a preset envelope for the selected shape.

```
Sub Test()
 Dim e As Effect
 For Each e In ActiveShape.Effects
  If e.Type = cdrEnvelope Then
   e.Envelope.Select 5
  End If
 Next e
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Effect.Extrude

Property **Extrude** As EffectExtrude

Description

Member of Effect

The **Extrude** property returns the EffectExtrude object for the extrusion effect.

The **Extrude** property returns a read-only value.

VBA example

The following VBA example checks all extruded objects on a page to make sure that no extrudes have an extrusion depth greater than **10**.

```
Sub Test()
 Dim s As Shape
 Dim e As Effect
 For Each s In ActivePage.Shapes
  For Each e In s.Effects
   If e.Type = cdrExtrude Then
    If e.Extrude.Depth > 10 Then e.Extrude.Depth = 10
   End If
  Next e
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Effect.Lens

Property **Lens** As EffectLens

Description

Member of Effect

The **Lens** property returns the EffectLens object for the lens effect.

The **Lens** property returns a read-only value.

VBA example

The following VBA example creates an ellipse and applies a frozen fisheye lens to it.

```
Sub Test()
 Dim s As Shape, e As Effect
 Dim x As Double, y As Double
 x = ActivePage.SizeWidth / 2
 y = ActivePage.SizeHeight / 2
 Set s = ActiveLayer.CreateEllipse2(x, y, 2)
 Set e = s.CreateLens(cdrLensFishEye, 100)
 e.Lens.Freeze
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Effect.Parent

Property **Parent** As Effects

Description

Member of Effect

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Effect.Perspective

Property **Perspective** As EffectPerspective

Description

Member of Effect

The **Perspective** property returns the EffectPerspective object for the perspective effect.

The **Perspective** property returns a read-only value.

VBA example

The following VBA example creates a rectangular grid in the lower-left corner of a 8.5" × 11" page, and applies horizontal perspective with a vanishing point at the lower-right corner of the page. It then modifies the perspective to add a vertical vanishing point at the upper-left corner of the page.

```
Sub Test()
 Dim s As Shape, e As Effect
 Set s = ActiveLayer.CreateGridBoxes(0, 0, 3, 3, 7, 7)
 Set e = s.CreatePerspective(8.5, 0)
 e.Perspective.VertVanishingPointX = 0
 e.Perspective.VertVanishingPointY = 11
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Effect.Separate

Function **Separate()** As ShapeRange

Description

Member of Effect

The **Separate** method separates effect-generated shapes from their control object(s).

VBA example

The following VBA example creates two circles, builds a blend effect between them, then separates the blend, ungroups the blend steps, and scatters them randomly.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Dim s As Shape
 Dim g As ShapeRange, stps As ShapeRange
 Set s1 = ActiveLayer.CreateEllipse(0, 0, 2, 2)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 Set s2 = ActiveLayer.CreateEllipse(6, 6, 7, 7)
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 s1.CreateBlend s2
 Set g = s1.Effects(1).Separate
 Set stps = g(1).Shapes.All
 g(1).Ungroup
 For Each s In stps
  s.Move (Rnd() - 0.5) * s.SizeWidth, (Rnd() - 0.5) * s.SizeHeight
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Effect.TextOnPath

Property **TextOnPath** As EffectTextOnPath

Description

Member of Effect

The **TextOnPath** property returns the EffectTextOnPath object for fitting text to a path.

The **TextOnPath** property returns a read-only value.

VBA example

The following VBA example sets the distance between the text and its path to 1" for each object with text fit to a path on the active page.

```
Sub Test()
 Dim s As Shape
 Dim e As Effect
 For Each s In ActivePage.FindShapes(Type:=cdrTextShape)
  For Each e In s.Effects
   If e.Type = cdrTextOnPath Then e.TextOnPath.DistanceFromPath = 1
  Next e
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Effect.Type

Property **Type** As cdrEffectType

Description

Member of Effect

The **Type** property returns the type of the current effect. Depending on the type of effect, an object of the effect's properties (for example, blend, contour, distortion, and so on) is accessible.

The **Type** property returns a read-only value of cdrEffectType.

VBA example

The following VBA example changes all blends attached to the selected shape so that they have only two steps.

```
Sub Test()
 Dim s As Shape
 Dim eff As Effect
 Set s = ActiveShape
 For Each eff In s.Effects
  If eff.Type = cdrBlend Then
   eff.Blend.Steps = 2
  End If
 Next eff
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend

Properties Methods

Description

The **EffectBlend** class represents the settings for a blend effect.

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.AccelerateSize

Property **AccelerateSize** As Boolean

Description

Member of EffectBlend

The **AccelerateSize** property returns or specifies whether the size of blend steps accelerates along the path for a blend.

VBA example

The following VBA example creates a non-uniform blend between a rectangle and a circle.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Set s1 = ActiveLayer.CreateEllipse2(2, 2, 1)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 Set s2 = ActiveLayer.CreateRectangle2(4, 4, 1, 1)
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 With s2.CreateBlend(s1).Blend
  .LinkAcceleration = False
  .ColorAcceleration = 50
  .SpacingAcceleration = -50
  .AccelerateSize = True
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.Angle

Property **Angle** As Double

Description

Member of EffectBlend

The **Angle** property returns or specifies the rotation angle of intermediate blend steps.

VBA example

The following VBA example creates a blend between two rectangles. The intermediate blend objects are rotated by 360° during the progression.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Set s1 = ActiveLayer.CreateRectangle2(0, 0, 3, 1)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 Set s2 = ActiveLayer.CreateRectangle2(4, 4, 3, 1)
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 With s2.CreateBlend(s1).Blend
  .Loop = False
  .Angle = 360
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.Application

Property **Application** As Application

Description

Member of EffectBlend

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.BlendGroup

Property **BlendGroup** As Shape

Description

Member of EffectBlend

The **BlendGroup** property returns a Shape object that represents a blend group (that is, all intermediate blend steps).

Blend objects in a group should be separated before working with an individual blend object.

The **BlendGroup** property returns a read-only value.

VBA example

The following VBA example creates a blend between two circles, separates the blend, and moves the blend steps up and to the right. In this example, the Effect.Separate method returns a ShapeRange object, the first element of which is the same blend group shape.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape, eff As Effect, s As Shape
 Set s1 = ActiveLayer.CreateEllipse(0, 10, 2, 8)
 Set s2 = s1.Duplicate(5, -7)
 s1.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
 s2.Fill.UniformColor.CMYKAssign 0, 100, 100, 0
 Set eff = s2.CreateBlend(s1)
 Set s = eff.Blend.BlendGroup
 eff.Separate
 s.Move 1, 1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.ColorAcceleration

Property **ColorAcceleration** As Long

Description

Member of EffectBlend

The **ColorAcceleration** property returns or specifies the rate of color acceleration along a path for a blend. Higher numbers allow the colors to move more quickly through the spectrum as they approach the end shape.

VBA example

The following VBA example creates a non-uniform blend between a rectangle and a circle.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Set s1 = ActiveLayer.CreateEllipse2(2, 2, 1)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 Set s2 = ActiveLayer.CreateRectangle2(4, 4, 1, 1)
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 With s2.CreateBlend(s1).Blend
  .LinkAcceleration = False
  .ColorAcceleration = 50
  .SpacingAcceleration = -50
  .AccelerateSize = True
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.ColorBlendType

Property **ColorBlendType** As cdrFountainFillBlendType

Description

Member of EffectBlend

The **ColorBlendType** property returns or specifies the color transition mode for a blend.

This property returns cdrFountainFillBlendType.

VBA example

The following VBA example finds blends with a rainbow color transition and changes them to direct color blends.

```
Sub Test()
 Dim s As Shape
 Dim b As EffectBlend
 For Each s In ActivePage.Shapes
  If s.Type = cdrBlendGroupShape Then
   Set b = s.Effect.Blend
   If b.ColorBlendType <> cdrDirectFountainFillBlend And _
    b.ColorBlendType <> cdrCustomFountainFillBlend Then
    b.ColorBlendType = cdrDirectFountainFillBlend
   End If
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.CopyFrom

Function **CopyFrom(**Source As EffectBlend**)** As Boolean

Description

Member of EffectBlend

The **CopyFrom** method copies the properties from one blend to another.

Parameter	Description
Source	Specifies the blend and copies its effect properties to the active blend

VBA example

The following VBA example creates a blend between two circles. It then creates another blend and copies the properties from the first one.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape, s3 As Shape, s4 As Shape
 Dim Blend As EffectBlend
 Set s1 = ActiveLayer.CreateEllipse2(0.6, 4.5, 1)
 Set s2 = s1.Duplicate(7.4, 4)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 Set Blend = s1.CreateBlend(s2, 30, cdrRainbowCWFountainFillBlend).Blend
 Set s3 = ActiveLayer.CreateEllipse2(0, 10, 1)
 Set s4 = s3.Duplicate(5, -3)
 s3.Fill.UniformColor.RGBAssign 0, 128, 0
 s4.Fill.UniformColor.RGBAssign 0, 0, 255
 s3.CreateBlend(s4).Blend.CopyFrom Blend
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.EndPoint

Property **EndPoint** As SnapPoint

Description

Member of EffectBlend

The **EndPoint** property returns or specifies the ending mapped node for a blend. The starting and ending mapped nodes determine how the intermediate objects are transformed from the start shape to become the end shape.

VBA example

The following VBA example creates a blend between a circle and a polygon, and specifies the key nodes on the two shapes that the blend uses as starting points of the shapes.

```
Sub Test()
Dim s1 As Shape, s2 As Shape, eff As Effect
Set s1 = ActiveLayer.CreateEllipse2(2, 9, 1)
Set s2 = ActiveLayer.CreatePolygon(4, 3, 6, 5, 5)
s1.Fill.UniformColor.RGBAssign 255, 0, 0
s2.Fill.UniformColor.RGBAssign 255, 255, 0
Set eff = s1.CreateBlend(s2)
With eff.Blend
.MapNodes = True
.StartPoint = s1.SnapPoints.Edge(4, 0)
.EndPoint = s2.SnapPoints.Edge(1, 0)
End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.EndShape

Property **EndShape** As Shape

Description

Member of EffectBlend

The **EndShape** property returns or specifies the end shape for a blend effect.

VBA example

The following VBA example changes all blends to progress from yellow to green by changing the fills of the control shapes.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Type = cdrBlendGroupShape Then
   s.Effect.Blend.StartShape.Fill.UniformColor.RGBAssign 255, 255, 0
   s.Effect.Blend.EndShape.Fill.UniformColor.RGBAssign 0, 128, 0
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.EndShapeOffset

Property **EndShapeOffset** As Double

Description

Member of EffectBlend

The **EndShapeOffset** returns or specifies the offset from the path for the ending shape of a blend.

VBA example

The following VBA example creates a blend and attaches it to a path.

```
Sub Test()
 Dim sPath As Shape, s1 As Shape, s2 As Shape, eff As Effect
 Set sPath = ActiveLayer.CreateCurveSegment(0.6, 4.5, 7.8, 8.5, 5.2, 62, 5.3, -96)
 Set s1 = ActiveLayer.CreateEllipse2(0, 0, 1)
 Set s2 = s1.Duplicate(8, 11)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 Set eff = s1.CreateBlend(s2)
 eff.Blend.Path = sPath
 eff.Blend.StartShapeOffset = 1
 eff.Blend.EndShapeOffset = 2.5
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.FullPath

Property **FullPath** As Boolean

Description

Member of EffectBlend

The **FullPath** property returns or specifies whether a blend follows a full path. A value of True causes the blend to spread along the whole path.

VBA example

The following VBA example creates a blend, attaches it to a path, and stretches it so that it follows the complete length of the path.

```
Sub Test()
 Dim sPath As Shape, s1 As Shape, s2 As Shape
 Set sPath = ActiveLayer.CreateCurveSegment(0.6, 4.5, 7.8, 8.5, 5.2, 62, 5.3, -96)
 Set s1 = ActiveLayer.CreateEllipse2(0, 0, 1)
 Set s2 = s1.Duplicate(5, 5)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 With s1.CreateBlend(s2).Blend
  .Path = sPath
  .FullPath = True
  .RotateShapes = True
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.FuseEnd

Function **FuseEnd()** As Boolean

Description

Member of EffectBlend

The **FuseEnd** method fuses the end components of two blends, attached to one shape, into one blend by removing the intermediate shape.

VBA example

The following VBA example creates two blends between three circles and then merges the blends by removing the middle circle.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape, s3 As Shape
 Dim eff As Effect
 Set s1 = ActiveLayer.CreateEllipse2(0, 0, 1)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 Set s2 = s1.Duplicate(4, 3)
 Set s3 = s1.Duplicate(8, 0)
 s3.OrderFrontOf s2
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 Set eff = s1.CreateBlend(s2)
 s2.CreateBlend s3
 eff.Blend.FuseEnd
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.FuseStart

Function **FuseStart()** As Boolean

Description

Member of EffectBlend

The **FuseStart** method fuses the start components of two blends, attached to one shape, into one blend by removing the intermediate shape.

VBA example

The following VBA example creates two blends from three circles. Then it merges the blends by removing the middle circle.

```
Sub Test()
Dim s1 As Shape, s2 As Shape, s3 As Shape
Dim eff As Effect
Set s1 = ActiveLayer.CreateEllipse2(0, 0, 1)
s1.Fill.UniformColor.RGBAssign 255, 0, 0
Set s2 = s1.Duplicate(4, 3)
Set s3 = s1.Duplicate(8, 0)
s3.OrderFrontOf s2
s2.Fill.UniformColor.RGBAssign 255, 255, 0
Set eff = s1.CreateBlend(s2)
Set eff = s2.CreateBlend(s3)
eff.Blend.FuseStart
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.LinkAcceleration

Property **LinkAcceleration** As Boolean

Description

Member of EffectBlend

The **LinkAcceleration** property returns or specifies a value that links color acceleration to object spacing acceleration for a blend.

VBA example

The following VBA example creates a non-uniform blend between a rectangle and a circle.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Set s1 = ActiveLayer.CreateEllipse2(2, 2, 1)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 Set s2 = ActiveLayer.CreateRectangle2(4, 4, 1, 1)
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 With s2.CreateBlend(s1).Blend
  .LinkAcceleration = False
  .ColorAcceleration = 50
  .SpacingAcceleration = -50
  .AccelerateSize = True
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.Loop

Property **Loop** As Boolean

Description

Member of EffectBlend

The **Loop** property returns or specifies value that indicates whether the blend steps should be placed on a loop.

VBA example

The following VBA example creates a blend between two rectangles. The intermediate blend objects are rotated by 360° during the progression.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Set s1 = ActiveLayer.CreateRectangle2(0, 0, 3, 1)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 Set s2 = ActiveLayer.CreateRectangle2(4, 4, 3, 1)
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 With s2.CreateBlend(s1).Blend
  .Loop = False
  .Angle = 360
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.MapNodes

Property **MapNodes** As Boolean

Description

Member of EffectBlend

The **MapNodes** property returns or specifies whether the nodes are mapped for a blend. The starting and ending mapped nodes determine how the intermediate objects are transformed from the start shape to become the end shape.

VBA example

The following VBA example creates a blend between a circle and a polygon and specifies the key nodes on the two shapes that the blend uses as starting points of the shapes.

```
Sub Test()
Dim s1 As Shape, s2 As Shape, eff As Effect
Set s1 = ActiveLayer.CreateEllipse2(2, 9, 1)
Set s2 = ActiveLayer.CreatePolygon(4, 3, 6, 5, 5)
s1.Fill.UniformColor.RGBAssign 255, 0, 0
s2.Fill.UniformColor.RGBAssign 255, 255, 0
Set eff = s1.CreateBlend(s2)
With eff.Blend
.MapNodes = True
.StartPoint = s1.SnapPoints.Edge(4, 0)
.EndPoint = s2.SnapPoints.Edge(1, 0)
End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.Mode

Property **Mode** As cdrBlendMode

Description

Member of EffectBlend

The **Mode** property returns or specifies how the distance between steps is calculated.

This property returns cdrBlendMode.

VBA example

The following VBA example creates a blend, attaches it to a path, and specifies that the blend steps should be placed at a fixed distance of 0.5" from each other.

```
Sub Test()
 Dim sPath As Shape, s1 As Shape, s2 As Shape
 Set sPath = ActiveLayer.CreateCurveSegment(0.6, 4.5, 7.8, 8.5, 5.2, 62, 5.3, -96)
 Set s1 = ActiveLayer.CreateEllipse2(0.6, 4.5, 1)
 Set s2 = s1.Duplicate(7.4, 4)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 With s1.CreateBlend(s2).Blend
  .Path = sPath
  .Mode = cdrBlendSpacing
  .Spacing = 0.5
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.Parent

Property **Parent** As Effect

Description

Member of EffectBlend

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.Path

Property **Path** As Shape

Description

Member of EffectBlend

The **Path** property returns or specifies the shape to which the blend is attached.

VBA example

The following VBA example creates a blend, attaches it to a path, and stretches it so that it follows the complete length of the path.

```
Sub Test()
 Dim sPath As Shape, s1 As Shape, s2 As Shape
 Set sPath = ActiveLayer.CreateCurveSegment(0.6, 4.5, 7.8, 8.5, 5.2, 62, 5.3, -96)
 Set s1 = ActiveLayer.CreateEllipse2(0, 0, 1)
 Set s2 = s1.Duplicate(5, 5)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 With s1.CreateBlend(s2).Blend
  .Path = sPath
  .FullPath = True
  .RotateShapes = True
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.RotateShapes

Property **RotateShapes** As Boolean

Description

Member of EffectBlend

The **RotateShapes** property returns or specifies whether a blend rotates the blend shapes to follow the direction of the path.

VBA example

The following VBA example creates a blend, attaches it to a path, and stretches it so that it follows the complete length of the path.

```
Sub Test()
 Dim sPath As Shape, s1 As Shape, s2 As Shape
 Set sPath = ActiveLayer.CreateCurveSegment(0.6, 4.5, 7.8, 8.5, 5.2, 62, 5.3, -96)
 Set s1 = ActiveLayer.CreateRectangle2(0, 0, 1, 1)
 Set s2 = s1.Duplicate(5, 5)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 With s1.CreateBlend(s2).Blend
  .Path = sPath
  .FullPath = True
  .RotateShapes = True
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.Spacing

Property **Spacing** As Double

Description

Member of EffectBlend

The **Spacing** property returns or set the spacing for a blend.

VBA example

The following VBA example creates a blend, attaches it to a path, and creates blend steps that are a fixed distance of 0.5" from each other.

```
Sub Test()
 Dim sPath As Shape, s1 As Shape, s2 As Shape
 Set sPath = ActiveLayer.CreateCurveSegment(0.6, 4.5, 7.8, 8.5, 5.2, 62, 5.3, -96)
 Set s1 = ActiveLayer.CreateEllipse2(0.6, 4.5, 1)
 Set s2 = s1.Duplicate(7.4, 4)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 With s1.CreateBlend(s2).Blend
  .Path = sPath
  .Mode = cdrBlendSpacing
  .Spacing = 0.5
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.SpacingAcceleration

Property **SpacingAcceleration** As Long

Description

Member of EffectBlend

The **SpacingAcceleration** property returns or specifies the rate of spacing acceleration along a path for a blend.

VBA example

The following VBA example creates a non-uniform blend between a rectangle and a circle.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Set s1 = ActiveLayer.CreateEllipse2(2, 2, 1)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 Set s2 = ActiveLayer.CreateRectangle2(4, 4, 1, 1)
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 With s2.CreateBlend(s1).Blend
  .LinkAcceleration = False
  .ColorAcceleration = 50
  .SpacingAcceleration = -50
  .AccelerateSize = True
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.Split

Function **Split(***StepNo As Long***)** As Shape

Description

Member of EffectBlend

The **Split** method splits a blend at a specified step. You can split a blend to create a compound blend. The shape in the blend at which point you choose to split the blend becomes the end shape for one component in the blend and the start shape for the other. Thus, the original blend is split into two components.

Parameter	Description
StepNo	Specifies the step in the blend where the split occurs

VBA example

The following VBA example creates a blend between two circles, splits the blend in the middle and moves the intermediate control shape upwards by 3".

```
Sub Test()
 Dim s1 As Shape, s2 As Shape, s3 As Shape
 Dim eff As Effect
 Set s1 = ActiveLayer.CreateEllipse2(0, 0, 1)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 Set s2 = s1.Duplicate(4, 0)
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 Set eff = s1.CreateBlend(s2, 15)
 Set s3 = eff.Blend.Split(8)
 s3.Move 0, 3
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.StartPoint

Property **StartPoint** As SnapPoint

Description

Member of EffectBlend

The **StartPoint** property returns or specifies the starting mapped node for a blend. The starting and ending mapped nodes determine how the intermediate objects are transformed from the start shape to become the end shape.

VBA example

The following VBA example creates a blend between a circle and a polygon and specifies the key nodes on the two shapes that the blend uses as starting points of the shapes.

```
Sub Test()
Dim s1 As Shape, s2 As Shape, eff As Effect
Set s1 = ActiveLayer.CreateEllipse2(2, 9, 1)
Set s2 = ActiveLayer.CreatePolygon(4, 3, 6, 5, 5)
s1.Fill.UniformColor.RGBAssign 255, 0, 0
s2.Fill.UniformColor.RGBAssign 255, 255, 0
Set eff = s1.CreateBlend(s2)
With eff.Blend
.MapNodes = True
.StartPoint = s1.SnapPoints.Edge(4, 0)
.EndPoint = s2.SnapPoints.Edge(1, 0)
End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.StartShape

Property **StartShape** As Shape

Description

Member of EffectBlend

The **StartShape** property returns or specifies the starting shape for a blend effect.

VBA example

The following VBA example changes all blends to progress from yellow to green by changing the fills of the control shapes.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Type = cdrBlendGroupShape Then
   s.Effect.Blend.StartShape.Fill.UniformColor.RGBAssign 255, 255, 0
   s.Effect.Blend.EndShape.Fill.UniformColor.RGBAssign 0, 128, 0
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.StartShapeOffset

Property **StartShapeOffset** As Double

Description

Member of EffectBlend

The **StartShapeOffset** returns or specifies the offset from the path for the start shape of a blend.

VBA example

The following VBA example creates a blend and attaches it to a path.

```
Sub Test()
 Dim sPath As Shape, s1 As Shape, s2 As Shape, eff As Effect
 Set sPath = ActiveLayer.CreateCurveSegment(0.6, 4.5, 7.8, 8.5, 5.2, 62, 5.3, -96)
 Set s1 = ActiveLayer.CreateEllipse2(0, 0, 1)
 Set s2 = s1.Duplicate(8, 11)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 Set eff = s1.CreateBlend(s2)
 eff.Blend.Path = sPath
 eff.Blend.StartShapeOffset = 1
 eff.Blend.EndShapeOffset = 2.5
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectBlend.Steps

Property **Steps** As Long

Description

Member of EffectBlend

The **Steps** property returns or specifies the number of steps in a blend.

VBA example

The following VBA example creates a blend, attaches it to a path, and creates 15 blend steps.

```
Sub Test()
 Dim sPath As Shape, s1 As Shape, s2 As Shape
 Set sPath = ActiveLayer.CreateCurveSegment(0.6, 4.5, 7.8, 8.5, 5.2, 62, 5.3, -96)
 Set s1 = ActiveLayer.CreateEllipse2(0.6, 4.5, 1)
 Set s2 = s1.Duplicate(7.4, 4)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 With s1.CreateBlend(s2).Blend
  .Path = sPath
  .Mode = cdrBlendSteps
  .Steps = 15
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectContour

Properties

Description

The **EffectContour** class represents the settings for a contour effect.

Copyright 2014 Corel Corporation. All rights reserved.

EffectContour.Application

Property **Application** As Application

Description

Member of EffectContour

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

EffectContour.ColorAcceleration

Property **ColorAcceleration** As Long

Description

Member of EffectContour

The **ColorAcceleration** property returns or specifies the rate of color aceleration in a contour effect. Higher numbers allow the colors to move more quickly through the spectrum as they approach the end object. You can change the progression of the outline and fill colors.

VBA example

The following VBA example creates a contour effect with non-uniform spacing and color transition.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(5.5, 4, 2)
 s.Fill.UniformColor.RGBAssign 255, 0, 0
 s.Outline.SetProperties 0.05, , CreateRGBColor(0, 255, 255)
 With s.CreateContour(cdrContourOutside, 0.5, 5, , , CreateRGBColor(255, 255, 0)).Contour
  .LinkAcceleration = False
  .ColorAcceleration = 50
  .SpacingAcceleration = -50
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectContour.ColorBlendType

Property **ColorBlendType** As cdrFountainFillBlendType

Description

Member of EffectContour

The **ColorBlendType** property returns or set the mode of the color blend of a fountain fill in a contour effect.

The **ColorBlendType** property returns cdrFountainFillBlendType.

VBA example

The following VBA example changes all clockwise rainbow-colored transitions to counterclockwise in contour effects.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrContour Then
    If eff.Contour.ColorBlendType = cdrRainbowCWFountainFillBlend Then
     eff.Contour.ColorBlendType = cdrRainbowCCWFountainFillBlend
    End If
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectContour.ContourGroup

Property **ContourGroup** As Shape

Description

Member of EffectContour

The **ContourGroup** property returns the contour group as a Shape object.

The **ContourGroup** property returns a read-only value.

VBA example

The following VBA example creates an ellipse and a rectangle, and applies a contour effect to each shape. It then applies a perspective to the contour group.

```
Sub Test()
 Dim s As Shape, s2 As Shape
 Dim e As Effect
 Set s = ActiveLayer.CreateEllipse2(5, 4, 2)
 s.Fill.UniformColor.RGBAssign 255, 0, 0
 Set s2 = ActiveLayer.CreateRectangle(3, 3, 5, 5)
 s2.Fill.UniformColor.RGBAssign 0, 0, 255
 For Each s In ActiveLayer.Shapes.All
  Set e = s.CreateContour(cdrContourInside, , 5)
  e.Contour.ContourGroup.CreatePerspective 2, 2
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectContour.CornerType

Property **CornerType** As cdrContourCornerType

Description

Member of EffectContour

The **CornerType** property returns or specifies the type of contour to apply at the cusp corners.

The **CornerType** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

EffectContour.Direction

Property **Direction** As cdrContourDirection

Description

Member of EffectContour

The **Direction** property returns or specifies the direction of a contour effect.

The **Direction** property returns a value of cdrContourDirection.

VBA example

The following VBA example checks all contours on the current page and changes them as follows: all outside contours are to have twice as many steps, and all inside contours are to have a step distance of half of the previous size. The contours to the center of the shape are left unchanged.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrContour Then
    Select Case eff.Contour.Direction
     Case cdrContourOutside
      eff.Contour.Steps = eff.Contour.Steps * 2
     Case cdrContourInside
      eff.Contour.Offset = eff.Contour.Offset / 2
     Case cdrContourToCenter
      ' Do nothing
    End Select
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectContour.EndCapType

Property **EndCapType** As cdrContourEndCapType

Description

Member of EffectContour

The **EndCapType** property returns or specifies the type of contour to apply at the end of open paths.

The **EndCapType** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

EffectContour.FillColor

Property **FillColor** As Color

Description

Member of EffectContour

The **FillColor** property returns or specifies the starting color of a fountain fill for the last contour shape.

VBA example

The following VBA example creates a contour with a color transition in the fountain fill.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(4.25, 5.5, 2)
 s.Fill.ApplyFountainFill CreateCMYKColor(100, 0, 0, 0), CreateCMYKColor(0, 0, 100, 0)
 s.Outline.SetProperties 0.02, , CreateCMYKColor(0, 0, 100, 0)
 With s.CreateContour(cdrContourOutside, 0.1, 20).Contour
  .FillColor.CMYKAssign 0, 0, 100, 0
  .FillColorTo.CMYKAssign 0, 100, 100, 0
  .OutlineColor.CMYKAssign 100, 0, 100, 0
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectContour.FillColorTo

Property **FillColorTo** As Color

Description

Member of EffectContour

The **FillColorTo** property returns or specifies the ending color of a fountain fill for the last contour shape.

VBA example

The following VBA example creates a contour with a color transition in the fountain fill.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(4.25, 5.5, 2)
 s.Fill.ApplyFountainFill CreateCMYKColor(100, 0, 0, 0), CreateCMYKColor(0, 0, 100, 0)
 s.Outline.SetProperties 0.02, , CreateCMYKColor(0, 0, 100, 0)
 With s.CreateContour(cdrContourOutside, 0.1, 20).Contour
  .FillColor.CMYKAssign 0, 0, 100, 0
  .FillColorTo.CMYKAssign 0, 100, 100, 0
  .OutlineColor.CMYKAssign 100, 0, 100, 0
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectContour.LinkAcceleration

Property **LinkAcceleration** As Boolean

Description

Member of EffectContour

The **LinkAcceleration** property returns or specifies whether color acceleration is linked to object-spacing acceleration in a contour effect.

VBA example

The following VBA example creates a contour effect with non-uniform spacing and color transition.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(5.5, 4, 2)
 s.Fill.UniformColor.RGBAssign 255, 0, 0
 s.Outline.SetProperties 0.05, , CreateRGBColor(0, 255, 255)
 With s.CreateContour(cdrContourOutside, 0.5, 5, , , CreateRGBColor(255, 255, 0)).Contour
  .LinkAcceleration = False
  .ColorAcceleration = 50
  .SpacingAcceleration = -50
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectContour.MiterLimit

Property **MiterLimit** As Double

Description

Member of EffectContour

The **MiterLimit** property returns or specifies the miter limit for contour corners.

The **MiterLimit** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

EffectContour.Offset

Property **Offset** As Double

Description

Member of EffectContour

The **Offset** property returns or specifies the offset distance, in document units, between contour lines in a contour effect. This automatically adjusts the number of contour steps.

VBA example

The following VBA example checks all contours on the current page and changes them as follows: all outside contours are to have twice as many steps, and all inside contours are to have a step distance of half of the previous size. The contours to the center of the shape are left unchanged.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrContour Then
    Select Case eff.Contour.Direction
     Case cdrContourOutside
      eff.Contour.Steps = eff.Contour.Steps * 2
     Case cdrContourInside
      eff.Contour.Offset = eff.Contour.Offset / 2
     Case cdrContourToCenter
      ' Do nothing
    End Select
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectContour.OutlineColor

Property **OutlineColor** As Color

Description

Member of EffectContour

The **OutlineColor** property returns or specifies the outline color of the last contour step.

VBA example

The following VBA example creates a contour with a color transition in the fountain fill.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(4.25, 5.5, 2)
 s.Fill.ApplyFountainFill CreateCMYKColor(100, 0, 0, 0), CreateCMYKColor(0, 0, 100, 0)
 s.Outline.SetProperties 0.02, , CreateCMYKColor(0, 0, 100, 0)
 With s.CreateContour(cdrContourOutside, 0.1, 20).Contour
  .FillColor.CMYKAssign 0, 0, 100, 0
  .FillColorTo.CMYKAssign 0, 100, 100, 0
  .OutlineColor.CMYKAssign 100, 0, 100, 0
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectContour.Parent

Property **Parent** As Effect

Description

Member of EffectContour

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

EffectContour.SpacingAcceleration

Property **SpacingAcceleration** As Long

Description

Member of EffectContour

The **SpacingAcceleration** property returns or specifies the rate of object acceleration in a contour effect. You can change the progression of the size of intermediate objects.

VBA example

The following VBA example creates a contour effect with non-uniform spacing and color transition.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(5.5, 4, 2)
 s.Fill.UniformColor.RGBAssign 255, 0, 0
 s.Outline.SetProperties 0.05, , CreateRGBColor(0, 255, 255)
 With s.CreateContour(cdrContourOutside, 0.5, 5, , , CreateRGBColor(255, 255, 0)).Contour
  .LinkAcceleration = False
  .ColorAcceleration = 50
  .SpacingAcceleration = -50
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectContour.Steps

Property **Steps** As Long

Description

Member of EffectContour

The **Steps** property returns or specifies the number of steps in a contour effect.

VBA example

The following VBA example checks all contours on the current page and changes them as follows: all outside contours are to have twice as many steps, and all inside contours are to have a step distance of half of the previous size. The contours to the center of the shape are left unchanged.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrContour Then
    Select Case eff.Contour.Direction
     Case cdrContourOutside
      eff.Contour.Steps = eff.Contour.Steps * 2
     Case cdrContourInside
      eff.Contour.Offset = eff.Contour.Offset / 2
     Case cdrContourToCenter
      ' Do nothing
    End Select
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectControlPath

Properties

Description

The **EffectControlPath** class provides access to all effects that are attached to a path.

A control path is a curve that determines the shape of an Artistic Media stroke. When you edit an Artistic Media stroke, you edit the control path of the stroke. The stroke itself is a closed path following the control path. When you shape the control path, the stroke shifts according to how you edit the control path. If you want to edit the closed path directly, you must first separate it from the control path.

Copyright 2014 Corel Corporation. All rights reserved.

EffectControlPath.Application

Property **Application** As Application

Description

Member of EffectControlPath

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

EffectControlPath.Effects

Property **Effects** As Effects

Description

Member of EffectControlPath

The **Effects** property returns a collection of effects that are attached to a path.

The **Effects** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

EffectControlPath.Parent

Property **Parent** As Effect

Description

Member of EffectControlPath

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

EffectCustomDistortion

Properties

Description

Copyright 2014 Corel Corporation. All rights reserved.

EffectCustomDistortion.DistortionID

Property **DistortionID** As String

Description

Member of EffectCustomDistortion

The **DistortionID** property returns the ID of a customized distortion effect.

The **DistortionID** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

EffectDistortion

Properties Methods

Description

The **EffectDistortion** class represents the settings for a distortion effect.

Copyright 2014 Corel Corporation. All rights reserved.

EffectDistortion.Application

Property **Application** As Application

Description

Member of EffectDistortion

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

EffectDistortion.CenterDistortion

Sub **CenterDistortion()**

Description

Member of EffectDistortion

The **CenterDistortion** method centers a distortion effect in its shape.

VBA example

The following VBA example centers all distortion effects on the page.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrDistortion Then
    eff.Distortion.CenterDistortion
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDistortion.Custom

Property **Custom** As EffectCustomDistortion

Description

Member of EffectDistortion

The **Custom** property returns properties of a custom distortion effect.

The **Custom** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

EffectDistortion.OriginX

Property **OriginX** As Double

Description

Member of EffectDistortion

The **OriginX** property returns or specifies the x-coordinate of the point of origin of a distortion effect. The coordinate is relative to the center of the shape. This property is measured in document units.

VBA example

The following VBA example applies a Zipper distortion to an ellipse and then moves the shape's center by 1" to the right.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(1, 1, 1)
 With s.CreateZipperDistortion(0, 0, 10, 6).Distortion
  .OriginX = 1
  .OriginY = 0
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDistortion.OriginY

Property **OriginY** As Double

Description

Member of EffectDistortion

The **OriginY** property returns or specifies the y-coordinate of the point of origin of a distortion effect. The coordinate is relative to the center of the shape.

This property is measured in document units

VBA example

The following VBA example applies a Zipper distortion to an ellipse and then moves the shape's center by 1" to the right.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(1, 1, 1)
 With s.CreateZipperDistortion(0, 0, 10, 6).Distortion
  .OriginX = 1
  .OriginY = 0
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDistortion.Parent

Property **Parent** As Effect

Description

Member of EffectDistortion

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

EffectDistortion.PushPull

Property **PushPull** As EffectPushPullDistortion

Description

Member of EffectDistortion

The **PushPull** property represents the settings for a Push-and-pull distortion object.

VBA example

The following VBA example looks through all shapes and distortion effects. Depending on the type of distortion effect, corresponding effect parameters are altered.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrDistortion Then
    Select Case eff.Distortion.Type
     Case cdrDistortionPushPull
      eff.Distortion.PushPull.Amplitude = 50
     Case cdrDistortionTwister
      eff.Distortion.Twister.Angle = 400
     Case cdrDistortionZipper
      eff.Distortion.Zipper.Smooth = True
    End Select
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDistortion.Twister

Property **Twister** As EffectTwisterDistortion

Description

Member of EffectDistortion

The **Twister** property represents the settings for a Twister distortion object.

VBA example

The following VBA example looks through all shapes and distortion effects. Depending on the type of distortion effect, corresponding effect parameters are altered.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrDistortion Then
    Select Case eff.Distortion.Type
     Case cdrDistortionPushPull
      eff.Distortion.PushPull.Amplitude = 50
     Case cdrDistortionTwister
      eff.Distortion.Twister.Angle = 400
     Case cdrDistortionZipper
      eff.Distortion.Zipper.Smooth = True
    End Select
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDistortion.Type

Property **Type** As cdrDistortionType

Description

Member of EffectDistortion

The **Type** property returns or specifies the type of distortion. Depending on the value of **Type** property, one of the effect objects (PushPull, Twister, or Zipper) is accessible.

The **Type** property returns a value of cdrDistortionType.

VBA example

The following VBA example looks through all shapes and distortion effects. Depending on the type of distortion effect, corresponding effect parameters are altered.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrDistortion Then
    Select Case eff.Distortion.Type
     Case cdrDistortionPushPull
      eff.Distortion.PushPull.Amplitude = 50
     Case cdrDistortionTwister
      eff.Distortion.Twister.Angle = 400
     Case cdrDistortionZipper
      eff.Distortion.Zipper.Smooth = True
    End Select
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDistortion.Zipper

Property **Zipper** As EffectZipperDistortion

Description

Member of EffectDistortion

The **Zipper** property represents the settings for a Zipper distortion object.

VBA example

The following VBA example looks through all shapes and distortion effects. Depending on the type of distortion effect, corresponding effect parameters are altered.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrDistortion Then
    Select Case eff.Distortion.Type
     Case cdrDistortionPushPull
      eff.Distortion.PushPull.Amplitude = 50
     Case cdrDistortionTwister
      eff.Distortion.Twister.Angle = 400
     Case cdrDistortionZipper
      eff.Distortion.Zipper.Smooth = True
    End Select
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDropShadow

Properties Methods

Description

The **EffectDropShadow** class represents the settings for a drop-shadow effect.

Copyright 2014 Corel Corporation. All rights reserved.

EffectDropShadow.Application

Property **Application** As Application

Description

Member of EffectDropShadow

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

EffectDropShadow.Color

Property **Color** As Color

Description

Member of EffectDropShadow

The **Color** property returns or specifies the Color object that represents the color of the drop shadow.

VBA example

The following VBA example changes the color of all drop shadows to red.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrDropShadow Then
    eff.DropShadow.Color.RGBAssign 255, 0, 0
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDropShadow.Fade

Property **Fade** As Long

Description

Member of EffectDropShadow

The **Fade** property returns or specifies the fading of a perspective drop shadow. Values range from **0**% to **100**%.

VBA example

The following VBA example sets the fading of every perspective shadow to **80**%.

```
Sub Test()
 Dim s As Shape, ds As EffectDropShadow
 For Each s In ActivePage.Shapes
  If s.Type = cdrDropShadowGroupShape Then
   Set ds = s.Effect.DropShadow
   If ds.Type <> cdrDropShadowFlat Then
    ds.Opacity = 100
    ds.Fade = 80
   End If
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDropShadow.Feather

Property **Feather** As Long

Description

Member of EffectDropShadow

The **Feather** property returns or specifies the feathering length of a drop shadow. Values range from **0**% to **100**%. Low values create a more subtle feathering effect, while high values create a more pronounced effect.

VBA example

The following VBA example applies **50**% outside feathering with inverse squared edges to all drop shadows on the active page.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Type = cdrDropShadowGroupShape Then
   With s.Effect.DropShadow
    .FeatherType = cdrFeatherOutside
    .FeatherEdge = cdrEdgeInverseSquared
    .Feather = 50
   End With
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDropShadow.FeatherEdge

Property **FeatherEdge** As cdrEdgeType

Description

Member of EffectDropShadow

The **FeatherEdge** property returns or specifies the type of feathering edge for a drop shadow. Values range from **0**% to **100**%.

This property returns cdrEdgeType.

VBA example

The following VBA example applies **50**% outside feathering with inverse squared edges to all drop shadows on the active page.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Type = cdrDropShadowGroupShape Then
   With s.Effect.DropShadow
    .FeatherType = cdrFeatherOutside
    .FeatherEdge = cdrEdgeInverseSquared
    .Feather = 50
   End With
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDropShadow.FeatherType

Property **FeatherType** As cdrFeatherType

Description

Member of EffectDropShadow

The **FeatherType** property returns or specifies the type of feather for a drop shadow.

This property returns cdrFeatherType.

VBA example

The following VBA example applies **50**% outside feathering with inverse squared edges to all drop shadows on the active page.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Type = cdrDropShadowGroupShape Then
   With s.Effect.DropShadow
    .FeatherType = cdrFeatherOutside
    .FeatherEdge = cdrEdgeInverseSquared
    .Feather = 50
   End With
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDropShadow.MergeMode

Property **MergeMode** As cdrMergeMode

Description

Member of EffectDropShadow

The **MergeMode** property returns or specifies the **MergeMode** property for the drop shadow.

Copyright 2014 Corel Corporation. All rights reserved.

EffectDropShadow.OffsetX

Property **OffsetX** As Double

Description

Member of EffectDropShadow

The **OffsetX** property returns or specifies the horizontal offset of a flat drop shadow.

- See also the EffectDropShadow.SetOffset method.

VBA example

The following VBA example moves all flat drop shadows — so that the offset distance is **0.5**" — while preserving the original offset angle.

```
Sub Test()
 Const Radius As Double = 0.5
 Dim s As Shape, ds As EffectDropShadow
 Dim dx As Double, dy As Double, r As Double
 For Each s In ActivePage.Shapes
  If s.Type = cdrDropShadowGroupShape Then
   Set ds = s.Effect.DropShadow
   If ds.Type = cdrDropShadowFlat Then
    dx = ds.OffsetX
    dy = ds.OffsetY
    r = Sqr(dx * dx + dy * dy)
    If r = 0 Then
     dx = 1
     r = 1
    End If
    ds.OffsetX = dx * Radius / r
    ds.OffsetY = dy * Radius / r
   End If
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDropShadow.OffsetY

Property **OffsetY** As Double

Description

Member of EffectDropShadow

The **OffsetY** property returns or specifies the vertical offset of a flat drop shadow.

- See also the EffectDropShadow.SetOffset method.

VBA example

The following VBA example moves all flat drop shadows — so that the offset distance is **0.5**" — while preserving the original offset angle.

```
Sub Test()
 Const Radius As Double = 0.5
 Dim s As Shape, ds As EffectDropShadow
 Dim dx As Double, dy As Double, r As Double
 For Each s In ActivePage.Shapes
  If s.Type = cdrDropShadowGroupShape Then
   Set ds = s.Effect.DropShadow
   If ds.Type = cdrDropShadowFlat Then
    dx = ds.OffsetX
    dy = ds.OffsetY
    r = Sqr(dx * dx + dy * dy)
    If r = 0 Then
     dx = 1
     r = 1
    End If
    ds.OffsetX = dx * Radius / r
    ds.OffsetY = dy * Radius / r
   End If
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDropShadow.Opacity

Property **Opacity** As Long

Description

Member of EffectDropShadow

The **Opacity** property returns or specifies the opacity value of a drop shadow. Values range from **0**% to **100**%. Low values create a less opaque drop shadow, while high values create a more opaque drop shadow.

VBA example

The following VBA example sets the opacity of the selected drop shadow to **80**%.

```
Sub Test()
 Dim eff As Effect
 Dim bDone As Boolean
 If ActiveShape Is Nothing Then
  MsgBox "Nothing selected", vbCritical
  Exit Sub
 End If
 bDone = False
 If ActiveShape.Next.Type = cdrDropShadowGroupShape Then
  Set eff = ActiveShape.Next.Effect
  eff.DropShadow.Opacity = 80
  bDone = True
 End If
 If Not bDone Then
  MsgBox "The selected shape doesn't have a dropshadow", vbCritical
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDropShadow.Parent

Property **Parent** As Effect

Description

Member of EffectDropShadow

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

EffectDropShadow.PerspectiveAngle

Property **PerspectiveAngle** As Double

Description

Member of EffectDropShadow

The **PersectiveAngle** returns or specifies the angle of a perspective drop shadow.

VBA example

The following VBA example converts all flat drop shadows to perspective drop shadows.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Type = cdrDropShadowGroupShape Then
   With s.Effect.DropShadow
    If .Type = cdrDropShadowFlat Then
     .Type = cdrDropShadowBottom
     .PerspectiveAngle = 45
     .PerspectiveStretch = -0.5
    End If
   End With
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDropShadow.PerspectiveStretch

Property **PerspectiveStretch** As Double

Description

Member of EffectDropShadow

The **PerspectiveStretch** returns or specifies the stretch parameters of a perspective drop shadow.

VBA example

The following VBA example converts all flat drop shadows to perspective drop shadows.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Type = cdrDropShadowGroupShape Then
   With s.Effect.DropShadow
    If .Type = cdrDropShadowFlat Then
     .Type = cdrDropShadowBottom
     .PerspectiveAngle = 45
     .PerspectiveStretch = -0.5
    End If
   End With
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDropShadow.SetOffset

Sub **SetOffset(***OffsetX As Double*, *OffsetY As Double***)**

Description

Member of EffectDropShadow

The **Offset** property specifies the horizontal and vertical offset of a flat drop shadow from its control object.

- See also the EffectDropShadow.OffsetX and EffectDropShadow.OffsetY properties.

Parameter	Description
OffsetX	Specifies the horizontal offset
OffsetY	Specifies the vertical offset

VBA example

The following VBA example moves all drop shadows by **2** document units to the right (along the x-axis) and **1** document unit down (along the y-axis).

```
Sub Test()
 Dim s As Shape, ds As EffectDropShadow
 For Each s In ActivePage.Shapes
  If s.Type = cdrDropShadowGroupShape Then
   Set ds = s.Effect.DropShadow
    ds.SetOffset 2,-1
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectDropShadow.ShadowGroup

Property **ShadowGroup** As Shape

Description

Member of EffectDropShadow

The **ShadowGroup** property returns the bitmap shape of a drop shadow.

The **ShadowGroup** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

EffectDropShadow.Type

Property **Type** As cdrDropShadowType

Description

Member of EffectDropShadow

The **Type** property returns or specifies the type of the drop shadow.

This property returns cdrDropShadowType.

VBA example

The following VBA example selects all shapes with flat drop shadows on the page.

```
Sub Test()
 Dim s As Shape
 Dim sr As New ShapeRange
 For Each s In ActivePage.Shapes
  If s.Type = cdrDropShadowGroupShape Then
   If s.Effect.DropShadow.Type = cdrDropShadowFlat Then
    sr.Add s.Previous ' To select the control shape
    sr.Add s ' To select the shadow bitmap itself
   End If
  End If
 Next s
 sr.CreateSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectEnvelope

Properties Methods

Description

The **EffectEnvelope** class represents the settings for an envelope effect, which lets you distort the shape of an object by changing the shape of an imaginary box (or “envelope”) around that object.

Copyright 2014 Corel Corporation. All rights reserved.

EffectEnvelope.Application

Property **Application** As Application

Description

Member of EffectEnvelope

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

EffectEnvelope.Container

Property **Container** As Curve

Description

Member of EffectEnvelope

The **Container** property returns or specifies a curve that defines the envelope's borders.

Copyright 2014 Corel Corporation. All rights reserved.

EffectEnvelope.CopyFrom

Sub **CopyFrom(**Source As EffectEnvelope**)**

Description

Member of EffectEnvelope

The **CopyFrom** method copies the properties from one envelope effect to another.

If you've applied an effect to the object since you applied the envelope, you won't be able to copy the envelope.

Parameter	Description
Source	Specifies the envelope effect from which to copy properties

VBA example

The following VBA example creates a text object and applies an envelope effect to it. It then creates a group of rectangles and applies an envelope to them, using the same parameters as the text's envelope.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape, eff As Effect
 Set s1 = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s1.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 Set eff = s1.CreateEnvelope(3, cdrEnvelopePutty, True)
 Set s2 = ActiveLayer.CreateGridBoxes(0, 0, 3, 3, 8, 8)
 s2.CreateEnvelope(1).Envelope.CopyFrom eff.Envelope
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectEnvelope.CopyFromCurve

Function **CopyFromCurve(**Source As Curve**, [**Mode As cdrEnvelopeMode = cdrEnvelopePutty**], [**KeepLines As Boolean = False**], [**CopyMode As cdrEnvelopeCopyMode = cdrEnvelopeCenter**], [***CornerIndices***])** As Boolean

Description

Member of EffectEnvelope

The **CopyFromCurve** method updates the envelope container from the specified curve.

Parameter	Description
Source	Specifies the envelope effect from which to copy properties
Mode	Specifies an envelope mode. This parameter is optional, and its default value is cdrEnvelopePutty.
KeepLines	Specifies whether to keep lines. This parameter is optional, and its default value is **False**.
CopyMode	Specifies a copy mode. This parameter is optional, and its default value is cdrEnvelopeCenter.
CornerIndices	Specifies corner indices. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

EffectEnvelope.CopyFromShape

Function **CopyFromShape(**Source As Shape**, [**Mode As cdrEnvelopeMode = cdrEnvelopePutty**], [**KeepLines As Boolean = False**], [**CopyMode As cdrEnvelopeCopyMode = cdrEnvelopeCenter**], [***CornerIndices***])** As Boolean

Description

Member of EffectEnvelope

The **CopyFromShape** method updates the envelope container from the specified shape.

Parameter	Description
Source	Specifies the envelope effect from which to copy properties
Mode	Specifies an envelope mode. This parameter is optional, and its default value is cdrEnvelopePutty.
KeepLines	Specifies whether to keep lines. This parameter is optional, and its default value is **False**.
CopyMode	Specifies a copy mode. This parameter is optional, and its default value is cdrEnvelopeCenter.
CornerIndices	Specifies corner indices. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

EffectEnvelope.CornerIndices

Property **CornerIndices** As Variant

Description

Member of EffectEnvelope

The **CornerIndices** property returns or specifies an array of four integers that specifies the node indices in an envelope container curve and that identify the four corners of the deformed envelope rectangle.

Copyright 2014 Corel Corporation. All rights reserved.

EffectEnvelope.KeepLines

Property **KeepLines** As Boolean

Description

Member of EffectEnvelope

The **KeepLines** property returns or specifies whether straight line segments are warped in the envelope. If the **KeepLines** property is **True**, the envelope effect keeps its lines straight.

VBA example

The following VBA example creates a text object, applies an envelope effect to it, and then specifies that straight lines are to be preserved in the distorted text object.

```
Sub Test()
 Dim s As Shape, eff As Effect
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 Set eff = s.CreateEnvelope(3)
 eff.Envelope.KeepLines = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectEnvelope.Mode

Property **Mode** As cdrEnvelopeMode

Description

Member of EffectEnvelope

The **Mode** property returns or specifies the mapping mode by which an object is fitted to an envelope.

The **Mode** property returns a value of cdrEnvelopeMode. There are four mapping modes: **Horizontal**, **Original**, **Putty**, and **Vertical**.

VBA example

The following VBA example selects all shapes to which envelopes with the **Original** mode have been applied.

```
Sub Test()
 Dim s As Shape, eff As Effect
 Dim sr As New ShapeRange
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrEnvelope Then
    If eff.Envelope.Mode = cdrEnvelopeOriginal Then sr.Add s
    Exit For
   End If
 Next eff
 Next s
 sr.CreateSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectEnvelope.Parent

Property **Parent** As Effect

Description

Member of EffectEnvelope

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

EffectEnvelope.Select

Sub **Select(***PresetIndex As Long***)**

Description

Member of EffectEnvelope

The **Select** method chooses a given envelope preset.

Parameter	Description
PresetIndex	Specifies an index number that uniquely identifies a preset envelope effect

VBA example

The following VBA example places a text object in a heart-shaped envelope.

```
Sub Test()
 Dim s As Shape, eff As Effect
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 Set eff = s.CreateEnvelope(1)
 eff.Envelope.Select 12
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude

Properties Methods

Description

The **EffectExtrude** class represents the settings for an extrusion effect.

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.AngleX

Property **AngleX** As Double

Description

Member of EffectExtrude

The **AngleX** property returns or specifies the x-axis extrusion angle for an extruded object.

This property is a percentage that rotates the extrusion along the x-axis.

VBA example

The following VBA example selects all objects with extrusions that were rotated in three-dimensional space.

```
Sub Test()
 Dim s As Shape, eff As Effect
 Dim sr As New ShapeRange
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrExtrude Then
    With eff.Extrude
     If .AngleX <> 0 Or .AngleY <> 0 Or .AngleZ <> 0 Then sr.Add s
    End With
    Exit For
   End If
  Next eff
 Next s
 sr.CreateSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.AngleY

Property **AngleY** As Double

Description

Member of EffectExtrude

The **AngleY** property returns or specifies the y-axis extrusion angle for an extruded object.

This property is a percentage that rotates the extrusion along the y-axis.

VBA example

The following VBA example selects all objects with extrusions that were rotated in three-dimensional space.

```
Sub Test()
 Dim s As Shape, eff As Effect
 Dim sr As New ShapeRange
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrExtrude Then
    With eff.Extrude
     If .AngleX <> 0 Or .AngleY <> 0 Or .AngleZ <> 0 Then sr.Add s
    End With
    Exit For
   End If
  Next eff
 Next s
 sr.CreateSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.AngleZ

Property **AngleZ** As Double

Description

Member of EffectExtrude

The **AngleZ** property returns or specifies the z-axis extrusion angle for an extruded object.

This property is a percentage that rotates the extrusion along the z-axis.

VBA example

The following VBA example selects all objects with extrusions that were rotated in three-dimensional space.

```
Sub Test()
 Dim s As Shape, eff As Effect
 Dim sr As New ShapeRange
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrExtrude Then
    With eff.Extrude
     If .AngleX <> 0 Or .AngleY <> 0 Or .AngleZ <> 0 Then sr.Add s
    End With
    Exit For
   End If
  Next eff
 Next s
 sr.CreateSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.Application

Property **Application** As Application

Description

Member of EffectExtrude

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.BaseColor

Property **BaseColor** As Color

Description

Member of EffectExtrude

The **BaseColor** property returns or specifies the solid fill or starting shading color for an extrusion.

VBA example

The following VBA example creates an extruded text shape and shades the extrusion with a fountain color transition from red to yellow.

```
Sub Test()
 Dim s As Shape, eff As Effect
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 Set eff = s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4, 8)
 With eff.Extrude
  .Shading = cdrExtrudeColorShading
  .BaseColor.RGBAssign 255, 0, 0
  .ShadingColor.RGBAssign 255, 255, 0
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.BevelAngle

Property **BevelAngle** As Double

Description

Member of EffectExtrude

The **BevelAngle** returns or specifies the bevel angle for an extrusion.

- See also the EffectExtrude.SetBevel method.

VBA example

The following VBA example creates an extruded text shape. The extrusion is created with a yellow bevel that is 0.1" wide and has a 45° slope.

```
Sub Test()
 Dim s As Shape, eff As Effect
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 Set eff = s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4,
  8, , cdrExtrudeColorShading, CreateRGBColor(0, 0, 0), CreateRGBColor(255, 255, 255))
 With eff.Extrude
  .UseBevel = True
  .BevelAngle = 45
  .BevelDepth = 0.1
  .UseExtrudeColorForBevel = False
  .BevelColor.RGBAssign 255, 255, 0
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.BevelColor

Property **BevelColor** As Color

Description

Member of EffectExtrude

The **BevelColor** property returns or specifies the bevel color for an extrusion.

- See also the EffectExtrude.SetBevel method.

VBA example

The following VBA example creates an extruded text shape. The extrusion is created with a yellow bevel that is 0.1" wide and has a 45° slope.

```
Sub Test()
 Dim s As Shape, eff As Effect
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 Set eff = s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4,
  8, , cdrExtrudeColorShading, CreateRGBColor(0, 0, 0), CreateRGBColor(255, 255, 255))
 With eff.Extrude
  .UseBevel = True
  .BevelAngle = 45
  .BevelDepth = 0.1
  .UseExtrudeColorForBevel = False
  .BevelColor.RGBAssign 255, 255, 0
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.BevelDepth

Property **BevelDepth** As Double

Description

Member of EffectExtrude

The **BevelDepth** property returns or specifies the bevel depth for an extrusion.

- See also the EffectExtrude.SetBevel method.

VBA example

The following VBA example creates an extruded text shape. The extrusion is created with a yellow bevel that is 0.1" wide and has a 45° slope.

```
Sub Test()
 Dim s As Shape, eff As Effect
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 Set eff = s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4,
  8, , cdrExtrudeColorShading, CreateRGBColor(0, 0, 0), CreateRGBColor(255, 255, 255))
 With eff.Extrude
  .UseBevel = True
  .BevelAngle = 45
  .BevelDepth = 0.1
  .UseExtrudeColorForBevel = False
  .BevelColor.RGBAssign 255, 255, 0
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.BevelGroup

Property **BevelGroup** As Shape

Description

Member of EffectExtrude

The **BevelGroup** property returns a Shape object representing a bevel group.

- You must separate the extrusion from its control shape before using the returned shape.

The **BevelGroup** property returns a read-only value.

VBA example

The following VBA example creates an extruded text shape with a bevel, separates the extrusion, and moves the bevel group up by 3".

```
Sub Test()
 Dim s As Shape, eff As Effect, sBevel As Shape
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 Set eff = s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4,
  8, , cdrExtrudeColorShading, CreateRGBColor(0, 0, 0), CreateRGBColor(255, 255, 255), _
  0.1, 45, CreateRGBColor(255, 0, 0))
 Set sBevel = eff.Extrude.BevelGroup
 ' Effect.Separate doesn't work well on beveled extrudes
 ' So, let's use ActiveSelection.Separate instead
 s.CreateSelection ' Select the control text object
 eff.Extrude.ExtrudeGroup.Selected = True ' Add the extrusion to the selection
 sBevel.Selected = True ' Add the bevel group to the selection
 ActiveSelection.Separate ' Separate the selection
 sBevel.Move 0, 3
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.CopyFrom

Sub **CopyFrom(**Source As EffectExtrude**)**

Description

Member of EffectExtrude

The **CopyFrom** method copies the extrusion properties from one extrusion to another.

Parameter	Description
Source	Specifies the extrusion from which to copy properties

VBA example

The following VBA example creates an extruded text shape and copies extrusion properties from the selected extruded shape.

```
Sub Test()
 Dim s As Shape, ext As EffectExtrude
 If ActiveShape Is Nothing Then
  MsgBox "Nothing selected", vbCritical
  Exit Sub
 End If
 Select Case ActiveShape.Type
  Case cdrExtrudeGroupShape
   Set s = ActiveShape
  Case cdrBevelGroupShape
   Set s = ActiveShape.Next.Next
  Case Else
   If ActiveShape.Next.Type = cdrExtrudeGroupShape Then
    Set s = ActiveShape.Next
   Else
    MsgBox "An extruded shape must be selected"
    Exit Sub
   End If
 End Select
 Set ext = s.Effect.Extrude
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 s.Fill.UniformColor.RGBAssign 0, 0, 255
 With s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4, 8).Extrude
  .CopyFrom ext
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.Depth

Property **Depth** As Long

Description

Member of EffectExtrude

The **Depth** property returns or specifies the depth of the extrusion. This parameter cannot be used with a parallel extrusion.

VBA example

The following VBA example selects all extruded shapes whose extrusion depth is more than 20 units.

```
Sub Test()
 Dim s As Shape, eff As Effect
 Dim sr As New ShapeRange
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrExtrude Then
    With eff.Extrude
     If .Type <> cdrExtrudeFrontParallel And .Type <> cdrExtrudeFrontParallel Then
      If .Depth > 20 Then
       sr.Add s
       If Not .ShowBevelOnly Then sr.Add .ExtrudeGroup
       If .UseBevel Then sr.Add .BevelGroup
      End If
     End If
    End With
    Exit For
   End If
  Next eff
 Next s
 sr.CreateSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.ExtrudeGroup

Property **ExtrudeGroup** As Shape

Description

Member of EffectExtrude

The **ExtrudeGroup** property returns a Shape object that represents the extrusion group.

- You must separate the extrusion from its control shape before using the returned shape.

The **ExtrudeGroup** property returns a read-only value.

VBA example

The following VBA example creates an extruded text shape with a bevel, separates the extrusion, and moves the bevel group up by 3".

```
Sub Test()
 Dim s As Shape, eff As Effect, sBevel As Shape
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 Set eff = s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4,
  8, , cdrExtrudeColorShading, CreateRGBColor(0, 0, 0), CreateRGBColor(255, 255, 255), _
  0.1, 45, CreateRGBColor(255, 0, 0))
 Set sBevel = eff.Extrude.BevelGroup
 ' Effect.Separate doesn't work well on beveled extrudes
 ' So, let's use ActiveSelection.Separate instead
 s.CreateSelection ' Select the control text object
 eff.Extrude.ExtrudeGroup.Selected = True ' Add the extrusion to the selection
 sBevel.Selected = True ' Add the bevel group to the selection
 ActiveSelection.Separate ' Separate the selection
 sBevel.Move 0, 3
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.FaceShape

Property **FaceShape** As Shape

Description

Member of EffectExtrude

The **FaceShape** property returns a Shape object representing the control shape of the extrusion.

The **FaceShape** property returns a read-only value.

VBA example

The following VBA example finds all extruded shapes on a page, fills the control shapes with yellow, and changes the extrusion color to a two-color fountain fill that progresses from red to white.

```
Sub Test()
 Dim s As Shape, ext As EffectExtrude
 For Each s In ActivePage.Shapes
  If s.Type = cdrExtrudeGroupShape Then
   Set ext = s.Effect.Extrude
   ext.FaceShape.Fill.UniformColor.RGBAssign 255, 255, 0
   ext.Shading = cdrExtrudeColorShading
   ext.BaseColor.RGBAssign 255, 0, 0
   ext.ShadingColor.RGBAssign 255, 255, 255
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.FaceVisible

Property **FaceVisible** As Boolean

Description

Member of EffectExtrude

The **FaceVisible** property returns whether the control face is visible for an extrusion. It returns **True** if the extrusion's control shape is visible.

The face may not be visible if the extrusion was rotated in three-dimensional space or if one of the following extrusion type was used: **Front Parallel**, **Small Front**, or **Big Front**.

The **FaceVisible** property returns a read-only value.

VBA example

The following VBA example selects all extruded shapes for which the faces are not visible.

```
Sub Test()
 Dim s As Shape, ext As EffectExtrude
 Dim sr As New ShapeRange
 For Each s In ActivePage.Shapes
  If s.Type = cdrExtrudeGroupShape Then
   Set ext = s.Effect.Extrude
   If ext.FaceVisible = False Then
    sr.Add ext.FaceShape
    If Not ext.ShowBevelOnly Then sr.Add s
    If ext.UseBevel Then sr.Add ext.BevelGroup
   End If
  End If
 Next s
 sr.CreateSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.LightIntensity

Property **LightIntensity(***Index As Long***)** As Long

Description

Member of EffectExtrude

The **LightIntensity** property returns or specifies the light intensity at a given index for an extrusion.

- See also the EffectExtrude.SetLight method.

Parameter	Description
Index	Specifies the light source used for an extrusion.You can apply as many as three light sources. You can also remove applied light sources.

VBA example

The following VBA example creates an extrusion and adds two light sources to it.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 s.Fill.UniformColor.RGBAssign 0, 0, 255
 With s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4, _
   8, , cdrExtrudeSolidFill, CreateRGBColor(255, 0, 0)).Extrude
  .LightPresent(1) = True
  .LightPosition(1) = cdrLightBackTopRight
  .LightIntensity(1) = 100
  .LightPresent(2) = True
  .LightPosition(2) = cdrLightFrontCenter
  .LightIntensity(2) = 50
  .LightPresent(3) = False
  .UseFullColorRange = True
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.LightPosition

Property **LightPosition(***Index As Long***)** As cdrExtrudeLightPosition

Description

Member of EffectExtrude

The **LightPosition** property returns or specifies the light position at a given index for an extrusion.

The **LightPosition** property returns cdrExtrudeLightPosition.

- See also the EffectExtrude.SetLight method.

Parameter	Description
Index	Specifies the light source used for an extrusion.You can apply as many as three light sources. You can also remove applied light sources.

VBA example

The following VBA example creates an extrusion and adds two light sources to it.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 s.Fill.UniformColor.RGBAssign 0, 0, 255
 With s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4, _
   8, , cdrExtrudeSolidFill, CreateRGBColor(255, 0, 0)).Extrude
  .LightPresent(1) = True
  .LightPosition(1) = cdrLightBackTopRight
  .LightIntensity(1) = 100
  .LightPresent(2) = True
  .LightPosition(2) = cdrLightFrontCenter
  .LightIntensity(2) = 50
  .LightPresent(3) = False
  .UseFullColorRange = True
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.LightPresent

Property **LightPresent(***Index As Long***)** As Boolean

Description

Member of EffectExtrude

The **LightPresent** property returns or specifies whether light is present at a given index for an extrusion. You can specify up to three light sources.

- See also the EffectExtrude.SetLight method.

Parameter	Description
Index	Specifies the light source used. You can apply as many as three light sources. You can also remove applied light sources.

VBA example

The following VBA example creates an extrusion and adds two light sources to it.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 s.Fill.UniformColor.RGBAssign 0, 0, 255
 With s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4, _
   8, , cdrExtrudeSolidFill, CreateRGBColor(255, 0, 0)).Extrude
  .LightPresent(1) = True
  .LightPosition(1) = cdrLightBackTopRight
  .LightIntensity(1) = 100
  .LightPresent(2) = True
  .LightPosition(2) = cdrLightFrontCenter
  .LightIntensity(2) = 50
  .LightPresent(3) = False
  .UseFullColorRange = True
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.Parent

Property **Parent** As Effect

Description

Member of EffectExtrude

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.Rotate

Sub **Rotate(***AngleX As Double***,** *AngleY As Double***,** *AngleZ As Double***)**

Description

Member of EffectExtrude

The **Rotate** method rotates an extrusion in three-dimensional space.

- See also the EffectExtrude.AngleX, EffectExtrude.AngleY, and EffectExtrude.AngleZ properties.

Parameter	Description
AngleX	Specifies the degree of the rotation along the x-axis
AngleY	Specifies the degree of the rotation along the y-axis
AngleZ	Specifies the degree of the rotation along the z-axis

VBA example

The following VBA example creates a rotated and extruded text shape.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 s.Fill.UniformColor.RGBAssign 0, 0, 255
 s.Outline.SetProperties 0.01, , CreateRGBColor(0, 0, 0)
 With s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4, 8, , cdrExtrudeSolidFill, CreateRGBColor(0,
128, 0)).Extrude
  .Rotate 10, 20, 30
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.SetBevel

Sub **SetBevel(***Depth As Double*, *Angle As Double*, *ShowBevelOnly As Boolean***)**

Description

Member of EffectExtrude

The **SetBevel** method specifies all properties for the bevel in an extrusion.

Parameter	Description
Depth	Specifies the depth percentage of the bevel
Angle	Specifies the degree of the bevel
ShowBevelOnly	Specifies whether to show only the bevel in the extrusion effect

VBA example

The following VBA example creates an extruded text shape with a bevel.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 s.Fill.UniformColor.RGBAssign 0, 0, 255
 s.Outline.SetProperties 0.01, , CreateRGBColor(0, 0, 0)
 With s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4, 8, , cdrExtrudeSolidFill, CreateRGBColor(0,
128, 0)).Extrude
  .SetBevel 0.05, 45, False
  .UseExtrudeColorForBevel = False
  .BevelColor.RGBAssign 255, 255, 0
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.SetLight

Sub **SetLight(***Index As Long***,** Position As cdrExtrudeLightPosition**,** *LightIntensity As Long***)**

Description

Member of EffectExtrude

The **SetLight** method enables the given light source and specifies its properties for an extrusion.

- See also EffectExtrude.LightPresent, EffectExtrude.LightPosition, and EffectExtrude.LightIntensity properties.

Parameter	Description
Index	Specifies the index where the light property is set
Position	Specifies the position of the light property in the extrusion effect. This value returns cdrExtrudeLightPosition
LightIntensity	Specifies the light intensity

VBA example

The following VBA example creates an extrusion with two light sources.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 s.Fill.UniformColor.RGBAssign 0, 0, 255
 With s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4, _
   8, , cdrExtrudeSolidFill, CreateRGBColor(255, 0, 0)).Extrude
  .SetLight 1, cdrLightBackTopRight, 100
  .SetLight 2, cdrLightFrontCenter, 50
  .LightPresent(3) = False
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.Shading

Property **Shading** As cdrExtrudeShading

Description

Member of EffectExtrude

The **Shading** property returns or specifies the shading type for an extrusion.

This property returns cdrExtrudeShading.

VBA example

The following VBA example creates an extruded text shape and shades the extrusion with a fountain color transition from red to yellow.

```
Sub Test()
 Dim s As Shape, eff As Effect
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 Set eff = s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4, 8)
 With eff.Extrude
  .Shading = cdrExtrudeColorShading
  .BaseColor.RGBAssign 255, 0, 0
  .ShadingColor.RGBAssign 255, 255, 0
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.ShadingColor

Property **ShadingColor** As Color

Description

Member of EffectExtrude

The **ShadingColor** property returns or specifies the ending shading color for an extrusion.

VBA example

The following VBA example creates an extruded text shape and shades the extrusion with a fountain color transition from red to yellow.

```
Sub Test()
 Dim s As Shape, eff As Effect
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 Set eff = s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4, 8)
 With eff.Extrude
  .Shading = cdrExtrudeColorShading
  .BaseColor.RGBAssign 255, 0, 0
  .ShadingColor.RGBAssign 255, 255, 0
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.ShowBevelOnly

Property **ShowBevelOnly** As Boolean

Description

Member of EffectExtrude

The **ShowBevelOnly** property returns or specifies whether to show only the bevel of an extrusion. When set to **True**, only the bevel is visible.

VBA example

The following VBA example finds extruded text shapes. It adds a bevel to extrusions and makes only the bevel visible.

```
Sub Test()
 Dim s As Shape, ext As EffectExtrude
 For Each s In ActivePage.Shapes
  If s.Type = cdrExtrudeGroupShape Then
   Set ext = s.Effect.Extrude
   If ext.FaceShape.Type = cdrTextShape And Not ext.UseBevel Then
    ext.UseBevel = True
    ext.BevelAngle = 45
    ext.BevelDepth = 0.1
    ext.UseExtrudeColorForBevel = True
    ext.ShowBevelOnly = True
   End If
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.Type

Property **Type** As cdrExtrudeType

Description

Member of EffectExtrude

The **Type** property returns or specifies the extrusion type.

This property returns cdrExtrudeType.

VBA example

The following VBA example changes the type of all extrusions from **Back Parallel** to **Small Back**.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Type = cdrExtrudeGroupShape Then
   If s.Effect.Extrude.Type = cdrExtrudeBackParallel Then
   s.Effect.Extrude.Type = cdrExtrudeSmallBack
   End If
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.UseBevel

Property **UseBevel** As Boolean

Description

Member of EffectExtrude

The **UseBevel** property returns or specifies whether to use a bevel for an extrusion. It also allows you to set options for a bevel.

- See also the EffectExtrude.SetBevel method.

VBA example

The following VBA example creates an extruded text shape. The extrusion is created with a yellow bevel that is 0.1" wide and has a 45° slope.

```
Sub Test()
 Dim s As Shape, eff As Effect
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 Set eff = s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4,
  8, , cdrExtrudeColorShading, CreateRGBColor(0, 0, 0), CreateRGBColor(255, 255, 255))
 With eff.Extrude
  .UseBevel = True
  .BevelAngle = 45
  .BevelDepth = 0.1
  .UseExtrudeColorForBevel = False
  .BevelColor.RGBAssign 255, 255, 0
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.UseExtrudeColorForBevel

Property **UseExtrudeColorForBevel** As Boolean

Description

Member of EffectExtrude

The **UseExtrudeColorForBevel** property returns or specifies whether to use the same color for the bevel and the rest of the extrusion.

- See also the EffectExtrude.SetBevel method.

VBA example

The following VBA example creates an extruded text shape. The extrusion is created with a yellow bevel that is 0.1" wide and has a 45° slope.

```
Sub Test()
 Dim s As Shape, eff As Effect
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 Set eff = s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4,
  8, , cdrExtrudeColorShading, CreateRGBColor(0, 0, 0), CreateRGBColor(255, 255, 255))
 With eff.Extrude
  .UseBevel = True
  .BevelAngle = 45
  .BevelDepth = 0.1
  .UseExtrudeColorForBevel = False
  .BevelColor.RGBAssign 255, 255, 0
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.UseFullColorRange

Property **UseFullColorRange** As Boolean

Description

Member of EffectExtrude

The **UseFullColorRange** property returns or specifies whether to combine light and dark shades (brightness and saturation) of a light source precisely for an extrusion.

- See also the EffectExtrude.SetLight method.

VBA example

The following VBA example creates an extrusion and adds two light sources to it.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateArtisticText(2.75, 5, "Text")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 s.Fill.UniformColor.RGBAssign 0, 0, 255
 With s.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4, _
   8, , cdrExtrudeSolidFill, CreateRGBColor(255, 0, 0)).Extrude
  .LightPresent(1) = True
  .LightPosition(1) = cdrLightBackTopRight
  .LightIntensity(1) = 100
  .LightPresent(2) = True
  .LightPosition(2) = cdrLightFrontCenter
  .LightIntensity(2) = 50
  .LightPresent(3) = False
  .UseFullColorRange = True
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectExtrude.VanishingPoint

Property **VanishingPoint** As ExtrudeVanishingPoint

Description

Member of EffectExtrude

The **VanishingPoint** property returns or specifies an ExtrudeVanishingPoint object, which lets you change the coordinates of an extrusion's vanishing point.

VBA example

The following VBA example sets the vanishing point to the center of the control shape.

```
Sub Test()
 Dim s As Shape, ext As EffectExtrude
 ActiveDocument.ReferencePoint = cdrCenter
 For Each s In ActivePage.Shapes
  If s.Type = cdrExtrudeGroupShape Then
   Set ext = s.Effect.Extrude
   With ext.VanishingPoint
    .Type = cdrVPLockedToShape
    .PositionX = 0
    .PositionY = 0
   End With
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens

Properties Methods

Description

The **EffectLens** class represents the settings for a lens effect.

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.Application

Property **Application** As Application

Description

Member of EffectLens

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.Color

Property **Color** As Color

Description

Member of EffectLens

The **Color** property returns or specifies the color of a lens.

This property is available for the following types of lenses: **Color add**, **Color limit**, **Tinted grayscale**, and **Transparency**.

The following lens types do not accept color parameters: **Brighten**, **Fish eye**, **Heat map**, **Invert**, and **Magnify**.

VBA example

The following VBA example changes the color of all lenses on the page to red. For the **Custom Color Map** and **Wireframe** lenses, yellow is also used.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrLens Then
    Select Case eff.Lens.Type
     Case cdrLensColorAdd, cdrLensColorLimit, _
      cdrLensTintedGrayscale, cdrLensTransparency
     eff.Lens.Color.RGBAssign 255, 0, 0
     Case cdrLensCustomColorMap
      eff.Lens.FromColor.RGBAssign 255, 0, 0
      eff.Lens.ToColor.RGBAssign 255, 255, 0
     Case cdrLensWireframe
      With eff.Lens
       .UseFillColor = True
       .UseOutlineColor = True
       .FillColor.RGBAssign 255, 0, 0
       .OutlineColor.RGBAssign 255, 255, 0
      End With
     End Select
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.ColorMapPalette

Property **ColorMapPalette** As cdrFountainFillBlendType

Description

Member of EffectLens

The **ColorMapPalette** property returns or specifies the color-blending mode to use for a **Custom Color Map** lens.

The **ColorMapPalette** property returns cdrFountainFillBlendType.

VBA example

The following VBA example creates a **Custom Color Map** lens with a **Forward rainbow color** blend.

```
Sub Test()
 Dim s As Shape, eff As Effect
 Set s = ActiveLayer.CreateRectangle(0, 0, 5, 5)
 s.Fill.ApplyFountainFill
 Set s = ActiveLayer.CreateEllipse(1, 1, 6, 6)
 Set eff = s.CreateLens(cdrLensCustomColorMap, , CreateRGBColor(255, 0, 0), CreateRGBColor(255, 255, 0))
 eff.Lens.ColorMapPalette = cdrRainbowCWFountainFillBlend
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.FillColor

Property **FillColor** As Color

Description

Member of EffectLens

The **FillColor** property returns or specifies the fill color for a **Wireframe** lens.

The following lens types do not accept color parameters: **Brighten**, **Fish eye**, **Heat map**, **Invert**, and **Magnify**.

VBA example

The following VBA example changes the color of all lenses on the page to red. For the **Custom Color Map** and **Wireframe** lenses, yellow is also used.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrLens Then
    Select Case eff.Lens.Type
     Case cdrLensColorAdd, cdrLensColorLimit, _
      cdrLensTintedGrayscale, cdrLensTransparency
     eff.Lens.Color.RGBAssign 255, 0, 0
     Case cdrLensCustomColorMap
      eff.Lens.FromColor.RGBAssign 255, 0, 0
      eff.Lens.ToColor.RGBAssign 255, 255, 0
     Case cdrLensWireframe
      With eff.Lens
       .UseFillColor = True
       .UseOutlineColor = True
       .FillColor.RGBAssign 255, 0, 0
       .OutlineColor.RGBAssign 255, 255, 0
      End With
     End Select
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.Freeze

Sub **Freeze()**

Description

Member of EffectLens

The **Freeze** method freezes a lens.

Frozen lenses redraw more quickly than non-frozen lenses. When a lens is frozen, the contents of the object no longer interact with other objects on the screen.

VBA example

The following VBA example creates a **Fish eye** lens, freezes it, and then ungroups and moves the resulting objects by **4**" to the right.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape, sr As ShapeRange
 Set s1 = ActiveLayer.CreateRectangle(0, 0, 5, 5)
 s1.Fill.ApplyFountainFill
 Set s2 = ActiveLayer.CreateEllipse(1, 1, 6, 6)
 With s2.CreateLens(cdrLensFishEye, 100).Lens
  .Freeze
  Set sr = .Ungroup
 End With
 sr.Move 4, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.FromColor

Property **FromColor** As Color

Description

Member of EffectLens

The **FromColor** property returns or specifies the starting color for the **Custom Color Map** lens.

The following lens types do not accept color parameters: **Brighten**, **Fish eye**, **Heat map**, **Invert**, and **Magnify**.

VBA example

The following VBA example changes the color of all lenses on the page to red. For the **Custom Color Map** and **Wireframe** lenses, yellow is also used.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrLens Then
    Select Case eff.Lens.Type
     Case cdrLensColorAdd, cdrLensColorLimit, _
      cdrLensTintedGrayscale, cdrLensTransparency
     eff.Lens.Color.RGBAssign 255, 0, 0
     Case cdrLensCustomColorMap
      eff.Lens.FromColor.RGBAssign 255, 0, 0
      eff.Lens.ToColor.RGBAssign 255, 255, 0
     Case cdrLensWireframe
      With eff.Lens
       .UseFillColor = True
       .UseOutlineColor = True
       .FillColor.RGBAssign 255, 0, 0
       .OutlineColor.RGBAssign 255, 255, 0
      End With
     End Select
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.Frozen

Property **Frozen** As Boolean

Description

Member of EffectLens

The **Frozen** property returns **True** if the lens is frozen.

The **Frozen** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.Magnification

Property **Magnification** As Double

Description

Member of EffectLens

The **Magnification** property returns or set the magnification level of a **Magnify** lens.

VBA example

The following VBA example makes sure that no **Magnify** lens uses magnification level greater than 3.0×.

```
Sub Test1()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrLens Then
    If eff.Lens.Type = cdrLensMagnify Then
     If eff.Lens.Magnification > 3 Then
      eff.Lens.Magnification = 3
     End If
    End If
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.OutlineColor

Property **OutlineColor** As Color

Description

Member of EffectLens

The **OutlineColor** property returns or specifies the outline color for a **Wireframe** lens.

The following lens types do not accept color parameters: **Brighten**, **Fish eye**, **Heat map**, **Invert**, and **Magnify**.

VBA example

The following VBA example changes the color of all lenses on the page to red. For the **Custom Color Map** and **Wireframe** lenses, yellow is also used.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrLens Then
    Select Case eff.Lens.Type
     Case cdrLensColorAdd, cdrLensColorLimit, _
      cdrLensTintedGrayscale, cdrLensTransparency
     eff.Lens.Color.RGBAssign 255, 0, 0
     Case cdrLensCustomColorMap
      eff.Lens.FromColor.RGBAssign 255, 0, 0
      eff.Lens.ToColor.RGBAssign 255, 255, 0
     Case cdrLensWireframe
      With eff.Lens
       .UseFillColor = True
       .UseOutlineColor = True
       .FillColor.RGBAssign 255, 0, 0
       .OutlineColor.RGBAssign 255, 255, 0
      End With
     End Select
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.PaletteRotation

Property **PaletteRotation** As Long

Description

Member of EffectLens

The **PaletteRotation** property returns or set the palette rotation for a **Heat map** lens.

VBA example

The following VBA example creates a **Heat map** lens with a palette rotation of 50%. (In this example, the palette rotation value can be specified directly in the **CreateLens** method as its second parameter. The current approach is used for illustration only).

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Set s1 = ActiveLayer.CreateRectangle(0, 0, 5, 5)
 s1.Fill.ApplyFountainFill
 Set s2 = ActiveLayer.CreateEllipse(1, 1, 6, 6)
 With s2.CreateLens(cdrLensHeatMap).Lens
  .PaletteRotation = 50
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.Parent

Property **Parent** As Effect

Description

Member of EffectLens

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.Rate

Property **Rate** As Long

Description

Member of EffectLens

The **Rate** property returns or specifies the strength of the lens effect. Values range from **0**% to **100**%.

The **Rate** property is available only for the following types of lenses: **Brighten**, **Color add**, **Color limit**, **Fish eye**, and **Transparency**.

VBA example

The following VBA example selects all shapes with a **Transparency** lens and with a transparency level greater than **80**%.

```
Sub Test()
 Dim s As Shape, eff As Effect
 Dim sr As New ShapeRange
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrLens Then
    If eff.Lens.Type = cdrLensTransparency Then
     If eff.Lens.Rate > 80 Then sr.Add s
    End If
    Exit For
   End If
  Next eff
 Next s
 sr.CreateSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.RemoveFace

Property **RemoveFace** As Boolean

Description

Member of EffectLens

The **RemoveFace** property returns or specifies whether to show the lens face or the effect of a lens. If this property is set to **True**, the lens displays its effects only where it covers the object.

The **RemoveFace** option is available for color-altering lenses only and is not available for **Fish eye** and **Magnify** lenses.

VBA example

The following VBA example creates two **Heat map** lenses, one with and one without the **RemoveFace** option.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Set s1 = ActiveLayer.CreateRectangle2(0, 2, 3, 2)
 s1.Fill.ApplyFountainFill
 Set s2 = ActiveLayer.CreateEllipse2(1.5, 4.5, 1.5)
 s2.CreateLens(cdrLensHeatMap, 20).Lens.RemoveFace = True
 Set s2 = ActiveLayer.CreateEllipse2(1.5, 1.5, 1.5)
 s2.CreateLens(cdrLensHeatMap, 20).Lens.RemoveFace = False
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.Shapes

Property **Shapes** As Shapes

Description

Member of EffectLens

The **Shapes** property returns the Shapes collection, which contains all intermediate shapes generated by a frozen lens.

The **Shapes** property returns a read-only value.

VBA example

The following VBA example creates a **Fish eye** lens, freezes it, and then ungroups and moves the resulting objects by **4**" to the right.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape, sr As ShapeRange
 Set s1 = ActiveLayer.CreateRectangle(0, 0, 5, 5)
 s1.Fill.ApplyFountainFill
 Set s2 = ActiveLayer.CreateEllipse(1, 1, 6, 6)
 With s2.CreateLens(cdrLensFishEye, 100).Lens
  .Freeze
  Set sr = .Ungroup
 End With
 sr.Move 4, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.ToColor

Property **ToColor** As Color

Description

Member of EffectLens

The **ToColor** property returns or specifies the ending color for the **Custom Color Map** lens.

The following lens types do not accept color parameters: **Brighten**, **Fish eye**, **Heat map**, **Invert**, and **Magnify**.

VBA example

The following VBA example changes the color of all lenses on the page to red. For the **Custom Color Map** and **Wireframe** lenses, yellow is also used.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrLens Then
    Select Case eff.Lens.Type
     Case cdrLensColorAdd, cdrLensColorLimit, _
      cdrLensTintedGrayscale, cdrLensTransparency
     eff.Lens.Color.RGBAssign 255, 0, 0
     Case cdrLensCustomColorMap
      eff.Lens.FromColor.RGBAssign 255, 0, 0
      eff.Lens.ToColor.RGBAssign 255, 255, 0
     Case cdrLensWireframe
      With eff.Lens
       .UseFillColor = True
       .UseOutlineColor = True
       .FillColor.RGBAssign 255, 0, 0
       .OutlineColor.RGBAssign 255, 255, 0
      End With
     End Select
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.Type

Property **Type** As cdrLensType

Description

Member of EffectLens

The **Type** property returns or specifies the lens type.

The **Type** property returns cdrLensType.

VBA example

The following VBA example selects all **Transparency** lenses on the page.

```
Sub Test1()
 Dim s As Shape, eff As Effect
 Dim sr As New ShapeRange
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrLens Then
    If eff.Lens.Type = cdrLensTransparency Then sr.Add s
    Exit For
   End If
  Next eff
 Next s
 sr.CreateSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.Unfreeze

Sub **Unfreeze()**

Description

Member of EffectLens

The **Unfreeze** method removes the freeze on a lens.

Frozen lenses redraw more quickly than non-frozen lenses. When a lens is frozen, the contents of the object no longer interact with other objects on the screen.

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.Ungroup

Function **Ungroup()** As ShapeRange

Description

Member of EffectLens

The **Ungroup** method breaks up the group of contents in a frozen lens, resulting in a number of individual shapes generated by the lens. The shapes are returned from the method as a ShapeRange collection.

VBA example

The following VBA example creates a **Fish eye** lens, freezes it, and then ungroups and moves the resulting objects by **4"** to the right.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape, sr As ShapeRange
 Set s1 = ActiveLayer.CreateRectangle(0, 0, 5, 5)
 s1.Fill.ApplyFountainFill
 Set s2 = ActiveLayer.CreateEllipse(1, 1, 6, 6)
 With s2.CreateLens(cdrLensFishEye, 100).Lens
  .Freeze
  Set sr = .Ungroup
 End With
 sr.Move 4, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.UseFillColor

Property **UseFillColor** As Boolean

Description

Member of EffectLens

The **UseFillColor** property returns or specifies whether the fill color is for a **Wireframe** lens.

The following lens types do not accept color parameters: **Brighten**, **Fish eye**, **Heat map**, **Invert**, and **Magnify**.

VBA example

The following VBA example changes the color of all lenses on the page to red. For the **Custom Color Map** and **Wireframe** lenses, yellow is also used.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrLens Then
    Select Case eff.Lens.Type
     Case cdrLensColorAdd, cdrLensColorLimit, _
      cdrLensTintedGrayscale, cdrLensTransparency
     eff.Lens.Color.RGBAssign 255, 0, 0
     Case cdrLensCustomColorMap
      eff.Lens.FromColor.RGBAssign 255, 0, 0
      eff.Lens.ToColor.RGBAssign 255, 255, 0
     Case cdrLensWireframe
      With eff.Lens
       .UseFillColor = True
       .UseOutlineColor = True
       .FillColor.RGBAssign 255, 0, 0
       .OutlineColor.RGBAssign 255, 255, 0
      End With
     End Select
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.UseOutlineColor

Property **UseOutlineColor** As Boolean

Description

Member of EffectLens

The **UseOutlineColor** property returns or specifies whether the outline color is used for a **Wireframe** lens.

The following lens types do not accept color parameters: **Brighten**, **Fish eye**, **Heat map**, **Invert**, and **Magnify**.

VBA example

The following VBA example changes the color of all lenses on the page to red. For the **Custom Color Map** and **Wireframe** lenses, yellow is also used.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrLens Then
    Select Case eff.Lens.Type
     Case cdrLensColorAdd, cdrLensColorLimit, _
      cdrLensTintedGrayscale, cdrLensTransparency
     eff.Lens.Color.RGBAssign 255, 0, 0
     Case cdrLensCustomColorMap
      eff.Lens.FromColor.RGBAssign 255, 0, 0
      eff.Lens.ToColor.RGBAssign 255, 255, 0
     Case cdrLensWireframe
      With eff.Lens
       .UseFillColor = True
       .UseOutlineColor = True
       .FillColor.RGBAssign 255, 0, 0
       .OutlineColor.RGBAssign 255, 255, 0
      End With
     End Select
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.UseViewPoint

Property **UseViewPoint** As Boolean

Description

Member of EffectLens

The **UseViewPoint** property returns or specifies whether a viewpoint is used in a lens.

VBA example

The following VBA example creates a magnified view of a certain region of the drawing.

```
Sub Test()
 Dim sText As Shape, sLens As Shape
 Set sText = ActiveLayer.CreateArtisticText(0, 0, "Some Text")
 sText.Fill.UniformColor.RGBAssign 255, 0, 0
 Set sLens = ActiveLayer.CreateEllipse2(1.5, 1.5, 0.7)
 With sLens.CreateLens(cdrLensMagnify, 3).Lens
  .UseViewPoint = True
  .ViewPointX = 0.6
  .ViewPointY = 0.08
 End With
 ActiveLayer.CreateEllipse2 0.6, 0.08, 0.23
 ActiveLayer.CreateLineSegment 0.74, -0.1, 2.02, 1.02
 ActiveLayer.CreateLineSegment 0.39, 0.15, 0.85, 1.76
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.ViewPointX

Property **ViewPointX** As Double

Description

Member of EffectLens

The **ViewPointX** property returns or specifies the x-coordinate of a viewpoint in a lens.

VBA example

The following VBA example creates a magnified view of a certain region of the drawing.

```
Sub Test()
 Dim sText As Shape, sLens As Shape
 Set sText = ActiveLayer.CreateArtisticText(0, 0, "Some Text")
 sText.Fill.UniformColor.RGBAssign 255, 0, 0
 Set sLens = ActiveLayer.CreateEllipse2(1.5, 1.5, 0.7)
 With sLens.CreateLens(cdrLensMagnify, 3).Lens
  .UseViewPoint = True
  .ViewPointX = 0.6
  .ViewPointY = 0.08
 End With
 ActiveLayer.CreateEllipse2 0.6, 0.08, 0.23
 ActiveLayer.CreateLineSegment 0.74, -0.1, 2.02, 1.02
 ActiveLayer.CreateLineSegment 0.39, 0.15, 0.85, 1.76
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectLens.ViewPointY

Property **ViewPointY** As Double

Description

Member of EffectLens

The **ViewPointY** property returns or specifies the y-coordinate of a viewpoint in a lens.

VBA example

The following VBA example creates a magnified view of a certain region of the drawing.

```
Sub Test()
 Dim sText As Shape, sLens As Shape
 Set sText = ActiveLayer.CreateArtisticText(0, 0, "Some Text")
 sText.Fill.UniformColor.RGBAssign 255, 0, 0
 Set sLens = ActiveLayer.CreateEllipse2(1.5, 1.5, 0.7)
 With sLens.CreateLens(cdrLensMagnify, 3).Lens
  .UseViewPoint = True
  .ViewPointX = 0.6
  .ViewPointY = 0.08
 End With
 ActiveLayer.CreateEllipse2 0.6, 0.08, 0.23
 ActiveLayer.CreateLineSegment 0.74, -0.1, 2.02, 1.02
 ActiveLayer.CreateLineSegment 0.39, 0.15, 0.85, 1.76
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectPerspective

Properties

Description

The **EffectPerspective** represents the settings for perspective effects.

Copyright 2014 Corel Corporation. All rights reserved.

EffectPerspective.Application

Property **Application** As Application

Description

Member of EffectPerspective

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

EffectPerspective.HorizVanishingPointX

Property **HorizVanishingPointX** As Double

Description

Member of EffectPerspective

The **HorizVanishingPointX** property returns or specifies the x-coordinate of the horizontal vanishing point in a perspective effect.

VBA example

The following VBA example changes the position of vanishing points for all perspective effects so that the horizontal vanishing point is placed in the middle of the left edge of the page, while the vertical vanishing point is placed in the middle of the top edge of the page.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrPerspective Then
    With eff.Perspective
     If .UseHorizVanishingPoint Then
      .HorizVanishingPointX = 0
      .HorizVanishingPointY = ActivePage.SizeHeight / 2
     End If
     If .UseVertVanishingPoint Then
      .VertVanishingPointX = ActivePage.SizeWidth / 2
      .VertVanishingPointY = ActivePage.SizeHeight
     End If
    End With
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectPerspective.HorizVanishingPointY

Property **HorizVanishingPointY** As Double

Description

Member of EffectPerspective

The **HorizVanishingPointY** property returns or specifies the y-coordinate of the horizontal vanishing point in a perspective effect.

VBA example

The following VBA example changes the position of vanishing points for all perspective effects so that the horizontal vanishing point is placed in the middle of the left edge of the page, while the vertical vanishing point is placed in the middle of the top edge of the page.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrPerspective Then
    With eff.Perspective
     If .UseHorizVanishingPoint Then
      .HorizVanishingPointX = 0
      .HorizVanishingPointY = ActivePage.SizeHeight / 2
     End If
     If .UseVertVanishingPoint Then
      .VertVanishingPointX = ActivePage.SizeWidth / 2
      .VertVanishingPointY = ActivePage.SizeHeight
     End If
    End With
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectPerspective.Parent

Property **Parent** As Effect

Description

Member of EffectPerspective

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

EffectPerspective.UseHorizVanishingPoint

Property **UseHorizVanishingPoint** As Boolean

Description

Member of EffectPerspective

The **UseHorizVanishingPoint** property returns or specifies whether to use a horizontal vanishing point in a perspective effect.

If **UseHorizVanishingPoint** is set to **False**, the corresponding vanishing point is set to infinity.

VBA example

The following VBA example changes the position of vanishing points for all perspective effects so that the horizontal vanishing point is placed in the middle of the left edge of the page, while the vertical vanishing point is placed in the middle of the top edge of the page.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrPerspective Then
    With eff.Perspective
     If .UseHorizVanishingPoint Then
      .HorizVanishingPointX = 0
      .HorizVanishingPointY = ActivePage.SizeHeight / 2
     End If
     If .UseVertVanishingPoint Then
      .VertVanishingPointX = ActivePage.SizeWidth / 2
      .VertVanishingPointY = ActivePage.SizeHeight
     End If
    End With
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectPerspective.UseVertVanishingPoint

Property **UseVertVanishingPoint** As Boolean

Description

Member of EffectPerspective

The **UseVertVanishingPoint** property returns or specifies whether to use a vertical vanishing point in a perspective effect.

If **UseVertVanishingPoint** is set to **False**, the corresponding vanishing point is set to infinity.

VBA example

The following VBA example changes the position of vanishing points for all perspective effects so that the horizontal vanishing point is placed in the middle of the left edge of the page, while the vertical vanishing point is placed in the middle of the top edge of the page.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrPerspective Then
    With eff.Perspective
     If .UseHorizVanishingPoint Then
      .HorizVanishingPointX = 0
      .HorizVanishingPointY = ActivePage.SizeHeight / 2
     End If
     If .UseVertVanishingPoint Then
      .VertVanishingPointX = ActivePage.SizeWidth / 2
      .VertVanishingPointY = ActivePage.SizeHeight
     End If
    End With
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectPerspective.VertVanishingPointX

Property **VertVanishingPointX** As Double

Description

Member of EffectPerspective

The **VertVanishingPointX** property returns or specifies the x-coordinate of the vertical vanishing point in a perspective effect.

VBA example

The following VBA example changes the position of vanishing points for all perspective effects so that the horizontal vanishing point is placed in the middle of the left edge of the page, while the vertical vanishing point is placed in the middle of the top edge of the page.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrPerspective Then
    With eff.Perspective
     If .UseHorizVanishingPoint Then
      .HorizVanishingPointX = 0
      .HorizVanishingPointY = ActivePage.SizeHeight / 2
     End If
     If .UseVertVanishingPoint Then
      .VertVanishingPointX = ActivePage.SizeWidth / 2
      .VertVanishingPointY = ActivePage.SizeHeight
     End If
    End With
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectPerspective.VertVanishingPointY

Property **VertVanishingPointY** As Double

Description

Member of EffectPerspective

The **VertVanishingPointY** property returns or specifies the y-coordinate of the vertical vanishing point in a perspective effect.

VBA example

The following VBA example changes the position of vanishing points for all perspective effects so that the horizontal vanishing point is placed in the middle of the left edge of the page, while the vertical vanishing point is placed in the middle of the top edge of the page.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrPerspective Then
    With eff.Perspective
     If .UseHorizVanishingPoint Then
      .HorizVanishingPointX = 0
      .HorizVanishingPointY = ActivePage.SizeHeight / 2
     End If
     If .UseVertVanishingPoint Then
      .VertVanishingPointX = ActivePage.SizeWidth / 2
      .VertVanishingPointY = ActivePage.SizeHeight
     End If
    End With
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectPushPullDistortion

Properties

Description

The **EffectPushPullDistortion** class represents the settings for a Push-and-pull distortion effect.

Copyright 2014 Corel Corporation. All rights reserved.

EffectPushPullDistortion.Amplitude

Property **Amplitude** As Long

Description

Member of EffectPushPullDistortion

The **Amplitude** property returns or specifies the strength of the effect in a Push-and-pull distortion effect.

The range of the distortion value is **1** to **200**.

VBA example

The following VBA example sets the amplitude of all Push-and-pull distortion effects to **30**.

```
Sub Test()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrDistortion Then
    If eff.Distortion.Type = cdrDistortionPushPull Then
     eff.Distortion.PushPull.Amplitude = 30
    End If
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectPushPullDistortion.Application

Property **Application** As Application

Description

Member of EffectPushPullDistortion

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

EffectPushPullDistortion.Parent

Property **Parent** As EffectDistortion

Description

Member of EffectPushPullDistortion

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Effects

Properties

Description

The **Effects** class represents a collection of all effects applied to a shape.

Copyright 2014 Corel Corporation. All rights reserved.

Effects.Application

Property **Application** As Application

Description

Member of Effects

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Effects.BlendEffects

Property **BlendEffects** As Effects

Description

Member of Effects

The **BlendEffects** property returns a collection of all blend effects applied to a shape.

The **BlendEffects** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Effects.ContourEffect

Property **ContourEffect** As Effect

Description

Member of Effects

The **ContourEffect** property returns the current contour effect applied to a shape.

The **ContourEffect** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Effects.ControlPathEffect

Property **ControlPathEffect** As Effect

Description

Member of Effects

The **ControlPathEffect** property returns an effect object representing all blend and text-on-path effects for the current curve shape.

The **ControlPathEffect** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Effects.Count

Property **Count** As Long

Description

Member of Effects

The **Count** property returns the number of effects in the Effects collection.

The **Count** property returns a read-only value.

VBA example

The following VBA example selects the first shape to which an effect is applied.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Effects.Count <> 0 Then
   s.CreateSelection
   Exit For
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Effects.CustomEffects

Property **CustomEffects** As Effects

Description

Member of Effects

The **CustomEffects** property returns a collection of all custom effects applied to a shape.

The **CustomEffects** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Effects.DistortionEffects

Property **DistortionEffects** As Effects

Description

Member of Effects

The **DistortionEffects** property returns a collection of all distortion effects applied to a shape.

The **DistortionEffects** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Effects.DropShadowEffect

Property **DropShadowEffect** As Effect

Description

Member of Effects

The **DropShadowEffects** property returns the current drop-shadow effect applied to a shape.

The **DropShadowEffects** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Effects.EnvelopeEffects

Property **EnvelopeEffects** As Effects

Description

Member of Effects

The **EnvelopeEffects** property returns a collection of all envelope effects applied to a shape.

The **EnvelopeEffects** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Effects.ExtrudeEffect

Property **ExtrudeEffect** As Effect

Description

Member of Effects

The **ExtrudeEffect** property returns the current extrusion effect applied to a shape.

The **ExtrudeEffect** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Effects.Item

Property **Item(***Index As Long***)** As Effect

Description

Member of Effects

The **Item** property returns a specific Effect object representing the effect applied.

Item is the default property of the Effects class, and its reference can be omitted when you are accessing items in an **Effects** collection. For example, **Effects.Item(2)** is the same as **Effects(2)** — they both reference the second effect in the collection.

The **Item** property returns returns a read-only value.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each member of the **Effects** collection

VBA example

The following VBA example places text on a path.

```
Sub Test()
 Dim sText As Shape, sEllipse As Shape
 Set sText = ActiveLayer.CreateArtisticText(0, 0, "Text On Path")
 Set sEllipse = ActiveLayer.CreateEllipse2(4, 5, 2)
 sText.Text.FitToPath sEllipse
 sText.Effects(1).TextOnPath.Quadrant = cdrBottomQuadrant
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Effects.LensEffect

Property **LensEffect** As Effect

Description

Member of Effects

The **LensEffect** property returns the current lens effect applied to the shape.

The **LensEffect** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Effects.Parent

Property **Parent** As Shape

Description

Member of Effects

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Effects.PerspectiveEffects

Property **PerspectiveEffects** As Effects

Description

Member of Effects

The **PerspectiveEffects** property returns a collection of all perspective effects applied to a shape.

The **PerspectiveEffects** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Effects.TextOnPathEffect

Property **TextOnPathEffect** As Effect

Description

Member of Effects

The **TextOnPathEffect** property returns the current text-on-path effect applied to a shape.

The **TextOnPathEffect** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

EffectTextOnPath

Properties

Description

The **EffectTextOnPath** class represents the settings for a text-on-path-effect.

Copyright 2014 Corel Corporation. All rights reserved.

EffectTextOnPath.Application

Property **Application** As Application

Description

Member of EffectTextOnPath

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

EffectTextOnPath.DistanceFromPath

Property **DistanceFromPath** As Double

Description

Member of EffectTextOnPath

The **DistanceFromPath** property returns or specifies the vertical distance (offset) between the text and its path. The distance is specified in document units of measurements.

VBA example

The following VBA example creates text fitted to a circle and specifies a distance of **0.5**" between the text and the circle.

```
Sub Test()
 Dim sText As Shape, sEllipse As Shape
 Set sText = ActiveLayer.CreateArtisticText(0, 0, "Text On Path")
 Set sEllipse = ActiveLayer.CreateEllipse2(4, 5, 2)
 sText.Text.FitToPath sEllipse
 sText.Effects(1).TextOnPath.DistanceFromPath = 0.5
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectTextOnPath.Offset

Property **Offset** As Double

Description

Member of EffectTextOnPath

The **Offset** property returns or specifies the horizontal text offset from the beginning of the path.

VBA example

The following VBA example attaches a text shape to a path and places it **2**" from the beginning of the path.

```
Sub Test()
 Dim sText As Shape, sPath As Shape
 Set sText = ActiveLayer.CreateArtisticText(0, 0, "Text On Path")
 Set sPath = ActiveLayer.CreateCurveSegment(0.6, 4.5, 7.8, 8.5, 5.2, 62, 5.3, -96)
 sText.Text.FitToPath sPath
 sText.Effects(1).TextOnPath.Offset = 2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectTextOnPath.Orientation

Property **Orientation** As cdrFittedOrientation

Description

Member of EffectTextOnPath

The **Orientation** property returns or specifies the character orientation as the text follows the control path.

This value returns cdrFittedOrientation.

VBA example

The following VBA example creates a text shape fitted to a path and makes the text remain upright by skewing characters vertically.

```
Sub Test()
 Dim sText As Shape, sPath As Shape
 Set sText = ActiveLayer.CreateArtisticText(0, 0, "Some Long Text Line")
 Set sPath = ActiveLayer.CreateCurveSegment(0.6, 4.5, 5, 5.5, 3, 80, 3, -100)
 sText.Text.FontProperties.Size = 48
 sText.Text.FitToPath sPath
 sText.Effects(1).TextOnPath.Orientation = cdrVerticalSkewOrientation
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectTextOnPath.Parent

Property **Parent** As Effect

Description

Member of EffectTextOnPath

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

EffectTextOnPath.Path

Property **Path** As Shape

Description

Member of EffectTextOnPath

The **Path** property returns or specifies the path Shape object to which the text is attached.

VBA example

The following VBA example applies a red outline to all paths with text attached.

```
Sub Test1()
 Dim s As Shape, eff As Effect
 For Each s In ActivePage.FindShapes(, cdrTextShape)
  For Each eff In s.Effects
   If eff.Type = cdrTextOnPath Then
    eff.TextOnPath.Path.Outline.Color.RGBAssign 255, 0, 0
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectTextOnPath.Placement

Property **Placement** As cdrFittedPlacement

Description

Member of EffectTextOnPath

The **Placement** property returns or specifies the placement of text on an open curve.

This property returns a value of cdrFittedPlacement.

- See also the EffectTextOnPath.Quadrant property.

VBA example

The following VBA example places the text in the middle of a curve.

```
Sub Test()
 Dim sText As Shape, sPath As Shape
 Set sText = ActiveLayer.CreateArtisticText(0, 0, "Some Text")
 Set sPath = ActiveLayer.CreateCurveSegment(0.6, 4.5, 5, 5.5, 3, 80, 3, -100)
 sText.Text.FitToPath sPath
 sText.Effects(1).TextOnPath.Placement = cdrCenterPlacement
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectTextOnPath.PlaceOnOtherSide

Property **PlaceOnOtherSide** As Boolean

Description

Member of EffectTextOnPath

The **PlaceOnOtherSide** property returns whether text is placed on the opposite side of the path in a text-on-path effect. A value of **True** places the text on the opposite side of the path object.

VBA example

The following VBA example places the text inside an ellipse.

```
Sub Test()
 Dim sText As Shape, sPath As Shape
 Set sText = ActiveLayer.CreateArtisticText(0, 0, "Some Text")
 Set sPath = ActiveLayer.CreateEllipse2(4.25, 5.5, 2, 3)
 sText.Text.FitToPath sPath
 With sText.Effects(1).TextOnPath
  .Quadrant = cdrBottomQuadrant
  .PlaceOnOtherSide = True
  .DistanceFromPath = 0.1
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectTextOnPath.Quadrant

Property **Quadrant** As cdrFittedQuadrant

Description

Member of EffectTextOnPath

The **Quadrant** property returns or specifies the placement of text on a closed curve.

This property returns cdrFittedQuadrant.

- See also the EffectTextOnPath.Placement property.

VBA example

The following VBA example places the text on the right side of a circle.

```
Sub Test()
 Dim sText As Shape, sPath As Shape
 Set sText = ActiveLayer.CreateArtisticText(0, 0, "Some Text")
 Set sPath = ActiveLayer.CreateEllipse2(4.25, 5.5, 2)
 sText.Text.FitToPath sPath
 sText.Effects(1).TextOnPath.Quadrant = cdrRightQuadrant
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectTextOnPath.Text

Property **Text** As Shape

Description

Member of EffectTextOnPath

The **Text** property returns or specifies the text Shape that is fitted to a path.

Copyright 2014 Corel Corporation. All rights reserved.

EffectTextOnPath.VertPlacement

Property **VertPlacement** As cdrFittedVertPlacement

Description

Member of EffectTextOnPath

The **VertPlacement** property returns or specifies the mode of the vertical placement of text for a text-on-path effect.

The **VertPlacement** property returns cdrFittedVertPlacement.

VBA example

The following VBA example places the text on a circle, so it appears centered vertically relative to the circle.

```
Sub Test()
 Dim sText As Shape, sPath As Shape
 Set sText = ActiveLayer.CreateArtisticText(0, 0, "Some Text")
 Set sPath = ActiveLayer.CreateEllipse2(4.25, 5.5, 2)
 sText.Text.FitToPath sPath
 sText.Effects(1).TextOnPath.VertPlacement = cdrCenterVertPlacement
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectTwisterDistortion

Properties

Description

The **EffectTwisterDistortion** class represents the settings for a Twister distortion effect.

Copyright 2014 Corel Corporation. All rights reserved.

EffectTwisterDistortion.Angle

Property **Angle** As Double

Description

Member of EffectTwisterDistortion

The **Angle** property returns or specifies the twist angle in a Twister distortion effect.

Positive values denote a counterclockwise rotation, while negative values represent a clockwise rotation. To achieve several full rotations, multiply the number of rotations by 360 for the resultant rotation angle.

VBA example

The following VBA example creates a text shape and applies a Twister distortion effect to it. The twisting angle specified is 450° counterclockwise, resulting in one complete rotation and an additional rotation of 90°.

```
Sub Test()
 Dim sText As Shape, eff As Effect
 Set sText = ActiveLayer.CreateArtisticText(1.5, 5, "Twister")
 sText.Text.FontProperties.Size = 150
 Set eff = sText.CreateTwisterDistortion(0, 0, 0)
 eff.Distortion.Twister.Angle = -450
End Sub
```

Alternatively, you can specify the angle in the call to the Shape.CreateTwisterDistortion method, resulting in a procedure that works faster.

Copyright 2014 Corel Corporation. All rights reserved.

EffectTwisterDistortion.Application

Property **Application** As Application

Description

Member of EffectTwisterDistortion

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

EffectTwisterDistortion.Parent

Property **Parent** As EffectDistortion

Description

Member of EffectTwisterDistortion

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

EffectZipperDistortion

Properties

Description

The **EffectZipperDistortion** class represents the settings for a Zipper distortion effect.

Copyright 2014 Corel Corporation. All rights reserved.

EffectZipperDistortion.Amplitude

Property **Amplitude** As Long

Description

Member of EffectZipperDistortion

The **Amplitude** property returns or specifies the amplitude or strength of a Zipper distortion effect.

Values range from **0**% to **100**%. Higher values produce a more pronounced Zipper distortion effect.

VBA example

The following VBA example specifies a wave amplitude of **20**% for each Zipper distortion effect with a frequency greater than **10**.

```
Sub Test()
 Dim s As Shape, eff As Effect, zip As EffectZipperDistortion
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrDistortion Then
    If eff.Distortion.Type = cdrDistortionZipper Then
     Set zip = eff.Distortion.Zipper
     If zip.Frequency > 10 Then zip.Amplitude = 20
    End If
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectZipperDistortion.Application

Property **Application** As Application

Description

Member of EffectZipperDistortion

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

EffectZipperDistortion.Frequency

Property **Frequency** As Long

Description

Member of EffectZipperDistortion

The **Frequency** property returns or specifies the frequency of a Zipper distortion effect.

Values range from **0** to **100**. A higher frequency value creates more zipper points in the distortion effect.

VBA example

The following VBA example specifies a wave amplitude of **20**% for each Zipper distortion effect with a frequency greater than **10**.

```
Sub Test()
 Dim s As Shape, eff As Effect, zip As EffectZipperDistortion
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrDistortion Then
    If eff.Distortion.Type = cdrDistortionZipper Then
     Set zip = eff.Distortion.Zipper
     If zip.Frequency > 10 Then zip.Amplitude = 20
    End If
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectZipperDistortion.Local

Property **Local** As Boolean

Description

Member of EffectZipperDistortion

The **Local** property returns or specifies whether the Zipper distortion effect is emphasized in an area of the object.

When **Local** is set to **True**, the transformation amplitude becomes dependent on the distance from the center of distortion.

VBA example

The following VBA example selects all shapes having a Zipper distortion effect that is smooth, random, and not local.

```
Sub Test()
 Dim s As Shape, eff As Effect, zip As EffectZipperDistortion
 Dim sr As New ShapeRange
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrDistortion Then
    If eff.Distortion.Type = cdrDistortionZipper Then
     Set zip = eff.Distortion.Zipper
     If zip.Smooth And zip.Random And Not zip.Local Then sr.Add s
    End If
    Exit For
   End If
  Next eff
 Next s
 sr.CreateSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectZipperDistortion.Parent

Property **Parent** As EffectDistortion

Description

Member of EffectZipperDistortion

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

EffectZipperDistortion.Random

Property **Random** As Boolean

Description

Member of EffectZipperDistortion

The **Random** property returns or specifies whether the distorting waves in a Zipper distortion effect should be generated with random amplitudes.

VBA example

The following VBA example selects all shapes having a Zipper distortion effect that is smooth, random, and not local.

```
Sub Test()
 Dim s As Shape, eff As Effect, zip As EffectZipperDistortion
 Dim sr As New ShapeRange
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrDistortion Then
    If eff.Distortion.Type = cdrDistortionZipper Then
     Set zip = eff.Distortion.Zipper
     If zip.Smooth And zip.Random And Not zip.Local Then sr.Add s
    End If
    Exit For
   End If
  Next eff
 Next s
 sr.CreateSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EffectZipperDistortion.Smooth

Property **Smooth** As Boolean

Description

Member of EffectZipperDistortion

The **Smooth** property returns or specifies whether the wave peaks are smooth in a Zipper distortion effect.

VBA example

The following VBA example selects all shapes having a Zipper distortion effect that is smooth, random, and not local.

```
Sub Test()
 Dim s As Shape, eff As Effect, zip As EffectZipperDistortion
 Dim sr As New ShapeRange
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrDistortion Then
    If eff.Distortion.Type = cdrDistortionZipper Then
     Set zip = eff.Distortion.Zipper
     If zip.Smooth And zip.Random And Not zip.Local Then sr.Add s
    End If
    Exit For
   End If
  Next eff
 Next s
 sr.CreateSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Ellipse

Properties Methods

Description

The **Ellipse** class represents the ellipse-specific settings for a shape (or Shape object).

Copyright 2014 Corel Corporation. All rights reserved.

Ellipse.CenterX

Property **CenterX** As Double

Description

Member of Ellipse

The **CenterX** property returns or specifies the position of the x-coordinate for the center of an ellipse, arc, or pie. This is not the same as the geometrical center of the shape for an arc or a pie.

VBA example

The following VBA example moves the ellipse so that its center appears at the left side of the current page.

```
Sub Test()
 ActiveShape.Ellipse.CenterX = 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Ellipse.CenterY

Property **CenterY** As Double

Description

Member of Ellipse

The **CenterY** property returns or specifies the position of the y-coordinate for the center of an ellipse, arc, or pie. This is not the same as the geometrical center of the shape for an arc or a pie.

VBA example

The following VBA example moves the ellipse so that its center appears at the bottom side of the current page.

```
Sub Test()
 ActiveShape.Ellipse.CenterY = 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Ellipse.Clockwise

Property **Clockwise** As Boolean

Description

Member of Ellipse

The **Clockwise** property returns or specifies a value indicating whether the ellipse, arc, or pie goes from the start angle to the end angle in a clockwise or counterclockwise direction. If the value returned is **True**, the ellipse has a clockwise rotation.

VBA example

The following VBA example converts the selected ellipse to a pie with a start angle of 0°, an end angle of 90°, and a clockwise rotation.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveSelection.Shapes(1)
 If s.Type = cdrEllipseShape Then
  With s.Ellipse
   .StartAngle = 0
   .EndAngle = 90
   .Clockwise = True
   .Type = cdrPie
  End With
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Ellipse.EndAngle

Property **EndAngle** As Double

Description

Member of Ellipse

The **EndAngle** property returns or specifies the end angle of an arc or pie.

VBA example

The following VBA example sets the start angle of the pie or arc to be 90° greater than its end angle (making sure that the angle does not exceed the limit of 360°).

```
Sub Test()
 Dim s As Shape
 Dim a As Double
 Set s = ActiveShape
 If s.Type = cdrEllipseShape Then
  a = s.Ellipse.EndAngle + 90
  If a >= 360 Then a = a - 360 * Fix(a / 360)
  s.Ellipse.StartAngle = a
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Ellipse.GetCenterPosition

Sub **GetCenterPosition(***PositionX As Double***,** *PositionY As Double***)**

Description

Member of Ellipse

The **GetCenterPosition** method retrieves the coordinates of the center of an ellipse. Using **GetCenterPosition** is equivalent to getting the values of both CenterX and CenterY properties at the same time.

Parameter	Description
PositionX	Specifies the x-coordinate for the center of an ellipse, measured in document units
PositionY	Specifies the y-coordinate for the center of an ellipse, measured in document units

VBA example

The following VBA example increases the radius of the ellipse both horizontally and vertically by 2". Changing the radius of an ellipse causes its center to move. To preserve the center position of the ellipse, the **GetCenterPosition** and SetCenterPosition methods are used.

```
Sub Test()
 Dim x As Double, y As Double
 Dim rx As Double, ry As Double
 With ActiveShape.Ellipse
  .GetCenterPosition x, y
  .GetRadius rx, ry
  .SetRadius rx + 2, ry + 2
  .SetCenterPosition x, y
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Ellipse.GetRadius

Sub **GetRadius(***HRadius As Double***,** *VRadius As Double***)**

Description

Member of Ellipse

The **GetRadius** method retrieves the horizontal and vertical radii of an ellipse.

Using **GetRadius** is equivalent to getting the values of both the HRadius and VRadius properties at the same time.

Parameter	Description
HRadius	Specifies the horizontal radius of an ellipse, measured in document units
VRadius	Specifies the vertical radius of an ellipse, measured in document units

VBA example

The following VBA example increases the radius of the ellipse both horizontally and vertically by 2". Changing the radius of an ellipse causes its center to move. To preserve the center position of the ellipse, the GetCenterPosition and SetCenterPosition methods are used.

```
Sub Test()
 Dim x As Double, y As Double
 Dim rx As Double, ry As Double
 With ActiveShape.Ellipse
  .GetCenterPosition x, y
  .GetRadius rx, ry
  .SetRadius rx + 2, ry + 2
  .SetCenterPosition x, y
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Ellipse.HRadius

Property **HRadius** As Double

Description

Member of Ellipse

The **HRadius** property returns or specifies the horizontal radius of an ellipse.

The **HRadius** property does not take object rotation into account; thus, an ellipse that is rotated 90° returns the same horizontal radius as the ellipse before the rotation.

VBA example

The following VBA example sets the horizontal radius of the selected ellipse to 1".

```
Sub Test()
 ActiveShape.Ellipse.HRadius = 1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Ellipse.SetCenterPosition

Sub **SetCenterPosition(***PositionX As Double***,** *PositionY As Double***)**

Description

Member of Ellipse

The **SetCenterPosition** method moves the ellipse so that its center is located at given coordinates. Using **SetCenterPosition** is equivalent to setting the values of both CenterX and CenterY properties at the same time.

Parameter	Description
PositionX	Specifies the x-coordinate for the center of an ellipse, measured in document units
PositionY	Specifies the y-coordinate for the center of an ellipse, measured in document units

VBA example

The following VBA example increases the radius of the ellipse both horizontally and vertically by 2". Changing the radius of an ellipse causes its center to move. To preserve the center position of the ellipse, the GetCenterPosition and **SetCenterPosition** methods are used.

```
Sub Test()
 Dim x As Double, y As Double
 Dim rx As Double, ry As Double
 With ActiveShape.Ellipse
  .GetCenterPosition x, y
  .GetRadius rx, ry
  .SetRadius rx + 2, ry + 2
  .SetCenterPosition x, y
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Ellipse.SetRadius

Sub **SetRadius(***HRadius As Double***, [***VRadius As Double***])**

Description

Member of Ellipse

The **SetRadius** method specifies both the horizontal and the vertical radii of an ellipse.

Using **SetRadius** is equivalent to setting the values of both the HRadius and VRadius properties at the same time.

Parameter	Description
HRadius	Specifies the horizontal radius of an ellipse, measured in document units
VRadius	Specifies the vertical radius of an ellipse, measured in document units. If this value is not specified, it is assigned the same value as the **HRadius** parameter. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example increases the radius of the ellipse both horizontally and vertically by 2". Changing the radius of an ellipse causes its center to move. To preserve the center position of the ellipse, the GetCenterPosition and SetCenterPosition methods are used.

```
Sub Test()
 Dim x As Double, y As Double
 Dim rx As Double, ry As Double
 With ActiveShape.Ellipse
  .GetCenterPosition x, y
  .GetRadius rx, ry
  .SetRadius rx + 2, ry + 2
  .SetCenterPosition x, y
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Ellipse.StartAngle

Property **StartAngle** As Double

Description

Member of Ellipse

The **StartAngle** property returns or specifies the start angle of an arc or pie.

VBA example

The following VBA example sets the start angle of the pie or arc to be 90° greater than its end angle (making sure that the angle does not exceed the limit of 360°).

```
Sub Test()
 Dim s As Shape
 Dim a As Double
 Set s = ActiveShape
 If s.Type = cdrEllipseShape Then
  a = s.Ellipse.EndAngle + 90
  If a >= 360 Then a = a - 360 * Fix(a / 360)
  s.Ellipse.StartAngle = a
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Ellipse.Type

Property **Type** As cdrEllipseType

Description

Member of Ellipse

The **Type** property returns or specifies a value indicating whether the ellipse shape is a full ellipse, a pie, or an arc.

The **Type** property returns a value of cdrEllipseType.

VBA example

The following VBA example loops through all of the shapes on the active page of the active document, fills all ellipses with red, and changes arcs to pies.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Type = cdrEllipseShape Then
   If s.Ellipse.Type = cdrArc Then s.Ellipse.Type = cdrPie
   s.Fill.UniformColor.RGBAssign 255, 0, 0
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Ellipse.VRadius

Property **VRadius** As Double

Description

Member of Ellipse

The **VRadius** property returns or specifies the vertical radius of an ellipse.

The **VRadius** property does not take object rotation into account; thus, an ellipse that is rotated 90° returns the same vertical radius as the ellipse before the rotation.

VBA example

The following VBA example sets the vertical radius of the selected ellipse to 1".

```
Sub Test()
 ActiveShape.Ellipse.VRadius = 1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

EPS

Properties Methods

Description

The **EPS** class represents the settings for an Encapsulated PostScript (EPS) object.

Copyright 2014 Corel Corporation. All rights reserved.

EPS.BoundingBoxPath

Property **BoundingBoxPath** As Curve

Description

Member of EPS

The **BoundingBoxPath** property returns a curve that represents the original bounding box of the object.

The **BoundingBoxPath** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

EPS.CropEnvelope

Property **CropEnvelope** As Curve

Description

Member of EPS

The **CropEnvelope** property returns a curve representing the clipping path of the object.

The **CropEnvelope** property a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

EPS.CropEnvelopeModified

Property **CropEnvelopeModified** As Boolean

Description

Member of EPS

The **CropEnvelopeModified** property returns **True** if the clipping path of the object has been modified.

The **CropEnvelopeModified** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

EPS.Data

Property **Data** As Byte()

Description

Member of EPS

The **Data** property returns the EPS data stream as a binary array.

The **Data** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

EPS.DataAsString

Property **DataAsString** As String

Description

Member of EPS

The **DataAsString** property returns the EPS data stream as a string.

The **DataAsString** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

EPS.DCSFileNames

Property **DCSFileNames** As String()

Description

Member of EPS

The **DCSFileNames** property returns an array of strings representing the filenames of each color separation component of a DCS EPS file.

The **DCSFileNames** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

EPS.LinkFileName

Property **LinkFileName** As String

Description

Member of EPS

The **LinkFileName** property returns the path to the linked EPS file.

Copyright 2014 Corel Corporation. All rights reserved.

EPS.PreviewBitmap

Property **PreviewBitmap** As Bitmap

Description

Member of EPS

The **PreviewBitmap** property returns the preview bitmap.

The **PreviewBitmap** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

EPS.ResetCropEnvelope

Sub **ResetCropEnvelope()**

Description

Member of EPS

The **ResetCropEnvelope** method resets the clipping path to its original rectangular shape.

Copyright 2014 Corel Corporation. All rights reserved.

ExportFilter

Properties Methods

Description

The **ExportFilter** class represents export filters and their settings.

Copyright 2014 Corel Corporation. All rights reserved.

ExportFilter.Finish

Sub **Finish()**

Description

Member of ExportFilter

The **Finish** method completes the export process.

VBA example

The following VBA example creates a document and an ellipse and exports the document to JPEG.

```
Sub Test()
 Dim ex As ExportFilter
 Dim d As Document
 Set d = CreateDocument
 d.ActiveLayer.CreateEllipse2 4, 4, 1
 Set ex = d.ExportEx("c:\test.jpg", cdrJPEG)
 ex.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ExportFilter.HasDialog

Property **HasDialog** As Boolean

Description

Member of ExportFilter

The **HasDialog** property returns **True** if a filter has a filter-specific dialog box.

The **HasDialog** property returns a read-only value.

VBA example

The following VBA example creates a document and an ellipse. When exporting the document to JPEG, the dialog box for the filter is displayed (if one exists), and the export process is completed.

```
Sub Test()
 Dim ex As ExportFilter
 Dim d As Document
 Set d = CreateDocument
 d.ActiveLayer.CreateEllipse2 4, 4, 1
 Set ex = d.ExportEx("c:\test.jpg", cdrJPEG)
 With ex
  If .HasDialog Then
   .ShowDialog
  End If
  .Finish
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ExportFilter.Reset

Sub **Reset()**

Description

Member of ExportFilter

The **Reset** method restores the default settings for a filter.

VBA example

The following VBA example creates a document and an ellipse. When exporting the document to JPEG, the dialog box for the filter is displayed (if one exists). If the user clicks **Cancel**, the default settings for the filter are restored.

```
Sub Test()
 Dim ex As ExportFilter
 Dim d As Document
 Set d = CreateDocument
 d.ActiveLayer.CreateEllipse2 4, 4, 1
 Set ex = d.ExportEx("c:\test.jpg", cdrJPEG)
 With ex
  If .HasDialog Then
   If Not .ShowDialog Then .Reset
   .Finish
  End If
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ExportFilter.ShowDialog

Function **ShowDialog([***hWnd As Long***])** As Boolean

Description

Member of ExportFilter

The **ShowDialog** method displays the dialog box for an export filter.

Parameter	Description
hWnd	This parameter is optional, and its default value is **0**.

VBA example

The following VBA example creates a document and an ellipse. When exporting the document to JPEG, the dialog box for the filter is displayed (if one exists), and the export process is completed.

```
Sub Test()
 Dim ex As ExportFilter
 Dim d As Document
 Set d = CreateDocument
 d.ActiveLayer.CreateEllipse2 4, 4, 1
 Set ex = d.ExportEx("c:\test.jpg", cdrJPEG)
 With ex
  If .HasDialog Then
   .ShowDialog
  End If
  .Finish
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ExtrudeVanishingPoint

Properties Methods

Description

The **ExtrudeVanishingPoint** class represents the vanishing point used by an extrusion.

Copyright 2014 Corel Corporation. All rights reserved.

ExtrudeVanishingPoint.Application

Property **Application** As Application

Description

Member of ExtrudeVanishingPoint

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

ExtrudeVanishingPoint.Effects

Property **Effects** As Effects

Description

Member of ExtrudeVanishingPoint

The **Effects** property returns a collection of extrusion-effect objects containing references to extrusions with the same vanishing point.

The **Effects** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ExtrudeVanishingPoint.Parent

Property **Parent** As EffectExtrude

Description

Member of ExtrudeVanishingPoint

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

ExtrudeVanishingPoint.PositionX

Property **PositionX** As Double

Description

Member of ExtrudeVanishingPoint

The **PositionX** property returns or specifies the x-coordinate of a vanishing point for an extrusion.

VBA example

The following VBA example locks, to the page, all vanishing points for all extrusions on the page, and it moves the vanishing points to the lower-left corner of the page.

```
Sub Test1()
 Dim s As Shape, eff As Effect, zip As EffectZipperDistortion
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrExtrude Then
    With eff.Extrude.VanishingPoint
     .Type = cdrVPLockedToPage
     .PositionX = 0
     .PositionY = 0
     End With
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ExtrudeVanishingPoint.PositionY

Property **PositionY** As Double

Description

Member of ExtrudeVanishingPoint

The **PositionY** property returns or specifies the y-coordinate of a vanishing point for an extrusion.

VBA example

The following VBA example locks, to the page, all vanishing points for all extrusions on the page, and it moves the vanishing points to the lower-left corner of the page.

```
Sub Test1()
 Dim s As Shape, eff As Effect, zip As EffectZipperDistortion
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrExtrude Then
    With eff.Extrude.VanishingPoint
     .Type = cdrVPLockedToPage
     .PositionX = 0
     .PositionY = 0
     End With
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ExtrudeVanishingPoint.Share

Function **Share(**Source As EffectExtrude**)** As Boolean

Description

Member of ExtrudeVanishingPoint

The **Share** property shares a vanishing point with another extrusion.

You can copy a vanishing point to another object or have multiple vector extrusions share a vanishing point.

Parameter	Description
Source	Specifies the extrusion with the vanishing point to be shared

VBA example

The following VBA example creates an extruded text object and a circle. It then shares the vanishing point between the two.

```
Sub Test()
 Dim sText As Shape, eff1 As Effect, eff2 As Effect
 Dim sEllipse As Shape
 Set sText = ActiveLayer.CreateArtisticText(1.5, 5, "3D Text")
 sText.Text.FontProperties.Size = 150
 sText.Fill.UniformColor.RGBAssign 0, 0, 255
 Set eff1 = sText.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToPage, 7, 7)
 Set sEllipse = ActiveLayer.CreateEllipse2(4, 9, 2)
 sEllipse.Fill.UniformColor.RGBAssign 255, 255, 0
 Set eff2 = sEllipse.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToPage, 5, 10)
 eff2.Extrude.VanishingPoint.Share eff1.Extrude
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ExtrudeVanishingPoint.Type

Property **Type** As cdrExtrudeVPType

Description

Member of ExtrudeVanishingPoint

The **Type** property returns or set the type of vanishing point for an extrusion.

This property returns a value of cdrExtrudeVPType.

VBA example

The following VBA example locks, to the page, all vanishing points for all extrusions on the page, and it moves the vanishing points to the lower-left corner of the page.

```
Sub Test1()
 Dim s As Shape, eff As Effect, zip As EffectZipperDistortion
 For Each s In ActivePage.Shapes
  For Each eff In s.Effects
   If eff.Type = cdrExtrude Then
    With eff.Extrude.VanishingPoint
     .Type = cdrVPLockedToPage
     .PositionX = 0
     .PositionY = 0
     End With
    Exit For
   End If
  Next eff
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Fill

Properties Methods

Description

The **Fill** class represents the fill of a shape.

Copyright 2014 Corel Corporation. All rights reserved.

Fill.ApplyCustomHatchFill

Function **ApplyCustomHatchFill(***Angle As Double***,** *Spacing As Double***, [***Shift As Double***], [***OriginX As Double***], [***OriginY As Double***], [**Width As Double = -1**], [**Color As Color**], [**Style As OutlineStyle**], [**DashDotLength As Double = -1**], [***PenWidth As Double***], [**BackColor As Color**], [**TransformWithShape As Boolean = False**], [**ScaleLinesWithShape As Boolean = False**], [**UseWorldCoordinates As Boolean = False**], [***FillScale As Double***], [***LineScale As Double***], [***FillAngle As Double***], [***FillSkew As Double***]) As HatchFill

Description

Member of Fill

The **ApplyCustomHatchFill** method applies a custom hatch fill.

Parameter	Description
Angle	Specifies the rotation angle of the lines in the hatch-fill pattern
Spacing	Specifies the line spacing in the hatch-fill pattern
Shift	Specifies an additional relative horizontal shift of the lines in the hatch-fill pattern. This parameter is optional, and its default value is **0**.
OriginX	Specifies the horizontal offset of the start of the first line in the hatch-fill pattern. This parameter is optional, and its default value is **0**.
OriginY	Specifies the vertical offset of the start of the first line in the hatch-fill pattern. This parameter is optional, and its default value is **0**.
Width	Specifies the width at which to apply the hatch fill. This parameter is optional, and its default value is **-1**.
Color	Specifies the color for the hatch fill. This parameter is optional, and its default value is **Nothing**.
Style	Specifies the outline style for the hatch fill. This parameter is optional, and its default value is **Nothing**.
DashDotLength	Specifies the dash-dot length of the lines in the hatch fill. This parameter is optional, and its default value is **-1**.
PenWidth	Specifies the pen width of the lines in the hatch fill. This parameter is optional, and its default value is **0**.
BackColor	Specifies a background color for the hatch fill. This parameter is optional, and its default value is **Nothing**.
TransformWithShape	Specifies whether to transform the hatch fill with the shape to which the hatch fill is applied. This parameter is optional, and its default value is **False**.
ScaleLinesWithShape	Specifies whether to scale the hatch-fill lines with the shape to which the hatch fill is applied. This parameter is optional, and its default value is **False**.
UseWorldCoordinates	Specifies whether local or world coordinates are used to align the hatch fills that are applied to different objects. This parameter is optional, and its default value is **False**.
FillScale	Specifies the average scale factor for the hatch fill. This parameter is optional, and its default value is **0**.
LineScale	Specifies the average line-thickness scale factor for the hatch fill. This parameter is optional, and its default value is **0**.
FillAngle	Specifies the rotation angle for the hatch fill. This parameter is optional, and its default value is **0**.
FillSkew	Specifies the skew angle for the hatch fill. This parameter is optional, and its default value is **0**.

Copyright 2014 Corel Corporation. All rights reserved.

Fill.ApplyFountainFill

Function **ApplyFountainFill(**[StartColor As Color]**,** [EndColor As Color]**,** [Type As cdrFountainFillType = cdrLinearFountainFill]**,** [*Angle As Double*]**,** [*Steps As Long*]**,** [*EdgePad As Long*]**,** [MidPoint As Long = 50]**,** [BlendType As cdrFountainFillBlendType = cdrDirectFountainFillBlend]**,** [*CenterOffsetX As Double*]**,** [*CenterOffsetY As Double*]**)** As FountainFill

Description

Member of Fill

The **ApplyFountainFill** method applies a fountain fill to an object.

Parameter	Description
StartColor	Specifies the starting color of the fountain fill. This parameter is optional, and its default value is **Nothing**.
EndColor	Specifies the ending color of the fountain fill effect. This parameter is optional, and its default value is **Nothing**.
Type	Specifies the type of the fountain fill through a value of cdrFountainFillType. This parameter is optional, and its default value is cdrLinearFountainFill (**1**).
Angle	Specifies the angle in linear, conical, or square fountain fills. Positive values rotate the fill counterclockwise; negative values rotate it clockwise. This parameter is optional, and its default value is **0**.
Steps	Specifies the number of steps in the fountain fill. This parameter is optional, and its default value is **0**.
EdgePad	Specifies the length of the edge pad of linear, radial, and square fountain fills. This parameter is optional, and its default value is **0**.
MidPoint	Specifies the point at which two colors in a fountain fill converge. This value is expressed as a percentage. This parameter is optional, and its default value is **50**.
BlendType	Specifies the type of fountain-fill blend. This parameter is optional, and its default value is cdrDirectFountainFillBlend (**0**).
CenterOffsetX	Specifies a horizontal offset for the center of the fountain fill. This parameter is optional, and its default value is **0**.
CenterOffsetY	Specifies a vertical offset for the center of the fountain fill. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example creates a rectangle and applies a fountain fill that blends from red to yellow:

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 5, 5)
 s.Fill.ApplyFountainFill CreateRGBColor(255, 0, 0), CreateRGBColor(255, 255, 0)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Fill.ApplyHatchFill

Function **ApplyHatchFill(***LibraryName As String***,** *HatchNameOrIndex As Variant***, [**BackColor As Color**], [**TransformWithShape As Boolean = False**], [**ScaleLinesWithShape As Boolean = False**], [**UseWorldCoordinates As Boolean = False**], [***FillScale As Double***], [***LineScale As Double***], [***FillAngle As Double***], [***FillSkew As Double***])** As HatchFill

Description

Member of Fill

The **ApplyHatchFill** method applies a preset hatch fill from a library.

Parameter	Description
LibraryName	Specifies the library name for the hatch-fill pattern
HatchNameOrIndex	Specifies the name or index number of the hatch-fill pattern
BackColor	Specifies the background color for the hatch fill. This parameter is optional, and its default value is **Nothing**.
TransformWithShape	Specifies whether to transform the hatch fill with the shape to which the hatch fill is applied. This parameter is optional, and its default value is **False**.
ScaleLinesWithShape	Specifies whether to scale the hatch-fill lines with the shape to which the hatch fill is applied. This parameter is optional, and its default value is **False**.
UseWorldCoordinates	Specifies whether local or world coordinates are used to align the hatch fills that are applied to different objects. This parameter is optional, and its default value is **False**.
FillScale	Specifies the average scale factor for the hatch fill. This parameter is optional, and its default value is **0**.
LineScale	Specifies the average line-thickness scale factor for the hatch fill. This parameter is optional, and its default value is **0**.
FillAngle	Specifies the rotation angle for the hatch fill. This parameter is optional, and its default value is **0**.
FillSkew	Specifies the skew angle for the hatch fill. This parameter is optional, and its default value is **0**.

Copyright 2014 Corel Corporation. All rights reserved.

Fill.ApplyNoFill

Sub **ApplyNoFill()**

Description

Member of Fill

The **ApplyNoFill** method removes the fill from an object, leaving it unfilled.

VBA example

The following VBA example removes the fill from the currently selected objects.

```
Sub Test()
 ActiveSelection.Fill.ApplyNoFill
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Fill.ApplyPatternFill

Function **ApplyPatternFill(**Type As cdrPatternFillType**, [***FileName As String***],** [PatternCanvasIndex As Long = 1**], [**FrontColor As Color**], [**EndColor As Color**], [**TransformWithShape As Boolean = False**])** As PatternFill

Description

Member of Fill

The **ApplyPatternFill** method applies a pattern fill to a shape. There are three types of pattern fills: two-color, full-color vector, and bitmapped.

Parameter	Description
Type	Specifies the type of the pattern fill and returns cdrPatternFillType
FileName	Specifies the full path and filename of the graphic that is imported as a pattern fill. This parameter is optional.
PatternCanvasIndex	Specifies the pattern canvas by its index number. This parameter is optional, and its default value is **1**.
FrontColor	Specifies the foreground color for the pattern fill. This parameter is optional, and its default value is **Nothing**.
EndColor	Specifies the background color for the pattern fill. This parameter is optional, and its default value is **Nothing**.
TransformWithShape	Specifies whether to transform the pattern fill with the shape. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example creates a rectangle and applies a bitmapped pattern fill to it.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 5, 5)
 s.Fill.ApplyPatternFill cdrBitmapPattern, Application.Path + "Custom Data\Canvas\breadc.pcx"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Fill.ApplyPostscriptFill

Function **ApplyPostscriptFill(***IndexOrName As Variant***)** As PostScriptFill

Description

Member of Fill

The **ApplyPostscriptFill** method applies a PostScript fill to a shape.

Parameter	Description
IndexOrName	Specifies the PostScript fill by its name (for example, **Bubbles**) or by its number in the list of available PostScript fills

VBA example

The following VBA example creates a rectangle and applies the **Bubbles** PostScript fill to it.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 5, 5)
 s.Fill.ApplyPostscriptFill "Bubbles"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Fill.ApplyTextureFill

Function **ApplyTextureFill(***TextureName As String*, **[***LibraryName As String***])** As TextureFill

Description

Member of Fill

The **ApplyTextureFill** method applies a texture fill to a shape.

Parameter	Description
TextureName	Specifies the name of a texture-fill pattern
LibraryName	Specifies the name of the texture library. If this value is omitted, the main styles are used. This parameter is optional.

VBA example

The following VBA example applies the **Blend Edges** texture from the **Styles** library.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 5, 5)
 s.Fill.ApplyTextureFill "Blend Edges"
End Sub
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 5, 5)
 s.Fill.ApplyTextureFill "Alien Eyes", "Samples 9"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Fill.ApplyUniformFill

Sub **ApplyUniformFill(**Color As Color**)**

Description

Member of Fill

The **ApplyUniformFill** method applies a uniform fill to a shape by using a Color object.

- Alternatively, you can assign a uniform fill to a shape by modifying the Fill.UniformColor property.

Parameter	Description
Color	Specifies the fill color by referencing an existing color component in a palette or a **Create...Color** method (for example, Application.CreateCMYKColor or Application.CreateRGBColor)

VBA example

The following VBA examples creates swatches for each color in the default color palette that is open. A rectangle is created for each color in the palette and is then filled with the color. New pages are added if the swatches cannot fit on a single page.

```
Sub Test()
 Dim d As Document
 Dim p As Page
 Dim c As Color
 Dim s As Shape
 Const sx As Double = 0.5
 Const sy As Double = 0.5
 Dim x As Double, y As Double
 Dim MaxX As Long, nx As Long
 Dim MaxY As Long, ny As Long
 x = 0
 y = 0
 nx = 0
 Set d = CreateDocument
 d.Unit = cdrInch
 Set p = d.ActivePage
 MaxX = CLng(p.SizeWidth / sx)
 MaxY = CLng(p.SizeHeight / sy)
 For Each c In ActivePalette.Colors
  Set s = p.ActiveLayer.CreateRectangle(x, y, x + sx, y + sy)
  s.Fill.ApplyUniformFill c
  x = x + sx
  nx = nx + 1
  If nx = MaxX Then
   nx = 0
   x = 0
   y = y + sy
   ny = ny + 1
   If ny = MaxY Then
    ny = 0
    y = 0
    Set p = d.AddPages(1)
   End If
  End If
 Next c
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Fill.CompareWith

Function **CompareWith(**Fill As Fill**)** As Boolean

Description

Member of Fill

The **CompareWith** method compares the properties of two fills.

Parameter	Description
Fill	Specifies the fill

Copyright 2014 Corel Corporation. All rights reserved.

Fill.CopyAssign

Sub **CopyAssign(**SourceFill As Fill**)**

Description

Member of Fill

The **CopyAssign** method copies the properties of a given fill.

Parameter	Description
SourceFill	Specifies the fill

Copyright 2014 Corel Corporation. All rights reserved.

Fill.Fountain

Property **Fountain** As FountainFill

Description

Member of Fill

The **Fountain** property returns a FountainFill object that represents the settings for a fountain fill.

VBA example

The following VBA example unlocks the fountain steps for all shapes on a page.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Fill.Type = cdrFountainFill Then
   If s.Fill.Fountain.Steps <> 0 Then
    s.Fill.Fountain.Steps = 0
   End If
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Fill.GetCopy

Function **GetCopy()** As Fill

Description

Member of Fill

The **GetCopy** method returns an unattached copy of the fill object.

Copyright 2014 Corel Corporation. All rights reserved.

Fill.Hatch

Property **Hatch** As HatchFill

Description

Member of Fill

The **Hatch** property returns or specifies hatch-fill properties.

Copyright 2014 Corel Corporation. All rights reserved.

Fill.Pattern

Property **Pattern** As PatternFill

Description

Member of Fill

The **Pattern** property returns a PatternFill object that represents the settings for a pattern fill.

VBA example

The following VBA example creates a rectangle and applies a skewed two-color pattern fill to it.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 s.Fill.ApplyPatternFill cdrTwoColorPattern, , 4, CreateRGBColor(255, 0, 0), CreateRGBColor(255, 255, 0)
 s.Fill.Pattern.SkewAngle = 20
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Fill.PostScript

Property **PostScript** As PostScriptFill

Description

Member of Fill

The **PostScript** property returns a PostScriptFill object that represents the settings for a PostScript fill.

VBA example

The following VBA example creates a rectangle and applies a PostScript fill to it. The bar-width parameter is then changed to **40**.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 s.Fill.ApplyPostscriptFill "Bars"
 s.Fill.PostScript.Properties(1) = 40
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Fill.PSScreen

Property **PSScreen** As PSScreenOptions

Description

Member of Fill

The **PSScreen** property specifies the halftone screen options for a PostScript fill.

The **PSScreen** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Fill.Texture

Property **Texture** As TextureFill

Description

Member of Fill

The **Texture** property returns a TextureFill object that represents the settings for a texture fill.

VBA example

The following VBA example creates a rectangle and applies a texture fill to it. The background color of the fill is then changed to red.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 s.Fill.ApplyTextureFill "Patches 2C"
 s.Fill.Texture.Properties("Background:").Value = CreateRGBColor(255, 0, 0)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Fill.Type

Property **Type** As cdrFillType

Description

Member of Fill

The **Type** property returns the type of the fill. Depending on the current type of the fill, one of the following fill sub-objects is available: Fill.Fountain, Fill.Hatch, Fill.Pattern, Fill.PostScript, Fill.Texture, Fill.UniformColor.

- To change the type of fill, you should use the corresponding **Apply...** method of the Fill class. The exception is applying a uniform fill: assigning a color to the Fill.UniformColor property automatically sets the fill type to cdrUniformFill.

The **Type** property returns a read-only value.

VBA example

The following VBA example lists the number of shapes with different fills in the document.

```
Sub Test()
 Dim d As Document
 Dim p As Page
 Dim s As Shape
 Dim msg As String
 Dim num As Long
 Dim NoFill As Long, Uniform As Long
 Dim Fountain As Long, Pattern As Long
 Dim Texture As Long, PostScript As Long
 NoFill = 0
 Uniform = 0
 Fountain = 0
 Pattern = 0
 Texture = 0
 PostScript = 0
 num = 0
 Set d = ActiveDocument
 For Each p In d.Pages
  For Each s In p.Shapes
   Select Case s.Fill.Type
    Case cdrNoFill
     NoFill = NoFill + 1
    Case cdrUniformFill
     Uniform = Uniform + 1
    Case cdrFountainFill
     Fountain = Fountain + 1
    Case cdrPatternFill
     Pattern = Pattern + 1
    Case cdrTextureFill
     Texture = Texture + 1
    Case cdrPostscriptFill
     PostScript = PostScript + 1
   End Select
   num = num + 1
  Next s
 Next p
 msg = "The document contains " & num & " shapes with:" & vbCr
 msg = msg & "No fill: " & NoFill & vbCr
 msg = msg & "Uniform fill: " & Uniform & vbCr
 msg = msg & "Fountain fill: " & Fountain & vbCr
 msg = msg & "Pattern fill: " & Pattern & vbCr
 msg = msg & "Texture fill: " & Texture & vbCr
 msg = msg & "PostScript fill: " & PostScript
 MsgBox msg, vbInformation, "Statistics"
End Sub
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Fill.Type = cdrPostscriptFill Then
   s.Fill.PostScript.Select "Bricks"
  End If
 Next s
End Sub
Sub Test()
 Dim s As Shape
 Dim cc As FountainColor
 For Each s In ActivePage.Shapes
  Select Case s.Fill.Type
   Case cdrUniformFill
    s.Fill.UniformColor.ConvertToGray
   Case cdrFountainFill
    s.Fill.Fountain.StartColor.ConvertToGray
    s.Fill.Fountain.EndColor.ConvertToGray
    For Each cc In s.Fill.Fountain.Colors
     cc.Color.ConvertToGray
    Next cc
  End Select
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Fill.UniformColor

Property **UniformColor** As Color

Description

Member of Fill

The **UniformColor** property returns a Color object that represents the uniform fill of a shape.

- Assigning a color to **UniformColor** property automatically sets the fill type to cdrUniformFill.

VBA example

The following VBA example creates a yellow rectangle.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 s.Fill.UniformColor.RGBAssign 255, 255, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Fill.UserAssign

Function **UserAssign([**FillType As cdrFillType = cdrNoFill**], [**PatternType As cdrPatternFillType = cdrTwoColorPattern**], [***ParentWindowHandle As Long***])** As Boolean

Description

Member of Fill

The **UserAssign** method shows the corresponding **Properties** dialog box for a fill.

Parameter	Description
FillType	Specifies the fill type. This parameter is optional, and its default value is cdrNoFill (**0**).
PatternType	Specifies the pattern type. This parameter is optional, and its default value is cdrTwoColorPattern (**0**).
ParentWindowHandle	Specifies the handle of the parent window. This parameter is optional, and its default value is **0**.

Copyright 2014 Corel Corporation. All rights reserved.

FillMetadata

Properties

Description

The **FillMetadata** class represents the metadata associated with a fill.

Copyright 2014 Corel Corporation. All rights reserved.

FillMetadata.Copyright

Property **Copyright** As LocalizableString

Description

Member of FillMetadata

The **Copyright** property returns the copyright of the fill. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FillMetadata.CreationDate

Property **CreationDate** As Date

Description

Member of FillMetadata

The **CreationDate** property returns the time and the date when the fill was created. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FillMetadata.CreatorTool

Property **CreatorTool** As String

Description

Member of FillMetadata

The **CreatorTool** property returns the name of the application in which the fill was created. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FillMetadata.DerivedFrom

Property **DerivedFrom** As String()

Description

Member of FillMetadata

The **DerivedFrom** property returns the list of files on which the fill is based on. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FillMetadata.Description

Property **Description** As LocalizableString

Description

Member of FillMetadata

The **Description** property returns the description of the fill. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FillMetadata.DocumentID

Property **DocumentID** As String

Description

Member of FillMetadata

The **DocumentID** property returns the unique ID of the fill file and all its parents and descendants. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FillMetadata.InstanceID

Property **InstanceID** As String

Description

Member of FillMetadata

The **InstanceID** property returns the unique ID of this specific fill instance. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FillMetadata.Keywords

Property **Keywords** As LocalizableString

Description

Member of FillMetadata

The **Keywords** property lists the keywords associated with the fill. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FillMetadata.ModificationDate

Property **ModificationDate** As Date

Description

Member of FillMetadata

The **ModificationDate** property returns the date and time when the fill file was last modified. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FillMetadata.Subject

Property **Subject** As LocalizableString

Description

Member of FillMetadata

The **Subject** property specifies the subject of the fill. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FillMetadata.Title

Property **Title** As LocalizableString

Description

Member of FillMetadata

The **Title** property specifies the title of the fill. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FontList

Properties

Description

The **FontList** class represents the list of all installed fonts.

Copyright 2014 Corel Corporation. All rights reserved.

FontList.Application

Property **Application** As Object

Description

Member of FontList

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

FontList.Count

Property **Count** As Long

Description

Member of FontList

The **Count** property returns the total number of installed fonts.

The **Count** property returns a read-only value.

VBA example

The following VBA example displays the number of fonts currently installed.

```
Sub Test()
 MsgBox "Total number of fonts currently installed: " & FontList.Count
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FontList.Item

Property **Item(***Index As Long***)** As String

Description

Member of FontList

The **Item** property returns the name of the specified font.

Item is the default property of the FontList class, and its reference can be omitted when you are accessing items in a **FontList** collection. For example, **FontList.Item(2)** is the same as **FontList(2)** — they both reference the second font object in the collection.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the font by its index number

VBA example

The following VBA example checks whether the Arial font is installed.

```
Sub Test()
 If Not FontInstalled("Arial") Then
  MsgBox "Font 'Arial' is not installed on your system"
 End If
End Sub
'---- The following function determines if the given font is installed
Private Function FontInstalled(Name As String) As Boolean
 Dim b As Boolean, n As Long
 b = False
 For n = 1 To FontList.Count
  If UCase$(FontList(n)) = UCase$(Name) Then
   b = True
   Exit For
  End If
 Next n
 FontInstalled = b
End Function
```

Copyright 2014 Corel Corporation. All rights reserved.

FontList.Parent

Property **Parent** As Object

Description

Member of FontList

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

FountainColor

Properties Methods

Description

The **FountainColor** class represents a single color point in a fountain fill.

Copyright 2014 Corel Corporation. All rights reserved.

FountainColor.BlendType

Property **BlendType** As cdrFountainFillBlendType

Description

Member of FountainColor

The **BlendType** property returns or sets the blend type of a fountain fill.

Copyright 2014 Corel Corporation. All rights reserved.

FountainColor.Color

Property **Color** As Color

Description

Member of FountainColor

The **Color** property returns a Color object that represents color information about the color point in a fountain fill.

For a fountain transparency, the color is always grayscale.

VBA example

The following VBA example converts all colors in the fountain fill to grayscale.

```
Sub Test()
 Dim cl As FountainColor
 If ActiveShape.Fill.Type <> cdrFountainFill Then
  MsgBox "The selected shape must have a fountain fill."
  Exit Sub
 End If
 For Each cl In ActiveShape.Fill.Fountain.Colors
  cl.Color.ConvertToGray
 Next cl
 ActiveShape.Fill.Fountain.StartColor.ConvertToGray
 ActiveShape.Fill.Fountain.EndColor.ConvertToGray
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainColor.Delete

Sub **Delete()**

Description

Member of FountainColor

The **Delete** method removes a color point from a fountain fill.

- You cannot delete starting and ending color points.

VBA example

The following VBA example removes any intermediate color points in a fountain fill, leaving only the starting and ending points.

```
Sub Test()
 Dim cl As FountainColor
 If ActiveShape.Fill.Type <> cdrFountainFill Then
  MsgBox "The selected shape must have a fountain fill."
  Exit Sub
 End If
 For Each cl In ActiveShape.Fill.Fountain.Colors
  If cl.Position > 0 And cl.Position < 100 Then cl.Delete
 Next cl
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainColor.MidPoint

Property **MidPoint** As Long

Description

Member of FountainColor

The **MidPoint** property returns or specifies the midpoint of a color transition.

Copyright 2014 Corel Corporation. All rights reserved.

FountainColor.Move

Sub **Move(***NewPosition As Long***)**

Description

Member of FountainColor

The **Move** method moves a color point to a specified position. If there is a color point at the specified position, it is replaced by the moved color point.

Parameter	Description
NewPosition	Specifies the new location of a color point. Valid positions range from **1** to **99**.

VBA example

The following VBA example redistributes color points evenly within the selected fountain fill.

```
Sub Test()
 Dim n As Long, i As Long
 If ActiveShape.Fill.Type <> cdrFountainFill Then
  MsgBox "The selected shape must have a fountain fill."
  Exit Sub
 End If
 n = ActiveShape.Fill.Fountain.Colors.Count
 If n > 0 Then
  For i = 1 To n
   ActiveShape.Fill.Fountain.Colors(i).Move i * 100 / (n + 1)
  Next i
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainColor.Opacity

Property **Opacity** As Byte

Description

Member of FountainColor

The **Opacity** property returns or specifies the opacity value of a color.

Copyright 2014 Corel Corporation. All rights reserved.

FountainColor.Position

Property **Position** As Long

Description

Member of FountainColor

The **Position** property returns the position of a color point in a fountain fill. Valid positions range from **1** to **99**.

The **Position** property returns a read-only value.

VBA example

The following VBA example deletes any color point with a position located at a distance greater than **50**%.

```
Sub Test()
 Dim cl As FountainColor
 If ActiveShape.Fill.Type <> cdrFountainFill Then
  MsgBox "The selected shape must have a fountain fill."
  Exit Sub
 End If
 For Each cl In ActiveShape.Fill.Fountain.Colors
  If cl.Position < 100 And cl.Position > 50 Then cl.Delete
 Next cl
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainColors

Properties Methods

Description

The **FountainColors** class represents a collection of color points (or FountainColor objects) in a fountain fill or a fountain transparency.

Copyright 2014 Corel Corporation. All rights reserved.

FountainColors.Add

Sub **Add(**Color As Color**,** *Position As Long***)**

Description

Member of FountainColors

The **Add** method places a new color point at the specified position. If there is a color point at the specified position, the new color point replaces the existing color point. Valid positions range from **1** to **99**.

Parameter	Description
Color	Specifies the color of the new color point. You can use an existing color name or a **Create...Color** method (for example, **CreateCMYKColor**, **CreateRGBColor**).
Position	Specifies the location of the new color point. Valid positions range from **1** to **99** and are expressed as a percentage from the starting position.

VBA example

The following VBA example creates a rectangle and applies a linear fountain fill to it. It then adds two color points to the fill: yellow at **30**%, and cyan at **60**%.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(1, 1, 4, 3)
 With s.Fill.ApplyFountainFill(CreateRGBColor(0, 0, 0), CreateRGBColor(255, 0, 0))
  .Colors.Add CreateRGBColor(255, 255, 0), 30
  .Colors.Add CreateRGBColor(0, 255, 255), 60
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainColors.AddGrayLevel

Sub **AddGrayLevel(***GrayLevel As Long*, *Position As Long***)**

Description

Member of FountainColors

The **AddGrayLevel** method adds a new grayscale color point at a specified position. If there is a color point at the specified position, the new color point replaces the existing color point. Valid positions range from **1** to **99**.

Parameter	Description
GrayLevel	Specifies the transparency level for the fountain transparency. The **Index** value can range from **0** to **Count+1**, where **0** is the starting color point and **Count+1** is the ending color point in the fountain or transparency.
Position	Specifies the location of gray level in the **FountainColors** collection. If a color is given the position of **2**, it is actually the third color point in the fountain effect because the starting point holds an index of **0** and is not included as a collection point. Valid positions range from **1** to **99**.

VBA example

The following VBA example creates an ellipse containing a fountain fill with a fountain transparency containing five interleaving transparency points:

```
Sub Test()
 Dim s As Shape
 Dim ff As FountainFill
 Dim n As Long
 Set s = ActiveLayer.CreateEllipse2(4, 5.5, 4)
 s.Fill.ApplyFountainFill CreateRGBColor(255, 0, 0), CreateRGBColor(255, 255, 0), , 90
 Set ff = s.Transparency.ApplyFountainTransparency(100, 100)
 For n = 1 To 5
  ff.Colors.AddGrayLevel (n Mod 2) * 255, n * 100 / 6
 Next n
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainColors.Count

Property **Count** As Long

Description

Member of FountainColors

The **Count** property returns the number of color points in the **FountainColors** collection.

- The starting and ending color points are not included in the count of color points in the collection. Only the color points between the start and end points are included in the **Count** property.

The **Count** property returns a read-only value.

VBA example

The following VBA example displays the number of color points in the fountain fill of the selected object. The selected object must have fountain fill before executing this code.

```
Sub Test()
 MsgBox "Fountain fill contains " & ActiveShape.Fill.Fountain.Colors.Count & _
  " intermediate color points."
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainColors.First

Property **First** As FountainColor

Description

Member of FountainColors

The **First** property returns the starting color of the fountain fill.

The **First** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FountainColors.GrayLevel

Property **GrayLevel(***Index As Long***)** As Long

Description

Member of FountainColors

The **GrayLevel** property returns or specifies the gray level of the specified color point. It is also useful for specifying the transparency level for a fountain transparency.

The index can range from **0** to **(Count+1)**, where **GrayLevel(0)** represents the starting point and **GrayLevel(Count+1)** represents the ending color point of the fountain fill or transparency.

Parameter	Description
Index	Specifies the color point by its index number

VBA example

The following VBA example displays the number of points in the fountain transparency of the active shape. The points that are counted must have a transparency level of at least **50**%.

```
Sub Test()
 Dim ff As FountainFill
 Dim t As Transparency
 Dim n As Long, i As Long
 Set t = ActiveShape.Transparency
 If t.Type = cdrFountainTransparency Then
  Set ff = t.Fountain
  n = 0
  For i = 1 To ff.Colors.Count
   If ff.Colors.GrayLevel(i) < 128 Then n = n + 1
  Next i
  MsgBox "The current shape has " & n & " transparency points with 50% or greater transparency level."
 Else
  MsgBox "The shape doesn't have a fountain transparency."
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainColors.Item

Property **Item(***Index As Long***)** As FountainColor

Description

Member of FountainColors

The **Item** property returns a FountainColor object for the specified color point.

The index can range from **0** to **(Count+1)**, where **Item(0)** represents the starting point and **Item(Count+1)** represents the ending color point of the fountain fill or transparency.

Item is the default property of the FountainColors class, and its reference can be omitted when you are accessing items in a **FountainColors** collection. For example, **Fountain.Colors.Item(2)** is the same as **Fountain.Colors(2)** — they both reference the second color in the collection.

Parameter	Description
Index	Specifies the color point by its index number

VBA example

The following VBA example converts all colors in the fountain fill to grayscale.

```
Sub Test()
 Dim ff As FountainFill
 Dim i As Long
 Set ff = ActiveShape.Fill.Fountain
 For i = 0 To ff.Colors.Count + 1
  ff.Colors(i).Color.ConvertToGray
 Next i
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainColors.Last

Property **Last** As FountainColor

Description

Member of FountainColors

The **Last** property returns the ending color of the fountain fill.

The **Last** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill

Properties Methods

Description

The **FountainFill** class represents a fountain fill or a fountain transparency.

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.Angle

Property **Angle** As Double

Description

Member of FountainFill

The **Angle** property returns the angle of a fountain fill. Positive values rotate the fill counterclockwise, while negative values rotate it clockwise.

You can use the SetAngle method to change the angle of fountain fill.

The **Angle** property returns a read-only value.

VBA example

The following VBA example displays the angle of the fountain fill of the selected shape.

```
Sub Test()
 MsgBox ActiveShape.Fill.Fountain.Angle
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.Anisotropic

Property **Anisotropic** As Boolean

Description

Member of FountainFill

The **Anisotropic** property returns or specifies a fill that can skewed and rotated freely.

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.BlendAcceleration

Property **BlendAcceleration** As Double

Description

Member of FountainFill

The **BlendAcceleration** property returns or specifies how quickly a fountain fill blends from one color to another.

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.CenterOffsetX

Property **CenterOffsetX** As Double

Description

Member of FountainFill

The **CenterOffsetX** property returns or specifies the horizontal fill-center offset relative to the center of object, in percent of object width.

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.CenterOffsetY

Property **CenterOffsetY** As Double

Description

Member of FountainFill

The **CenterOffsetY** property returns or specifies the vertical fill-center offset relative to the center of object, in percent of object height.

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.Colors

Property **Colors** As FountainColors

Description

Member of FountainFill

The **Colors** property returns the FountainColors collection, which represents all color points of a fountain fill.

The element with an index value of **0** represents the starting color point of the fountain fill. The last element (**Count+1**) is the last color point of the fill.

VBA example

The following VBA example converts all colors of fountain fills in shapes to grayscale.

```
Sub Test()
 Dim s As Shape
 Dim ff As FountainFill
 Dim i As Long
 For Each s In ActivePage.Shapes
  If s.Fill.Type = cdrFountainFill Then
   Set ff = s.Fill.Fountain
   For i = 0 To ff.Colors.Count + 1
    ff.Colors(i).Color.ConvertToGray
   Next i
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.End2X

Property **End2X** As Double

Description

Member of FountainFill

The **End2X** property returns or specifies the second horizontal ending-coordinate of a fountain-fill vector.

The **End2X** property is measured in document units.

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.End2Y

Property **End2Y** As Double

Description

Member of FountainFill

The **End2Y** property returns or specifies the second vertical ending-coordinate of a fountain-fill vector.

The **EndY** property is measured in document units.

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.EndColor

Property **EndColor** As Color

Description

Member of FountainFill

The **EndColor** property returns or specifies the ending color a fountain fill.

You can also access the ending color point of the fill by using the **.Colors(.Colors.Count+1)** property of the FountainColors collection.

VBA example

The following VBA example displays the names of the colors of the starting and ending color points of the fountain fill.

```
Sub Test()
 Dim ff As FountainFill
 If ActiveShape.Fill.Type = cdrFountainFill Then
  Set ff = ActiveShape.Fill.Fountain
  MsgBox "The fountain fill is from " & ff.StartColor.Name & _
    " to " & ff.EndColor.Name
 Else
  MsgBox "The selected shape doesn't have a fountain fill"
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.EndX

Property **EndX** As Double

Description

Member of FountainFill

The **EndX** property returns or specifies the horizontal ending-coordinate of a fountain-fill vector. For radial, rectangular, and conical fills, the starting point is the center point of the fill.

The **EndX** property is measured in document units.

VBA example

The following VBA example draws circles around the starting and ending points of the fountain-fill vector.

```
Sub Test()
 With ActiveShape.Fill.Fountain
  ActiveLayer.CreateEllipse2 .StartX, .StartY, 0.2
  ActiveLayer.CreateEllipse2 .EndX, .EndY, 0.2
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.EndY

Property **EndY** As Double

Description

Member of FountainFill

The **EndY** property returns or specifies the vertical ending-coordinate of a fountain-fill vector. For radial, rectangular, and conical fills, the starting point is the center point of the fill.

The **EndY** property is measured in document units.

VBA example

The following VBA example draws circles around the starting and ending points of the fountain-fill vector.

```
Sub Test()
 With ActiveShape.Fill.Fountain
  ActiveLayer.CreateEllipse2 .StartX, .StartY, 0.2
  ActiveLayer.CreateEllipse2 .EndX, .EndY, 0.2
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.GetTransformations

Sub **GetTransformations(*d11*** As Double, **d12** As Double, **d21** As Double, **d22** *As Double*)

Description

Member of FountainFill

The **GetTransformations** method returns the transformations applied to the fountain fill.

Parameter	Description
d11	Specifies the horizontal stretch factor multiplied by the cosine of the rotation angle
d12	Specifies the vertical stretch factor multiplied by the sine of the sum of the rotation and skew angles. This value is expressed as the negative of the resultant value.
d21	Specifies the horizontal stretch factor multiplied by the sine of the rotation angle
d22	Specifies the vertical stretch factor multiplied by the cosine of the sum of the rotation and skew angles

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.HasHSBBlends

Property **HasHSBBlends** As Boolean

Description

Member of FountainFill

The **HasHSBBlends** property checks if the fountain fill contains HSB blends. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.HasNonLinearBlends

Property **HasNonLinearBlends** As Boolean

Description

Member of FountainFill

The **HasNonLinearBlends** property checks if the fountain fill contains nonlinear blends. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.IsTransparent

Property **IsTransparent** As Boolean

Description

Member of FountainFill

The **IsTransparent** property checks if the fountain fill contains transparencies. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.MakeOpaque

Sub **MakeOpaque()**

Description

Member of FountainFill

The **MakeOpaque** method removes any transparency from the fill.

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.ScaleX

Property **ScaleX** As Double

Description

Member of FountainFill

The **ScaleX** property returns or specifies the width of the fill as a percentage of the object's width.

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.ScaleY

Property **ScaleY** As Double

Description

Member of FountainFill

The **ScaleY** property returns or specifies the height of the fill as a percentage of the object's height.

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.SetAngle

Sub **SetAngle(***Angle As Double***)**

Description

Member of FountainFill

The **Angle** property rotates the fountain-fill vector. Positive values rotate the fill counterclockwise; negative values rotate it clockwise.

Parameter	Description
Angle	Specifies the rotation in degrees. This value can range from **0** to **360**.

VBA example

The following VBA example sets the rotation angle of the fountain fill to **30**°.

```
Sub Test()
 ActiveShape.Fill.Fountain.SetAngle 30
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.SetTransformations

Sub **SetTransformations(*d11*** As Double, **d12** As Double, **d21** As Double, **d22** *As Double*)

Description

Member of FountainFill

The **SetTransformations** method specifies what transformations to apply to the fountain fill.

Parameter	Description
d11	Specifies the horizontal stretch factor multiplied by the cosine of the rotation angle
d12	Specifies the vertical stretch factor multiplied by the sine of the sum of the rotation and skew angles. This value is expressed as the negative of the resultant value.
d21	Specifies the horizontal stretch factor multiplied by the sine of the rotation angle
d22	Specifies the vertical stretch factor multiplied by the cosine of the sum of the rotation and skew angles

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.Skew

Property **Skew** As Double

Description

Member of FountainFill

The **Skew** property returns or specifies the angle at which the fill is slanted.

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.SmoothBlend

Property **SmoothBlend** As Double

Description

Member of FountainFill

The **SmoothBlend** property returns or specifies smoother color transitions between fountain fill nodes.

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.SpreadMethod

Property **SpreadMethod** As cdrFountainFillSpreadMethod

Description

Member of FountainFill

The **SpreadMethod** property returns or specifies whether the fill is padded, reflected and repeated, or repeated.

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.StartColor

Property **StartColor** As Color

Description

Member of FountainFill

The **StartColor** property returns or specifies the starting color a fountain fill.

You can also access the starting color point of the fill by using the **.Colors(0)** property of the FountainColors collection.

VBA example

The following VBA example displays the names of the colors of the starting and ending color points of the fountain fill.

```
Sub Test()
 Dim ff As FountainFill
 If ActiveShape.Fill.Type = cdrFountainFill Then
  Set ff = ActiveShape.Fill.Fountain
  MsgBox "The fountain fill is from " & ff.StartColor.Name & _
    " to " & ff.EndColor.Name
 Else
  MsgBox "The selected shape doesn't have a fountain fill"
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.StartX

Property **StartX** As Double

Description

Member of FountainFill

The **StartX** property returns or specifies the horizontal starting-coordinate of a fountain-fill vector. For radial, rectangular, and conical fills, the starting point is the center point of the fill.

The **StartX** property is measured in document units.

VBA example

The following VBA example draws circles around the starting and ending points of the fountain-fill vector.

```
Sub Test()
 With ActiveShape.Fill.Fountain
  ActiveLayer.CreateEllipse2 .StartX, .StartY, 0.2
  ActiveLayer.CreateEllipse2 .EndX, .EndY, 0.2
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.StartY

Property **StartY** As Double

Description

Member of FountainFill

The **StartY** property returns or specifies the vertical starting-coordinate of a fountain-fill vector. For radial, rectangular, and conical fills, the starting point is the center point of the fill.

The **StartY** property is measured in document units.

VBA example

The following VBA example draws circles around the starting and ending points of the fountain-fill vector.

```
Sub Test()
 With ActiveShape.Fill.Fountain
  ActiveLayer.CreateEllipse2 .StartX, .StartY, 0.2
  ActiveLayer.CreateEllipse2 .EndX, .EndY, 0.2
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.Steps

Property **Steps** As Long

Description

Member of FountainFill

The **Steps** property returns or specifies the number of steps in a fountain fill. The value can range from **2** to **999**. If the value is equal to zero, the default number of steps of the document is used.

VBA example

The following VBA example searches through all shapes on the current page for a fountain fill with a specified number of fountain steps (that is, where the value of the **Steps** property is not **0**). If a shape is selected before this macro is played, the next shape with a fixed number of steps is searched for.

```
Sub FindFixedSteps()
 Dim s As Shape, id As Long
 Dim bLoop As Boolean
 Set s = ActiveShape
 If s Is Nothing Then
  ' Nothing selected. Get the first shape on the page.
  Set s = ActivePage.Shapes(1)
  If TestShape(s) Then
   s.CreateSelection
   Exit Sub ' Shape Found
  End If
 End If
 id = s.StaticID ' Remember the ID of the selected shape.
 Do
  Set s = s.Next(cdrLevelPage, True, True) ' Get the next shape.
  If TestShape(s) Then
   s.CreateSelection
   Exit Sub ' Shape Found
  End If
 Loop While id <> s.StaticID ' Loop until we find the selected shape again.
 MsgBox "Shape not found", vbCritical
End Sub
' The following function is used to check whether the current shape is the one
' we are looking for.
Private Function TestShape(s As Shape) As Boolean
 Dim b As Boolean
 b = False
 If s.Fill.Type = cdrFountainFill Then
  If s.Fill.Fountain.Steps <> 0 Then b = True
 End If
 TestShape = b
End Function
```

Copyright 2014 Corel Corporation. All rights reserved.

FountanFill.Translate

Sub **Translate(***x As Double***,** *y As Double***)**

Description

Member of FountainFill

The **Translate** method repositions the fountain-fill vector. Both the starting and ending points of the fountain fill vector are moved by the specified offset.

Parameter	Description
x	Specifies the horizontal offset, measured in document units
y	Specifies the vertical offset, measured in document units

VBA example

The following VBA example centers a fountain fill in the active shape (by placing the center of the fill in the center of the shape).

```
Sub Test()
 Dim ff As FountainFill
 Dim cx As Double, cy As Double ' Current position of fill center
 Dim sx As Double, sy As Double ' Shape's center
 If ActiveShape.Fill.Type = cdrFountainFill Then
  Set ff = ActiveShape.Fill.Fountain
  Select Case ff.Type
   Case cdrSquareFountainFill, cdrRadialFountainFill, cdrConicalFountainFill
    cx = ff.StartX
    cy = ff.StartY
   Case cdrLinearFountainFill
    cx = (ff.StartX + ff.EndX) / 2
    cy = (ff.StartY + ff.EndY) / 2
  End Select
  ActiveDocument.ReferencePoint = cdrCenter
  ActiveShape.GetPosition sx, sy
  ff.Translate sx - cx, sy - cy
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FountainFill.Type

Property **Type** As cdrFountainFillType

Description

Member of FountainFill

The **Type** property returns or specifies the type of the fountain fill. A fountain fill can be linear, conical, radial, or square. The **Type** parameter returns cdrFountainFillType.

VBA example

The following VBA example changes all linear fountain fills on the active page to conical fountain fills.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Fill.Type = cdrFountainFill Then
   If s.Fill.Fountain.Type = cdrLinearFountainFill Then
    s.Fill.Fountain.Type = cdrConicalFountainFill
   End If
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow

Properties Methods

Description

The **FrameWindow** class represents a floating application window.

For an example that uses this class, see Cascading views.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow.Activate

Sub **Activate()**

Description

Member of FrameWindow

The **Activate** method activates the window.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow.Caption

Property **Caption** As String

Description

Member of FrameWindow

The **Caption** property returns the caption text of the frame window.

The **Caption** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow.Close

Sub **Close()**

Description

Member of FrameWindow

The **Close** method closes the window and all contained views.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow.CombineViews

Sub **CombineViews()**

Description

Member of FrameWindow

The **CombineViews** method combines all views in one view host.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow.DockHosts

Property **DockHosts** As DockHosts

Description

Member of FrameWindow

The **DockHosts** property returns a collection of all the dock hosts owned by a frame window.

The **DockHosts** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow.Handle

Property **Handle** As Long

Description

Member of FrameWindow

The **Handle** property returns the Windows platform handle of the window.

The **Handle** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow.ID

Property **ID** As String

Description

Member of FrameWindow

The **ID** property returns the ID of the frame window.

The **ID** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow.IsActive

Property **IsActive** As Boolean

Description

Member of FrameWindow

The **IsActive** property returns True if this is the active frame window.

The **IsActive** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow.IsMainFrame

Property **IsMainFrame** As Boolean

Description

Member of FrameWindow

The **IsMainFrame** property returns True if this is the active frame window.

The **IsMainFrame** property returns a read-only value.

For an example that usese this property, see Understanding the layout structure.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow.Maximize

Sub **Maximize()**

Description

Member of FrameWindow

The **Maximize** method maximizes the frame window.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow.Minimize

Sub **Minimize()**

Description

Member of FrameWindow

The **Minimize** method minimizes the frame window.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow.Position

Property **Position** As ScreenRect

Description

Member of FrameWindow

The **Position** property returns the position and size of the window on the screen.

The **Position** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow.Restore

Sub **Restore()**

Description

Member of FrameWindow

The **Restore** method restores the position and size of the frame window.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow.RootDockHost

Property **RootDockHost** As DockHost

Description

Member of FrameWindow

The **RootDockHost** property returns the top-level DockHost of the frame window.

The **RootDockHost** property returns a read-only value.

For an example that usese this property, see Combining views.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow.State

Property **State** As cuiWindowState

Description

Member of FrameWindow

The **State** property returns the current state of the window.

The **State** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow.TileViews

Sub **TileViews**([TileHorizontally As Boolean = True])

Description

Member of FrameWindow

The **TileViews** method tiles all contained views vertically or horizontally.

Parameter	Description
TileHorizontally	Tiles views horizontally The default value is True.

Example

The following macro tiles all the views inside the main frame window by using a grid.

```
Sub TileViews()
 Dim views As New Collection
 Dim fw As FrameWindow
 Dim vh As ViewHost, vw As ViewWindow, dh As DockHost
 Dim rows As Long, cols As Long
 Dim x As Long, y As Long, i As Long
 Dim r As DockItem, c As DockItem
  For Each fw In FrameWork.FrameWindows
   For Each vh In fw.ViewHosts
    For Each vw In vh.views
        views.Add vw
      Next vw
    Next vh
  Next fw
    If views.Count = 0 Then Exit Sub
    rows = CLng(Sqr(views.Count))
  cols = (views.Count + rows - 1) \ rows
    Set fw = FrameWork.MainFrameWindow
    For y = 1 To rows
    i = (y - 1) * cols + 1
    If dh Is Nothing Then
      If fw.RootDockHost.Orientation = cuiDockHostVertical Then
        Set vh = fw.RootDockHost.InsertView(views(i), y)
        Set dh = vh.DockHost
      Else
        Set vh = fw.RootDockHost.InsertView(views(i), 0, cuiDockOperationSplitTopLeft)
        Set dh = vh.DockHost
      End If
    Else
      Set vh = dh.InsertView(views(i), y)
    End If
    For x = 2 To cols
      i = i + 1
      If i <= views.Count Then
        If dh.Children(y).Type = cuiDockItemDockHost Then
          dh.Children(y).DockHost.InsertView views(i), x
        Else
          dh.InsertView views(i), y, cuiDockOperationSplitBottomRight
        End If
      End If
    Next x
  Next y
  For Each r In fw.RootDockHost.Children
    r.RelativeSize = fw.RootDockHost.Position.Height / rows
    If r.Type = cuiDockItemDockHost Then
      For Each c In r.DockHost.Children
        c.RelativeSize = fw.RootDockHost.Position.Width / cols
      Next c
    End If
  Next r
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindow.ViewHosts

Property **ViewHosts** As ViewHosts

Description

Member of FrameWindow

The **ViewHosts** property returns a collection of all the view hosts owned by the frame window.

The **ViewHosts** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindows

Properties Methods

Description

The **FrameWindows** class represents document and application windows.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindows.Count

Property **Count** As Long

Description

Member of FrameWindows

The **Count** property returns the number of available frame windows.

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindows.Find

Function **Find**(ID As String) As FrameWindow

Description

Member of FrameWindows

The **Find** method finds a frame window by using its ID.

Parameter	Description
ID	Specifies the ID

The return value of this method is FrameWindow.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindows.First

Property **First** As FrameWindow

Description

Member of FrameWindows

The **First** property returns the first frame window.

The **First** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindows.Item

Property **Item**(Index As Long) As FrameWindow

Description

Member of FrameWindows

The **Item** property returns a frame window by index.

The **Item** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWindows.Last

Property **Last** As FrameWindow

Description

Member of FrameWindows

The **Last** property returns the last frame window.

The **Last** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWork

Properties Methods

Description

The **FrameWork** class represents the UI (User Interface) framework.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWork.AddDocker

Sub **AddDocker(**Guid As String, ClassName As String, [*AssemblyPath As String = ""*]**)**

Description

Member of FrameWork

The **AddDocker** method adds a custom docker from a .Net assembly.

Parameter	Description
Guid	Specifies the docker name
ClassName	Specifies the class name
AssemblyPath	

Copyright 2014 Corel Corporation. All rights reserved.

FrameWork.Application

Property **Application** As ICUIApplication

Description

Member of FrameWork

The **Application** property returns the application object.

The **Application** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWork.Automation

Property **Automation** As ICUIAutomation

Description

Member of FrameWork

The **Automation** property's gives access to properties of specific UI controls.

The **Automation** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWork.CommandBars

Property **CommandBars** As Long

Description

Member of FrameWork

The **CommandBars** property returns the collection of available command bars.

The **CommandBars** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWork.CreateFrameWindowForView

Function **CreateFrameWindowForView**(*ViewToInsert As* ViewWindow*)* As FrameWindow

Description

Member of FrameWork

The **CreateFrameWindowForView** method creates a new frame window and moves the view in the new window.

Parameter	Description
ViewToInsert	Specifies the view to be moved

For an example that usese this function, see Cascading views.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWork.CreateFrameWindowForViewHost

Function **CreateFrameWindowForViewHost**(*ViewHostToInsert As* ViewHost*)* As FrameWindow

Description

Member of FrameWork

The **CreateFrameWindowForView** method creates a new frame window and moves the view host in the new window.

Parameter	Description
ViewHostToInsert	Specifies the view host to be moved

Copyright 2014 Corel Corporation. All rights reserved.

FrameWork.FrameWindows

Property **FrameWindows** As FrameWindows

Description

Member of FrameWork

The **FrameWindows** property returns a collection of frame windows.

The **FrameWindows** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWork.HideDocker

Sub **HideDocker(***Guid As String***)**

Description

Member of FrameWork

The **HideDocker** method hides a docker.

Parameter	Description
Guid	Specifies which docker to hide

Copyright 2014 Corel Corporation. All rights reserved.

FrameWork.ImportWorkspace

Sub **ImportWorkspace(***FileName As String***)**

Description

Member of FrameWork

The **ImportWorkspace** method imports a workspace in the framework.

Parameter	Description
FileName	Specifies the name of the file from which to import the workspace

Copyright 2014 Corel Corporation. All rights reserved.

FrameWork.IsDockerVisible

Function **IsDockerVisible(***Guid As String***)** As Boolean

Description

Member of FrameWork

The **IsDockerVisible** method specifies if a docker is visible.

Parameter	Description
Guid	Specifies the name of the docker

Copyright 2014 Corel Corporation. All rights reserved.

FrameWork.MainFrameWindow

Property **MainFrameWindow** As FrameWindow

Description

Member of FrameWork

The **MainFrameWindow** property returns a main frame window.

The **MainFrameWindow** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWork.MainMenu

Property **MainMenu** As CommandBar

Description

Member of FrameWork

The **MainMenu** property returns the main menu of the application.

The **MainMenu** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWork.Name

Property **Name** As String

Description

Member of FrameWork

The **Name** property returns the name of the control.

The **Name** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

FrameWork.RemoveDocker

Sub **RemoveDocker**(*Guid As String*)

Description

Member of FrameWork

The **RemoveDocker** method removes a custom docker.

Parameter	Description
Guid	Specifies the name of the docker

Copyright 2014 Corel Corporation. All rights reserved.

FrameWork.ShowDocker

Sub **ShowDocker**(*Guid As String*)

Description

Member of FrameWork

The **ShowDocker** method displays a docker.

Parameter	Description
Guid	Specifies the name of the docker

Copyright 2014 Corel Corporation. All rights reserved.

FrameWork.StatusBar

Property **StatusBar** As CommandBar

Description

Member of FrameWork

The **StatusBar** property returns the main status bar of the application.

The **StatusBar** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

GlobalMacroStorage

Events

Description

The **GlobalMacroStorage** class represents events that are triggered by a specific action made in the application or document.

Copyright 2014 Corel Corporation. All rights reserved.

GMSManager

Properties Methods

Description

The **GMSManager** class lets you work with GMS (Global Macro Storage) modules and run VBA macros from other programs.

Copyright 2014 Corel Corporation. All rights reserved.

GMSManager.GMSPath

Property **GMSPath** As String

Description

Member of GMSManager

The **GMSPath** property returns the path to the folder where all GMS modules are installed. The path always ends with the backslash character (\ ).

The **GMSPath** property returns a read-only value.

VBA example

The following VBA example displays the path to the GMS folder in the current CorelDRAW installation.

```
Sub Test()
 MsgBox GMSManager.GMSPath
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

GMSManager.RunMacro

Function **RunMacro(***ModuleName As String***,** *MacroName As String***,** *Parameter() As Variant***)** As Variant

Description

Member of GMSManager

The **RunMacro** method runs a function or a subroutine located in another GMS module.

Parameter	Description
ModuleName	Specifies the name of the module
MacroName	Specifies the name of the macro to run
Parameter	Represents values that are passed to the function or subroutine that is called. The types and the number of parameters must match those of the function or subroutine that is called. If you call a function, its return value is returned by the **RunMacro** method.

This method returns a variant.

The following subroutine is contained in the module **MyModule**, which is part of the GMS file **GlobalMacros**.

```
Sub MyTestSub()
 MsgBox "Hello world!"
End Sub
Sub Test()
 GMSManager.RunMacro "GlobalMacros", "MyModule.MyTestSub"
End Sub
The following function is contained in the module "MyModule" which is part of the GMS file "GlobalMacros."
Function Multiply(x As Double, y As Double) As Double
 Multiply = x * y
End Function
Sub Test()
 Dim v As Double
 v = GMSManager.RunMacro("GlobalMacros", "MyModule.Multiply", 4, 7)
 MsgBox "4 * 7 = " & v
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

GMSManager.UserGMSPath

Property **UserGMSPath** As String

Description

Member of GMSManager

The **UserGMSPath** returns a path to the folder where all GMS modules are stored in the user's system profile.

The **UserGMSPath** returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Grid

Properties Methods

Description

The **Grid** class represents the grid settings for a document.

Copyright 2014 Corel Corporation. All rights reserved.

Grid.Application

Property **Application** As Application

Description

Member of Grid

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Grid.Parent

Property **Parent** As Document

Description

Member of Grid

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Grid.SetFrequency

Sub **SetFrequency**(*GridX As Double*, *GridY As Double*)

Description

Member of Grid

The **SetFrequency** method specifies grid spacing as frequency — the number of grid lines (or dots) per unit of length.

Parameter	Description
GridX	Specifies the number of horizontal grid lines or dots to appear per unit of length. The minimum value is **0.005**".
GridY	Specifies the number of vertical grid lines or dots to appear per unit of length. The minimum value is **0.005**".

VBA example

The following VBA example sets five lines per inch horizontally and three lines per inch vertically in the grid.

```
Sub Test()
 ActiveDocument.Unit = cdrInch
 ActiveDocument.Grid.SetFrequency 5, 3
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Grid.Snap

Property **Snap** As Boolean

Description

Member of Grid

The **Snap** property returns **True** if the **Snap To Grid** feature is enabled, **False** otherwise.

VBA example

The following VBA example enables snapping to a grid.

```
Sub Test()
 ActiveDocument.Grid.Snap = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Grid.SpacingX

Property **SpacingX** As Double

Description

Member of Grid

The **SpacingX** property returns or specifies the horizontal distance between grid lines or dots.

The minimum value is **0.005**".

You can use the SetFrequency method to specify the frequency of the lines or dots per unit length.

VBA example

The following VBA example sets the spacing within the grid so that horizontal and vertical grid lines appear every **0.5**" from each other.

```
Sub Test()
 With ActiveDocument.Grid
  .SpacingX = 0.5
  .SpacingY = 0.5
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Grid.SpacingY

Property **SpacingY** As Double

Description

Member of Grid

The **SpacingY** property returns or specifies the vertical spacing between grid lines or dots.

The minimum value is **0.005**".

You can use the SetFrequency method to specify the frequency of the lines or dots per unit length.

VBA example

The following VBA example sets the spacing within the grid so that horizontal and vertical grid lines appear every **0.5**" from each other.

```
Sub Test()
 With ActiveDocument.Grid
  .SpacingX = 0.5
  .SpacingY = 0.5
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Grid.Type

Property **Type** As cdrGridType

Description

Member of Grid

The **Type** property returns or specifies whether the grid is visible as dots or as lines.

The **Type** property returns a value of cdrGridType**.**

VBA example

The following VBA example creates a grid with intersecting lines.

```
Sub Test()
 ActiveDocument.Grid.Type = cdrGridLine
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Grid.Visible

Property **Visible** As Boolean

Description

Member of Grid

The **Visible** property shows or hides the grid. If the **Visible** property is **True**, the grid is displayed in the drawing window.

VBA example

The following VBA example hides the grid.

```
Sub Test()
 ActiveDocument.Grid.Visible = False
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Guide

Properties Methods

Description

The **Guide** class represents guideline-specific information for a shape (or Shape object).

Copyright 2014 Corel Corporation. All rights reserved.

Guide.Angle

Property **Angle** As Double

Description

Member of Guide

The **Angle** property returns the slope angle of a guideline.

The **Angle** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Guide.CenterX

Property **CenterX** As Double

Description

Member of Guide

The **CenterX** property returns the x-coordinate of the point on a guideline closest to the page center.

The **CenterX** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Guide.CenterY

Property **CenterY** As Double

Description

Member of Guide

The **CenterY** property returns the y-coordinate of the point on a guideline closest to the page center.

The **CenterY** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Guide.GetPointAndAngle

Sub **GetPointAndAngle(***PointX As Double***,** *PointY As Double***,** *Angle As Double***)**

Description

Member of Guide

The **GetPointAndAngle** method returns the position of a point on a guideline and the slope angle.

Parameter	Description
PointX	Specifies the x-coordinate of the point
PointY	Specifies the y-coordinate of the point
Angle	Specifies the slope angle

Copyright 2014 Corel Corporation. All rights reserved.

Guide.GetPoints

Sub **GetPoints**(*Point1X As Double*, *Point1Y As Double*, *Point2X As Double*, *Point2Y As Double*)

Description

Member of Guide

The **GetPoints** method returns the x- and y-coordinates of two points on a guideline.

Parameter	Description
Point1X	Specifies the x-coordinate of the first point
Point1Y	Specifies the y-coordinate of the first point
Point2X	Specifies the x-coordinate of the second point
Point2Y	Specifies the y-coordinate of the second point

Copyright 2014 Corel Corporation. All rights reserved.

Guide.InterceptX

Property **InterceptX** As Double

Description

Member of Guide

The **Intercept**X property returns the x-coordinate of the intersection of a guideline and the horizontal axis going through the center of the page.

The **Intercept**X property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Guide.InterceptY

Property **InterceptY** As Double

Description

Member of Guide

The **InterceptY** property returns the y-coordinate of the intersection of a guideline and the vertical axis going through the center of the page.

The **InterceptY** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Guide.MakeEditable

Sub **MakeEditable()**

Description

Member of Guide

The **MakeEditable** method converts a preset guideline to a normal guideline that can be edited directly on the drawing page.

VBA example

The following VBA example converts all preset guidelines to normal guidelines on the master page.

```
Sub Test()
 Dim s As Shape
 For Each s In ActiveDocument.Pages(0).Guides(cdrAllGuides)
  If s.Guide.Preset Then s.Guide.MakeEditable
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Guide.Point1X

Property **Point1X** As Double

Description

Member of Guide

The **Point1X** property returns the horizontal position of the first point on a guideline.

The **Point1X** property returnsa read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Guide.Point1Y

Property **Point1Y** As Double

Description

Member of Guide

The **Point1Y** property returns the vertical position of the first point on a guideline.

The **Point1Y** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Guide.Point2X

Property **Point2X** As Double

Description

Member of Guide

The **Point2X** property returns the horizontal position of the second point on a guideline.

The **Point2X** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Guide.Point2Y

Property **Point2Y** As Double

Description

Member of Guide

The **Point2Y** property returns the vertical position of the second point on a guideline.

The **Point2Y** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Guide.Preset

Property **Preset** As Boolean

Description

Member of Guide

The **Preset** property returns a value of **True** if a guideline is a preset guideline, **False** if it is not.

The **Preset** property returns a read-only value.

VBA example

The following VBA example removes all guidelines that are not preset guidelines on the master page.

```
Sub Test()
 Dim s As Shape
 For Each s In ActiveDocument.Pages(0).Guides(cdrAllGuides)
  If Not s.Guide.Preset Then s.Delete
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Guide.SetPointAndAngle

Sub **SetPointAndAngle(***PointX As Double***,** *PointY As Double***,** *Angle As Double***)**

Description

Member of Guide

The **SetPointAndAngle** method moves and rotates a guideline by specifying a point and a slope angle

Parameter	Description
PointX	Specifies the x-coordinate of the point
PointY	Specifies the y-coordinate of the point
Angle	Specifies the slope angle

Copyright 2014 Corel Corporation. All rights reserved.

Guide.SetPoints

Sub **SetPoints(***Point1X As Double*, *Point1Y As Double*, *Point2X As Double*, *Point2Y As Double***)**

Description

Member of Guide

The **SetPoints** method moves and rotates a guideline by specifying two points.

Parameter	Description
Point1X	Specifies the x-coordinate of the first point
Point1Y	Specifies the y-coordinate of the first point
Point2X	Specifies the x-coordinate of the second point
Point2Y	Specifies the y-coordinate of the second point

Copyright 2014 Corel Corporation. All rights reserved.

Guide.Type

Property **Type** As cdrGuideType

Description

Member of Guide

The **Type** property returns the guideline type. A guideline can be one of three types: horizontal, vertical, or slanted.

The **Type** property returns a read-only value.

VBA example

The following VBA example displays the number of horizontal, vertical, and slanted guidelines on the master page.

```
Sub Test()
 Dim s As Shape
 Dim hg As Long, vg As Long, sg As Long
 For Each s In ActiveDocument.Pages(0).Guides(cdrAllGuides)
  Select Case s.Guide.Type
   Case cdrVerticalGuide
    vg = vg + 1
   Case cdrSlantedGuide
    sg = sg + 1
   Case cdrHorizontalGuide
    hg = hg + 1
  End Select
 Next s
 MsgBox "The document contains:" & vbCr & _
  "Horizontal guides: " & hg & vbCr & _
  "Vertical guides: " & vg & vbCr & _
  "Slanted guides: " & sg
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill

Properties Methods

Description

The **HatchFill** class represents the settings for a hatch fill.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.AddPattern

Function **AddPattern(***Angle As Double***,** *Spacing As Double***, [***Shift As Double***], [***OriginX As Double***], [***OriginY As Double***], [***Width As Double***], [**Color As Color**], [**Style As OutlineStyle**], [**DashDotLength As Double = -1**], [***PenWidth As Double***])** As HatchPattern

Description

Member of HatchFill

The **AddPattern** method adds a new pattern to the hatch.

Parameter	Description
Angle	Specifies the rotation angle of the lines in the hatch-fill pattern
Spacing	Specifies the line spacing in the hatch-fill pattern
Shift	Specifies an additional relative horizontal shift of the lines in the hatch-fill pattern. This parameter is optional, and its default value is **0**.
OriginX	Specifies the horizontal offset of the start of the first line in the hatch-fill pattern. This parameter is optional, and its default value is **0**.
OriginY	Specifies the vertical offset of the start of the first line in the hatch-fill pattern. This parameter is optional, and its default value is **0**.
Width	Specifies the width at which to apply the hatch fill. This parameter is optional, and its default value is **0**.
Color	Specifies the color for the hatch fill. This parameter is optional, and its default value is **Nothing**.
Style	Specifies the outline style for the hatch fill. This parameter is optional, and its default value is **Nothing**.
DashDotLength	Specifies the dash-dot length of the lines in the hatch fill. This parameter is optional, and its default value is **-1**.
PenWidth	Specifies the pen width of the lines in the hatch fill. This parameter is optional, and its default value is **0**.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.AddToLibrary

Sub **AddToLibrary(***LibraryName As String***, [***HatchName As String***])**

Description

Member of HatchFill

The **AddToLibrary** method adds the current hatch fill to a hatch-fill library.

Parameter	Description
LibraryName	Specifies the name of the library
HatchName	Specifies the name of the fill. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.BackColor

Property **BackColor** As Color

Description

Member of HatchFill

The **BackColor** property returns or specifies the background color of a hatch fill. **Nothing** is used to specify no color.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.FillScaleX

Property **FillScaleX** As Double

Description

Member of HatchFill

The **FillScaleX** property specifies the horizontal scale factor for a hatch fill.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.FillScaleY

Property **FillScaleY** As Double

Description

Member of HatchFill

The **FillScaleY** property specifies the vertical scale factor for a hatch fill.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.GetFillScale

Function **GetFillScale()** As Double

Description

Member of HatchFill

The **GetFillScale** method returns the average scale factor for a hatch fill.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.GetLineScale

Function **GetLineScale()** As Double

Description

Member of HatchFill

The **GetLineScale** method returns the average line-thickness scale factor for a hatch fill.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.HasBackground

Property **HasBackground** As Boolean

Description

Member of HatchFill

The **HasBackground** property returns **True** if a hatch fill has an opaque background.

The **HasBackground** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.HatchName

Property HatchName As String

Description

Member of HatchFill

The HatchName property returns the name of the hatch-fill pattern, as it appears in its hatch-fill library.

The HatchName property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.Index

Property **Index** As Long

Description

Member of HatchFill

The **Index** property returns the index number of a hatch-fill pattern (as it appears in its hatch-fill library) or **0** if the pattern is not part of a library.

The **Index** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.IsFromLibrary

Property **IsFromLibrary** As Boolean

Description

Member of HatchFill

The **IsFromLibrary** property returns **True** if a hatch fill belongs to a hatch-fill library. **False** is returned if the hatch fill has instead been modified since its original definition in its hatch-fill library.

The **IsFromLibrary** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.Library

Property **Library** As HatchLibrary

Description

Member of HatchFill

The **Library** property returns the hatch-fill library (or HatchLibrary object) to which a hatch fill belongs or **Nothing** if the fill is not part of a library.

The **Library** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.LibraryName

Property **LibraryName** As String

Description

Member of HatchFill

The **LibraryName** property returns the name of the hatch-fill library from which a hatch fill is applied.

The **LibraryName** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.Patterns

Property **Patterns** As HatchPatterns

Description

Member of HatchFill

The **Patterns** property returns a collection of hatch-fill patterns (or HatchPatterns objects).

The **Patterns** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.RotationAngle

Property **RotationAngle** As Double

Description

Member of HatchFill

The **RotationAngle** property specifies an additional rotation angle for a hatch fill.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.ScaleLinesWithShape

Property **ScaleLinesWithShape** As Boolean

Description

Member of HatchFill

The **ScaleLinesWithShape** property specifies whether to scale the line thicknesses in a hatch fill along with the shape to which the hatch fill is applied.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.Select

Sub **Select(***LibraryName As String***,** *HatchNameOrIndex As Variant***, [**BackColor As Color**], [**TransformWithShape As Boolean = False**], [**ScaleLinesWithShape As Boolean = False**], [**UseWorldCoordinates As Boolean = False**], [***FillScale As Double***], [***LineScale As Double***], [***FillAngle As Double***], [***FillSkew As Double***])**

Description

Member of HatchFill

The **Select** method selects a new hatch fill from the specified library.

Parameter	Description
LibraryName	Specifies the name of the library
HatchNameOrIndex	Specifies the name or index number of the hatch-fill pattern
BackColor	Specifies a background color for the hatch fill. This parameter is optional, and its default value is **Nothing**.
TransformWithShape	Specifies whether to transform the hatch fill with the shape to which the hatch fill is applied. This parameter is optional, and its default value is **False**.
ScaleLinesWithShape	Specifies whether to scale the hatch-fill lines with the shape to which the hatch fill is applied. This parameter is optional, and its default value is **False**.
UseWorldCoordinates	Specifies whether local or world coordinates are used to align the hatch fills applied to different objects. This parameter is optional, and its default value is **False**.
FillScale	Specifies the average scale factor for the hatch fill. This parameter is optional, and its default value is **0**.
LineScale	Specifies the average line-thickness scale factor for the hatch fill. This parameter is optional, and its default value is **0**.
FillAngle	Specifies the rotation angle for the hatch fill. This parameter is optional, and its default value is **0**.
FillSkew	Specifies the skew angle for the hatch fill. This parameter is optional, and its default value is **0**.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.SetFillScale

Sub **SetFillScale(***FillScale As Double***)**

Description

Member of HatchFill

The **SetFillScale** method sets the average scale factor for a hatch fill.

Parameter	Description
FillScale	Specifies the scale factor

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.SetLineScale

Sub **SetLineScale(***LineScale As Double***)**

Description

Member of HatchFill

The **SetLineScale** method sets the average line-thickness scale factor for a hatch fill.

Parameter	Description
LineScale	Specifies the line-thickness scale factor

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.SetNoBackColor

Sub **SetNoBackColor()**

Description

Member of HatchFill

The **SetNoBackColor** method makes the background of a hatch fill transparent.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.SkewAngle

Property **SkewAngle** As Double

Description

Member of HatchFill

The **SkewAngle** property specifies an additional skew angle for a hatch fill.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.TransformWithShape

Property **TransformWithShape** As Boolean

Description

Member of HatchFill

The **TransformWithShape** property specifies whether to transform a hatch fill along with the shape to which the hatch fill is applied.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFill.UseWorldCoordinates

Property **UseWorldCoordinates** As Boolean

Description

Member of HatchFill

The **UseWorldCoordinates** property specifies whether local or world coordinates are used to align the hatch fills that are applied to different objects.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFills

Properties Methods

Description

The **HatchFills** class represents a collection of hatch fills.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFills.Count

Property **Count** As Long

Description

Member of HatchFills

The **Count** property returns the number of hatch fills in a hatch-fill library.

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchFills.Find

Function **Find(***Name As String***)** As Fill

Description

Member of HatchFills

The **Find** method finds a hatch fill in a hatch-fill library, by name. If no hatch fill is found, **Nothing** is returned.

Parameter	Description
Name	Specifies the name of the hatch fill

Copyright 2014 Corel Corporation. All rights reserved.

HatchFills.Item

Property **Item(***IndexOrName As Variant***)** As Fill

Description

Member of HatchFills

The **Item** property returns a hatch fill from its hatch-fill library, by index number or name. It is the default property of the HatchFills class.

The **Item** property returns a read-only value.

Parameter	Description
IndexOrName	Specifies the hatch fill by its index number or name: • **Index** — Specifies the preset placeholder that uniquely identifies each hatch fill • **Name** — Specifies the string that uniquely identifies each hatch fill

Copyright 2014 Corel Corporation. All rights reserved.

HatchLibraries

Properties Methods

Description

The **HatchLibraries** class represents a collection of hatch libraries (or HatchLibrary objects).

Copyright 2014 Corel Corporation. All rights reserved.

HatchLibraries.ActiveLibrary

Property **ActiveLibrary** As HatchLibrary

Description

Member of HatchLibraries

The **ActiveLibrary** property returns the last selected hatch-fill library.

The **ActiveLibrary** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchLibraries.Count

Property **Count** As Long

Description

Member of HatchLibraries

The **Count** property returns the number of hatch-fill libraries available.

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchLibraries.DefaultLibrary

Property **DefaultLibrary** As HatchLibrary

Description

Member of HatchLibraries

The **DefaultLibrary** property returns the default hatch-fill library.

The **DefaultLibrary** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchLibraries.Find

Function **Find(***Name As String***)** As HatchLibrary

Description

Member of HatchLibraries

The **Find** method finds a hatch-fill library by name. If no hatch-fill library is found, **Nothing** is returned.

Parameter	Description
Name	Specifies the name of the hatch-fill library

Copyright 2014 Corel Corporation. All rights reserved.

HatchLibraries.Item

Property **Item(***IndexOrName As Variant***)** As HatchLibrary

Description

Member of HatchLibraries

The **Item** property returns a hatch-fill library, by index number or name. It is the default property of the HatchLibraries.

The **Item** property returns a read-only value.

Parameter	Description
IndexOrName	Specifies the hatch-fill library by its index number or name: • **Index** — Specifies the preset placeholder that uniquely identifies each hatch-fill library • **Name** — Specifies the string that uniquely identifies each hatch-fill library

Copyright 2014 Corel Corporation. All rights reserved.

HatchLibrary

Properties Methods

Description

The **HatchLibrary** class represents a hatch-fill library.

Copyright 2014 Corel Corporation. All rights reserved.

HatchLibrary.Activate

Sub **Activate()**

Description

Member of HatchLibrary

The **Activate** method activates a hatch-fill library in the user interface of the application.

Copyright 2014 Corel Corporation. All rights reserved.

HatchLibrary.Active

Property **Active** As Boolean

Description

Member of HatchLibrary

The **Active** property returns **True** if a hatch-fill library is currently active.

The **Active** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchLibrary.DisplayName

Property **DisplayName** As String

Description

Member of HatchLibrary

The **DisplayName** property returns the translated name of a hatch-fill library.

The **DisplayName** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchLibrary.Fills

Property **Fills** As HatchFills

Description

Member of HatchLibrary

The **Fills** property returns the number of hatch fills in a hatch-fill library.

The **Fills** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchLibrary.Index

Property **Index** As Long

Description

Member of HatchLibrary

The **Index** property returns the index number of a hatch-fill library.

The **Index** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchLibrary.Name

Property **Name** As String

Description

Member of HatchLibrary

The **Name** property returns the English name of a hatch-fill library.

The **Name** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchPattern

Properties Methods

Description

The **HatchPattern** class represents the available hatch-fill patterns.

Copyright 2014 Corel Corporation. All rights reserved.

HatchPattern.Angle

Property **Angle** As Double

Description

Member of HatchPattern

The **Angle** property specifies the rotation angle of the lines in a hatch-fill pattern.

Copyright 2014 Corel Corporation. All rights reserved.

HatchPattern.Delete

Sub **Delete()**

Description

Member of HatchPattern

The **Delete** method deletes the current hatch-fill pattern from the collection.

Copyright 2014 Corel Corporation. All rights reserved.

HatchPattern.GetOrigin

Sub **GetOrigin(***OriginX As Double***,** *OriginY As Double***)**

Description

Member of HatchPattern

The **GetOrigin** method returns the horizontal and vertical offsets of the start of the first line in a hatch-fill pattern.

Parameter	Description
OriginX	Specifies the horizontal offset of the start of the first line in the hatch-fill pattern
OriginY	Specifies the vertical offset of the start of the first line in the hatch-fill pattern

Copyright 2014 Corel Corporation. All rights reserved.

HatchPattern.Index

Property **Index** As Long

Description

Member of HatchPattern

The **Index** property returns the index number of a hatch-fill pattern.

The **Index** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchPattern.OriginX

Property **OriginX** As Double

Description

Member of HatchPattern

The **OriginX** property specifies the horizontal offset of the start of the first line in a hatch-fill pattern.

Copyright 2014 Corel Corporation. All rights reserved.

HatchPattern.OriginY

Property **OriginY** As Double

Description

Member of HatchPattern

The **OriginY** property specifies the vertical offset of the start of the first line in a hatch-fill pattern.

Copyright 2014 Corel Corporation. All rights reserved.

HatchPattern.Outline

Property **Outline** As Outline

Description

Member of HatchPattern

The **Outline** property specifies the outline properties of a line in a hatch-fill pattern.

The **Outline** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchPattern.Reset

Sub **Reset()**

Description

Member of HatchPattern

The **Reset** method resets the parameters of a hatch-fill pattern to their default values.

Copyright 2014 Corel Corporation. All rights reserved.

HatchPattern.SetOrigin

Sub **SetOrigin(***OriginX As Double***,** *OriginY As Double***)**

Description

Member of HatchPattern

The **SetOrigin** method sets the horizontal and vertical offsets of the start of the first line in a hatch-fill pattern.

Parameter	Description
OriginX	Specifies the horizontal offset of the start of the first line in the hatch-fill pattern
OriginY	Specifies the vertical offset of the start of the first line in the hatch-fill pattern

Copyright 2014 Corel Corporation. All rights reserved.

HatchPattern.SetProperties

Sub **SetProperties([***Angle As Variant***], [***Spacing As Double***], [***Shift As Variant***], [***OriginX As Variant***], [***OriginY As Variant***], [**Width As Double = -1**], [**Color As Color**], [**Style As OutlineStyle**], [**DashDotLength As Double = -1**], [***PenWidth As Double***])**

Description

Member of HatchPattern

The **SetProperties** method specifies commonly used properties for hatch-fill patterns.

Parameter	Description
Angle	Specifies the rotation angle of the lines in the hatch-fill pattern. This parameter is optional.
Spacing	Specifies the line spacing in the hatch-fill pattern. This parameter is optional, and its default value is **0**.
Shift	Specifies an additional relative horizontal shift of the lines in the hatch-fill pattern. This parameter is optional.
OriginX	Specifies the horizontal offset of the start of the first line in the hatch-fill pattern. This parameter is optional.
OriginY	Specifies the vertical offset of the start of the first line in the hatch-fill pattern. This parameter is optional.
Width	Specifies the width at which to apply the hatch fill. This parameter is optional, and its default value is **-1**.
Color	Specifies the color for the hatch fill. This parameter is optional, and its default value is **Nothing**.
Style	Specifies the outline style for the hatch fill. This parameter is optional, and its default value is **Nothing**.
DashDotLength	Specifies the dash-dot length of the lines in the hatch fill. This parameter is optional, and its default value is **-1**.
PenWidth	Specifies the pen width of the lines in the hatch fill. This parameter is optional, and its default value is **0**.

Copyright 2014 Corel Corporation. All rights reserved.

HatchPattern.Shift

Property **Shift** As Double

Description

Member of HatchPattern

This **Shift** property specifies an additional relative horizontal shift of the lines in a hatch-fill pattern.

Copyright 2014 Corel Corporation. All rights reserved.

HatchPattern.ShiftPercent

Property **ShiftPercent** As Double

Description

Member of HatchPattern

The **ShiftPerfect** property specifies an additional relative horizontal shift of the lines in a hatch-fill pattern, as a percentage of dash-dot pattern length.

Copyright 2014 Corel Corporation. All rights reserved.

HatchPattern.Spacing

Property **Spacing** As Double

Description

Member of HatchPattern

The **Spacing** property specifies the line spacing in a hatch-fill pattern.

Copyright 2014 Corel Corporation. All rights reserved.

HatchPatterns

Properties Methods

Description

The **HatchPatterns** class represents a collection of hatch-fill patterns (or HatchPattern objects).

Copyright 2014 Corel Corporation. All rights reserved.

HatchPatterns.Count

Property **Count** As Long

Description

Member of HatchPatterns

The **Count** property returns the number of hatch-fill patterns in a collection.

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

HatchPatterns.Item

Property **Item(***Index As Long***)** As HatchPattern

Description

Member of HatchPatterns

The **Item** property returns a given hatch-fill pattern by its index number. It is the default property of the HatchPattern class.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the index number of the hatch-fill pattern

Copyright 2014 Corel Corporation. All rights reserved.

HatchPatterns.Reset

Sub **Reset()**

Description

Member of HatchPatterns

The **Reset** method deletes all but one hatch-fill pattern from a collection and resets the properties of that remaining hatch-fill pattern to its defaults.

Copyright 2014 Corel Corporation. All rights reserved.

ImageList

Properties Methods

Description

The **ImageList** class represents an image list.

Copyright 2014 Corel Corporation. All rights reserved.

ImageList.AddImage

Function **AddImage**(*Key As String, ImageData As Variant, [MaxSize As Long = 0]*) As Boolean

Description

Member of ImageList

The **AddImage** method adds an image to the image list. The image list can be a file name, raw image data as a byte-array, or an image data stream.

Parameter	Description
Key	Specifies the image key
ImageData	Specifies what image data to add
MaxSize	Specifies the maximum width or height of images. Images that exceed the maximum width or height are shrunk. A value of 0 specifies that there is no restriction for the height and width of an image.

Copyright 2014 Corel Corporation. All rights reserved.

ImageList.ImageCount

Property **ImageCount** As Long

Description

Member of ImageList

The **ImageCount** returns all the images that are added to the image list.

The **ImageCount** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ImageList.ImageExists

Function **ImageExists**(*Key As String*) As Boolean

Description

Member of ImageList

The **ImageExists** method checks if the image with the given key exists in the image list.

Parameter	Description
Key	Specifies the image key

Copyright 2014 Corel Corporation. All rights reserved.

ImageList.ImageKeys

Property **ImageKeys**() As String

Description

Member of ImageList

The **ImageKeys** returns the list of keys that are included in the image list.

The **ImageKeys** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ImageList.RemoveAll

Sub **RemoveAll**()

Description

Member of ImageList

The **RemoveAll** method removes all the images from the image list.

Copyright 2014 Corel Corporation. All rights reserved.

ImageList.RemoveImage

Function **RemoveImage**(*Key As String*) As Boolean

Description

Member of ImageList

The **RemoveImage** method removes an image from the image list.

Parameter	Description
Key	Specifies the image key

Copyright 2014 Corel Corporation. All rights reserved.

ImportFilter

Properties Methods

Description

The **ImportFilter** class represents import filters and their settings.

Copyright 2014 Corel Corporation. All rights reserved.

ImportFilter.Finish

Sub **Finish()**

Description

Member of ImportFilter

The **Finish** method finishes the import process for a file.

VBA example

The following VBA example imports the file **C:\Example.jpg** and returns an ImportFilter object that is used to determine whether the filter has a dialog box. If the filter has a dialog box, that dialog box is displayed; otherwise, the default JPEG settings are applied. The **Finish** method is called to finish the import.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim i As ImportFilter
 Set d = CreateDocument
 Set i = d.ActiveLayer.ImportEx("C:\Example.jpg", cdrJPEG)
 If i.HasDialog Then
  i.ShowDialog
  i.Finish
 Else
  i.Reset
  i.Finish
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ImportFilter.HasDialog

Property **HasDialog** As Boolean

Description

Member of ImportFilter

The **HasDialog** determines whether an import filter has a dialog box associated with it.

The **HasDialog** property returns a read-only value.

VBA example

The following VBA example imports the file **C:\Example.jpg** and returns an ImportFilter object that is used to determine whether the filter has a dialog box. If the filter has a dialog box, that dialog box is displayed; otherwise, the default JPEG settings are applied. The Finish method is called to finish the import.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim i As ImportFilter
 Set d = CreateDocument
 Set i = d.ActiveLayer.ImportEx("C:\Example.jpg", cdrJPEG)
 If i.HasDialog Then
  i.ShowDialog
  i.Finish
 Else
  i.Reset
  i.Finish
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ImportFilter.Reset

Sub **Reset()**

Description

Member of ImportFilter

The **Reset** method applies the default settings for an import filter.

VBA example

The following VBA example imports the file **C:\Example.jpg** and returns an ImportFilter object that is used to determine whether the filter has a dialog box. If the filter has a dialog box, that dialog box is displayed; otherwise, the default JPEG settings are applied. The Finish method is called to finish the import.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim i As ImportFilter
 Set d = CreateDocument
 Set i = d.ActiveLayer.ImportEx("C:\Example.jpg", cdrJPEG)
 If i.HasDialog Then
  i.ShowDialog
  i.Finish
 Else
  i.Reset
  i.Finish
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ImportFilter.ShowDialog

Function **ShowDialog([***hWnd As Long***])** As Boolean

The **ShowDialog** method displays the dialog box associated with an import filter.

Description

Member of ImportFilter

Parameter	Description
hWnd	This parameter is optional, and its default value is **0**.

VBA example

The following VBA example imports the file **C:\Example.jpg** and returns an ImportFilter object that is used to determine whether the filter has a dialog box. If the filter has a dialog box, that dialog box is displayed; otherwise, the default JPEG settings are applied. The Finish method is called to finish the import.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim i As ImportFilter
 Set d = CreateDocument
 Set i = d.ActiveLayer.ImportEx("C:\Example.jpg", cdrJPEG)
 If i.HasDialog Then
  i.ShowDialog
  i.Finish
 Else
  i.Reset
  i.Finish
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer

Properties Methods

Description

The **Layer** class represents a layer in a document.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Above

Property **Above([**IgnoreMasters As Boolean = True**])** As Layer

Description

Member of Layer

The **Above** property returns the layer above the current one.

The **Above** property returns a read-only value.

Parameter	Description
IgnoreMasters	Specifies whether to take master layers into account. This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.AbsoluteIndex

Property **AbsoluteIndex** As Long

Description

Member of Layer

The **AbsoluteIndex** property returns the index number of a layer on the page, taking the master layers into account.

The **AbsoluteIndex** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Activate

Sub **Activate()**

Description

Member of Layer

The **Activate** method activates a layer, making it the active layer.

VBA example

The following VBA example activates the layer named **Layer 1** in the active page.

```
Sub Test()
 ActivePage.Layers("Layer 1").Activate
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Application

Property **Application** As Application

Description

Member of Layer

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Below

Property **Below([**IgnoreMasters As Boolean = True**])** As Layer

Description

Member of Layer

The **Below** property returns the layer below the current one.

The **Below** property returns a read-only value.

Parameter	Description
IgnoreMasters	Specifies whether to take master layers into account. This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Color

Property **Color** As Color

Description

Member of Layer

The **Color** property returns or specifies the override color of a layer.

VBA example

The following VBA example sets the color-override feature to **True** in the active layer and the override color to RGB Red.

```
Sub Test()
 ActiveLayer.OverrideColor = True
 ActiveLayer.Color.RGBAssign 255, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateAngularDimension

Function **CreateAngularDimension(**Center As SnapPoint**,** Point1 As SnapPoint**,** Point2 As SnapPoint**,** *TextX As Double***,** *TextY As Double***, [**Precision As Long = 2**], [**ShowUnits As Boolean = True**], [**Units As cdrDimensionAngularUnits = cdrDimensionUnitDegrees**], [**BoxedText As Boolean = False**], [**LeadingZero As Boolean = True**], [***Prefix As String***], [***Suffix As String***], [**OutlineWidth As Double = -1**], [**Arrows As ArrowHead**], [**OutlineColor As Color**], [***TextFont As String***], [***TextSize As Double***], [**TextColor As Color**])** As Shape

Description

Member of Layer

The **CreateAngularDimension** method creates an angular dimension at a specified location on a layer.

Parameter	Description
Center	Specifies the snap point that represents the vertex (center coordinate) of the angular dimension
Point1	Specifies the snap point that represents an endpoint of the “arms” (or arc) of the angular dimension
Point2	Specifies the snap point that represents an endpoint of the “arms” (or arc) of the angular dimension
TextX	Specifies the horizontal position of the text label
TextY	Specifies the vertical position of the text label
Precision	Specifies the number of significant digits for the dimension label to display after the decimal point, if using a decimal format for the dimension value. This parameter is optional, and its default value is **2**.
ShowUnits	Specifies whether to display the unit of measurement in the label. This parameter is optional, and its default value is **True**.
Units	Specifies the unit of measurement for the dimension value. This parameter is optional, and its default value is cdrDimensionUnitDegrees (**0**).
BoxedText	Specifies whether the dimension value has a visible border with the same properties as the dimension line — that is, whether the dimension label is enclosed by a rectangle. This parameter is optional, and its default value is **False**.
LeadingZero	Specifies whether the text value displays a leading zero for numbers that are less than **1.0** and for which a decimal format is used. This parameter is optional, and its default value is **True**.
Prefix	Specifies the prefix for the dimension label (that is, the text displayed before the dimension value). This parameter is optional.
Suffix	Specifies the suffix for the dimension label (that is, the text displayed after the dimension value). This parameter is optional.
OutlineWidth	Specifies the outline width. This parameter is optional, and its default value is **-1**.
Arrows	Specifies the desired arrowheads. This parameter is optional, and its default value is **Nothing**.
OutlineColor	Specifies the outline color. This parameter is optional, and its default value is **Nothing**.
TextFont	Specifies the text font. This parameter is optional.
TextSize	Specifies the text size. This parameter is optional, and its default value is **0**.
TextColor	Specifies the text color. This parameter is optional, and its default value is **Nothing**.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateArtisticText

Function **CreateArtisticText(***Left As Double***,** *Bottom As Double***,** *Text As String***, [**LanguageID As cdrTextLanguage = cdrLanguageNone**], [**CharSet As cdrTextCharSet = cdrCharSetMixed**], [***Font As String***], [***Size As Single***], [**Bold As cdrTriState = cdrUndefined**], [**Italic As cdrTriState = cdrUndefined**], [**Underline As cdrFontLine = cdrMixedFontLine**]), [**Alignment As cdrAlignment = cdrMixedAlignment**]) As Shape

Description

Member of Layer

The **CreateArtisticText** method creates an artistic text object at a specified location on a layer. You can specify various properties for the object.

Parameter	Description
Left	Specifies, in document units, the horizontal position of the artistic text
Bottom	Specifies, in document units, the vertical position of the artistic text
Text	Specifies the content for the artistic text. The value of the **Text** parameter becomes the actual text created with the **CreateArtisticText** method.
LanguageID	Specifies the language. This parameter is optional, and its default value is cdrLanguageNone (**0**).
CharSet	Specifies the character set. This parameter is optional, and its default value is cdrCharSetMixed (**-1**).
Font	Specifies the font. This parameter is optional.
Size	Specifies the font size. This parameter is optional, and its default value is **0**.
Bold	Specifies whether to apply boldface. This parameter is optional, and its default value is cdrUndefined (**-2**).
Italic	Specifies whether to apply italics. This parameter is optional, and its default value is cdrUndefined (**-2**).
Underline	Specifies an underline to apply. This parameter is optional, and its default value is cdrMixedFontLine (**7**).
Alignment	Specifies the alignment. This parameter is optional, and its default value is cdrMixedAlignment (**6**).

VBA example

The following VBA example adds the word **page:** and the page number to the lower-left corner of the active layer of each page.

```
Sub Test()
 Dim p As Page
 For Each p In ActiveDocument.Pages
  p.ActiveLayer.CreateArtisticText 0, 0, "page: " & p.Index, _
   cdrEnglishUS, , "Arial", 6, cdrTrue, cdrTrue, , cdrLeftAlignment
 Next p
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateArtisticTextWide

Function **CreateArtisticTextWide(***Left As Double*, *Bottom As Double*, *Text As String*, **[**LanguageID As cdrTextLanguage = cdrLanguageNone**], [**CharSet As cdrTextCharSet = cdrCharSetMixed**], [***Font As String***], [***Size As Single***], [**Bold As cdrTriState = cdrUndefined**], [**Italic As cdrTriState = cdrUndefined**], [**Underline As cdrFontLine = cdrMixedFontLine**], [**Alignment As cdrAlignment = cdrMixedAlignment**]) As** Shape

Description

Member of Layer

The **ArtisticTextWide** method creates artistic text, in Unicode, at a specified location on a layer. You can specify various properties for the text.

Parameter	Description
Left	Specifies the horizontal positioning of the artistic text. This value is measured in document units.
Bottom	Specifies the vertical positioning of the artistic text. This value is measured in document units.
Text	Specifies the content for the artistic text
LanguageID	Specifies the language. This parameter is optional, and its default value is cdrLanguageNone (**0**).
CharSet	Specifies the character set. This parameter is optional, and its default value is cdrCharSetMixed (**-1**)
Font	Specifies the font. This parameter is optional.
Size	Specifies the font size. This parameter is optional, and its default value is **0**.
Bold	Specifies whether to apply boldface. This parameter is optional, and its default value is cdrUndefined (**-2**).
Italic	Specifies whether to apply italics. This parameter is optional, and its default value is cdrUndefined (**-2**).
Underline	Specifies an underline to apply. This parameter is optional, and its default value is cdrMixedFontLine (**7**).
Alignment	Specifies the alignment. This parameter is optional, and its default value is cdrMixedAlignment (**6**).

Creates a Greek text string on the current layer of the active document at the lower-left corner of the current page.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateArtisticTextWide(0, 0, Chr(216) & Chr(231) & Chr(241) & _
  Chr(233) & Chr(243), cdrGreek, cdrCharSetGreek, "Times New Roman", 24)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateBSpline

Function **CreateBSpline(**Source As BSpline**)** As Shape

Description

Member of Layer

The **CreateBSpline** method creates a B-spline at a specified location on a layer.

Parameter	Description
Source	Specifies the source of the B-spline

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateConnector

Function **CreateConnector(**Start As SnapPoint**,** End As SnapPoint**)** As Shape

Description

Member of Layer

The **CreateConnector** method creates a connector line at a specified location on a layer.

- See also the Layer.CreateFreeConnector method.

Parameter	Description
Start	Specifies the starting point of the connector-line object
End	Specifies the ending point of the connector-line object

VBA example

The following VBA example creates a rectangle and ellipse on the active layer and draws a connector line between them.

```
Sub Test()
 Dim rect As Shape, ell As Shape
 Dim lr As Layer
 Set lr = ActiveLayer
 Set rect = lr.CreateRectangle(0, 0, 3, 3)
 Set ell = lr.CreateEllipse2(5, 5, 1, 1)
 lr.CreateConnector rect.SnapPoints(9), ell.SnapPoints(5)
End Sub
```

VBA example

The following VBA example creates a rectangle and an ellipse and draws a connector line that joins the center of each object.

```
Sub Test()
 Dim r As Shape, e As Shape
 Set r = ActiveLayer.CreateRectangle(0, 0, 3, 3)
 Set e = ActiveLayer.CreateEllipse2(5, 5, 1, 1)
 ActiveLayer.CreateConnector r.SnapPoints(r.SnapPoints.Count), _
  e.SnapPoints(e.SnapPoints.Count)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateConnectorEx

Function **CreateConnectorEx(**Type As cdrConnectorType**,** Start As SnapPoint**,** End As SnapPoint**)** As Shape

Description

Member of Layer

The **CreateConnectorEx** method creates a connector line of a given type at a specified location on a layer.

Parameter	Description
Type	Specifies, through a value of cdrConnectorType, the connector-line type
Start	Specifies the starting point of the connector-line object
End	Specifies the ending point of the connector-line object

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateCurve

Function **CreateCurve(**Source As Curve**)** As Shape

Description

Member of Layer

The **CreateCurve** method creates a curve at a specified location on a layer. You can use this method after you have created an empty curve and have appended segments to it.

- See the Application.CreateCurve method to create a curve in memory.

Parameter	Description
Source	Specifies the source of the curve

VBA example 1

The following VBA example creates a curve on the active layer.

```
Sub Test()
Dim crv As New Curve
Dim s As Shape
Dim sp As SubPath
Set crv = Application.CreateCurve(ActiveDocument)
Set sp = crv.CreateSubPath(1, 5)
sp.AppendLineSegment 2, 0
sp.AppendCurveSegment2 5, 7, 6, 6, 3, 5
sp.AppendCurveSegment2 7, 2, 3, 6, 7, 1
sp.AppendLineSegment 9, 6
sp.Nodes(3).Type = cdrSmoothNode
Set s = ActiveLayer.CreateCurve(crv)
End Sub
```

VBA example 2

The following VBA example creates a puzzle piece:

```
Sub Test()
 Dim s As Shape, sp As SubPath, crv As Curve
 Set crv = Application.CreateCurve(ActiveDocument)
 Set sp = crv.CreateSubPath(1.351, 8.545)
 sp.AppendCurveSegment 1.351, 8.926, 0.127, 89.901, 0.127, -64.56
 sp.AppendCurveSegment 1.156, 8.952, 0.066, 115.44, 0.066, -48.906
 sp.AppendCurveSegment 1.156, 9.15, 0.065, 131.09, 0.065, -133.149
 sp.AppendCurveSegment 1.351, 9.163, 0.065, 46.846, 0.065, -116.315
 sp.AppendCurveSegment 1.351, 9.545, 0.127, 63.683, 0.127, -89.902
 sp.AppendCurveSegment 0.976, 9.545, 0.125, 179.951, 0.125, 25.612
 sp.AppendCurveSegment 0.96, 9.342, 0.063, -154.391, 0.063, 40.943
 sp.AppendCurveSegment 0.767, 9.339, 0.067, -139.06, 0.067, -41.987
 sp.AppendCurveSegment 0.752, 9.547, 0.063, 138.014, 0.065, -33.906
 sp.AppendCurveSegment 0.351, 9.545, 0.134, 146.087, 0.134, 0.045
 sp.AppendCurveSegment 0.351, 9.163, 0.127, -90#, 0.127, 63.681
 sp.AppendCurveSegment 0.156, 9.15, 0.065, -116.317, 0.065, 46.846
 sp.AppendCurveSegment 0.156, 8.952, 0.065, -133.152, 0.065, 131.093
 sp.AppendCurveSegment 0.351, 8.926, 0.066, -48.906, 0.066, 115.439
 sp.AppendCurveSegment 0.351, 8.545, 0.127, -64.561, 0.127, 90#
 sp.AppendCurveSegment 0.752, 8.547, 0.134, 0.002, 0.134, 146.087
 sp.AppendCurveSegment 0.767, 8.339, 0.065, -33.908, 0.063, 138.012
 sp.AppendCurveSegment 0.96, 8.342, 0.067, -41.987, 0.067, -139.058
 sp.AppendCurveSegment 0.976, 8.545, 0.063, 40.943, 0.063, -154.388
 sp.AppendCurveSegment 1.351, 8.545, 0.125, 25.613, 0.125, 179.998
 sp.Closed = True
 Set s = ActiveLayer.CreateCurve(crv)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateCurveSegment

Function **CreateCurveSegment(***StartX As Double***,** *StartY As Double***,** *EndX As Double***,** *EndY As Double***, [**StartingControlPointLength As Double = -1**], [***StartingControlPointAngle As Double***], [**EndingControlPointLength As Double = -1**], [***EndingControlPointAngle As Double***])** As Shape

Description

Member of Layer

The **CreateCurveSegment** method creates a single curve at a specified location on a layer.

Parameter	Description
StartX	Specifies, in document units, the x-coordinate for the starting point of the curve segment
StartY	Specifies, in document units, the y-coordinate for the starting point of the curve segment
EndX	Specifies, in document units, the x-coordinate for the ending point of the curve segment
EndY	Specifies, in document units, the y-coordinate for the ending point of the curve segment
StartingControlPointLength	Specifies, in document units, the length of the starting control point. This parameter is optional, and its default value is **-1**.
StartingControlPointAngle	Specifies the angle, measured in degrees, of the starting control. This parameter is optional, and its default value is **0**.
EndingControlPointLength	Specifies, in document units, the length of the ending control point. This parameter is optional, and its default value is **-1**.
EndingControlPointAngle	Specifies the angle, measured in degrees, of the ending control point. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example creates a curve segment on the active layer. The starting point of the curve is (**3**, **3**), and the ending point is (**6**, **6**). The length of the starting and ending control points is **5**, and the starting and ending angles of the control points are **45**°.

```
Sub CurveCreate()
 ActiveLayer.CreateCurveSegment(3, 3, 6, 6, 5, 45, 5, 45)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateCurveSegment2

Function **CreateCurveSegment2(***x1 As Double*, *y1 As Double*, *StartingControlPointX As Double*, *StartingControlPointY As Double*, *EndingControlPointX As Double*, *EndingControlPointY As Double*, *x2 As Double*, *y2 As Double***)** As Shape

Description

Member of Layer

The **CreateCurveSegment2** method uses specified control-point coordinates to create a curve segment at a specified location on a layer.

Parameter	Description
x1	Specifies the x-coordinate for the starting point of the curve segment. This value is measured in document units.
y1	Specifies the y-coordinate for the starting point of the curve segment. This value is measured in document units.
StartingControlPointX	Specifies the x-coordinate for the starting control point
StartingControlPointY	Specifies the y-coordinate for the starting control point
EndingControlPointX	Specifies the x-coordinate for the ending control point
EndingControlPointY	Specifies the y-coordinate for the ending control point
x2	Specifies the x-coordinate for the ending point of the curve segment. This value is measured in document units.
y2	Specifies the y-coordinate for the ending point of the curve segment. This value is measured in document units.

VBA example

The following VBA example creates a curve and adds text along the curve.

```
Sub Test()
 Dim sText As Shape, sPath As Shape
 Set sText = ActiveLayer.CreateArtisticText(0, 0, "Some Text")
 Set sPath = ActiveLayer.CreateCurveSegment2(0.6, 4.5, 0, 3, 5.2, 8.2, 5.3, 7)
 sText.Text.FitToPath sPath
 sText.Effects(1).TextOnPath.Placement = cdrCenterPlacement
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateCustomShape

Function **CreateCustomShape(***TypeID As String*, *Parameter() As Variant***)** As Shape

Description

Member of Layer

The **CreateCustomShape** method creates a custom shape on a layer.

Parameter	Description
TypeID	Specifies the Type ID of the desired custom shape
Parameter	Specifies the parameters for the desired custom shape

- For information on returning the properties of custom shapes, see the Shape.Custom property.

Creating tables

CorelDRAW supports the automation of tables through the use of custom shapes. Here is the syntax for creating a table:

Function **CreateCustomShape(**"Table", Left As Double, Top As Double, Right As Double, Bottom As Double, Columns As Long, Rows As Long**)** As Shape

Parameter	Description
Left	Specifies the distance from the left side of the table to the left side of the page frame. This value is measured in document units.
Top	Specifies the distance from the top of the table to the top of the page frame. This value is measured in document units.
Right	Specifies the distance from the right side of the table to the right side of the page frame. This value is measured in document units.
Bottom	Specifies the distance from the bottom of the table to the bottom of the page frame. This value is measured in document units.
Columns	Specifies the number of columns
Rows	Specifies the number of rows

For information on working with tables, see the TableShape class. The Shape.Custom property provides access to the properties and methods of the **TableShape** class.

VBA example

The following VBA example creates a document containing a calendar for the month of January 2009, highlighting the cell for January 1st.

```
Sub Test()
Dim s1 As Shape
CreateDocument
'Create a Table with 7 columns and 7 rows
Set s1 = ActiveLayer.CreateCustomShape("Table", 1, 10, 5, 7, 7, 6)
'Add Days of the Week to the each column in Row 1
s1.Custom.Cell(1, 1).TextShape.Text.Story = "Sun"
s1.Custom.Cell(2, 1).TextShape.Text.Story = "Mon"
s1.Custom.Cell(3, 1).TextShape.Text.Story = "Tue"
s1.Custom.Cell(4, 1).TextShape.Text.Story = "Wed"
s1.Custom.Cell(5, 1).TextShape.Text.Story = "Thu"
s1.Custom.Cell(6, 1).TextShape.Text.Story = "Fri"
s1.Custom.Cell(7, 1).TextShape.Text.Story = "Sat"
'Add a row above the first column
s1.Custom.AddRow 1
'Merge the cells in row
'Add the Title 'January'
'Center the text
s1.Custom.Rows(1).Cells.All.Merge
s1.Custom.Cell(1, 1).TextShape.Text.Story = "January"
s1.Custom.Cell(1, 1).TextShape.Text.Story.Words.All.Size = 22
s1.Custom.Cell(1, 1).TextShape.Text.Story.Alignment = _
cdrCenterAlignment
'Populate the calendar with dates
Dim i As Integer
For i = 1 To 31
'Insert the numbers starting at cell 13 (ie 1+12)
s1.Custom.Cells(i + 12).TextShape.Text.Story = i
Next i
```

```
'Merge the cells with no date
s1.Custom.Cells.Range(9, 10, 11, 12).Merge
'Place a fill in the cells containing no dates
Dim f1 As Fill
Set f1 = ActiveDocument.CreateFill("EmptyCellFill")
f1.ApplyUniformFill CreateRGBColor(220, 220, 220)
s1.Custom.Cells.Range(9, 10, 11, 12).ApplyFill f1
'Put a border around the tableshape
s1.Outline.Width = 0.05
'Put a border around row 1 of the tableshape
s1.Custom.Rows(1).Cells.All.Borders.All.Width = 0.05
'Put a green border around the January 1st cell
s1.Custom.Cells(10).Borders.All.Width = 0.05
s1.Custom.Cells.Range(10).Borders.All.Color.RGBAssign 0, 255, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateEllipse

Function **CreateEllipse(***Left As Double***,** *Top As Double***,** *Right As Double***,** *Bottom As Double***, [**StartAngle As Double = 90**], [**EndAngle As Double = 90**], [**Pie As Boolean = False**])** As Shape

Description

Member of Layer

The **CreateEllipse** method creates an ellipse shape at a specified location on a layer. The **CreateEllipse** method creates the ellipse by using the corners of its bounding box.

Parameter	Description
Left	Specifies, in document units, the distance from the left side of the ellipse to the left side of the page frame
Top	Specifies, in document units, the distance from the top of the ellipse to the top of the page frame
Right	Specifies, in document units, the distance from the right side of the ellipse to the right side of the page frame
Bottom	Specifies, in document units, the distance from the bottom of the ellipse to the bottom of the page frame
StartAngle	Specifies the degree of the start angle for the ellipse. This parameter is optional, and its default value is **90**.
EndAngle	Specifies the degree of the end angle of the ellipse. Altering the start angle changes the shape of the ellipse. This parameter is optional, and its default value is **90**.
Pie	Specifies whether to change the ellipse into a pie. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example creates a rectangle with a red ellipse inside it, both at the lower-left corner of the page.

```
Sub Test()
 Dim s As Shape
 Dim lr As Layer
 Set lr = ActiveLayer
 ActiveDocument.DrawingOriginX = -ActivePage.SizeWidth / 2
 ActiveDocument.DrawingOriginY = -ActivePage.SizeHeight / 2
 lr.CreateRectangle 0, 0, 3, 2
 Set s = lr.CreateEllipse(0, 0, 3, 2)
 s.Fill.UniformColor.RGBAssign 255, 0, 0 'Red
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateEllipse2

Function **CreateEllipse2(***CenterX As Double***,** *CenterY As Double***,** *Radius1 As Double***, [***Radius2 As Double***],** [StartAngle As Double = 90**], [**EndAngle As Double = 90**], [**Pie As Boolean = False**])** As Shape

Description

Member of Layer

The **CreateEllipse2** method creates an ellipse, at a specified location on a layer, by using the coordinates of the shape's center, the horizontal radius, and (if desired) the vertical radius.

Parameter	Description
CenterX	Specifies, in document units, the x-coordinate of the center point
CenterY	Specifies, in document units, the y-coordinate of the center point
Radius1	Specifies , in document units, the measurement from the x-coordinate of the center point to the circumference
Radius2	Specifies, in document units, the measurement from the y-coordinate of the center point to the circumference. This parameter is optional, and its default value is **0**.
StartAngle	Specifies the degree of the start angle for the ellipse. This parameter is optional, and its default value is **90**.
EndAngle	Specifies the degree of the end angle for the ellipse. This parameter is optional, and its default value is **90**.
Pie	Specifies whether the ellipse is a pie. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example creates a yellow circle in the middle of the page and a green ellipse above it.

```
Sub Test()
 Dim s As Shape
 Dim lr As Layer
 Set lr = ActiveLayer
 ActiveDocument.DrawingOriginX = 0
 ActiveDocument.DrawingOriginY = 0
 Set s = lr.CreateEllipse2(0, 0, 1)
 s.Fill.UniformColor.RGBAssign 255, 255, 0 'Yellow
 Set s = lr.CreateEllipse2(0, 2, 2, 1)
 s.Fill.UniformColor.RGBAssign 0, 255, 0 'Green
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateEllipseRect

Function **CreateEllipseRect(**Rect As Rect**, [**StartAngle As Double = 90**], [**EndAngle As Double = 90**], [**Pie As Boolean = False**])** As Shape

Description

Member of Layer

The **CreateEllipseRect** method creates an ellipse, at a specified location on a layer, by using the rectangular area specified.

Parameter	Description
Rect	Specifies the bounding box for the rectangular area
StartAngle	Specifies the degree of the start angle for the ellipse. This parameter is optional, and its default value is **90**.
EndAngle	Specifies the degree of the end angle for the ellipse. This parameter is optional, and its default value is **90**.
Pie	Specifies whether the ellipse is a pie. This parameter is optional, and its default value is **False**.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateFreeConnector

Function **CreateFreeConnector(***x1 As Double***,** *y1 As Double***,** *x2 As Double***,** *y2 As Double***)** As Shape

Description

Member of Layer

The **CreateFreeConnector** method creates, at a specified location on a layer, a connector line that is not connected to any shape.

- See also the Layer.CreateConnector method.

Parameter	Description
x1	Specifies the x-coordinate for the starting point of the connector line. This value is measured in document units.
y1	Specifies the y-coordinate for the starting point of the connector line. This value is measured in document units.
x2	Specifies the x-coordinate for the ending point of the connector line. This value is measured in document units.
y2	Specifies the y-coordinate for the ending point of the connector line. This value is measured in document units.

VBA example

The following VBA example creates a free connector line on the active layer in the active document.

```
Sub LayerConnector()
 ActiveLayer.CreateFreeConnector 2, 3, 6, 7
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateGridBoxes

Function **CreateGridBoxes(***Left As Double*, *Top As Double*, *Right As Double*, *Bottom As Double*, *Wide As Long*, *High As Long***)** As Shape

Description

Member of Layer

The **CreateGridBoxes** method creates a group of rectangles (similarly to using the **Graph Paper** tool) at a specified location on a layer.

Parameter	Description
Left	Specifies the distance from the left side of the first rectangle grid box to the left side of the page frame. This value is measured in document units.
Top	Specifies the distance from the top of the first rectangle grid box to the top of the page frame. This value is measured in document units.
Right	Specifies the distance from the right side of the first rectangle grid box to the right side of the page frame. This value is measured in document units.
Bottom	Specifies the distance from the bottom of the first rectangle grid box to the bottom of the page frame. This value is measured in document units.
Wide	Specifies the horizontal size of each rectangular grid box. This value is measured in document units.
High	Specifies the vertical measurement of the rectangle. This value is measured in document units.

VBA example

The following VBA example creates a series of rectangles on the active layer, resembling **2 × 3** graph paper.

```
Sub Test()
 ActiveLayer.CreateGridBoxes 0, 0, 5, 5, 2, 3
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateGuide

Function **CreateGuide(***x1 As Double*, *y1 As Double*, *x2 As Double*, *y2 As Double***)** As Shape

Description

Member of Layer

The **CreateGuide** method creates a guideline, at a specified location on a layer, by using two points.

Parameter	Description
x1	Specifies the x-coordinate for the first point that defines the guideline. This value is measured in document units.
y1	Specifies the y-coordinate for the first point that defines the guideline. This value is measured in document units.
x2	Specifies the x-coordinate for the second point that defines the guideline. This value is measured in document units.
y2	Specifies the y-coordinate for the second point that defines the guideline. This value is measured in document units.

VBA example

The following VBA example divides a page into **4 × 8** rectangles by using guidelines.

```
Sub Test()
 Const sx As Long = 4
 Const sy As Long = 8
 Dim i As Long
 Dim px As Double, py As Double
 px = ActivePage.SizeWidth
 py = ActivePage.SizeHeight
 For i = 0 To sx
  ActiveLayer.CreateGuide i * px / sx, 0, i * px / sx, py
 Next i
 For i = 0 To sy
  ActiveLayer.CreateGuide 0, i * py / sy, px, i * py / sy
 Next i
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateGuideAngle

Function **CreateGuideAngle(***x As Double***,** *y As Double***,** *Angle As Double***)** As Shape

Description

Member of Layer

The **CreateGuideAngle** method creates a guideline, at a specified location on a layer, by using a point and an angle.

Parameter	Description
x	Specifies the x-coordinate for the point that defines the guideline. This value is measured in document units.
y	Specifies the y-coordinate for the point that defines the guideline. This value is measured in document units.
Angle	Specifies the degree to which the guideline is slanted. Values range from **0** to **360** degrees.

VBA example

The following VBA example creates **10** guidelines that intersect at the center of the page.

```
Sub Test()
 Const an As Long = 10
 Dim i As Long
 ActiveDocument.DrawingOriginX = 0
 ActiveDocument.DrawingOriginY = 0
 For i = 0 To an - 1
  ActiveLayer.CreateGuideAngle 0, 0, i * 360 / an
 Next i
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateLinearDimension

Function **CreateLinearDimension(**Type As cdrLinearDimensionType**,** Point1 As SnapPoint**,** Point2 As SnapPoint**, [**TextCentered As Boolean = True**], [***TextX As Double***], [***TextY As Double***], [**Style As cdrDimensionStyle = cdrDimensionStyleDecimal**], [**Precision As Long = 2**], [**ShowUnits As Boolean = True**], [**Units As cdrDimensionLinearUnits = cdrDimensionUnitMM**], [**Placement As cdrDimensionPlacement = cdrDimensionWithinLine**], [**HorizontalText As Boolean = False**], [**BoxedText As Boolean = False**], [**LeadingZero As Boolean = True**], [***Prefix As String***], [***Suffix As String***], [**OutlineWidth As Double = -1**], [**Arrows As ArrowHead**], [**OutlineColor As Color**], [***TextFont As String***], [***TextSize As Double***], [**TextColor As Color**]) As Shape

Description

Member of Layer

The **CreateLinearDimension** method creates a linear dimension at a specified location on a layer.

Parameter	Description
Type	Specifies the type of linear dimension that is created
Point1	Specifies a snap point that represents one endpoint of the linear dimension
Point2	Specifies a snap point that represents one endpoint of the linear dimension
TextCentered	Specifies whether to center the text on the dimension line. **True** centers the text, while **False** leaves the text at the specified coordinates. This parameter is optional, and its default value is **True**.
TextX	Specifies the horizontal position of the text label. This parameter is optional, and its default value is **0**.
TextY	Specifies the vertical position of the text label. This parameter is optional, and its default value is **0**.
Style	Specifies the number-formatting style for the dimension value of the text label. This parameter is optional, and its default value is cdrDimensionStyleDecimal (**0**).
Precision	Specifies the number of significant digits for the dimension label to display after the decimal point, if using a decimal format for the dimension value. This parameter is optional, and its default value is **2**.
ShowUnits	Specifies whether to display the unit of measurement in the label. This parameter is optional, and its default value is **True**.
Units	Specifies the unit of measurement for the dimension value. This parameter is optional, and its default value is cdrDimensionUnitMM (**15**).
Placement	Specifies the placement of the text label relative to its dimension line. This parameter is optional, and its default value is cdrDimensionWithinLine (**1**).
HorizontalText	Specifies how to position dimension text. **True** rotates the dimension text horizontally, while **False** leaves the dimension text parallel to the dimension line. This parameter is optional, and its default value is **False**.
BoxedText	Specifies whether the dimension value has a visible border with the same properties as the dimension line — that is, whether the dimension label is enclosed by a rectangle. This parameter is optional, and its default value is **False**.
LeadingZero	Specifies whether the text value displays a leading zero for numbers that are less than **1.0** and for which a decimal format is used. This parameter is optional, and its default value is **True**.
Prefix	Specifies the prefix for the dimension label (that is, the text displayed before the dimension value). This parameter is optional.
Suffix	Specifies the suffix for the dimension label (that is, the text displayed after the dimension value). This parameter is optional.
OutlineWidth	Specifies the outline width. This parameter is optional, and its default value is **-1**.
Arrows	Specifies the desired arrowheads. This parameter is optional, and its default value is **Nothing**.
OutlineColor	Specifies the outline color. This parameter is optional, and its default value is **Nothing**.

TextFont	Specifies the text font. This parameter is optional.
TextSize	Specifies the text size. This parameter is optional, and its default value is **0**.
TextColor	Specifies the text color. This parameter is optional, and its default value is **Nothing**.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateLineSegment

Function **CreateLineSegment(***StartX As Double*, *StartY As Double*, *EndX As Double*, *EndY As Double***)** As Shape

Description

Member of Layer

The **CreateLineSegment** method creates a curve comprised of a single line segment at a specified location on a layer.

Parameter	Description
StartX	Specifies the x-coordinate for the starting point of the line segment. This value is measured in document units.
StartY	Specifies the y-coordinate for the starting point of the line segment. This value is measured in document units.
EndX	Specifies the x-coordinate for the ending point of the line segment. This value is measured in document units.
EndY	Specifies the y-coordinate for the ending point of the line segment. This value is measured in document units.

VBA example

The following VBA example creates a line segment on the active layer.

```
Sub Test()
 ActiveLayer.CreateLineSegment 1, 2, 5, 6
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateOLEObject

Function **CreateOLEObject(***ObjectID As String***, [**DisplayAsIcon As Boolean = False**], [***Caption As String***], [***Icon As Variant***])** As Shape

Description

Member of Layer

The **CreateOLEObject** method creates a new OLE object on a layer.

Parameter	Description
ObjectID	Specifies the ID of the OLE object
DisplayAsIcon	Specifies whether to display the OLE object as an icon. This parameter is optional, and its default value is **False**.
Caption	Specifies a caption for the OLE object. This parameter is optional.
Icon	Specifies an icon for the OLE object. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateOLEObjectFromFile

Function **CreateOLEObjectFromFile(***FileName As String***, [**Link As Boolean = False**], [**DisplayAsIcon As Boolean = False**], [***Caption As String***], [***Icon As Variant***])** As Shape

Description

Member of Layer

The **CreateOLEObjectFromFile** method creates a new OLE object from file.

Parameter	Description
FileName	Specifies the filename of the OLE object
Link	Specifies a link to the OLE object. This parameter is optional, and its default value is **False**.
DisplayAsIcon	Specifies whether to display the OLE object as an icon. This parameter is optional, and its default value is **False**.
Caption	Specifies a caption for the OLE object. This parameter is optional.
Icon	Specifies an icon for the OLE object. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateParagraphText

Function **CreateParagraphText(***Left As Double***,** *Top As Double***,** *Right As Double***,** *Bottom As Double***, [***Text As String***], [**LanguageID As cdrTextLanguage = cdrLanguageNone**], [**CharSet As cdrTextCharSet = cdrCharSetMixed**], [***Font As String***], [***Size As Single***], [**Bold As cdrTriState = cdrUndefined**], [**Italic As cdrTriState = cdrUndefined**], [**Underline As cdrFontLine = cdrMixedFontLine**], [**Alignment As cdrAlignment = cdrMixedAlignment**]) As Shape

Description

Member of Layer

The **CreateParagraphText** method creates a paragraph-text object at a specified location on a layer.

Parameter	Description
Left	Specifies, in document units, the distance from the left side of the paragraph-text frame to the left side of the page frame
Top	Specifies, in document units, the distance from the top side of the paragraph-text frame to the top of the page frame
Right	Specifies, in document units, the distance from the right side of the paragraph-text frame to the right side of the page frame
Bottom	Specifies, in document units, the distance from the bottom of the paragraph-text frame to the bottom of the page frame
Text	Specifies the content of the newly created paragraph text. The value of the **Text** parameter becomes the actual text created with the **CreateParagraphText** method. This parameter is optional.
LanguageID	Specifies the language. This parameter is optional, and its default value is cdrLanguageNone (**0**).
CharSet	Specifies the character set. This parameter is optional, and its default value is cdrCharSetMixed (**-1**).
Font	Specifies the font. This parameter is optional.
Size	Specifies the font size. This parameter is optional, and its default value is **0**.
Bold	Specifies whether to apply boldface. This parameter is optional, and its default value is cdrUndefined (**-2**).
Italic	Specifies whether to apply italics. This parameter is optional, and its default value is cdrUndefined (**-2**).
Underline	Specifies an underline to apply. This parameter is optional, and its default value is cdrMixedFontLine (**7**).
Alignment	Specifies the alignment. This parameter is optional, and its default value is cdrMixedAlignment (**6**).

VBA example

The following VBA example creates a paragraph-text object, formatted in boldface Times New Roman font.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateParagraphText(0, 0, 4, 4, "Paragraph Text", , , _
  "Times New Roman", 24, cdrTrue, cdrTrue, , cdrCenterAlignment)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateParagraphTextWide

Function **CreateParagraphTextWide(***Left As Double***,** *Top As Double***,** *Right As Double***,** *Bottom As Double***, [***Text As String***], [**LanguageID As cdrTextLanguage = cdrLanguageNone**], [**CharSet As cdrTextCharSet = cdrCharSetMixed**], [***Font As String***], [***Size As Single***], [**Bold As cdrTriState = cdrUndefined**], [**Italic As cdrTriState = cdrUndefined**], [**Underline As cdrFontLine = cdrMixedFontLine**], [**Alignment As cdrAlignment = cdrMixedAlignment**])** As Shape

Description

Member of Layer

The **CreateParagraphTextWide** method creates paragraph text, in Unicode, at a specified location on a layer.

Parameter	Description
Left	Specifies the distance from the left side of the paragraph-text frame to the left side of the page frame
Top	Specifies the distance from the top side of the paragraph-text frame to the top of the page frame
Right	Specifies the distance from the right side of the paragraph-text frame to the right side of the page frame
Bottom	Specifies the distance from the bottom of the paragraph-text frame to the bottom of the page frame
Text	Specifies the text. This parameter is optional.
LanguageID	Specifies the language. This parameter is optional, and its default value is cdrLanguageNone (**0**).
CharSet	Specifies the character set. This parameter is optional, and its default value is cdrCharSetMixed (**-1**).
Font	Specifies the font. This parameter is optional.
Size	Specifies the font size. This parameter is optional, and its default value is **0**.
Bold	Specifies whether to apply boldface. This parameter is optional, and its default value is cdrUndefined (**-2**).
Italic	Specifies whether to apply italics. This parameter is optional, and its default value is cdrUndefined (**-2**).
Underline	Specifies an underline to apply. This parameter is optional, and its default value is cdrMixedFontLine (**7**).
Alignment	Specifies the alignment. This parameter is optional, and its default value is cdrMixedAlignment (**6**).

VBA example

The following VBA example creates a paragraph-text object in Greek.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateParagraphTextWide(0, 3, 3, 0, Chr(216) & _
  Chr(231) & Chr(241) & Chr(233) & Chr(243), cdrGreek, cdrCharSetGreek, _
  "Times New Roman", 24)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreatePolygon

Function **CreatePolygon(***Left As Double*, *Top As Double*, *Right As Double*, *Bottom As Double*, *Sides As Long*, **[**SubPaths As Long = 1**], [**Complexity As Long = 1**], [**Star As Boolean = False**], [**StarComplexity As Long = 50**], [**MaxComplexity As Long = 100**])** As Shape

Description

Member of Layer

The **CreatePolygon** method creates a new polygon at a specified location on a layer.

Parameter	Description
Left	Specifies, in document units, the distance from the left side of the polygon to the left side of the page frame
Top	Specifies, in document units, the distance from the top of the polygon to the top of the page frame
Right	Specifies, in document units, the distance from the right side of the polygon to the right side of the page frame
Bottom	Specifies the distance from the bottom of the polygon to the bottom of the page frame. This value is measured in document units.
Sides	Specifies the number of sides in the polygon, from **3** to **500**.
SubPaths	Specifies the number of subpaths in the polygon. This parameter is optional, and its default value is **1**.
Complexity	This parameter is optional, and its default value is **1**.
Star	Specifies whether the polygon appears as a star shape. This parameter is optional, and its default value is **False**.
StarComplexity	This parameter is optional, and its default value is **50**.
MaxComplexity	This parameter is optional, and its default value is **100**.

VBA example

The following VBA example creates a star on the active layer.

```
Sub Test()
 ActiveLayer.CreatePolygon 0, 3, 3, 0, 5, 1, 1, True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreatePolygon2

Function **CreatePolygon2(***CenterX As Double***,** *CenterY As Double***,** *Radius As Double***,** *Sides As Long***, [***Angle As Double***], [***InnerRadius As Double***],** [Star As Boolean = False**], [***Sharpness As Long***])** As Shape

Description

Member of Layer

The **CreatePolygon2** method creates a symmetical polygon, at a specified location on a layer, by using a center point and radius.

Parameter	Description
CenterX	Specifies the x-coordinate of the center point
CenterY	Specifies the y-coordinate of the center point
Radius	Specifies the radius of the polygon
Sides	Specifies the number of sides in the polygon, from **3** to **500**.
Angle	This parameter is optional, and its default value is **0**.
InnerRadius	This parameter is optional, and its default value is **0**.
Star	Specifies whether the polygon appears as a star shape. This parameter is optional, and its default value is **False**.
Sharpness	Specifies the sharpness of a star-shaped polygon. The maximum value of this property is determined by the number of sides that the star contains. This parameter is optional, and its default value is **0**.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateRectangle

Function **CreateRectangle(***Left As Double***,** *Top As Double***,** *Right As Double***,** *Bottom As Double***, [***CornerUL As Long***], [***CornerUR As Long***], [***CornerLR As Long***], [***CornerLL As Long***])** As Shape

Description

Member of Layer

The **CreateRectangle** method creates a rectangle at a specified location on a layer.

This method uses the coordinates of the upper-left and lower-right corners of the rectangle as parameters and, optionally, the roundness of each corner.

Parameter	Description
Left	Specifies the distance from the left side of the rectangle to the left side of the page frame. This value is measured in document units.
Top	Specifies the distance from the top of the rectangle to the top of the page frame. This value is measured in document units.
Right	Specifies the distance from the right side of the rectangle to the right side of the page frame. This value is measured in document units.
Bottom	Specifies the distance from the bottom of the rectangle to the bottom of the page frame. This value is measured in document units.
CornerUL	Specifies the roundness measurement of the upper-left corner of the rectangle. Values range between **0** and **100**. This parameter is optional, and its default value is **0**.
CornerUR	Specifies the roundness measurement of the upper-right corner of the rectangle. Values range between **0** and **100**. This parameter is optional, and its default value is **0**.
CornerLR	Specifies the roundness measurement of the lower-right corner of the rectangle. Values range between **0** and **100**. This parameter is optional, and its default value is **0**.
CornerLL	Specifies the roundness measurement of the lower-left corner of the rectangle. Values range between **0** and **100**. This parameter is optional, and its default value is **0**.

- When you round the corners of a rectangle, CorelDRAW splits each corner node in two and draws an arc between each of these two new nodes.

VBA example

The following VBA example creates a 5" square with **20**% corner roundness (that is, a corner radius of 0.5").

```
Sub Test()
 ActiveLayer.CreateRectangle 0, 0, 5, 5, 20, 20, 20, 20
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateRectangle2

Function **CreateRectangle2(***x As Double***,** *y As Double***,** *Width As Double***,** *Height As Double***, [***RadiusUL As Double***], [***RadiusUR As Double***], [***RadiusLR As Double***], [***RadiusLL As Double***])** As Shape

Description

Member of Layer

The **CreateRectangle2** method creates a rectangle, at a specified location on a layer, by using the coordinates for the upper-left corner, the width, the height, and the corner radii.

Parameter	Description
x	Specifies, in document units, the horizontal position of the upper-left corner coordinate
y	Specifies, in document units, the vertical position of the upper-left corner coordinate
Width	Specifies the horizontal measurement in document units
Height	Specifies the vertical measurementin document units
RadiusUL	Specifies the actual corner radius measurement of the upper-left corner. This parameter is optional, and its default value is **0**.
RadiusUR	Specifies the actual corner radius measurement of the upper-right corner. This parameter is optional, and its default value is **0**.
RadiusLR	Specifies the actual corner radius measurement of the lower-right corner. This parameter is optional, and its default value is **0**.
RadiusLL	Specifies the actual corner radius measurement of the lower-left corner. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example creates a blend between two rectangles. The intermediate blend objects are rotated by 360° during the progression.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Set s1 = ActiveLayer.CreateRectangle2(0, 0, 3, 1)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 Set s2 = ActiveLayer.CreateRectangle2(4, 4, 3, 1)
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 With s2.CreateBlend(s1).Blend
  .Loop = False
  .Angle = 360
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateRectangleRect

Function **CreateRectangleRect(**Rect As Rect**, [**RadiusUL As Double = 0**], [**RadiusUR As Double = 0**], [**RadiusLR As Double = 0**], [**RadiusLL As Double = 0**])** As Shape

Description

Member of Layer

The **CreateRectangleRect** method creates a rectangle shape, at a specified location on a layer, by using the specified rectangular area.

Parameter	Description
Rect	Specifies the bounding box for the rectangular area.
RadiusUL	Specifies the actual corner radius measurement of the upper-left corner. This parameter is optional, and its default value is **0**.
RadiusUR	Specifies the actual corner radius measurement of the upper-right corner. This parameter is optional, and its default value is **0**.
RadiusLR	Specifies the actual corner radius measurement of the lower-right corner. This parameter is optional, and its default value is **0**.
RadiusLL	Specifies the actual corner radius measurement of the lower-left corner. This parameter is optional, and its default value is **0**.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateRightAngleConnector

Function **CreateRightAngleConnector(**Start As SnapPoint**,** End As SnapPoint**, [***CornerRadius As Double***])** As Shape

Description

Member of Layer

The **CreateRightAngleConnector** method creates a right-angled connector line.

Parameter	Description
Start	Specifies the starting point of the connector-line object
End	Specifies the ending point of the connector-line object
CornerRadius	Specifies the corner radius. This parameter is optional, and its default value is **0**.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateSpiral

Function **CreateSpiral(***Left As Double*, *Top As Double*, *Right As Double*, *Bottom As Double*, *NumRevolutions As Long*, SpiralType As cdrSpiralType, *GrowthRate As Long***)** As Shape

Description

Member of Layer

The **CreateSpiral** method creates a spiral at a specified location on a layer.

Parameter	Description
Left	Specifies, in document units, the distance from the left side of the spiral to the left side of the page frame
Top	Specifies, in document units, the distance from the top of the spiral to the top of the page frame
Right	Specifies, in document units, the distance from the right side of the spiral to the right side of the page frame
Bottom	Specifies, in document units, the distance from the bottom of the spiral to the bottom of the page frame
NumRevolutions	Specifies the number of revolutions in the spiral
SpiralType	Specifies the type of spiral to create, and returns cdrSpiralType
GrowthRate	Specifies the factor by which to increase the distance between revolutions in a logarithmic spiral. Values range from **1** to **100**.

VBA example

The following VBA example creates a logarithmic spiral on the active layer. The spiral has four revolutions with a growth factor of **100** within each revolution.

```
Sub Test()
 ActiveLayer.CreateSpiral 0, 0, 5, 5, 4, cdrLogarithmic, 100
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CreateSymbol

Function **CreateSymbol(***x As Double***,** *y As Double***,** *SymbolName As String***, [**Library As SymbolLibrary**])** As Shape

Description

Member of Layer

The **CreateSymbol** method creates an instance of a symbol at a specified location on a layer.

Parameter	Description
x	Specifies the x-coordinate at which to place the symbol
y	Specifies the y-coordinate at which to place the symbol
SymbolName	Specifies the name of the symbol
Library	Specifies the name of the library. This parameter is optional, and its default value is **Nothing**.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.CustomCommand

Function **CustomCommand(***ComponentID As String***,** *CommandID As String***,** *Parameter() As Variant***)** As Variant

Description

Member of Layer

The **CustomCommand** method executes a layer-specific command provided by a component. For example, you can use the **CustomCommand** method to execute table commands by using the **Table...** classes.

Parameter	Description
ComponentID	Specifies the ID of the desired component
CommandID	Specifies the ID of the desired command
Parameter	Specifies the desired parameters

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Delete

Sub **Delete()**

Description

Member of Layer

The **Delete** method removes a layer and its contents.

VBA example

The following VBA example deletes the layer named **Layer 1** on the active page, as well as its contents.

```
Sub Test()
 ActivePage.Layers("Layer 1").Delete
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Editable

Property **Editable** As Boolean

Description

Member of Layer

The **Editable** property returns or specifies whether a layer is editable (that is, unlocked).

If the **Editable** property of a layer is **True**, the layer and its contents are editable.

VBA example

The following VBA example locks the active layer, preventing both the layer and its contents from being edited.

```
Sub Test()
 ActiveLayer.Editable = False
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.FindShape

Function **FindShape([***Name As String***], [**Type As cdrShapeType = cdrNoShape**], [***StaticID As Long***], [**Recursive As Boolean = True**])** As Shape

Description

Member of Layer

The **FindShape** method locates a shape with specified properties on a layer. If the shape cannot be found, an empty reference (nothing) is returned.

Parameter	Description
Name	Specifies the name of the shape for which to search. This parameter is optional.
Type	Specifies the shape type, and returns cdrShapeType. This parameter is optional, and its default value is cdrNoShape (**0**).
StaticID	Specifies the shape's unique ID. This parameter is optional, and its default value is **0**.
Recursive	Specifies whether to iterate through all shapes. This parameter is optional, and its default value is **True**.

VBA example

The following VBA example finds a rectangle named **Frame** and selects it.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.FindShape(Name:="Frame", Type:=cdrRectangleShape)
 If s Is Nothing Then
  MsgBox "The rectangle 'Frame' cannot be found on layer " & ActiveLayer.Name
 Else
  s.CreateSelection
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.FindShapes

Function **FindShapes([***Name As String***], [**Type As cdrShapeType = cdrNoShape**], [**Recursive As Boolean = True**])** As ShapeRange

Description

Member of Layer

The **FindShapes** method locates all shapes on a layer that have the specified properties. It returns a ShapeRange object containing all shapes found.

Parameter	Description
Name	Specifies the name of the shape for which to search. This parameter is optional.
Type	Specifies the shape type, and returns cdrShapeType. This parameter is optional, and its default value is cdrNoShape (**0**).
Recursive	Specifies whether to iterate through all shapes. This parameter is optional, and its default value is **True**.

VBA example

The following VBA example finds all rectangles on the current layer and fills them with a red uniform fill.

```
Sub Test()
 Dim sr As ShapeRange
 Set sr = ActiveLayer.FindShapes(Type:=cdrRectangleShape)
 If sr.Count <> 0 Then
  sr.ApplyUniformFill CreateRGBColor(255, 0, 0)
 Else
  MsgBox "There are no rectangles on the current layer"
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Import

Sub Import(*FileName As String*, [*Filter As* cdrFilter = cdrAutoSense], [*Options As StructImportOptions*])

Description

Member of Layer

The **Import** method imports shapes from a disk file and places them on a specified layer.

- The imported shapes are selected after the method is executed. You can use the Document.Selection function to access those shapes.

Parameter	Description
FileName	Specifies the full path name of the disk file that contains the shapes to be imported. For example, the following **FileName** value represents a CorelDRAW document that is stored at the root of the C drive and that is named **Importing.cdr**: **C:\Importing.cdr**
Filter	Specifies the import filter, and returns cdrFilter. This parameter is optional, and its default value is cdrAutoSense (**0**).
Options	Specifies additional parameters for the import. This parameter is optional, and its default value is **Nothing**.

VBA example

The following VBA example imports the file **mygraphic.cmx** (stored at the root of C) to the active layer.

```
Sub Test()
 ActiveLayer.Import "C:\MyGraphic.cmx"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.ImportEx

Function **ImportEx(***FileName As String***, [**Filter As cdrFilter = cdrAutoSense**], [**Options As StructImportOptions**]) As** ImportFilter

Description

Member of Layer

The **ImportEx** method imports a file and returns an ImportFilter object.

Parameter	Description
FileName	Specifies the file to import
Filter	Specifies the import filter, and returns cdrFilter. This parameter is optional, and its default value is cdrAutoSense (**0**).
Options	Specifies additional parameters for the import. This parameter is optional, and its default value is **Nothing**.

VBA example

The following VBA example imports the specified Corel Presentation Exchange (CMX) file to the active layer.

```
Sub Test()
 Dim im As ImportFilter
 Set im = ActiveLayer.ImportEx(SetupPath & "Draw\CustomMediaStrokes\Arrow.cmx")
 im.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Index

Property **Index** As Long

Description

Member of Layer

The **Index** property returns the index number of a layer within a Layers collection.

The **Index** property returns a read-only value.

VBA example

The following VBA example adds a text string named **Layer:** and the index number of each layer to the lower-left corner of each layer in the active page.

```
Sub Test()
 Dim l As Layer
 For Each l In ActivePage.Layers
  l.CreateArtisticText 0, 0, "Layer:" & l.Index, , , 10
 Next l
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.IsDesktopLayer

Property **IsDesktopLayer** As Boolean

Description

Member of Layer

The **IsDesktopLayer** property returns **True** if the given layer is the desktop layer.

The **IsDesktopLayer** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.IsGridLayer

Property **IsGridLayer** As Boolean

Description

Member of Layer

The **IsGridLayer** property returns **True** if the given layer is the grid layer.

The **IsGridLayer** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.IsGuidesLayer

Property **IsGuidesLayer** As Boolean

Description

Member of Layer

The **IsGuidesLayer** property returns **True** if the given layer is the guideline layer.

The **IsGuidesLayer** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.IsSpecialLayer

Property **IsSpecialLayer** As Boolean

Description

Member of Layer

The **IsSpecialLayer** property returns **True** if the given layer is a special layer (such as a guideline, desktop, or grid).

The **IsSpecialLayer** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Master

Property **Master** As Boolean

Description

Member of Layer

The **Master** property returns or specifies whether the layer is a master layer or a local layer.

If the **Master** property is **True**, the layer acts as a master layer for the entire document, and its contents appear on every page in that document.

VBA example

The following VBA example makes the active layer a master layer, ensuring that its content appears on every page throughout the document.

```
Sub Test()
 ActiveLayer.Master = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.MasterLayer

Property **MasterLayer** As Layer

Description

Member of Layer

The **MasterLayer** property returns the corresponding layer from the master page.

The **MasterLayer** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.MasterProperties

Property **MasterProperties** As Properties

Description

Member of Layer

The **MasterProperties** property returns the Properties collection, which allows you to specify and manipulate custom data for a given layer on all pages of the document.

The **MasterProperties** property returns a read-only value.

VBA example

The following VBA example creates **100** shapes and stores their IDs in the active layer for future reference.

```
Sub CreateAndStoreShapes()
 Dim i As Long
 Dim x As Double, y As Double, r As Double
 Dim MaxX As Double, MaxY As Double, MaxR As Double
 Dim s As Shape, Num As Long
 MaxX = ActivePage.SizeWidth
 MaxY = ActivePage.SizeHeight
 MaxR = 1
 Num = 100
 ActiveLayer.Properties("ShapeArray", 0) = Num ' Store the total number of shapes
 For i = 1 To Num
  x = Rnd() * MaxX
  y = Rnd() * MaxY
  r = Rnd() * MaxR
  Set s = ActiveLayer.CreateEllipse2(x, y, r)
  s.Fill.UniformColor.RGBAssign Rnd() * 256, Rnd() * 256, Rnd() * 256
  ActiveLayer.Properties("ShapeArray", i) = s.StaticID ' Store the current shape's ID number
 Next i
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.MoveAbove

Sub **MoveAbove(**Layer As Layer**)**

Description

Member of Layer

The **MoveAbove** method changes the stacking order of a specified layer by placing another layer above it, thereby rearranging them.

Parameter	Description
Layer	Specifies the layer above which to move another layer

VBA example

The following VBA example moves the active layer and places it above the layer named **Layer 1**.

```
Sub Test()
 ActiveLayer.MoveAbove ActivePage.Layers("Layer 1")
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.MoveBelow

Sub **MoveBelow(**Layer As Layer**)**

Description

Member of Layer

The **MoveBelow** method changes the stacking order of a specified layer by placing another layer below it, thereby rearranging them.

Parameter	Description
Layer	Specifies the layer below which to move another layer

VBA example

The following VBA example moves the current layer and places it below the layer named **Layer 1**.

```
Sub Test()
 ActiveLayer.MoveBelow ActivePage.Layers("Layer 1")
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Name

Property **Name** As String

Description

Member of Layer

The **Name** property returns or specifies the name of a layer.

VBA example

The following VBA example displays, in a message box, the name of the active layer.

```
Sub Test()
 MsgBox "Active Layer is " & ActiveLayer.Name
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.OverrideColor

Property **OverrideColor** As Boolean

Description

Member of Layer

The **OverrideColor** property returns or specifies whether to use the override color of a layer to draw object outlines in Normal view mode.

VBA example

The following VBA example sets the color-override feature to **True** in the active layer and the override color to RGB Red.

```
Sub Test()
 ActiveLayer.OverrideColor = True
 ActiveLayer.Color.RGBAssign 255, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Page

Property **Page** As Page

Description

Member of Layer

The **Page** property returns the page on which a layer is located.

The **Page** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Parent

Property **Parent** As Layers

Description

Member of Layer

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Paste

Function **Paste()** As Shape

Description

Member of Layer

The **Paste** method places the Clipboard contents on a layer.

VBA example

The following VBA example copies the shapes from the current page to the Clipboard, adds three empty pages to the end of the document, and pastes the objects on the active layer of each new page.

```
Sub Test()
 Dim p As Page
 Dim i As Long, idx As Long
 ActivePage.Shapes.All.Copy
 Set p = ActiveDocument.AddPages(3)
 idx = p.Index
 For i = idx To ActiveDocument.Pages.Count
 Set p = ActiveDocument.Pages(i)
 p.Activate
 p.ActiveLayer.Paste
 Next i
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.PasteEx

Function **PasteEx(**Options As StructPasteOptions**)** As ShapeRange

Description

Member of Layer

The **PasteEx** method places the Clipboard contents on a layer and returns the range of objects that were pasted. The optional parameter **Options** allows for various settings to be specified.

Parameter	Description
Options	Specifies any settings. This parameter is optional, and its default value is **Nothing**.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.PasteSpecial

Function **PasteSpecial(***FormatName As String***, [**PasteLink As Boolean = False**], [**DisplayAsIcon As Boolean = False**], [***Caption As String***], [***Icon As Variant***])** As Boolean

Description

Member of Layer

The **Paste** method places the Clipboard contents in a specified format on a layer.

Parameter	Description
FormatName	Specifies the format
PasteLink	Specifies whether to paste a link to the contents. This parameter is optional, and its default value is **False**.
DisplayAsIcon	Specifies whether to display the contents as an icon. This parameter is optional, and its default value is **False**.
Caption	Specifies a caption for the contents. This parameter is optional.
Icon	Specifies an icon for the contents. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Printable

Property **Printable** As Boolean

Description

Member of Layer

The **Printable** property returns or specifies whether a layer is printable.

If the **Printable** property of a layer is **True**, the layer and its contents are printable.

VBA example

The following VBA example makes the **Grid** layer on the master page printable.

```
Sub Test()
 ActiveDocument.Pages(0).Layers("Grid").Printable = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Properties

Property **Properties** As Properties

Description

Member of Layer

The **Properties** property returns the Properties collection, which lets you specify and manipulate the custom data that is associated with a given layer that belongs to a specified page only.

The **Properties** property returns a read-only value.

VBA example

The following VBA example creates **100** shapes and stores their IDs in the active layer for future reference.

```
Sub CreateAndStoreShapes()
 Dim i As Long
 Dim x As Double, y As Double, r As Double
 Dim MaxX As Double, MaxY As Double, MaxR As Double
 Dim s As Shape, Num As Long
 MaxX = ActivePage.SizeWidth
 MaxY = ActivePage.SizeHeight
 MaxR = 1
 Num = 100
 ActiveLayer.Properties("ShapeArray", 0) = Num ' Store the total number of shapes
 For i = 1 To Num
  x = Rnd() * MaxX
  y = Rnd() * MaxY
  r = Rnd() * MaxR
  Set s = ActiveLayer.CreateEllipse2(x, y, r)
  s.Fill.UniformColor.RGBAssign Rnd() * 256, Rnd() * 256, Rnd() * 256
  ActiveLayer.Properties("ShapeArray", i) = s.StaticID ' Store the current shape's ID number
 Next i
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.SelectableShapes

Property **SelectableShapes** As Shapes

Description

Member of Layer

The **SelectableShapes** property returns a collection of all selectable shapes on a layer.

The **SelectableShapes** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Shapes

Property **Shapes** As Shapes

Description

Member of Layer

The **Shapes** property returns a collection of all shapes on a specified layer.

The **Shapes** property returns a read-only value.

VBA example

The following VBA example deletes the active layer and moves all shapes on the active layer to the next layer on the page.

```
Sub Test()
 Dim Target As Layer
 Dim s As Shape
 Dim idx As Long
 If ActivePage.Layers.Count = 1 Then
  MsgBox "Cannot delete a single layer"
 End If
 If ActiveLayer.Shapes.Count Then
  idx = 1 ' Determining the index number of the active layer
  For Each Target In ActivePage.Layers
   If Target Is ActiveLayer Then Exit For
     idx = idx + 1
  Next Target
  ' Finding the index number of the target layer
  If idx = 1 Then idx = 2 Else idx = idx - 1
  Set Target = ActivePage.Layers(idx)
  ActiveDocument.ClearSelection
  ActiveLayer.Shapes.All.AddToSelection
  ActiveSelection.Layer = Target
 End If
 ActiveLayer.Delete
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layer.TreeNode

Property **TreeNode** As TreeNode

Description

Member of Layer

The **TreeNode** property returns a tree-node object corresponding to a given layer.

The **TreeNode** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Layer.Visible

Property **Visible** As Boolean

Description

Member of Layer

The **Visible** property returns or specifies the visibility status of a layer and of all shapes on that layer.

If the **Visible** property is set the **True**, the layer is visible.

VBA example

The following VBA example shows a warning message if the current layer is invisible.

```
Sub Test()
 If Not ActiveLayer.Visible Then
  MsgBox "The Current Layer is invisible!"
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layers

Properties

Description

The **Layers** class represents a collection of document layers (or Layer objects).

Copyright 2014 Corel Corporation. All rights reserved.

Layers.Application

Property **Application** As Application

Description

Member of Layers

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Layers.Bottom

Property **Bottom** As Layer

Description

Member of Layers

The **Bottom** property returns the bottommost layer on a page.

The **Bottom** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Layers.Count

Property **Count** As Long

Description

Member of Layers

The **Count** property returns the number of layers available.

- To access master layers, you must access the Layers collection of the master page. The master page is accessible as **Document.Pages(0)**.

The **Count** property returns a read-only value.

VBA example

The following VBA example displays the number of master layers in the active document.

```
Sub Test()
 MsgBox "Document contains " & ActiveDocument.Pages(0).Layers.Count & " layer(s)"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layers.Find

Function **Find(***LayerName As String***)** As Layer

Description

Member of Layers

The **Find** method returns a layer by name.

Parameter	Description
LayerName	Specifies the name of the layer for which to search

Copyright 2014 Corel Corporation. All rights reserved.

Layers.Item

Property **Item(***IndexOrName As Variant***)** As Layer

Description

Member of Layers

The **Item** property returns the layer associated with a specified index number. It is the default property of the Layers class.

You can access layers by their index number or name.

The **Item** property returns a read-only value.

Parameter	Description
IndexOrName	Specifies the layer by its index number or name: • **Index** — Specifies the preset placeholder that uniquely identifies each member of the **Layers** collection • **Name** — Specifies the string that uniquely identifies each layer

VBA example

The following VBA example creates a rectangle on the topmost layer of the first page of the active document, and it also creates a horizontal line on the **Guides** layer.

```
Sub Test()
 Dim d As Document
 Dim p As Page
 Set d = ActiveDocument
 Set p = d.Pages(1)
 p.Layers(1).CreateRectangle 0, 0, 3, 3
 d.Pages(0).Layers("Guides").CreateLineSegment 0, 4, 5, 4
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Layers.Parent

Property **Parent** As Page

Description

Member of Layers

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Layers.Top

Property **Top** As Layer

Description

Member of Layers

The **Top** property returns the topmost layer on a page.

The **Top** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

LocalizableString

Properties Methods

Description

The **LocalizableString** class represents text strings that can appear in one or more languages. For example, document metadata, such as keywords and titles, can be specified in multiple languages.

Copyright 2014 Corel Corporation. All rights reserved.

LocalizableString.Clear

Sub **Clear()**

Description

Member of LocalizableString

The **Clear** method clears the strings for all languages.

Copyright 2014 Corel Corporation. All rights reserved.

LocalizableString.DefaultLangString

Property **DefaultLangString** As String

Description

Member of LocalizableString

The **DefaultLangString** property returns or specifies the default language of text strings.

Copyright 2014 Corel Corporation. All rights reserved.

LocalizableString.GetLangString

Function **GetLangString(***Language As String***)** As String

Description

Member of LocalizableString

The **GetLangString** method returns the string for the specified language. If the string is missing, the method returns the default language string or the first available string in other languages.

Parameter	Description
Language	Specifies the language of the string

Copyright 2014 Corel Corporation. All rights reserved.

LocalizableString.GetLanguages

Function **GetLanguages()** As String

Description

Member of LocalizableString

The **GetLanguages** method returns the list of languages in which the strings are available.

Copyright 2014 Corel Corporation. All rights reserved.

LocalizableString.HasDefaultLangString

Property **HasDefaultLangString** As Boolean

Description

Member of LocalizableString

The **HasDefaultLangString** property checks whether there is a default language string specified. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

LocalizableString.HasDefaultLangStringOnly

Property **HasDefaultLangStringOnly** As Boolean

Description

Member of LocalizableString

The **HasDefaultLangStringOnly** property checks whether there is only a default language string specified. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

LocalizableString.HasLangString

Function **HasLangString(***Language As String***)** As Boolean

Description

Member of LocalizableString

The **HasLangString** method checks if the string exists for the specified language.

Parameter	Description
Language	Specifies the language of the string

Copyright 2014 Corel Corporation. All rights reserved.

LocalizableString.HasNonDefaultLangStrings

Property **HasNonDefaultLangStrings** As Boolean

Description

Member of LocalizableString

The **HasNonDefaultLangStrings** property checks whether there are any other language strings specified in addition to the default language string. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

LocalizableString.IsEmpty

Property **IsEmpty** As Boolean

Description

Member of LocalizableString

The **IsEmpty** property returns True if there is at least one language string specified. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

LocalizableString.SetLangString

Function **SetLangString**(Language As String, Value As String)

Description

Member of LocalizableString

The **SetLangString** method sets the string for the specified language.

Parameters	Description
Language	Specifies the language of the string
Value	Specifies the text

Copyright 2014 Corel Corporation. All rights reserved.

Metadata

Properties

Description

The **Metadata** class represents document metadata.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.Author

Property **Author** As String

Description

Member of Metadata

The **Author** property returns or specifies the name of the creator of a document.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.Copyright

Property **Copyright** As String

Description

Member of Metadata

The **Copyright** property returns or specifies the copyright information for a document.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.DocID

Property **DocID** As String

Description

Member of Metadata

The **DocID** property returns or specifies a unique ID for the contents of a document.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.DocLanguage

Property **DocLanguage** As cdrTextLanguage

Description

Member of Metadata

The **DocLanguage** property returns or specifies the language for which a document is designed.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.Keywords

Property **Keywords** As String

Description

Member of Metadata

The **Keywords** property returns or specifies the keywords for a document.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.LastAuthor

Property **LastAuthor** As String

Description

Member of Metadata

The **LastAuthor** property returns the name of the person who last edited a document.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.LocalizableCopyright

Property **LocalizableCopyright** As LocalizableString

Description

Member of Metadata

The **LocalizableCopyright** property returns or specifies the copyright information of a document.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.LocalizableKeywords

Property **LocalizableKeywords** As LocalizableString

Description

Member of Metadata

The **LocalizableKeywords** property returns or specifies document keywords.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.LocalizableNotes

Property **LocalizableNotes** As LocalizableString

Description

Member of Metadata

The **LocalizableNotes** property returns or specifies the notes for a document.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.LocalizableSubject

Property **LocalizableSubject** As LocalizableString

Description

Member of Metadata

The **LocalizableSubject** property returns or specifies the subject of a document.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.LocalizableTemplateDesignerNotes

Property **LocalizableTemplateDesignerNotes** As LocalizableString

Description

Member of Metadata

The **LocalizableTemplateDesignerNotes** property returns or specifies the designer notes of a template.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.LocalizableTitle

Property **LocalizableTitle** As LocalizableString

Description

Member of Metadata

The **LocalizableTitle** property returns or specifies the title of a document.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.Notes

Property **Notes** As String

Description

Member of Metadata

The **Notes** property returns or specifies the notes for a document.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.Revision

Property **Revision** As Long

Description

Member of Metadata

The **Revision** property returns or specifies the revision number for a document.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.Subject

Property **Subject** As String

Description

Member of Metadata

The **Subject** property returns or specifies the subject of a document.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.TemplateDesignerNotes

Property **TemplateDesignerNotes** As String

Description

Member of Metadata

The **TemplateDesignerNotes** property returns or specifies the designer notes for a template.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.TemplateFolds

Property **TemplateFolds** As String

Description

Member of Metadata

The **TemplateFolds** property returns or specifies the number of folds required by a template.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.TemplateIndustry

Property **TemplateIndustry** As String

Description

Member of Metadata

The **TemplateIndustry** property returns or specifies the target industry for a template.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.TemplateSided

Property **TemplateSided** As String

Description

Member of Metadata

The **TemplateSided** property returns or specifies whether a template is single- or double-sided.

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.TemplateType

Property **TemplateType** As String

Description

Member of Metadata

The **TemplateType** property returns or specifies the template type (for example, banner or poster).

Copyright 2014 Corel Corporation. All rights reserved.

Metadata.Title

Property **Title** As String

Description

Member of Metadata

The **Title** property returns or specifies the title of a document.

Copyright 2014 Corel Corporation. All rights reserved.

Node

Properties Methods

Description

The **Node** class represents a single node on a curve.

Copyright 2014 Corel Corporation. All rights reserved.

Node.AbsoluteIndex

Property **AbsoluteIndex** As Long

Description

Member of Node

The **AbsoluteIndex** property returns the index number of a node within a curve (including all subpaths for the curve).

- The Index property returns the index number of a node within its subpath. The Absolute**Index** and **Index** properties return the same value if the node belongs to the first subpath of the curve.

The **AbsoluteIndex** property returns a read-only value.

VBA example

The following VBA example loops through each node of each subpath and prints the **Index** and **AbsoluteIndex** properties in the **Intermediate** window of the Macro Editor.

```
Sub Test()
 Dim s As Shape
 Dim sp As SubPath
 Dim n As Node
 Set s = ActiveShape
 If s.Type = cdrCurveShape Then
  For Each sp In s.Curve.Subpaths
   For Each n In sp.Nodes
    Debug.Print n.Index, n.AbsoluteIndex
   Next n
  Next sp
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.Application

Property **Application** As Application

Description

Member of Node

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Node.AveragePositionWith

Sub **AveragePositionWith(**Node2 As Node**, [**JoinPaths As Boolean = False**])**

Description

Member of Node

The **AveragePositionWith** method moves two nodes to the midpoint of their original positions.

Parameter	Description
Node2	Specifies the second node
JoinPaths	Specifies whether to join the paths. This parameter is optional, and its default value is **False**.

Copyright 2014 Corel Corporation. All rights reserved.

Node.BreakApart

Sub **BreakApart()**

Description

Member of Node

The **BreakApart** method breaks a subpath at the specified node.

VBA example

The following VBA example breaks the curve into individual segments.

```
Sub Test()
 Dim s As Shape
 Dim i As Long
 Set s = ActiveShape
 If s.Type <> cdrCurveShape Then s.ConvertToCurves
 s.Curve.Closed = False
 For i = s.Curve.Nodes.Count To 1 Step -1
  s.Curve.Nodes(i).BreakApart
 Next i
 s.BreakApart
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.Chamfer

Function **Chamfer(***DistanceA As Double***,** *DistanceB As Double***, [**CombineSmoothSegments As Boolean = True**])** As Boolean

Description

Member of Node

The **Chamfer** method creates a chamfer on the node.

Parameter	Description
DistanceA	
DistanceB	
CombineSmoothSegments	Specifies whether to combine smooth segments. This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

Node.ConnectWith

Sub **ConnectWith(**Target As Node**)**

Description

Member of Node

The **ConnectWith** method connects two ending nodes by drawing a straight line between them.

- The JoinWith method connects two ending nodes by merging them into one.

Parameter	Description
Target	Specifies the node to join to the current node

VBA example

The following VBA example connects the ending node of each open subpath with the starting node of the next open subpath.

```
Sub Test()
 Dim s As Shape
 Dim spath As SubPath
 Dim n1 As Node, n2 As Node
 Dim Joined As Boolean, Repeat As Boolean
 Set s = ActiveShape
 If s.Type <> cdrCurveShape Then s.ConvertToCurves
 Repeat = True
 While Repeat
  Set n1 = Nothing
  Set n2 = Nothing
  Joined = False
  For Each spath In s.Curve.Subpaths
   If Not spath.Closed Then
    If n2 Is Nothing Then
     ' The first open SubPath found
     Set n1 = spath.StartNode
     Set n2 = spath.EndNode
    Else
     ' n2 is the last node of previous open SubPath
     ' Join it with the first node of the current subpath
     n2.ConnectWith spath.StartNode
     ' Joining subpaths reduces the number of subpath in the curve
     ' So we need to restart
     Joined = True
     Exit For
    End If
   End If
  Next spath
  If Not Joined Then
   If Not n1 Is Nothing Then
    ' There's only one open subpath left. Close it
    n1.ConnectWith n2
   End If
   Repeat = False
  End If
 Wend
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.CreateSelection

Sub **CreateSelection()**

Description

Member of Node

The **CreateSelection** method deselects all nodes in a curve and then selects only the specified node.

Copyright 2014 Corel Corporation. All rights reserved.

Node.Delete

Sub **Delete()**

Description

Member of Node

The **Delete** method breaks a subpath at the specified node by removing a node from the curve.

- If you delete a node from a segment that contains two nodes, the whole segment is removed.

VBA example

The following VBA example deletes all cusp nodes in the curve.

```
Sub Test()
 Dim s As Shape
 Dim n As Node
 Dim i As Long, Num As Long
 Set s = ActiveShape
 If s.Type <> cdrCurveShape Then Exit Sub
 Num = s.Curve.Nodes.Count
 i = 1
 While i <= Num
  Set n = s.Curve.Nodes(i)
  If n.Type = cdrCuspNode Then
   If n.SubPath.Nodes.Count = 2 Then
    ' Deleting a node from a segment containing only 2 nodes
    ' will remove the whole segment. If we are deleting the last
    ' node of the subpath, then we must move one more step back.
    If n.SubPath.EndNode Is n Then i = i - 1
    n.Delete
    Num = Num - 2
    i = i - 1
   Else
    ' Just delete the node and adjust the number of nodes left.
    n.Delete
    Num = Num - 1
    i = i - 1
   End If
  End If
  i = i + 1
 Wend
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.ExtendSubPaths

Function **ExtendSubPaths(**Node2 As Node**, [**JoinPaths As Boolean = False**])** As Boolean

Description

Member of Node

The **ExtendSubPaths** method extends two open subpaths until they meet.

Parameter	Description
Node2	Specifies the second node
JoinPaths	Specifies whether to join the paths. This parameter is optional, and its default value is **False**.

Copyright 2014 Corel Corporation. All rights reserved.

Node.Fillet

Function **Fillet(***Radius As Double***, [**CombineSmoothSegments As Boolean = True**])** As Boolean

Description

Member of Node

The **Fillet** method creates a fillet on the cusp node.

Parameter	Description
Radius	Specifies the radius of the fillet
CombineSmoothSegments	Specifies whether to combine smooth segments. This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

Node.GetDistanceFrom

Function **GetDistanceFrom(**Node As Node**)** As Double

Description

Member of Node

The **GetDistanceFrom** method returns the distance from the current node to a specified node.

Parameter	Description
Node	Specifies the node from which to return the distance

VBA example

The following VBA example closes all open subpaths in a curve by joining or connecting each one with the closest node of another open subpath.

```
Sub CloseShape()
 Dim s As Shape
 Dim e As Double, r As Double, nr As Double
 Dim sp As SubPath
 Dim sn As Node, en As Node, n1 As Node, n2 As Node
 Dim b As Boolean
 Set s = ActiveShape
 If s.Type <> cdrCurveShape Then
  MsgBox "Curve must be selected"
  Exit Sub
 End If
 ' E is auto-join limit beyond which the nodes are joined rather than connected
 ' Here assumed to be 1% of an average object size
 e = s.SizeHeight * s.SizeWidth / 10000
 Do
  Set sn = Nothing
  Set en = Nothing
  Set n1 = Nothing
  Set n2 = Nothing
  b = False
  For Each sp In s.Curve.Subpaths
   If Not sp.Closed Then
    Set n1 = sp.StartNode
    Set n2 = sp.EndNode
    nr = n1.GetDistanceFrom(n2)
    If nr < e And sp.Nodes.Count > 2 Then
     n1.JoinWith n2
     b = True
    Else
     If sn Is Nothing Then
      Set sn = n1
      Set en = n2
      r = nr
     Else
      nr = sn.GetDistanceFrom(n1)
      If nr < r Then
       Set en = n1
       r = nr
      End If
      nr = sn.GetDistanceFrom(n2)
      If nr < r Then
       Set en = n2
       r = nr
      End If
     End If
    End If
   End If
   If b Then Exit For
  Next sp
  If Not b And Not sn Is Nothing Then
   If r < e Then sn.JoinWith en Else sn.ConnectWith en
   b = True
  End If
 Loop While b
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.GetPosition

Sub **GetPosition(***PositionX As Double***,** *PositionY As Double***)**

Description

Member of Node

The **GetPosition** method returns the x- and y-coordinates of a node.

- The SetPosition method moves a node to new coordinates.

Parameter	Description
PositionX	Specifies the x-, or horizontal, coordinate of the node, measured in document units
PositionY	Specifies the y-, or vertical, coordinate of the node, measured in document units

VBA example

The following VBA example draws a small ellipse over each node in the selected curve.

```
Sub Test()
 Dim n As Node
 Dim x As Double, y As Double
 For Each n In ActiveShape.Curve.Nodes
  n.GetPosition x, y
  ActiveLayer.CreateEllipse2 x, y, 0.05
 Next n
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.Index

Property **Index** As Long

Description

Member of Node

The **Index** property returns the index number of a node within a subpath.

- The AbsoluteIndex property returns the index number of a node within a curve (including all subpaths for the curve). The **Index** and **AbsoluteIndex** properties return the same value if the node belongs to the first subpath of the curve.

The **Index** property returns a read-only value.

VBA example

The following VBA example loops through each node of each subpath and prints the **Index** and **AbsoluteIndex** properties in the **Intermediate** window of the Macro Editor.

```
Sub Test()
 Dim s As Shape
 Dim sp As SubPath
 Dim n As Node
 Set s = ActiveShape
 If s.Type = cdrCurveShape Then
  For Each sp In s.Curve.Subpaths
   For Each n In sp.Nodes
    Debug.Print n.Index, n.AbsoluteIndex
   Next n
  Next sp
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.IsEnding

Property **IsEnding** As Boolean

Description

Member of Node

The **IsEnding** property returns **True** if a node is the first or last node of an open subpath.

The **IsEnding** property returns a read-only value.

VBA example

The following VBA example marks, with a small circle, each ending node in a curve.

```
Sub Test()
 Dim n As Node
 For Each n In ActiveShape.Curve.Nodes
  If n.IsEnding Then
   ActiveLayer.CreateEllipse2 n.PositionX, n.PositionY, 0.1
  End If
 Next n
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.JoinWith

Sub **JoinWith(**Target As Node**)**

Description

Member of Node

The **JoinWith** method connects two ending nodes by merging them into one.

- The ConnectWith method connects two ending nodes by drawing a straight line between them.

Parameter	Description
Target	Specifies the node to join to the current node

VBA example

The following VBA example joins the first and last nodes of the active curve by merging them into one.

```
Sub Connect()
 Dim s as Shape
 Dim sp as SubPath
 Set s = ActiveShape
 Set sp = ActiveShape.Curve.Subpaths(1)
 With s.Curve.Nodes(1)
  .JoinWith sp.Nodes(9)
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.Move

Sub **Move([***DeltaX As Double***], [***DeltaY As Double***])**

Description

Member of Node

The **Move** method offsets the position of a node relative to its original location.

Parameter	Description
DeltaX	Specifies the horizontal offset. This parameter is optional, and its default value is **0**.
DeltaY	Specifies the vertical offset. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example randomly distorts the selected curve. This macro loops through all nodes and changes their positions by moving each one by a random offset.

```
Sub Test()
 Dim s As Shape
 Dim n As Node
 Dim dx As Double, dy As Double
 Const Amplitude As Double = 0.5
 Set s = ActiveShape
 If s.Type = cdrCurveShape Then
  For Each n In s.Curve.Nodes
   dx = (Rnd() - 0.5) * Amplitude
   dy = (Rnd() - 0.5) * Amplitude
   n.Move dx, dy
  Next n
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.Next

Function **Next()** As Node

Description

Member of Node

The **Next** method returns the next node in a curve, relative to a given node.

VBA example

The following VBA example changes the fifth node to a smooth node if the fourth node of the curve is symmetrical and the fifth node is a cusp node.

```
Sub Test()
 Dim s As Shape
 Dim n As Node
 Set s = ActiveShape
 If s.Type = cdrCurveShape Then
  Set n = s.Curve.Nodes(4)
  If n.Type = cdrSymmetricalNode And n.Next.Type = cdrCuspNode Then
   n.Next.Type = cdrSmoothNode
  End If
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.NextSegment

Property **NextSegment** As Segment

Description

Member of Node

The **NextSegment** property returns the next segment that is adjacent to a node, or it returns **Nothing** if no such segment exists.

The **NextSegment** property returns a read-only value.

VBA example

The following VBA example creates an ellipse on the active layer, converts it to curves, and returns its first segment.

```
Sub Test()
 Dim s1 As Shape
 Dim sg As Segment
 Set s1 = ActiveLayer.CreateEllipse(0, 0, 2, 2)
 s1.ConvertToCurves
 Set sg = s1.Curve.Nodes(1).NextSegment
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.Parent

Property **Parent** As Curve

Description

Member of Node

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Node.PositionX

Property **PositionX** As Double

Description

Member of Node

The **PositionX** property returns or specifies the x-coordinate of a node relative to its reference point.

VBA example

The following VBA example draws a small ellipse over each node in the selected curve and colors each ellipse according to the node type.

```
Sub ShowNodes()
 Dim n As Node
 Dim s As Shape
 For Each n In ActiveShape.Curve.Nodes
  Set s = ActiveLayer.CreateEllipse2(n.PositionX, n.PositionY, 0.05)
  Select Case n.Type
   Case cdrSymmetricalNode
    s.Fill.UniformColor.RGBAssign 0, 0, 255
   Case cdrSmoothNode
    s.Fill.UniformColor.RGBAssign 255, 255, 0
   Case cdrCuspNode
    s.Fill.UniformColor.RGBAssign 255, 0, 0
  End Select
 Next n
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.PositionY

Property **PositionY** As Double

Description

Member of Node

The **PositionY** property returns or specifies the y-coordinate of a node relative to its reference point.

VBA example

The following VBA example draws a small ellipse over each node in the selected curve and colors each ellipse according to the node type.

```
Sub ShowNodes()
 Dim n As Node
 Dim s As Shape
 For Each n In ActiveShape.Curve.Nodes
  Set s = ActiveLayer.CreateEllipse2(n.PositionX, n.PositionY, 0.05)
  Select Case n.Type
   Case cdrSymmetricalNode
    s.Fill.UniformColor.RGBAssign 0, 0, 255
   Case cdrSmoothNode
    s.Fill.UniformColor.RGBAssign 255, 255, 0
   Case cdrCuspNode
    s.Fill.UniformColor.RGBAssign 255, 0, 0
  End Select
 Next n
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.Previous

Function **Previous()** As Node

Description

Member of Node

The **Previous** method returns the preceding node in a curve, relative to the given node.

VBA example

The following VBA example creates a curve with six segments, finds the first symmetrical node, and displays the index number of the node preceding the first symmetrical node.

```
Sub Test()
 Dim s As Shape
 Dim n As Node
 Dim sp As SubPath
 Dim crv As Curve
 Set crv = CreateCurve(ActiveDocument)
 ActiveDocument.ReferencePoint = cdrBottomLeft
 Set sp = crv.CreateSubPath(1, 1)
 sp.AppendLineSegment 1, 1
 sp.AppendCurveSegment 3, 3
 sp.AppendCurveSegment 5, 1
 sp.AppendCurveSegment 6, 4
 sp.AppendCurveSegment 8, 2
 sp.AppendLineSegment 10, 5
 sp.Nodes(2).Type = cdrSmoothNode
 sp.Nodes(3).Type = cdrSmoothNode
 sp.Nodes(4).Type = cdrSymmetricalNode
 sp.Nodes(5).Type = cdrSmoothNode
 Set s = ActiveLayer.CreateCurve(crv)
 For Each n In s.Curve.Nodes
  If n.Type = cdrSymmetricalNode Then
   Set n = s.Curve.Nodes.Item(n.Index).Previous
   Exit For
  End If
 Next n
 MsgBox n.Index
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.PrevSegment

Property **PrevSegment** As Segment

Description

Member of Node

The **PrevSegment** property returns the previous segment that is adjacent to a node, or it returns **Nothing** if no such segment exists.

The **PrevSegment** property returns a read-only value.

VBA example

The following VBA example creates an ellipse on the active layer, converts it to curves, and returns its third segment.

```
Sub Test()
 Dim s1 As Shape
 Dim sg As Segment
 Set s1 = ActiveLayer.CreateEllipse(0, 0, 2, 2)
 s1.ConvertToCurves
 Set sg = s1.Curve.Nodes(s1.Curve.Nodes.Count).PrevSegment
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.Scallop

Function **Scallop(***Radius As Double***, [**CombineSmoothSegments As Boolean = True**])** As Boolean

Description

Member of Node

The **Scallop** method creates a scallop on the node.

Parameter	Description
Radius	Specifies the radius of the scallop
CombineSmoothSegments	Specifies whether to combine smooth segments. This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

Node.Segment

Property **Segment** As Segment

Description

Member of Node

The **Segment** property returns the segment that contains a specified node.

The **Segment** property returns a read-only value.

VBA example

The following VBA example converts, to a line, the segment that is adjacent to third node in the selected curve.

```
Sub Test()
 ActiveShape.Curve.Nodes(3).Segment.Type = cdrLineSegment
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.Selected

Property **Selected** As Boolean

Description

Member of Node

The **Selected** property returns **True** if a specified node is currently selected, or it selects or deselects the node.

Copyright 2014 Corel Corporation. All rights reserved.

Node.SetPosition

Sub **SetPosition(***PositionX As Double***,** *PositionY As Double***)**

Description

Member of Node

The **SetPosition** method moves a node to the specified x- and y-coordinates.

- The GetPosition method returns the x- and y-coordinates of a node.

Parameter	Description
PositionX	Specifies, in document units, the x-coordinate of the node
PositionY	Specifies, in document units, the y-coordinate of the node

VBA example

The following VBA example distorts the selected curve. The amount of distortion depends on the distance between the node and the center of the shape. The node is moved only radially.

```
Sub Test()
 Dim s As Shape
 Dim n As Node
 Dim xc As Double, yc As Double
 Dim r As Double
 Dim dx As Double, dy As Double
 Const Amplitude As Double = 0.2
 Set s = ActiveShape
 If s.Type = cdrCurveShape Then
  ActiveDocument.ReferencePoint = cdrCenter
  s.GetPosition xc, yc
  For Each n In s.Curve.Nodes
   dx = n.PositionX - xc
   dy = n.PositionY - yc
   r = Exp((Rnd() - 0.5) * Amplitude)
   n.SetPosition xc + dx * r, yc + dy * r
  Next n
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.SubPath

Property **SubPath** As SubPath

Description

Member of Node

The **SubPath** property returns the subpath to which a node belongs.

The **SubPath** property returns a read-only value.

VBA example

The following VBA example displays the length of a node's subpath, measured in document units.

```
Sub PathLength()
 With ActiveShape.Curve.Nodes(1)
  MsgBox .Subpath.Length
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.SubPathIndex

Property **SubPathIndex** As Long

Description

Member of Node

The **SubPathIndex** property returns the index number of a subpath within the Curve.Subpaths collection.

The **SubPathIndex** property returns a read-only value.

VBA example

The following VBA example displays the number of nodes that are selected on a curve and the number of subpaths on which they reside. Before running this macro, you must use the **Shape** tool to select nodes.

```
Sub Test()
 Dim nr As NodeRange
 Dim n As Node
 Dim spi As New Collection
 Dim Found As Boolean
 Dim idx As Variant
 If ActiveShape Is Nothing Then
  MsgBox "Nothing is selected."
  Exit Sub
 End If
 If ActiveShape.Type <> cdrCurveShape Then
  MsgBox "A curve must be selected."
  Exit Sub
 End If
 Set nr = ActiveShape.Curve.Selection
 If nr.Count = 0 Then
  MsgBox "Please use the Shape tool to select several nodes."
  Exit Sub
 End If
 For i = 1 To nr.Count
  Set n = nr(i)
  Found = False
  For Each idx In spi
   If n.SubPathIndex = idx Then
    Found = True
    Exit For
   End If
  Next idx
  If Not Found Then spi.Add n.SubPathIndex
 Next i
 MsgBox "Selected " & nr.Count & " node(s) on " & spi.Count & " different subpath(s)"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Node.Type

Property **Type** As cdrNodeType

Description

Member of Node

The **Type** property returns or specifies the node type as cusp, smooth, or symmetrical. The **Type** property returns a value of cdrNodeType.

VBA example

The following VBA example converts all of the cusp nodes in the curve to smooth nodes.

```
Sub Test()
 Dim n As Node
 For Each n In ActiveShape.Curve.Nodes
  If n.Type = cdrCuspNode Then n.Type = cdrSmoothNode
 Next n
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange

Properties Methods

Description

The **NodeRange** class represents an array (or range) of nodes on a curve.

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.Add

Sub **Add(**Node As Node**)**

Description

Member of NodeRange

The **Add** method places a specified node in a node range.

Adding a node to a node range doesn't make that node active within a curve — it merely includes the node in future references to that node range.

Parameter	Description
Node	Specifies the node to add to the node range

VBA example

The following VBA example creates a node range containing the first, second, and third nodes of the curve. A fifth node is added to the curve, and then all four nodes are deleted from the curve.

```
Sub Test()
 Dim nr As NodeRange
 Set nr = ActiveShape.Curve.Nodes.Range(1, 2, 3)
 nr.Add ActiveShape.Curve.Nodes(5)
 nr.Delete
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.AddRange

Sub **AddRange(**NodeRange As NodeRange**)**

Description

Member of NodeRange

The **AddRange** method adds nodes from another node range to the current node range.

Parameter	Description
NodeRange	Specifies the range of nodes to add to the current node range

VBA example

The following VBA example sets the node type to smooth for all nodes on the first and second subpaths of the selected curve.

```
Sub Test()
 Dim nr As NodeRange
 Set nr = ActiveShape.Curve.Subpaths(1).Nodes.All
 nr.AddRange ActiveShape.Curve.Subpaths(2).Nodes.All
 nr.SetType cdrSmoothNode
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.AddToSelection

Sub **AddToSelection()**

Description

Member of NodeRange

The **AddToSelection** method adds the nodes in a range to the current selection.

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.Application

Property **Application** As Application

Description

Member of NodeRange

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.AutoReduce

Sub **AutoReduce(***PrecisionMargin As Double***)**

Description

Member of NodeRange

The **AutoReduce** method remove extra nodes, keeping the shape of the curve within a given margin of deviation.

Parameter	Description
PrecisionMargin	Specifies the maximum allowable deviation of the curve shape. This value is measured in document units of length. Specifying larger numbers leaves fewer nodes and may cause a larger distortion of the shape.

VBA example

The following VBA example removes any extra nodes in the active shape, keeping changes in the curve's shape within **0.01**" (where inches is the document's unit of measurement).

```
Sub Test()
 ActiveShape.Curve.Nodes.All.AutoReduce 0.01
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.BoundingBox

Property **BoundingBox** As Rect

Description

Member of NodeRange

The **BoundingBox** property returns the rectangle bounding the nodes in a node range.

The **BoundingBox** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.BreakApart

Sub **BreakApart()**

Description

Member of NodeRange

The **BreakApart** method breaks a curve at each node in the range of nodes.

VBA example

The following VBA example breaks the selected curve into a set of individual segments and then scatters each segment randomly.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveShape
 s.Curve.Nodes.All.BreakApart ' Break apart curve into multiple subpaths
 s.BreakApart ' Break apart subpaths into individual shapes
 For Each s In ActiveSelection.Shapes
  s.Move Rnd() - 0.5, Rnd() - 0.5
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.Chamfer

Sub **Chamfer(***DistanceA As Double***,** *DistanceB As Double***, [**CombineSmoothSegments As Boolean = True**])**

Description

Member of NodeRange

The **Chamfer** method creates chamfers on the nodes in the node range.

Parameter	Description
DistanceA	
DistanceB	
CombineSmoothSegments	Specifies whether to combine smooth segments. This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.Count

Property **Count** As Long

Description

Member of NodeRange

The **Count** property returns the number of nodes in a node range (or NodeRange object).

The **Count** property returns a read-only value.

VBA example

The following VBA example displays the number of nodes selected with the **Shape** tool.

```
Sub Test()
 Dim nr As NodeRange
 Set nr = ActiveShape.Curve.Selection
 MsgBox nr.Count & " node(s) selected in the curve"
End Sub
Sub Test()
 Dim nr As New NodeRange
 Dim n As Node
 Dim ret As VbMsgBoxResult
 For Each n In ActiveShape.Curve.Nodes
  If n.Type = cdrCuspNode Then nr.Add n
 Next n
 If nr.Count = 0 Then
  MsgBox "No cusp nodes found"
 Else
  ret = MsgBox(nr.Count & " cusp nodes found. Do you want to delete them?", vbYesNo)
  If ret = vbYes Then nr.Delete
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.CreateSelection

Sub **CreateSelection()**

Description

Member of NodeRange

The **CreateSelection** method selects all nodes in a node range.

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.Delete

Sub **Delete()**

Description

Member of NodeRange

The **Delete** method removes all nodes in a node range. The nodes are physically removed from the curve object.

- Deleting all nodes from a curve deletes the curve itself.

VBA example

The following VBA example deletes all selected nodes in the curve.

```
Sub Test()
 ActiveShape.Curve.Selection.Delete
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.Fillet

Sub **Fillet(***Radius As Double***, [**CombineSmoothSegments As Boolean = True**])**

Description

Member of NodeRange

The **Fillet** method creates fillets on the nodes in a node range.

Parameter	Description
Radius	Specifies the radius of the fillet
CombineSmoothSegments	Specifies whether to combine smooth segments. This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.FirstNode

Property **FirstNode** As Node

Description

Member of NodeRange

The **FirstNode** property returns the first node in a range.

The **FirstNode** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.GetBoundingBox

Function **GetBoundingBox(***x As Double*, *y As Double*, *Width As Double*, *Height As Double***)** As Boolean

Description

Member of NodeRange

The **GetBoundingBox** method returns the bounding box around the nodes in a node range.

Parameter	Description
x	Specifies the x-coordinate
y	Specifies the y-coordinate
Width	Specifies the width of the bounding box
Height	Specifies the height of the bounding box

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.Item

Property **Item(***Index As Long***)** As Node

Description

Member of NodeRange

The **Item** property returns the specified node (or Node object) from a node range (or NodeRange object).

Item is the default property of the **NodeRange** class, and its reference can be omitted when you are accessing items in a **NodeRange** collection. For example, **NodeRange.Item(2)** is the same as **NodeRange(2)** — they both reference the second node in a node range.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the node by its index number

VBA example

The following VBA example creates a node range from all nodes in the curve, and it removes all symmetrical and smooth nodes from the range (although it does not delete the nodes from the curve). The remaining collection of cusp nodes is rotated by **30**°, relative to its geometric center.

```
Sub Test()
 Dim nr As NodeRange
 Dim n As Node
 Dim i As Long
 Set nr = ActiveShape.Curve.Nodes.All
 For i = nr.Count To 1 Step -1
  If nr.Item(i).Type <> cdrCuspNode Then nr.Remove i
  ' The same as: If nr(i).Type <> cdrCuspNode Then nr.Remove i
 Next i
 ActiveDocument.ReferencePoint = cdrCenter
 If nr.Count > 0 Then nr.Rotate 30
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.LastNode

Property **LastNode** As Node

Description

Member of NodeRange

The **LastNode** property returns the last node in a range.

The **LastNode** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.Move

Sub **Move([***DeltaX As Double***], [***DeltaY As Double***], [**AnchorIndex As Long = 1**], [**ElasticMode As Boolean = False**])**

Description

Member of NodeRange

The **Move** method repositions all nodes in a node range by moving each node by a specified offset.

Parameter	Description
DeltaX	Specifies the horizontal distance to move the nodes. This parameter is optional, and its default value is **0**.
DeltaY	Specifies the vertical distance to move the nodes. This parameter is optional, and its default value is **0**.
AnchorIndex	Specifies, by index number, the node in the node range to act as an anchor. This parameter is optional, and its default value is **1**.
ElasticMode	Specifies whether to use Elastic Mode. If this value is set to **True**, only the node identified by the **AnchorIndex** parameter is moved by the exact offset specified, while the remaining nodes are offset by a smaller value depending on their position in the curve. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example creates a node range from all nodes in the curve except for the first and the last nodes. The nodes are then moved up (vertically) by **1**" and moved back down by **1**" with Elastic Mode enabled. The middle node (**node_count/2**) is used as an anchor node in the last operation.

```
Sub Test()
 Dim crv As Curve
 Dim nr As NodeRange
 Set crv = ActiveShape.Curve
 Set nr = crv.Nodes.AllExcluding(1, crv.Nodes.Count)
 nr.Move 0, 1
 nr.Move 0, -1, nr.Count \ 2, True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.Parent

Property **Parent** As Curve

Description

Member of NodeRange

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.PositionX

Property **PositionX** As Double

Description

Member of NodeRange

The **PositionX** property returns the horizontal position of the bounding box that encloses all nodes in a node range. This position is relative to the document's reference point and is measured in document units.

- The value of **PositionX** is **0** if there are no nodes in the node range.

The **PositionX** property returns a read-only value.

VBA example

The following VBA example draws a rectangle around the selected nodes.

```
Sub Test()
 Dim nr As NodeRange
 Dim x1 As Double, y1 As Double
 Dim x2 As Double, y2 As Double
 Set nr = ActiveShape.Curve.Selection
 ActiveDocument.ReferencePoint = cdrTopLeft
 x1 = nr.PositionX
 y1 = nr.PositionY
 ActiveDocument.ReferencePoint = cdrBottomRight
 x2 = nr.PositionX
 y2 = nr.PositionY
 ActiveLayer.CreateRectangle x1, y1, x2, y2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.PositionY

Property **PositionY** As Double

Description

Member of NodeRange

The **PositionY** property returns the vertical position of the bounding box that encloses all nodes in a node range. This position is relative to the document's reference point and is measured in document units.

- The value of **PositionY** is **0** if there are no nodes in the node range.

The **PositionY** property returns a read-only value.

VBA example

The following VBA example draws a rectangle around the selected nodes.

```
Sub Test()
 Dim nr As NodeRange
 Dim x1 As Double, y1 As Double
 Dim x2 As Double, y2 As Double
 Set nr = ActiveShape.Curve.Selection
 ActiveDocument.ReferencePoint = cdrTopLeft
 x1 = nr.PositionX
 y1 = nr.PositionY
 ActiveDocument.ReferencePoint = cdrBottomRight
 x2 = nr.PositionX
 y2 = nr.PositionY
 ActiveLayer.CreateRectangle x1, y1, x2, y2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.Remove

Sub **Remove(***Index As Long***)**

Description

Member of NodeRange

The **Remove** method removes a specified node from a node range.

- Removing a node from a node range doesn't delete the node from its curve. However, the node is not included in future references to the node range.

Parameter	Description
Index	Specifies the node to removed from the node range

VBA example

The following VBA example returns the selected nodes, removes the first and last selected nodes from the range, and deletes the remaining nodes. As a result, all selected nodes (except the first and last ones) are deleted from the curve.

```
Sub Test()
 Dim nr As NodeRange
 Set nr = ActiveShape.Curve.Selection
 nr.Remove 1
 nr.Remove nr.Count
 nr.Delete
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.RemoveAll

Sub **RemoveAll()**

Description

Member of NodeRange

The **RemoveAll** method empties a node range by removings all nodes from it.

- This method does not delete the nodes; it merely removes them from the node range.

VBA example

The following VBA example displays the number of nodes in the selected curve. It then empties the node range and displays the number of nodes (zero) now stored in it.

```
Sub Test()
 Dim nr As NodeRange
 Set nr = ActiveShape.Curve.Nodes.All
 MsgBox "There are " & nr.Count & " nodes in the curve."
 nr.RemoveAll
 MsgBox "Now the range contains " & nr.Count & " nodes."
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.RemoveFromSelection

Sub **RemoveFromSelection()**

Description

Member of NodeRange

The **RemoveFromSelection** method deselects the nodes in a node range.

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.RemoveRange

Sub **RemoveRange(**NodeRange As NodeRange**)**

Description

Member of NodeRange

The **RemoveRange** method removes the nodes in a specified node range from the current node range.

Parameter	Description
NodeRange	Specifies the nodes to remove

VBA example

The following VBA example creates a curve and two node ranges. The first node range contains all nodes, and the second node range contains only the cusp nodes. The second node range is removed from the first, leaving only the non-cusp nodes in the first node range.

```
Sub Test()
 Dim s As Shape
 Dim n As Node
 Dim sp As SubPath
 Dim crv As Curve
 Dim nr1 As NodeRange
 Dim nr2 As New NodeRange
 Set crv = CreateCurve(ActiveDocument)
 ActiveDocument.ReferencePoint = cdrBottomLeft
 Set sp = crv.CreateSubPath(-1, 0.2)
 sp.AppendLineSegment 0.5, 1
 sp.AppendCurveSegment 2, 3
 sp.AppendCurveSegment 4, 1
 sp.AppendCurveSegment 5, 4
 sp.AppendCurveSegment 7, 2
 sp.AppendLineSegment 8, 5
 sp.AppendLineSegment 9, 1
 sp.Nodes(2).Type = cdrSmoothNode
 sp.Nodes(4).Type = cdrSmoothNode
 Set s = ActiveLayer.CreateCurve(crv)
 Set nr1 = s.Curve.Nodes.All
 For Each n In s.Curve.Nodes
  If n.Type = cdrCuspNode Then
   nr2.Add n
  End If
 Next n
 nr1.RemoveRange nr2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.Rotate

Sub **Rotate(***Angle As Double***, [**UseCenterPoint As Boolean = False**], [***RotationCenterX As Double***], [***RotationCenterY As Double***])**

Description

Member of NodeRange

The **Rotate** property rotates the nodes in a node range as though the node range were a separate shape object.

Parameter	Description
Angle	Specifies the angle, measured in degrees, to rotate the node range
UseCenterPoint	Specifies whether to rotate the node range around its center point. This parameter is optional, and its default value is **False**.
RotationCenterX	Specifies the x-coordinate of the center of rotation. This parameter is optional, and its default value is **0**.
RotationCenterY	Specifies the y-coordinate of the center of rotation. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example rotates the selected nodes **30**° around the geometrical center of their node range.

```
Sub Test()
 Dim nr As NodeRange
 Set nr = ActiveShape.Curve.Selection
 ActiveDocument.ReferencePoint = cdrCenter
 nr.Rotate 30
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.Scallop

Sub **Scallop(***Radius As Double***, [**CombineSmoothSegments As Boolean = True**])**

Description

Member of NodeRange

The **Scallop** property creates scallops on the nodes in a node range.

Parameter	Description
Radius	Specifies the radius of the scallop
CombineSmoothSegments	Specifies whether to combine smooth segments. This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.SegmentRange

Property **SegmentRange** As SegmentRange

Description

Member of NodeRange

The **SegmentRange** property returns a SegmentRange object containing all segments that start at the nodes in the current node range.

The **SegmentRange** property returns a read-only value.

VBA example

The following VBA example converts all selected nodes in the current curve to smooth nodes, and it converts all of the associated segments to curve segments.

```
Sub Test()
 Dim nr As NodeRange
 Dim sr As SegmentRange
 Set nr = ActiveShape.Curve.Selection
 If nr.Count > 0 Then
  Set sr = nr.SegmentRange
  sr.SetType cdrCurveSegment
  nr.SetType cdrSmoothNode
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.SetType

Sub **SetType(**Type As cdrNodeType**)**

Description

Member of NodeRange

The **SetType** method sets the type for all nodes in a node range.

The **SetType** method returns a value of cdrNodeType.

Parameter	Description
Type	Specifies the node type for all nodes in a node range

VBA example

The following VBA example changes all nodes in the active shape to cusp nodes.

```
Sub Test()
 ActiveShape.Curve.Nodes.All.SetType cdrCuspNode
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.SizeHeight

Property **SizeHeight** As Double

Description

Member of NodeRange

The **SizeHeight** property returns the height (measured in document units) of the bounding box enclosing all nodes in a node range.

The **SizeHeight** property returns a read-only value.

VBA example

The following VBA example draws a rectangle around the selected nodes.

```
Sub Test()
 Dim nr As NodeRange
 Dim x1 As Double, y1 As Double
 Dim x2 As Double, y2 As Double
 Set nr = ActiveShape.Curve.Selection
 ActiveDocument.ReferencePoint = cdrBottomLeft
 x1 = nr.PositionX
 y1 = nr.PositionY
 x2 = x1 + nr.SizeWidth
 y2 = y1 + nr.SizeHeight
 ActiveLayer.CreateRectangle x1, y1, x2, y2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.SizeWidth

Property **SizeWidth** As Double

Description

Member of NodeRange

The **SizeWidth** property returns the width (measured in document units) of the bounding box enclosing all nodes in a node range.

The **SizeWidth** property returns a read-only value.

VBA example

The following VBA example draws a rectangle around the selected nodes.

```
Sub Test()
 Dim nr As NodeRange
 Dim x1 As Double, y1 As Double
 Dim x2 As Double, y2 As Double
 Set nr = ActiveShape.Curve.Selection
 ActiveDocument.ReferencePoint = cdrBottomLeft
 x1 = nr.PositionX
 y1 = nr.PositionY
 x2 = x1 + nr.SizeWidth
 y2 = y1 + nr.SizeHeight
 ActiveLayer.CreateRectangle x1, y1, x2, y2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.Skew

Sub **Skew([***AngleX As Double***], [***AngleY As Double***], [**UseAnchorPoint As Boolean = False**], [***SkewAnchorX As Double***], [***SkewAnchorY As Double***])**

Description

Member of NodeRange

The **Skew** property skews the nodes in a node range as though the node range were a separate shape object.

Parameter	Description
AngleX	Specifies the degree to which to horizontally slant the node range. This parameter is optional, and its default value is **0**.
AngleY	Specifies the degree to which to vertically slant the node range. This parameter is optional, and its default value is **0**.
UseAnchorPoint	Specifies whether to use an anchor point. This parameter is optional, and its default value is **False**.
SkewAnchorX	Specifies, in document units, the x-coordinate of the anchor point when skewing the node range. This parameter is optional, and its default value is **0**.
SkewAnchorY	Specifies, in document units, the y-coordinate of the anchor point when skewing the node range. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example skews the node range in the active shape horizontally and vertically by **25**°. A reference point is not set, but the anchor point is set at (**0**, **0**).

```
Sub Test()
 Dim nr as NodeRange
 Set nr = ActiveShape.Curve.Nodes.All
 With nr
  .Skew 25, 25, False, 0, 0
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.Smoothen

Sub **Smoothen(***Smoothness As Long***)**

Description

Member of NodeRange

The **Smoothen** method sets the curve smoothness at each node in a node range.

- This method produces the same effect as changing the value of the **Curve smoothness** slider on the property bar.

Parameter	Description
Smoothness	Specifies the level of curve smoothness. Higher values indicate an increased level of smoothness. Values range from **0** to **100**.

VBA example

The following VBA example smooths all curves on the active page in the drawing.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Type = cdrCurveShape Then
   s.Curve.Nodes.All.Smoothen 20
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.Stretch

Sub **Stretch([**RatioX As Single = 1**], [**RatioY As Single = 1**], [**UseAnchorPoint As Boolean = False**], [***StretchAnchorX As Double***], [***StretchAnchorY As Double***])**

Description

Member of NodeRange

The **Stretch** property stretches the nodes in a node range as though the node range were a separate shape object.

Parameter	Description
RatioX	Specifies the width of the aspect ratio to use when stretching objects, expressed as a multiple of the current width. This parameter is optional, and its default value is **1**.
RatioY	Specifies the height of the aspect ratio to use when stretching objects, expressed as a multiple of the current height. This parameter is optional, and its default value is **1**.
UseAnchorPoint	Specifies whether to use an anchor point. This parameter is optional, and its default value is **False**.
StretchAnchorX	Specifies, in document units, the x-coordinate of the anchor point to use when stretching the node range. This parameter is optional, and its default value is **0**.
StretchAnchorY	Specifies, in document units, the y-coordinate of the anchor point to use when stretching the node range. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example stretches the node range in the active shape with ratio values of **1**, no reference point, and an anchor point of (**0**, **0**).

```
Sub SkewNode()
 Dim nr as NodeRange
 Set nr = ActiveShape.Curve.Nodes.All
 With nr
  .Stretch 1, 1, False, 0, 0
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

NodeRange.Type

Property **Type** As cdrNodeType

Description

Member of NodeRange

The **Type** property returns the node type used in a node range. If multiple node types are used, cdrNodeType is returned.

- The **Type** property can be used with the NodeRange.Item property, to return the node type for a specific node within a range.

The Type property returns a read-only value.

VBA example

The following VBA example displays the number of nodes selected and their type — for example, **5 cusp nodes selected** or **3 nodes of different type selected**.

```
Sub Test()
 Dim nr As NodeRange
 Dim s As String
 Set nr = ActiveShape.Curve.Selection
 If nr.Count = 0 Then
  s = "No nodes selected"
 Else
  s = CStr(nr.Count) & " "
  Select Case nr.Type
   Case cdrSymmetricalNode
    s = s & "symmetrical"
   Case cdrSmoothNode
    s = s & "smooth"
   Case cdrCuspNode
    s = s & "cusp"
   Case cdrMixedNodes
    s = s & "nodes of different type"
  End Select
  If nr.Type <> cdrMixedNodes Then s = s & " nodes"
  s = s & " selected"
 End If
 MsgBox s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Nodes

Properties Methods

Description

The **Nodes** class represents a collection of nodes (or Node objects) on a curve.

Copyright 2014 Corel Corporation. All rights reserved.

Nodes.All

Function **All()** As NodeRange

Description

Member of Nodes

The **All** method returns a node range that contains all nodes in a Nodes collection.

VBA example

The following VBA example applies auto-reduction to all curves on the active page.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Type = cdrCurveShape Then
   s.Curve.Nodes.All.AutoReduce 0.05
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Nodes.AllExcluding

Function **AllExcluding(***IndexArray() As Variant***)** As NodeRange

Description

Member of Nodes

The **AllExcluding** method returns a node range that contains all nodes in a Nodes collection except for the specified nodes.

- The **AllExcluding** method accepts a variable number of arguments. It also accepts arrays.

Parameter	Description
IndexArray	Specifies a range of index numbers that identify and group specific nodes

VBA example

The following VBA example deletes all nodes in the curve, with the exception of the first three nodes. Deleting nodes alters the appearance of the active shape.

```
Sub Test()
 Dim nr As NodeRange
 Set nr = ActiveShape.Curve.Nodes.AllExcluding(1, 2, 3)
 nr.Delete
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Nodes.Application

Property **Application** As Application

Description

Member of Nodes

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Nodes.Count

Property **Count** As Long

Description

Member of Nodes

The **Count** property returns the total number of nodes in a Nodes collection.

The **Count** property returns a read-only value.

VBA example

The following VBA example displays the number of nodes, segments, and subpaths in the curve.

```
Sub Test()
 Dim crv As Curve
 Set crv = ActiveShape.Curve
 MsgBox "The curve contains:" & vbCr & _
  "Nodes: " & crv.Nodes.Count & vbCr & _
  "Segments: " & crv.Segments.Count & vbCr & _
  "Subpaths: " & crv.Subpaths.Count
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Nodes.First

Property **First** As Node

Description

Member of Nodes

The **First** property returns the first node in a Nodes collection.

The **First** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Nodes.Item

Property **Item(***Index As Long***)** As Node

Description

Member of Nodes

The **Item** property returns the specified node in a Nodes collection.

Item is the default property of the **Nodes** class, and its reference can be omitted when you are accessing items in a **Nodes** collection. For example, **Nodes.Item(2)** is the same as **Nodes(2)** — they both reference the second node object in the collection.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the node by its index number

VBA example

The following VBA example converts all nodes in the curve to cusp nodes.

```
Sub Test()
 Dim i As Long
 For i = 1 To ActiveShape.Curve.Nodes.Count
  ActiveShape.Curve.Nodes(i).Type = cdrCuspNode
 Next i
End Sub
Sub Test()
 Dim n As Node
 For Each n In ActiveShape.Curve.Nodes
  n.Type = cdrCuspNode
 Next n
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Nodes.Last

Property **Last** As Node

Description

Member of Nodes

The **Last** property returns the last node in a Nodes collection.

The **Last** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Nodes.Parent

Property **Parent** As Curve

Description

Member of Nodes

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Nodes.Range

Function **Range(***IndexArray() As Variant***)** As NodeRange

Description

Member of Nodes

The **Range** method returns a node range that contains all specified nodes in a Nodes collection.

- The **Range** method accepts a variable number of arguments. It also accepts arrays.

Parameter	Description
IndexArray	Specifies a range of index numbers that identify and group specific nodes

VBA example

The following VBA example moves nodes the first, third, and fifth nodes by two inches towards the top of the page.

```
Sub Test()
 Dim nr As NodeRange
 Set nr = ActiveShape.Curve.Nodes.Range(Array(1, 3, 5))
 nr.Move 0, 2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ObjectSnapPoint

Properties

Description

The **ObjectSnapPoint** class represents object snap points.

Copyright 2014 Corel Corporation. All rights reserved.

ObjectSnapPoint.Type

Property **Type** As cdrObjectSnapPointType

Description

Member of ObjectSnapPoint

The **Type** property returns a read-only value that is associated with the type of an object snap point.

Copyright 2014 Corel Corporation. All rights reserved.

OLE

Properties Methods

Description

The **OLE** class represents an OLE (object linking and embedding) object.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.Activate

Sub **Activate()**

Description

Member of OLE

The **Activate** method performs the default action associated with double-clicking an OLE object.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.ClassID

Property **ClassID** As String

Description

Member of OLE

The **ClassID** property returns the class ID for an OLE object.

The **ClassID** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.Deactivate

Sub **Deactivate()**

Description

Member of OLE

The **Deactivate** method finishes editing an OLE object.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.DoVerb

Sub **DoVerb(***VerbID As Long***)**

Description

Member of OLE

The **DoVerb** method performs actions specific to a given OLE object.

Parameter	Description
VerbID	

Copyright 2014 Corel Corporation. All rights reserved.

OLE.Edit

Sub **Edit()**

Description

Member of OLE

The **Edit** method edits an OLE object in-place.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.FullName

Property **FullName** As String

Description

Member of OLE

The **FullName** property returns the full name of an OLE object.

The **FullName** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.InPlaceWindowHandle

Property **InPlaceWindowHandle** As Long

Description

Member of OLE

The **InPlaceWindowHandle** property returns the in-place editing-window handle to be used in Windows API calls.

The **InPlaceWindowHandle** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.IsInPlaceActive

Property **IsInPlaceActive** As Boolean

Description

Member of OLE

The **IsInPlaceActive** property returns **True** if an OLE object is being edited in-place.

The **IsInPlaceActive** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.IsLinkUpToDate

Property **IsLinkUpToDate** As Boolean

Description

Member of OLE

The **IsLinkUpToDate** property checks whether a linked OLE object is up-to-date.

The **IsLinkUpToDate** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.IsOpen

Property **IsOpen** As Boolean

Description

Member of OLE

The **IsOpen** property returns **True** if an OLE object is being edited in a separate window.

The **IsOpen** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.IsServerRunning

Property **IsServerRunning** As Boolean

Description

Member of OLE

The **IsServerRunning** property returns **True** if the application server is running.

The **IsServerRunning** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.LinkPath

Property **LinkPath** As String

Description

Member of OLE

The **LinkPath** property returns the file path to a linked OLE object.

The **LinkPath** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.Modified

Property **Modified** As Boolean

Description

Member of OLE

The **Modified** property returns **True** if an OLE object has been modified.

The **Modified** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.Open

Sub **Open()**

Description

Member of OLE

The **Open** method edits an OLE object in a separate window.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.ProgID

Property **ProgID** As String

Description

Member of OLE

The **ProgID** property returns the program ID for an OLE object.

The **ProgID** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.ServerName

Property **ServerName** As String

Description

Member of OLE

The **ServerName** property returns the application name that is serving an OLE object.

The **ServerName** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.ShortName

Property **ShortName** As String

Description

Member of OLE

The **ShortName** property returns the short name for an OLE object.

The **ShortName** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.Type

Property **Type** As cdrOLEType

Description

Member of OLE

The **Type** property returns the type for an OLE object.

The **Type** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

OLE.UpdateLink

Sub **UpdateLink()**

Description

Member of OLE

The **UpdateLink** method updates a linked OLE object.

Copyright 2014 Corel Corporation. All rights reserved.

Outline

Properties Methods

Description

The **Outline** class represents the outline-specific settings for a shape.

Copyright 2014 Corel Corporation. All rights reserved.

Outline.BehindFill

Property **BehindFill** As Boolean

Description

Member of Outline

The **BehindFill** property determines whether to place an outline behind an object's fill. If the **BehindFill** property is set to **True**, the outline appears behind the fill.

VBA example

The following VBA example creates an ellipse, and a thick outline is placed behind the ellipse's fill.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(3, 3, 2)
 s.Fill.UniformColor.RGBAssign 255, 0, 0
 With s.Outline
  .Width = 0.2
  .Color.RGBAssign 0, 0, 255
  .BehindFill = True
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Outline.Color

Property **Color** As Color

Description

Member of Outline

The **Color** property returns or specifies the color of an outline.

VBA example 1

The following VBA example converts to grayscale all outline colors of all objects on the active page.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Outline.Type = cdrOutline Then
   s.Outline.Color.ConvertToGray
  End If
 Next s
End Sub
```

VBA example 2

The following VBA example creates a copy of the selected object's outline as a set of shapes — one for each curve segment. It then applies a color that gradually changes from black to red to each subsequent segment, causing the effect of a fountain fill on path.

```
Sub Test()
 Dim seg As Segment
 Dim sr As New ShapeRange
 Dim s As Shape, st As Shape
 Dim Steps As Long
 Set s = ActiveShape
 Optimization = True
 If s Is Nothing Then
  MsgBox "Nothing is selected."
  Exit Sub
 End If
 If s.Type <> cdrCurveShape Then
  MsgBox "A curve must be selected. Try again."
  Exit Sub
 End If
 If s.Outline.Type = cdrNoOutline Then
  MsgBox "The curve must have an outline. Try again."
  Exit Sub
 End If
 Steps = s.Curve.Segments.Count
 For Each seg In s.Curve.Segments
  Select Case seg.Type
   Case cdrLineSegment
    Set st = ActiveLayer.CreateLineSegment(_
      seg.StartNode.PositionX, seg.StartNode.PositionY, _
      seg.EndNode.PositionX, seg.EndNode.PositionY)
   Case cdrCurveSegment
    Set st = ActiveLayer.CreateCurveSegment(_
      seg.StartNode.PositionX, seg.StartNode.PositionY, _
      seg.EndNode.PositionX, seg.EndNode.PositionY, _
      seg.StartingControlPointLength, _
      seg.StartingControlPointAngle, _
      seg.EndingControlPointLength, _
      seg.EndingControlPointAngle)
  End Select
  st.Outline.Width = s.Outline.Width
  st.Outline.Color.RGBAssign 255 * seg.Index / Steps, 0, 0
  sr.Add st
 Next seg
 sr.Group
 Optimization = False
 ActiveWindow.Refresh
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Outline.CompareWith

Function **CompareWith(**Outline As Outline**)** As Boolean

Description

Member of Outline

The **CompareWith** method compares two outlines and returns **True** if they are equal.

Parameter	Description
Outline	Specifies an outline

Copyright 2014 Corel Corporation. All rights reserved.

Outline.ConvertToObject

Function **ConvertToObject()** As Shape

Description

Member of Outline

The **ConvertToObject** method converts an object's outline into a separate shape and returns the new Shape object. If the Outline.BehindFill option is enabled, the outline object appears behind the original object.

VBA example

The following VBA example creates an ellipse with a thick outline. A shape is created from the outline and is offset by **1**" both horizontally and vertically.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Set s1 = ActiveLayer.CreateEllipse2(3, 3, 2)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 s1.Outline.Width = 0.2
 s1.Outline.Color.RGBAssign 0, 0, 255
 Set s2 = s1.Outline.ConvertToObject
 s2.Move 1, 1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Outline.CopyAssign

Sub **CopyAssign(**SourceOutline As Outline**)**

Description

Member of Outline

The **CopyAssign** method copies the properties of a given outline.

Parameter	Description
SourceOutline	Specifies the source outline

Copyright 2014 Corel Corporation. All rights reserved.

Outline.DashDotLength

Property **DashDotLength** As Double

Description

Member of Outline

The **DashDotLength** property returns or specifies the absolute length of an outline's dash-dot pattern.

Copyright 2014 Corel Corporation. All rights reserved.

Outline.EndArrow

Property **EndArrow** As ArrowHead

Description

Member of Outline

The **EndArrow** property represents the ending arrowhead of an outline.

VBA example

The following VBA example applies the fifth arrowhead to the ending point of the selected curve.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveShape
 If s Is Nothing Then
  MsgBox "Nothing is selected."
  Exit Sub
 End If
 If s.Outline.Type = cdrOutline Then
  s.Outline.EndArrow = ArrowHeads(5)
 End If
End Sub
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Outline.Type = cdrOutline Then
   s.Outline.StartArrow = Nothing
   s.Outline.EndArrow = Nothing
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Outline.EndArrowOptions

Property **EndArrowOptions** As ArrowHeadOptions

Description

Member of Outline

The **EndArrowOptions** property returns or specifies right-arrowhead parameters.

Copyright 2014 Corel Corporation. All rights reserved.

Outline.GetCopy

Function **GetCopy()** As Outline

Description

Member of Outline

The **GetCopy** method returns an unattached copy of an outline object.

Copyright 2014 Corel Corporation. All rights reserved.

Outline.Justification

Property **Justification** As cdrOutlineJustification

Description

Member of Outline

The **Justification** property returns or specifies the justification settings of outlines.

Copyright 2014 Corel Corporation. All rights reserved.

Outline.LineCaps

Property **LineCaps** As cdrOutlineLineCaps

Description

Member of Outline

The **LineCaps** property returns or specifies the endpoint style of an open-path outline.

The **LineCaps** property has a value of cdrOutlineLineCaps**.**

VBA example

The following VBA example assigns round line caps and round joins to the outline of the selected shape.

```
Sub Test()
 ActiveShape.Outline.LineCaps = cdrOutlineRoundLineCaps
 ActiveShape.Outline.LineJoin = cdrOutlineRoundLineJoin
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Outline.LineJoin

Property **LineJoin** As cdrOutlineLineJoin

Description

Member of Outline

The **LineJoin** property returns or specifies the type of join for lines that intersect in an outline.

The **LineJoin** property returns a value of cdrOutlineLineJoin**.**

VBA example

The following VBA example assigns round line caps and round joins to the outline of the selected shape.

```
Sub Test()
 ActiveShape.Outline.LineCaps = cdrOutlineRoundLineCaps
 ActiveShape.Outline.LineJoin = cdrOutlineRoundLineJoin
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Outline.MiterLimit

Property **MiterLimit** As Double

Description

Member of Outline

The **MiterLimit** property returns or specifies the miter limit for outline corners.

Copyright 2014 Corel Corporation. All rights reserved.

Outline.NibAngle

Property **NibAngle** As Double

Description

Member of Outline

The **NibAngle** property returns or specifies the angle of the **Brush** tool in a calligraphic outline.

The default value of the **NibAngle** property is **0**.

VBA example

The following VBA example assigns a very thin horizontal pen nib to the outline of the active shape.

```
Sub Test()
 ActiveShape.Outline.NibAngle = 90
 ActiveShape.Outline.NibStretch = 1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Outline.NibStretch

Property **NibStretch** As Long

Description

Member of Outline

The **NibStretch** property returns or specifies the thickness of the **Brush** tool in a calligraphic outline.

Values range from **1** to **100**, and the default value is **100**.

VBA example

The following VBA example assigns a very thin horizontal pen nib to the outline of the active shape.

```
Sub Test()
 ActiveShape.Outline.NibAngle = 90
 ActiveShape.Outline.NibStretch = 1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Outline.PenWidth

Property **PenWidth** As Double

Description

Member of Outline

The **PenWidth** property returns or specifies an outline's pen width, which is used to render enhanced outlines.

Copyright 2014 Corel Corporation. All rights reserved.

Outline.PSScreen

Property **PSScreen** As PSScreenOptions

Description

Member of Outline

The **PSScreen** property specifies the PostScript halftone screen options for an outline.

The **PSScreen** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Outline.ScaleWithShape

Property **ScaleWithShape** As Boolean

Description

Member of Outline

The **ScaleWithShape** property determines whether an object's outline maintains the size proportions of the object. If this property is set to **True**, the outline's properties are scaled along with its shape.

VBA example

The following VBA example creates an ellipse and applies an outline that is **0.1**" wide. The ellipse is then enlarged to twice its previous size, and the outline's width (now at 0.2") is displayed.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(4, 4, 2)
 s.Outline.Width = 0.1
 s.Outline.ScaleWithShape = True
 s.Stretch 2
 MsgBox "Outline width is " & s.Outline.Width
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Outline.SetNoOutline

Sub **SetNoOutline()**

Description

Member of Outline

The **SetNoOutline** method removes an outline.

Copyright 2014 Corel Corporation. All rights reserved.

Outline.SetProperties

Sub **SetProperties([**Width As Double = -1**], [**Style As OutlineStyle**], [**Color As Color**], [**StartArrow As ArrowHead**], [**EndArrow As ArrowHead**], [**BehindFill As cdrTriState = cdrUndefined**], [**ScaleWithShape As cdrTriState = cdrUndefined**], [**LineCaps As cdrOutlineLineCaps = cdrOutlineUndefinedLineCaps**], [**LineJoin As cdrOutlineLineJoin = cdrOutlineUndefinedLineJoin**], [**NibAngle As Double = -9999**], [***NibStretch As Long***], [**DashDotLength As Double = -1**], [***PenWidth As Double***], [***MiterLimit As Double***])**

Description

Member of Outline

The **SetProperties** method allows you to set all outline properties with a single command.

Any missing parameter does not change the corresponding property.

Parameter	Description
Width	Specifies, in points, the width of the object's outline. This parameter is optional, and its default value is **-1**.
Style	Specifies the outline style of the object's outline. This parameter is optional, and its default value is **Nothing**.
Color	Specifies the color of the object's outline. This parameter is optional, and its default value is **Nothing**.
StartArrow	Specifies the start arrow of the object's outline. This parameter is optional, and its default value is **Nothing**.
EndArrow	Specifies the end arrow of the object's outline. This parameter is optional, and its default value is **Nothing**.
BehindFill	Determines whether the outline is behind the object's fill. This parameter is optional, and its default value is cdrUndefined (**-2**).
ScaleWithShape	Determines whether the object's outline maintains the size proportions of the object. This parameter is optional, and its default value is cdrUndefined (**-2**).
LineCaps	Specifies the endpoint style if the outline is open-path. This parameter is optional, and its default value is cdrOutlineUndefinedLineCaps (**-1**).
LineJoin	Specifies the appearance of the lines that intersect each other in the outline, and returns cdrOutlineLineJoin. This parameter is optional, and its default value is cdrOutlineUndefinedLineJoin (**-1**).
NibAngle	Specifies the angle of the **Brush** tool if the outline is calligraphic. This parameter is optional, and its default value is **-9999**.
NibStretch	Specifies the thickness of the **Brush** tool if the oultine is calligraphic. This parameter is optional, and its default value is **0**.
DashDotLength	Specifies the absolute length of the outline's dash-dot pattern. This parameter is optional, and its default value is **-1**.
PenWidth	Specifies the pen width, if the outline is enhanced. This parameter is optional, and its default value is **0**.
MiterLimit	Specifies the miter limit. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example creates a rectangle with an outline that is **0.3** inches wide. The blue outline is set behind the rectangle's fill and does not to scale to size with the rectangle. The outline's fill has round line caps and beveled line joins. The nib angle is set to **34**° with a nib stretch of **100**.

```
Sub test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(3, 3, 7, 7)
 s.Outline.SetProperties 0.3, , CreateRGBColor(0, 0, 255), , , True, _
  False, cdrOutlineRoundLineCaps, cdrOutlineBevelLineJoin, 34, 100
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Outline.SetPropertiesEx

Sub **SetPropertiesEx([**Width As Double = -1**], [**Style As OutlineStyle**], [**Color As Color**], [**StartArrow As ArrowHead**], [**EndArrow As ArrowHead**], [**BehindFill As cdrTriState = cdrUndefined**], [**ScaleWithShape As cdrTriState = cdrUndefined**], [**LineCaps As cdrOutlineLineCaps = cdrOutlineUndefinedLineCaps**], [**LineJoin As cdrOutlineLineJoin = cdrOutlineUndefinedLineJoin**], [**NibAngle As Double = -9999**], [***NibStretch As Long***], [**DashDotLength As Double = -1**], [***PenWidth As Double***], [***MiterLimit As Double***], [**Justification As cdrOutlineJustification=cdrOutlineJustificationUndefined**])**

Description

Member of Outline

The **SetPropertiesEx** method allows you to set all outline properties, including outline justification, with a single command.

Any missing parameter does not change the corresponding property.

Parameter	Description
Width	Specifies, in points, the width of the object's outline. This parameter is optional, and its default value is **-1**.
Style	Specifies the outline style of the object's outline. This parameter is optional, and its default value is **Nothing**.
Color	Specifies the color of the object's outline. This parameter is optional, and its default value is **Nothing**.
StartArrow	Specifies the start arrow of the object's outline. This parameter is optional, and its default value is **Nothing**.
EndArrow	Specifies the end arrow of the object's outline. This parameter is optional, and its default value is **Nothing**.
BehindFill	Determines whether the outline is behind the object's fill. This parameter is optional, and its default value is cdrUndefined (**-2**).
ScaleWithShape	Determines whether the object's outline maintains the size proportions of the object. This parameter is optional, and its default value is cdrUndefined (**-2**).
LineCaps	Specifies the endpoint style if the outline is open-path. This parameter is optional, and its default value is cdrOutlineUndefinedLineCaps (**-1**).
LineJoin	Specifies the appearance of the lines that intersect each other in the outline, and returns cdrOutlineLineJoin. This parameter is optional, and its default value is cdrOutlineUndefinedLineJoin (**-1**).
NibAngle	Specifies the angle of the **Brush** tool if the outline is calligraphic. This parameter is optional, and its default value is **-9999**.
NibStretch	Specifies the thickness of the **Brush** tool if the oultine is calligraphic. This parameter is optional, and its default value is **0**.
DashDotLength	Specifies the absolute length of the outline's dash-dot pattern. This parameter is optional, and its default value is **-1**.
PenWidth	Specifies the pen width, if the outline is enhanced. This parameter is optional, and its default value is **0**.
MiterLimit	Specifies the miter limit. This parameter is optional, and its default value is **0**.
Justification	Specifies the outline justification settings. This parameter is optional, and its default value is **-1**.

Copyright 2014 Corel Corporation. All rights reserved.

Outline.StartArrow

Property **StartArrow** As ArrowHead

Description

Member of Outline

The **StartArrow** property represents the starting arrowhead for an outline.

VBA example

The following VBA example replaces all starting arrowheads that are represented by the third arrow from the arrowhead list with the fifth arrowhead from the list. The color of the outline of the shape is changed to red.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  With s.Outline
   If .Type = cdrOutline Then
    If .StartArrow.Index = 3 Then
     .StartArrow = ArrowHeads(5)
     .Color.RGBAssign 255, 0, 0
    End If
   End If
  End With
 Next s
End Sub
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Outline.Type = cdrOutline Then
   s.Outline.StartArrow = Nothing
   s.Outline.EndArrow = Nothing
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Outline.StartArrowOptions

Property **StartArrowOptions** As ArrowHeadOptions

Description

Member of Outline

The **StartArrowOptions** property returns or specifies left-arrowhead parameters.

Copyright 2014 Corel Corporation. All rights reserved.

Outline.Style

Property **Style** As OutlineStyle

Description

Member of Outline

The **Style** property returns an OutlineStyle object that represents the outline style (for example, solid, dashed, and so on).

VBA example

The following VBA example searches through all shapes on the active page. If the width of a shape's outline is greater than **0.1**", a **Dot** outline style is applied to the shape.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Outline.Width > 0.1 Then
   s.Outline.Style = OutlineStyles(1)
  End If
 Next s
End Sub
Sub Test()
 With ActiveShape.Outline
  .Width = 0.03
  .Style.DashCount = 2
  .Style.DashLength(1) = 1
  .Style.DashLength(2) = 10
  .Style.GapLength(1) = 4
  .Style.GapLength(2) = 4
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Outline.Type

Property **Type** As cdrOutlineType

Description

Member of Outline

The **Type** property lets you remove an outline or check whether an outline is available for a shape.

The **Type** property returns a value of cdrOutlineType.

VBA example

The following VBA example removes the outline from the selected shape.

```
Sub Test()
 ActiveShape.Outline.Type = cdrNoOutline
End Sub
Sub Test()
 If ActiveShape.Outline.Type = cdrNoOutline Then
  ActiveShape.Outline.Width = 0.1
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Outline.UserAssign

Function **UserAssign([***ParentWindowHandle As Long***])** As Boolean

Description

Member of Outline

The **UserAssign** method displays the **Outline Properties** dialog box.

Parameter	Description
ParentWindowHandle	Specifies the handle of the parent window. This parameter is optional, and its default value is **0**.

Copyright 2014 Corel Corporation. All rights reserved.

Outline.Width

Property **Width** As Double

Description

Member of Outline

The **Width** property returns or specifies the width, in points, of a shape's outline. Assigning a value to this property automatically adds an outline to the shape if one does not already exist.

VBA example

The following VBA example creates an ellipse with an outline that is **0.1**" in width.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(4, 4, 2)
 s.Outline.Width = 0.1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

OutlineStyle

Properties

Description

The **OutlineStyle** class represents the dash style applied to an outline.

Copyright 2014 Corel Corporation. All rights reserved.

OutlineStyle.DashCount

Property **DashCount** As Long

Description

Member of OutlineStyle

The **DashCount** property specifies how many pairs of dashes and gaps appear in an outline style. In an outline style, the number of dash and gap pairs can range from one to five.

VBA example

The following VBA example applies a custom outline style to the selected shape. The new outline appears as a small dot followed by a long dash, with equal gaps between each dash.

```
Sub Test()
 With ActiveShape.Outline
  .Width = 0.03
  .Style.DashCount = 2
  .Style.DashLength(1) = 1
  .Style.DashLength(2) = 10
  .Style.GapLength(1) = 4
  .Style.GapLength(2) = 4
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

OutlineStyle.DashLength

Property **DashLength(***Index As Long***)** As Long

Description

Member of OutlineStyle

The **DashLength** property returns or specifies the length of each dash in an outline style. The number of dash/gap pairs can range from one to five. The length of each dash is calculated as a multiple of the width of the outline and is measured in document units. For example, if **DashLength(1) = 2** and the width of the outline is **0.5**", then the length of the first dash in the dash/gap pair is **1**".

Parameter	Description
Index	Specifies the dash/gap pair for the outline style

VBA example

The following VBA example creates the dash/gap pattern of a selected dashed outline as a set of rectangles at the bottom of the page.

```
Sub Test()
 Const w As Double = 0.2
 Dim x As Double, dx As Double
 Dim i As Long
 Dim s As Shape
 With ActiveShape.Outline
  If .Type = cdrOutline Then
   For i = 1 To .Style.DashCount
    dx = .Style.DashLength(i) * w
    Set s = ActiveLayer.CreateRectangle(x, 0, x + dx, w)
    s.Fill.UniformColor.RGBAssign 255, 0, 0
    x = x + dx
    dx = .Style.GapLength(i) * w
    Set s = ActiveLayer.CreateRectangle(x, 0, x + dx, w)
    s.Fill.UniformColor.RGBAssign 255, 255, 0
    x = x + dx
   Next i
  End If
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

OutlineStyle.Enhanced

Property **Enhanced** As Boolean

Description

Member of OutlineStyle

The **Enhanced** method returns **True** if an outline style refers to an enhanced outline.

The **Enhanced** method returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

OutlineStyle.GapLength

Property **GapLength(***Index As Long***)** As Long

Description

Member of OutlineStyle

The **GapLength** property returns or specifies the length of each gap in an outline style. The number of dash/gap pairs can range from one to five. The length of each gap is calculated as a multiple of the width of the outline and is measured in document units. For example, if **GapLength(1) = 2** and the width of the outline is **0.5**", then the length of the first gap in the dash/gap pair is **1**".

Parameter	Description
Index	Specifies the dash/gap pair for the outline style

VBA example

The following VBA example creates the dash/gap pattern of a selected dashed outline as a set of rectangles at the bottom of the page.

```
Sub Test()
 Const w As Double = 0.2
 Dim x As Double, dx As Double
 Dim i As Long
 Dim s As Shape
 With ActiveShape.Outline
  If .Type = cdrOutline Then
   For i = 1 To .Style.DashCount
    dx = .Style.DashLength(i) * w
    Set s = ActiveLayer.CreateRectangle(x, 0, x + dx, w)
    s.Fill.UniformColor.RGBAssign 255, 0, 0
    x = x + dx
    dx = .Style.GapLength(i) * w
    Set s = ActiveLayer.CreateRectangle(x, 0, x + dx, w)
    s.Fill.UniformColor.RGBAssign 255, 255, 0
    x = x + dx
   Next i
  End If
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

OutlineStyle.Index

Property **Index** As Long

Description

Member of OutlineStyle

The **Index** property returns the index number of a dash style in the OutlineStyles collection. If the outline style is not saved in the global style collection, this property returns **-1**.

The **Index** property returns a read-only value.

VBA example

The following VBA example changes all dotted outlines to long-dashed outlines.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Outline.Type = cdrOutline Then
   If s.Outline.Style.Index = 1 Then
    s.Outline.Style = OutlineStyles(7)
   End If
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

OutlineStyles

Properties Methods

Description

The **OutlineStyles** class represents the set of dash styles (or OutlineStyle objects) available to outlines.

Copyright 2014 Corel Corporation. All rights reserved.

OutlineStyles.Add

Function **Add()** As OutlineStyle

Description

Member of OutlineStyles

The **Add** method adds a new outline style to the OutlineStyles collection.

- You can call the Save method after you modify the list of outline styles so that the changes are available the next time you start CorelDRAW.

VBA example

The following VBA example creates a new outline style and applies the new style to a line segment that is created on the active layer. After the style has been added to the **OutlineStyles** collection, it can be accessed through both the collection and the **Outline Properties** dialog box.

```
Sub Test()
 Dim s As Shape
 Dim stl As OutlineStyle
 Set stl = OutlineStyles.Add()
 stl.DashCount = 1
 stl.DashLength(1) = 20
 stl.GapLength(1) = 1
 OutlineStyles.Save
 Set s = ActiveLayer.CreateLineSegment(0, 0, 5, 5)
 s.Outline.Width = 0.1
 s.Outline.Style = stl
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

OutlineStyles.AddStyle

Function **AddStyle(**Style As OutlineStyle**)** As OutlineStyle

Description

Member of OutlineStyles

The **AddStyle** method adds a new outline style to the OutlineStyles collection. The new style is based on an existing style.

- You can call the Save method after you modify the list of outline styles so that the changes are available the next time you start CorelDRAW.

This method returns an OutlineStyle object.

Parameter	Description
Style	Specifies the style from which to copy the dash/gap pattern

VBA example

The following VBA example creates a custom outline style based on the second outline in the collection. The changes are then saved.

```
Sub Test()
 Dim stl As OutlineStyle
 Set stl = OutlineStyles.AddStyle(OutlineStyles(2))
 stl.DashLength(1) = 3
 OutlineStyles.Save
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

OutlineStyles.Application

Property **Application** As Application

Description

Member of OutlineStyles

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

OutlineStyles.Count

Property **Count** As Long

Description

Member of OutlineStyles

The **Count** property returns the number of outline styles available.

The **Count** property returns a read-only value.

VBA example

The following VBA example creates lines and applies a different outline style to each of them.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim i As Long
 Dim y As Double
 Set d = CreateDocument()
 For i = 1 To OutlineStyles.Count
  y = i * 0.3
  Set s = d.ActiveLayer.CreateLineSegment(0, y, 5, y)
  s.Outline.Width = 0.01
  s.Outline.Style = OutlineStyles(i)
 Next i
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

OutlineStyles.Item

Property **Item(***Index As Long***)** As OutlineStyle

Description

Member of OutlineStyles

The **Item** property returns a specified outline style from an OutlineStyles collection.

Item is the default property of the **OutlineStyles** class, and its reference can be omitted when you are accessing items in an **OutlineStyles** collection. For example, **OutlineStyles.Item(2)** is the same as **OutlineStyles(2)** — they both reference the second outline style object in the collection.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies an outline style by its index number

VBA example 1

The following VBA example applies a dotted outline style (the second option in the **Style** list of the **Outline Properties** dialog box) to the selected shape.

```
Sub Test()
 ActiveShape.Outline.Style = OutlineStyles(2)
End Sub
```

VBA example 2

```
The following VBA example creates a sample of each available outline style by creating lines and applying a style
to each one in turn.
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim stl As OutlineStyle
 Dim y As Double
 Set d = CreateDocument()
 For Each stl In OutlineStyles
  y = stl.Index * 0.3
  Set s = d.ActiveLayer.CreateLineSegment(0, y, 5, y)
  s.Outline.Width = 0.01
  s.Outline.Style = stl
 Next stl
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

OutlineStyles.Parent

Property **Parent** As Application

Description

Member of OutlineStyles

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

OutlineStyles.Remove

Sub **Remove(***Index As Long***)**

Description

Member of OutlineStyles

The **Remove** method removes an outline style from the OutlineStyles collection.

Parameter	Description
Index	Specifies the outline style to remove

VBA example

The following VBA example creates an outline style, applies it to a line segment, and then removes the style from the collection.

```
Sub Test()
 Dim s As Shape
 Dim stl As OutlineStyle
 Set stl = OutlineStyles.Add()
 stl.DashCount = 1
 stl.DashLength(1) = 20
 stl.GapLength(1) = 1
 OutlineStyles.Save
 Set s = ActiveLayer.CreateLineSegment(0,0,5,5)
 s.Outline.Width = 0.1
 s.Outline.Style = stl
 OutlineStyles.Remove stl.Index
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

OutlineStyles.Save

Sub **Save()**

Description

Member of OutlineStyles

The **Save** method saves the list of outline styles. Calling this method after modifying the list of outline styles ensures that the changes are available the next time you start CorelDRAW.

VBA example

The following VBA example creates a custom outline style based on the second outline in the collection. The changes are then saved.

```
Sub Test()
 Dim stl As OutlineStyle
 Set stl = OutlineStyles.AddStyle(OutlineStyles(2))
 stl.DashLength(1) = 3
 OutlineStyles.Save
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page

Properties Methods

Description

The **Page** class represents a page in a document.

Copyright 2014 Corel Corporation. All rights reserved.

Page.Activate

Sub **Activate()**

Description

Member of Page

The **Activate** method makes a specified page active.

VBA example

The following VBA example activates the first page and displays it on the screen.

```
Sub Test()
 ActiveDocument.Pages(1).Activate
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.ActiveLayer

Property **ActiveLayer** As Layer

Description

Member of Page

The **ActiveLayer** property returns the active layer of a specified page.

The **ActiveLayer** property returns a read-only value.

VBA example

The following VBA example places page numbers on each page of the document.

```
Sub Test()
 Dim p As Page
 For Each p In ActiveDocument.Pages
  p.ActiveLayer.CreateArtisticText 0, 0, "Page " & p.Index
 Next p
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.AllLayers

Property **AllLayers** As Layers

Description

Member of Page

The **AllLayers** property returns a collection of all layers on the page, including the master layers.

The **AllLayers** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Page.Application

Property **Application** As Application

Description

Member of Page

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Page.Background

Property **Background** As cdrPageBackground

Description

Member of Page

The **Background** property returns or specifies the type of background for a page.

The **Background** property returns a value of cdrPageBackground. A background can contain a bitmap image, a solid fill, or nothing at all.

VBA example

The following VBA example displays the type of background for the specified page.

```
Sub Test()
 Select Case ActiveDocument.Pages(0).Background
  Case cdrPageBackgroundNone
   MsgBox "No page background"
  Case cdrPageBackgroundSolid
   MsgBox "Solid color background"
  Case cdrPageBackgroundBitmap
   MsgBox "Bitmap page background"
 End Select
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.Bleed

Property **Bleed** As Double

Description

Member of Page

The **Bleed** property returns or specifies the bleed of a page.

VBA example

The following VBA example sets the bleed value to **0.1**", the document resolution to **150** dpi, and the page background to yellow (which is omitted when printing or exporting the document).

```
Sub Test()
 With ActiveDocument.Pages(0)
  .Color.RGBAssign 255, 255, 0
  .PrintExportBackground = False
  .Bleed = 0.1
  .Resolution = 150
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.BottomY

Property **BottomY** As Double

Description

Member of Page

The **BottomY** property returns the y-coordinate of the page's bottom edge.

The **BottomY** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Page.BoundingBox

Property **BoundingBox** As Rect

Description

Member of Page

The **BoundingBox** property returns the bounding rectangle around the page.

The **BoundingBox** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Page.CenterX

Property **CenterX** As Double

Description

Member of Page

The **CenterX** property returns the x-coordinate of the center of the page.

The **CenterX** property returns a read-only value.

VBA example

The following VBA example creates an ellipse with a radius of **2**" at the center of the active page.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(ActivePage.CenterX, ActivePage.CenterY, 2)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.CenterY

Property **CenterY** As Double

Description

Member of Page

The **CenterY** property returns the y-coordinate of the center of the page.

The **CenterY** property returns a read-only value.

VBA example

The following VBA example creates an ellipse with a radius of **2**" at the center of the active page.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(ActivePage.CenterX, ActivePage.CenterY, 2)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.Color

Property **Color** As Color

Description

Member of Page

The **Color** property returns or specifies the background color of a page.

- The **Color** property applies only if the Background property is set to cdrPageBackgroundSolid.

VBA example

The following VBA example creates a red background in the master page of the active document. Applying a red background to the master page applies that background to every page in the document.

```
Sub Test()
 ActiveDocument.Pages(0).Color.RGBAssign 255, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.CreateLayer

Function **CreateLayer(***LayerName As String***)** As Layer

Description

Member of Page

The **CreateLayer** method adds a new layer to a document. If the layer is created on a master page, it becomes a master layer.

Parameter	Description
LayerName	Specifies the name of the new layer

VBA example

The following VBA example adds a new layer named **MyLayer** to the active page and creates a rectangle on the new layer.

```
Sub Test()
 Dim lr As Layer
 Set lr = ActivePage.CreateLayer("MyLayer")
 lr.CreateRectangle 0, 0, 2, 2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.CustomCommand

Function **CustomCommand(***ComponentID As String***,** *CommandID As String***,** *Parameter() As Variant***)** As Variant

Description

Member of Page

The **CustomCommand** method executes a page-specific command provided by a component.

Parameter	Description
ComponentID	Specifies the component ID
CommandID	Specifies the command ID
Parameter	Specifies the parameters

Copyright 2014 Corel Corporation. All rights reserved.

Page.Delete

Sub **Delete()**

Description

Member of Page

The **Delete** method removes a page from a document and deletes all shapes on that page.

VBA example

The following VBA example deletes all empty pages in the active document.

```
Sub Test()
 Dim p As Page
 For Each p In ActiveDocument.Pages
  If p.Shapes.Count = 0 Then p.Delete
 Next p
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.DesktopLayer

Property **DesktopLayer** As Layer

Description

Member of Page

The **DesktopLayer** property returns the desktop layer on a given page.

The **DesktopLayer** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Page.FindClosestSnapPoint

Function **FindClosestSnapPoint(**TypeSet As cdrPointType**,** *PositionX As Double*, *PositionY As Double*, **[**HotArea As Double = -1**])** As SnapPoint

Description

Member of Page

The **FindShape** method finds a snap point closest to the given point on a page.

Parameter	Description
TypeSet	Specifies the snap-point type
PositionX	Specifies the x-coordinate of the specified point on the page
PositionY	Specifies the y-coordinate of the specified point on the page
HotArea	Specifies the area in which to search. This parameter is optional, and its default value is **-1**.

Copyright 2014 Corel Corporation. All rights reserved.

Page.FindShape

Function **FindShape([***Name As String***], [**Type As cdrShapeType = cdrNoShape**], [***StaticID As Long***], [**Recursive As Boolean = True**])** As Shape

Description

Member of Page

The **FindShape** method locates a shape that has the specified properties. If the shape cannot be found on the page, an empty reference (**Nothing**) is returned.

Parameter	Description
Name	Specifies the name of the shape on the page. This parameter is optional.
Type	Specifies the type of shape, and returns cdrShapeType. This parameter is optional, and its default value is cdrNoShape (**0**).
StaticID	Specifies the shape's unique ID. This parameter is optional, and its default value is **0**.
Recursive	Specifies whether to iterate through all shapes. This parameter is optional, and its default value is **True**.

VBA example

The following VBA example finds a rectangle named **Frame** and selects it.

```
Sub Test()
 Dim s As Shape
 Set s = ActivePage.FindShape(Name:="Frame", Type:=cdrRectangleShape)
 If s Is Nothing Then
  MsgBox "The rectange 'Frame' cannot be found on page " & ActivePage.Index
 Else
  s.CreateSelection
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.FindShapes

Function **FindShapes([***Name As String***], [**Type As cdrShapeType = cdrNoShape**], [**Recursive As Boolean = True**]) As** ShapeRange

Description

Member of Page

The **FindShapes** method locates all shapes that have certain properties on a page. It returns a ShapeRange object that contains all shapes that are found.

Parameter	Description
Name	Specifies the name of the shape on the page. This parameter is optional.
Type	Specifies the type of shape, and returns cdrShapeType. This parameter is optional, and its default value is cdrNoShape (**0**).
Recursive	Specifies whether to iterate through all shapes. This parameter is optional, and its default value is **True**.

VBA example

The following VBA example finds all rectangles on the active page and fills them with a uniform red fill.

```
Sub Test()
 Dim sr As ShapeRange
 Set sr = ActivePage.FindShapes(Type:=cdrRectangleShape)
 If sr.Count <> 0 Then
  sr.ApplyUniformFill CreateRGBColor(255, 0, 0)
 Else
  MsgBox "There are no rectangles on the current page"
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.GetBoundingBox

Sub **GetBoundingBox(***x As Double*, *y As Double*, *Width As Double*, *Height As Double***)**

Description

Member of Page

The **GetBoundingBox** method returns the position of lower-left corner of a page and the page dimensions.

Parameter	Description
x	Specifies the x-coordinate of the lower-left corner of the page
y	Specifies the y-coordinate of the lower-left corner of the page
Width	Specifies the width of the page
Height	Specifies the height of the page

Copyright 2014 Corel Corporation. All rights reserved.

Page.GetCenterPosition

Sub **GetCenterPosition(***CenterX As Double***,** *CenterY As Double***)**

Description

Member of Page

The GetCenterPosition method returns the x-and y-coordinates of the center of a page.

Parameter	Description
CenterX	Specifies the x-coordinate of the center of the page
CenterY	Specifies the y-coordinate of the center of the page

Copyright 2014 Corel Corporation. All rights reserved.

Page.GetObjectsBoundingBox

Sub **GetObjectsBoundingBox([**SelectedOnly As Boolean = False**], [**IncludeNonPrintable As Boolean = False**]) As** Rect

Description

Member of Page

The **GetObjectsBoundingBox** method returns the bounding rectangle for the objects on a page.

Parameter	Description
SelectedOnly	Specifies whether to include only the selected objects. This parameter is optional, and its default value is **False**.
IncludeNonPrintable	Specifies whether to include non-printable objects. This parameter is optional, and its default value is **False**.

Copyright 2014 Corel Corporation. All rights reserved.

Page.GetSize

Sub **GetSize(***Width As Double***,** *Height As Double***)**

Description

Member of Page

The **GetSize** method returns both the width and height of a page.

Parameter	Description
Width	Specifies the width of the page, measured in document units
Height	Specifies the height of a page, measured in document units

VBA example

The following VBA example creates a rectangle with the size of active page (that is, the page frame).

```
Sub Test()
 Dim sx As Double, sy As Double
 ActivePage.GetSize sx, sy
 ActiveLayer.CreateRectangle2 0, 0, sx, sy
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.GridLayer

Property **GridLayer** As Layer

Description

Member of Page

The **GridLayer** property returns the grid layer on a given page.

The **GridLayer** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Page.Guides

Property **Guides([**Type As cdrGuideType = cdrAllGuides**])** As ShapeRange

Description

Member of Page

The **Guides** property returns a set of local guidelines defined on the page.

The **Guides** property returns a read-only value.

Parameter	Description
Type	Specifies the type of guideline on a page, and returns cdrGuideType. This parameter is optional, and its default value is cdrAllGuides (**-1**).

VBA example

The following VBA example deletes all of the local vertical guidelines on the active page.

```
Sub Test()
 ActiveDocument.MasterPage.Guides(cdrVerticalGuide).Delete
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.GuidesLayer

Property **GuidesLayer** As Layer

Description

Member of Page

The **GuidesLayer** property returns the guideline layer on a given page.

The **GuidesLayer** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Page.Index

Property **Index** As Long

Description

Member of Page

The **Index** property returns the index number of a page.

The **Index** property returns a read-only value.

VBA example

The following VBA example places page numbers on each page of the document.

```
Sub Test()
 Dim p As Page
 Dim s As Shape
 For Each p In ActiveDocument.Pages
  Set s = p.ActiveLayer.CreateArtisticText(p.SizeWidth / 2, 0.5, "- Page " & p.Index & " -")
  s.Text.AlignProperties.Alignment = cdrCenterAlignment
 Next p
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.Layers

Property **Layers** As Layers

Description

Member of Page

The **Layers** property returns the collection of all layers in a document. If you want to access a master layer, you can use the master page returned by **Pages(0)**.

The **Layers** property returns a read-only value.

VBA example

The following VBA example creates a text object on each layer of the page. The text object contains the name of the corresponding layer.

```
Sub Test()
 Dim lyr As Layer
 Dim n As Long
 n = 0
 For Each lyr In ActivePage.Layers
  lyr.CreateArtisticText 0, n, lyr.Name
  n = n + 1
 Next lyr
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.LeftX

Property **LeftX** As Double

Description

Member of Page

The **LeftX** property returns the x-coordinate of a page's left edge.

The **LeftX** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Page.MoveTo

Sub **MoveTo(***Index As Long***)**

Description

Member of Page

The **MoveTo** method moves a page to a specified position in the document.

Parameter	Description
Index	Specifies a new index number for the page, thereby repositioning the page in the Pages collection

VBA example

The following VBA example moves the second page to the beginning of the document.

```
Sub Test()
 ActiveDocument.Pages(2).MoveTo 1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.Name

Property **Name** As String

Description

Member of Page

The **Name** property returns or specifies the name of a page.

VBA example

The following VBA example displays the name of the active page.

```
Sub Test()
 MsgBox "Current Page: " & ActivePage.Name
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.Next

Property **Next** As Page

Description

Member of Page

The **Next** property returns the next page in a document.

The **Next** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Page.Orientation

Property **Orientation** As cdrPageOrientation

Description

Member of Page

The **Orientation** property returns or specifies the orientation of a page. When setting a different orientation for the page, the values for the width and height are exchanged.

The **Orientation** property returns a value of cdrPageOrientation.

VBA example

The following VBA example inserts a text object on each page, indicating the page orientation of the page.

```
Sub Test()
 Dim Orient As String
 Dim p As Page
 For Each p In ActiveDocument.Pages
  If p.Orientation = cdrPortrait Then
   Orient = "Portrait"
  Else
   Orient = "Landscape"
  End If
  p.ActiveLayer.CreateArtisticText 0, 0, Orient
 Next p
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.Paper

Property **Paper** As String

Description

Member of Page

The **Paper** property returns the name of the paper size, if such a name exists.

The **Paper** property returns a read-only value.

VBA example

The following VBA example checks whether the active page size is set to letter-sized (8.5" × 11") paper. If it is not letter-sized, the correct values are applied to the SizeWidth and SizeHeight values.

```
Sub Test()
 If ActivePage.Paper <> "Letter" Then
  ActivePage.SizeWidth = 8.5
  ActivePage.SizeHeight = 11
 End If
End Sub
```

VBA example

```
The following VBA example displays a warning if the selected paper size is not a standard one.
Sub Test()
 If ActivePage.Paper = "Custom" Then
  MsgBox "Attention: non-standard page size used!"
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.Parent

Property **Parent** As Pages

Description

Member of Page

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Page.Previous

Property **Previous** As Page

Description

Member of Page

The **Previous** property returns the previous page in a document.

The **Previous** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Page.PrintExportBackground

Property **PrintExportBackground** As Boolean

Description

Member of Page

The **PrintExportBackground** property returns or specifies whether the background of a page is printed or exported.

VBA example

The following VBA example sets the bleed value to **0.1**", the document resolution to **150** dpi, and the page background to yellow (which is omitted when printing or exporting the document).

```
Sub Test()
 With ActiveDocument.Pages(0)
  .Color.RGBAssign 255, 255, 0
  .PrintExportBackground = False
  .Bleed = 0.1
  .Resolution = 150
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.Properties

Property **Properties** As Properties

Description

Member of Page

The **Properties** property returns the Properties collection, which allows you to specify and manipulate custom data associated with a page.

The **Properties** property returns a read-only value.

VBA example 1

The following VBA example creates **100** shapes and stores their IDs for future reference in the active page.

```
Sub CreateAndStoreShapes()
 Dim i As Long
 Dim x As Double, y As Double, r As Double
 Dim MaxX As Double, MaxY As Double, MaxR As Double
 Dim s As Shape, Num As Long
 MaxX = ActivePage.SizeWidth
 MaxY = ActivePage.SizeHeight
 MaxR = 1
 Num = 100
 ' Store the total number of shapes
 ActivePage.Properties("ShapeArray", 0) = Num
 For i = 1 To Num
  x = Rnd() * MaxX
  y = Rnd() * MaxY
  r = Rnd() * MaxR
  Set s = ActiveLayer.CreateEllipse2(x, y, r)
  s.Fill.UniformColor.RGBAssign Rnd() * 256, Rnd() * 256, Rnd() * 256
  ' Store the current shape's ID number
  ActivePage.Properties("ShapeArray", i) = s.StaticID
 Next i
End Sub
```

VBA example 2

The following VBA example retrieves all shape references stored in the page and deletes them.

```
Sub DeleteStoredShapes()
 Dim s As Shape, sr As New ShapeRange
 Dim v As Variant
 Dim Num As Long, i As Long, id As Long
 v = ActivePage.Properties("ShapeArray", 0) ' Retrieving the total number of shape references stored
 If Not IsNull(v) Then
  ' Deleting the property
  ActivePage.Properties.Delete "ShapeArray", 0
  Num = v
  ActiveDocument.ClearSelection
  For i = 1 To Num
   ' Getting the current shape's ID to find
   id = ActivePage.Properties("ShapeArray", i)
   Set s = ActivePage.FindShape(StaticID:=id)
   ' Add the shape to the shape range
   If Not s Is Nothing Then sr.Add s
   ' Delete the property
   ActivePage.Properties.Delete "ShapeArray", i
  Next i
  sr.Delete ' Delete all shapes found
 Else
  MsgBox "No shape references are stored in the active page."
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.Resolution

Property **Resolution** As Long

Description

Member of Page

The **Resolution** property returns or specifies the resolution for bitmap rendering, measured in dots per inch (dpi).

VBA example

The following VBA example sets the bleed value to **0.1**", the document resolution to **150** dpi, and the page background to yellow (which is omitted when printing or exporting the document).

```
Sub Test()
 With ActiveDocument.Pages(0)
  .Color.RGBAssign 255, 255, 0
  .PrintExportBackground = False
  .Bleed = 0.1
  .Resolution = 150
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.RightX

Property **RightX** As Double

Description

Member of Page

The **RightX** property returns the x-coordinate of a page's right edge.

The **RightX** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Page.SelectableShapes

Property **SelectableShapes** As Shapes

Description

Member of Page

The **SelectableShapes** property returns the collection of all selectable shapes on a page.

The **SelectableShapes** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Page.SelectShapesAtPoint

Function **SelectShapesAtPoint(***x As Double***,** *y As Double***,** *SelectUnfilled As Boolean***, [**HotArea As Double = -1**])** As Shape

Description

Member of Page

The **SelectShapesAtPoint** method selects all shapes at a specified point in a document. This method creates a new selection and returns the selection-shape object.

Parameter	Description
x	Specifies, in document units, the x-coordinate of the point
y	Specifies, in document units, the y-coordinate of the point
SelectUnfilled	Specifies whether to select the shapes inside the shape
HotArea	Specifies the area around the point to include. This parameter is optional, and its default value is **-1**.

VBA example

The following VBA example allows the user to click over a shape. The shape's fill is then changed by shifting its hue by **30**°.

```
Sub Test()
 Dim d As Document
 Dim sel As Shape, s As Shape
 Dim x As Double, y As Double, Shift As Long
 Dim c As New Color
 Set d = ActiveDocument
 d.ShapeEnumDirection = cdrShapeEnumBottomFirst
 While d.GetUserClick(x, y, Shift, 100, False, cdrCursorWinArrow) = 0
  Set sel = d.ActivePage.SelectShapesAtPoint(x, y, False)
  If sel.Shapes.Count > 0 Then
   Set s = sel.Shapes(1)
   d.ClearSelection
   s.AddToSelection
   If s.Fill.Type <> cdrUniformFill Then
    s.Fill.UniformColor.RGBAssign 255, 0, 0
   Else
    c.CopyAssign s.Fill.UniformColor
    c.ConvertToHLS
    c.HLSHue = (c.HLSHue + 30) Mod 360
    s.Fill.ApplyUniformFill c
   End If
  End If
 Wend
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.SelectShapesFromRectangle

Function **SelectShapesFromRectangle(***x1 As Double*, *y1 As Double*, *x2 As Double*, *y2 As Double*, *Touch As Boolean***)** As Shape

Description

Member of Page

The **SelectShapesFromRectangle** method selects all shapes within a given rectangle as if selected with a marquee.

This method creates a new selection and returns the selection-shape object.

Parameter	Description
x1	Specifies the x-coordinate of the upper-left corner of the rectangle, measured in document units
y1	Specifies the y-coordinate of the upper-left corner of the rectangle, measured in document units
x2	Specifies the x-coordinate of the lower-right corner of the rectangle, measured in document units
y2	Specifies the y-coordinate of the lower-right corner of the rectangle, measured in document units
Touch	Specifies whether to select shapes not completely enclosed within the rectangle **True** selects shapes not completely enclosed within the rectangle.

VBA example

The following VBA example allows the user to pick a color, which is used to fill all shapes in a defined area. This procedure repeats until **Esc** is pressed.

```
Sub Test()
 Dim d As Document
 Dim sel As Shape, s As Shape
 Dim x1 As Double, y1 As Double, x2 As Double, y2 As Double, Shift As Long
 Dim c As New Color
 Set d = ActiveDocument
 c.UserAssign
 While d.GetUserArea(x1, y1, x2, y2, Shift, 100, False, cdrCursorWinCross) = 0
  Set sel = d.ActivePage.SelectShapesFromRectangle(x1, y1, x2, y2, False)
  For Each s In sel.Shapes
   s.Fill.ApplyUniformFill c
  Next s
 Wend
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.SelectSize

Sub **SelectSize(***PageSizeName As String***, [**Landscape As Boolean = False**])**

Description

Member of Page

The **SelectSize** method changes the page size based on a given preset page-size name.

Parameter	Description
PageSizeName	Specifies the page-size name
Landscape	Specifies whether the page layout is landscape. This parameter is optional, and its default value is **False**.

Copyright 2014 Corel Corporation. All rights reserved.

Page.SetSize

Sub **SetSize(***Width As Double***,** *Height As Double***)**

Description

Member of Page

The **SetSize** method sets both the width and height of a page.

Parameter	Description
Width	Specifies the width of the page, measured in document units
Height	Specifies the height of the page, measured in document units

VBA example

The following VBA example sets the width of the active page to **4.25**" and the height to **5.5**".

```
Sub Test()
 ActivePage.SetSize 4.25, 5.5
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.Shapes

Property **Shapes** As Shapes

Description

Member of Page

The **Shapes** property returns the collection of shapes on a page.

The **Shapes** property returns a read-only value.

The following code fills each object on the active page with the color assigned to the layer it reside on (that is, the layer-override color).

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  s.Fill.ApplyUniformFill s.Layer.Color
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.SizeHeight

Property **SizeHeight** As Double

Description

Member of Page

The **SizeHeight** property returns or specifies the height of a page.

VBA example

The following VBA example sets all document pages to **5**" × **11**".

```
Sub Test()
 Dim p As Page
 For Each p In ActiveDocument.Pages
  p.SizeWidth = 5
  p.SizeHeight = 11
 Next p
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.SizeWidth

Property **SizeWidth** As Double

Description

Member of Page

The **SizeWidth** property returns or specifies the width of a page.

VBA example

The following VBA example sets all document pages to **5**" × **11**".

```
Sub Test()
 Dim p As Page
 For Each p In ActiveDocument.Pages
  p.SizeWidth = 5
  p.SizeHeight = 11
 Next p
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.Spread

Property **Spread** As Spread

Description

Member of Page

The **Spread** property returns a read-only value that is associated with the page spread to which the current page belongs.

Copyright 2014 Corel Corporation. All rights reserved.

Page.TextFind

Function **TextFind(***Text As String***,** *CaseSensitive As Boolean***)** As Shape

Description

Member of Page

The **TextFind** method finds a text object that contains the specified text.

Parameter	Description
Text	Specifies the text to search for
CaseSensitive	Specifies whether the search string is case-sensitive If the parameter is set to **True**, the text in the **Text** parameter must match the case of the text in the text range.

VBA example

The following VBA example creates three text objects, finds the text object that contains the word **Sentence**, and fills the text object with red.

```
Sub Test()
 Dim s As Shape
 ActiveLayer.CreateArtisticText 0, 0, "Text1"
 ActiveLayer.CreateArtisticText 0, 3, "Some Sentence."
 ActiveLayer.CreateArtisticText 0, 5, "Word"
 Set s = ActivePage.TextFind("Sentence", True)
 If Not s Is Nothing Then
  s.Fill.UniformColor.RGBAssign 255, 0, 0
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.TextReplace

Sub **TextReplace(***OldText As String*, *NewText As String*, *CaseSensitive As Boolean*, **[**ReplaceSelectedOnly As Boolean = True**])**

Description

Member of Page

The **Replace** method finds and replaces a specified text string.

Parameter	Description
OldText	Specifies the text to be replaced
NewText	Specifies the new text
CaseSensitive	Specifies whether the search string is case-sensitive
ReplaceSelectedOnly	Specifies whether only the selected text is to be replaced with the **TextReplace** method. This parameter is optional, and its default value is **True**.

VBA example

The following VBA example creates three text objects and replaces the word **Some** with **Short** (resulting in one of the text objects becoming **Short Sentence**).

```
Sub Test()
 ActiveLayer.CreateArtisticText 0, 0, "Text1"
 ActiveLayer.CreateArtisticText 0, 3, "Some Sentence."
 ActiveLayer.CreateArtisticText 0, 5, "Word"
 ActivePage.TextReplace "Some", "Short", True, False
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Page.TopY

Property **TopY** As Double

Description

Member of Page

The **TopY** property returns the y-coordinate of a page's top edge.

The **TopY** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Page.TreeNode

Property **TreeNode** As TreeNode

Description

Member of Page

The **TreeNode** property returns the tree-node object corresponding to a given page.

The **TreeNode** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Page.UnlockAllShapes

Sub **UnlockAllShapes()**

Description

Member of Page

The **UnlockAllShapes** method unlocks all locked shapes on a page. When objects on a page are unlocked, they can be edited.

VBA example

The following VBA example unlocks all shapes on the active page.

```
Sub CountProp()
 ActivePage.UnlockAllShapes
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Pages

Properties

Description

The **Pages** class represents a collection of all pages (or Page objects) in a document.

Copyright 2014 Corel Corporation. All rights reserved.

Pages.Application

Property **Application** As Application

Description

Member of Pages

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Pages.Count

Property **Count** As Long

Description

Member of Pages

The **Count** property returns the number of pages in a document.

The **Count** property returns a read-only value.

VBA example

The following VBA example returns a message if the document contains only one page.

```
Sub Test()
 Dim ret As VbMsgBoxResult
 If ActiveDocument.Pages.Count = 1 Then
  ret = MsgBox("Document contains only 1 page. Do you want to continue?", vbYesNo)
  If ret = vbNo Then Exit Sub
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Pages.First

Property **First** As Page

Description

Member of Pages

The **First** property returns the first document page.

The **First** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Pages.Item

Property **Item(***Index As Long***)** As Page

Description

Member of Pages

The **Item** property returns a specified page from a document.

Item is the default property of the Pages class, and its reference can be omitted when you are accessing items in a **Pages** collection. For example, **Pages.Item(2)** is the same as **Pages(2)** — they both reference the second page in the collection.

- A page with an index number of **0** returns the master page. Some layers, such as **Guides** or **Grid**, are available only on the master page.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the page by its index number

VBA example

The following VBA example places page numbers on each page in the active document.

```
Sub Test()
 Dim p As Page
 Dim i As Long
 For i = 1 To ActiveDocument.Pages.Count
  Set p = ActiveDocument.Pages(i)
  p.ActiveLayer.CreateArtisticText 0, 0, "Page " & p.Index
 Next i
End Sub
Sub Test()
 Dim p As Page
 For Each p In ActiveDocument.Pages
  p.ActiveLayer.CreateArtisticText 0, 0, "Page " & p.Index
 Next p
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Pages.Last

Property **Last** As Page

Description

Member of Pages

The **Last** property returns the last document page.

The **Last** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Pages.Parent

Property **Parent** As Document

Description

Member of Pages

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

PageSize

Properties Methods

Description

The **PageSize** class represents the size-related settings of a page.

Copyright 2014 Corel Corporation. All rights reserved.

PageSize.BuiltIn

Property **BuiltIn** As Boolean

Description

Member of PageSize

The **BuiltIn** property returns **True** if the paper type is predefined.

The **BuiltIn** property returns a read-only value.

VBA example

The following VBA example displays the names of all page sizes, and their widths and heights, if the paper type is predefined.

```
Sub Test()
 Dim ps As PageSizes
 Dim d As Document
 Dim p As PageSize
 Dim st As String
 Dim s As Shape
 Set d = CreateDocument
 Set ps = d.PageSizes
 For Each p In ps
  If p.BuiltIn Then
   st = st & p.Name & "(" & p.Width & " X " & p.Height & ")" & vbCr
  End If
 Next p
 Set s = d.ActiveLayer.CreateParagraphText(8.5, 11, 0, 0, st)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PageSize.DefaultUnit

Property **DefaultUnit** As cdrUnit

Description

Member of PageSize

The **DefaultUnit** property returns the default units of measurement for a given page size.

The **DefaultUnit** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

PageSize.Delete

Sub **Delete()**

Description

Member of PageSize

The **Delete** property deletes a custom paper type.

VBA example

The following VBA example deletes all page sizes that are not predefined, including custom page sizes.

```
Sub Test()
 Dim ps As PageSizes
 Dim d As Document
 Dim p As PageSize
 Set d = CreateDocument
 Set ps = d.PageSizes
 For Each p In ps
  If Not p.BuiltIn Then
   p.Delete
  End If
 Next p
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PageSize.FixedOrientation

Property **FixedOrientation** As Boolean

Description

Member of PageSize

The **FixedOrientation** property checks whether the orientation of a page can be changed.

The **FixedOrientation** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

PageSize.Height

Property **Height** As Double

Description

Member of PageSize

The **Height** property returns the height of a page.

VBA example

The following VBA example displays the names of all page sizes, and their widths and heights, if the paper type is predefined.

```
Sub Test()
 Dim ps As PageSizes
 Dim d As Document
 Dim p As PageSize
 Dim st As String
 Dim s As Shape
 Set d = CreateDocument
 Set ps = d.PageSizes
 For Each p In ps
  If p.BuiltIn Then
   st = st & p.Name & "(" & p.Width & " X " & p.Height & ")" & vbCr
  End If
 Next p
 Set s = d.ActiveLayer.CreateParagraphText(8.5, 11, 0, 0, st)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PageSize.Index

Property **Index** As Long

Description

Member of PageSize

The **Index** property returns the index number for a paper type.

The **Index** property returns a read-only value.

VBA example

The following VBA example displays the names of all page sizes, and their index numbers, if the paper type is predefined.

```
Sub Test()
 Dim ps As PageSizes
 Dim d As Document
 Dim p As PageSize
 Dim st As String
 Dim s As Shape
 Set d = CreateDocument
 Set ps = d.PageSizes
 For Each p In ps
  If p.BuiltIn Then
   st = st & p.Name & "(" & p.Index & ")" & vbCr
  End If
 Next p
 Set s = d.ActiveLayer.CreateParagraphText(8.5, 11, 0, 0, st)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PageSize.Name

Property **Name** As String

Description

Member of PageSize

The **Name** property returns the name of a paper type.

The **Name** property returns a read-only value.

VBA example

The following VBA example displays the names of all page sizes, and their widths and heights, if the paper type is predefined.

```
Sub Test()
 Dim ps As PageSizes
 Dim d As Document
 Dim p As PageSize
 Dim st As String
 Dim s As Shape
 Set d = CreateDocument
 Set ps = d.PageSizes
 For Each p In ps
  If p.BuiltIn Then
   st = st & p.Name & "(" & p.Width & " X " & p.Height & ")" & vbCr
  End If
 Next p
 Set s = d.ActiveLayer.CreateParagraphText(8.5, 11, 0, 0, st)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PageSize.Parent

Property **Parent** As PageSizes

Description

Member of PageSize

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

PageSize.Width

Property Width As Double

Description

Member of PageSize

The **Width** property returns the width of a page.

VBA example

The following VBA example displays the names of all page sizes, and their widths and heights, if the paper type is predefined.

```
Sub Test()
 Dim ps As PageSizes
 Dim d As Document
 Dim p As PageSize
 Dim st As String
 Dim s As Shape
 Set d = CreateDocument
 Set ps = d.PageSizes
 For Each p In ps
  If p.BuiltIn Then
   st = st & p.Name & "(" & p.Width & " X " & p.Height & ")" & vbCr
  End If
 Next p
 Set s = d.ActiveLayer.CreateParagraphText(8.5, 11, 0, 0, st)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PageSizes

Properties Methods

Description

The **PageSizes** class represents a collection of page sizes (or PageSize objects).

Copyright 2014 Corel Corporation. All rights reserved.

PageSizes.Add

Function **Add(***Name As String***,** *Width As Double***,** *Height As Double***)** As PageSize

Description

Member of PageSizes

The **Add** method adds a custom page size to a collection.

Parameter	Description
Name	Specifies the name of the custom page size
Width	Specifies the width of the page
Height	Specifies the height of the page

VBA example

The following VBA example adds a new page size named **Test Paper Size**, which has a width of **5.5**" and a height of **9.5**".

```
Public Sub PageSizes_Add()
 Dim ps As PageSizes
 Dim d As Document
 Set d = CreateDocument
 Set ps = d.PageSizes
 ps.Add "Test Paper Size", 5.5, 9.5
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PageSizes.Count

Property **Count** As Long

Description

Member of PageSizes

The **Count** property returns the number of objects in a PageSizes collection.

The **Count** property returns a read-only value.

VBA example

The following VBA example displays the number of available page sizes for the active document.

```
Sub Test()
 MsgBox ActiveDocument.PageSizes.Count
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PageSizes.Item

Property **Item(***IndexOrName As Variant***)** As PageSize

Description

Member of PageSizes

The **Item** property returns a specified PageSize object. It is the default property of the PageSizes class.

The **Item** property returns a read-only value.

Parameter	Description
IndexOrName	Specifies the page size by its index number or name • **Index** — Specifies the preset placeholder that uniquely identifies each member of the **PageSizes** collection • **Name** — Specifies the string that uniquely identifies each page size

VBA example

The following VBA example displays the name of the second page size in the PageSizes collection:

```
Sub Test()
 MsgBox ActiveDocument.PageSizes(2).Name
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PageSizes.Parent

Property **Parent** As Document

Description

Member of PageSizes

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Palette

Properties Methods

Description

The **Palette** class represents a color palette.

Copyright 2014 Corel Corporation. All rights reserved.

Palette.AddColor

Sub **AddColor(**Color As Color**)**

Description

Member of Palette

The **AddColor** method adds a color to a custom color palette.

Parameter	Description
Color	Specifies the color to add

VBA example

The following VBA example creates a new palette and adds **21** colors with different shades of cyan varying by steps of **5**%.

```
Sub Test()
 Dim pal As Palette
 Dim lvl As Long
 Dim c As New Color
 Set pal = Palettes.Create("Shades of Cyan",, True)
 For lvl = 0 To 100 Step 5
  c.CMYKAssign lvl, 0, 0, 0
  pal.AddColor c
 Next lvl
 pal.Save
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palette.Application

Property **Application** As Object

Description

Member of Palette

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Palette.Close

Sub **Close()**

Description

Member of Palette

The **Close** method closes a specified palette.

VBA example

The following VBA example closes all palettes except for the standard palette in CorelDRAW.

```
Sub Test()
 Dim pal As Palette
 For Each pal In Palettes
  If pal.Name <> "Default CMYK palette" Then pal.Close
 Next pal
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palette.Color

Property **Color(***Index As Long***)** As Color

Description

Member of Palette

The **Color** property returns a specified color from a palette.

- This property is similar to using the Colors collection, but it works faster when you need to access only a single color from the palette.

Parameter	Description
Index	Specifies the color from the palette by using its index number

VBA example

The following VBA example creates an ellipse and fills it with the **15**th color of the default color palette.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(2, 2, 1)
 s.Fill.ApplyUniformFill ActivePalette.Color(15)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palette.ColorCount

Property **ColorCount** As Long

Description

Member of Palette

The **ColorCount** property returns the number of colors in a color palette.

- The **ColorCount** property functions similarly to, but faster than, Colors.Count.

The **ColorCount** property returns a read-only value.

VBA example

The following VBA example displays the total number of colors found in the default palette.

```
Sub Test()
 Dim pal As Palette
 Set pal = ActivePalette
 MsgBox "Default palette contains " & pal.ColorCount & " color(s)"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palette.Colors

Function **Colors()** As Colors

Description

Member of Palette

The **Colors** property returns the collection of all colors in a palette.

VBA example

The following VBA example displays the name of the default color palette and the number of colors it contains.

```
Sub Test()
 Dim pal As Palette
 Set pal = ActivePalette
 MsgBox "Default palette '" & pal.Name & "' contains " & pal.Colors.Count & " color(s)"
End Sub
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(2, 2, 1)
 s.Fill.ApplyUniformFill ActivePalette.Colors(15)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palette.Default

Property **Default** As Boolean

Description

Member of Palette

The **Default** property returns **True** if this is the application-default color palette (Palette object).

The **Default** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Palette.Delete

Function **Delete()** As Boolean

Description

Member of Palette

The **Delete** method deletes a color palette (Palette object) along with its associated palette file.

Copyright 2014 Corel Corporation. All rights reserved.

Palette.Document

Property **Document** As Document

Description

Member of Palette

The **Document** property returns the document (Document object) for a document-specific color palette (Palette object).

The **Document** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Palette.DuplicatePresent

Property **DuplicatePresent** As Boolean

Description

Member of Palette

The **DuplicatePresent** property determines whether a color is repeated in a color palette. If the value returned is **True**, there are any duplicate colors in the palette.

The **DuplicatePresent** property returns a read-only value.

VBA example

The following VBA example displays a message if there are any duplicate colors in the default palette.

```
Sub Test()
 If ActivePalette.DuplicatePresent Then
  MsgBox "Default palette contains duplicate colors"
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palette.FileName

Property **FileName** As String

Description

Member of Palette

The **FileName** property returns the filename of a palette.

The **FileName** property returns a read-only value.

VBA example

The following VBA example displays the filename of the palette.

```
Sub Test()
 MsgBox ActivePalette.FileName
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palette.FindColor

Function **FindColor(***Name As String***)** As Long

Description

Member of Palette

The **FindColor** method finds a color by its name. If the name is found in the color palette, it returns the index number of the color in the palette; if the color is not found, it returns **Nothing** (**0**).

Parameter	Description
Name	Specifies the name to find

VBA example

The following VBA example searches the active palette for **Red**. If the color is not found, it is added to the palette.

```
Sub Test()
 If ActivePalette.FindColor("Red") = 0 Then
  ActivePalette.AddColor CreateRGBColor(255, 0, 0)
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palette.GetIndexOfColor

Function **GetIndexOfColor(**Color As Color**)** As Long

Description

Member of Palette

The **GetIndexOfColor** property finds the specified color in the color palette. It returns the index number of the color in the palette. If the color is not found in the palette, it returns **Nothing** (**0**).

Parameter	Description
Color	Specifies the color

VBA example

The following VBA example finds the CMYK color cyan in the default palette and displays its index.

```
Sub Test()
 Dim c As New Color
 Dim idx As Long
 c.CMYKAssign 100, 0, 0, 0
 idx = ActivePalette.GetIndexOfColor(c)
 MsgBox "Cyan color is at index " & idx
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palette.Identifier

Property **Identifier** As String

Description

Member of Palette

The **Identifier** property returns the unique identifier of the color palette (Palette object).

The **Identifier** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Palette.InsertColor

Sub **InsertColor(***Index As Long***,** Color As Color**)**

Description

Member of Palette

The **InsertColor** method adds an existing color to a palette at a specified position

Parameter	Description
Index	Specifies the position of the color in the color palette
Color	Specifies the color to add

VBA example

The following VBA example adds the registration color to the beginning of the default palette.

```
Sub Test()
 Dim c As New Color
 c.RegistrationAssign
 ActivePalette.InsertColor 1, c
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palette.IsEmpty

Property **IsEmpty** As Boolean

Description

Member of Palette

The **IsEmpty** property returns **True** if the color palette (Palette object) is empty.

The **IsEmpty** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Palette.IsOpen

Property **IsOpen** As Boolean

Description

Member of Palette

The **IsOpen** property returns **True** if the color palette (Palette object) is currently visible on the screen.

The **IsOpen** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Palette.Locked

Property **Locked** As Boolean

Description

Member of Palette

The **Locked** property returns **True** if the color palette (Palette object) is not editable.

The **Locked** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Palette.MakeDefault

Sub **MakeDefault()**

Description

Member of Palette

The **MakeDefault** method makes this color palette (Palette object) the default palette for the application.

Copyright 2014 Corel Corporation. All rights reserved.

Palette.MatchColor

Function **MatchColor(**Color As Color**)** As Long

Description

Member of Palette

The **MatchColor** method finds the closest match for a color from the given palette.

Parameter	Description
Color	Specifies the color to match

VBA example

The following VBA example creates red by using the CMYK color model and then converts the color to an RGB color. The **MatchColor** method then finds the closest match from the active palette and displays the name of that color.

```
Sub TestPalette()
 Dim pal As Palette
 Dim cColor As Color
 Dim i As Integer
 Set pal = ActivePalette
 Set cColor = CreateCMYKColor(0, 100, 100, 0) 'Red
 cColor.ConvertToRGB
 i = pal.MatchColor(cColor)
 MsgBox pal.Color(i).Name
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palette.Name

Property **Name** As String

Description

Member of Palette

The **Name** property returns or specifies the name of a palette.

- The palette name can be set with the **Name** property only if the palette is a custom palette.

VBA example

The following VBA example displays the name of all open palettes.

```
Sub Test()
 Dim s As String
 Dim pal As Palette
 s = "Open palettes:" & vbCr
 For Each pal In Palettes
  s = s & vbCr & pal.Name
 Next pal
 MsgBox s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palette.Open

Sub **Open()**

Description

Member of Palette

The **Open** method opens the color palette (Palette object) on screen.

Copyright 2014 Corel Corporation. All rights reserved.

Palette.Parent

Property **Parent** As Object

Description

Member of Palette

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Palette.RemoveColor

Sub **RemoveColor(***Index As Long***)**

Description

Member of Palette

The **RemoveColor** method removes the specified color from a color palette.

Parameter	Description
Index	Specifies the color by its index number

VBA example

The following VBA example duplicates the default palette and then removes all dark colors (the colors that have a lightness less than 50%) from it.

```
Sub Test()
 Dim c As New Color
 Dim src As Palette, dest As Palette
 Dim idx As Long
 Set src = ActivePalette
 Set dest = Palettes.Create("Bright Colors")
 For Each c In src.Colors
  dest.AddColor c
 Next c
 For idx = dest.ColorCount To 1 Step -1
  c.CopyAssign dest.Color(idx)
  c.ConvertToHLS
  If c.HLSLightness < 128 Then dest.RemoveColor idx
 Next idx
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palette.Save

Sub **Save()**

Description

Member of Palette

The **Save** method saves the changes to a color palette.

VBA example

The following VBA example adds a brown color to the default palette and saves the changed palette.

```
Sub Test()
 Dim c As New Color
 c.RGBAssign 128, 0, 0
 ActivePalette.InsertColor 1, c
 ActivePalette.Save
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palette.SaveAs

Sub **SaveAs(***FileName As String***, [***Name As String***], [**Version As cdrPaletteVersion = cdrPaletteVersion12**])**

Description

Member of Palette

The **SaveAs** method saves a palette to a new file.

Parameter	Description
FileName	Specifies the filename
Name	Specifies the name of the palette. This parameter is optional.
Version	Specifies the version. This parameter is optional, and its default value is cdrPaletteVersion12 (**1**).

Copyright 2014 Corel Corporation. All rights reserved.

Palette.Type

Property **Type** As cdrPaletteType

Description

Member of Palette

The **Type** property returns whether a palette is a custom palette (for example, a CorelDRAW palette or any user-created palette) or a fixed palette (for example, PANTONE, Netscape, TOYO, or FOCOLTONE).

The **Type** property returns a read-only value, cdrPaletteType.

VBA example

The following VBA example displays the total number of palettes that are open, as well as the number of fixed and custom palettes.

```
Sub Test()
 Dim fx As Long, cs As Long
 Dim pal As Palette
 fx = 0
 cs = 0
 For Each pal In Palettes
  Select Case pal.Type
   Case cdrFixedPalette
    fx = fx + 1
   Case cdrCustomPalette
    cs = cs + 1
  End Select
 Next pal
 MsgBox "Total palettes open: " & Palettes.Count & vbCr & _
  "Fixed palettes: " & fx & vbCr & _
  "Custom palettes: " & cs
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PaletteManager

Properties Methods

Description

The **PaletteManager** class represents color-palette settings.

Copyright 2014 Corel Corporation. All rights reserved.

PaletteManager.DefaultPalette

Property **DefaultPalette** As Palette

Description

Member of PaletteManager

The **DefaultPalette** property returns the default color palette (Palette object) for the application.

The **DefaultPalette** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

PaletteManager.GetPalette

Function **GetPalette** (*IndexOrName As Variant*) As Palette

Description

Member of PaletteManager

The **GetPalette** method returns the specified color palette (Palette object) by index number, unique identifier, name, or filename.

Parameter	Description
IndexOrName	Specifies the item by its index number or name: • **Index** — Specifies the preset placeholder that uniquely identifies each member of the **Palettes** collection • **Name** — Specifies the string that uniquely identifies each color palette

Copyright 2014 Corel Corporation. All rights reserved.

PaletteManager.LoadAllPalettes

Sub **LoadAllPalettes()**

Description

Member of PaletteManager

The **LoadAllPalettes** method loads all color palettes (Palette objects) that are registered with the application.

Copyright 2014 Corel Corporation. All rights reserved.

PaletteManager.LoadPalette

Function **LoadPalette(***FileName As String***)** As Palette

Description

Member of PaletteManager

The **LoadPalette** method loads the specified color palette (Palette object) file.

Parameter	Description
FileName	Specifies the filename

Copyright 2014 Corel Corporation. All rights reserved.

PaletteManager.OpenPalettes

Property **OpenPalettes** As Palettes

Description

Member of PaletteManager

The **OpenPalettes** property returns a Palettes object that contains the collection of all color palettes (Palette objects) on the screen.

The **OpenPalettes** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

PaletteManager.PaletteCount

Property **PaletteCount** As Long

Description

Member of PaletteManager

The **PaletteCount** property returns the total number of color palettes (Palette objects) currently loaded by the application.

The **PaletteCount** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Palettes

Properties Methods

Description

The **Palettes** class represents a collection of all open color palettes (or Palette objects).

Copyright 2014 Corel Corporation. All rights reserved.

Palettes.Application

Property **Application** As Object

Description

Member of Palettes

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Palettes.Count

Property **Count** As Long

Description

Member of Palettes

The **Count** property returns the number of color palettes that are open.

The **Count** property returns a read-only value.

VBA example

The following VBA example displays the number of open color palettes.

```
Sub PalettesCount()
 MsgBox Palettes.Count & " palettes are open."
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palettes.Create

Function **Create(***Name As String***, [***FileName As String***], [**Overwrite As Boolean = False**])** As Palette

Description

Member of Palettes

The **Create** method creates a new empty custom color palette.

Parameter	Description
Name	Specifies the name of the new palette
FileName	Specifies the path and filename for the palette. This parameter is optional.
Overwrite	Specifies whether to overwrite the default palette. If this value is set to **True**, the new palette replaces the default palette. If it is set to **False**, the new palette coexists with the default palette. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example creates a new palette and adds colors with different shades of cyan varying by steps of **5**%.

```
Sub Test()
 Dim pal As Palette
 Dim lvl As Long
 Dim c As New Color
 Set pal = Palettes.Create("Shades of Cyan", Application.UserDataPath & _
  "Palettes\CyanShades.xml", True)
 For lvl = 0 To 100 Step 5
  c.CMYKAssign lvl, 0, 0, 0
  pal.AddColor c
 Next lvl
 pal.Save
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palettes.CreateFromDocument

Function **CreateFromDocument(***Name As String***, [***FileName As String***], [**Overwrite As Boolean = False**]) As** Palette

Description

Member of Palettes

The **CreateFromDocument** method creates a new custom color palette based on the colors used in the active document.

Parameter	Description
Name	Specifies the name of the new palette
FileName	Specifies the path and filename for the palette. This parameter is optional.
Overwrite	Specifies whether to overwrite the default palette. If this parameter is set to **True**, the new palette replaces the default palette. If it is set to **False**, the new palette coexists with the default palette. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example displays the number of colors used in the active document.

```
Sub Test()
 Dim pal As Palette
 Set pal = Palettes.CreateFromDocument("Document Colors", _
  Application.UserDataPath & "Palettes\DocColors.xml", True)
 MsgBox "The document uses " & pal.ColorCount & " colors"
 pal.Close
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palettes.CreateFromSelection

Function **CreateFromSelection(***Name As String***, [***FileName As String***], [**Overwrite As Boolean = False**]) As** Palette

Description

Member of Palettes

The **CreateFromSelection** method creates a new custom color palette based on the colors used in a selection of objects.

Parameter	Description
Name	Specifies the name of the new palette
FileName	Specifies the path and filename for the palette. This parameter is optional.
Overwrite	Specifies whether to overwrite the default palette. If this parameter is set to **True**, the new palette replaces the default palette. If it is set to **False**, the new palette coexists with the default palette. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example displays the number of colors used in the selection.

```
Sub Test()
 Dim pal As Palette
 Set pal = Palettes.CreateFromSelection("Selection Colors", _
  Application.UserDataPath & "Palettes\SelectionColors.xml", True)
 MsgBox "The selection uses " & pal.ColorCount & " colors"
 pal.Close
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palettes.Item

Property **Item(***IndexOrName As Variant***)** As Palette

Description

Member of Palettes

The **Item** property returns the specified Palette object from a Palettes collection. It is the default property of the **Palettes** class.

The **Item** property returns a read-only value.

Parameter	Description
IndexOrName	Specifies the item by its index number or name: • **Index** — Specifies the preset placeholder that uniquely identifies each member of the **Palettes** collection • **Name** — Specifies the string that uniquely identifies each color palette

VBA example

The following VBA example closes the palette that was opened first.

```
Sub Test()
 Palettes.Item(1).Close
End Sub
Sub Test()
 Palettes("Default CMYK palette").Close
End Sub
```

- You can also reference the first-opened palette by using **Palettes(1).Close**.

Copyright 2014 Corel Corporation. All rights reserved.

Palettes.Open

Function **Open(***FileName As String***)** As Palette

Description

Member of Palettes

The **Open** method opens an existing custom color palette.

Parameter	Description
FileName	Specifies the full path name (with a **.xml** extension) of the color palette

VBA example

The following VBA example opens the specified palette from file.

```
Sub Test()
 Palettes.Open Application.SetupPath & "Custom\coreldrw.xml"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Palettes.Parent

Property **Parent** As Object

Description

Member of Palettes

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvas

Properties Methods

Description

The **PatternCanvas** class represents the settings for a two-color bitmap-fill pattern. You can use the **PatternCanvas** object to create new patterns or modify existing ones.

- You can create a **PatternCanvas** object by using the **New** keyword in Visual Basic.

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvas.Clear

Sub **Clear()**

Description

Member of PatternCanvas

The **Clear** method clears a pattern canvas by filling it with white.

VBA example

The following VBA example creates a new pattern fill in a 64 × 64 bitmap and then applies the fill to a newly created rectangle.

```
Sub Test()
 Dim c As New PatternCanvas
 Dim n As Long
 c.Size = cdrPatternCanvas64x64
 c.Clear
 For n = 2 To 63 Step 2
  c.Line (0, 0)-(n, n), , B
 Next n
 With ActiveLayer.CreateRectangle(0, 0, 2, 2)
  .Fill.ApplyPatternFill cdrTwoColorPattern
  .Fill.Pattern.Canvas = c
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvas.CopyArea

Sub **CopyArea**(*x1 As Long*, *y1 As Long*, *x2 As Long*, *y2 As Long*, *x As Long*, *y As Long*)

Description

Member of PatternCanvas

The **CopyArea** method copies an area of a pattern canvas, defined by two coordinates, and then moves that area to a new location on the canvas.

Parameter	Description
x1	Specifies the x-coordinate of the first point that defines the area to copy on the pattern canvas. This value is measured in document units.
y1	Specifies the y-coordinate of the first point that defines the area to copy on the pattern canvas. This value is measured in document units.
x2	Specifies the x-coordinate of the second point that defines the area to copy on the pattern canvas. This value is measured in document units.
y2	Specifies the y-coordinate of the second point that defines the area to copy on the pattern canvas. This value is measured in document units.
x	Specifies the horizontal position of the point on the pattern canvas that marks the new location of the copied area. This value is measured in document units.
y	Specifies the vertical position of a point on the pattern canvas that marks the new location of the copied area. This value is measured in document units.

VBA example

The following VBA example creates a “windmill” pattern by drawing a circle and rotating half of that circle by **90**°. It then copies the resulting pattern and rotates the copy by **180**°.

```
Sub Test()
 Dim c As New PatternCanvas
 Dim a As Double, x As Long, y As Long
 c.Size = cdrPatternCanvas64x64
 c.Clear
 DrawCircle c, 32, 16, 16, True
 c.CopyArea 0, 0, 31, 31, 32, 0
 c.RotateArea 32, 0, 63, 31, -90
 c.CopyArea 0, 0, 63, 31, 0, 32
 c.RotateArea 0, 32, 63, 63, 180
 With ActiveLayer.CreateRectangle(0, 0, 2, 2)
  .Fill.ApplyPatternFill cdrTwoColorPattern
  .Fill.Pattern.Canvas = c
 End With
End Sub
' ==== The following two subroutines draw a circle on a canvas
Private Sub DrawCircle(c As PatternCanvas, CenterX As Long, CenterY As Long, Radius As Long, Filled As Boolean)
 Dim p As Long, x As Long, y As Long
 x = 0
 y = Radius
 Plot c, x, y, CenterX, CenterY, Filled
 p = 1 - Radius
 While x < y
  If p < 0 Then
   x = x + 1
   p = p + 2 * x + 1
  Else
   x = x + 1
   y = y - 1
   p = p + 2 * (x - y) + 1
  End If
  Plot c, x, y, CenterX, CenterY, Filled
 Wend
End Sub
Private Sub Plot(c As PatternCanvas, x As Long, y As Long, cx As Long, cy As Long, Filled As Boolean)
 If Filled Then
  c.Line (cx + x, cy + y)-(cx - x, cy + y)
  c.Line (cx + x, cy - y)-(cx - x, cy - y)
  c.Line (cx + y, cy + x)-(cx - y, cy + x)
  c.Line (cx + y, cy - x)-(cx - y, cy - x)
 Else
  c.PSet (cx + x, cy + y)
  c.PSet (cx - x, cy + y)
  c.PSet (cx + x, cy - y)
  c.PSet (cx - x, cy - y)
  c.PSet (cx + y, cy + x)
  c.PSet (cx - y, cy + x)
```

```
  c.PSet (cx + y, cy - x)
  c.PSet (cx - y, cy - x)
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvas.Data

Property **Data** As String

Description

Member of PatternCanvas

The **Data** property returns or specifies the string representing a bitmap pattern. The pattern is encoded with a special algorithm to allow the binary bitmap data to be represented in a text form.

Data is the default property of the PatternCanvas class.

VBA example

The following VBA example creates a new checkerboard pattern that is 16 × 16 pixels and then applies it to a rectangle.

```
Sub Test()
 Dim c As New PatternCanvas
 c.Data = "%%['$aH,&A5&0C"
 With ActiveLayer.CreateRectangle(0, 0, 3, 3)
  .Fill.ApplyPatternFill cdrTwoColorPattern
  .Fill.Pattern.Canvas = c
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvas.FillArea

Sub **FillArea(***x1 As Long*, *y1 As Long*, *x2 As Long*, *y2 As Long*, **[**State As Boolean = True**])**

Description

Member of PatternCanvas

The **FillArea** method fills a rectangular area of a pattern canvas with black or white pixels.

- See also the PatternCanvas.Line method.

Parameter	Description
x1	Specifies the x-coordinate of the first point that defines the area to fill on the pattern canvas. This value is measured in document units.
y1	Specifies the y-coordinate of the first point that defines the area to fill on the pattern canvas. This value is measured in document units.
x2	Specifies the x-coordinate of the second point that defines the area to fill on the pattern canvas. This value is measured in document units.
y2	Specifies the y-coordinate of the second point that defines the area to fill on the pattern canvas. This value is measured in document units.
State	Specifies whether the filled area is returned to its original state after the fill is removed on the pattern canvas. If the value is **True**, the area is returned to its original state. This parameter is optional, and its default value is **True**.

VBA example

The following VBA example creates a pattern of two overlapping, filled rectangles with an unfilled area at their intersection.

```
Sub Test()
 Dim c As New PatternCanvas
 c.Size = cdrPatternCanvas32x32
 c.FillArea 0, 0, 31, 31, True
 c.FillArea 0, 0, 18, 18, False
 c.FillArea 14, 14, 31, 31, False
 c.FillArea 14, 14, 18, 18, True
 With ActiveLayer.CreateRectangle(0, 0, 2, 2)
  .Fill.ApplyPatternFill cdrTwoColorPattern
  .Fill.Pattern.Canvas = c
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvas.FlipArea

Sub **FlipArea(***x1 As Long*, *y1 As Long*, *x2 As Long*, *y2 As Long*, Axes As cdrFlipAxes**)**

Description

Member of PatternCanvas

The **FlipArea** method repositions an area of a pattern canvas, as defined by two coordinates. You can flip the area horizontally or vertically, or both.

Parameter	Description
x1	Specifies the x-coordinate of the first point that defines the area to flip on the pattern canvas. This value is measured in document units.
y1	Specifies the y-coordinate of the first point that defines the area to flip on the pattern canvas. This value is measured in document units.
x2	Specifies the x-coordinate of the second point that defines the area to flip on the pattern canvas. This value is measured in document units.
y2	Specifies the y-coordinate of the second point that defines the area to flip on the pattern canvas. This value is measured in document units.
Axes	Specifies how the area of the pattern canvas is flipped. An area can be flipped horizontally or vertically, or both.

VBA example

The following VBA example creates a pattern that uses the Mandelbrot set. The set is built only in the upper half of the complex plane, while the other half is a flipped duplicate.

```
Sub Test()
 Dim c As New PatternCanvas
 Dim nx As Long, ny As Long
 Dim cx As Double, cy As Double
 Dim zx As Double, zy As Double, zz As Double
 Dim n As Long
 c.Height = 256
 c.Width = 256
 For nx = 0 To 255
  cx = nx / 100 - 2
  For ny = 0 To 127
   cy = 1.27 - ny / 100
   zx = 0: zy = 0: n = 0
   While n < 10 And zx * zx + zy * zx < 4
    zz = zx * zx - zy * zy + cx
    zy = 2 * zx * zy + cy
    zx = zz
    n = n + 1
   Wend
   c.PSet (nx, ny), (n < 10)
  Next ny
 Next nx
 c.CopyArea 0, 0, 255, 127, 0, 128
 ' Since the axes are mixed up,
 ' as a workaround, the following
 ' command should be called with
 ' cdrFlipVertical as the last parameter:
 c.FlipArea 0, 128, 255, 255, cdrFlipHorizontal
 With ActiveLayer.CreateRectangle(0, 0, 2, 2)
  .Fill.ApplyPatternFill cdrTwoColorPattern
  .Fill.Pattern.Canvas = c
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvas.Height

Property **Height** As Long

Description

Member of PatternCanvas

The **Height** property returns or specifies the vertical size of a pattern canvas. Allowed values range from **1** to **256** pixels.

VBA example

The following VBA example creates a small bitmap pattern that is 2 × 2 pixels in size. The upper-left and lower-right pixels are set to black, creating a checkerboard pattern.

```
Sub Test()
 Dim c As New PatternCanvas
 c.Width = 2
 c.Height = 2
 c.Clear
 c.PSet (0, 0)
 c.PSet (1, 1)
 With ActiveLayer.CreateRectangle(0, 0, 3, 3)
  .Fill.ApplyPatternFill cdrTwoColorPattern
  .Fill.Pattern.Canvas = c
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvas.Index

Property **Index** As Long

Description

Member of PatternCanvas

The **Index** property returns the index number of a pattern canvas in the list of available patterns.

This property returns **0** if the pattern is not from the PatternCanvas collection.

The **Index** property returns a read-only value.

VBA example

The following VBA example creates a sample tile of each available pattern fill.

```
Sub Test()
 Dim c As PatternCanvas
 Dim y As Long
 For Each c In PatternCanvases
  y = c.Index
  With ActiveLayer.CreateRectangle(0, (y - 1) / 2, 3, y / 2)
   .Fill.ApplyPatternFill cdrTwoColorPattern,, y
  End With
 Next c
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvas.Line

Sub **Line**(*Flags As Integer*, *x1 As Long*, *y1 As Long*, *x2 As Long*, *y2 As Long*, *Color As Boolean*)

Description

Member of PatternCanvas

The **Line** method draws a line, or a rectangle that is either filled or unfilled.

- See also the PatternCanvas.FillArea method.
- For detailed descriptions of the parameters for this function, see the Visual Basic Help.

Parameter	Description
Flags	
x1	Specifies the x-coordinate of the starting point of the new line on the canvas. This value is measured in document units.
y1	Specifies the y-coordinate of the starting point of the new line on the canvas. This value is measured in document units.
x2	Specifies the x-coordinate of the ending point of the new line on the canvas. This value is measured in document units.
y2	Specifies the y-coordinate of the ending point of the new line on the canvas. This value is measured in document units.
Color	Specifies whether the new line has a color applied to it on the pattern canvas. If this value is set to **True**, the selected color in the active color palette is applied to the new line.

VBA example

The following VBA example creates a pattern consisting of a diagonal line, an unfilled rectangle, and two pixels in the upper-right and lower-left corners of the canvas.

```
Sub Test()
 Dim c As New PatternCanvas
 c.Size = cdrPatternCanvas32x32
 c.Clear
 c.Line (0, 0)-(31, 31)
 c.Line (5, 5)-(27, 27), , B
 c.PSet (30, 2)
 c.PSet (2, 30)
 With ActiveLayer.CreateRectangle(0, 0, 2, 2)
  .Fill.ApplyPatternFill cdrTwoColorPattern
  .Fill.Pattern.Canvas = c
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvas.Pixel

Property **Pixel(***x As Long*, *y As Long***)** As Boolean

Description

Member of PatternCanvas

The **Pixel** property returns or specifies the color of a pixel in a bitmap pattern. If this property is set to **True**, the pixel represents black. If it is set to **False**, the pixel represents white.

- This property is equivalent to the Visual Basic **PSet** command, for changing and reading pixel colors.

Parameter	Description
x	Specifies the horizontal position of the pixel on the pattern canvas. This value is measured in document units.
y	Specifies the vertical position of the pixel on the pattern canvas. This value is measured in document units.

VBA example

The following VBA example inverts an existing bitmap pattern and applies both the inverted pattern and the original pattern to a rectangle.

```
Sub Test()
 Dim c As New PatternCanvas
 Dim x As Long, y As Long
 c.PutCopy PatternCanvases(8)
 For x = 0 To c.Width - 1
  For y = 0 To c.Height - 1
   c.Pixel(x, y) = Not c.Pixel(x, y)
  Next y
 Next x
 With ActiveLayer.CreateRectangle(0, 0, 3, 3)
  .Fill.ApplyPatternFill cdrTwoColorPattern, , 8
 End With
 With ActiveLayer.CreateRectangle(3, 0, 6, 3)
  .Fill.ApplyPatternFill cdrTwoColorPattern
  .Fill.Pattern.Canvas = c
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvas.PSet

Sub **PSet**(*Step As Integer*, *x As Long*, *y As Long*, *Color As Boolean*)

Description

Member of PatternCanvas

The **PSet** method sets a pixel of a given color at a specified coordinate on a pattern canvas. If this property is set to **True**, the pixel represents white. If it is set to **False**, the pixel represents black.

- See also the PatternCanvas.Pixel property.
- For detailed descriptions of the parameters for this function, see the Visual Basic Help.

Parameter	Description
Step	Specifies the number of bands (or steps)
x	Specifies the horizontal position of the point on the pattern canvas. This value is measured in document units.
y	Specifies the vertical position of the point on the pattern canvas. This value is measured in document units.
Color	Indicates whether the pixel has a color applied to it on the pattern canvas. If this value is set to **True**, the selected color in the active color palette is applied to the pixel.

VBA example

The following VBA example creates a pattern consisting of a diagonal line, an unfilled rectangle, and two pixels in the upper-right and lower-left corners of the canvas.

```
Sub Test()
 Dim c As New PatternCanvas
 c.Size = cdrPatternCanvas32x32
 c.Clear
 c.Line (0, 0)-(31, 31)
 c.Line (5, 5)-(27, 27), , B
 c.PSet (30, 2)
 c.PSet (2, 30)
 With ActiveLayer.CreateRectangle(0, 0, 2, 2)
  .Fill.ApplyPatternFill cdrTwoColorPattern
  .Fill.Pattern.Canvas = c
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvas.PutCopy

Sub **PutCopy**(PatternCanvas As PatternCanvas**)**

Description

Member of PatternCanvas

The **PutCopy** method places the content of one pattern canvas into the active pattern canvas.

Parameter	Description
PatternCanvas	Specifies the pattern canvas to be copied

VBA example

The following VBA example creates a new pattern based on the first available fill pattern in the PatternCanvases collection. The new pattern contains a small white rectangle at its center.

```
Sub Test()
 Dim c As New PatternCanvas
 Dim x As Long, y As Long
 c.PutCopy PatternCanvases(1)
 x = c.Width / 2
 y = c.Height / 2
 c.FillArea x - 10, y - 10, x + 10, y + 10, True
 With ActiveLayer.CreateRectangle(0, 0, 2, 2)
  .Fill.ApplyPatternFill cdrTwoColorPattern
  .Fill.Pattern.Canvas = c
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvas.RotateArea

Sub **RotateArea**(*x1 As Long*, *y1 As Long*, *x2 As Long*, *y2 As Long*, *Angle As Double*)

Description

Member of PatternCanvas

The **RotateArea** method rotates an area, as defined by two coordinates, of a pattern canvas. The rotation is measured in degrees.

- Currently, only integer angle values divisible by 90 can be used (for example, **0**°, **90**°, **180**°, and **270**°).

Parameter	Description
x1	Specifies the x-coordinate of the first point that defines the area to rotate on the pattern canvas. This value is measured in document units.
y1	Specifies the y-coordinate of the first point that defines the area to rotate on the pattern canvas. This value is measured in document units.
x2	Specifies the x-coordinate of the second point that defines the area to rotate on the pattern canvas. This value is measured in document units.
y2	Specifies the y-coordinate of the second point that defines the area to rotate on the pattern canvas. This value is measured in document units.
Angle	Specifies the angle, measured in degrees, at which to rotate the pattern canvas

VBA example

The following VBA example creates a new fill by rotating the default brick pattern by **90**°.

```
Sub Test()
 Dim c As New PatternCanvas
 c.PutCopy PatternCanvases(4)
 c.RotateArea 0, 0, c.Width - 1, c.Height - 1, 90
 With ActiveLayer.CreateRectangle(0, 0, 2, 2)
  .Fill.ApplyPatternFill cdrTwoColorPattern
  .Fill.Pattern.Canvas = c
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvas.Select

Sub **Select(***Index As Long***)**

Description

Member of PatternCanvas

The **Select** method chooses a specific pattern canvas from the PatternCanvases collection (that is, the list of available two-color fill patterns).

Parameter	Description
Index	Specifies the desired pattern canvas in the PatternCanvases collection

VBA example

The following VBA example selects the next pattern fill for each object with a two-color pattern fill.

```
Sub Test()
 Dim s As Shape
 Dim c As PatternCanvas
 For Each s In ActivePage.Shapes
  If s.Fill.Type = cdrPatternFill Then
   If s.Fill.Pattern.Type = cdrTwoColorPattern Then
    If s.Fill.Pattern.Canvas.Index <> PatternCanvases.Count Then
     Set c = New PatternCanvas
     c.Select s.Fill.Pattern.Canvas.Index + 1
     s.Fill.Pattern.Canvas = c
    End If
   End If
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvas.Size

Property **Size** As cdrPatternCanvasSize

Description

Member of PatternCanvas

The **Size** property returns or specifies one of the standard canvas sizes (16 × 16, 32 × 32, or 64 × 64 pixels). Any other sizes are treated as custom sizes.

- Instead of setting the values of the Width and Height properties, you can use the **Size** property to set both dimensions to one of the standard values.

The **Size** property returns a value of cdrPatternCanvasSize.

VBA example

The following VBA example creates a new pattern canvas that is 64 × 64 pixels and then applies it to a rectangle.

```
Sub Test()
 Dim c As New PatternCanvas
 Dim x As Long, y As Long
 c.Size = cdrPatternCanvas64x64
 c.Clear
 For x = 0 To c.Width - 1
  For y = 0 To c.Height - 1
   c.Pixel(x, y) = (((x + y) \ 2) Mod 2) <> 0
  Next y
 Next x
 With ActiveLayer.CreateRectangle(0, 0, 2, 2)
  .Fill.ApplyPatternFill cdrTwoColorPattern
  .Fill.Pattern.Canvas = c
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvas.Width

Property **Width** As Long

Description

Member of PatternCanvas

The **Width** property returns or specifies the horizontal size of a pattern canvas. Allowed values range from 1 to 256 pixels.

VBA example

The following VBA example creates a small bitmap pattern that is 2 × 2 pixels in size. The upper-left and lower-right pixels are set to black, creating a checkerboard pattern.

```
Sub Test()
 Dim c As New PatternCanvas
 c.Width = 2
 c.Height = 2
 c.Clear
 c.PSet (0, 0)
 c.PSet (1, 1)
 With ActiveLayer.CreateRectangle(0, 0, 3, 3)
  .Fill.ApplyPatternFill cdrTwoColorPattern
  .Fill.Pattern.Canvas = c
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvases

Properties Methods

Description

The **PatternCanvases** class represents a collection of all available two-color fill patterns (or PatternCanvas objects).

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvases.Add

Function **Add(**PatternCanvas As PatternCanvases**)** As Long

Description

Member of PatternCanvases

The **Add** method adds a two-color fill pattern to the PatternCanvases collection. The additional pattern is added to the **2-color** list box in the **Pattern Fill** dialog box.

Parameter	Description
PatternCanvas	Specifies the pattern canvas to add to the PatternCanvases collection

VBA example

The following VBA example creates a pattern on a new 64 × 64 bitmap and adds it to the list of available two-color fills. It then applies the fill pattern to a newly created rectangle.

```
Sub Test()
 Dim c As New PatternCanvas
 Dim n As Long
 c.Size = cdrPatternCanvas64x64
 c.Clear
 For n = 2 To 63 Step 2
  c.Line (0, 0)-(n, n), , B
 Next n
 On Error Resume Next ' The code in green is a workaround.
 n = PatternCanvases.Add(c)
 If Err.Number Then n = PatternCanvases.Add(c)
 On Error GoTo 0
 With ActiveLayer.CreateRectangle(0, 0, 3, 3)
  .Fill.ApplyPatternFill cdrTwoColorPattern, , n
 End With
End Sub
```

- You can apply a pattern canvas without adding it to the PatternCanvases collection.

- See also the example for the PatternCanvases.Item property.

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvases.Count

Property **Count** As Long

Description

Member of PatternCanvases

The **Count** property returns the number of pattern canvases available in the PatternCanvases collection.

The **Count** property returns a read-only value.

VBA example

The following VBA example creates a sample tile of each available two-color pattern fill.

```
Sub Test()
 Const cx As Long = 8
 Const cy As Long = 10
 Dim i As Long
 Dim nx As Long, ny As Long
 Dim x As Double, y As Double
 Dim sx As Double, sy As Double
 Dim s As Shape
 sx = ActivePage.SizeWidth / cx
 sy = ActivePage.SizeHeight / cy
 nx = 0
 ny = 0
 For i = 1 To PatternCanvases.Count
  x = nx * sx
  y = ny * sy
  Set s = ActiveLayer.CreateRectangle2(x, y, sx, sy)
  s.Fill.ApplyPatternFill cdrTwoColorPattern, , i
  nx = nx + 1
  If nx >= cx Then
   nx = 0
   ny = ny + 1
  End If
 Next i
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvases.Item

Property **Item(***Index As Long***)** As PatternCanvas

Description

Member of PatternCanvases

The **Item** property returns or specifies a reference to a specified pattern canvas in a PatternCanvases collection.

Item is the default property of the **PatternCanvases** class, and its reference can be omitted when you are accessing items in a **PatternCanvases** collection. For example, **PatternCanvases.Item(2)** is the same as **PatternCanvases(2)** — they both reference the second pattern canvas in the collection.

Parameter	Description
Index	Specifies the desired pattern canvas within the **PatternCanvases** collection

VBA example

The following VBA example creates a rectangle and fills it with the **Maple leaf** pattern, turned upside-down:

```
Sub Test()
 Dim c As New PatternCanvas
 c.PutCopy PatternCanvases(25)
 c.RotateArea 0, 0, c.Width - 1, c.Height - 1, 180
 With ActiveLayer.CreateRectangle(0, 0, 3, 3)
  .Fill.ApplyPatternFill cdrTwoColorPattern
  .Fill.Pattern.Canvas = c
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternCanvases.Remove

Sub **Remove(***Index As Long***)**

Description

Member of PatternCanvases

The **Remove** method removes a pattern from the PatternCanvases collection.

Parameter	Description
Index	Specifies the desired pattern canvas within the PatternCanvases collection

VBA example

The following VBA example removes the last available two-color pattern.

```
Sub Test()
 PatternCanvases.Remove PatternCanvases.Count
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.BackColor

Property **BackColor** As Color

Description

Member of PatternFill

The **BackColor** property returns or specifies the background color in a two-color bitmap pattern fill.

VBA example

The following VBA example creates a rectangle, applies a two-color bitmap pattern to it, and changes the background color to red.

```
Sub Test()
 Dim s As Shape
 Dim pf As PatternFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 Set pf = s.Fill.ApplyPatternFill(cdrTwoColorPattern, , 6)
 pf.BackColor.RGBAssign 255, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.Canvas

Property **Canvas** As PatternCanvas

Description

Member of PatternFill

The **Canvas** property returns a PatternCanvas object that manipulates two-color bitmap patterns.

VBA example

The following VBA example creates a new 16 × 16 checkerboard pattern and applies it to a rectangle.

```
Sub Test()
 Dim c As New PatternCanvas
 c.Data = "%%['$aH,&A5&0C"
 With ActiveLayer.CreateRectangle(0, 0, 3, 3)
  .Fill.ApplyPatternFill cdrTwoColorPattern
  .Fill.Pattern.Canvas = c
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.FilePath

Property **FilePath** As String

Description

Member of PatternFill

The **FilePath** property returns the full file path of the vector-pattern file used in a pattern.

The **FilePath** property returns a read-only value.

VBA example

The following VBA example displays the file path of the full-color pattern of the selected shape.

```
Sub Test()
 Dim pf As PatternFill
 If ActiveShape.Fill.Type <> cdrPatternFill Then
  MsgBox "Select an object with a pattern fill"
  Exit Sub
 End If
 Set pf = ActiveShape.Fill.Pattern
 If pf.Type <> cdrFullColorPattern Then
  MsgBox "Select an object with a full color pattern fill"
  Exit Sub
 End If
 MsgBox pf.FilePath
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.FrontColor

Property **FrontColor** As Color

Description

Member of PatternFill

The **FrontColor** property returns or specifies the foreground color in a two-color bitmap pattern fill.

VBA example

The following VBA example creates a rectangle, applies a two-color bitmap pattern to it, and changes the foreground color to red.

```
Sub Test()
 Dim s As Shape
 Dim pf As PatternFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 Set pf = s.Fill.ApplyPatternFill(cdrTwoColorPattern, , 6)
 pf.FrontColor.RGBAssign 255, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.Load

Function **Load(***FileName As String***)** As Boolean

Description

Member of PatternFill

The **Load** method imports a bitmap or vector pattern to use as a pattern fill.

Parameter	Description
FileName	Specifies the full path and filename of the graphic to be imported

VBA example

The following VBA example applies a two-color pattern fill and then loads a pattern from a file.

```
Sub Test()
 Dim s As Shape
 Dim pf As PatternFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set pf = s.Fill.ApplyPatternFill(cdrTwoColorPattern)
 pf.Load SetupPath & "Custom Data\Bumpmap\Stlplate.cpt"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.MirrorFill

Property **MirrorFill** As Boolean

Description

Member of PatternFill

The **MirrorFill** property returns or specifies whether to mirror the pattern tiles in a pattern fill.

VBA example

The following VBA example applies a full-color bitmap pattern to a rectangle and flips the pattern tiles to create a seamless pattern fill.

```
Sub test()
Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 s.Style.Fill.LoadFill ("C:\Users\Public\Documents\Corel\Content X7\Fills\30 Vector Pattern 277.fill")
 s.Fill.Pattern.MirrorFill = True
 s.Fill.Pattern.OriginX = -0.2
 s.Fill.Pattern.OriginY = -0.2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.MirrorFillX

Property **MirrorFillX** As Boolean

Description

Member of PatternFill

The **MirrorFillX** property returns or specifies whether to mirror the pattern tiles in a pattern fill horizontally.

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.MirrorFillY

Property **MirrorFillY** As Boolean

Description

Member of PatternFill

The **MirrorFillY**property returns or specifies whether to mirror the pattern tiles in a pattern fill vertically.

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.OriginX

Property **OriginX** As Double

Description

Member of PatternFill

The **OriginX** property returns or specifies the x-coordinate of the point of origin for a pattern.

The **OriginX** property is measured in document units.

VBA example

The following VBA example applies a full-color pattern to a rectangle and offsets the first tile by 1" to the right and 1.5" upwards, relative to the lower-left corner of the rectangle.

```
Sub test()
Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 s.Style.Fill.LoadFill ("C:\Users\Public\Documents\Corel\Content X7\Fills\30 Vector Pattern 277.fill")
 s.Fill.Pattern.MirrorFill = True
 s.Fill.Pattern.OriginX = -0.2
 s.Fill.Pattern.OriginY = -0.2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.OriginY

Property **OriginY** As Double

Description

Member of PatternFill

The **OriginY** property returns or specifies the y-coordinate of the point of origin for a pattern.

The **OriginY** property is measured in document units.

VBA example

The following VBA example applies a full-color pattern to a rectangle and offsets the first tile by 1" to the right and 1.5" upwards, relative to the lower-left corner of the rectangle.

```
Sub Test()
 Dim s As Shape
 Dim pf As PatternFill
 Dim FileName As String
 FileName = Application.SetupPath & "Custom\Patterns\drwx0835.pat"
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set pf = s.Fill.ApplyPatternFill(cdrFullColorPattern, FileName)
 pf.OriginX = 1
 pf.OriginY = 1.5
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.RotationAngle

Property **RotationAngle** As Double

Description

Member of PatternFill

The **RotationAngle** property returns or specifies the rotation angle of a pattern fill.

VBA example

The following VBA example applies a brick fill pattern to a rectangle. The pattern is rotated by **30**° counterclockwise and slanted by **10**° to the left.

```
Sub Test()
 Dim s As Shape
 Dim pf As PatternFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set pf = s.Fill.ApplyPatternFill(cdrTwoColorPattern, , 4)
 pf.RotationAngle = 30
 pf.SkewAngle = 10
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.SkewAngle

Property **SkewAngle** As Double

Description

Member of PatternFill

The **SkewAngle** property returns or specifies the degree of slant for a pattern fill.

VBA example

The following VBA example applies a brick fill pattern to a rectangle. The pattern is rotated by **30**° counterclockwise and slanted by **10**° to the left.

```
Sub Test()
 Dim s As Shape
 Dim pf As PatternFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set pf = s.Fill.ApplyPatternFill(cdrTwoColorPattern, , 4)
 pf.RotationAngle = 30
 pf.SkewAngle = 10
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.TileHeight

Property **TileHeight** As Double

Description

Member of PatternFill

The **TileHeight** property returns or specifies the vertical size of a pattern tile, measured in document units.

VBA example

The following VBA example applies a two-color bitmap pattern to a tile that is 3" wide × 1" high.

```
Sub Test()
 Dim s As Shape
 Dim pf As PatternFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set pf = s.Fill.ApplyPatternFill(cdrTwoColorPattern, , 8)
 pf.TileWidth = 3
 pf.TileHeight = 1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.TileOffset

Property **TileOffset** As Long

Description

Member of PatternFill

The **TileOffset** property returns or specifies the offset of the pattern tiles in a pattern fill. The value is a percentage of the actual tile size in the pattern fill.

- You can use the TileOffsetType property to set the type of offset.

A pattern can be offset by row or by column.

VBA example

The following VBA example applies a two-color bitmap pattern to a rectangle and offsets rows by **50**% relative to each other.

```
Sub Test()
 Dim s As Shape
 Dim pf As PatternFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set pf = s.Fill.ApplyPatternFill(cdrTwoColorPattern, , 8)
 pf.TileWidth = 1
 pf.TileHeight = 1
 pf.TileOffsetType = cdrTileOffsetRow
 pf.TileOffset = 50
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.TileOffsetType

Property **TileOffsetType** As cdrTileOffsetType

Description

Member of PatternFill

The **TileOffsetType** property returns or specifies the type of offset for a tile in a pattern fill.

A pattern can be offset by row or by column.

The **TileOffsetType** property returns a value of cdrTileOffsetType.

- You can use the TileOffset property to set the offset.

VBA example

The following VBA example applies a two-color bitmap pattern to a rectangle and offsets rows by **50**% relative to each other.

```
Sub Test()
 Dim s As Shape
 Dim pf As PatternFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set pf = s.Fill.ApplyPatternFill(cdrTwoColorPattern, , 8)
 pf.TileWidth = 1
 pf.TileHeight = 1
 pf.TileOffsetType = cdrTileOffsetRow
 pf.TileOffset = 50
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.TileWidth

Property **TileWidth** As Double

Description

Member of PatternFill

The **TileWidth** property returns or specifies the horizontal size of a pattern tile, measured in document units.

VBA example

The following VBA example applies a two-color bitmap pattern to a tile that is 3" wide × 1" high.

```
Sub Test()
 Dim s As Shape
 Dim pf As PatternFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set pf = s.Fill.ApplyPatternFill(cdrTwoColorPattern, , 8)
 pf.TileWidth = 3
 pf.TileHeight = 1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.TransformWithShape

Property **TransformWithShape** As Boolean

Description

Member of PatternFill

The **TransformWithShape** property returns or specifies whether a pattern fill is transformed (that is, stretched, rotated, or skewed) along with its parent shape.

VBA example

The following VBA example applies a pattern fill to a rectangle and specifies that the fill is transformed when the shape object is altered. The shape is then duplicated and stretched by 200%.

```
Sub Test()
 Dim s As Shape
 Dim pf As PatternFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set pf = s.Fill.ApplyPatternFill(cdrTwoColorPattern, , 8)
 pf.TransformWithShape = True
 Set s = s.Duplicate(4, 0)
 s.StretchEx 2, , 4, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PatternFill.Type

Property **Type** As cdrPatternFillType

Description

Member of PatternFill

The **Type** property returns or specifies the type of pattern fill (two-color bitmap, full-color bitmap, or vector).

The **Type** property returns a value of cdrPatternFillType.

VBA example

The following VBA example changes all colors in two-color pattern fills to grayscale.

```
Sub Test()
 Dim s As Shape
 Dim pf As PatternFill
 For Each s In ActivePage.Shapes
  If s.Fill.Type = cdrPatternFill Then
   Set pf = s.Fill.Pattern
   If pf.Type = cdrTwoColorPattern Then
    pf.BackColor.ConvertToGray
    pf.FrontColor.ConvertToGray
   End If
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

pdfASCII85

The following enumerations have this constant:

- pdfEncodingType

Copyright 2014 Corel Corporation. All rights reserved.

pdfBinary

The following enumerations have this constant:

- pdfEncodingType

Copyright 2014 Corel Corporation. All rights reserved.

pdfBitmapCompressionType

The **pdfBitmapCompressionType** enumeration has the following constants:

Constant	Value	Description
pdfNone	**0**	Specifies no compression
pdfLZW	**1**	Specifies LZW compression
pdfJPEG	**2**	Specifies JPEG compression
pdfZIP	**3**	Specifies ZIP compression
pdfJP2	**4**	Specifies JP2 compression

Copyright 2014 Corel Corporation. All rights reserved.

PDFBookmarks

The following enumerations have this constant:

- pdfDisplayOnStart

Copyright 2014 Corel Corporation. All rights reserved.

pdfCMYK

The following enumerations have this constant:

- pdfColorMode

Copyright 2014 Corel Corporation. All rights reserved.

pdfColorMode

The **pdfColorMode** enumeration has the following constants:

Constant	Value	Description
pdfRGB	**0**	Specifies RGB color mode
pdfCMYK	**1**	Specifies CMYK color mode
pdfGrayscale	**2**	Specifies grayscale color mode
pdfNative	**3**	Specifies native color mode

Copyright 2014 Corel Corporation. All rights reserved.

pdfColorProfile

The **pdfColorProfile** enumeration has the following constants:

Constant	Value	Description
pdfCompositeProfile	**0**	Specifies composite profile
pdfSeparationProfile	**1**	Specifies separation profile

Copyright 2014 Corel Corporation. All rights reserved.

pdfCompositeProfile

The following enumerations have this constant:

- pdfColorProfile

Copyright 2014 Corel Corporation. All rights reserved.

pdfCurrentPage

The following enumerations have this constant:

- pdfExportRange

Copyright 2014 Corel Corporation. All rights reserved.

pdfDisplayOnStart

The **pdfDisplayOnStart** enumeration has the following constants:

Constant	Value	Description
pdfPageOnly	**0**	Specifies page only
pdfFullScreen	**1**	Specifies full screen
PDFBookmarks	**2**	Specifies PDF bookmarks
pdfThumbnails	**3**	Specifies PDF thumbnails

Copyright 2014 Corel Corporation. All rights reserved.

pdfEditPermissionAny

The following enumerations have this constant:

- pdfEditPermissions

Copyright 2014 Corel Corporation. All rights reserved.

pdfEditPermissionInsertDeleteRotatePage

The following enumerations have this constant:

- pdfEditPermissions

Copyright 2014 Corel Corporation. All rights reserved.

pdfEditPermissionNone

The following enumerations have this constant:

- pdfEditPermissions

Copyright 2014 Corel Corporation. All rights reserved.

pdfEditPermissions

The **pdfEditPermissions** enumeration has the following constants:

Constant	Value	Description
pdfEditPermissionNone	**0**	Specifies that no permissions are required
pdfEditPermissionInsertDeleteRotatePage	**1**	Specifies that permissions are required to insert, delete, or rotate pages
pdfEditPermissionAny	**2**	Specifies that permissions are required for doing anything

Copyright 2014 Corel Corporation. All rights reserved.

pdfEncodingType

The **pdfEncodingType** enumeration has the following constants:

Constant	Value	Description
pdfASCII85	**0**	Specifies ASCII encoding
pdfBinary	**1**	Specifies binary encoding

Copyright 2014 Corel Corporation. All rights reserved.

pdfEncryptionType

The **pdfEncryptionType** enumeration has the following constants:

Constant	Value	Description
pdfEncryptTypeNone	**0**	Specifies no encryption
pdfEncryptTypeStandard	**1**	Specifies standard encryption
pdfEncryptTypeAES	**2**	Specifies AES encryption
pdfEncryptTypeAES256	**3**	Specifies AES256 encryption

Copyright 2014 Corel Corporation. All rights reserved.

pdfEncryptTypeAES

The following enumerations have this constant:

- pdfEncryptionType

Copyright 2014 Corel Corporation. All rights reserved.

pdfEncryptTypeAES256

The following enumerations have this constant:

- pdfEncryptionType

Copyright 2014 Corel Corporation. All rights reserved.

pdfEncryptTypeNone

The following enumerations have this constant:

- pdfEncryptionType

Copyright 2014 Corel Corporation. All rights reserved.

pdfEncryptTypeStandard

The following enumerations have this constant:

- pdfEncryptionType

Copyright 2014 Corel Corporation. All rights reserved.

pdfEPSAs

The **pdfEPSAs** enumeration has the following constants:

Constant	Value	Description
pdfPostscript	**0**	Specifies PostScript EPS
pdfPreview	**1**	Specifies preview-enabled EPS

Copyright 2014 Corel Corporation. All rights reserved.

pdfExportRange

The **pdfExportRange** enumeration has the following constants:

Constant	Value	Description
pdfWholeDocument	**0**	Specifies the whole document
pdfCurrentPage	**1**	Specifies the current page
pdfSelection	**2**	Specifies the selection
pdfPageRange	**3**	Specifies a page range

Copyright 2014 Corel Corporation. All rights reserved.

pdfFullScreen

The following enumerations have this constant:

- pdfDisplayOnStart

Copyright 2014 Corel Corporation. All rights reserved.

pdfGrayscale

The following enumerations have this constant:

- pdfColorMode

Copyright 2014 Corel Corporation. All rights reserved.

pdfJP2

The following enumerations have this constant:

- pdfBitmapCompressionType

Copyright 2014 Corel Corporation. All rights reserved.

pdfJPEG

The following enumerations have this constant:

- pdfBitmapCompressionType

Copyright 2014 Corel Corporation. All rights reserved.

pdfLZW

The following enumerations have this constant:

- pdfBitmapCompressionType

Copyright 2014 Corel Corporation. All rights reserved.

pdfNative

The following enumerations have this constant:

- pdfColorMode

Copyright 2014 Corel Corporation. All rights reserved.

pdfNone

The following enumerations have this constant:

- pdfBitmapCompressionType

Copyright 2014 Corel Corporation. All rights reserved.

pdfPageOnly

The following enumerations have this constant:

- pdfDisplayOnStart

Copyright 2014 Corel Corporation. All rights reserved.

pdfPageRange

The following enumerations have this constant:

- pdfExportRange

Copyright 2014 Corel Corporation. All rights reserved.

pdfPostscript

The following enumerations have this constant:

- pdfEPSAs

Copyright 2014 Corel Corporation. All rights reserved.

pdfPreview

The following enumerations have this constant:

- pdfEPSAs

Copyright 2014 Corel Corporation. All rights reserved.

pdfPrintPermissionHighResolution

The following enumerations have this constant:

- pdfPrintPermissions

Copyright 2014 Corel Corporation. All rights reserved.

pdfPrintPermissionLowResolution

The following enumerations have this constant:

- pdfPrintPermissions

Copyright 2014 Corel Corporation. All rights reserved.

pdfPrintPermissionNone

The following enumerations have this constant:

- pdfPrintPermissions

Copyright 2014 Corel Corporation. All rights reserved.

pdfPrintPermissions

The **pdfPrintPermissions** enumeration has the following constants:

Constant	Value	Description
pdfPrintPermissionNone	**0**	Specifies no permissions for printing
pdfPrintPermissionLowResolution	**1**	Specifies to allow low-resolution printing
pdfPrintPermissionHighResolution	**2**	Specifies to allow high-resolution printing

Copyright 2014 Corel Corporation. All rights reserved.

pdfRGB

The following enumerations have this constant:

- pdfColorMode

Copyright 2014 Corel Corporation. All rights reserved.

pdfSelection

The following enumerations have this constant:

- pdfExportRange

Copyright 2014 Corel Corporation. All rights reserved.

pdfSeparationProfile

The following enumerations have this constant:

- pdfColorProfile

Copyright 2014 Corel Corporation. All rights reserved.

pdfSpotAsCMYK

The following enumerations have this constant:

- pdfSpotType

Copyright 2014 Corel Corporation. All rights reserved.

pdfSpotAsGray

The following enumerations have this constant:

- pdfSpotType

Copyright 2014 Corel Corporation. All rights reserved.

pdfSpotAsRGB

The following enumerations have this constant:

- pdfSpotType

Copyright 2014 Corel Corporation. All rights reserved.

pdfSpotAsSpot

The following enumerations have this constant:

- pdfSpotType

Copyright 2014 Corel Corporation. All rights reserved.

pdfSpotType

The **pdfSpotType** enumeration has the following constants:

Constant	Value	Description
pdfSpotAsSpot	**0**	Specifies spot colors as spot colors
pdfSpotAsRGB	**1**	Specifies spot colors as RGB
pdfSpotAsCMYK	**2**	Specifies spot colors as CMYK
pdfSpotAsGray	**3**	Specifies spot colors as grayscale

Copyright 2014 Corel Corporation. All rights reserved.

pdfTextAsAscii

The following enumerations have this constant:

- pdfTextExportMode

Copyright 2014 Corel Corporation. All rights reserved.

pdfTextAsUnicode

The following enumerations have this constant:

- pdfTextExportMode

Copyright 2014 Corel Corporation. All rights reserved.

pdfTextExportMode

The **pdfTextExportMode** enumeration has the following constants:

Constant	Value	Description
pdfTextAsUnicode	**0**	Specifies Unicode text
pdfTextAsAscii	**1**	Specifies ASCII text

Copyright 2014 Corel Corporation. All rights reserved.

pdfThumbnails

The following enumerations have this constant:

- pdfDisplayOnStart

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings

Properties Methods

Description

The **PDFVBASettings** class represents the settings used when publishing a document to PDF.

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.Author

Property **Author** As String

Description

Member of PDFVBASettings

The **Author** property sets or returns the author of a PDF document.

VBA example

The following VBA example publishes the active document to PDF and specifies the file's author, subject, and keywords.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .Author = "Graphix Design, Inc"
  .Keywords = "Animals, Farm, Bulls"
  .Subject = "Animal Farms"
 End With
ActiveDocument.PublishToPDF "C:\MyFarm.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.BitmapCompression

Property **BitmapCompression** As pdfBitmapCompressionType

Description

Member of PDFVBASettings

The **BitmapCompression** property sets the compression algorithm for the bitmaps in a PDF document.

VBA example

The following VBA example publishes the active document to PDF by using JPEG bitmap compression with a compression factor of **30**.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .BitmapCompression = pdfJPEG
  .JPEGQualityFactor = 30
 End With
ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.Bleed

Property **Bleed** As Integer

Description

Member of PDFVBASettings

The **Bleed** property sets the bleed value, measured in tenths of a micron, for a PDF document.

- For a bleed to be included in a document, the IncludeBleed property must be set to **True**.

VBA example

The following VBA example creates a **1**" bleed area around the page and then publishes the active document to PDF.

```
Sub Test()
 With ActiveDocument.PDFSettings
  IncludeBleed = True
  Bleed = CorelScriptTools.FromInches(1)
 End With
ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.Bookmarks

Property **Bookmarks** As Boolean

Description

Member of PDFVBASettings

The **Bookmarks** property determines whether to include bookmarks in a PDF document.

VBA example

The following VBA example publishes the active document to PDF. The resulting document includes bookmarks, hyperlinks, and thumbnails.

```
Sub Test()
 With ActiveDocument.PDFSettings
  Bookmarks = True
  Hyperlinks = True
  Thumbnails = True
 End With
ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.ColorMode

Property **ColorMode** As pdfColorMode

Description

Member of PDFVBASettings

The **ColorMode** property sets the color mode for the objects in a PDF document.

The following ccode example publishes the active document to PDF. All objects are exported by using the RGB color model, and the color profile of the composite printer is applied.

```
Sub Test()
 With ActiveDocument.PDFSettings
  ColorMode = pdfRGB
  UseColorProfile = True
  ColorProfile = pdfCompositeProfile
 End With
ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.ColorProfile

Property **ColorProfile** As pdfColorProfile

Description

Member of PDFVBASettings

The **ColorProfile** property sets the color profile of a PDF document.

- For a color profile to be applied, the UseColorProfile property must be set to **True**.

VBA example

The following VBA example publishes the active document to PDF. All objects are exported by using the RGB color model, and the color profile of the composite printer is applied.

```
Sub Test()
 With ActiveDocument.PDFSettings
  ColorMode = pdfRGB
  UseColorProfile = True
  ColorProfile = pdfCompositeProfile
 End With
ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.ColorResolution

Property **ColorResolution** As Long

Description

Member of PDFVBASettings

The **ColorResolution** property sets the resolution for the downsampled color bitmaps in a PDF document.

- For the resolution to be applied, the DownsampleColor option must be set to **True**.

VBA example

The following VBA example publishes the active document to PDF. Color and grayscale bitmaps are downsampled to **72** dpi, and monochrome bitmaps are downsampled to **150** dpi.

```
Sub Test()
 With ActiveDocument.PDFSettings
  DownsampleColor = True
  DownsampleGray = True
  DownsampleMono = True
  ColorResolution = 72
  GrayResolution = 72
  MonoResolution = 150
 End With
ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.ComplexFillsAsBitmaps

Property **ComplexFillsAsBitmaps** As Boolean

Description

Member of PDFVBASettings

The **ComplexFillsAsBitmaps** property determines whether complex fills are rendered as bitmaps in a PDF document.

VBA example

The following VBA example sets options for publishing the active document to PDF. Complex fills are rendered as bitmaps; halftone screens and overprints are included, while Open Prepress Interface (OPI) links and spot colors are not maintained.

```
Sub Test()
 With ActiveDocument.PDFSettings
  ComplexFillsAsBitmaps = True
  Halftones = True
  MaintainOPILinks = False
  Overprints = True
  SpotColors = False
 End With
ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.CompressText

Property **CompressText** As Boolean

Description

Member of PDFVBASettings

The **CompressText** property determines whether to compress the text and line art in a PDF document.

VBA example

VBA example

The following VBA example compresses text and line art when publishing the active document to PDF.

```
Sub Test()
 With ActiveDocument
  .PDFSettings.CompressText = True
  .PublishToPDF "C:\MyDocument.pdf"
  With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.ContentCopyingAllowed

Property **ContentCopyingAllowed** As Boolean

Description

Member of PDFVBASettings

The **ContentCopyingAllowed** property specifies whether the content of a PDF document can be copied to the Clipboard.

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.CropMarks

Property **CropMarks** As Boolean

Description

Member of PDFVBASettings

The **CropMarks** property determines whether crop marks are included in a PDF document.

VBA example

The following VBA example publishes the document to PDF. Crop marks, densitometer scales, file information, and color registration marks are included in the PDF document.

```
Sub Test()
 With ActiveDocument.PDFSettings
  CropMarks = True
  DensitometerScales = True
  FileInformation = True
  RegistrationMarks = True
 End With
ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.DensitometerScales

Property **DensitometerScales** As Boolean

Description

Member of PDFVBASettings

The **DensitometerScales** property determines whether densitometer scales are included in a PDF document.

VBA example

The following VBA example publishes the document to PDF. Crop marks, densitometer scales, file information, and color registration marks are included in the PDF document.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .CropMarks = True
  .DensitometerScales = True
  .FileInformation = True
  .RegistrationMarks = True
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.DownsampleColor

Property **DownsampleColor** As Boolean

Description

Member of PDFVBASettings

The **DownsampleColor** property determines whether color bitmaps are downsampled in a PDF document.

- You can use the ColorResolution property to set the resolution.

VBA example

The following VBA example publishes the active document to PDF. Color and grayscale bitmaps are downsampled to **72** dpi, and monochrome bitmaps are downsampled to **150** dpi.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .DownsampleColor = True
  .DownsampleGray = True
  .DownsampleMono = True
  .ColorResolution = 72
  .GrayResolution = 72
  .MonoResolution = 150
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.DownsampleGray

Property **DownsampleGray** As Boolean

Description

Member of PDFVBASettings

The **DownsampleGray** property determines whether gray bitmaps are downsampled in a PDF document.

- You can use the GrayResolution property to set the resolution.

VBA example

The following VBA example publishes the active document to PDF. Color and grayscale bitmaps are downsampled to **72** dpi, and monochrome bitmaps are downsampled to **150** dpi.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .DownsampleColor = True
  .DownsampleGray = True
  .DownsampleMono = True
  .ColorResolution = 72
  .GrayResolution = 72
  .MonoResolution = 150
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.DownsampleMono

Property **DownsampleMono** As Boolean

Description

Member of PDFVBASettings

The **DownsampleMono** property determines whether monochrome bitmaps are downsampled in a PDF document.

- You can use the MonoResolution property to set the resolution.

VBA example

The following VBA example publishes the active document to PDF. Color and grayscale bitmaps are downsampled to **72** dpi, and monochrome bitmaps are downsampled to **150** dpi.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .DownsampleColor = True
  .DownsampleGray = True
  .DownsampleMono = True
  .ColorResolution = 72
  .GrayResolution = 72
  .MonoResolution = 150
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.EditPermissions

Property **EditPermissions** As pdfEditPermissions

Description

Member of PDFVBASettings

The **EditPermissions** property specifies the editing permissions of a PDF document.

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.EmbedBaseFonts

Property **EmbedBaseFonts** As Boolean

Description

Member of PDFVBASettings

The **EmbedBaseFonts** property determines whether to embed base-14 fonts in a PDF document.

VBA example

The following VBA example publishes the document to PDF. All document fonts are converted to Type 1 and embedded in the PDF file along with the base-14 fonts. Fonts are subset if less than **80**% of their character set is used.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .EmbedBaseFonts = True
  .EmbedFonts = True
  .SubsetFonts = True
  .SubsetPct = 80
  .TextAsCurves = False
  .TrueTypeToType1 = True
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.EmbedFile

Property **EmbedFile** As Boolean

Description

Member of PDFVBASettings

The **EmbedFile** property specifies the paths of files to be embedded in a PDF document. Individual files are separated by a vertical bar (**|**).

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.EmbedFilename

Property **EmbedFilename** As String

Description

Member of PDFVBASettings

The **EmbedFilename** property specifies whether one or more files are embedded in a PDF document.

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.EmbedFonts

Property **EmbedFonts** As Boolean

Description

Member of PDFVBASettings

The **EmbedFonts** property determines whether to embed fonts in a PDF document.

VBA example

The following VBA example publishes the document to PDF. All document fonts are converted to Type 1 and embedded in the PDF file along with the base-14 fonts. Fonts are subset if less than **80**% of their character set is used.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .EmbedBaseFonts = True
  .EmbedFonts = True
  .SubsetFonts = True
  .SubsetPct = 80
  .TextAsCurves = False
  .TrueTypeToType1 = True
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.Encoding

Property **Encoding** As pdfEncodingType

Description

Member of PDFVBASettings

The **Encoding** property specifies the data-encoding method of a PDF document.

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.EncryptType

Property **EncryptType** As pdfEncryptionType

Description

Member of PDFVBASettings

The **EncryptType** property specifies the encryption level of a PDF document.

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.EPSAs

Property **EPSAs** As pdfEPSAs

Description

Member of PDFVBASettings

The **EPSAs** property determines how embedded EPS files are published to PDF.

VBA example

The following VBA example publishes the document to PDF and specifies that only previews of EPS art are published.

```
Sub Test()
 ActiveDocument.PDFSettings.EPSAs = pdfPreview
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.FileInformation

Property **FileInformation** As Boolean

Description

Member of PDFVBASettings

The **FileInformation** property determines whether to include file information in a PDF document.

VBA example

The following VBA example publishes the document to PDF. Crop marks, densitometer scales, file information, and color registration marks are included in the PDF document.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .CropMarks = True
  .DensitometerScales = True
  .FileInformation = True
  .RegistrationMarks = True
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.FountainSteps

Property **FountainSteps** As Long

Description

Member of PDFVBASettings

The **FountainSteps** property sets the number of steps to use when banding fountain fills in a PDF document.

VBA example

The following VBA example publishes the active document to PDF and applies **100** steps to fountain fills.

```
Sub Test()
 ActiveDocument.PDFSettings.FountainSteps = 100
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.GrayResolution

Property **GrayResolution** As Long

Description

Member of PDFVBASettings

The **GrayResolution** property sets the resolution for the downsampled grayscale bitmaps in a PDF document.

- For the resolution to be applied, the DownsampleGray option must be set to **True**.

VBA example

The following VBA example publishes the active document to PDF. Color and grayscale bitmaps are downsampled to **72** dpi, and monochrome bitmaps are downsampled to **150** dpi.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .DownsampleColor = True
  .DownsampleGray = True
  .DownsampleMono = True
  .ColorResolution = 72
  .GrayResolution = 72
  .MonoResolution = 150
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.Halftones

Property **Halftones** As Boolean

Description

Member of PDFVBASettings

The **Halftones** property determines whether to preserve halftone-screen information in a PDF document.

VBA example

The following VBA example sets options for publishing the active document to PDF. Complex fills are rendered as bitmaps; halftone screens and overprints are included, while Open Prepress Interface (OPI) links and spot colors are not maintained.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .ComplexFillsAsBitmaps = True
  .Halftones = True
  .MaintainOPILinks = False
  .Overprints = True
  .SpotColors = False
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.Hyperlinks

Property **Hyperlinks** As Boolean

Description

Member of PDFVBASettings

The **Hyperlinks** property determines whether to include hyperlinks in a PDF document.

VBA example

The following VBA example publishes the active document to PDF. The resulting document includes bookmarks, hyperlinks, and thumbnails.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .Bookmarks = True
  .Hyperlinks = True
  .Thumbnails = True
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.IncludeBleed

Property **IncludeBleed** As Boolean

Description

Member of PDFVBASettings

The **IncludeBleed** property determines whether to include a bleed in a PDF document.

- The Bleed property sets the bleed value, measured in tenths of a micron.

VBA example

The following VBA example creates a 1" bleed area around the page and then publishes the active document to PDF.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .IncludeBleed = True
  .Bleed = CorelScriptTools.FromInches(1)
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.JP2QualityFactor

Property **JP2QualityFactor** As Long

Description

Member of PDFVBASettings

The **JP2QualityFactor** property specifies the JPEG2000 compression level of a PDF document.

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.JPEGQualityFactor

Property **JPEGQualityFactor** As Integer

Description

Member of PDFVBASettings

The **JPEGQualityFactor** sets the JPEG-algorithm compression rate for the bitmaps in a PDF document.

VBA example

The following VBA example publishes the active document to PDF by using a JPEG-compression factor of **30**.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .BitmapCompression = pdfJPEG
  .JPEGQualityFactor = 30
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.Keywords

Property **Keywords** As String

Description

Member of PDFVBASettings

The **Keywords** property associates keywords with a PDF document.

VBA example

The following VBA example publishes the active document to PDF, and specifies the file's author, subject, and keywords.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .Author = "Graphix Design, Inc"
  .Keywords = "Animals, Farm, Bulls"
  .Subject = "Animal Farms"
 End With
 ActiveDocument.PublishToPDF "C:\MyFarm.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.Linearize

Property **Linearize** As Boolean

Description

Member of PDFVBASettings

The **Linearize** property determines whether to optimize a PDF document for the Web.

VBA example

The following VBA example optimizes the active document for the Web and publishes it to PDF.

```
Sub Test()
 ActiveDocument.PDFSettings.Linearize = True
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.Load

Function **Load(***SettingName As String***)** As Boolean

Description

Member of PDFVBASettings

The **Load** method loads PDF settings from a specified preset file. A Boolean value is returned.

Parameter	Description
SettingName	Specifies the name of the setting

VBA example

The following VBA example loads the **PDF for Document Distribution** publishing style and uses it to publish the active document to PDF.

```
Sub Test()
 ActiveDocument.PDFSettings.Load "PDF for Document Distribution"
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.MaintainOPILinks

Property **MaintainOPILinks** As Boolean

Description

Member of PDFVBASettings

The **MaintainOPILinks** property determines whether to substitute low-resolution images for high-resolution ones in a PDF document.

VBA example

The following VBA example sets the options for publishing the active document to PDF. Complex fills are rendered as bitmaps; halftone screens and overprints are included, while Open Prepress Interface (OPI) links and spot colors are not maintained.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .ComplexFillsAsBitmaps = True
  .Halftones = True
  .MaintainOPILinks = False
  .Overprints = True
  .SpotColors = False
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.MonoResolution

Property **MonoResolution** As Long

Description

Member of PDFVBASettings

The **MonoResolution** property sets the resolution for the downsampled monochrome bitmaps in a PDF document.

- For the resolution to be applied, the DownsampleMono option must be set to **True**.

VBA example

The following VBA example publishes the active document to PDF. Color and grayscale bitmaps are downsampled to 72 dpi, and monochrome bitmaps are downsampled to 150 dpi.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .DownsampleColor = True
  .DownsampleGray = True
  .DownsampleMono = True
  .ColorResolution = 72
  .GrayResolution = 72
  .MonoResolution = 150
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.OpenPassword

Property **OpenPassword** As String

Description

Member of PDFVBASettings

The **OpenPassword** property specifies the password required to open a PDF document.

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.OutputSpotColorsAs

Property **OutputSpotColorsAs** As pdfSpotType

Description

Member of PDFVBASettings

The **OutputSpotColorsAs** property specifies whether to convert spot colors.

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.OverprintBlackLimit

Property **OverprintBlackLimit** As Long

Description

Member of PDFVBASettings

The **OverprintBlackLimit** property specifies the overprint black limit.

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.Overprints

Property **Overprints** As Boolean

Description

Member of PDFVBASettings

The **Overprints** property determines whether to preserve document overprints in a PDF document.

VBA example

The following VBA example sets the options for publishing the active document to PDF. Complex fills are rendered as bitmaps; halftone screens and overprints are included, while Open Prepress Interface (OPI) links and spot colors are not maintained.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .ComplexFillsAsBitmaps = True
  .Halftones = True
  .MaintainOPILinks = False
  .Overprints = True
  .SpotColors = False
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.