PDFVBASettings.PageRange

Property **PageRange** As String

Description

Member of PDFVBASettings

The **PageRange** property sets the range of pages to publish to PDF.

- For this property to be applied, the PublishRange property must be set to pdfPageRange.

VBA example

The following VBA example publishes the first three pages of the active document to PDF.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .PublishRange = pdfPageRange
  .PageRange = "1-3"
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.pdfVersion

Property **pdfVersion** As pdfVersion

Description

Member of PDFVBASettings

The **pdfVersion** property optimizes a PDF document for the specified version.

VBA example

The following VBA example publishes the active document to the PDF/X-1 format.

```
Sub Test()
 ActiveDocument.PDFSettings.pdfVersion = pdfVersionPDFX1
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.PermissionPassword

Property **PermissionPassword** As String

Description

Member of PDFVBASettings

The **PermissionPassword** property specifies the password required to print or edit a PDF document.

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.PrintPermissions

Property **PrintPermissions** As pdfPrintPermissions

Description

Member of PDFVBASettings

The **PrintPermissions** property specifies the printing permissions for a PDF document.

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.PublishRange

Property **PublishRange** As pdfExportRange

Description

Member of PDFVBASettings

The **PublishRange** property specifies the portion of a document to publish to PDF.

- If you choose pdfPageRange, you can set the page range by setting the PageRange property.

VBA example

The following VBA example publishes the first three pages of the active document to PDF.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .PublishRange = pdfPageRange
  .PageRange = "1-3"
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.RegistrationMarks

Property **RegistrationMarks** As Boolean

Description

Member of PDFVBASettings

The **RegistrationMarks** property determines whether to include registration marks in a PDF document.

VBA example

The following VBA example publishes the document to PDF. Crop marks, densitometer scales, file information, and color registration marks are included in the PDF document.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .CropMarks = True
  .DensitometerScales = True
  .FileInformation = True
  .RegistrationMarks = True
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.Reset

Sub **Reset()**

Description

Member of PDFVBASettings

The **Reset** method resets all PDF settings for a document to their default values.

VBA example

The following VBA example applies the default settings when publishing the active document to PDF. All objects are published by using the CMYK color model.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .Reset
  .ColorMode = pdfCMYK
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.Save

Function **Save(***SettingName As String***)** As Boolean

Description

Member of PDFVBASettings

The **Save** method saves PDF settings to a specified preset file. A Boolean value is returned.

Parameter	Description
SettingName	Specifies the name of the setting

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.ShowDialog

Function **ShowDialog()** As Boolean

Description

Member of PDFVBASettings

The **ShowDialog** method displays the **Publish To PDF** dialog box. A Boolean value is returned.

VBA example

The following VBA example displays the **Publish To PDF** dialog box. If the user chooses a bitmap-compression method other than JPEG, a warning message is displayed and JPEG compression is applied.

```
Sub Test()
 Dim ps As PDFVBASettings
 Set ps = ActiveDocument.PDFSettings
 ps.Reset
 If ps.ShowDialog Then Exit Sub
 If ps.BitmapCompression <> pdfJPEG Then
  MsgBox "You must use JPEG bitmap compression."
  ps.BitmapCompression = pdfJPEG
 End If
 ps.JPEGQualityFactor = 150
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.Startup

Property **Startup** As pdfDisplayOnStart

Description

Member of PDFVBASettings

The **Startup** property sets the default Adobe Acrobat Reader viewing mode for a PDF document.

VBA example

The following VBA example publishes the active document to PDF and specifies the thumbnail view as the default viewing mode.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .Thumbnails = True
  .Startup = pdfThumbnails
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.Subject

Property **Subject** As String

Description

Member of PDFVBASettings

The **Subject** property specifies the subject of a PDF document.

VBA example

The following VBA example publishes the active document to PDF and specifies the file's author, subject, and keywords.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .Author = "Graphix Design, Inc"
  .Keywords = "Animals, Farm, Bulls"
  .Subject = "Animal Farms"
 End With
 ActiveDocument.PublishToPDF "C:\MyFarm.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.SubsetFonts

Property **SubsetFonts** As Boolean

Description

Member of PDFVBASettings

The **SubsetFonts** property determines whether to substitute the fonts in a PDF document.

- You can use the SubsetPct property to set the maximum percentage of the character set used.

VBA example

The following VBA example publishes the document to PDF. All document fonts are converted to Type 1 and embedded in the PDF file along with the base-14 fonts. Fonts are subset if less than 80% of their character set is used.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .EmbedBaseFonts = True
  .EmbedFonts = True
  .SubsetFonts = True
  .SubsetPct = 80
  .TextAsCurves = False
  .TrueTypeToType1 = True
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.SubsetPct

Property **SubsetPct** As Long

Description

Member of PDFVBASettings

The **SubsetPct** property sets the maximum percentage of the character set used. If the percentage of the character set used in the document is less than this value, only the characters that are used are embedded. Otherwise, the whole font is embedded.

- For the **SubsetPct** property to be applied, the SubsetFonts property must be set to **True**.

VBA example

The following VBA example publishes the document to PDF. All document fonts are converted to Type 1 and embedded in the PDF file along with the base-14 fonts. Fonts are subset if less than 80% of their character set is used.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .EmbedBaseFonts = True
  .EmbedFonts = True
  .SubsetFonts = True
  .SubsetPct = 80
  .TextAsCurves = False
  .TrueTypeToType1 = True
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.TextAsCurves

Property **TextAsCurves** As Boolean

Description

Member of PDFVBASettings

The **TextAsCurves** property determines whether to export text as curves when publishing a document to PDF.

VBA example

The following VBA example publishes the document to PDF. All document fonts are converted to Type 1 and embedded in the PDF file along with the base-14 fonts. Fonts are subset if less than 80% of their character set is used.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .EmbedBaseFonts = True
  .EmbedFonts = True
  .SubsetFonts = True
  .SubsetPct = 80
  .TextAsCurves = False
  .TrueTypeToType1 = True
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.TextExportMode

Property **TextExportMode** As pdfTextExportMode

Description

Member of PDFVBASettings

The **TextExportMode** property specifies how text streams are encoded in a PDF document.

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.Thumbnails

Property **Thumbnails** As Boolean

Description

Member of PDFVBASettings

The **Thumbnails** property determines whether to include thumbnails in a PDF document.

VBA example

The following VBA example publishes the active document to PDF. The resulting document includes bookmarks, hyperlinks, and thumbnails.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .Bookmarks = True
  .Hyperlinks = True
  .Thumbnails = True
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.TrueTypeToType1

Property **TrueTypeToType1** As Boolean

Description

Member of PDFVBASettings

The **TrueTypeToType1** property determines whether to convert TrueType fonts to Type 1 fonts when publishing a document to PDF.

VBA example

The following VBA example publishes the document to PDF. All document fonts are converted to Type 1 and embedded in the PDF file along with the base-14 fonts. Fonts are subset if less than 80% of their character set is used.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .EmbedBaseFonts = True
  .EmbedFonts = True
  .SubsetFonts = True
  .SubsetPct = 80
  .TextAsCurves = False
  .TrueTypeToType1 = True
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PDFVBASettings.UseColorProfile

Property **UseColorProfile** As Boolean

Description

Member of PDFVBASettings

The **UseColorProfile** property determines whether to use a color profile when publishing a document to PDF.

- You can use the ColorProfile property to specify the color profile.

VBA example

The following VBA example publishes the active document to PDF. All objects are exported by using the RGB color model, and the color profile of the composite printer is applied.

```
Sub Test()
 With ActiveDocument.PDFSettings
  .ColorMode = pdfRGB
  .UseColorProfile = True
  .ColorProfile = pdfCompositeProfile
 End With
 ActiveDocument.PublishToPDF "C:\MyDocument.pdf"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

pdfVersion

The **pdfVersion** enumeration has the following constants:

Constant	Value	Description
pdfVersion12	**0**	Specifies version 1.2
pdfVersion13	**1**	Specifies version 1.3
pdfVersionPDFX1	**2**	Specifies PDFX1
pdfVersion14	**3**	Specifies version 1.4
pdfVersionPDFX1a	**4**	Specifies PDFX1a
pdfVersionPDFX3	**5**	Specifies PDFX3
pdfVersion15	**6**	Specifies version 1.5
pdfVersionPDFA1b	**7**	Specifies version PDFA1b
pdfVersion17	**8**	Specifies version 1.7
pdfVersion17_Acrobat9	**9**	Specifies version 1.7 for Adobe Acrobat 9

Copyright 2014 Corel Corporation. All rights reserved.

pdfVersion12

The following enumerations have this constant:

- pdfVersion

Copyright 2014 Corel Corporation. All rights reserved.

pdfVersion13

The following enumerations have this constant:

- pdfVersion

Copyright 2014 Corel Corporation. All rights reserved.

pdfVersion14

The following enumerations have this constant:

- pdfVersion

Copyright 2014 Corel Corporation. All rights reserved.

pdfVersion15

The following enumerations have this constant:

- pdfVersion

Copyright 2014 Corel Corporation. All rights reserved.

pdfVersion17

The following enumerations have this constant:

- pdfVersion

Copyright 2014 Corel Corporation. All rights reserved.

pdfVersion17_Acrobat9

The following enumerations have this constant:

- pdfVersion

Copyright 2014 Corel Corporation. All rights reserved.

pdfVersionPDFA1b

The following enumerations have this constant:

- pdfVersion

Copyright 2014 Corel Corporation. All rights reserved.

pdfVersionPDFX1

The following enumerations have this constant:

- pdfVersion

Copyright 2014 Corel Corporation. All rights reserved.

pdfVersionPDFX1a

The following enumerations have this constant:

- pdfVersion

Copyright 2014 Corel Corporation. All rights reserved.

pdfVersionPDFX3

The following enumerations have this constant:

- pdfVersion

Copyright 2014 Corel Corporation. All rights reserved.

pdfWholeDocument

The following enumerations have this constant:

- pdfExportRange

Copyright 2014 Corel Corporation. All rights reserved.

pdfZIP

The following enumerations have this constant:

- pdfBitmapCompressionType

Copyright 2014 Corel Corporation. All rights reserved.

Polygon

Properties

Description

The **Polygon** class represents the polygon-specific settings for a shape (or Shape object).

Copyright 2014 Corel Corporation. All rights reserved.

Polygon.Sharpness

Property **Sharpness** As Long

Description

Member of Polygon

The **Sharpness** property returns or specifies the sharpness of a star-shaped polygon. The maximum value of this property is determined by the number of sides contained by the star.

VBA example

The following VBA example sets the sharpness of the currently selected polygon.

```
Sub Test()
 ActiveShape.Polygon.Sharpness = 2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Polygon.Sides

Property **Sides** As Long

Description

Member of Polygon

The **Sides** property returns or specifies the number of sides for a polygon.

VBA example

The following VBA example displays the number of polygons with a different number of sides in the current document.

```
Sub Test()
 Dim s As Shape
 Dim str As String
 Dim cnt(3 To 10) As Long, n As Long
 For n = 3 To 10
  cnt(n) = 0
 Next n
 For Each s In ActivePage.Shapes
  If s.Type = cdrPolygonShape Then
   n = s.Polygon.Sides
   If n > 9 Then n = 10
   cnt(n) = cnt(n) + 1
  End If
 Next s
 str = "The document contains" & vbCr & _
  "the following polygons:" & vbCr & vbCr & _
  "Sides" & vbTab & "Count"
 For n = 3 To 9
  str = str & vbCr & n & vbTab & cnt(n)
 Next n
 If cnt(10) Then
  str = str & vbCr & "Other" & vbTab & cnt(10)
 End If
 MsgBox str
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Polygon.Type

Property **Type** As cdrPolygonType

Description

Member of Polygon

The **Type** property returns or specifies the type of polygon.

This property returns a value of cdrPolygonType.

The following code converts, to stars, all polygons that have more than four sides.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Type = cdrPolygonShape Then
   If s.Polygon.Type = cdrPolygon And s.Polygon.Sides > 4 Then
    s.Polygon.Type = cdrStar
    s.Polygon.Sharpness = 1
   End If
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PostScriptFill

Properties Methods

Description

The **PostScriptFill** class represents the settings for a PostScript fill.

Copyright 2014 Corel Corporation. All rights reserved.

PostScriptFill.Index

Property **Index** As Long

Description

Member of PostScriptFill

The **Index** property returns the index number associated with a PostScript fill.

The **Index** property returns a read-only value.

VBA example

The following VBA example applies the sixth (**6**th) available PostScript fill to a rectangle and displays its name.

```
Sub Test()
 Dim s As Shape
 Dim pf As PostScriptFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set pf = s.Fill.ApplyPostscriptFill(6)
 MsgBox pf.Name & " #" & pf.Index
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PostScriptFill.Name

Property **Name** As String

Description

Member of PostScriptFill

The **Name** property returns the name of a PostScript fill.

The **Name** property returns a read-only value.

VBA example

The following VBA example applies the sixth (**6**th) available PostScript fill to a rectangle and displays its name.

```
Sub Test()
 Dim s As Shape
 Dim pf As PostScriptFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set pf = s.Fill.ApplyPostscriptFill(6)
 MsgBox pf.Name & " #" & pf.Index
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PostScriptFill.Properties

Property **Properties(***Index As Long***)** As Long

Description

Member of PostScriptFill

The **Properties** property returns or specifies a specified property for a PostScript fill by referencing the index number of that property.

Parameter	Description
Index	Specifies the PostScript fill property. For example, the **Bricks** PostScript fill has four properties; **PostScriptFill.Properties(2)** returns the line width of the fill.

VBA example

The following VBA example applies the **Birds** pattern to a rectangle. It then changes the frequency value to **4** and background gray level to **50**%.

```
Sub Test()
 Dim s As Shape
 Dim pf As PostScriptFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set pf = s.Fill.ApplyPostscriptFill("Birds")
 pf.Properties(1) = 4
 pf.Properties(4) = 50
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PostScriptFill.Select

Sub **Select(***IndexOrName As Variant***)**

Description

Member of PostScriptFill

The **Select** method chooses a specified PostScript fill by referencing the index number of name of the fill.

Parameter	Description
IndexOrName	Specifies the PostScript fill by its index number or name: • **Index** — Specifies the preset placeholder that uniquely identifies each PostScript fill • **Name** — Specifies the string that uniquely identifies each PostScript fill

VBA example

The following VBA example replaces the **Birds** pattern with the **ColorBubbles** for all shapes on the page.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Fill.Type = cdrPostscriptFill Then
   If s.Fill.PostScript.Name = "Birds" Then
    s.Fill.PostScript.Select "ColorBubbles"
   End If
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PostScriptFill.SetProperties

Sub **SetProperties(***Param1 As Long***, [***Param2 As Long***], [***Param3 As Long***], [***Param4 As Long***], [***Param5 As Long***])**

Description

Member of PostScriptFill

The **SetProperties** method allows you to set all the properties of a PostScript fill at the same time.

- The **SetProperties** method has placeholders for a maximum of five PostScript fill properties.

Parameter	Description
Param1	Specifies the first property of a PostScript fill. For example, the **Param1** value of the **Bars** fill is **Width**.
Param2	Specifies the second property of a PostScript fill. For example, the **Param2** value of the **Bars** fill references the **Spacing (%)** of the fill. This parameter is optional, and its default value is **0**.
Param3	Specifies the third property of a PostScript fill. For example, the **Param3** value of the **Bars** fill references the **Maximum gray** value of the fill. This parameter is optional, and its default value is **0**.
Param4	Specifies the fourth property of a PostScript fill. For example, the **Param4** value of the **Bars** fill references the **Minimum gray** value of the fill. This parameter is optional, and its default value is **0**.
Param5	Specifies the fifth property of a PostScript fill. For example, the **Param5** value of the **Checks** fill references the **Line width** value of the fill. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example applies applies the **ColorBubbles** pattern to a rectangle and specifies the following fill properties: **Number of circles** = **10**, **Max size**=**300**, **Min Size**=**100**, **Line Width** = **26**, and **Random Seed** = **10**.

```
Sub Test()
 Dim s As Shape
 Dim pf As PostScriptFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set pf = s.Fill.ApplyPostscriptFill("ColorBubbles")
 pf.SetProperties 10, 300, 100, 26, 10
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PowerClip

Properties Methods

Description

The **PowerClip** class represents the settings for a PowerClip object.

Copyright 2014 Corel Corporation. All rights reserved.

PowerClip.Application

Property **Application** As Application

Description

Member of PowerClip

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

PowerClip.ContentsLocked

Property **ContentsLocked** As Boolean

Description

Member of PowerClip

The **ContentsLocked** property determines whether to lock the contents of a PowerClip object. When the contents of a PowerClip object are locked, moving the container moves its contents.

- The contents of the PowerClip object are locked when the **ContentsLocked** property is set to **True**.

VBA example

The following VBA example creates **150** randomly colored circles, places them inside a text shape, and attaches the contents of the PowerClip object to the text.

```
Sub Test()
 Dim sr As New ShapeRange
 Dim s As Shape, n As Long
 For n = 1 To 150
  Set s = ActiveLayer.CreateEllipse2(Rnd() * 4, Rnd() * 2, Rnd() * 0.3)
  s.Fill.UniformColor.RGBAssign Rnd() * 256, Rnd() * 256, Rnd() * 256
  sr.Add s
 Next n
 Set s = ActiveLayer.CreateArtisticText(0, 0, "Clip")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 sr.AddToPowerClip s
 s.PowerClip.ContentsLocked = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PowerClip.EnterEditMode

Sub **EnterEditMode()**

Description

Member of PowerClip

The **EnterEditMode** method activates the PowerClip-editing mode, thereby allowing PowerClip objects to have their contents edited.

- When a PowerClip object is viewed in PowerClip-editing mode, its contents are displayed as objects that can be edited, while its container is displayed as a wireframe object that cannot be edited.

VBA example

The following VBA example adds **20** vertical lines to every PowerClip object on the page.

```
Sub Test()
 Const NumLines As Long = 20
 Dim s As Shape
 Dim pwc As PowerClip
 Dim x As Double, y As Double, sx As Double, sy As Double
 Dim xx As Double
 Dim n As Long
 For Each s In ActivePage.Shapes
  Set pwc = Nothing
  On Error Resume Next
  Set pwc = s.PowerClip
  On Error GoTo 0
  If Not pwc Is Nothing Then
   s.CreateSelection
   s.GetBoundingBox x, y, sx, sy
   pwc.EnterEditMode
   For n = 1 To NumLines
    xx = x + n * sx / (NumLines + 1)
    ActiveLayer.CreateLineSegment xx, y, xx, y + sy
   Next n
   pwc.LeaveEditMode
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PowerClip.ExtractShapes

Function **ExtractShapes()** As ShapeRange

Description

Member of PowerClip

The **ExtractShapes** method removes all shapes from all PowerClip objects. When the contents of a PowerClip object are extracted, the container and its contents become separate objects.

VBA example

The following VBA example extracts all shapes from all PowerClip objects on the active page.

```
Sub Test()
 Dim s As Shape
 Dim pwc As PowerClip
 For Each s In ActivePage.Shapes
  Set pwc = Nothing
  On Error Resume Next
  Set pwc = s.PowerClip
  On Error GoTo 0
  If Not pwc Is Nothing Then
   s.CreateSelection
   pwc.ExtractShapes
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PowerClip.LeaveEditMode

Sub **LeaveEditMode()**

Description

Member of PowerClip

The **LeaveEditMode** method deactivates the PowerClip-editing mode, thereby preventing PowerClip objects from having their contents edited.

VBA example

The following VBA example adds **20** vertical lines to every PowerClip object on the page.

```
Sub Test()
 Const NumLines As Long = 20
 Dim s As Shape
 Dim pwc As PowerClip
 Dim x As Double, y As Double, sx As Double, sy As Double
 Dim xx As Double
 Dim n As Long
 For Each s In ActivePage.Shapes
  Set pwc = Nothing
  On Error Resume Next
  Set pwc = s.PowerClip
  On Error GoTo 0
  If Not pwc Is Nothing Then
   s.CreateSelection
   s.GetBoundingBox x, y, sx, sy
   pwc.EnterEditMode
   For n = 1 To NumLines
    xx = x + n * sx / (NumLines + 1)
    ActiveLayer.CreateLineSegment xx, y, xx, y + sy
   Next n
   pwc.LeaveEditMode
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PowerClip.Parent

Property **Parent** As Shape

Description

Member of PowerClip

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

PowerClip.Shapes

Property **Shapes** As Shapes

Description

Member of PowerClip

The **Shapes** property returns a Shapes object containing all of the shapes in a PowerClip object.

The **Shapes** property returns a read-only value.

VBA example

The following VBA example fills with red all of the rectangles in a PowerClip object.

```
Sub Test()
 Dim s As Shape, sp As Shape
 Dim pwc As PowerClip
 For Each s In ActivePage.Shapes
  Set pwc = Nothing
  On Error Resume Next
  Set pwc = s.PowerClip
  On Error GoTo 0
  If Not pwc Is Nothing Then
   For Each sp In pwc.Shapes
    If sp.Type = cdrRectangleShape Then
     sp.Fill.UniformColor.RGBAssign 255, 0, 0
    End If
   Next sp
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintDocuments

Properties

Description

The **PrintDocuments** class represents a set of print documents.

Copyright 2014 Corel Corporation. All rights reserved.

PrintDocuments.Count

Property **Count** As Long

Description

Member of PrintDocuments

The **Count** property returns the total number of documents in a PrintDocuments collection.

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Printer

Properties Methods

Description

The **Printer** class represents the settings for an installed printer.

Copyright 2014 Corel Corporation. All rights reserved.

Printer.ColorEnabled

Property **ColorEnabled** As Boolean

Description

Member of Printer

The **ColorEnabled** property returns whether an installed printer can print in color.

The **ColorEnabled** property returns a read-only value.

VBA example

The following VBA example lists the model names of the installed printers that can print in color.

```
Sub Test()
 Dim intCounter As Integer
 Dim Prn As Printer
 Dim s As String
  For intCounter = 1 To Printers.Count
   Set Prn = Printers(intCounter)
    If Prn.ColorEnabled = True Then
     s = s & Prn.Type & vbCr
    End If
  Next intCounter
MsgBox "The following printers are able to print in color: " & vbCr & s
 Set Prn = Nothing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Printer.Default

Property **Default** As Boolean

Description

Member of Printer

The **Default** property returns whether a specified printer is the default printer.

The **Default** property returns a read-only value.

VBA example

The following VBA example displays a message box containing the model name of the default printer.

```
Sub Test()
Dim intCounter As Integer, Prn As Printer
 For intCounter = 1 To Printers.Count
  Set Prn = Printers.Item(intCounter)
  If Prn.Default = True Then
   MsgBox "The default printer is: " & Prn.Type
  End If
 Next intCounter
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Printer.Description

Property **Description** As String

Description

Member of Printer

The **Description** property returns the description of a printer.

The **Description** property returns a read-only value.

VBA example

The following VBA example lists the model names and descriptions of all installed printers.

```
Sub Test()
 Dim intCounter As Integer
 Dim Prn As Printer
 Dim s As String
  For intCounter = 1 To Printers.Count
   Set Prn = Printers(intCounter)
    If Prn.Description <> "" Then
     s = s & Prn.Type & " - " & Prn.Description & vbCr
    End If
  Next intCounter
 MsgBox "The following printers are installed on your system: " & vbCr & vbCr & s
 Set Prn = Nothing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Printer.Name

Property **Name** As String

Description

Member of Printer

The **Name** property returns the name of a printer.

The **Name** property returns a read-only value.

VBA example

The following VBA example lists the names of all installed printers.

```
Sub Test()
 Dim intCounter As Integer
 Dim Prn As Printer
 Dim s As String
  For intCounter = 1 To Printers.Count
   Set Prn = Printers(intCounter)
   s = s & Prn.Name & vbCr
  Next intCounter
 MsgBox "The following printers are installed on your system: " & vbCr & vbCr & s
 Set Prn = Nothing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Printer.PageSizeMatchingSupported

Property **PageSizeMatchingSupported** As Boolean

Description

Member of Printer

The **PageSizeMatchingSupported** property specifies whether page-size matching is enabled for this printer.

Copyright 2014 Corel Corporation. All rights reserved.

Printer.Port

Property **Port** As String

Description

Member of Printer

The **Port** property returns the name of the port (for example, LPT1) to which a printer prints.

The **Port** property returns a read-only value.

VBA example

The following VBA example displays the port of the default printer.

```
Sub Test()
 MsgBox "The default printer prints to: " & Printers.Default.Port
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Printer.PostScriptEnabled

Property **PostScriptEnabled** As Boolean

Description

Member of Printer

The **PostScriptEnabled** property returns whether a printer can print PostScript.

The **PostScriptEnabled** property returns a read-only value.

VBA example

The following VBA example displays a message box for each printer that can print PostScript.

```
Sub Test()
 Dim intCounter As Integer
 Dim Prn As Printer
  For intCounter = 1 To Printers.Count
   Set Prn = Printers(intCounter)
    If Prn.PostScriptEnabled = True Then
     MsgBox "The " & Prn.Type & " is able to print PostScript."
    End If
  Next intCounter
 Set Prn = Nothing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Printer.Ready

Property **Ready** As Boolean

Description

Member of Printer

The **Ready** property returns the ready state of a printer.

The **Ready** property returns a read-only value.

VBA example

The following VBA example lists all printers that are not ready to print.

```
Sub Test()
 Dim intCounter As Integer
 Dim Prn As Printer
 Dim s As String
  For intCounter = 1 To Printers.Count
   Set Prn = Printers(intCounter)
    If Prn.Ready = False Then
     s = s & Prn.Type & vbCr
    End If
  Next intCounter
 MsgBox "The following printers are not ready: " & vbCr & vbCr & s
 Set Prn = Nothing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Printer.ShowDialog

Sub **ShowDialog()**

Description

Member of Printer

The **ShowDialog** method displays the **Properties** dialog box for a printer.

VBA example

The following VBA example displays the **Properties** dialog box for the default printer.

```
Sub Test()
 Printers.Default.ShowDialog
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Printer.Type

Property **Type** As String

Description

Member of Printer

The **Type** property returns the model name of a printer.

The **Type** property returns a read-only value.

VBA example

The following VBA example displays whether the HP LaserJet 5P/5MP PostScript printer is installed.

```
Sub Test()
 Dim intCounter As Integer
 Dim Prn As Printer
  For intCounter = 1 To Printers.Count
   Set Prn = Printers(intCounter)
    If Prn.Type = "HP LaserJet 5P/5MP PostScript" Then
     MsgBox "The " & Prn.Type & " printer is installed."
     Exit For
  Next intCounter
 Set Prn = Nothing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintJob

Properties Methods

Description

The **PrintJob** class represents print-job properties.

Copyright 2014 Corel Corporation. All rights reserved.

PrintJob.AddDocument

Sub **AddDocument(**Document As IPrnVBAPrintDocument**, [***PageRange As String***])**

Description

Member of PrintJob

The AddDocument property adds one or more document pages to a print job.

Parameter	Description
Document	Specifies the document
PageRange	Specifies the page range. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

PrintJob.Clear

Sub **Clear()**

Description

Member of PrintJob

The **Clear** method clears the contents of a print job.

Copyright 2014 Corel Corporation. All rights reserved.

PrintJob.Documents

Property **Documents** As PrintDocuments

Description

Member of PrintJob

The **Documents** property specifies the documents to be printed in a print job.

The **Documents** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

PrintJob.Pages

Property **Pages** As PrintPages

Description

Member of PrintJob

The **Pages** property specifies the pages to be printed in a print job.

The **Pages** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

PrintJob.PrintOut

Sub **PrintOut()**

Description

Member of PrintJob

The **PrintOut** method outputs a print job to the printer.

Copyright 2014 Corel Corporation. All rights reserved.

PrintJob.Settings

Property **Settings** As PrintSettings

Description

Member of PrintJob

The **Settings** property specifies the settings for a print job.

The **Settings** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

PrintLayout

Properties

Description

The **PrintLayout** class represents print-layout properties.

Copyright 2014 Corel Corporation. All rights reserved.

PrintLayout.BleedLimit

Property **BleedLimit** As Double

Description

Member of PrintLayout

The **BleedLimit** property specifies the amount of bleed to create around pages.

Copyright 2014 Corel Corporation. All rights reserved.

PrintLayout.Placement

Property **Placement** As PrnPlaceType

Description

Member of PrintLayout

The **Placement** property specifies the placement of document pages on the printer pages.

Copyright 2014 Corel Corporation. All rights reserved.

PrintLayout.PrintTiledPages

Property **PrintTiledPages** As Boolean

Description

Member of PrintLayout

The PrintTiledPages property specifies whether to span large document pages over several printer pages.

Copyright 2014 Corel Corporation. All rights reserved.

PrintLayout.PrintTilingMarks

Property **PrintTilingMarks** As Boolean

Description

Member of PrintLayout

The **PrintTilingMarks** property specifies whether to print tiling marks.

Copyright 2014 Corel Corporation. All rights reserved.

PrintLayout.TileOverlap

Property **TileOverlap** As Double

Description

Member of PrintLayout

The **TileOverlap** property specifies the amount of overlap between page tiles.

Copyright 2014 Corel Corporation. All rights reserved.

PrintLayout.UseBleedLimit

Property **UseBleedLimit** As Boolean

Description

Member of PrintLayout

The **UseBleedLimit** property specifies whether to create bleeds around pages.

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions

Properties

Description

The **PrintOptions** class represents the available print options.

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.AppInfo

Property **AppInfo** As Boolean

Description

Member of PrintOptions

The **AppInfo** property determines whether to print application information on a job-information sheet.

VBA example

The following VBA example prints the job-information sheet with application information, driver information, and font information.

```
Sub Test()
 Dim DrawPrintOptions As PrintOptions
 Set DrawPrintOptions = ActiveDocument.PrintSettings.Options
 With DrawPrintOptions
  .JobInformation = True
  .AppInfo = True
  .DriverInfo = True
  .PrintJobInfo = False
  .FontInfo = True
  .SepsInfo = False
 End With
 'print the document
 ActiveDocument.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.ColorMode

Property **ColorMode** As PrnColorMode

Description

Member of PrintOptions

The **ColorMode** property returns or specifies how colors are printed. You can print colors in full color, black and white, or grayscale.

VBA example

The following VBA example changes the **ColorMode** setting from the default (full color) to grayscale.

```
Sub Test()
 ActiveDocument.PrintSettings.Options.ColorMode = prnModeGrayscale
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.ColorResolution

Property **ColorResolution** As Long

Description

Member of PrintOptions

The **ColorResolution** property returns or specifies the printing resolution of color bitmaps.

VBA example

The following VBA example activates downsampling for color, grayscale, and monochrome bitmaps. It then sets the resolution and prints the document.

```
Sub Test()
 Dim DrawPrintOptions As PrintOptions
 Set DrawPrintOptions = ActiveDocument.PrintSettings.Options
 With DrawPrintOptions
  'set all downsampling to True
  .DownsampleColor = True
  .DownsampleGray = True
  .DownsampleMono = True
  'set the resolution
  .ColorResolution = 96
  .GrayResolution = 150
  .MonoResolution = 600
 End With
 'print the document
 ActiveDocument.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.DownsampleColor

Property **DownsampleColor** As Boolean

Description

Member of PrintOptions

The **DownsampleColor** property returns or specifies the printing resolution of color bitmaps.

VBA example

The following VBA example saves the current downsampling settings, changes the settings, and prints the document. The saved settings are then restored.

```
Sub Test()
 Dim bDownSampleColor As Boolean
 Dim bDownSampleGray As Boolean
 Dim bDownSampleMono As Boolean
 Dim DrawPrintOptions As PrintOptions
 Set DrawPrintOptions = ActiveDocument.PrintSettings.Options
 With DrawPrintOptions
  'save the current setting
  bDownSampleColor = .DownsampleColor
  bDownSampleGray = .DownsampleGray
  bDownSampleMono = .DownsampleMono
  'change the setting
  .DownsampleColor = True
  .DownsampleGray = True
  .DownsampleMono = False
 End With
 'print the document
 ActiveDocument.PrintOut
 'restore the downsample setting
 With DrawPrintOptions
  .DownsampleColor = bDownSampleColor
  .DownsampleGray = bDownSampleGray
  .DownsampleMono = bDownSampleMono
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.DownsampleGray

Property **DownsampleGray** As Boolean

Description

Member of PrintOptions

The **DownsampleGray** property returns or specifies the printing resolution of grayscale bitmaps.

VBA example

The following VBA example saves the current downsampling settings, changes the settings, and prints the document. The saved settings are then restored.

```
Sub Test()
 Dim bDownSampleColor As Boolean
 Dim bDownSampleGray As Boolean
 Dim bDownSampleMono As Boolean
 Dim DrawPrintOptions As PrintOptions
 Set DrawPrintOptions = ActiveDocument.PrintSettings.Options
 With DrawPrintOptions
  'save the current setting
  bDownSampleColor = .DownsampleColor
  bDownSampleGray = .DownsampleGray
  bDownSampleMono = .DownsampleMono
  'change the setting
  .DownsampleColor = True
  .DownsampleGray = True
  .DownsampleMono = False
 End With
 'print the document
 ActiveDocument.PrintOut
 'restore the downsample setting
 With DrawPrintOptions
  .DownsampleColor = bDownSampleColor
  .DownsampleGray = bDownSampleGray
  .DownsampleMono = bDownSampleMono
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.DownsampleMono

Property **DownsampleMono** As Boolean

Description

Member of PrintOptions

The **DownsampleMono** property returns or specifies the printing resolution of monochrome bitmaps.

VBA example

The following VBA example saves the current downsampling settings, changes the settings, and prints the document. The saved settings are then restored.

```
Sub Test()
 Dim bDownSampleColor As Boolean
 Dim bDownSampleGray As Boolean
 Dim bDownSampleMono As Boolean
 Dim DrawPrintOptions As PrintOptions
 Set DrawPrintOptions = ActiveDocument.PrintSettings.Options
 With DrawPrintOptions
  'save the current setting
  bDownSampleColor = .DownsampleColor
  bDownSampleGray = .DownsampleGray
  bDownSampleMono = .DownsampleMono
  'change the setting
  .DownsampleColor = True
  .DownsampleGray = True
  .DownsampleMono = False
 End With
 'print the document
 ActiveDocument.PrintOut
 'restore the downsample setting
 With DrawPrintOptions
  .DownsampleColor = bDownSampleColor
  .DownsampleGray = bDownSampleGray
  .DownsampleMono = bDownSampleMono
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.DriverInfo

Property **DriverInfo** As Boolean

Description

Member of PrintOptions

The **DriverInfo** property determines whether to print driver and device information on a job-information sheet.

VBA example

The following VBA example prints the job information sheet with application information, driver information, and font information.

```
Sub Test()
 Dim DrawPrintOptions As PrintOptions
 Set DrawPrintOptions = ActiveDocument.PrintSettings.Options
 With DrawPrintOptions
  .JobInformation = True
  .AppInfo = True
  .DriverInfo = True
  .PrintJobInfo = False
  .FontInfo = True
  .SepsInfo = False
 End With
 'print the document
 ActiveDocument.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.FontInfo

Property **FontInfo** As Boolean

Description

Member of PrintOptions

The **FontInfo** property determines whether to print font information on a job-information sheet.

VBA example

The following VBA example prints the job-information sheet with application information, driver information, and font information.

```
Sub Test()
 Dim DrawPrintOptions As PrintOptions
 Set DrawPrintOptions = ActiveDocument.PrintSettings.Options
 With DrawPrintOptions
  .JobInformation = True
  .AppInfo = True
  .DriverInfo = True
  .PrintJobInfo = False
  .FontInfo = True
  .SepsInfo = False
 End With
 'print the document
 ActiveDocument.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.FountainSteps

Property **FountainSteps** As Long

Description

Member of PrintOptions

The **FountainSteps** property returns or specifies the number of steps to use when printing fountain fills.

VBA example

The following VBA example displays the current value for the **FountainSteps** property, changes the value to **256**, and displays the new value.

```
Sub Test()
 MsgBox "Fountain fills will print using " & _
  ActiveDocument.PrintSettings.Options.FountainSteps & " steps."
 ActiveDocument.PrintSettings.Options.FountainSteps = 256
 MsgBox "Fountain fills will now print using " & _
  ActiveDocument.PrintSettings.Options.FountainSteps & " steps."
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.GrayResolution

Property **GrayResolution** As Long

Description

Member of PrintOptions

The **GrayResolution** property returns or specifies the printing resolution of grayscale bitmaps.

VBA example

The following VBA example activates downsampling for color, grayscale, and monochrome bitmaps. It then sets the resolution and prints the document.

```
Sub Test()
 Dim DrawPrintOptions As PrintOptions
 Set DrawPrintOptions = ActiveDocument.PrintSettings.Options
 With DrawPrintOptions
  'set all downsampling to True
  .DownsampleColor = True
  .DownsampleGray = True
  .DownsampleMono = True
  'set the resolution
  .ColorResolution = 96
  .GrayResolution = 150
  .MonoResolution = 600
 End With
 'print the document
 ActiveDocument.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.InRIPTrapInfo

Property **InRIPTrapInfo** As Boolean

Description

Member of PrintOptions

The **InRIPTrapInfo** property specifies whether to print in-RIP trapping information on a job-information sheet.

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.JobInformation

Property **JobInformation** As Boolean

Description

Member of PrintOptions

The **JobInformation** property determines whether to print a job-information sheet.

VBA example

The following VBA example prints the job-information sheet with application information, driver information, and font information:

```
Sub Test()
 Dim DrawPrintOptions As PrintOptions
 Set DrawPrintOptions = ActiveDocument.PrintSettings.Options
 With DrawPrintOptions
  .JobInformation = True
  .AppInfo = True
  .DriverInfo = True
  .PrintJobInfo = False
  .FontInfo = True
  .SepsInfo = False
 End With
 'print the document
 ActiveDocument.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.LinkInfo

Property **LinkInfo** As Boolean

Description

Member of PrintOptions

The **LinkInfo** property determines whether to print information about images with Open Prepress Interface (OPI) links on a job-information sheet.

VBA example

The following VBA example prints the job-information sheet with application information, driver information, and font information.

```
Sub Test()
 Dim DrawPrintOptions As PrintOptions
 Set DrawPrintOptions = ActiveDocument.PrintSettings.Options
 With DrawPrintOptions
  .JobInformation = True
  .AppInfo = True
  .DriverInfo = True
  .PrintJobInfo = False
  .FontInfo = True
  .SepsInfo = False
 End With
 'print the document
 ActiveDocument.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.MarksToPage

Property **MarksToPage** As Boolean

Description

Member of PrintOptions

The **MarksToPage** property fits a printer's marks to the printable page.

VBA example

The following VBA example disables the **MarksToPage** setting, enables registration marks, creates a rectangle, and prints the document. It then enables the **MarksToPage** setting and prints the document again.

```
Sub Test()
 Dim s As Shape
 With ActiveDocument
  .PrintSettings.Options.MarksToPage = False
  .PrintSettings.Prepress.RegistrationMarks = True
  Set s = .ActiveLayer.CreateRectangle(2, 6, 8, 8)
  .PrintOut
  .PrintSettings.Options.MarksToPage = True
  .PrintSettings.Prepress.RegistrationMarks = True
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.MonoResolution

Property **MonoResolution** As Long

Description

Member of PrintOptions

The **MonoResolution** property returns or specifies the printing resolution of monochrome bitmaps.

VBA example

The following VBA example activates downsampling for color, grayscale, and monochrome bitmaps. It then sets the resolution and prints the document.

```
Sub Test()
 Dim DrawPrintOptions As PrintOptions
 Set DrawPrintOptions = ActiveDocument.PrintSettings.Options
 With DrawPrintOptions
  'set all downsampling to True
  .DownsampleColor = True
  .DownsampleGray = True
  .DownsampleMono = True
  'set the resolution
  .ColorResolution = 96
  .GrayResolution = 150
  .MonoResolution = 600
 End With
 'print the document
 ActiveDocument.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.ObjectsColorMode

Property **ObjectsColorMode** As PrnObjectsColorMode

Description

Member of PrintOptions

The **ObjectsColorMode** property specifies the color mode for outputting objects.

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.PrintBitmaps

Property **PrintBitmaps** As Boolean

Description

Member of PrintOptions

The **PrintBitmaps** property returns or specifies whether bitmaps are printed.

VBA example

The following VBA example creates a rectangle, fills the rectangle, and converts it to a bitmap. It then creates another rectangle. Finally, before printing the document, it sets vectors, but not bitmaps, to print.

```
Sub Test()
 Dim s As Shape
 With ActiveDocument
   Set s = .ActiveLayer.CreateRectangle(2, 6, 8, 8)
   s.Fill.UniformColor.RGBAssign 255, 0, 0
   s.ConvertToBitmap , , , , 96
   Set s = .ActiveLayer.CreateRectangle(4, 6, 8, 2)
   .PrintSettings.Options.PrintBitmaps = False
   .PrintSettings.Options.PrintVectors = True
   .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.PrintJobInfo

Property **PrintJobInfo** As Boolean

Description

Member of PrintOptions

The **PrintJobInfo** property determines whether to print information about the print job on a job-information sheet.

VBA example

The following VBA example prints the job-information sheet with application information, driver information, and font information.

```
Sub Test()
 Dim DrawPrintOptions As PrintOptions
 Set DrawPrintOptions = ActiveDocument.PrintSettings.Options
 With DrawPrintOptions
  .JobInformation = True
  .AppInfo = True
  .DriverInfo = True
  .PrintJobInfo = False
  .FontInfo = True
  .SepsInfo = False
 End With
 'print the document
 ActiveDocument.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.PrintText

Property **PrintText** As Boolean

Description

Member of PrintOptions

The **PrintText** property returns or specifies whether text is printed.

VBA example

The following VBA example creates a text string and adds a uniform fill to it. The text is then set to print in black, and the document is printed.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateArtisticText(4, 5, "Some Text String")
 s.Fill.UniformColor.RGBAssign 255, 0, 0
 With ActiveDocument.PrintSettings.Options
  .PrintText = True
  .TextInBlack = True
 End With
 ActiveDocument.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.PrintVectors

Property **PrintVectors** As Boolean

Description

Member of PrintOptions

The **PrintVectors** property returns or specifies whether vectors are printed.

VBA example

The following VBA example creates a rectangle, fills the rectangle, and converts it to a bitmap. It then creates another rectangle. Finally, before printing the document, it sets vectors, but not bitmaps, to print.

```
Sub Test()
 Dim s As Shape
 With ActiveDocument
   Set s = .ActiveLayer.CreateRectangle(2, 6, 8, 8)
   s.Fill.UniformColor.RGBAssign 255, 0, 0
   s.ConvertToBitmap , , , , 96
   Set s = .ActiveLayer.CreateRectangle(4, 6, 8, 2)
   .PrintSettings.Options.PrintBitmaps = False
   .PrintSettings.Options.PrintVectors = True
   .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.RasterizePage

Property **RasterizePage** As Boolean

Description

Member of PrintOptions

The **RasterizePage** property returns or specifies whether to print a document as a bitmap.

VBA example

The following VBA example sets each page to print as a bitmap, sets the resolution of the bitmap to **300** dpi, and then prints the document.

```
Sub Test()
 With ActiveDocument.PrintSettings.Options
  .RasterizePage = True
  .RasterizeResolution = 300
 End With
 ActiveDocument.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.RasterizeResolution

Property **RasterizeResolution** As Long

Description

Member of PrintOptions

The **RasterizeResolution** property returns or specifies the resolution of a bitmap.

- This property is used in conjunction with the RasterizePage property, which lets you print a document as a bitmap.

VBA example

The following VBA example sets each page to print as a bitmap, sets the resolution of the bitmap to **300** dpi, and then prints the document.

```
Sub Test()
 With ActiveDocument.PrintSettings.Options
  .RasterizePage = True
  .RasterizeResolution = 300
 End With
 ActiveDocument.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.SepsInfo

Property **SepsInfo** As Boolean

Description

Member of PrintOptions

The **SepsInfo** property determines whether to print information about print separations on a job-information sheet.

VBA example

The following VBA example prints the job-information sheet with application information, driver information, and font information.

```
Sub Test()
 Dim DrawPrintOptions As PrintOptions
 Set DrawPrintOptions = ActiveDocument.PrintSettings.Options
 With DrawPrintOptions
  .JobInformation = True
  .AppInfo = True
  .DriverInfo = True
  .PrintJobInfo = False
  .FontInfo = True
  .SepsInfo = False
 End With
 'print the document
 ActiveDocument.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.TextInBlack

Property **TextInBlack** As Boolean

Description

Member of PrintOptions

The **TextInBlack** property returns or specifies whether to print all text in black.

VBA example

The following VBA example creates a text string and adds a uniform fill to it. The text is then set to print in black, and the document is printed.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateArtisticText(4, 5, "Some Text String")
 s.Fill.UniformColor.RGBAssign 255, 0, 0
 With ActiveDocument.PrintSettings.Options
  .PrintText = True
  .TextInBlack = True
 End With
 ActiveDocument.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintOptions.UseColorProfile

Property **UseColorProfile** As Boolean

Description

Member of PrintOptions

The **UseColorProfile** property returns or specifies whether to use the selected color profile. Using a color profile reproduces colors more accurately.

- This setting does not affect grayscale output.

VBA example

The following VBA example creates a rectangle, fills it, and prints the document. Then color profile is applied, and the document is printed again.

```
Sub Test()
 Dim s As Shape
 With ActiveDocument
  .PrintSettings.Options.UseColorProfile = False
  Set s = .ActiveLayer.CreateRectangle(2, 6, 8, 8)
  s.Fill.UniformColor.RGBAssign 255, 255, 0
  .PrintOut
  .PrintSettings.Options.UseColorProfile = True
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPages

Properties

Description

The **PrintPages** class represents the set of all the pages included in a print job.

Copyright 2014 Corel Corporation. All rights reserved.

PrintPages.Count

Property **Count** As Long

Description

Member of PrintPages

The **Count** property returns the number of pages in a PrintPages collection.

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript

Properties

Description

The **PrintPostScript** class represents the PostScript settings of the CorelDRAW print engine.

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript.AutoIncreaseFlatness

Property **AutoIncreaseFlatness** As Boolean

Description

Member of PrintPostScript

The **AutoIncreaseFlatness** property specifies how the print engine handles object flatness. When this property is set to **True**, the print engine increases the object flatness in increments of two.

VBA example

The following VBA example creates a curve, sets the **AutoIncreaseFlatness** property to **True**, and prints the document.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateCurve
 With s.Curve.CreateSubPath(0.492835, 10.327087)
  .AppendCurveSegment False, 1.065118, 9.879213, 0.189492, -23.198591, 0.646929, 0#
  .AppendCurveSegment False, 1.313937, 9.381575, 0.497638, 180#, 0.225315, 173.659808
  .AppendCurveSegment False, 1.363701, 9.05811, 0.15135, -9.462322, 0.12687, 11.309932
  .AppendCurveSegment False, 0.791417, 8.859055, 0.078681, -161.565051, 0.174173, 90#
  .AppendCurveSegment False, 1.438346, 8.560472, 0.348346, -90#, 0.248819, 90#
  .AppendCurveSegment False, 0.890945, 8.386299, 0.323465, -90#, 0.223937, 0#
  .AppendCurveSegment False, 1.139764, 8.062835, 0.373228, 180#, 0.124409, 180#
  .AppendCurveSegment False, 1.413465, 7.490551, 0.750177, -5.710593, 0.497638, 90#
  .AppendCurveSegment False, 1.911102, 7.391024, 0.099528, -90#, 0.102591, 104.036243
  .AppendCurveSegment False, 1.811575, 6.793858, 0.338429, -72.897271, 0.380618, 168.690068
  .AppendCurveSegment False, 2.209685, 7.117323, 0.537126, -13.392498, 0.278185, -116.565051
  .AppendCurveSegment False, 3.478661, 6.768976, 0.556374, 63.434949, 0.746457, 90#
  .AppendCurveSegment False, 2.981024, 6.669449, 0.174173, -90#, 0.099528, 0#
  .AppendCurveSegment False, 2.682441, 7.21685, 0.200602, 172.874984, 0#, 0#
 End With
 With ActiveDocument.PrintSettings.PostScript
  .AutoIncreaseFlatness = True
 End With
 ActiveDocument.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript.AutoIncreaseFountainSteps

Property **AutoIncreaseFountainSteps** As Boolean

Description

Member of PrintPostScript

The **AutoIncreaseFlatness** property controls whether the print engine increases the number of fountain steps to reduce banding. When this property is set to **True**, the print engine makes the increase only if necessary.

VBA example

The following VBA example creates a rectangle and fills it with a a conical fountain fill. After it sets **AutoIncreaseFountainSteps** to True, it prints the document.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(2, 4, 6, 8)
 s.Fill.ApplyFountainFill CreateRGBColor(255, 0, 0), CreateRGBColor(0, 255, 0), cdrConicalFountainFill, , 4
 With ActiveDocument
  .PrintSettings.PostScript.AutoIncreaseFountainSteps = True
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript.ConformToDSC

Property **ConformToDSC** As Boolean

Description

Member of PrintPostScript

The **ConformtoDSC** property ensures that a PostScript file conforms to the Document Structuring Convention.

VBA example

The following VBA example saves the current value of the **ConformToDSC** property and sets it to **True**. After it prints the document, it restores the saved value.

```
Sub Test()
 Dim bConformToDSC As Boolean
 'save current value
 With ActiveDocument.PrintSettings.PostScript
  bConformToDSC = .ConformToDSC
  'set new value
  .ConformToDSC = True
 End With
 'print document
 ActiveDocument.PrintOut
 'restore saved value
 With ActiveDocument.PrintSettings.PostScript
  .ConformToDSC = bConformToDSC
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript.DownloadType1

Property **DownloadType1** As Boolean

Description

Member of PrintPostScript

The **DownloadType1** property controls the download of Type 1 fonts to a PostScript printer. If fonts are not downloaded to the printer (and they are not already installed on the printer), the fonts print as curves or bitmaps.

VBA example

The following VBA example creates text strings in various fonts and prints them. The fonts are downloaded to the printer (if PostScript), and the document is printed again.

```
Sub Test()
 Dim s As Shape
 Dim n As Integer
 Dim dLeft As Double
 Dim dBottom As Double
 dLeft = 0.25
 dBottom = ActivePage.SizeHeight - 0.4
 For n = 1 To FontList.Count Step 5
  Set s = ActiveLayer.CreateArtisticText(dLeft, dBottom, "Some Text String")
  s.Text.FontProperties.Name = FontList(n)
  dBottom = dBottom - 0.4
 Next n
 With ActiveDocument
  .PrintSettings.PostScript.DownloadType1 = False
  .PrintSettings.PostScript.TrueTypeToType1 = False
  .PrintOut
  .PrintSettings.PostScript.DownloadType1 = True
  .PrintSettings.PostScript.TrueTypeToType1 = True
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript.Flatness

Property **Flatness** As Long

Description

Member of PrintPostScript

The **Flatness** property specifies how the print engine handles curve flatness.

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript.JPEGCompression

Property **JPEGCompression** As Boolean

Description

Member of PrintPostScript

The **JPEGCompression** property returns or specifies whether to compress the bitmaps in a print job.

- You can use the JPEGQuality property to specify the quality of the compression.

VBA example

The following VBA example creates a rectangle, an ellipse, and a polygon. It fills each of them with a texture fill and converts them to bitmaps. JPEG compression is disabled, and the document is printed. Then JPEG compression is enabled, the quality of the compression is set, and the document is printed again.

```
Sub Test()
 Dim shRect As Shape
 Set shRect = ActiveLayer.CreateRectangle(1.114882, 10.078268, 3.030787, 8.485827, 0, 0, 0, 0)
 Dim shEllipse As Shape
 Set shEllipse = ActiveLayer.CreateEllipse(4.075827, 7.540315, 6.016614, 5.375591, 90#, 90#, False)
 Dim shPolygon As Shape
 Set shPolygon = ActiveLayer.CreatePolygon(5.842445, 2.912283, 7.758343, 0.44898, 5, 1, 1, False, 50, 100)
 With shPolygon.Fill.ApplyTextureFill("Alien Eyes", "Samples 9")
  .SetProperties 3281, 2, 0, 150, 25, 1, CreateRGBColor(25, 0, 73), CreateRGBColor(229, 255, 0), 0
  .MaximumTileWidth = 2049
  .TransformWithShape = True
  .MirrorFill = False
  .TileOffsetType = cdrTileOffsetRow
  .TileOffset = 0
  .Resolution = 300
  .RotationAngle = 0#
  .SkewAngle = 0#
  .TileHeight = 2.228083
  .TileWidth = 1.822134
  .OriginX = 0#
  .OriginY = 0#
 End With
 shPolygon.ConvertToBitmap , , , False, 150
 With shEllipse.Fill.ApplyTextureFill("Disco Nightmare", "Samples 9")
  .SetProperties 4641, 0, 100, 0, 100, CreateRGBColor(51, 0, 204), CreateRGBColor(255, 102, 0), 0
  .MaximumTileWidth = 2049
  .TransformWithShape = True
  .MirrorFill = False
  .TileOffsetType = cdrTileOffsetRow
  .TileOffset = 0
  .Resolution = 300
  .RotationAngle = 0#
  .SkewAngle = 0#
  .TileHeight = 2.164724
  .TileWidth = 1.940787
  .OriginX = 0#
  .OriginY = 0#
 End With
 shEllipse.ConvertToBitmap , , , False, 150
 With shRect.Fill.ApplyTextureFill("Solder", "Samples 9")
  .SetProperties 19195, 60, 0, 75, 25, 100, 50, 50, CreateRGBColor(25, 25, 255), CreateRGBColor(0, 0, 0),
CreateRGBColor(255, 255, 255), 0
  .MaximumTileWidth = 2049
  .TransformWithShape = True
  .MirrorFill = False
  .TileOffsetType = cdrTileOffsetRow
  .TileOffset = 0
  .Resolution = 300
  .RotationAngle = 0#
  .SkewAngle = 0#
  .TileHeight = 2.662362
  .TileWidth = 1.84126
  .OriginX = 0.000008
  .OriginY = 0.000004
 End With
 shRect.ConvertToBitmap , , , False, 150
 With ActiveDocument
  .PrintSettings.PostScript.JPEGCompression = False
  .PrintOut
  .PrintSettings.PostScript.JPEGCompression = True
  .PrintSettings.PostScript.JPEGQuality = 100
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript.JPEGQuality

Property **JPEGQuality** As Long

Description

Member of PrintPostScript

The **JPEGQuality** property returns or specifies the quality of compressed bitmaps in a print job. To use this property, you must enable the JPEGCompression property (which allows for the compression).

VBA example

The following VBA example creates a rectangle, an ellipse, and a polygon. It fills each of them with a texture fill and converts them to bitmaps. JPEG compression is disabled, and the document is printed. Then JPEG compression is enabled, the quality of the compression is set, and the document is printed again.

```
Sub Test()
 Dim shRect As Shape
 Set shRect = ActiveLayer.CreateRectangle(1.114882, 10.078268, 3.030787, 8.485827, 0, 0, 0, 0)
 Dim shEllipse As Shape
 Set shEllipse = ActiveLayer.CreateEllipse(4.075827, 7.540315, 6.016614, 5.375591, 90#, 90#, False)
 Dim shPolygon As Shape
 Set shPolygon = ActiveLayer.CreatePolygon(5.842445, 2.912283, 7.758343, 0.44898, 5, 1, 1, False, 50, 100)
 With shPolygon.Fill.ApplyTextureFill("Alien Eyes", "Samples 9")
  .SetProperties 3281, 2, 0, 150, 25, 1, CreateRGBColor(25, 0, 73), CreateRGBColor(229, 255, 0), 0
  .MaximumTileWidth = 2049
  .TransformWithShape = True
  .MirrorFill = False
  .TileOffsetType = cdrTileOffsetRow
  .TileOffset = 0
  .Resolution = 300
  .RotationAngle = 0#
  .SkewAngle = 0#
  .TileHeight = 2.228083
  .TileWidth = 1.822134
  .OriginX = 0#
  .OriginY = 0#
 End With
 shPolygon.ConvertToBitmap , , , False, 150
 With shEllipse.Fill.ApplyTextureFill("Disco Nightmare", "Samples 9")
  .SetProperties 4641, 0, 100, 0, 100, CreateRGBColor(51, 0, 204), CreateRGBColor(255, 102, 0), 0
  .MaximumTileWidth = 2049
  .TransformWithShape = True
  .MirrorFill = False
  .TileOffsetType = cdrTileOffsetRow
  .TileOffset = 0
  .Resolution = 300
  .RotationAngle = 0#
  .SkewAngle = 0#
  .TileHeight = 2.164724
  .TileWidth = 1.940787
  .OriginX = 0#
  .OriginY = 0#
 End With
 shEllipse.ConvertToBitmap , , , False, 150
 With shRect.Fill.ApplyTextureFill("Solder", "Samples 9")
  .SetProperties 19195, 60, 0, 75, 25, 100, 50, 50, CreateRGBColor(25, 25, 255), CreateRGBColor(0, 0, 0),
CreateRGBColor(255, 255, 255), 0
  .MaximumTileWidth = 2049
  .TransformWithShape = True
  .MirrorFill = False
  .TileOffsetType = cdrTileOffsetRow
  .TileOffset = 0
  .Resolution = 300
  .RotationAngle = 0#
  .SkewAngle = 0#
  .TileHeight = 2.662362
  .TileWidth = 1.84126
  .OriginX = 0.000008
  .OriginY = 0.000004
 End With
 shRect.ConvertToBitmap , , , False, 150
 With ActiveDocument
  .PrintSettings.PostScript.JPEGCompression = False
  .PrintOut
  .PrintSettings.PostScript.JPEGCompression = True
  .PrintSettings.PostScript.JPEGQuality = 100
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript.Level

Property **Level** As PrnPostScriptLevel

Description

Member of PrintPostScript

The **Level** property returns or specifies the PostScript level of the print engine.

VBA example

The following VBA example displays the current PostScript level.

```
Sub Test()
 MsgBox "The current PostScript level is level " & _
  ActiveDocument.PrintSettings.PostScript.Level
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript.MaintainOPILinks

Property **MaintainOPILinks** As Boolean

Description

Member of PrintPostScript

The **MaintainOPILinks** property specifies whether to maintain Open Prepress Interface (OPI) links when distilling a PostScript file.

VBA example

The following VBA example sets the **MaintainOPILinks** and **ResolveDCSLinks** properties to **True** and prints the document to file.

```
Sub Test()
 With ActiveDocument
  .PrintSettings.PostScript.MaintainOPILinks = True
  .PrintSettings.PostScript.ResolveDCSLinks = True
  .PrintSettings.FileName = "c:\Temp.ps"
  .PrintSettings.PrintToFile = True
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript.MaxPointsPerCurve

Property **MaxPointsPerCurve** As Long

Description

Member of PrintPostScript

The **MaxPointsPerCurve** property returns or specifies the maximum allowable number of control points per curve.

VBA example

The following VBA example displays the current value of the **MaxPointsPerCurve** property. It then sets the value to one-half of the previous value and displays the new value.

```
Sub Test()
 With ActiveDocument
  MsgBox "The current value of MaxPointsPerCurve is " & _
   .PrintSettings.PostScript.MaxPointsPerCurve
  .PrintSettings.PostScript.MaxPointsPerCurve = .PrintSettings.PostScript.MaxPointsPerCurve / 2
  MsgBox "The current value of MaxPointsPerCurve is " & _
   .PrintSettings.PostScript.MaxPointsPerCurve
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript.OptimizeFountainFills

Property **OptimizeFountainFills** As Boolean

Description

Member of PrintPostScript

The **OptimizeFountainFills** property determines whether the print engine decreases the number of fountain steps. When this property is set to **True**, the print engine makes the decrease only if necessary.

VBA example

The following VBA example creates a rectangle, fills it with a conical fountain fill with **256** steps, sets the **OptimizeFountainFills** property to **True**, and prints the document.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(2, 4, 6, 8)
 s.Fill.ApplyFountainFill CreateRGBColor(255, 0, 0), CreateRGBColor(0, 255, 0), cdrConicalFountainFill, , 256
 With ActiveDocument
  .PrintSettings.PostScript.OptimizeFountainFills = True
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript.pdfBookmarks

Property **pdfBookmarks** As Boolean

Description

Member of PrintPostScript

The **pdfBookmarks** property determines whether to include bookmarks when distilling a PostScript file into a PDF file.

VBA example

The following VBA example sets the options for distilling a PostScript file into a PDF file. The resulting PDF file displays document outlines on startup and contains hyperlinks and bookmarks.

```
Sub TestPDF()
 With ActiveDocument.PrintSettings.PostScript
  .PDFStartup = prnPDFOutlines
  .PDFBookmarks = True
  .PDFHyperlinks = True
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript.PDFHyperlinks

Property **PDFHyperlinks** As Boolean

Description

Member of PrintPostScript

The **PDFHyperlinks** property determines whether to include hyperlinks when distilling a PostScript file into a PDF file.

VBA example

The following VBA example sets the options for distilling a PostScript file into a PDF file. The resulting PDF file displays document outlines on startup and contains hyperlinks and bookmarks.

```
Sub TestPDF()
 With ActiveDocument.PrintSettings.PostScript
  .PDFStartup = prnPDFOutlines
  .PDFBookmarks = True
  .PDFHyperlinks = True
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript.PDFStartup

Property **PDFStartup** As PrnPDFStartup

Description

Member of PrintPostScript

The **PDFStartup** property specifies the startup behavior for PDF files created from a PostScript file.

VBA example

The following VBA example sets the options for distilling a PostScript file into a PDF file. The resulting PDF file displays document outlines on startup and contains hyperlinks and bookmarks.

```
Sub TestPDF()
 With ActiveDocument.PrintSettings.PostScript
  .PDFStartup = prnPDFOutlines
  .PDFBookmarks = True
  .PDFHyperlinks = True
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript.ResolveDCSLinks

Property **ResolveDCSLinks** As Boolean

Description

Member of PrintPostScript

The **ResolveDCSLinks** property specifies whether to resolve Desktop Color Separation (DCS) links when distilling a PostScript file.

VBA example

The following VBA example sets the **MaintainOPILinks** and **ResolveDCSLinks** properties to **True** and prints the document to file.

```
Sub Test()
 With ActiveDocument
  .PrintSettings.PostScript.MaintainOPILinks = True
  .PrintSettings.PostScript.ResolveDCSLinks = True
  .PrintSettings.FileName = "c:\Temp.ps"
  .PrintSettings.PrintToFile = True
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript.ScreenFrequency

Property **ScreenFrequency** As Long

Description

Member of PrintPostScript

The **ScreenFrequency** property returns or specifies the basic halftone-screen frequency of a print job in lines per inch (lpi).

VBA example

The following VBA example sets the screen frequency to **120** lpi.

```
Sub Test()
 With ActiveDocument.PrintSettings.PostScript
  .ScreenFrequency = 120
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPostScript.TrueTypeToType1

Property **TrueTypeToType1** As Boolean

Description

Member of PrintPostScript

The **TrueTypeToType1** property controls the download of TrueType fonts to a PostScript printer. TrueType fonts are converted to Type 1 fonts so that they can be downloaded. If fonts are not downloaded to the printer (and they are not already installed on the printer), the fonts print as curves or bitmaps.

VBA example

The following VBA example creates text strings in different fonts and then prints them. The fonts are downloaded to the printer (if PostScript), and the document is printed again.

```
Sub Test()
 Dim s As Shape
 Dim n As Integer
 Dim dLeft As Double
 Dim dBottom As Double
 dLeft = 0.25
 dBottom = ActivePage.SizeHeight - 0.4
 For n = 1 To FontList.Count Step 5
  Set s = ActiveLayer.CreateArtisticText(dLeft, dBottom, "Some Text String")
  s.Text.FontProperties.Name = FontList(n)
  dBottom = dBottom - 0.4
 Next n
 With ActiveDocument
  .PrintSettings.PostScript.DownloadType1 = False
  .PrintSettings.PostScript.TrueTypeToType1 = False
  .PrintOut
  .PrintSettings.PostScript.DownloadType1 = True
  .PrintSettings.PostScript.TrueTypeToType1 = True
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPrepress

Properties

Description

The **PrintPrepress** class represents the prepress settings of the CorelDRAW print engine.

Copyright 2014 Corel Corporation. All rights reserved.

PrintPrepress.ColorCalibrationBar

Property **ColorCalibrationBar** As Boolean

Description

Member of PrintPrepress

The **ColorCalibrationBar** property determines whether to print a color-calibration bar. When set to **True**, this property prints a bar of six basic colors.

VBA example

The following VBA example creates a new document containing four rectangles. Each rectangle is filled with a different color (cyan, magenta, yellow, or black). A calibration bar is added, and then the document is printed.

```
Sub PrePressColorCalibrationBar()
 Dim doc As Document
 Dim s As Shape
 Set doc = CreateDocument
 Set s = ActiveLayer.CreateRectangle(0.667008, 10.302205, 2.906378, 8.062835, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 100, 0, 0, 0
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(4.77252, 10.351969, 6.987008, 8.13748, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(0.990472, 6.569921, 3.105433, 4.454961, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(4.872047, 6.81874, 7.01189, 4.678898, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 0, 0, 100
 s.Outline.Type = cdrNoOutline
 With doc
  With .PrintSettings
   .Options.MarksToPage = True
   .Prepress.ColorCalibrationBar = True
  End With
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPrepress.CropMarks

Property **CropMarks** As Boolean

Description

Member of PrintPrepress

The **CropMarks** property determines whether any crop and fold marks that reside within the page are printed.

VBA example

The following VBA example creates a new document containing two rectangles. Each rectangle is filled with a different color (cyan or magenta). The document and any crop marks that appear within the page are then printed.

```
Sub Test()
 Dim doc As Document
 Dim s As Shape
 Set doc = CreateDocument
 Set s = ActiveLayer.CreateRectangle(0.667008, 10.302205, 2.906378, 8.062835, 0, 0, 0, 0)
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(4.77252, 10.351969, 6.987008, 8.13748, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
 s.Outline.Type = cdrNoOutline
 With doc
  With .PrintSettings
   .Prepress.CropMarks = True
   .Prepress.ExteriorCropMarks = False
   .Options.MarksToPage = True
  End With
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPrepress.Densities

Property **Densities(***Index As Long***)** As Long

Description

Member of PrintPrepress

The **Densities** property returns or specifies the density of the squares in the densitometer scale.

Parameter	Description
Index	Specifies the square in the densitometer scale

VBA example

The following VBA example creates a new document containing four shapes of a different color. It sets the density of the second square in the densitometer scale to **15**. When the document is printed, the densitometer scale is also printed.

```
Sub DensityTest()
 Dim doc As Document
 Dim s As Shape
 Set doc = CreateDocument
 Set s = ActiveLayer.CreateEllipse(0.766535, 9.928976, 3.180079, 7.515433, 90#, 90#, False)
 s.Fill.UniformColor.CMYKAssign 100, 0, 0, 0
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreatePolygon(5.643386, 9.953858, 8.355512, 7.241732, 5, 1, 1, False, 50, 100)
 s.Move -0.870866, 0.174173
 s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateGridBoxes(1.388583, 5.699055, 3.279606, 3.658748, 4, 3)
 s.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
 Set s = ActiveLayer.CreateRectangle(5.295039, 5.723937, 7.061654, 3.957323, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 0, 0, 100
 s.Outline.Type = cdrNoOutline
 With doc
  With .PrintSettings
   .Prepress.Densities(1) = 15
   .Prepress.DensitometerScale = True
   .Options.MarksToPage = True
  End With
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPrepress.DensitometerScale

Property **DensitometerScale** As Boolean

Description

Member of PrintPrepress

The **DensitometerScale** property returns or specifies whether a densitometer scale is printed in the document.

VBA example

The following VBA example creates a new document containing four shapes of a different color. It sets the density of the second square in the densitometer scale to **15**. When the document is printed, the densitometer scale is also printed.

```
Sub DensityTest()
 Dim doc As Document
 Dim s As Shape
 Set doc = CreateDocument
 Set s = ActiveLayer.CreateEllipse(0.766535, 9.928976, 3.180079, 7.515433, 90#, 90#, False)
 s.Fill.UniformColor.CMYKAssign 100, 0, 0, 0
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreatePolygon(5.643386, 9.953858, 8.355512, 7.241732, 5, 1, 1, False, 50, 100)
 s.Move -0.870866, 0.174173
 s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateGridBoxes(1.388583, 5.699055, 3.279606, 3.658748, 4, 3)
 s.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
 Set s = ActiveLayer.CreateRectangle(5.295039, 5.723937, 7.061654, 3.957323, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 0, 0, 100
 s.Outline.Type = cdrNoOutline
 With doc
  With .PrintSettings
   .Prepress.Densities(1) = 15
   .Prepress.DensitometerScale = True
   .Options.MarksToPage = True
  End With
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPrepress.ExteriorCropMarks

Property **ExteriorCropMarks** As Boolean

Description

Member of PrintPrepress

The **ExteriorCropMarks** property determines whether any crop and fold marks that reside outside the page are printed.

VBA example

The following VBA example creates a new document containing two rectangles. Each rectangle is filled with a different color (cyan or magenta). The document and any crop marks that appear within the page are then printed.

```
Sub Test()
 Dim doc As Document
 Dim s As Shape
 Set doc = CreateDocument
 Set s = ActiveLayer.CreateRectangle(0.667008, 10.302205, 2.906378, 8.062835, 0, 0, 0, 0)
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(4.77252, 10.351969, 6.987008, 8.13748, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
 s.Outline.Type = cdrNoOutline
 With doc
  With .PrintSettings
   .Prepress.CropMarks = True
   .Prepress.ExteriorCropMarks = False
   .Options.MarksToPage = True
  End With
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPrepress.FileInfo

Property **FileInfo** As Boolean

Description

Member of PrintPrepress

The **FileInfo** property specifies whetherto print file information.

VBA example

The following VBA example creates a new document and adds three pages to it. It specifies that file information is to be printed, along with the job name and page numbers. As it iterates through the pages of the document, it adds text to each page and then prints the entire document.

```
Sub Test()
 Dim doc As Document
 Dim page As page
 Set doc = CreateDocument
 With doc
  .AddPages 3
  With .PrintSettings.Prepress
   .FileInfo = True
   .JobName = "Test of VBA methods"
   .PageNumbers = True
   .InfoWithinPage = True
  End With
  For Each page In doc.Pages
   page.ActiveLayer.CreateArtisticText page.SizeWidth / 2, page.SizeHeight / 2, "This is page " & page.Index
  Next page
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPrepress.InfoWithinPage

Property **InfoWithinPage** As Boolean

Description

Member of PrintPrepress

The **InfoWithinPage** property specifies whether file information is positioned within the page when printed.

VBA example

The following VBA example creates a new document and adds three pages to it. It specifies that file information is to be printed, along with the job name and page numbers. As it iterates through the pages of the document, it adds text to each page and then prints the entire document.

```
Sub Test()
 Dim doc As Document
 Dim page As page
 Set doc = CreateDocument
 With doc
  .AddPages 3
  With .PrintSettings.Prepress
   .FileInfo = True
   .JobName = "Test of VBA methods"
   .PageNumbers = True
   .InfoWithinPage = True
  End With
  For Each page In doc.Pages
   page.ActiveLayer.CreateArtisticText page.SizeWidth / 2, page.SizeHeight / 2, "This is page " & page.Index
  Next page
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPrepress.Invert

Property **Invert** As Boolean

Description

Member of PrintPrepress

The **Invert** property determines whether a print job produces negative images on film.

VBA example

The following VBA example sets the **Invert** property to **True** and prints the document.

```
Sub Test()
 With ActiveDocument
  .PrintSettings.Prepress.Invert = True
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPrepress.JobName

Property **JobName** As String

Description

Member of PrintPrepress

The **JobName** property specifies whether to print the name of a job.

VBA example

The following VBA example creates a new document and adds three pages to it. It specifies that file information is to be printed, along with the job name and page numbers. As it iterates through the pages of the document, it adds text to each page and then prints the entire document.

```
Sub Test()
 Dim doc As Document
 Dim page As page
 Set doc = CreateDocument
 With doc
  .AddPages 3
  With .PrintSettings.Prepress
   .FileInfo = True
   .JobName = "Test of VBA methods"
   .PageNumbers = True
   .InfoWithinPage = True
  End With
  For Each page In doc.Pages
   page.ActiveLayer.CreateArtisticText page.SizeWidth / 2, page.SizeHeight / 2, "This is page " & page.Index
  Next page
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPrepress.MarksToObjects

Property **MarksToObjects** As Boolean

Description

Member of PrintPrepress

The **MarksToObjects** property specifies whether to print prepress information around the objects rather than the page.

Copyright 2014 Corel Corporation. All rights reserved.

PrintPrepress.Mirror

Property **Mirror** As Boolean

Description

Member of PrintPrepress

The **Mirror** property determines whether the film emulsion faces down.

VBA example

The following VBA example prints the document with the emulsion facing up and then prints the document again with the emulsion facing down.

```
Sub Test()
 With ActiveDocument
  .PrintSettings.Prepress.Mirror = False
  .PrintOut
  .PrintSettings.Prepress.Mirror = True
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPrepress.PageNumbers

Property **PageNumbers** As Boolean

Description

Member of PrintPrepress

The **PageNumbers** property specifies whether to print page numbers.

VBA example

The following VBA example creates a new document and adds three pages to it. It specifies that file information is to be printed, along with the job name and page numbers. As it iterates through the pages of the document, it adds text to each page and then prints the entire document.

```
Sub Test()
 Dim doc As Document
 Dim page As page
 Set doc = CreateDocument
 With doc
  .AddPages 3
  With .PrintSettings.Prepress
   .FileInfo = True
   .JobName = "Test of VBA methods"
   .PageNumbers = True
   .InfoWithinPage = True
  End With
  For Each page In doc.Pages
   page.ActiveLayer.CreateArtisticText page.SizeWidth / 2, page.SizeHeight / 2, "This is page " & page.Index
  Next page
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPrepress.RegistrationMarks

Property **RegistrationMarks** As Boolean

Description

Member of PrintPrepress

The **RegistrationMarks** property determines whether to print registration marks.

- You can use the RegistrationStyle property to choose the style of the registration marks.

VBA example

The following VBA example sets Corel registration marks to print within the page. It displays the **Print** dialog box and then prints the document.

```
Sub Test()
 With ActiveDocument
  With .PrintSettings.Prepress
   .RegistrationMarks = True
   .RegistrationStyle = prnCorel
  End With
  .PrintSettings.Options.MarksToPage = True
  .PrintSettings.ShowDialog
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintPrepress.RegistrationStyle

Property **RegistrationStyle** As PrnRegistrationStyle

Description

Member of PrintPrepress

The **RegistrationStyle** property determines the style of the registration marks to be printed.

- To print registration marks, you must enable the RegistrationMarks property.

VBA example

The following VBA example sets Corel registration marks to print within the page. It displays the **Print** dialog box and then prints the document.

```
Sub Test()
 With ActiveDocument
  With .PrintSettings.Prepress
   .RegistrationMarks = True
   .RegistrationStyle = prnCorel
  End With
  .PrintSettings.Options.MarksToPage = True
  .PrintSettings.ShowDialog
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations

Properties

Description

The **PrintSeparations** class represents the print-separations settings of the CorelDRAW print engine.

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations.AdvancedSettings

Property **AdvancedSettings** As Boolean

Description

Member of PrintSeparations

The **AdvancedSettings** property determines whether advanced print-separations settings are used. These settings allow for greater control when printing separations.

VBA example

The following VBA example iterates through the SystemPrinters collection until it finds the specified printer. Print separations are enabled, and advanced settings are specified. The **Print** dialog box is then displayed.

```
Sub Test()
 Dim prn As Printer
 Dim intCounter As Integer
 For intCounter = 1 To Printers.Count
  Set prn = Printers.Item(intCounter)
   If prn.Name = "Device Independent PostScript File" Then
    Exit For
   End If
 Next intCounter
 With ActiveDocument
  With .PrintSettings
   Set .Printer = prn
   With .Separations
    .Enabled = True
    .AdvancedSettings = True
    .ScreenTechnology = "RT Screening - Lino 330"
    .Resolution = 1270
    .BasicScreen = "109"
   End With
   .ShowDialog
  End With
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations.AlwaysOverprintBlack

Property **AlwaysOverprintBlack** As Boolean

Description

Member of PrintSeparations

The **AlwaysOverprintBlack** property determines whether black is always overprinted.

VBA example

The following VBA example creates a new document and inserts two overlapping rectangles. Uniform fills of different colors (cyan and magenta) are applied to the rectangles, and an outline of 24pt is added to the overlying rectangle. Before the document is printed, separations are enabled.

```
Sub Test()
 Dim doc As Document
 Dim s As Shape
 Set doc = CreateDocument
 With doc
  Set s = .ActiveLayer.CreateRectangle(2.209685, 8.809291, 5.742913, 6.196693, 0, 0, 0, 0)
  s.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
  s.Outline.Type = cdrNoOutline
  Set s = .ActiveLayer.CreateRectangle(3.578189, 7.838898, 7.285591, 5.251181, 0, 0, 0, 0)
  s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
  s.Outline.Width = 0.333335
  With .PrintSettings.Separations
   .Enabled = True
   .AlwaysOverprintBlack = False
  End With
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations.AutoSpreadAmount

Property **AutoSpreadAmount** As Double

Description

Member of PrintSeparations

The **AutoSpreadAmount** property returns or specifies the amount of spread (that is, the maximum outline width) for auto-trapping.

VBA example

The following VBA example iterates through the SystemPrinters collection until it finds the specified printer. In a new document, it creates five shapes. It then enables print separations and auto-spreading. The **Print** dialog box is then displayed.

```
Sub Test()
 Dim doc As Document
 Dim s As Shape
 Dim prn As Printer
 Dim intCounter As Integer
 For intCounter = 1 To Printers.Count
  Set prn = Printers.Item(intCounter)
   If prn.Name = "Device Independent PostScript File" Then
    Exit For
   End If
 Next intCounter
 Set doc = CreateDocument
 With doc
  Set s = .ActiveLayer.CreateEllipse(0.592362, 10.426614, 7.534409, 7.366142, 90#, 90#, False)
  s.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
  s.Outline.Type = cdrNoOutline
  Set s = .ActiveLayer.CreateArtisticText(1.25, 8.85, "This is a test of text")
  s.Text.FontProperties.Size = 48
  Set s = .ActiveLayer.CreateRectangle(1.712047, 6.321102, 5.668268, 4.654016, 0, 0, 0, 0)
  s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
  s.Outline.Type = cdrNoOutline
  s.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
  Set s = .ActiveLayer.CreateRectangle(3.926535, 5.599528, 7.335354, 3.459685, 0, 0, 0, 0)
  s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
  s.Outline.Type = cdrNoOutline
  Set s = .ActiveLayer.CreateRectangle(0.642126, 5.276063, 5.071102, 2.215591, 0, 0, 0, 0)
  s.Fill.UniformColor.CMYKAssign 100, 100, 0, 0
  s.Outline.Type = cdrNoOutline
  With .PrintSettings
   Set .Printer = prn
   With .Separations
   .Enabled = True
   .AutoSpreadAmount = 3527.77778
   .AutoSpreading = True
   .AutoSpreadTextAbove = 254000
   End With
   .ShowDialog
  End With
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations.AutoSpreadFixed

Property **AutoSpreadFixed** As Boolean

Description

Member of PrintSeparations

The **AutoSpreadFixed** property returns or specifies outlines of equal width for auto-spreading.

VBA example

The following VBA example displays the current value of the **AutoSpreadFixed** property.

```
Sub Test()
 With ActiveDocument
  MsgBox "The current value for AutoSpreadFixed is " & _
   .PrintSettings.Separations.AutoSpreadFixed
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations.AutoSpreading

Property **AutoSpreading** As Boolean

Description

Member of PrintSeparations

The **AutoSpreading** property determines whether auto-spreading is enabled.

VBA example

The following VBA example iterates through the SystemPrinters collection until it finds the specified printer. In a new document, it creates five shapes. It then enables separations and auto-spreading. The **Print** dialog box is then displayed.

```
Sub Test()
 Dim doc As Document
 Dim s As Shape
 Dim prn As Printer
 Dim intCounter As Integer
 For intCounter = 1 To Printers.Count
  Set prn = Printers.Item(intCounter)
   If prn.Name = "Device Independent PostScript File" Then
    Exit For
   End If
 Next intCounter
 Set doc = CreateDocument
 With doc
  Set s = .ActiveLayer.CreateEllipse(0.592362, 10.426614, 7.534409, 7.366142, 90#, 90#, False)
  s.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
  s.Outline.Type = cdrNoOutline
  Set s = .ActiveLayer.CreateArtisticText(1.25, 8.85, "This is a test of text")
  s.Text.FontProperties.Size = 48
  Set s = .ActiveLayer.CreateRectangle(1.712047, 6.321102, 5.668268, 4.654016, 0, 0, 0, 0)
  s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
  s.Outline.Type = cdrNoOutline
  s.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
  Set s = .ActiveLayer.CreateRectangle(3.926535, 5.599528, 7.335354, 3.459685, 0, 0, 0, 0)
  s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
  s.Outline.Type = cdrNoOutline
  Set s = .ActiveLayer.CreateRectangle(0.642126, 5.276063, 5.071102, 2.215591, 0, 0, 0, 0)
  s.Fill.UniformColor.CMYKAssign 100, 100, 0, 0
  s.Outline.Type = cdrNoOutline
  With .PrintSettings
   Set .Printer = prn
   With .Separations
   .Enabled = True
   .AutoSpreadAmount = 3527.77778
   .AutoSpreading = True
   .AutoSpreadTextAbove = 254000
   End With
   .ShowDialog
  End With
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations.AutoSpreadTextAbove

Property **AutoSpreadTextAbove** As Double

Description

Member of PrintSeparations

The **AutoSpreadTextAbove** property returns or specifies the smallest point size for text to be trapped automatically.

VBA example

The following VBA example iterates through the SystemPrinters collection until it finds the specified printer. In a new document, it creates five shapes. It then enables separations and auto-spreading. The **Print** dialog box is then displayed.

```
Sub Test()
 Dim doc As Document
 Dim s As Shape
 Dim prn As Printer
 Dim intCounter As Integer
 For intCounter = 1 To Printers.Count
  Set prn = Printers.Item(intCounter)
   If prn.Name = "Device Independent PostScript File" Then
    Exit For
   End If
 Next intCounter
 Set doc = CreateDocument
 With doc
  Set s = .ActiveLayer.CreateEllipse(0.592362, 10.426614, 7.534409, 7.366142, 90#, 90#, False)
  s.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
  s.Outline.Type = cdrNoOutline
  Set s = .ActiveLayer.CreateArtisticText(1.25, 8.85, "This is a test of text")
  s.Text.FontProperties.Size = 48
  Set s = .ActiveLayer.CreateRectangle(1.712047, 6.321102, 5.668268, 4.654016, 0, 0, 0, 0)
  s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
  s.Outline.Type = cdrNoOutline
  s.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
  Set s = .ActiveLayer.CreateRectangle(3.926535, 5.599528, 7.335354, 3.459685, 0, 0, 0, 0)
  s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
  s.Outline.Type = cdrNoOutline
  Set s = .ActiveLayer.CreateRectangle(0.642126, 5.276063, 5.071102, 2.215591, 0, 0, 0, 0)
  s.Fill.UniformColor.CMYKAssign 100, 100, 0, 0
  s.Outline.Type = cdrNoOutline
  With .PrintSettings
   Set .Printer = prn
   With .Separations
   .Enabled = True
   .AutoSpreadAmount = 3527.77778
   .AutoSpreading = True
   .AutoSpreadTextAbove = 254000
   End With
   .ShowDialog
  End With
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations.BasicScreen

Property **BasicScreen** As String

Description

Member of PrintSeparations

The **BasicScreen** property returns or specifies the basic screen used for printing separations.

- For this property to be used, the AdvancedSettings property must be set to **True**.

VBA example

The following VBA example iterates through the SystemPrinters collection until it finds the specified printer. It then enables print separations and sets advanced settings. The **Print** dialog box is then displayed.

```
Sub Test()
 Dim prn As Printer
 Dim intCounter As Integer
 For intCounter = 1 To Printers.Count
  Set prn = Printers.Item(intCounter)
   If prn.Name = "Device Independent PostScript File" Then
    Exit For
   End If
 Next intCounter
 With ActiveDocument
  With .PrintSettings
   Set .Printer = prn
   With .Separations
    .Enabled = True
    .AdvancedSettings = True
    .ScreenTechnology = "RT Screening - Lino 330"
    .Resolution = 1270
    .BasicScreen = "109"
   End With
   .ShowDialog
  End With
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations.EmptyPlates

Property **EmptyPlates** As Boolean

Description

Member of PrintSeparations

The **EmptyPlates** property determines whether all plates, including empty ones, are printed.

VBA example

The following VBA example creates two rectangles with uniform fills. It then enables print separations and prints all four plates.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(1.239291, 7.590079, 4.050945, 4.778425, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 100, 0, 0, 0
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(2.607795, 6.395748, 5.344803, 3.65874, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
 s.Outline.Type = cdrNoOutline
 With ActiveDocument
  With .PrintSettings
   .Separations.Enabled = True
   .Separations.EmptyPlates = True
   .ShowDialog
  End With
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations.Enabled

Property **Enabled** As Boolean

Description

Member of PrintSeparations

The **PrintSeparations** property determines whether separations are printed.

VBA example

The following VBA example enables separations and displays the **Print** dialog box.

```
Sub Test()
 With ActiveDocument
  With .PrintSettings
   .Separations.Enabled = True
   .ShowDialog
  End With
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations.HalftoneType

Property **HalftoneType** As String

Description

Member of PrintSeparations

The **HalftoneType** property returns the selected halftone type.

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations.Hexachrome

Property **Hexachrome** As Boolean

Description

Member of PrintSeparations

The **Hexachrome** property determines whether PANTONE Hexachrome process colors are used.

VBA example

The following VBA example creates two rectangles with uniform fills. It then enables separations and Hexachrome colors. The **Print** dialog box is then displayed.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(1.239291, 7.590079, 4.050945, 4.778425, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 100, 0, 0, 0
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(2.607795, 6.395748, 5.344803, 3.65874, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
 s.Outline.Type = cdrNoOutline
 With ActiveDocument
  With .PrintSettings
   .Separations.Enabled = True
   .Separations.Hexachrome = True
   .ShowDialog
  End With
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations.InColor

Property **InColor** As Boolean

Description

Member of PrintSeparations

The **InColor** property determines whether separations are printed in color.

VBA example

The following VBA example iterates through the SystemPrinters collection until it finds the specified printer. It then enables color separations and displays the **Print** dialog box.

```
Sub Test()
 Dim prn As Printer
 Dim intCounter As Integer
 For intCounter = 1 To Printers.Count
  Set prn = Printers.Item(intCounter)
   If prn.ColorEnabled Then
    Exit For
   End If
 Next intCounter
 With ActiveDocument
  With .PrintSettings
   Set .Printer = prn
   .Separations.Enabled = True
   .Separations.InColor = True
   .ShowDialog
  End With
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations.Plates

Property **Plates** As SeparationPlates

Description

Member of PrintSeparations

The **Plates** property returns a read-only reference to the SeparationPlates collection.

VBA example

The following VBA example displays the number of items in the **SeparationPlates** collection.

```
Sub Test()
 Dim Seps As SeparationPlates
 With ActiveDocument
  With .PrintSettings
   Set Seps = .Separations.Plates
   .Separations.Enabled = True
   MsgBox "There are " & Seps.Count & " plates."
  End With
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations.PreserveOverprints

Property **PreserveOverprints** As Boolean

Description

Member of PrintSeparations

The **PreserveOverprints** property determines whether a document's overprint settings are maintained in the print job.

VBA example

The following VBA example creates two overlapping rectangles with uniform fills. It then enables separations, sets the **PreseveOverprints** property to **True**, and prints the document.

```
Sub Test()
 Dim s As Shape
 Dim doc As Document
 Set doc = CreateDocument
 With doc
  Set s = .ActiveLayer.CreateRectangle(2.110157, 9.605512, 5.69315, 6.94315, 0, 0, 0, 0)
  s.Fill.UniformColor.CMYKAssign 100, 0, 0, 0
  s.Outline.Type = cdrNoOutline
  Set s = .ActiveLayer.CreateRectangle(3.428898, 8.859055, 7.111417, 5.89811, 0, 0, 0, 0)
  s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
  s.Outline.Width = 0.33333
  s.Outline.Color.CMYKAssign 0, 100, 0, 0
  s.OverprintOutline = True
  With .PrintSettings.Separations
   .PreserveOverprints = True
   .Enabled = True
  End With
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations.Resolution

Property **Resolution** As Long

Description

Member of PrintSeparations

The **Resolution** property returns or specifies the resolution used for printing separations.

- For this property to be used, the AdvancedSettings property must be set to **True**.

VBA example

The following VBA example iterates through the SystemPrinters collection until it finds the specified printer. It then enables separations and sets advanced settings. The **Print** dialog box is then displayed.

```
Sub Test()
 Dim prn As Printer
 Dim intCounter As Integer
 For intCounter = 1 To Printers.Count
  Set prn = Printers.Item(intCounter)
   If prn.Name = "Device Independent PostScript File" Then
    Exit For
   End If
 Next intCounter
 With ActiveDocument
  With .PrintSettings
   Set .Printer = prn
   With .Separations
    .Enabled = True
    .AdvancedSettings = True
    .ScreenTechnology = "RT Screening - Lino 330"
    .Resolution = 1270
    .BasicScreen = "109"
   End With
   .ShowDialog
  End With
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations.ScreenTechnology

Property **ScreenTechnology** As String

Description

Member of PrintSeparations

The **ScreenTechnology** property returns or specifies the screening technology used for printing separations.

- For this property to be used, the AdvancedSettings property must be set to **True**.

VBA example

The following VBA example iterates through the **SystemPrinters** collection until it finds the specified printer. It enables separations and sets advanced settings. The **Print** dialog box is then displayed.

```
Sub Test()
 Dim prn As Printer
 Dim intCounter As Integer
 For intCounter = 1 To Printers.Count
  Set prn = Printers.Item(intCounter)
   If prn.Name = "Device Independent PostScript File" Then
    Exit For
   End If
 Next intCounter
 With ActiveDocument
  With .PrintSettings
   Set .Printer = prn
   With .Separations
    .Enabled = True
    .AdvancedSettings = True
    .ScreenTechnology = "RT Screening - Lino 330"
    .Resolution = 1270
    .BasicScreen = "109"
   End With
   .ShowDialog
  End With
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSeparations.SpotToCMYK

Property **SpotToCMYK** As Boolean

Description

Member of PrintSeparations

The **SpotToCMYK** property determines whether to convert spot colors to process colors.

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings

Properties Methods

Description

The **PrintSettings** class represents the settings of the CorelDRAW print engine.

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.Collate

Property **Collate** As Boolean

Description

Member of PrintSettings

The **Collate** property determines whether the pages of a document print together when several copies are printed.

- The number of copies to be printed is set by the Copies property.

VBA example

The following VBA example creates a new document containing two pages. It adds the page number to each page and then prints three collated copies of the document.

```
Sub Test()
 Dim doc As Document
 Dim page As page
 Set doc = CreateDocument
 With doc
  .AddPages 2
  For Each page In .Pages
   page.ActiveLayer.CreateArtisticText page.SizeWidth / 2, page.SizeHeight / 2, "This is page " & page.Index
  Next page
  .PrintSettings.Copies = 3
  .PrintSettings.Collate = True
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.Copies

Property **Copies** As Long

Description

Member of PrintSettings

The **Copies** property returns or specifies the number of copies of a document to be printed.

- You can ensure that the pages of a document print together by setting the Collate property.

VBA example

The following VBA example creates a new document containing two pages. It adds the page number to each page and then prints three collated copies of the document.

```
Sub Test()
 Dim doc As Document
 Dim page As page
 Set doc = CreateDocument
 With doc
  .AddPages 2
  For Each page In .Pages
   page.ActiveLayer.CreateArtisticText page.SizeWidth / 2, page.SizeHeight / 2, "This is page " & page.Index
  Next page
  .PrintSettings.Copies = 3
  .PrintSettings.Collate = True
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.FileMode

Property **FileMode** As PrnFileMode

Description

Member of PrintSettings

The **FileMode** property returns or specifies the output of pages or plates when printing to file.

VBA example

The following VBA example creates a new document containing three shapes and then prints the document to file.

```
Sub Test()
 Dim doc As Document
 Dim s As Shape
 Set doc = CreateDocument
 Set s = ActiveLayer.CreateRectangle(1.114882, 10.078268, 3.030787, 8.485827, 0, 0, 0, 0)
 Set s = ActiveLayer.CreateEllipse(4.075827, 7.540315, 6.016614, 5.375591, 90#, 90#, False)
 Set s = ActiveLayer.CreatePolygon(5.842445, 2.912283, 7.758343, 0.44898, 5, 1, 1, False, 50, 100)
 With doc
  With .PrintSettings
   .PrintToFile = True
   .ForMac = False
   .FileMode = prnSingleFile
   .FileName = "C:\Temp.prn"
  End With
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.FileName

Property **FileName** As String

Description

Member of PrintSettings

The **FileName** property returns or specifies the filename when printing to file.

VBA example

The following VBA example creates a new document containing three shapes and then prints the document to file.

```
Sub Test()
 Dim doc As Document
 Dim s As Shape
 Set doc = CreateDocument
 Set s = ActiveLayer.CreateRectangle(1.114882, 10.078268, 3.030787, 8.485827, 0, 0, 0, 0)
 Set s = ActiveLayer.CreateEllipse(4.075827, 7.540315, 6.016614, 5.375591, 90#, 90#, False)
 Set s = ActiveLayer.CreatePolygon(5.842445, 2.912283, 7.758343, 0.44898, 5, 1, 1, False, 50, 100)
 With doc
  With .PrintSettings
   .PrintToFile = True
   .ForMac = False
   .FileMode = prnSingleFile
   .FileName = "C:\Temp.prn"
  End With
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.ForMac

Property **ForMac** As Boolean

Description

Member of PrintSettings

The **ForMac** property determines, when printing to file, whether the file is readable on a Macintosh computer.

VBA example

The following VBA example creates a new document containing three shapes and then prints the document to file.

```
Sub Test()
 Dim doc As Document
 Dim s As Shape
 Set doc = CreateDocument
 Set s = ActiveLayer.CreateRectangle(1.114882, 10.078268, 3.030787, 8.485827, 0, 0, 0, 0)
 Set s = ActiveLayer.CreateEllipse(4.075827, 7.540315, 6.016614, 5.375591, 90#, 90#, False)
 Set s = ActiveLayer.CreatePolygon(5.842445, 2.912283, 7.758343, 0.44898, 5, 1, 1, False, 50, 100)
 With doc
  With .PrintSettings
   .PrintToFile = True
   .ForMac = False
   .FileMode = prnSingleFile
   .FileName = "C:\Temp.prn"
  End With
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.Layout

Property **Layout** As PrintLayout

Description

Member of PrintSettings

The **Layout** property specifies the layout settings for a document.

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.Load

Function **Load(***FileName As String***)** As Boolean

Description

Member of PrintSettings

The **Load** method applies a saved print style.

Parameter	Description
FileName	Specifies the full path and filename of the saved print style

VBA example

The following VBA example creates a new document containing four rectangles, each filled with a different uniform color. It then creates and saves a new print style. After reverting to the default print style, it prints the document. It then loads the saved print style and prints the document again.

```
Sub Test()
 Dim doc As Document
 Dim s As Shape
 Set doc = CreateDocument
 Set s = ActiveLayer.CreateRectangle(0.940709, 10.177795, 3.130315, 8.411181, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 0, 0, 100
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(1.139764, 5.201417, 3.553307, 3.111339, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(4.896929, 10.202677, 7.186063, 8.510709, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(5.245276, 5.450236, 7.683701, 3.285512, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 100, 0, 0, 0
 s.Outline.Type = cdrNoOutline
 With doc
  With .PrintSettings
   .Separations.Enabled = True
   .Copies = 5
   .Save "c:\Seps.prs"
   .Reset
  End With
  .PrintOut
  With .PrintSettings
   .Load "c:\Seps.prs"
  End With
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.Options

Property **Options** As PrintOptions

Description

Member of PrintSettings

The **Options** property returns a PrintOptions object, which specifies various print settings.

The **Options** property returns a read-only value.

VBA example

The following VBA example returns a reference to the **PrintOptions** object and displays the current color mode.

```
Sub Test()
 Dim DrawPrnOptions As PrintOptions
 Set DrawPrnOptions = ActiveDocument.PrintSettings.Options
 With DrawPrnOptions
  MsgBox "The current color mode is " & .ColorMode
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.PageMatchingMode

Property **PageMatchingMode** As PrnPageMatchingMode

Description

Member of PrintSettings

The **PageMatchingMode** property specifies the page-matching mode for the printer.

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.PageRange

Property **PageRange** As String

Description

Member of PrintSettings

The **PageRange** property specifies which pages to print.

- For this property to be used, the PrintRange property must be set to prnPageRange.

VBA example

The following VBA example creates a new document containing four pages with page numbers. It then prints pages two and four.

```
Sub Test()
 Dim doc As Document
 Dim page As page
 Dim DrwPrnSettings As PrintSettings
 Set doc = CreateDocument
 doc.AddPages 4
 For Each page In doc.Pages
  page.ActiveLayer.CreateArtisticText page.SizeWidth / 2, page.SizeHeight / 2, "This is page " & page.Index
 Next page
 Set DrwPrnSettings = ActiveDocument.PrintSettings
 With DrwPrnSettings
  .PrintRange = prnPageRange
  .PageRange = "2,4"
 End With
 doc.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.PageSet

Property **PageSet** As PrnPageSet

Description

Member of PrintSettings

The **PageSet** property specifies a subset of pages to be printed.

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.PaperHeight

Property **PaperHeight** As Double

Description

Member of PrintSettings

The **PaperHeight** property returns the paper height of a printer.

The **PaperHeight** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.PaperOrientation

Property **PaperOrientation** As PrnPaperOrientation

Description

Member of PrintSettings

The **PaperOrientation** property specifies the paper orientation of a printer.

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.PaperSize

Property **PaperSize** As PrnPaperSize

Description

Member of PrintSettings

The **PaperSize** property specifies the preset paper size of a printer.

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.PaperWidth

Property **PaperWidth** As Double

Description

Member of PrintSettings

The **PaperWidth** property returns the paper width of a printer.

The **PaperWidth** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.PostScript

Property **PostScript** As PrintPostScript

Description

Member of PrintSettings

The **PostScript** property returns a PrintPostScript object, which represents the PostScript print settings of the CorelDRAW print engine.

The **PostScript** property returns a read-only value.

VBA example

The following VBA example displays the PostScript level of the current PostScript device.

```
Sub Test()
 Dim DrwPostScriptSettings As PrintPostScript
 Set DrwPostScriptSettings = ActiveDocument.PrintSettings.PostScript
 With DrwPostScriptSettings
  MsgBox "The current printing device is a PostScript level " & _
    .Level & " device."
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.PPDFile

Property **PPDFile** As String

Description

Member of PrintSettings

The **PPDFile** property specifies the name of a PostScript Printer Description (PPD) file.

- For this property to be used, the UsePPD property must be set to **True**.

VBA example

The following VBA example prints the active document by using the specified PPD file.

```
Sub Test()
 With ActiveDocument.PrintSettings
  .UsePPD = True
  .PPDFile = "C:\WINNT4\system32\spool\drivers\w32x86\HPLJ5P_1.PPD"
 End With
 ActiveDocument.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.Prepress

Property **Prepress** As PrintPrepress

Description

Member of PrintSettings

The **Prepress** property returns a PrintPrepress object, which represents prepress settings.

The **Prepress** property returns a read-only value.

VBA example

The following VBA example prints the active document with page numbers displayed.

```
Sub Test()
 With ActiveDocument
  .PrintSettings.Prepress.PageNumbers = True
  .PrintSettings.Prepress.InfoWithinPage = True
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.PrintColorProof

Sub **PrintColorProof(**ProofSettings As Object**)**

Description

Member of PrintSettings

The **PrintColorProof** method prints out a color proof for the document without re-analyzing its contents.

Parameter	Description
ProofSettings	Specifies the color-proofing settings

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.Printer

Property **Printer** As Printer

Description

Member of PrintSettings

The **Printer** property returns a Printer value, which is reference to the current printer.

VBA example

The following VBA example displays the name of the current printer.

```
Sub Test()
 MsgBox "The current printer is:" & vbCr & _
  ActiveDocument.PrintSettings.Printer.Name
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.PrintOut

Sub **PrintOut()**

Description

Member of PrintSettings

The **PrintOut** method prints a document without re-analyzing its contents.

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.PrintRange

Property **PrintRange** As PrnPrintRange

Description

Member of PrintSettings

The **PrintRange** property specifies whether to print a full document, a page, a selection, or a range of pages.

- If you choose to print a range of pages, you can specify the pages to print by using the PrintSettings.PageRange property.

VBA example

The following VBA example creates a new document containing four pages with page numbers. It then prints pages two and four.

```
Sub Test()
 Dim doc As Document
 Dim page As page
 Dim DrwPrnSettings As PrintSettings
 Set doc = CreateDocument
 doc.AddPages 4
 For Each page In doc.Pages
  page.ActiveLayer.CreateArtisticText page.SizeWidth / 2, page.SizeHeight / 2, "This is page " & page.Index
 Next page
 Set DrwPrnSettings = ActiveDocument.PrintSettings
 With DrwPrnSettings
  .PrintRange = prnPageRange
  .PageRange = "2,4"
 End With
 doc.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.PrintToFile

Property **PrintToFile** As Boolean

Description

Member of PrintSettings

The **PrintToFile** property determines whether to print a document to file.

VBA example

The following VBA example creates a new document containing three shapes and then prints the document to file.

```
Sub Test()
 Dim doc As Document
 Dim s As Shape
 Set doc = CreateDocument
 Set s = ActiveLayer.CreateRectangle(1.114882, 10.078268, 3.030787, 8.485827, 0, 0, 0, 0)
 Set s = ActiveLayer.CreateEllipse(4.075827, 7.540315, 6.016614, 5.375591, 90#, 90#, False)
 Set s = ActiveLayer.CreatePolygon(5.842445, 2.912283, 7.758343, 0.44898, 5, 1, 1, False, 50, 100)
 With doc
  With .PrintSettings
   .PrintToFile = True
   .ForMac = False
   .FileMode = prnSingleFile
   .FileName = "C:\Temp.prn"
  End With
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.Reset

Sub **Reset()**

Description

Member of PrintSettings

The **Reset** method reverts to the default print style.

VBA example

The following VBA example creates a new document containing four rectangles, each filled with a different uniform color. It then creates and saves a new print style. After reverting to the default print style, it prints the document. It then loads the saved print style and prints the document again.

```
Sub Test()
 Dim doc As Document
 Dim s As Shape
 Set doc = CreateDocument
 Set s = ActiveLayer.CreateRectangle(0.940709, 10.177795, 3.130315, 8.411181, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 0, 0, 100
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(1.139764, 5.201417, 3.553307, 3.111339, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(4.896929, 10.202677, 7.186063, 8.510709, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(5.245276, 5.450236, 7.683701, 3.285512, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 100, 0, 0, 0
 s.Outline.Type = cdrNoOutline
 With doc
  With .PrintSettings
   .Separations.Enabled = True
   .Copies = 5
   .Save "c:\Seps.prs"
   .Reset
  End With
  .PrintOut
  With .PrintSettings
   .Load "c:\Seps.prs"
  End With
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.Save

Function **Save(***FileName As String***)** As Boolean

Description

Member of PrintSettings

The **Save** method saves a print style.

Parameter	Description
FileName	Specifies the full path and filename of the file containing the print settings

VBA example

The following VBA example creates a new document containing four rectangles, each filled with a different uniform color. It then creates and saves a new print style. After reverting to the default print style, it prints the document. It then loads the saved print style and prints the document again.

```
Sub Test()
 Dim doc As Document
 Dim s As Shape
 Set doc = CreateDocument
 Set s = ActiveLayer.CreateRectangle(0.940709, 10.177795, 3.130315, 8.411181, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 0, 0, 100
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(1.139764, 5.201417, 3.553307, 3.111339, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(4.896929, 10.202677, 7.186063, 8.510709, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(5.245276, 5.450236, 7.683701, 3.285512, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 100, 0, 0, 0
 s.Outline.Type = cdrNoOutline
 With doc
  With .PrintSettings
   .Separations.Enabled = True
   .Copies = 5
   .Save "c:\Seps.prs"
   .Reset
  End With
  .PrintOut
  With .PrintSettings
   .Load "c:\Seps.prs"
  End With
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.SelectPrinter

Sub **SelectPrinter(***Name As String***)**

Description

Member of PrintSettings

The **SelectPrinter** method selects the destination printer by name.

Parameter	Description
Name	Specifies the name of the destination printer

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.Separations

Property **Separations** As PrintSeparations

Description

Member of PrintSettings

The **Separations** property returns a PrintSeparations object.

The **Separations** property returns a read-only value.

VBA example

The following VBA example creates a new document. Four rectangles, each filled with a different uniform color (cyan, yellow, magenta, or black) are created, and then separations are printed.

```
Sub Test()
 Dim doc As Document
 Dim s As Shape
 Set doc = CreateDocument
 Set s = ActiveLayer.CreateRectangle(0.940709, 10.177795, 3.130315, 8.411181, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 0, 0, 100
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(1.139764, 5.201417, 3.553307, 3.111339, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(4.896929, 10.202677, 7.186063, 8.510709, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 0, 100, 0, 0
 s.Outline.Type = cdrNoOutline
 Set s = ActiveLayer.CreateRectangle(5.245276, 5.450236, 7.683701, 3.285512, 0, 0, 0, 0)
 s.Fill.UniformColor.CMYKAssign 100, 0, 0, 0
 s.Outline.Type = cdrNoOutline
 With doc
  .PrintSettings.Separations.Enabled = True
  .PrintOut
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.SetCustomPaperSize

Sub **SetCustomPaperSize(***Width As Double***,** *Height As Double***,** Orientation As PrnPaperOrientation**)**

Description

Member of PrintSettings

The **SetCustomPaperSize** method specifies a custom paper size for a printer.

Parameter	Description
Width	Specifies the width of the paper
Height	Specifies the height of the paper
Orientation	Specifies the orientation of the paper

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.SetPaperSize

Sub **SetPaperSize(**PaperSize As PrnPaperSize**,** Orientation As PrnPaperOrientation**)**

Description

Member of PrintSettings

The **SetPaperSize** method selects a preset paper size and orientation for a printer.

Parameter	Description
PaperSize	Selects the paper size
Orientation	Selects the orientation

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.ShowDialog

Function **ShowDialog()** As Boolean

Description

Member of PrintSettings

The **ShowDialog** method displays the **Print** dialog box.

VBA example

The following VBA example displays the **Print** dialog box for the first file in the specified folder and then prints the CorelDRAW (CDR) files contained in that folder.

```
Sub Test()
 Dim ldDocument As Document
 Dim lcFolder As String
 Dim lcFileName As String
 Dim lcFullName As String
 Dim Prn As CorelDRAW.Printer
 Dim nCopies As Long
 Dim bFirst As Boolean
 lcFolder = "k:\cdrs\"
 lcFileName$ = Dir(lcFolder & "*.cdr")
 bFirst = True
 While lcFileName$ <> ""
  lcFullName = lcFolder & lcFileName
  Set ldDocument = laCorel.OpenDocument(lcFullName)
  With ldDocument.PrintSettings
   If bFirst Then
    If Not .ShowDialog Then Exit Sub
    Set Prn = .Printer
    nCopies = .Copies
    bFirst = False
   Else
    Set .Printer = Prn
    .Copies = nCopies
   End If
  End With
  ldDocument.PrintOut
  ldDocument.Close
  lcFileName$ = Dir()
 Wend
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.Trapping

Property **Trapping** As PrintTrapping

Description

Member of PrintSettings

The **Trapping** property returns a PrintTrapping object.

The **Trapping** property returns a read-only value.

VBA example

The following VBA example displays the **Print** dialog box followed by a message box containing the current trapping width.

```
Sub Test()
 With ActiveDocument.PrintSettings
  .PostScript.Level = prnPSLevel3
  .Separations.Enabled = False
  .Trapping.Enabled = True
  .ShowDialog
  MsgBox "The current trapping width is " & Round((.Trapping.Width / 254000) * 72, 1) & " pt"
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintSettings.UsePPD

Property **UsePPD** As Boolean

Description

Member of PrintSettings

The **UsePPD** property determines whether a PostScript Printer Description (PPD) file is used.

- The PrintSettings.PPDFile property can be used to specify the name of the PPD file.

VBA example

The following VBA example prints the active document by using the specified PPD file.

```
Sub Test()
 With ActiveDocument.PrintSettings
  .UsePPD = True
  .PPDFile = "C:\WINNT4\system32\spool\drivers\w32x86\HPLJ5P_1.PPD"
 End With
 ActiveDocument.PrintOut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintTrapping

Properties

Description

The **PrintTrapping** class represents the color-trapping settings of the CorelDRAW print engine.

Copyright 2014 Corel Corporation. All rights reserved.

PrintTrapping.BlackColorLimit

Property **BlackColorLimit** As Long

Description

Member of PrintTrapping

The **BlackColorLimit** property sets the threshold at which process black is considered pure black for print trapping.

VBA example

The following VBA example displays the values of properties that represent the thresholds of print trapping.

```
Sub Test()
 Dim s As String
 With ActiveDocument.PrintSettings.Trapping
  s = "Black Color Limit: " & .BlackColorLimit & vbCr
  s = s & "Black Density Limit: " & .BlackDensityLimit & vbCr
  s = s & "Sliding Trap Limit: " & .SlidingTrapLimit & vbCr
  s = s & "Step Limit: " & .StepLimit
 End With
 MsgBox s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintTrapping.BlackDensityLimit

Property **BlackDensityLimit** As Double

Description

Member of PrintTrapping

The **BlackDensityLimit** property sets the neutral density value for the black ink in print trapping.

VBA example

The following VBA example displays the values of properties that represent the thresholds of print trapping.

```
Sub Test()
 Dim s As String
 With ActiveDocument.PrintSettings.Trapping
  s = "Black Color Limit: " & .BlackColorLimit & vbCr
  s = s & "Black Density Limit: " & .BlackDensityLimit & vbCr
  s = s & "Sliding Trap Limit: " & .SlidingTrapLimit & vbCr
  s = s & "Step Limit: " & .StepLimit
 End With
 MsgBox s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintTrapping.BlackWidth

Property **BlackWidth** As Double

Description

Member of PrintTrapping

The **BlackWidth** property sets the black trap width when trapping to black.

VBA example

The following VBA example sets the PostScript.Level property to level **3**, changes both the trapping and the black widths, and then displays the **Print** dialog box.

```
Sub Test()
 Dim s As String
 With ActiveDocument.PrintSettings
  .PostScript.Level = prnPSLevel3
  With .Trapping
   .BlackWidth = 0.6 / 72 * 254000
   .Width = 0.35 / 72 * 254000
  End With
  .ShowDialog
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintTrapping.ColorScaling

Property **ColorScaling** As Long

Description

Member of PrintTrapping

The **ColorScaling** property sets the amount by which the ink color in a trap decreases.

VBA example

The following VBA example displays the current value for color scaling.

```
Sub Test()
 With ActiveDocument.PrintSettings.Trapping
  MsgBox "The current value for color scaling is: " & .ColorScaling
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintTrapping.Enabled

Property **Enabled** As Boolean

Description

Member of PrintTrapping

The **Enabled** property determines whether print trapping is turned on.

VBA example

The following VBA example displays the current status of print trapping and displays the **Print** dialog box.

```
Sub Test()
 With ActiveDocument.PrintSettings
  With .Trapping
   If .Enabled = True Then
    MsgBox "Print trapping is currently enabled"
   Else
    MsgBox "Print trapping is currently disabled"
   End If
  End With
  .ShowDialog
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintTrapping.ImageTrap

Property **ImageTrap** As PrnImageTrap

Description

Member of PrintTrapping

The **ImageTrap** property sets the placement of a color trap.

VBA example

The following VBA example sets the placement of the trap to **Choke**.

```
Sub Test()
 With ActiveDocument.PrintSettings.Trapping
  .ImageTrap = prnTrapChoke
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintTrapping.InternalImageTrapping

Property **InternalImageTrapping** As Boolean

Description

Member of PrintTrapping

The **InternalImageTrapping** property applies a color trap within an image.

VBA example

The following VBA example enables image trapping.

```
Sub Test()
 With ActiveDocument.PrintSettings
  With .Trapping
   .InternalImageTrapping = False
  End With
  .ShowDialog
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintTrapping.Layers

Property **Layers** As TrapLayers

Description

Member of PrintTrapping

The **Layers** property returns a TrapLayers collection.

The **Layers** property returns a read-only value.

VBA example

The following VBA example displays the number of items in the **TrapLayers** collection.

```
Sub Test()
 With ActiveDocument.PrintSettings.Trapping
  MsgBox .Layers.Count
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintTrapping.MinResolution

Property **MinResolution** As Long

Description

Member of PrintTrapping

The **MinResolution** property sets the minimum resolution of an image to be considered for trapping.

VBA example

The following VBA example displays the current minimum bitmap resolution.

```
Sub Test()
 With ActiveDocument.PrintSettings
  With .Trapping
   MsgBox .MinResolution, vbOKOnly, "MinResolution"
  End With
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintTrapping.ObjectsToImage

Property **ObjectsToImage** As Boolean

Description

Member of PrintTrapping

The **ObjectsToImage** property determines whether vector objects are trapped to images.

VBA example

The following VBA example stores the current setting of objects-to-image trapping. It displays a dialog box indicating that this option is enabled and then restores the previous setting.

```
Sub Test()
 Dim bObjectsToImage As Boolean
 With ActiveDocument.PrintSettings
  With .Trapping
   bObjectsToImage = .ObjectsToImage
   .ObjectsToImage = True
  End With
  .ShowDialog
  .Trapping.ObjectsToImage = bObjectsToImage
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintTrapping.SlidingTrapLimit

Property **SlidingTrapLimit** As Long

Description

Member of PrintTrapping

The **SlidingTrapLimit** property sets the sliding-trap threshold for print trapping.

VBA example

The following VBA example displays the values of properties that represent the thresholds of print trapping.

```
Sub Test()
 Dim s As String
 With ActiveDocument.PrintSettings.Trapping
  s = "Black Color Limit: " & .BlackColorLimit & vbCr
  s = s & "Black Density Limit: " & .BlackDensityLimit & vbCr
  s = s & "Sliding Trap Limit: " & .SlidingTrapLimit & vbCr
  s = s & "Step Limit: " & .StepLimit
 End With
 MsgBox s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintTrapping.StepLimit

Property **StepLimit** As Long

Description

Member of PrintTrapping

The **StepLimit** property sets the threshold between color variations for print trapping.

VBA example

The following VBA example displays the values of properties that represent the thresholds of print trapping.

```
Sub Test()
 Dim s As String
 With ActiveDocument.PrintSettings.Trapping
  s = "Black Color Limit: " & .BlackColorLimit & vbCr
  s = s & "Black Density Limit: " & .BlackDensityLimit & vbCr
  s = s & "Sliding Trap Limit: " & .SlidingTrapLimit & vbCr
  s = s & "Step Limit: " & .StepLimit
 End With
 MsgBox s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PrintTrapping.TrapMonoBitmaps

Property **TrapMonoBitmaps** As Boolean

Description

Member of PrintTrapping

The **TrapMonoBitmaps** property specifies whether monochrome black-and-white bitmaps are trapped.

Copyright 2014 Corel Corporation. All rights reserved.

PrintTrapping.Width

Property **Width** As Double

Description

Member of PrintTrapping

The **Width** property sets the amount by which one color spreads into another for print trapping.

VBA example

The following VBA example sets the PostScript.Level property to level **3**, changes both the trapping and the black widths, and then displays the **Print** dialog box.

```
Sub Test()
 Dim s As String
 With ActiveDocument.PrintSettings
  .PostScript.Level = prnPSLevel3
  With .Trapping
   .BlackWidth = 0.6 / 72 * 254000
   .Width = 0.35 / 72 * 254000
  End With
  .ShowDialog
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

prnBlack

The following enumerations have this constant:

- PrnPlateType

Copyright 2014 Corel Corporation. All rights reserved.

PrnColorMode

The **PrnColorMode** enumeration has the following constants:

Constant	Value	Description
prnModeFullColor	**0**	Specifies full-color printing
prnModeGrayscale	**1**	Specifies grayscale printing
prnModeBlack	**2**	Specifies black printing

Copyright 2014 Corel Corporation. All rights reserved.

prnCorel

The following enumerations have this constant:

- PrnRegistrationStyle

Copyright 2014 Corel Corporation. All rights reserved.

prnCurrentPage

The following enumerations have this constant:

- PrnPrintRange

Copyright 2014 Corel Corporation. All rights reserved.

prnCyan

The following enumerations have this constant:

- PrnPlateType

Copyright 2014 Corel Corporation. All rights reserved.

PrnFileMode

The **PrnFileMode** enumeration has the following constants:

Constant	Value	Description
prnSingleFile	**0**	Specifies single-file printing
prnSeparatePages	**1**	Specifies separate-page printing
prnSeparatePlates	**2**	Specifies separate-plate printing

Copyright 2014 Corel Corporation. All rights reserved.

prnGreen

The following enumerations have this constant:

- PrnPlateType

Copyright 2014 Corel Corporation. All rights reserved.

prnHalfInverted

The following enumerations have this constant:

- PrnRegistrationStyle

Copyright 2014 Corel Corporation. All rights reserved.

PrnImageTrap

The **PrnImageType** enumeration has the following constants:

Constant	Value	Description
prnTrapNormal	**0**	Specifies normal image trapping
prnTrapSpread	**1**	Specifies spread image trapping
prnTrapChoke	**2**	Specifies choke image trapping
prnTrapCenter	**3**	Specifies center image trapping

Copyright 2014 Corel Corporation. All rights reserved.

prnLayerNormal

The following enumerations have this constant:

- PrnTrapType

Copyright 2014 Corel Corporation. All rights reserved.

prnLayerOpaque

The following enumerations have this constant:

- PrnTrapType

Copyright 2014 Corel Corporation. All rights reserved.

prnLayerOpaqueIgnore

The following enumerations have this constant:

- PrnTrapType

Copyright 2014 Corel Corporation. All rights reserved.

prnLayerTransparent

The following enumerations have this constant:

- PrnTrapType

Copyright 2014 Corel Corporation. All rights reserved.

prnLong

The following enumerations have this constant:

- PrnRegistrationStyle

Copyright 2014 Corel Corporation. All rights reserved.

prnMagenta

The following enumerations have this constant:

- PrnPlateType

Copyright 2014 Corel Corporation. All rights reserved.

prnModeBlack

The following enumerations have this constant:

- PrnColorMode

Copyright 2014 Corel Corporation. All rights reserved.

prnModeFullColor

The following enumerations have this constant:

- PrnColorMode

Copyright 2014 Corel Corporation. All rights reserved.

prnModeGrayscale

The following enumerations have this constant:

- PrnColorMode

Copyright 2014 Corel Corporation. All rights reserved.

prnObjectsCMYK

The following enumerations have this constant:

- PrnObjectsColorMode

Copyright 2014 Corel Corporation. All rights reserved.

PrnObjectsColorMode

The **PrnObjectsColorMode** enumeration has the following constants:

Constant	Value	Description
prnObjectsCMYK	**0**	Specifies CMYK color mode
prnObjectsRGB	**1**	Specifies RGB color mode
prnObjectsGrayscale	**2**	Specifies grayscale color mode
prnObjectsNative	**3**	Specifies native color mode

Copyright 2014 Corel Corporation. All rights reserved.

prnObjectsGrayscale

The following enumerations have this constant:

- PrnObjectsColorMode

Copyright 2014 Corel Corporation. All rights reserved.

prnObjectsNative

The following enumerations have this constant:

- PrnObjectsColorMode

Copyright 2014 Corel Corporation. All rights reserved.

prnObjectsRGB

The following enumerations have this constant:

- PrnObjectsColorMode

Copyright 2014 Corel Corporation. All rights reserved.

prnOrange

The following enumerations have this constant:

- PrnPlateType

Copyright 2014 Corel Corporation. All rights reserved.

PrnPageMatchingMode

The **PrnPageMatchingMode** enumeration has the following constants:

Constant	Value	Description
prnPageMatchPrinterDefault	**0**	Matches the page to the printer defaults
prnPageMatchOrientation	**1**	Matches the page to orientation
prnPageMatchSizeAndOrientation	**2**	Matches the page to size and orientation

Copyright 2014 Corel Corporation. All rights reserved.

prnPageMatchOrientation

The following enumerations have this constant:

- PrnPageMatchingMode

Copyright 2014 Corel Corporation. All rights reserved.

prnPageMatchPrinterDefault

The following enumerations have this constant:

- PrnPageMatchingMode

Copyright 2014 Corel Corporation. All rights reserved.

prnPageMatchSizeAndOrientation

The following enumerations have this constant:

- PrnPageMatchingMode

Copyright 2014 Corel Corporation. All rights reserved.

prnPageRange

The following enumerations have this constant:

- PrnPrintRange

Copyright 2014 Corel Corporation. All rights reserved.

PrnPageSet

The **PrnPageSet** enumeration has the following constants:

Constant	Value	Description
prnPageSetAll	**0**	Specifies all pages
prnPageSetOdd	**1**	Specifies odd pages
prnPageSetEven	**2**	Specifies even pages
prnPageSetLeft	**3**	Specifies left pages
prnPageSetRight	**4**	Specifies right pages

Copyright 2014 Corel Corporation. All rights reserved.

prnPageSetAll

The following enumerations have this constant:

- PrnPageSet

Copyright 2014 Corel Corporation. All rights reserved.

prnPageSetEven

The following enumerations have this constant:

- PrnPageSet

Copyright 2014 Corel Corporation. All rights reserved.

prnPageSetLeft

The following enumerations have this constant:

- PrnPageSet

Copyright 2014 Corel Corporation. All rights reserved.

prnPageSetOdd

The following enumerations have this constant:

- PrnPrintRange

Copyright 2014 Corel Corporation. All rights reserved.

prnPageSetRight

The following enumerations have this constant:

- PrnPageSet

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperLandscape

The following enumerations have this constant:

- PrnPaperOrientation

Copyright 2014 Corel Corporation. All rights reserved.

PrnPaperOrientation

The **PrnPaperOrientation** enumeration has the following constants:

Constant	Value	Description
prnPaperPortrait	**1**	Specifies portrait orientation
prnPaperLandscape	**2**	Specifies landscape orientation
prnPaperRotatedLandscape	**3**	Specifies rotated-landscape orientation

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperPortrait

The following enumerations have this constant:

- PrnPaperOrientation

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperRotatedLandscape

The following enumerations have this constant:

- PrnPaperOrientation

Copyright 2014 Corel Corporation. All rights reserved.

PrnPaperSize

The **PrnPaperSize** enumeration has the following constants:

Constant	Value	Description
prnPaperSizeLetter	**1**	Specifies Letter size 8 1/2 × 11 inches
prnPaperSizeLetterSmall	**2**	Specifies Small Letter size 8 1/2 × 11 inches
prnPaperSizeTabloid	**3**	Specifies Tabloid size 11 × 17 inches
prnPaperSizeLedger	**4**	Specifies Ledger size 17 × 11 inches
prnPaperSizeLegal	**5**	Specifies Legal size 8 1/2 × 14 inches
prnPaperSizeStatement	**6**	Specifies Statement size 5 1/2 × 8 1/2 inches
prnPaperSizeExecutive	**7**	Specifies Executive size 7 1/4 × 10 1/2 inches
prnPaperSizeA3	**8**	Specifies A3 size 297 × 420 mm
prnPaperSizeA4	**9**	Specifies A4 size 210 × 297 mm
prnPaperSizeA4Small	**10**	Specifies A4 Small size 210 × 297 mm
prnPaperSizeA5	**11**	Specifies A5 size 148 × 210 mm
prnPaperSizeB4	**12**	Specifies B4 (JIS) size 250 × 354 mm
prnPaperSizeB5	**13**	Specifies B5 (JIS) size 182 × 257 mm
prnPaperSizeFolio	**14**	Specifies Folio size 8 1/2 × 13 inches
prnPaperSizeQuarto	**15**	Specifies Quarto size 215 × 275 mm
prnPaperSize10x14	**16**	Specifies size of 10 × 14 inches
prnPaperSize11x17	**17**	Specifies size of 11 × 17 inches
prnPaperSizeNote	**18**	Specifies Note size

		8 1/2 × 11 inches
prnPaperSizeEnv9	**19**	Specifies Envelope #9 size 3 7/8 × 8 7/8 inches
prnPaperSizeEnv10	**20**	Specifies Envelope #10 size 4 1/8 × 9 1/2 inches
prnPaperSizeEnv11	**21**	Specifies Envelope #11 size 4 1/2 × 10 3/8 inches
prnPaperSizeEnv12	**22**	Specifies Envelope #12 size 4.75 × 11 in inches
prnPaperSizeEnv14	**23**	Specifies Envelope #14 size 5 × 11 1/2 inches
prnPaperSizeCSheet	**24**	Specifies C-size sheet 17 × 22 inches
prnPaperSizeDSheet	**25**	Specifies D-size sheet 22 × 34 inches
prnPaperSizeESheet	**26**	Specifies E-size sheet 34 × 44 inches
prnPaperSizeEnvDL	**27**	Specifies Envelope size DL 110 × 220 mm
prnPaperSizeEnvC5	**28**	Specifies Envelope C5 size 162 × 229 mm
prnPaperSizeEnvC3	**29**	Specifies Envelope C3 size 324 × 458 mm
prnPaperSizeEnvC4	**30**	Specifies Envelope C4 size 229 × 324 mm
prnPaperSizeEnvC6	**31**	Specifies Envelope C6 size 114 × 162 mm
prnPaperSizeEnvC65	**32**	Specifies Envelope C65 size 114 × 229 mm
prnPaperSizeISOB4	**33**	Specifies B4 (ISO) size 250 × 353 mm
prnPaperSizeISOB5	**34**	Specifies B5 (ISO) size 176 × 250 mm
prnPaperSizeISOB6	**35**	Specifies B6 (ISO) B6 size 176 × 125 mm
prnPaperSizeEnvItaly	**36**	Specifies Italian Standard Envelope size 110 × 230 mm
prnPaperSizeEnvMonarch	**37**	Specifies Envelope Monarch size 3.875 × 7.5 inches

prnPaperSizeEnvPersonal	**38**	Specifies 6 3/4 Envelope size 3 5/8 × 6 1/2 inches
prnPaperSizeFanfoldUS	**39**	Specifies US Standard Fanfold size 14 7/8 × 11 inches
prnPaperSizeFanfoldGerman	**40**	Specifies German Standard Fanfold size 8 1/2 × 12 inches
prnPaperSizeFanfoldLglGerman	**41**	Specifies German Legal Fanfold size 8 1/2 × 13 inches
prnPaperSizeJapanesePostcard	**43**	Specifies Japanese Postcard size 100 × 148 mm
prnPaperSize9x11	**44**	Specifies size of 9 × 11 inches
prnPaperSize10x11	**45**	Specifies size of 10 × 11 inches
prnPaperSize15x11	**46**	Specifies size of 15 × 11 inches
prnPaperSizeEnvInvite	**47**	Specifies Invitation Envelope size 220 × 220 mm
prnPaperSizeLetterExtra	**50**	Specifies Letter Extra size 9.5 × 12 inches
prnPaperSizeLegalExtra	**51**	Specifies Legal Extra size 9.5 × 15 inches
prnPaperSizeTabloidExtra	**52**	Specifies Tabloid Extra size 12 × 18 inches
prnPaperSizeA4Extra	**53**	Specifies A4 Extra size 9.27 × 12.69 inches
prnPaperSizeLetterTransverse	**54**	Specifies Letter Transverse size 8.5 × 11 inches
prnPaperSizeA4Transverse	**55**	Specifies A4 Transverse size 210 × 297 mm
prnPaperSizeLetterExtraTransverse	**56**	Specifies Letter Extra Transverse size 9.5 × 12 inches
prnPaperSizeAPlus	**57**	Specifies SuperA/SuperA/A4 size 227 × 356 mm
prnPaperSizeBPlus	**58**	Specifies SuperB/SuperB/A3 size 305 × 487 mm
prnPaperSizeLetterPlus	**59**	Specifies Letter Plus size 8.5 × 12.69 inches
prnPaperSizeA4Plus	**60**	Specifies A4 Plus size 210 × 330 mm

prnPaperSizeA5Transverse	**61**	Specifies A5 Transverse size 148 × 210 mm
prnPaperSizeB5Transverse	**62**	Specifies B5 (JIS) Transverse size 182 × 257 mm
prnPaperSizeA3Extra	**63**	Specifies A3 Extra size 322 × 445 mm
prnPaperSizeA5Extra	**64**	Specifies A5 Extra size 174 × 235 mm
prnPaperSizeB5Extra	**65**	Specifies B5 (ISO) Extra size 201 × 276 mm
prnPaperSizeA2	**66**	Specifies A2 size 420 × 594 mm
prnPaperSizeA3Transverse	**67**	Specifies A3 Transverse size 297 × 420 mm
prnPaperSizeA3ExtraTransverse	**68**	Specifies A3 Extra Transverse size 322 × 445 mm
prnPaperSizeJapaneseDblPostcard	**69**	Specifies Japanese Double Postcard size 200 × 148 mm
prnPaperSizeA6	**70**	Specifies A6 size 105 × 148 mm
prnPaperSizeLetterRotated	**75**	Specifies Letter Rotated size 11 × 8.5 inches
prnPaperSizeA3Rotated	**76**	Specifies A3 Rotated size 420 × 297 mm
prnPaperSizeA4Rotated	**77**	Specifies A4 Rotated size 297 × 210 mm
prnPaperSizeA5Rotated	**78**	Specifies A5 Rotated size 210 × 148 mm
prnPaperSizeB4JISRotated	**79**	Specifies B4 (JIS) Rotated size 364 × 257 mm
prnPaperSizeB5JISRotated	**80**	Specifies B5 (JIS) Rotated size 257 × 182 mm
prnPaperSizeJapanesePostcardRotated	**81**	Specifies Japanese Postcard Rotated size 148 × 100 mm
prnPaperSizeJapaneseDlbPostcardRotated	**82**	Specifies Double Japanese Postcard Rotated size 148 × 200 mm
prnPaperSizeA6Rotated	**83**	Specifies A6 Rotated size 148 × 105 mm
prnPaperSizeB6JIS	**88**	Specifies B6 (JIS) size

		128 × 182 mm
prnPaperSizeB6JISRotated	**89**	Specifies B6 (JIS) Rotated size 182 × 128 mm
prnPaperSize12x11	**90**	Specifies size of 12 × 11 inches
prnPaperSizeP16K	**93**	Specifies PRC 16K size 146 × 215 mm
prnPaperSizeP32K	**94**	Specifies PRC 32K size 97 × 151 mm
prnPaperSizeP32KBig	**95**	Specifies PRC 32K(Big) size 97 × 151 mm
prnPaperSizePEnv1	**96**	Specifies PRC Envelope #1 size 102 × 165 mm
prnPaperSizePEnv2	**97**	Specifies PRC Envelope #2 size 102 × 176 mm
prnPaperSizePEnv3	**98**	Specifies PRC Envelope #3 size 125 × 176 mm
prnPaperSizePEnv4	**99**	Specifies PRC Envelope #4 size 110 × 208 mm
prnPaperSizePEnv5	**100**	Specifies PRC Envelope #5 size 110 × 220 mm
prnPaperSizePEnv6	**101**	Specifies PRC Envelope #6 size 120 × 230 mm
prnPaperSizePEnv7	**102**	Specifies PRC Envelope #7 size 160 × 230 mm
prnPaperSizePEnv8	**103**	Specifies PRC Envelope #8 size 120 × 309 mm
prnPaperSizePEnv9	**104**	Specifies PRC Envelope #9 size 229 × 324 mm
prnPaperSizePEnv10	**105**	Specifies PRC Envelope #10 size 324 × 458 mm
prnPaperSizeP16KRotated	**106**	Specifies PRC 16K Rotated size 215 × 146 mm
prnPaperSizeP32KRotated	**107**	Specifies PRC 32K Rotated size 151 × 97 mm
prnPaperSizeP32KBigRotated	**108**	Specifies PRC 32K (Big) Rotated size 151 × 97 mm
prnPaperSizePEnv1Rotated	**109**	Specifies PRC Envelope #1 Rotated size 165 × 102 mm

prnPaperSizePEnv2Rotated	**110**	Specifies PRC Envelope #2 Rotated size 176 × 102 mm
prnPaperSizePEnv3Rotated	**111**	Specifies PRC Envelope #3 Rotated size 176 × 125 mm
prnPaperSizePEnv4Rotated	**112**	Specifies PRC Envelope #4 Rotated size 208 × 110 mm
prnPaperSizePEnv5Rotated	**113**	Specifies PRC Envelope #5 Rotated size 220 × 110 mm
prnPaperSizePEnv6Rotated	**114**	Specifies PRC Envelope #6 Rotated size 230 × 120 mm
prnPaperSizePEnv7Rotated	**115**	Specifies PRC Envelope #7 Rotated size 230 × 160 mm
prnPaperSizePEnv8Rotated	**116**	Specifies PRC Envelope #8 Rotated size 309 × 120 mm
prnPaperSizePEnv9Rotated	**117**	Specifies PRC Envelope #9 Rotated size 324 × 229 mm
prnPaperSizePEnv10Rotated	**118**	Specifies PRC Envelope #10 Rotated size 458 × 324 mm

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSize9x11

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSize10x11

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSize10x14

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSize11x17

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSize12x11

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSize15x11

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA2

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA3

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA3Extra

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA3ExtraTransverse

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA3Rotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA3Transverse

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA4

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA4Extra

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA4Plus

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA4Rotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA4Small

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA4Transverse

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA5

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA5Extra

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA5Rotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA5Transverse

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA6

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeA6Rotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeAPlus

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeB4

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeB4JISRotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeB5

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeB5Extra

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeB5JISRotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeB5Transverse

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeB6JIS

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeB6JISRotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeBPlus

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeCSheet

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeDSheet

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeEnv9

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeEnv10

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeEnv11

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeEnv12

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeEnv14

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeEnvC3

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeEnvC4

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeEnvC5

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeEnvC6

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeEnvC65

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeEnvDL

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeEnvInvite

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeEnvItaly

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeEnvMonarch

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeEnvPersonal

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeESheet

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeExecutive

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeFanfoldGerman

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeFanfoldLglGerman

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeFanfoldUS

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeFolio

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeISOB4

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeISOB5

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeISOB6

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeJapaneseDblPostcard

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeJapaneseDlbPostcardRotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeJapanesePostcard

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeJapanesePostcardRotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeLedger

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeLegal

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeLegalExtra

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeLetter

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeLetterExtra

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeLetterExtraTransverse

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeLetterPlus

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeLetterRotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeLetterSmall

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeLetterTransverse

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeNote

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeP16K

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeP16KRotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeP32K

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeP32KBig

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeP32KBigRotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeP32KRotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv1

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv1Rotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv2

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv2Rotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv3

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv3Rotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv4

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv4Rotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv5

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv5Rotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv6

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv6Rotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv7

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv7Rotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv8

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv8Rotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv9

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv9Rotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv10

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizePEnv10Rotated

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeQuarto

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeStatement

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeTabloid

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPaperSizeTabloidExtra

The following enumerations have this constant:

- PrnPaperSize

Copyright 2014 Corel Corporation. All rights reserved.

prnPDFFullScreen

The following enumerations have this constant:

- PrnPDFStartup

Copyright 2014 Corel Corporation. All rights reserved.

prnPDFOutlines

The following enumerations have this constant:

- PrnPDFStartup

Copyright 2014 Corel Corporation. All rights reserved.

prnPDFPageOnly

The following enumerations have this constant:

- PrnPDFStartup

Copyright 2014 Corel Corporation. All rights reserved.

PrnPDFStartup

The **PrnPDFStartup** enumeration has the following constants:

Constant	Value	Description
prnPDFFullScreen	**0**	Specifies full-screen display at startup
prnPDFPageOnly	**1**	Specifies page-only display at startup
prnPDFThumbnails	**2**	Specifies thumbnail display at startup
prnPDFOutlines	**3**	Specifies outline display at startup

Copyright 2014 Corel Corporation. All rights reserved.

prnPDFThumbnails

The following enumerations have this constant:

- PrnPDFStartup

Copyright 2014 Corel Corporation. All rights reserved.

prnPlaceAsInDocument

The following enumerations have this constant:

- PrnPlaceType

Copyright 2014 Corel Corporation. All rights reserved.

prnPlaceCenterBottom

The following enumerations have this constant:

- PrnPlaceType

Copyright 2014 Corel Corporation. All rights reserved.

prnPlaceCenterLeft

The following enumerations have this constant:

- PrnPlaceType

Copyright 2014 Corel Corporation. All rights reserved.

prnPlaceCenterPage

The following enumerations have this constant:

- PrnPlaceType

Copyright 2014 Corel Corporation. All rights reserved.

prnPlaceCenterRight

The following enumerations have this constant:

- PrnPlaceType

Copyright 2014 Corel Corporation. All rights reserved.

prnPlaceCenterTop

The following enumerations have this constant:

- PrnPlaceType

Copyright 2014 Corel Corporation. All rights reserved.

prnPlaceCustom

The following enumerations have this constant:

- PrnPlaceType

Copyright 2014 Corel Corporation. All rights reserved.

prnPlaceFitToPage

The following enumerations have this constant:

- PrnPlaceType

Copyright 2014 Corel Corporation. All rights reserved.

prnPlaceLeftBottom

The following enumerations have this constant:

- PrnPlaceType

Copyright 2014 Corel Corporation. All rights reserved.

prnPlaceLeftTop

The following enumerations have this constant:

- PrnPlaceType

Copyright 2014 Corel Corporation. All rights reserved.

prnPlaceRightBottom

The following enumerations have this constant:

- PrnPlaceType

Copyright 2014 Corel Corporation. All rights reserved.

prnPlaceRightTop

The following enumerations have this constant:

- PrnPlaceType

Copyright 2014 Corel Corporation. All rights reserved.

PrnPlaceType

The **PrnPlaceType** enumeration has the following constants:

Constant	Value	Description
prnPlaceAsInDocument	**0**	Specifies to set as in the document
prnPlaceFitToPage	**1**	Specifies to fit to the page
prnPlaceCenterPage	**2**	Specifies page center
prnPlaceCenterTop	**3**	Specifies top center
prnPlaceCenterLeft	**4**	Specifies left center
prnPlaceCenterRight	**5**	Specifies right center
prnPlaceCenterBottom	**6**	Specifies bottom center
prnPlaceLeftTop	**7**	Specifies top left
prnPlaceRightTop	**8**	Specifies top right
prnPlaceLeftBottom	**9**	Specifies bottom left
prnPlaceRightBottom	**10**	Specifies bottom right
prnPlaceCustom	**11**	Specifies custom

Copyright 2014 Corel Corporation. All rights reserved.

PrnPlateType

The **PrnPlateType** enumeration has the following constants:

Constant	Value	Description
prnCyan	**0**	Specifies cyan plate
prnMagenta	**1**	Specifies magenta plate
prnYellow	**2**	Specifies yellow plate
prnBlack	**3**	Specifies black plate
prnOrange	**4**	Specifies orange plate
prnGreen	**5**	Specifies green plate
prnSpot	**6**	Specifies spot plate

Copyright 2014 Corel Corporation. All rights reserved.

PrnPostScriptLevel

The **PrnPostScriptLevel** enumeration has the following constants:

Constant	Value	Description
prnPSLevel1	**1**	Specifies level-1 PostScript
prnPSLevel2	**2**	Specifies level-2 PostScript
prnPSLevel3	**3**	Specifies level-3 PostScript

Copyright 2014 Corel Corporation. All rights reserved.

PrnPrintRange

The **PrnPrintRange** enumeration has the following constants:

Constant	Value	Description
prnWholeDocument	**0**	Specifies the whole document
prnCurrentPage	**1**	Specifies the current page
prnSelection	**2**	Specifies a selection
prnPageRange	**3**	Specifies a page range

Copyright 2014 Corel Corporation. All rights reserved.

prnPSLevel1

The following enumerations have this constant:

- PrnPostScriptLevel

Copyright 2014 Corel Corporation. All rights reserved.

prnPSLevel2

The following enumerations have this constant:

- PrnPostScriptLevel

Copyright 2014 Corel Corporation. All rights reserved.

prnPSLevel3

The following enumerations have this constant:

- PrnPostScriptLevel

Copyright 2014 Corel Corporation. All rights reserved.

PrnRegistrationStyle

The **PrnRegistrationStyle** enumeration has the following constants:

Constant	Value	Description
prnStandard	**0**	Specifies standard style
prnLong	**1**	Specifies long style
prnSquare	**2**	Specifies square style
prnHalfInverted	**3**	Specifies half-inverted style
prnCorel	**4**	Specifies Corel style

Copyright 2014 Corel Corporation. All rights reserved.

prnSelection

The following enumerations have this constant:

- PrnPrintRange

Copyright 2014 Corel Corporation. All rights reserved.

prnSeparatePages

The following enumerations have this constant:

- PrnFileMode

Copyright 2014 Corel Corporation. All rights reserved.

prnSeparatePlates

The following enumerations have this constant:

- PrnFileMode

Copyright 2014 Corel Corporation. All rights reserved.

prnSingleFile

The following enumerations have this constant:

- PrnFileMode

Copyright 2014 Corel Corporation. All rights reserved.

prnSpot

The following enumerations have this constant:

- PrnPlateType

Copyright 2014 Corel Corporation. All rights reserved.

prnSquare

The following enumerations have this constant:

- PrnRegistrationStyle

Copyright 2014 Corel Corporation. All rights reserved.

prnStandard

The following enumerations have this constant:

- PrnRegistrationStyle

Copyright 2014 Corel Corporation. All rights reserved.

prnTrapCenter

The following enumerations have this constant:

- PrnImageTrap

Copyright 2014 Corel Corporation. All rights reserved.

prnTrapChoke

The following enumerations have this constant:

- PrnImageTrap

Copyright 2014 Corel Corporation. All rights reserved.

prnTrapNormal

The following enumerations have this constant:

- PrnImageTrap

Copyright 2014 Corel Corporation. All rights reserved.

prnTrapSpread

The following enumerations have this constant:

- PrnImageTrap

Copyright 2014 Corel Corporation. All rights reserved.

PrnTrapType

The **PrnTrapType** enumeration has the following constants:

Constant	Value	Description
prnLayerNormal	**0**	Specifies normal trapping
prnLayerTransparent	**1**	Specifies transparent trapping
prnLayerOpaque	**2**	Specifies opaque trapping
prnLayerOpaqueIgnore	**3**	Specifies ignored opaque trapping

Copyright 2014 Corel Corporation. All rights reserved.

prnWholeDocument

The following enumerations have this constant:

- PrnPrintRange

Copyright 2014 Corel Corporation. All rights reserved.

prnYellow

The following enumerations have this constant:

- PrnPlateType

Copyright 2014 Corel Corporation. All rights reserved.

ProofColorSettings

Properties Methods

Description

The **ProofColorSettings** class represents color-proofing settings.

Copyright 2014 Corel Corporation. All rights reserved.

ProofColorSettings.ColorContext

Property **ColorContext** As ColorContext

Description

Member of ProofColorSettings

The **ColorContext** property specifies the color context of the environment to simulate.

Copyright 2014 Corel Corporation. All rights reserved.

ProofColorSettings.CopyAssign

Sub **CopyAssign(**Source As ProofColorSettings**)**

Description

Member of ProofColorSettings

The **CopyAssign** method copies the settings from the source object to the current one.

Parameter	Description
Source	Specifies the source object

Copyright 2014 Corel Corporation. All rights reserved.

ProofColorSettings.GetCopy

Function **GetCopy()** As ProofColorSettings

Description

Member of ProofColorSettings

The **GetCopy** method creates a copy of the object.

Copyright 2014 Corel Corporation. All rights reserved.

ProofColorSettings.OutOfGamutColor

Property **OutOfGamutColor** As Color

Description

Member of ProofColorSettings

The **OutOfGamutColor** property specifies the out-of-gamut warning overlay color.

Copyright 2014 Corel Corporation. All rights reserved.

ProofColorSettings.OutOfGamutTransparency

Property **OutOfGamutTransparency** As Double

Description

Member of ProofColorSettings

The **OutOfGamutTransparency** property specifies the out-of-gamut warning overlay transparency.

Copyright 2014 Corel Corporation. All rights reserved.

ProofColorSettings.PreserveColorValues

Property **PreserveColorValues** As Boolean

Description

Member of ProofColorSettings

The **PreserveColorValues** property specifies whether the color components are preserved when no color-model conversion is performed.

Copyright 2014 Corel Corporation. All rights reserved.

ProofColorSettings.ShowOutOfGamutWarning

Property **ShowOutOfGamutWarning** As Boolean

Description

Member of ProofColorSettings

The **ShowOutOfGamutWarning** property specifies whether the color out-of-gamut alarm is shown.

Copyright 2014 Corel Corporation. All rights reserved.

Properties

Properties Methods

Description

The **Properties** class represents a set of customized data items that is assigned to a Document, Page, Layer, or Shape object. Each property item is identified by a name and ID; the name can be a program or macro name that owns the data, while the ID is any integer number.

Copyright 2014 Corel Corporation. All rights reserved.

Properties.Count

Property **Count** As Long

Description

Member of Properties

The **Count** property returns the number of data items assigned to an object.

The **Count** property returns a read-only value.

VBA example

The following VBA example creates an ellipse and assigns the number **2** to its Properties collection. It then displays the number of elements in the collection (**1**).

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse(0, 0, 2, 2)
 s.Properties("MyMacroParam", 0) = 2
 MsgBox s.Properties.Count
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Properties.Delete

Sub **Delete(***Name As String*, *ID As Long***)**

Description

Member of Properties

The **Delete** method deletes a data item as specified by name and ID.

Parameter	Description
Name	Specifies the data item by its name
ID	Specifies the data item by its ID

VBA example

The following VBA example retrieves all shape references stored in the page and deletes them.

```
Sub DeleteStoredShapes()
 Dim s As Shape, sr As New ShapeRange
 Dim v As Variant
 Dim Num As Long, i As Long, id As Long
 v = ActivePage.Properties("ShapeArray", 0) ' Retrieving the total number of shape references stored
 If Not IsNull(v) Then
  ActivePage.Properties.Delete "ShapeArray", 0 ' Delete the property
  Num = v
  ActiveDocument.ClearSelection
  For i = 1 To Num
   id = ActivePage.Properties("ShapeArray", i) ' Getting the current shape's ID to find
   Set s = ActivePage.FindShape(StaticID:=id)
   If Not s Is Nothing Then sr.Add s ' Add the shape to the shape range
   ActivePage.Properties.Delete "ShapeArray", i ' Delete the property
  Next i
  sr.Delete ' Delete all shapes found
 Else
  MsgBox "No shape references stored in the active page"
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Properties.DeleteAll

Function **DeleteAll(***Name As String***)** As Boolean

Description

Member of Properties

The **DeleteAll** method deletes all properties associated with a given section name.

Copyright 2014 Corel Corporation. All rights reserved.

Properties.DeleteByIndex

Sub **DeleteByIndex(***Index As Long***)**

Description

Member of Properties

The **DeleteByIndex** method deletes a data item as specified by index number.

Parameter	Description
Index	Specifies the data item by its index number

VBA example

The following VBA example adds three data items to the document's property collection and then removes the second data item.

```
Sub Test()
 Dim p As Properties
 Set p = ActiveDocument.Properties
 p.Item("Application", 1) = "CorelDRAW"
 p.Item("Application", 2) = "Corel PHOTO-PAINT"
 p.Item("Application", 3) = "R.A.V.E"
 p.DeleteByIndex (2) ' Remove the second data item - "Corel PHOTO-PAINT."
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Properties.Description

Sub **Description(***Index As Long*, *Name As String*, *ID As Long***)**

Description

Member of Properties

The **Description** method returns the name and ID of a data item as specified by index number.

Parameter	Description
Index	Specifies the data item by its index number
Name	Specifies the data item by its name
ID	Specifies the data item by its ID

VBA example

The following VBA example shows the list of all properties and their values for the active document.

```
Sub Test()
 Dim s As String, i As Long
 Dim Name As String, ID As Long
 s = "Document property list:"
 For i = 1 To ActiveDocument.Properties.Count
  ActiveDocument.Properties.Description i, Name, ID
  s = s & vbCr & "<" & Name & "," & ID & "> = "
  s = s & ActiveDocument.Properties.ItemByIndex(i)
 Next i
 MsgBox s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Properties.Exists

Function **Exists(***Name As String*, *ID As Long***)** As Boolean

Description

Member of Properties

The **Exists** method returns whether a specified property exists. If the property exists, **True** is returned.

Copyright 2014 Corel Corporation. All rights reserved.

Properties.Index

Property **Index(***Name As String***,** *ID As Long***)** As Long

Description

Member of Properties

The **Index** property returns the index number of a data item with the specified item name and ID.

The **Index** property returns a read-only value.

Parameter	Description
Name	Specifies the data item by its name
ID	Specifies the data item by its ID

VBA example

The following VBA example creates an ellipse and assigns two data items to it. The index value of **2** is then displayed, representing the property specified by **(Name="Height", ID=0)**.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse(0, 0, 2, 2)
 s.Properties("Width", 0) = s.SizeWidth
 s.Properties("Height", 0) = s.SizeHeight
 MsgBox s.Properties.Index("Height", 0)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Properties.Item

Property **Item(***Name As String*, *ID As Long***)** As Variant

Description

Member of Properties

The **Item** property returns the data item specified by the data name and ID. It can also be used to assign data to an object.

Item is the default property of the Properties class.

Parameter	Description
Name	Specifies the data item by its name
ID	Specifies the data item by its ID

VBA example

The following VBA example creates three different custom property records in the current document and retrieves their values. The values are saved along with the document and made available in the next session, unless you delete them by using the Properties.Delete or Properties.DeleteByIndex method.

```
Sub Test()
 Const MyMacroName As String = "MyTestMacro"
 With ActiveDocument
  .Properties(MyMacroName, 1) = "My String 1" ' String
  .Properties(MyMacroName, 2) = 1     ' Integer
  .Properties(MyMacroName, 3) = Atn(1) * 4 ' Double

  MsgBox .Properties(MyMacroName, 1)
  MsgBox .Properties(MyMacroName, 2)
  MsgBox .Properties(MyMacroName, 3)
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Properties.ItemByIndex

Property ItemByIndex(*Index As Long*) As Variant

Description

Member of Properties

The **ItemByIndex** property returns the data item associated with a specified index number.

The **ItemByIndex** property returns a read-only value.

Parameter	Description
Index	Specifies the data item by its index number

VBA example

The following VBA example adds three data items to the document's property collection and displays the second data item.

```
Sub Test()
 Dim p As Properties
 Set p = ActiveDocument.Properties
 p.Item("Item", 1) = "Draw"
 p.Item("Item", 2) = "PhotoPaint"
 p.Item("Item", 3) = "R.A.V.E"
 MsgBox p.ItemByIndex(2)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

PSScreenOptions

Properties Methods

Description

The **PSScreenOptions** class represents a set of PostScript screen settings.

Copyright 2014 Corel Corporation. All rights reserved.

PSScreenOptions.Angle

Property **Angle** As Double

Description

Member of PSScreenOptions

The **Angle** property returns or specifies, in degrees, the angle of a halftone screen.

Copyright 2014 Corel Corporation. All rights reserved.

PSScreenOptions.Frequency

Property **Frequency** As Long

Description

Member of PSScreenOptions

The **Frequency** property returns or specifies, in lines per inch (lpi), the type frequency of a halftone screen.

Copyright 2014 Corel Corporation. All rights reserved.

PSScreenOptions.Index

Property **Index** As Long

Description

Member of PSScreenOptions

The **Index** property returns the index number of a PostScript halftone-screen type. It is the default property of the PSScreenOptions class.

The **Index** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

PSScreenOptions.Name

Property **Name** As String

Description

Member of PSScreenOptions

The **Name** property returns the name of a PostScript halftone-screen type.

The **Name** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

PSScreenOptions.NameByIndex

Function **NameByIndex(***Index As Long***)** As String

Description

Member of PSScreenOptions

The **NameByIndex** property determines the name of an available halftone-screen type, given its index number. If no such type is available, an empty string is returned.

Parameter	Description
Index	Specifies the half-tone screen type by index number

Copyright 2014 Corel Corporation. All rights reserved.

PSScreenOptions.Reset

Sub **Reset()**

Description

Member of PSScreenOptions

The **Reset** method resets a PostScript halftone screen to its default parameters.

Copyright 2014 Corel Corporation. All rights reserved.

PSScreenOptions.Select

Function **Select(***Name As String***)** As Boolean

Description

Member of PSScreenOptions

The **Select** method selects a new halftone-screen type by index number or name.

Parameter	Description
Name	Specifies the halftone-screen type by name

Copyright 2014 Corel Corporation. All rights reserved.

PSScreenOptions.SetProperties

Function **SetProperties(***IndexOrName As Variant***,** *Angle As Double***,** *Frequency As Long***)** As Boolean

Description

Member of PSScreenOptions

The **SetProperties** method specifies all of PostScript halftone-screen parameters in one call.

Parameter	Description
IndexOrName	Specifies the halftone-screen type by its index number or name: • **Index** — Specifies the preset placeholder that uniquely identifies each halftone- screen type • **Name** — Specifies the string that uniquely identifies each halftone-screen type
Angle	Specifies the angle of the halftone screen, in degrees
Frequency	Specifies the halftone-screen type frequency, in lines per inch (lpi)

Copyright 2014 Corel Corporation. All rights reserved.

PSScreenOptions.UserAssign

Function **UserAssign([***ParentWindowHandle As Long***])** As Boolean

Description

Member of PSScreenOptions

The **UserAssign** method displays the **Options** dialog box for a PostScript halftone screen.

Parameter	Description
ParentWindowHandle	Specifies the handle of the parent window. This parameter is optional, and its default value is **0**.

Copyright 2014 Corel Corporation. All rights reserved.

RecentFile

Properties Methods

Description

The **RecentFile** class represents one of the recent-file items on the **File** menu.

CorelDRAW keeps the four most recently opened documents in the Most Recently Used (MRU) list.

Copyright 2014 Corel Corporation. All rights reserved.

RecentFile.Application

Property **Application** As Object

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

RecentFile.Delete

Sub **Delete()**

Description

Member of RecentFile

The **Delete** method removes a specified document from the Most Recently Used (MRU) list.

- Removing a document with the **Delete** method does not delete the actual document — it only removes its name from the MRU list in CorelDRAW.

VBA example

The following VBA example clears the MRU list.

```
Sub Test()
 Dim rf As RecentFile
 While RecentFiles.Count <> 0
  RecentFiles(1).Delete
 Wend
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

RecentFile.FullName

Property **FullName** As String

Description

Member of RecentFile

The **FullName** property returns or specifies the full path and filename of an item in the Most Recently Used (MRU) list of CorelDRAW.

VBA example

The following VBA example displays the list of most recently used files and their paths.

```
Sub Test()
 Dim rf As RecentFile, s As String
 s = "Most Recently Used files:"
 For Each rf In RecentFiles
  s = s & vbCr & rf.Name & vbTab & rf.Path
 Next rf
 MsgBox s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

RecentFile.Index

Property Index As Long

Description

Member of RecentFile

The **Index** property returns the index number of the current file entry in the Most Recently Used (MRU) list of CorelDRAW.

The **Index** property returns a read-only value.

VBA example

The following VBA example displays the files in the MRU list.

```
Sub Test()
 Dim rf As RecentFile, s As String
 s = "Most Recently Used files:"
 For Each rf In RecentFiles
  s = s & vbCr & rf.Index & ". " & rf.Name
 Next rf
 MsgBox s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

RecentFile.Name

Property **Name** As String

Description

Member of RecentFile

The **Name** property returns or specifies the filename of an item in the Most Recently Used (MRU) list of CorelDRAW.

VBA example

The following VBA example displays the list of most recently used files and their paths.

```
Sub Test()
 Dim rf As RecentFile, s As String
 s = "Most Recently Used files:"
 For Each rf In RecentFiles
  s = s & vbCr & rf.Name & vbTab & rf.Path
 Next rf
 MsgBox s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

RecentFile.Open

Function **Open()** As Object

Description

Member of RecentFile

The **Open** method opens a document from the Most Recently Used (MRU) list.

The following code opens the second document in the MRU list of CorelDRAW and displays the number of pages it contains.

```
Sub Test()
 Dim doc As Document
 Set doc = RecentFiles(2).Open
 MsgBox "Number of pages = " & doc.Pages.Count
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

RecentFile.Parent

Property **Parent** As RecentFiles

Description

Member of RecentFile

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

RecentFile.Path

Property **Path** As String

Description

Member of RecentFile

The **Path** property returns or specifies the path of an item in the Most Recently Used (MRU) list of CorelDRAW.

VBA example

The following VBA example displays the list of most recently used files and their paths.

```
Sub Test()
 Dim rf As RecentFile, s As String
 s = "Most Recently Used files:"
 For Each rf In RecentFiles
  s = s & vbCr & rf.Name & vbTab & rf.Path
 Next rf
 MsgBox s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

RecentFiles

Properties Methods

Description

The **RecentFiles** class represents the list of Most Recently Used (MRU) files (or RecentFile objects).

CorelDRAW keeps the four most recently opened documents in the MRU list.

Copyright 2014 Corel Corporation. All rights reserved.

RecentFiles.Add

Function **Add(***Name As String***,** *Path As String***)** As RecentFile

Description

Member of RecentFiles

The **Add** method places a specified document in the Most Recently Used (MRU) list of CorelDRAW.

Parameter	Description
Name	Specifies the name of the file
Path	Specifies the path to the file

VBA example

The following VBA example adds the file **C:\Temp\Graphics\MyFile.cdr** to the list of most recently used files.

```
Sub Test()
 RecentFiles.Add "MyFile.cdr", "C:\Temp\Graphics\"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

RecentFiles.Application

Property **Application** As Object

Description

Member of RecentFiles

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

RecentFiles.Count

Property **Count** As Long

Description

Member of RecentFiles

The **Count** property returns the number of files in the Most Recently Used (MRU) list of CorelDRAW.

The **Count** property returns a read-only value.

VBA example

The following VBA example clears the MRU list.

```
Sub Test()
 Dim rf As RecentFile
 While RecentFiles.Count <> 0
  RecentFiles(1).Delete
 Wend
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

RecentFiles.Item

Property **Item(***Index As Long***)** As RecentFile

Description

Member of RecentFiles

The **Item** property returns the specified RecentFile object.

Item is the default property of the RecentFiles class, and its reference can be omitted when you are accessing items in a **RecentFiles** collection. For example, **RecentFiles.Item(2)** is the same as **RecentFiles(2)** — they both reference the second **RecentFile** object in the collection.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each member of the **RecentFiles** collection

VBA example

The following VBA example displays the list of most recently used files and their paths.

```
Sub Test()
 Dim rf As RecentFile, s As String, i As Long
 s = "Most Recently Used files:"
 For i = 1 To RecentFiles.Count
  Set rf = RecentFiles(i)
  s = s & vbCr & rf.Name & vbTab & rf.Path
 Next i
 MsgBox s
End Sub
Sub Test()
 Dim rf As RecentFile, s As String
 s = "Most Recently Used files:"
 For Each rf In RecentFiles
  s = s & vbCr & rf.Name & vbTab & rf.Path
 Next rf
 MsgBox s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

RecentFiles.Maximum

Property **Maximum** As Long

Description

Member of RecentFiles

The **Maximum** property returns the number of items that can be stored in the Most Recently Used (MRU) list of CorelDRAW.

The **Maximum** property returns a read-only value.

VBA example

The following VBA example displays the maximum number of documents that can be stored in the MRU list of CorelDRAW.

```
Sub FilesMax()
 MsgBox RecentFiles.Maximum
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

RecentFiles.Parent

Property **Parent** As Object

Description

Member of RecentFiles

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Rect

Properties Methods

Description

The **Rect** class represents the rectangular bounding box around an object.

Copyright 2014 Corel Corporation. All rights reserved.

Rect.Bottom

Property **Bottom** As Double

Description

Member of Rect

The **Bottom** property returns the coordinates of the bottom edge of a bounding box.

The **Bottom** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Rect.CenterX

Property **CenterX** As Double

Description

Member of Rect

The **CenterX** property returns the horizontal center of a bounding box.

The **CenterX** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Rect.CenterY

Property **CenterY** As Double

Description

Member of Rect

The **CenterY** property returns the vertical center of a bounding box.

The **CenterY** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Rect.ChangeContext

Function **ChangeContext(**SrcDoc As Document**,** DestDoc As Document**)** As Rect

Description

Member of Rect

The **ChangeContext** method translates the coordinates of a bounding box from the context of the source document to that of the target document.

Parameter	Description
SrcDoc	Specifies the source document
DestDoc	Specifies the target document

Copyright 2014 Corel Corporation. All rights reserved.

Rect.Clear

Sub **Clear()**

Description

Member of Rect

The **Clear** method deletes the contents of a bounding box.

Copyright 2014 Corel Corporation. All rights reserved.

Rect.CopyAssign

Sub **CopyAssign(**Source As Rect**)**

Description

Member of Rect

The **CopyAssign** method copies the position and size of a bounding box.

Parameter	Description
Source	Specifies the source

Copyright 2014 Corel Corporation. All rights reserved.

Rect.GetCopy

Function **GetCopy()** As Rect

Description

Member of Rect

The **GetCopy** method returns a copy of a bounding box.

Copyright 2014 Corel Corporation. All rights reserved.

Rect.GetRect

Sub **GetRect(***x As Double*, *y As Double*, *Width As Double*, *Height As Double***)**

Description

Member of Rect

The **GetRect** method returns the position and size of a bounding box.

Parameter	Description
x	Specifies the x-coordinate of the bounding box
y	Specifies the y-coordinate of the bounding box
Width	Specifies the width of the bounding box
Height	Specifies the height of the bounding box

Copyright 2014 Corel Corporation. All rights reserved.

Rect.Height

Property **Height** As Double

Description

Member of Rect

The **Height** property returns or specifies the height of a bounding box.

Copyright 2014 Corel Corporation. All rights reserved.

Rect.Inflate

Function **Inflate(***Left As Double*, *Top As Double*, *Right As Double*, *Bottom As Double***)** As Boolean

Description

Member of Rect

The **Inflate** method increases the size of a bounding box.

Parameter	Description
Left	Specifies the left value
Top	Specifies the top value
Right	Specifies the right value
Bottom	Specifies the bottom value

Copyright 2014 Corel Corporation. All rights reserved.

Rect.Intersect

Function **Intersect(**Rect As Rect**)** As Rect

Description

Member of Rect

The **Intersect** method intersects two bounding boxes and returns the overlapping region.

Parameter	Description
Rect	Specifies the bounding box

Copyright 2014 Corel Corporation. All rights reserved.

Rect.IsEmpty

Property **IsEmpty** As Boolean

Description

Member of Rect

The **IsEmpty** property determines whether a bounding box is empty.

The **IsEmpty** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Rect.IsPointInside

Function **IsPointInside(***x As Double***,** *y As Double***)** As Boolean

Description

Member of Rect

The **IsPointInside** method checks whether a bounding box contains the specified point.

Parameter	Description
x	Specifies the x-coordinate of the point
y	Specifies the y-coordinate of the point

Copyright 2014 Corel Corporation. All rights reserved.

Rect.Left

Property **Left** As Double

Description

Member of Rect

The **Left** property returns the coordinate of the left edge of a bounding box.

The **Left** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Rect.Offset

Sub **Offset(***OffsetX As Double***,** *OffsetY As Double***)**

Description

Member of Rect

The **Offset** method moves a bounding box.

Parameter	Description
OffsetX	Specifies the horizontal offset
OffsetY	Specifies the vertical offset

Copyright 2014 Corel Corporation. All rights reserved.

Rect.Right

Property **Right** As Double

Description

Member of Rect

The **Right** property returns the coordinate of the right edge of a bounding box.

The **Right** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Rect.SetRect

Sub **SetRect(***x As Double*, *y As Double*, *Width As Double*, *Height As Double***)**

Description

Member of Rect

The **SetRect** method sets the position and size of a bounding box.

Parameter	Description
x	Specifies the x-coordinate of the bounding box
y	Specifies the y-coordinate of the bounding box
Width	Specifies the width of the bounding box
Height	Specifies the height of the bounding box

Copyright 2014 Corel Corporation. All rights reserved.

Rect.Top

Property **Top** As Double

Description

Member of Rect

The **Top** property returns the coordinate of the top edge of a bounding box.

The **Top** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Rect.Union

Function **Union(**Rect As Rect**)** As Rect

Description

Member of Rect

The **Union** method creates a bounding box that encloses two other bounding boxes.

Parameter	Description
Rect	Specifies the bounding box

Copyright 2014 Corel Corporation. All rights reserved.

Rect.Width

Property **Width** As Double

Description

Member of Rect

The **Width** property returns or specifies the width of a bounding box.

Copyright 2014 Corel Corporation. All rights reserved.

Rect.x

Property **x** As Double

Description

Member of Rect

The **x** property returns or specifies the position of the left edge of a bounding box.

Copyright 2014 Corel Corporation. All rights reserved.

Rect.y

Property **y** As Double

Description

Member of Rect

The **y** property returns or specifies the position of the bottom edge of a bounding box.

Copyright 2014 Corel Corporation. All rights reserved.

Rectangle

Properties Methods

Description

The **Rectangle** class represents the rectangle-specific settings for a shape (or Shape object).

Copyright 2014 Corel Corporation. All rights reserved.

Rectangle.CornerLowerLeft

Property **CornerLowerLeft** As Long

Description

Member of Rectangle

The **CornerLowerLeft** property returns or specifies the roundness of the lower-left corner of a rectangle.

The value for the roundness ranges from **0** (a cusp corner) to **100** (the maximum corner radius, which is half the length of the shortest side).

VBA example

The following VBA example determines whether the selected rectangle has any rounded corners.

```
Sub Test()
 Dim r As Rectangle
 If ActiveShape.Type = cdrRectangleShape Then
  Set r = ActiveShape.Rectangle
  If r.CornerLowerLeft = 0 And r.EqualCorners Then
   MsgBox "The rectangle does not have rounded corners."
  Else
   MsgBox "The rectangle has rounded corners."
  End If
 Else
  MsgBox "The selected shape is not a rectangle."
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Rectangle.CornerLowerRight

Property **CornerLowerRight** As Long

Description

Member of Rectangle

The **CornerLowerRight** property returns or specifies the roundness of the lower-right corner of a rectangle.

The value for the roundness ranges from **0** (a cusp corner) to **100** (the maximum corner radius, which is half the length of the shortest side).

VBA example

The following VBA example determines whether the selected rectangle has any rounded corners.

```
Sub Test()
 Dim r As Rectangle
 If ActiveShape.Type = cdrRectangleShape Then
  Set r = ActiveShape.Rectangle
  If r.CornerLowerRight = 0 And r.EqualCorners Then
   MsgBox "The rectangle does not have rounded corners."
  Else
   MsgBox "The rectangle has rounded corners."
  End If
 Else
  MsgBox "The selected shape is not a rectangle."
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Rectangle.CornerType

Property **CornerType** As cdrCornerType

Description

Member of Rectangle

The **CornerType** property returns or specifies the corner type for a rectangle.

Copyright 2014 Corel Corporation. All rights reserved.

Rectangle.CornerUpperLeft

Property **CornerUpperLeft** As Long

Description

Member of Rectangle

The **CornerUpperLeft** property returns or specifies the roundness of the upper-left corner of a rectangle.

The value for the roundness ranges from **0** (a cusp corner) to **100** (the maximum corner radius, which is half the length of the shortest side).

VBA example

The following VBA example determines whether the selected rectangle has any rounded corners.

```
Sub Test()
 Dim r As Rectangle
 If ActiveShape.Type = cdrRectangleShape Then
  Set r = ActiveShape.Rectangle
  If r.CornerUpperLeft = 0 And r.EqualCorners Then
   MsgBox "The rectangle does not have rounded corners."
  Else
   MsgBox "The rectangle has rounded corners."
  End If
 Else
  MsgBox "The selected shape is not a rectangle."
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Rectangle.CornerUpperRight

Property **CornerUpperRight** As Long

Description

Member of Rectangle

The **CornerUpperRight** property returns or specifies the roundness of the upper-right corner of a rectangle.

The value for the roundness ranges from **0** (a cusp corner) to **100** (the maximum corner radius, which is half the length of the shortest side).

VBA example

The following VBA example determines whether the selected rectangle has any rounded corners.

```
Sub Test()
 Dim r As Rectangle
 If ActiveShape.Type = cdrRectangleShape Then
  Set r = ActiveShape.Rectangle
  If r.CornerUpperRight = 0 And r.EqualCorners Then
   MsgBox "The rectangle does not have rounded corners."
  Else
   MsgBox "The rectangle has rounded corners."
  End If
 Else
  MsgBox "The selected shape is not a rectangle."
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Rectangle.EqualCorners

Property **EqualCorners** As Boolean

Description

Member of Rectangle

The **EqualCorners** property returns **True** if all four corners of a rectangle have the same corner radius (if any at all).

The **EqualCorners** property returns a read-only value.

VBA example

The following VBA example checks whether each rectangle on the current page has equal corners. The radius of the smallest corner is applied to each rectangle with unequal corners.

```
Sub Test()
 Dim s As Shape
 Dim r As Rectangle
 Dim d As Long
 For Each s In ActivePage.FindShapes(Type:=cdrRectangleShape)
  Set r = s.Rectangle
  If Not r.EqualCorners Then
   d = r.CornerLowerLeft
   If d > r.CornerLowerRight Then d = r.CornerLowerRight
   If d > r.CornerUpperLeft Then d = r.CornerUpperLeft
   If d > r.CornerUpperRight Then d = r.CornerUpperRight
   r.SetRoundness d
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Rectangle.MaxRadius

Property **MaxRadius** As Double

Description

Member of Rectangle

The **MaxRadius** property returns the maximum radius value possible for a rectangle's rounded corner. This value is half the size of the shortest side of a rectangle.

The **MaxRadius** property returns a read-only value.

VBA example

The following VBA example sets the maximum corner radius for all rectangles to **0.5**".

```
Sub Test()
 Dim s As Shape
 Const r As Double = 0.5
 For Each s In ActivePage.FindShapes(Type:=cdrRectangleShape)
  If s.Rectangle.MaxRadius >= r Then
   s.Rectangle.SetRadius r
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Rectangle.RadiusLowerLeft

Property **RadiusLowerLeft** As Double

Description

Member of Rectangle

The **RadiusLowerLeft** property returns or specifies the radius of a rectangle's lower-left corner.

- The radius is measured in document units and is not relative to the size of the rectangle.

VBA example

The following VBA example rounds the corners of the selected rectangle by specifying a different radius (**0.1**", **0.2**", **0.3**", and **0.4**") for each corner.

```
Sub Test()
 If ActiveShape.Type <> cdrRectangleShape Then Exit Sub
 With ActiveShape.Rectangle
  .RadiusLowerLeft = 0.1
  .RadiusLowerRight = 0.2
  .RadiusUpperLeft = 0.3
  .RadiusUpperRight = 0.4
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Rectangle.RadiusLowerRight

Property **RadiusLowerRight** As Double

Description

Member of Rectangle

The **RadiusLowerRight** property returns or specifies the radius of a rectangle's lower-right corner.

- The radius is measured in document units and is not relative to the size of the rectangle.

VBA example

The following VBA example rounds the corners of the selected rectangle by specifying a different radius (**0.1**", **0.2**", **0.3**", and **0.4**") for each corner.

```
Sub Test()
 If ActiveShape.Type <> cdrRectangleShape Then Exit Sub
 With ActiveShape.Rectangle
  .RadiusLowerLeft = 0.1
  .RadiusLowerRight = 0.2
  .RadiusUpperLeft = 0.3
  .RadiusUpperRight = 0.4
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Rectangle.RadiusUpperLeft

Property **RadiusUpperLeft** As Double

Description

Member of Rectangle

The **RadiusUpperLeft** property returns or specifies the radius of a rectangle's upper-left corner.

- The radius is measured in document units and is not relative to the size of the rectangle.

VBA example

The following VBA example rounds the corners of the selected rectangle by specifying a different radius (**0.1**", **0.2**", **0.3**", and **0.4**") for each corner.

```
Sub Test()
 If ActiveShape.Type <> cdrRectangleShape Then Exit Sub
 With ActiveShape.Rectangle
  .RadiusLowerLeft = 0.1
  .RadiusLowerRight = 0.2
  .RadiusUpperLeft = 0.3
  .RadiusUpperRight = 0.4
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Rectangle.RadiusUpperRight

Property **RadiusUpperRight** As Double

Description

Member of Rectangle

The **RadiusUpperRight** property returns or specifies the radius of a rectangle's upper-right corner.

- The radius is measured in document units and is not relative to the size of the rectangle.

VBA example

The following VBA example rounds the corners of the selected rectangle by specifying a different radius (**0.1**", **0.2**", **0.3**", and **0.4**") for each corner:

```
Sub Test()
 If ActiveShape.Type <> cdrRectangleShape Then Exit Sub
 With ActiveShape.Rectangle
  .RadiusLowerLeft = 0.1
  .RadiusLowerRight = 0.2
  .RadiusUpperLeft = 0.3
  .RadiusUpperRight = 0.4
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Rectangle.RelativeCornerScaling

Property **RelativeCornerScaling** As Boolean

Description

Member of Rectangle

The **RelativeCornerScaling** property returns or specifies the corner scaling for a rectangle.

Copyright 2014 Corel Corporation. All rights reserved.

Rectangle.SetRadius

Sub **SetRadius(***Radius As Double***)**

Description

Member of Rectangle

The **SetRadius** method sets the same radius value for all corners in a rectangle. This value is measured in document units.

Parameter	Description
Radius	Specifies the value of the radius

VBA example

The following VBA example sets the radius of all corners in the active rectangle to **0.3**".

```
Sub Test()
 ActiveShape.Rectangle.SetRadius 0.3
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Rectangle.SetRoundness

Sub **SetRoundness(***Roundness As Long***)**

Description

Member of Rectangle

The **SetRoundness** method sets the same roundness for all corners in a rectangle.

The roundness value ranges from **0** (a cusp corner) to **100** (the maximum corner radius, which is half the length of the shortest side).

Parameter	Description
Roundness	Specifies the roundness. Values range from **0** to **100**.

VBA example

The following VBA example sets the roundness for all corners in the active rectangle to **50**%.

```
Sub Test()
 ActiveShape.Rectangle.SetRoundness 50
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Rulers

Properties

Description

The **Rulers** class represents the settings for the rulers in the drawing window.

Copyright 2014 Corel Corporation. All rights reserved.

Rulers.Application

Property **Application** As Application

Description

Member of Rulers

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Rulers.HUnits

Property **HUnits** As cdrUnit

Description

Member of Rulers

The **HUnits** property returns or specifies the unit of measurement for the horizontal ruler in the document window. This property returns or specifies a value of cdrUnit.

- The specified value affects only the user interface of CorelDRAW and has no effect on automation.

- See also the Document.Unit property.

VBA example

The following VBA example changes the unit of measurement for the horizontal ruler to inches and for the vertical ruler to centimeters.

```
Sub Test()
 With ActiveDocument.Rulers
  .HUnits = cdrInch
  .VUnits = cdrCentimeter
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Rulers.Parent

Property **Parent** As Document

Description

Member of Rulers

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Rulers.VUnits

Property **VUnits** As cdrUnit

Description

Member of Rulers

The **VUnits** property returns or specifies the unit of measurement for the vertical ruler in the document window. This property returns or specifies a value of cdrUnit.

- The specified value affects only the user interface of CorelDRAW and has no effect on automation.

- See also the Document.Unit property.

VBA example

The following VBA example changes the unit of measurement for the horizontal ruler to inches and for the vertical ruler to centimeters.

```
Sub Test()
 With ActiveDocument.Rulers
  .HUnits = cdrInch
  .VUnits = cdrCentimeter
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect

Properties Methods

Description

The **ScreenRect** class repesents the properties of a rectangle on the screen.

For an example that uses this class, see Cascading views.

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.Bottom

Property **Bottom** As Long

Description

Member of ScreenRect

The **Bottom** property returns or sets the positon of the bottom edge of the rectangle.

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.CenterX

Property **CenterX** As Long

Description

Member of ScreenRect

The **CenterX** property returns or sets the horizontal positon of the rectangle's center.

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.CenterY

Property **CenterY** As Long

Description

Member of ScreenRect

The **CenterY** property returns or sets the vertical positon of the rectangle's center.

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.CopyAssign

Sub **CopyAssign(**Source As ScreenRect**)**

Description

Member of ScreenRect

The **CopyAssign** method copies the position and size of the rectangle from a source.

Parameter	Description
Source	Specifies the source whose position and size to copy

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.GetCopy

Function **GetCopy()** As ScreenRect

Description

Member of ScreenRect

The **GetCopy** method returns a copy of the rectangle, detached from the original source.

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.Height

Property **Height** As Long

Description

Member of ScreenRect

The **Height** property returns or sets the height of the rectangle.

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.Inflate

Sub **Inflate(***Left As Long, Top As Long, Right As Long, Bottom As Long***)**

Description

Member of ScreenRect

The **Inflate** method inflates rectangle in each direction by a specified amount.

Parameter	Description
Left	Specifies the amount to inflate from the left edge
Top	Specifies the amount to inflate from the top edge
Right	Specifies the amount to inflate from the right edge
Bottom	Specifies the amount to inflate from the bottom edge

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.Intersect

Function **Intersect(**Source As ScreenRect**)** As ScreenRect

Description

Member of ScreenRect

The **Intersect** method makes the two rectangles intersect. The return value is ScreenRect.

Parameter	Description
Source	Specifies the source

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.IsEmpty

Function **IsEmpty()** As Boolean

Description

Member of ScreenRect

The **IsEmpty** method checks if the rectangle is empty.

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.IsPointInside

Function **IsPointInside(***x As Long, y As Long***)** As Boolean

Description

Member of ScreenRect

The **IsPointInside** method checks if the specified point is inside the rectangle.

Parameter	Description
x	Specifies the x-coordinate
y	Specifies the y-coordinate

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.Left

Property **Left** As Long

Description

Member of ScreenRect

The **Left** property returns or sets the postion of the rectangle's left edge.

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.Move

Sub **Move**(Left As Long, Top As Long)

Description

Member of ScreenRect

The **Move** method moves the rectangle to the specified position.

Parameter	Description
Left	Specifies the position of the left edge
Top	Specifies the positon of the top edge

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.Offset

Sub **Offset**(OffsetX As Long, OffsetY As Long)

Description

Member of ScreenRect

The **Offset** method moves the rectangle by the specified offset amount.

Parameter	Description
OffsetX	Specifies the amount by which to offset the rectangle horizontally
OffsetY	Specifies the amount by which to offset the rectangle vertically

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.ReadOnly

Property **ReadOnly** As Boolean

Description

Member of ScreenRect

The **ReadOnly** property teturns True if this is a read-only rectangle. Any attempt to update the size or position of the rectangle will fail.

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.Resize

Sub **Resize**(Width As Long, Height As Long)

Description

Member of ScreenRect

The **Resize** method resizes the rectangle.

Parameter	Description
Width	Specifies the new width of the rectangle
Height	Specifies the new height of the rectangle

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.Right

Property **Right** As Long

Description

Member of ScreenRect

The **Right** property returns or sets the postion of the rectangle's right edge.

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.SetPosition

Sub **SetPosition**(Left As Long, Top As Long, Width As Long, Height As Long)

Description

Member of ScreenRect

The **SetPosition** method specifies the position and size of the rectangle.

Parameter	Description
Left	Specifies the position of the left edge
Top	Specifies the position of the top edge
Width	Specifies the width of the rectangle
Height	Specifies the height of the rectangle

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.Top

Property **Top** As Long

Description

Member of ScreenRect

The **Top** property returns or sets the postion of the rectangle's top edge.

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.Union

Function **Union(**Source As ScreenRect**)** As ScreenRect

Description

Member of ScreenRect

The **Union** method combines the two rectangles and returns the resulting rectangle.

Parameter	Description
Left	Specifies the position of the left edge

Copyright 2014 Corel Corporation. All rights reserved.

ScreenRect.Width

Property **Width** As Long

Description

Member of ScreenRect

The **Width** property returns or sets the width of the rectangle.

Copyright 2014 Corel Corporation. All rights reserved.

Segment

Properties Methods

Description

The **Segment** class repesents the properties of a curve or line segment.

Copyright 2014 Corel Corporation. All rights reserved.

Segment.AbsoluteIndex

Property **AbsoluteIndex** As Long

Description

Member of Segment

The **AbsoluteIndex** property returns the index value of a segment within a curve.

- The Index and **AbsoluteIndex** properties return the same value if the segment belongs to the first subpath of the curve.

The **AbsoluteIndex** property returns a read-only value.

VBA example

The following VBA example loops through all segments of each subpath and prints each segment's **Index** and **AbsoluteIndex** property in the **Intermediate** window of the Macro Editor.

```
Sub Test()
 Dim s As Shape
 Dim sp As SubPath
 Dim seg As Segment
 Set s = ActiveShape
 If s.Type = cdrCurveShape Then
  For Each sp In s.Curve.Subpaths
   For Each seg In sp.Segments
    Debug.Print seg.Index, seg.AbsoluteIndex
   Next seg
  Next sp
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.AddNodeAt

Function **AddNodeAt([**Offset As Double = 0.5**], [**OffsetType As cdrSegmentOffsetType = cdrParamSegmentOffset**])** As Node

Description

Member of Segment

The **AddNodeAt** method adds a node to a segment at a specified offset.

Parameter	Description
Offset	Specifies the offset, in document units, from the beginning of the segment's subpath. This parameter is optional, and its default value is **0.5**.
OffsetType	Specifies the type of offset of the point on the curve's subpath, and returns cdrSegmentOffsetType. This parameter is optional, and its default value is cdrParamSegmentOffset (**2**).

VBA example

The following VBA example creates a curve segment and adds a node at its center.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateCurveSegment(2, 8.3, 5.3, 8.5, 1.5, -62, 2.4, 84)
 s.Curve.Segments(1).AddNodeAt 0.5, cdrRelativeSegmentOffset
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.Application

Property **Application** As Application

Description

Member of Segment

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Segment.BoundingBox

Property **BoundingBox** As Rect

Description

Member of Segment

The **BoundingBox** property returns the bounding box (rectangular area) around a segment.

The **BoundingBox** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Segment.BreakApartAt

Function **BreakApartAt([**Offset As Double = 0.5**], [**OffsetType As cdrSegmentOffsetType = cdrParamSegmentOffset (**2**)**]**) As Node

Description

Member of Segment

The **BreakApartAt** method divides a segment into two unconnected segments at a given point.

Currently, this method fails even if the segment is split successfully. Therefore, you must use the **On Error Resume Next** statement to catch the error and continue execution.

Parameter	Description
Offset	Specifies the offset, in document units, from the beginning of the segment's subpath. This parameter is optional, and its default value is **0.5**.
OffsetType	Specifies the type of offset of the point on the curve's subpath, and returns cdrSegmentOffsetType. This parameter is optional, and its default value is cdrParamSegmentOffset (**2**).

VBA example

The following VBA example creates a curve segment and divides it into two pieces at a point that is **1.3**" from the beginning of the segment.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateCurveSegment(2, 8.3, 5.3, 8.5, 1.5, -62, 2.4, 84)
 On Error Resume Next ' Lines in green are a workaround
 s.Curve.Segments(1).BreakApartAt 1.3, cdrAbsoluteSegmentOffset
 On Error GoTo 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.CreateSelection

```
Sub CreateSelection()
```

Description

Member of Segment

The **CreateSelection** method selects the curve node that controls the properties of a given segment.

Copyright 2014 Corel Corporation. All rights reserved.

Segment.EndingControlPointAngle

Property **EndingControlPointAngle** As Double

Description

Member of Segment

The **StartingControlPointAngle** property returns or specifies the angle, in degrees, of the control-point vector ending of a segment.

VBA example

The following VBA example constrains control-point angles to increments of 45°. Each control-point vector is rotated to the closest angle that is a multiple 45°.

```
Sub Test()
 Dim s As Shape
 Dim seg As Segment
 Set s = ActiveShape
 If s.Type = cdrCurveShape Then
  For Each seg In s.Curve.Segments
   If seg.Type = cdrCurveSegment Then
    seg.StartingControlPointAngle = Constrain(seg.StartingControlPointAngle)
    seg.EndingControlPointAngle = Constrain(seg.EndingControlPointAngle)
   End If
  Next seg
 End If
End Sub
Private Function Constrain(a As Double) As Double
 Constrain = Fix(a / 45 + 0.5) * 45
End Function
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.EndingControlPointLength

Property **EndingControlPointLength** As Double

Description

Member of Segment

The **EndingControlPointLength** property returns or specifies, in document units, the length of the control-point vector ending of a curve.

VBA example

The following VBA example sets the starting and ending control-point length for the first segment in the active shape.

```
Sub App()
 With ActiveShape.Curve.Segments(1)
  .StartingControlPointLength = 5
  .EndingControlPointLength = 5
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.EndingControlPointX

Property **EndingControlPointX** As Double

Description

Member of Segment

The **EndingControlPointX** property returns or specifies the x-coordinate of the ending control point of a curve segment. This property is measured in document units.

VBA example

The following VBA example marks, with a small circle, the position of each control point of the selected curve.

```
Sub Test()
 Dim s As Shape
 Dim seg As Segment
 Set s = ActiveShape
 If s.Type = cdrCurveShape Then
  For Each seg In s.Curve.Segments
   If seg.Type = cdrCurveSegment Then
    ActiveLayer.CreateEllipse2 seg.StartingControlPointX, seg.StartingControlPointY, 0.02
    ActiveLayer.CreateEllipse2 seg.EndingControlPointX, seg.EndingControlPointY, 0.02
   End If
  Next seg
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.EndingControlPointY

Property **EndingControlPointY** As Double

Description

Member of Segment

The **EndingControlPointY** property returns or specifies the y-coordinate of the ending control point of a curve segment. This property is measured in document units.

VBA example

The following VBA example marks, with a small circle, the position of each control point.

```
Sub Test()
 Dim s As Shape
 Dim seg As Segment
 Set s = ActiveShape
 If s.Type = cdrCurveShape Then
  For Each seg In s.Curve.Segments
   If seg.Type = cdrCurveSegment Then
    ActiveLayer.CreateEllipse2 seg.StartingControlPointX, seg.StartingControlPointY, 0.02
    ActiveLayer.CreateEllipse2 seg.EndingControlPointX, seg.EndingControlPointY, 0.02
   End If
  Next seg
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.EndNode

Property **EndNode** As Node

Description

Member of Segment

The **EndNode** property returns the ending node object of a segment.

The **EndNode** property returns a read-only value.

VBA example

The following VBA example re-creates the selected curve by creating each segment as a separate shape.

```
Sub Test()
 Dim seg As Segment
 If ActiveShape Is Nothing Then Exit Sub
 If ActiveShape.Type <> cdrCurveShape Then Exit Sub
 For Each seg In ActiveShape.Curve.Segments
  Select Case seg.Type
   Case cdrLineSegment
    ActiveLayer.CreateLineSegment seg.StartNode.PositionX, _
     seg.StartNode.PositionY, _
     seg.EndNode.PositionX, seg.EndNode.PositionY
   Case cdrCurveSegment
    ActiveLayer.CreateCurveSegment seg.StartNode.PositionX, _
     seg.StartNode.PositionY, _
     seg.EndNode.PositionX, seg.EndNode.PositionY, _
     seg.StartingControlPointLength, _
     seg.StartingControlPointAngle, _
     seg.EndingControlPointLength, _
     seg.EndingControlPointAngle
  End Select
 Next seg
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.FindClosestPoint

Function **FindClosestPoint(***x As Double*, *y As Double*, *ParamOffset As Double***)** As Boolean

Description

Member of Segment

The **FindClosestPoint** method finds the point along a segment that is closest to a specified point

Parameter	Description
x	Specifies the x-coordinate of the point
y	Specifies the y-coordinate of the point
ParamOffset	Specifies the value of the parametric offset

Copyright 2014 Corel Corporation. All rights reserved.

Segment.FindParamOffset

Function **FindParamOffset(***AbsoluteOffset As Double***,** *ParamOffset As Double***, [***Remainder As Double***])** As Boolean

Description

Member of Segment

The **FindParamOffset** method returns the parametric offset for a specified absolute offset.

If the segment is shorter than the specified offset, the function returns **False**, and the remainder of the offset is returned in the **Remainder** parameter. Otherwise, the function returns **True**, and the **ParamOffset** parameter returns the parametric offset for the segment.

Parameter	Description
AbsoluteOffset	Specifies the absolute offset value
ParamOffset	Specifies the value of the parametric offset
Remainder	Specifies the remainder. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example duplicates a shape and distributes it along a path. The shape and the path must be selected, and the path must be selected last.

```
Sub Test()
 Dim sr As ShapeRange
 Dim sPath As Shape, sShape As Shape, sWork As Shape
 Dim dWidth As Double, Offset As Double, Rest As Double, t As Double
 Dim x As Double, y As Double, a As Double, sx As Double, sy As Double
 Dim seg As Segment
 Set sr = ActiveSelectionRange
 If sr.Count <> 2 Then
  MsgBox "Please select two shapes", vbCritical
  Exit Sub
 End If
 If sr(1).Type <> cdrCurveShape Then
  MsgBox "Last selected shape must be a curve", vbCritical
  Exit Sub
 End If
 Set sPath = sr(1)
 Set sShape = sr(2)
 ActiveDocument.ReferencePoint = cdrCenter
 dWidth = sShape.SizeWidth
 sShape.GetPosition sx, sy
 Offset = dWidth / 2
 For Each seg In sPath.Curve.Segments
  While seg.FindParamOffset(Offset, t, Rest)
   seg.GetPointPositionAt x, y, t, cdrParamSegmentOffset
   a = seg.GetTangentAt(t, cdrParamSegmentOffset)
   Set sWork = sShape.Duplicate(x - sx, y - sy)
   sWork.Rotate a
   Offset = Offset + dWidth
  Wend
  Offset = Rest
 Next seg
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.FindParamOffsetAtPoint

Function **FindParamOffsetAtPoint(***x As Double*, *y As Double*, *ParamOffset As Double*, **[**HotArea As Double = -1**])** As Boolean

Description

Member of Segment

The **FindParamOffsetAtPoint** method finds the Bézier parameter along a segment that corresponds to a specified point.

Parameter	Description
x	Specifies the x-coordinate of the point
y	Specifies the y-coordinate of the point
ParamOffset	Specifies the value of the parametric offset
HotArea	Specifies the range in which to search

Copyright 2014 Corel Corporation. All rights reserved.

Segment.GetAbsoluteOffset

Function **GetAbsoluteOffset(***ParamOffset As Double***)** As Double

Description

Member of Segment

The **GetAbsoluteOffset** method returns the distance of a specified point from the beginning of a segment, thus effectively converting the parametric offset to an absolute offset value.

Parameter	Description
ParamOffset	Specifies the parametric offset value of the segment

VBA example

The following VBA example displays the distance of a point, with a parametric offset **0.5**, from the beginning of the first segment of the active curve.

```
Sub Test()
 MsgBox ActiveShape.Curve.Segments(1).GetAbsoluteOffset(0.5)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.GetBendPoints

Function **GetBendPoints(***Offset1 As Double***,** *Offset2 As Double***, [**OffsetType As cdrSegmentOffsetType = cdrParamSegmentOffset**])** As Long

Description

Member of Segment

The **GetBendPoints** method returns the number of bend points in a curve segment. A bend point is the offset where a curve segment bends (that is, where it changes its curvature from positive to negative). There can be a maximum of two bend points per segment, and possibly none.

Parameter	Description
Offset1	Specifies the offset, in document units, of the first bend point
Offset2	Specifies the offset, in document units, of the second bend point
OffsetType	Specifies the type of offset of the point on the curve's subpath, and returns cdrSegmentOffsetType. This parameter is optional, and its default value is cdrParamSegmentOffset (**2**).

VBA example

The following VBA example marks, with small circles, all bend points in the selected curve.

```
Sub Test()
Dim seg As Segment
Dim t1 As Double, t2 As Double, n As Long
For Each seg In ActiveShape.Curve.Segments
n = seg.GetBendPoints(t1, t2)
If n > 1 Then MarkPoint seg, t2
If n > 0 Then MarkPoint seg, t1
Next seg
End Sub
Private Sub MarkPoint(seg As Segment, t As Double)
Dim x As Double, y As Double
Dim s As Shape
seg.GetPointPositionAt x, y, t
Set s = ActiveLayer.CreateEllipse2(x, y, 0.03)
s.Fill.UniformColor.RGBAssign 255, 255, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.GetBoundingBox

Function **GetBoundingBox(***x As Double*, *y As Double*, *Width As Double*, *Height As Double***)** As Boolean

Description

Member of Segment

The **GetBoundingBox** method returns the bounding rectangle around a segment.

Parameter	Description
x	Specifies the x-coordinate
y	Specifies the y-coordinate
Width	Specifies the width of the bounding box
Height	Specifies the height of the bounding box

Copyright 2014 Corel Corporation. All rights reserved.

Segment.GetCopy

Function **GetCopy()** As Curve

Description

Member of Segment

The **GetCopy** method returns a copy of the active segment as a separate curve.

VBA example

The following VBA example creates a curve and copies its second segment to form a second curve. It then creates another shape from the second curve.

```
Sub Test()
 Dim s As Shape, s2 As Shape
 Dim sp As SubPath
 Dim crv As Curve, crv2 As Curve
 Set crv = CreateCurve(ActiveDocument)
 ActiveDocument.ReferencePoint = cdrBottomLeft
 Set sp = crv.CreateSubPath(1, 1)
 sp.AppendLineSegment 1, 1
 sp.AppendCurveSegment 3, 3
 sp.AppendCurveSegment 5, 1
 sp.AppendCurveSegment 6, 4
 sp.AppendCurveSegment 8, 2
 sp.AppendLineSegment 10, 5
 sp.Nodes(2).Type = cdrSmoothNode
 sp.Nodes(3).Type = cdrSmoothNode
 sp.Nodes(4).Type = cdrSymmetricalNode
 sp.Nodes(5).Type = cdrSmoothNode
 Set s = ActiveLayer.CreateCurve(crv)
 Set crv2 = s.Curve.Segments(2).GetCopy
 Set s2 = ActiveLayer.CreateCurve(crv2)
 s2.Move 0, 2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.GetCurvatureAt

Function **GetCurvatureAt([**Offset As Double = 0.5**], [**OffsetType As cdrSegmentOffsetType = cdrParamSegmentOffset**])** As Double

Description

Member of Segment

The **GetCurvatureAt** method returns a numerical value that indicates the curvature of a segment at a given point. The curvature value is the inverse of the curvature radius and depends on the current document units.

Parameter	Description
Offset	Specifies the offset, in document units, of the point on a segment's subpath. This parameter is optional, and its default value is **0.5**.
OffsetType	Specifies the type of offset. This parameter is optional, and its default value is cdrParamSegmentOffset (**2**).

VBA example

The following VBA example draws a circle so that it touches the selected curve at the point that represents **25**% of its length. This circle has the same curvature as the curve at this point; that is, it shows the curvature radius.

```
Sub Test()
Dim c As Double, r As Double
Dim x As Double, y As Double, pa As Double
Dim seg As Segment
Set seg = ActiveShape.Curve.Segments(1)
c = seg.GetCurvatureAt(0.25, cdrRelativeSegmentOffset)
If Abs(c) < 0.00001 Then
MsgBox "The segment is almost straight at this point", vbCritical
Exit Sub
End If
seg.GetPointPositionAt x, y, 0.25, cdrRelativeSegmentOffset
pa = seg.GetPerpendicularAt(0.25, cdrRelativeSegmentOffset)
pa = pa * 3.1415926 / 180
r = 1 / c
x = x + r * Cos(pa)
y = y + r * Sin(pa)
ActiveLayer.CreateEllipse2 x, y, r
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.GetCurveSpeedAt

Function **GetCurveSpeedAt([**Offset As Double = 0.5**], [**OffsetType As cdrSegmentOffsetType = cdrParamSegmentOffset**])** As Double

Description

Member of Segment

The **GetCurveSpeedAt** method returns a value that indicates how fast the curvature changes at a specified point. A value close to **0** means that the curvature is steady — for example, in a circle. A value greater than **0** means that the curvature increases — for example, in a spiral. A value of less than **0** value means that the curvature decreases — for example, in an unwinding spiral.

Parameter	Description
Offset	Specifies the offset, in document units, of the point on the segment's subpath. This parameter is optional, and its default value is **0.5**.
OffsetType	Specifies the offset type of the point. This parameter is optional, and its default value is cdrParamSegmentOffset (**2**).

VBA example

The following VBA example displays how fast the curvature changes in the middle of the first segment of the selected curve.

```
Sub Test()
 Dim c As Double
 Dim seg As Segment
 Set seg = ActiveShape.Curve.Segments(1)
 c = seg.GetCurveSpeedAt(0.5, cdrRelativeSegmentOffset)
 If Abs(c) < 0.01 Then
  MsgBox "Curvature is steady: " & c
 Else
  If c > 0 Then
   MsgBox "Curvature is increasing: " & c
  Else
   MsgBox "Curvature is decreasing: " & c
  End If
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.GetEndingControlPointPosition

Sub **GetEndingControlPointPosition(***PositionX As Double*, *PositionY As Double***)**

Description

Member of Segment

The **GetEndingControlPointPosition** method returns the position of the ending control point of a segment.

Parameter	Description
PositionX	Specifies the horizontal position of the control point
PositionY	Specifies the vertical position of the control point

VBA example

The following VBA example creates a curve and sets the ending control point of the last segment to the same position as the ending control point of the second segment.

```
Sub Test()
 Dim s As Shape, s2 As Shape
 Dim sp As SubPath
 Dim crv As Curve, crv2 As Curve
 Dim seg As Segment, seg2 As Segment
 Dim x As Double, y As Double
 Set crv = CreateCurve(ActiveDocument)
 ActiveDocument.ReferencePoint = cdrBottomLeft
 Set sp = crv.CreateSubPath(1, 1)
 sp.AppendLineSegment 1, 1
 sp.AppendCurveSegment 3, 3
 sp.AppendCurveSegment 5, 1
 sp.AppendCurveSegment 6, 4
 sp.Nodes(2).Type = cdrSmoothNode
 sp.Nodes(3).Type = cdrSmoothNode
 Set s = ActiveLayer.CreateCurve(crv)
 Set seg = ActiveShape.Curve.Segments(2)
 seg.GetEndingControlPointPosition x, y
 Set seg2 = ActiveShape.Curve.Segments(ActiveShape.Curve.Segments.Count)
 seg2.SetEndingControlPointPosition x, y
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.GetIntersections

Function **GetIntersections(**Target As Segment**, [**OffsetType As cdrSegmentOffsetType = cdrParamSegmentOffset**])** As CrossPoints

Description

Member of Segment

The **GetIntersections** method finds all points of intersection between two segments.

Parameter	Description
Target	Specifies the second object
OffsetType	Specifies the type of offset of the point on the curve's subpath, and returns cdrSegmentOffsetType. This parameter is optional, and its default value is cdrParamSegmentOffset (**2**).

VBA example

The following VBA example displays the number of times the first segment of the first two subpaths of the selected curve intersect, and it marks each intersection point with a small circle.

```
Sub Test()
 Dim seg1 As Segment, seg2 As Segment
 Dim cps As CrossPoints, cp As CrossPoint
 Dim x As Double, y As Double
 If ActiveShape Is Nothing Then
  MsgBox "Nothing selected", vbCritical
  Exit Sub
 End If
 If ActiveShape.Type <> cdrCurveShape Then
  MsgBox "Select a curve", vbCritical
  Exit Sub
 End If
 If ActiveShape.Curve.Subpaths.Count < 2 Then
  MsgBox "The curve must have 2 subpaths", vbCritical
  Exit Sub
 End If
 Set seg1 = ActiveShape.Curve.Subpaths(1).Segments(1)
 Set seg2 = ActiveShape.Curve.Subpaths(2).Segments(1)
 Set cps = seg1.GetIntersections(seg2)
 For Each cp In cps
  ActiveLayer.CreateEllipse2 cp.PositionX, cp.PositionY, 0.05
 Next cp
 MsgBox cps.Count & " intersection point(s) found"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.GetPeaks

Function **GetPeaks(***Angle As Double***,** *Offset1 As Double***,** *Offset2 As Double***, [**OffsetType As cdrSegmentOffsetType = cdrParamSegmentOffset**])** As Long

Description

Member of Segment

The **GetPeaks** method returns the number of points where a tangent at a specified angle can touch a curve segment. A segment can have up to two peaks.

Parameter	Description
Angle	Specifies the angle, measured in degrees
Offset1	Specifies the offset, in document units, of the first tangent from the beginning of the curve
Offset2	Specifies the offset, in document units, of the second tangent from the beginning of the curve
OffsetType	Specifies the type of offset of the point on the curve's subpath, and returns cdrSegmentOffsetType. This parameter is optional, and its default value is cdrParamSegmentOffset (**2**).

VBA example

The following VBA example marks the points on a curve through which tangents can be drawn at 30°.

```
Sub Test()
Const Angle As Double = 30
Dim seg As Segment
Dim t1 As Double, t2 As Double, n As Long
For Each seg In ActiveShape.Curve.Segments
n = seg.GetPeaks(Angle, t1, t2)
If n > 1 Then MarkPoint seg, t2, Angle
If n > 0 Then MarkPoint seg, t1, Angle
Next seg
End Sub
Private Sub MarkPoint(seg As Segment, t As Double, Angle As Double)
Dim x As Double, y As Double
Dim dx As Double, dy As Double
Dim s As Shape, a As Double
a = Angle * 3.1415926 / 180
dx = 1.5 * Cos(a)
dy = 1.5 * Sin(a)
seg.GetPointPositionAt x, y, t, cdrParamSegmentOffset
ActiveLayer.CreateLineSegment x + dx, y + dy, x - dx, y - dy
Set s = ActiveLayer.CreateEllipse2(x, y, 0.05)
s.Fill.UniformColor.RGBAssign 255, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.GetPerpendicularAt

Function **GetPerpendicularAt([**Offset As Double = 0.5**], [**OffsetType As cdrSegmentOffsetType = cdrParamSegmentOffset**])** As Double

Description

Member of Segment

The **GetPerpendicularAt** method returns the angle of the perpendicular at a specified point on a curve segment.

Parameter	Description
Offset	Specifies the offset, in document units, from the beginning of a segment's subpath. This parameter is optional, and its default value is **0.5**.
OffsetType	Specifies the type of offset of the point on the curve's subpath, and returns cdrSegmentOffsetType. This parameter is optional, and its default value is cdrParamSegmentOffset (**2**).

VBA example

The following VBA example draws perpendicular and tangent vectors for several points uniformly distributed along the segments of the selected curve.

```
Sub Test()
Dim seg As Segment
Dim t As Double
For Each seg In ActiveShape.Curve.Segments
For t = 0 To 10 Step 2
MarkPoint seg, t / 10
Next t
Next seg
End Sub
Private Sub MarkPoint(seg As Segment, t As Double)
Dim x As Double, y As Double
Dim dx As Double, dy As Double
Dim a1 As Double, a2 As Double
seg.GetPointPositionAt x, y, t, cdrRelativeSegmentOffset
a1 = seg.GetTangentAt(t, cdrRelativeSegmentOffset) ' * 3.1415926 / 180
a2 = seg.GetPerpendicularAt(t, cdrRelativeSegmentOffset) * 3.1415926 / 180
dx = 0.5 * Cos(a1)
dy = 0.5 * Sin(a1)
With ActiveLayer.CreateLineSegment(x, y, x + dx, y + dy)
.Outline.EndArrow = ArrowHeads(1)
End With
dx = 0.5 * Cos(a2)
dy = 0.5 * Sin(a2)
With ActiveLayer.CreateLineSegment(x, y, x + dx, y + dy)
.Outline.EndArrow = ArrowHeads(1)
End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.GetPointPositionAt

Sub **GetPointPositionAt**(*x As Double*, *y As Double*, **[**Offset As Double = 0.5**]**, **[**OffsetType As cdrSegmentOffsetType = cdrParamSegmentOffset**])**

Description

Member of Segment

The **GetPointPositionAt** method returns the coordinates of a point located on a segment.

Parameter	Description
x	Specifies the horizontal position of the point on the segment's subpath. The x-coordinate is measured in document units.
y	Specifies the vertical position of the point on the segment's subpath. The y-coordinate is measured in document units.
Offset	Specifies the offset, in document units, from the beginning of the segment's subpath. This parameter is optional, and its default value is **0.5**.
OffsetType	Specifies the offset type of the point on the curve's subpath, and returns cdrSegmentOffsetType. This parameter is optional, and its default value is cdrParamSegmentOffset (**2**).

VBA example

Here is a code example:

```
Sub GetPointPositionAt_Sample()
Dim s1 As Shape
Set s1 = ActiveLayer.CreateLineSegment(1.698224, 8.796287, 3.094059, 8.22337)
s1.Outline.SetProperties 0.1
'Someone could trace a constellation
'For this example we created Ursa Major using the code below
Dim crv As Curve
Set crv = ActiveDocument.CreateCurve
With crv.CreateSubPath(1.698224, 8.796287)
.AppendLineSegment 3.094059, 8.22337
.AppendLineSegment 3.583642, 7.317118
.AppendLineSegment 4.229476, 6.317118
.AppendLineSegment 6.239894, 5.306701
.AppendLineSegment 5.364894, 4.348366
.AppendLineSegment 3.885724, 5.317118
.AppendLineSegment 4.229476, 6.317118
End With
s1.Curve.CopyAssign crv
'This portion of the sample code could be run to
'automatically create the position of each star in the constellation
Dim sStarPosition As Shape
Dim x As Double, y As Double
Dim sg As Segment
For Each sg In ActiveShape.Curve.Segments
sg.GetPointPositionAt x, y, 0.01, cdrAbsoluteSegmentOffset
Set sStarPosition = ActiveLayer.CreateEllipse2(x, y, 0.1)
sStarPosition.Fill.UniformColor.BWAssign True
Next sg
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.GetPolyline

Function **GetPolyline([***CurvePrecision As Long***])** As Curve

Description

Member of Segment

The **GetPolyline** method returns a curve consisting of line segments approximating the current segment.

Parameter	Description
CurvePrecision	Specifies the precision level of the curve. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

Segment.GetStartingControlPointPosition

Sub **GetStartingControlPointPosition(***PositionX As Double***,** *PositionY As Double***)**

Description

Member of Segment

The **GetStartingControlPointPosition** method returns the position of the starting control point.

Parameter	Description
PositionX	Specifies the horizontal position
PositionY	Specifies the vertical position

VBA example

The following VBA example creates a curve, and it sets the starting control point of the last segment to the same position as the starting control point for the second segment.

```
Sub Test()
 Dim s As Shape, s2 As Shape
 Dim sp As SubPath
 Dim crv As Curve, crv2 As Curve
 Dim seg As Segment, seg2 As Segment
 Dim x As Double, y As Double
 Set crv = CreateCurve(ActiveDocument)
 ActiveDocument.ReferencePoint = cdrBottomLeft
 Set sp = crv.CreateSubPath(1, 1)
 sp.AppendLineSegment 1, 1
 sp.AppendCurveSegment 3, 3
 sp.AppendCurveSegment 5, 1
 sp.AppendCurveSegment 6, 4
 sp.Nodes(2).Type = cdrSmoothNode
 sp.Nodes(3).Type = cdrSmoothNode
 Set s = ActiveLayer.CreateCurve(crv)
 Set seg = ActiveShape.Curve.Segments(2)
 seg.GetStartingControlPointPosition x, y
 Set seg2 = ActiveShape.Curve.Segments(ActiveShape.Curve.Segments.Count)
 seg2.SetStartingControlPointPosition x, y
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.GetTangentAt

Function **GetTangentAt([**Offset As Double = 0.5**], [**OffsetType As cdrSegmentOffsetType = cdrParamSegmentOffset**])** As Double

Description

Member of Segment

The **GetTangentAt** method returns the angle of the tangent at a specified point on a curve segment.

Parameter	Description
Offset	Specifies the offset, in document units, from the beginning of the segment's subpath. This parameter is optional, and its default value is **0.5**.
OffsetType	Specifies the offset type of the point on the curve's subpath, and returns cdrSegmentOffsetType. This parameter is optional, and its default value is cdrParamSegmentOffset (**2**).

VBA example

The following VBA example draws perpendicular and tangent vectors for several points uniformly distributed along the segments of the selected curve.

```
Sub Test()
Dim seg As Segment
Dim t As Double
For Each seg In ActiveShape.Curve.Segments
For t = 0 To 10 Step 2
MarkPoint seg, t / 10
Next t
Next seg
End Sub
Private Sub MarkPoint(seg As Segment, t As Double)
Dim x As Double, y As Double
Dim dx As Double, dy As Double
Dim a1 As Double, a2 As Double
seg.GetPointPositionAt x, y, t, cdrRelativeSegmentOffset
a1 = seg.GetTangentAt(t, cdrRelativeSegmentOffset) ' * 3.1415926 / 180
a2 = seg.GetPerpendicularAt(t, cdrRelativeSegmentOffset) * 3.1415926 / 180
dx = 0.5 * Cos(a1)
dy = 0.5 * Sin(a1)
With ActiveLayer.CreateLineSegment(x, y, x + dx, y + dy)
.Outline.EndArrow = ArrowHeads(1)
End With
dx = 0.5 * Cos(a2)
dy = 0.5 * Sin(a2)
With ActiveLayer.CreateLineSegment(x, y, x + dx, y + dy)
.Outline.EndArrow = ArrowHeads(1)
End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.Index

Property **Index** As Long

Description

Member of Segment

The **Index** property returns the index number of a segment within its subpath.

- The **Index** and AbsoluteIndex properties return the same value if the segment belongs to the first subpath of the curve.

The **Index** property returns a read-only value.

VBA example

The following VBA example loops through all segments of each subpath and prints each segment's **Index** and **AbsoluteIndex** property in the **Intermediate** window of the Macro Editor.

```
Sub Test()
 Dim s As Shape
 Dim sp As SubPath
 Dim seg As Segment
 Set s = ActiveShape
 If s.Type = cdrCurveShape Then
  For Each sp In s.Curve.Subpaths
   For Each seg In sp.Segments
    Debug.Print seg.Index, seg.AbsoluteIndex
   Next seg
  Next sp
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.IsRectOnEdge

Function **IsRectOnEdge(***x1 As Double*, *y1 As Double*, *x2 As Double*, *y2 As Double***)** As Boolean

Description

Member of Segment

The **IsRectOnEdge** method returns **True** if a specified rectangle intersects a specified segment.

Parameter	Description
x1	Specifies the first x-coordinate
y1	Specifies the first y-coordinate
x2	Specifies the second x-coordinate
y2	Specifies the second y-coordinate

Copyright 2014 Corel Corporation. All rights reserved.

Segment.Length

Property **Length** As Double

Description

Member of Segment

The **Length** property returns the length, in document units, of a segment.

The **Length** property returns a read-only value.

VBA example

The following VBA example displays the length of the first segment of the selected curve.

```
Sub Test()
 MsgBox ActiveShape.Curve.Segments(1).Length
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.Next

Function **Next()** As Segment

Description

Member of Segment

The **Next** method returns the next segment on a subpath. If the last segment is reached and the subpath is not closed, **Nothing** is returned

VBA example

The following VBA example creates a triangle, converts the three segments to curves, and changes the type of the bottom nodes to smooth, producing a shape resembling a droplet.

Sub Test()

```
 Dim s As Shape
 Dim seg As Segment
 Set s = ActiveLayer.CreatePolygon(3, 6, 7, 2, 3)
 s.ConvertToCurves
 s.Curve.Nodes.Range(2, 4, 6).Delete
 Set seg = s.Curve.Segments(2)
 seg.Previous.Type = cdrCurveSegment
 seg.Next.Type = cdrCurveSegment
 seg.Type = cdrCurveSegment
 seg.StartNode.Type = cdrSmoothNode
 seg.EndNode.Type = cdrSmoothNode
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.Parent

Property **Parent** As Curve

Description

Member of Segment

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Segment.Previous

Function **Previous()** As Segment

Description

Member of Segment

The **Previous** method returns the previous segment on a subpath. If the first segment is reached and the subpath is not closed, **Nothing** is returned

VBA example

The following VBA example creates a triangle, converts the three segments to curves, and changes the type of the bottom nodes to smooth, producing a shape resembling a droplet.

```
Sub Test()
 Dim s As Shape
 Dim seg As Segment
 Set s = ActiveLayer.CreatePolygon(3, 6, 7, 2, 3)
 s.ConvertToCurves
 s.Curve.Nodes.Range(2, 4, 6).Delete
 Set seg = s.Curve.Segments(2)
 seg.Previous.Type = cdrCurveSegment
 seg.Next.Type = cdrCurveSegment
 seg.Type = cdrCurveSegment
 seg.StartNode.Type = cdrSmoothNode
 seg.EndNode.Type = cdrSmoothNode
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.Selected

Property **Selected** As Boolean

Description

Member of Segment

The **Started** property returns or specifies the selection property of the node controlling the properties of a given segment.

Copyright 2014 Corel Corporation. All rights reserved.

Segment.SetEndingControlPointPosition

Sub **SetEndingControlPointPosition**(*PositionX As Double*, *PositionY As Double*)

Description

Member of Segment

The **SetEndingControlPointPosition** method sets the position of the ending control point for a segment.

Parameter	Description
PositionX	Specifies the horizontal position
PositionY	Specifies the vertical position

VBA example

The following VBA example creates a curve, and it sets the ending control point of the last segment to the same position as the ending control point of the second segment.

```
Sub Test()
 Dim s As Shape, s2 As Shape
 Dim sp As SubPath
 Dim crv As Curve, crv2 As Curve
 Dim seg As Segment, seg2 As Segment
 Dim x As Double, y As Double
 Set crv = CreateCurve(ActiveDocument)
 ActiveDocument.ReferencePoint = cdrBottomLeft
 Set sp = crv.CreateSubPath(1, 1)
 sp.AppendLineSegment 1, 1
 sp.AppendCurveSegment 3, 3
 sp.AppendCurveSegment 5, 1
 sp.AppendCurveSegment 6, 4
 sp.Nodes(2).Type = cdrSmoothNode
 sp.Nodes(3).Type = cdrSmoothNode
 Set s = ActiveLayer.CreateCurve(crv)
 Set seg = ActiveShape.Curve.Segments(2)
 seg.GetEndingControlPointPosition x, y
 Set seg2 = ActiveShape.Curve.Segments(ActiveShape.Curve.Segments.Count)
 seg2.SetEndingControlPointPosition x, y
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.SetStartingControlPointPosition

Sub **SetStartingControlPointPosition(***PositionX As Double***,** *PositionY As Double***)**

Description

Member of Segment

The **SetStartingControlPointPosition** method sets the position of the starting control point for a segment.

Parameter	Description
PositionX	Specifies the horizontal position
PositionY	Specifies the vertical position

VBA example

The following VBA example creates a curve, and it sets the starting control point of the last segment to the same position as the starting control point for the second segment.

```
Sub Test()
 Dim s As Shape, s2 As Shape
 Dim sp As SubPath
 Dim crv As Curve, crv2 As Curve
 Dim seg As Segment, seg2 As Segment
 Dim x As Double, y As Double
 Set crv = CreateCurve(ActiveDocument)
 ActiveDocument.ReferencePoint = cdrBottomLeft
 Set sp = crv.CreateSubPath(1, 1)
 sp.AppendLineSegment 1, 1
 sp.AppendCurveSegment 3, 3
 sp.AppendCurveSegment 5, 1
 sp.AppendCurveSegment 6, 4
 sp.Nodes(2).Type = cdrSmoothNode
 sp.Nodes(3).Type = cdrSmoothNode
 Set s = ActiveLayer.CreateCurve(crv)
 Set seg = ActiveShape.Curve.Segments(2)
 seg.GetStartingControlPointPosition x, y
 Set seg2 = ActiveShape.Curve.Segments(ActiveShape.Curve.Segments.Count)
 seg2.SetStartingControlPointPosition x, y
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.StartingControlPointAngle

Property **StartingControlPointAngle** As Double

Description

Member of Segment

The **StartingControlPointAngle** property returns or specifies the angle, in degrees, of the control-point vector beginning of a segment.

VBA example

The following VBA example constrains control point angles to increments of 45°. Each control-point vector is rotated to the closest angle that is a multiple of 45°.

```
Sub Test()
 Dim s As Shape
 Dim seg As Segment
 Set s = ActiveShape
 If s.Type = cdrCurveShape Then
  For Each seg In s.Curve.Segments
   If seg.Type = cdrCurveSegment Then
    seg.StartingControlPointAngle = Constrain(seg.StartingControlPointAngle)
    seg.EndingControlPointAngle = Constrain(seg.EndingControlPointAngle)
   End If
  Next seg
 End If
End Sub
Private Function Constrain(a As Double) As Double
 Constrain = Fix(a / 45 + 0.5) * 45
End Function
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.StartingControlPointLength

Property **StartingControlPointLength** As Double

Description

Member of Segment

The **StartingControlPointLength** property returns or specifies the length, in document units, of the control-point vector beginning of a curve.

VBA example

The following VBA example sets the starting and ending control-point length for the first segment in the active shape.

```
Sub App()
 With ActiveShape.Curve.Segments(1)
  .StartingControlPointLength = 5
  .EndingControlPointLength = 5
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.StartingControlPointX

Property **StartingControlPointX** As Double

Description

Member of Segment

The **StartingControlPointX** property returns or specifies the x-coordinate of the starting control point of a curve segment. This property is measured in document units.

VBA example

The following VBA example marks, with a small circle, the position of each control point of the selected curve.

```
Sub Test()
 Dim s As Shape
 Dim seg As Segment
 Set s = ActiveShape
 If s.Type = cdrCurveShape Then
  For Each seg In s.Curve.Segments
   If seg.Type = cdrCurveSegment Then
    ActiveLayer.CreateEllipse2 seg.StartingControlPointX, seg.StartingControlPointY, 0.02
    ActiveLayer.CreateEllipse2 seg.EndingControlPointX, seg.EndingControlPointY, 0.02
   End If
  Next seg
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.StartingControlPointY

Property **StartingControlPointY** As Double

Description

Member of Segment

The **StartingControlPointY** property returns or specifies the y-coordinate of the starting control-point of a curve segment. This property is measured in document units.

VBA example

The following VBA example marks, with a small circle, the position of each control point of the selected curve.

```
Sub Test()
 Dim s As Shape
 Dim seg As Segment
 Set s = ActiveShape
 If s.Type = cdrCurveShape Then
  For Each seg In s.Curve.Segments
   If seg.Type = cdrCurveSegment Then
    ActiveLayer.CreateEllipse2 seg.StartingControlPointX, seg.StartingControlPointY, 0.02
    ActiveLayer.CreateEllipse2 seg.EndingControlPointX, seg.EndingControlPointY, 0.02
   End If
  Next seg
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.StartNode

Property **StartNode** As Node

Description

Member of Segment

The **StartNode** property returns the starting node object of a segment.

The **StartNode** property returns a read-only value.

VBA example

The following VBA example re-creates the selected curve by creating each segment as a separate shape.

```
Sub Test()
 Dim seg As Segment
 If ActiveShape Is Nothing Then Exit Sub
 If ActiveShape.Type <> cdrCurveShape Then Exit Sub
 For Each seg In ActiveShape.Curve.Segments
  Select Case seg.Type
   Case cdrLineSegment
    ActiveLayer.CreateLineSegment seg.StartNode.PositionX, seg.StartNode.PositionY, _
      seg.EndNode.PositionX, seg.EndNode.PositionY
   Case cdrCurveSegment
    ActiveLayer.CreateCurveSegment seg.StartNode.PositionX, seg.StartNode.PositionY, _
      seg.EndNode.PositionX, seg.EndNode.PositionY, seg.StartingControlPointLength, _
      seg.StartingControlPointAngle, seg.EndingControlPointLength, seg.EndingControlPointAngle
  End Select
 Next seg
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.SubPath

Property **SubPath** As SubPath

Description

Member of Segment

The **SubPath** property returns the SubPath object to which a segment belongs.

The **SubPath** property returns a read-only value.

VBA example

The following VBA example creates a curve with two subpaths. The subpath that contains the seventh segment is copied as a curve, and a shape is then created from that curve.

```
Sub Test()
 Dim s As Shape, s2 As Shape
 Dim sp As SubPath, sp2 As SubPath
 Dim crv As Curve, crv2 As Curve
 Set crv = CreateCurve(ActiveDocument)
 ActiveDocument.ReferencePoint = cdrBottomLeft
 Set sp = crv.CreateSubPath(1, 1)
 sp.AppendLineSegment 1, 1
 sp.AppendCurveSegment 3, 3
 sp.AppendCurveSegment 5, 1
 sp.AppendCurveSegment 6, 4
 sp.Nodes(2).Type = cdrSmoothNode
 sp.Nodes(3).Type = cdrSmoothNode
 Set sp2 = crv.CreateSubPath(6, 4)
 sp2.AppendLineSegment 5, 7
 sp2.AppendCurveSegment 3, 5
 sp2.AppendCurveSegment 1, 7
 sp2.Nodes(3).Type = cdrSmoothNode
 sp2.Nodes(4).Type = cdrSmoothNode
 Set s = ActiveLayer.CreateCurve(crv)
 Set sp2 = s.Curve.Segments(7).SubPath
 Set crv2 = sp2.GetCopy
 Set s2 = ActiveLayer.CreateCurve(crv2)
 s2.Move 0, 1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.SubPathIndex

Property SubPathIndex As Long

Description

Member of Segment

The **SubPathIndex** property returns the index value of the subpath to which the current segment belongs.

The **SubPathIndex** property returns a read-only value.

VBA example

The following VBA example re-creates each segment of the selected curve as a separate shape and gives each one a different outline color (depending on the subpath to which the original segment belonged).

```
Sub Test()
 Dim s As Shape
 Dim seg As Segment
 If ActiveShape Is Nothing Then Exit Sub
 If ActiveShape.Type <> cdrCurveShape Then Exit Sub
 For Each seg In ActiveShape.Curve.Segments
  Select Case seg.Type
   Case cdrLineSegment
    Set s = ActiveLayer.CreateLineSegment(seg.StartNode.PositionX, seg.StartNode.PositionY, _
      seg.EndNode.PositionX, seg.EndNode.PositionY)
   Case cdrCurveSegment
    Set s = ActiveLayer.CreateCurveSegment(seg.StartNode.PositionX, seg.StartNode.PositionY, _
      seg.EndNode.PositionX, seg.EndNode.PositionY, seg.StartingControlPointLength,
      seg.StartingControlPointAngle, seg.EndingControlPointLength, seg.EndingControlPointAngle)
  End Select
  s.Outline.Color = ActivePalette.Color(seg.SubPathIndex + 12)
 Next seg
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segment.Type

Property **Type** As cdrSegmentType

Description

Member of Segment

The **Type** property returns or specifies the type (line or curve) of the segment.

- This property can be used to convert the segment type between line and curve.

This property returns cdrSegmentType.

VBA example

The following VBA example counts the number of curve and line segments in the selected curve shape.

```
Sub Test()
 Dim seg As Segment, ls As Long, cs As Long
 If ActiveShape Is Nothing Then Exit Sub
 If ActiveShape.Type <> cdrCurveShape Then Exit Sub
 ls = 0
 cs = 0
 For Each seg In ActiveShape.Curve.Segments
  Select Case seg.Type
   Case cdrLineSegment
    ls = ls + 1
   Case cdrCurveSegment
    cs = cs + 1
  End Select
 Next seg
 MsgBox "The current curve has " & ActiveShape.Curve.Segments.Count & _
   " segments including:" & vbCr & _
   "Line segments: " & ls & vbCr & _
   "Curve segments: " & cs
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange

Properties Methods

Description

The **SegmentRange** class represents an array (or range) of curve segments (or Segment objects).

- You can create a **SegmentRange** object by using the **New** keyword in Visual Basic.

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.Add

Sub **Add(**Segment As Segment**)**

Description

Member of SegmentRange

The **Add** method adds a segment to a segment range.

Parameter	Description
Segment	Specifies the segment to be added

VBA example

The following VBA example adds an extra node to the middle of each segment longer than **1**", dividing it into two separate segments.

```
Sub Test()
 Dim sgr As New SegmentRange
 Dim seg As Segment
 Do
  sgr.RemoveAll
  For Each seg In ActiveShape.Curve.Segments
   If seg.Length > 1 Then sgr.Add seg
  Next seg
  If sgr.Count <> 0 Then sgr.AddNode
 Loop While sgr.Count <> 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.AddNode

Sub **AddNode()**

Description

Member of SegmentRange

The **AddNode** method adds a new node to the middle of each segment in a segment range.

VBA example

The following VBA example adds a node to the middle of each segment in the selected curve.

```
Sub Test()
 ActiveShape.Curve.Segments.All.AddNode
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.AddRange

Sub **AddRange(**SegmentRange As SegmentRange**)**

Description

Member of SegmentRange

The **AddRange** method adds segments from a specified segment range to the active range, combining the two ranges.

Parameter	Description
SegmentRange	Specifies the range of segment items to add to the active segment range

VBA example

The following VBA example creates a text object containing the letter **B** and converts it to curves. Then it creates a range containing the segments from the second and third subpaths (that is, the inner “holes” in the letter **B**) and converts those segments to lines.

```
Sub Test()
 Dim s As Shape
 Dim sgr As SegmentRange
 Set s = ActiveLayer.CreateArtisticText(0, 0, "B")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 72
 End With
 s.ConvertToCurves
 Set sgr = s.Curve.Subpaths(2).Segments.All
 sgr.AddRange s.Curve.Subpaths(3).Segments.All
 sgr.SetType cdrLineSegment
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.AddToSelection

Sub **AddToSelection()**

Description

Member of SegmentRange

The **AddToSelection** method adds the nodes that control the properties of the segments in the segment range to a selection.

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.Application

Property **Application** As Application

Description

Member of SegmentRange

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.Count

Property **Count** As Long

Description

Member of SegmentRange

The **Count** property returns the number of segments in a segment range.

The **Count** property returns a read-only value.

VBA example

The following VBA example displays the number of curve segments in the selected curve. It then lets you convert all curve segments to lines.

```
Sub Test()
 Dim sgr As New SegmentRange
 Dim seg As Segment
 Dim r As VbMsgBoxResult
 If ActiveShape Is Nothing Then Exit Sub
 If ActiveShape.Type <> cdrCurveShape Then
  MsgBox "Select a curve and try again"
  Exit Sub
 End If
 For Each seg In ActiveShape.Curve.Segments
  If seg.Type = cdrCurveSegment Then sgr.Add seg
 Next seg
 If sgr.Count = 0 Then
  MsgBox "No curve segments found"
 Else
  r = MsgBox(sgr.Count & " curve segments found. Convert them to lines?", vbYesNo)
  If r = vbYes Then
   sgr.SetType cdrLineSegment
  End If
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.CreateSelection

Sub **CreateSelection()**

Description

Member of SegmentRange

The **CreateSelection** method selects all curve nodes that control the properties of the segments in a segment range.

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.FirstSegment

Property **FirstSegment** As Segment

Description

Member of SegmentRange

The **FirstSegment** property returns the first segment in a segment range.

The **FirstSegment** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.Item

Property **Item(***Index As Long***)** As Segment

Description

Member of SegmentRange

The **Item** property returns the specified segment from a segment range.

Item is the default property of the SegmentRange class, and its reference can be omitted when you are accessing items in a segment range. For example, **SegmentRange.Item(2)** is the same as **SegmentRange(2)** — they both reference the second segment-range object in the range.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the segment to return

VBA example

The following VBA example adds a node to the middle of each curve segment in the selected curve.

```
Sub Test()
 Dim sgr As SegmentRange
 Dim n As Node
 Dim i As Long
 Set sgr = ActiveShape.Curve.Segments.All
 For i = sgr.Count To 1 Step -1
  If sgr(i).Type = cdrLineSegment Then sgr.Remove i
  ' Same as: If sgr.Item(i).Type <> cdrLineSegment Then sgr.Remove i
 Next i
 If sgr.Count > 0 Then sgr.AddNode
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.LastSegment

Property **LastSegment** As Segment

Description

Member of SegmentRange

The **LastSegment** property returns the last segment in a segment range.

The **LastSegment** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.Length

Property **Length** As Double

Description

Member of SegmentRange

The **Length** property returns the total length, in document units, of all segments in a segment range.

The **Length** property returns a read-only value.

VBA example

The following VBA example displays the total length of all curve segments in the selected curve.

```
Sub Test()
 Dim sgr As New SegmentRange
 Dim seg As Segment
 For Each seg In ActiveShape.Curve.Segments
  If seg.Type = cdrCurveSegment Then sgr.Add seg
 Next seg
 MsgBox "All curve segments have total length of " & sgr.Length & """"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.NodeRange

Property **NodeRange** As NodeRange

Description

Member of SegmentRange

The **NodeRange** property returns a node range (or NodeRange object) containing all nodes that end segments in the active segment-range object.

The **NodeRange** property returns a read-only value.

VBA example

The following VBA example converts all line segments to curves and changes the type of all segment-ending nodes to smooth.

```
Sub Test()
 Dim sgr As New SegmentRange
 Dim seg As Segment
 For Each seg In ActiveShape.Curve.Segments
  If seg.Type = cdrLineSegment Then sgr.Add seg
 Next seg
 sgr.SetType cdrCurveSegment
 sgr.NodeRange.SetType cdrSmoothNode
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.Parent

Property **Parent** As Curve

Description

Member of SegmentRange

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.Remove

Sub **Remove(***Index As Long***)**

Description

Member of SegmentRange

The **Remove** method removes a specified segment from a segment range without affecting the segment itself.

Parameter	Description
Index	Specifies the segment to be removed

VBA example

The following VBA example highlights each curve segment that is adjacent to a cusp node, using a red stroke.

```
Sub Test()
 Dim s As Shape
 Dim sgr As SegmentRange
 Dim seg As Segment
 Dim i As Long
 Set sgr = ActiveShape.Curve.Segments.All
 For i = sgr.Count To 1 Step -1
  Set seg = sgr(i)
  If seg.Type = cdrLineSegment Then
   sgr.Remove i
  Else
   If seg.StartNode.Type <> cdrCuspNode And seg.EndNode.Type <> cdrCuspNode Then
    sgr.Remove i
   End If
  End If
 Next i
 For Each seg In sgr
  Set s = ActiveLayer.CreateCurveSegment(seg.StartNode.PositionX, seg.StartNode.PositionY, _
   seg.EndNode.PositionX, seg.EndNode.PositionY, _
   seg.StartingControlPointLength, seg.StartingControlPointAngle, _
   seg.EndingControlPointLength, seg.EndingControlPointAngle)
  s.Outline.Width = 0.01
  s.Outline.Color.RGBAssign 255, 0, 0
 Next seg
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.RemoveAll

Sub **RemoveAll()**

Description

Member of SegmentRange

The **RemoveAll** method removes all segments from a segment range without affecting the segments themselves.

VBA example

The following VBA example adds an extra node to the middle of any segment longer than **1**", dividing it into two separate segments.

```
Sub Test()
 Dim sgr As New SegmentRange
 Dim seg As Segment
 Do
  sgr.RemoveAll
  For Each seg In ActiveShape.Curve.Segments
   If seg.Length > 1 Then sgr.Add seg
  Next seg
  If sgr.Count <> 0 Then sgr.AddNode
 Loop While sgr.Count <> 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SegementRange.RemoveFromSelection

Sub **RemoveFromSelection()**

Description

Member of SegmentRange

The **RemoveFromSelection** method removes the nodes that control the properties of the segments in the segment range from a selection.

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.RemoveRange

Sub **RemoveRange(**SegmentRange As SegmentRange**)**

Description

Member of SegmentRange

The **RemoveRange** method removes the segments in a specified range from the current range.

Parameter	Description
SegmentRange	Specifies the segment range to be removed

VBA example

The following VBA example creates a curve and two shape ranges. The first shape range contains all of the curve's segments, and the second range contains only the curved segments of the curve. The second range is then removed from the first range, leaving only the line segments in the first range.

```
Sub Test()
 Dim s As Shape
 Dim n As Node
 Dim sp As SubPath
 Dim crv As Curve
 Dim sg As Segment
 Dim sgr As SegmentRange
 Dim sgr2 As New SegmentRange
 Set crv = CreateCurve(ActiveDocument)
 ActiveDocument.ReferencePoint = cdrBottomLeft
 Set sp = crv.CreateSubPath(-1, 0.2)
 sp.AppendLineSegment 0.5, 1
 sp.AppendCurveSegment 2, 3
 sp.AppendCurveSegment 4, 1
 sp.AppendCurveSegment 5, 4
 sp.AppendCurveSegment 7, 2
 sp.AppendLineSegment 8, 5
 sp.AppendLineSegment 9, 1
 Set s = ActiveLayer.CreateCurve(crv)
 Set sgr = s.Curve.Segments.All
 For Each sg In s.Curve.Segments
  If sg.Type = cdrCurveSegment Then
   sgr2.Add sg
  End If
 Next sg
 sgr.RemoveRange sgr2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.SetType

Sub **SetType(**Type As cdrSegmentType**)**

Description

Member of SegmentRange

The **SetType** method sets the type of segment for all segments in a segment range.

Parameter	Description
Type	Specifies the type of segment for all segments in a segment range. The **Type** parameter accepts a value of cdrSegmentType.

VBA example

The following VBA example converts all segments in the selected shape to curve segments and changes the type of all of its nodes to smooth.

```
Sub Test()
 With ActiveShape.Curve
  .Segments.All.SetType cdrCurveSegment
  .Nodes.All.SetType cdrSmoothNode
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SegmentRange.Type

Property **Type** As cdrSegmentType

Description

Member of SegmentRange

The **Type** property returns a read-only value that is associated with the type of segments in a segment range.

The **Type** property returns a value of cdrSegmentType. If there is a mixture of line and curve segments, a value of cdrMixedSegments is returned.

VBA example

The following VBA example determines whether all segments in the selected shape are curves.

```
Sub Test()
 Dim sgr As SegmentRange
 Dim r As VbMsgBoxResult
 Set sgr = ActiveShape.Curve.Segments.All
 If sgr.Type <> cdrCurveSegment Then
  r = MsgBox("There are some lime segments in the shape." & vbCr & _
   "Do you want to convert them to curves?", vbYesNo)
  If r = vbYes Then sgr.SetType cdrCurveSegment
 Else
  MsgBox "All segments are curves"
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segments

Properties Methods

Description

The **Segments** class represents a collection of segments (or Segment objects) in a curve or subpath.

Copyright 2014 Corel Corporation. All rights reserved.

Segments.All

Function **All()** As SegmentRange

Description

Member of Segments

The **All** method returns a SegmentRange object containing all segments from a Segments collection.

VBA example

The following VBA example converts all curve segments in all curves to linear.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Type = cdrCurveShape Then
   s.Curve.Segments.All.SetType cdrLineSegment
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segments.AllExcluding

Function **AllExcluding(***IndexArray() As Variant***)** As SegmentRange

Description

Member of Segments

The **AllExcluding** method returns a SegmentRange object containing all segments (except for specified segments) from a Segments collection.

- This method accepts a variable number of arguments. It also accepts arrays.

Parameter	Description
IndexArray	Specifies a range of index numbers that identify and group specific segments

VBA example

The following VBA example adds a node to the middle of each curve segment except the first three.

```
Sub Test()
 Dim sgr As SegmentRange
 Set sgr = ActiveShape.Curve.Segments.AllExcluding(1, 2, 3)
 sgr.AddNode
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segments.Application

Property **Application** As Application

Description

Member of Segments

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Segments.Count

Property **Count** As Long

Description

Member of Segments

The **Count** property returns the number of segments in a Segments collection.

The **Count** property returns a read-only value.

VBA example

The following VBA example displays the number of nodes, segments, and subpaths in the active curve.

```
Sub Test()
 Dim crv As Curve
 Set crv = ActiveShape.Curve
 MsgBox "The curve contains:" & vbCr & _
  "Nodes: " & crv.Nodes.Count & vbCr & _
  "Segments: " & crv.Segments.Count & vbCr & _
  "Subpaths: " & crv.Subpaths.Count
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segments.First

Property **First** As Segment

Description

Member of Segments

The **First** property returns the first segment in a Segments collection.

The **First** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Segments.Item

Property **Item(***Index As Long***)** As Segment

Description

Member of Segments

The **Item** property returns a specified segment (or Segment object).

Item is the default property of the Segments class, and its reference can be omitted when you are accessing items in a **Segments** collection. For example, **Segments.Item(2)** is the same as **Segments(2)** — they both reference the second segment object in the collection.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the segment by its index number

VBA example

The following VBA example converts all segments in the curve to curve segments.

```
Sub Test()
 Dim i As Long
 For i = 1 To ActiveShape.Curve.Segments.Count
  ActiveShape.Curve.Segments(i).Type = cdrCurveSegment
 Next i
End Sub
Sub Test()
 Dim seg As Segment
 For Each seg In ActiveShape.Curve.Segments
  seg.Type = cdrCurveSegment
 Next seg
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Segments.Last

Property **Last** As Segment

Description

Member of Segments

The **Last** property returns the last segment in a Segments collection.

The **Last** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Segments.Parent

Property **Parent** As Curve

Description

Member of Segments

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Segments.Range

Function **Range(***IndexArray() As Variant***)** As SegmentRange

Description

Member of Segments

The **Range** method returns a SegmentRange object containing all specified segments from a Segments collection.

- This method accepts a variable number of arguments. It also accepts arrays.

Parameter	Description
IndexArray	Represents index numbers that identify specific segments

VBA example

The following VBA example converts segments 2, 3, and 4 of the selected curve to lines.

```
Sub Test()
 Dim sgr As SegmentRange
 Set sgr = ActiveShape.Curve.Segments.Range(Array(2, 3, 4))
 sgr.SetType cdrLineSegment
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo

Properties

Description

The **SelectionInfo** class represents the settings for a selection.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.Application

Property **Application** As Application

Description

Member of SelectionInfo

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.BlendBottomShape

Property **BlendBottomShape** As Shape

Description

Member of SelectionInfo

The **BlendBottomShape** property returns the bottom shape of the selected blend.

The **BlendBottomShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.BlendPath

Property **BlendPath** As Shape

Description

Member of SelectionInfo

The **BlendPath** property returns the path of a blend.

The **BlendPath** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.BlendTopShape

Property **BlendTopShape** As Shape

Description

Member of SelectionInfo

The **BlendTopShape** returns the top shape of the selected blend.

The **BlendTopShape** returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanApplyBlend

Property **CanApplyBlend** As Boolean

Description

Member of SelectionInfo

The **CanApplyBlend** property returns whether the selected shapes can be blended.

The **CanApplyBlend** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanApplyContour

Property **CanApplyContour** As Boolean

Description

Member of SelectionInfo

The **CanApplyContour** property returns whether the selected shape (or shapes) can be contoured.

The **CanApplyContour** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanApplyDistortion

Property **CanApplyDistortion** As Boolean

Description

Member of SelectionInfo

The **CanApplyDistortion** property returns whether a distortion can be applied to the selected shape (or shapes).

The **CanApplyDistortion** property returns returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanApplyEnvelope

Property **CanApplyEnvelope** As Boolean

Description

Member of SelectionInfo

The **CanApplyEnvelope** property returns whether an envelope can be applied to the selected shape (or shapes).

The **CanApplyEnvelope** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanApplyFill

Property **CanApplyFill** As Boolean

Description

Member of SelectionInfo

The **CanApplyFill** property returns whether the selected shape (or shapes) can have a fill.

The **CanApplyFill** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanApplyFillOutline

Property **CanApplyFillOutline** As Boolean

Description

Member of SelectionInfo

The **CanApplyFillOutline** property returns whether a fill and an outline can be applied to the selected shape.

The **CanApplyFillOutline** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanApplyOutline

Property **CanApplyOutline** As Boolean

Description

Member of SelectionInfo

The **CanApplyOutline** propety returns whether the selected shape (or shapes) can have an outline.

The **CanApplyOutline** propety returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanApplyTransparency

Property **CanApplyTransparency** As Boolean

Description

Member of SelectionInfo

The **CanApplyTransparency** property returns whether a transparency can be applied to the selected shape (or shapes).

The **CanApplyTransparency** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanAssignURL

Property **CanAssignURL** As Boolean

Description

Member of SelectionInfo

The **CanAssignURL** property returns whether a URL can be assigned to the selected shape (or shapes).

The **CanAssignURL** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanClone

Property **CanClone** As Boolean

Description

Member of SelectionInfo

The **CanClone** property returns whether the selected shapes can be cloned.

The **CanClone** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanCloneBlend

Property **CanCloneBlend** As Boolean

Description

Member of SelectionInfo

The **CanCloneBlend** property returns whether the selected blend can be cloned.

The **CanCloneBlend** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanCloneContour

Property **CanCloneContour** As Boolean

Description

Member of SelectionInfo

The **CanCloneContour** property returns whether the selected contour can be cloned.

The **CanCloneContour** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanCloneDropShadow

Property **CanCloneDropShadow** As Boolean

Description

Member of SelectionInfo

The **CanCloneDropShadow** property returns whether the selected drop shadow can be cloned.

The **CanCloneDropShadow** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanCloneExtrude

Property **CanCloneExtrude** As Boolean

Description

Member of SelectionInfo

The **CanCloneExtrude** property returns whether the selected extrusion can be cloned.

The **CanCloneExtrude** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanCopyBlend

Property **CanCopyBlend** As Boolean

Description

Member of SelectionInfo

The **CanCopyBlend** property returns whether the selected blend can be copied.

The **CanCopyBlend** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanCopyContour

Property **CanCopyContour** As Boolean

Description

Member of SelectionInfo

The **CanCopyContour** property returns whether the selected contour can be copied.

The **CanCopyContour** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanCopyDistortion

Property **CanCopyDistortion** As Boolean

Description

Member of SelectionInfo

The **CanCopyDistortion** property returns whether the selected distortion can be copied.

The **CanCopyDistortion** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanCopyDropShadow

Property **CanCopyDropShadow** As Boolean

Description

Member of SelectionInfo

The **CanCopyDropShadow** property returns whether the selected drop shadow can be copied.

The **CanCopyDropShadow** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanCopyEnvelope

Property **CanCopyEnvelope** As Boolean

Description

Member of SelectionInfo

The **CanCopyEnvelope** property returns whether the selected envelope can be copied.

The **CanCopyEnvelope** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanCopyExtrude

Property **CanCopyExtrude** As Boolean

Description

Member of SelectionInfo

The **CanCopyExtrude** property returns whether the selected extrusion can be copied.

The **CanCopyExtrude** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanCopyLens

Property **CanCopyLens** As Boolean

Description

Member of SelectionInfo

The **CanCopyLens** property returns whether the selected lens can be copied.

The **CanCopyLens** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanCopyPerspective

Property **CanCopyPerspective** As Boolean

Description

Member of SelectionInfo

The **CanCopyPerspective** property returns whether the selected perspective can be copied.

The **CanCopyPerspective** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanCopyPowerclip

Property **CanCopyPowerclip** As Boolean

Description

Member of SelectionInfo

The **CanCopyPowerclip** property returns whether the selected PowerClip object can be copied.

The **CanCopyPowerclip** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanCreateBlend

Property **CanCreateBlend** As Boolean

Description

Member of SelectionInfo

The **CanCreateBlend** property returns whether the selected shapes can create a blend.

The **CanCreateBlend** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanDeleteControl

Property **CanDeleteControl** As Boolean

Description

Member of SelectionInfo

The **CanDeleteControl** property returns whether the selected control can be deleted.

The **CanDeleteControl** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanLockShapes

Property **CanLockShapes** As Boolean

Description

Member of SelectionInfo

The **CanLockShapes** property returns whether the selected shapes can be locked.

The **CanLockShapes** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanPrint

Property **CanPrint** As Boolean

Description

Member of SelectionInfo

The **CanPrint** property returns whether the current document can be printed.

The **CanPrint** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanUngroup

Property **CanUngroup** As Boolean

Description

Member of SelectionInfo

The **CanUngroup** property returns whether any of the selected shapes can be ungrouped.

The **CanUngroup** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.CanUnlockShapes

Property **CanUnlockShapes** As Boolean

Description

Member of SelectionInfo

The **CanUnlockShapes** property returns whether the selected shapes can be unlocked.

The **CanUnlockShapes** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.ConnectorLines

Property **ConnectorLines** As Shape

Description

Member of SelectionInfo

The **ConnectorLines** property returns the selected connector lines.

The **ConnectorLines** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.ContainsRollOverParent

Property **ContainsRollOverParent** As Boolean

Description

Member of SelectionInfo

The **ContainsRollOverParent** returns whether any of the selected shapes is a rollover parent.

The **ContainsRollOverParent** returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.ContourControlShape

Property **ContourControlShape** As Shape

Description

Member of SelectionInfo

The **ContourControlShape** property returns the control shape of the selected contour.

The **ContourControlShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.ContourGroup

Property **ContourGroup** As Shape

Description

Member of SelectionInfo

The **ContourGroup** property returns the selected contour group.

The **ContourGroup** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.Count

Property **Count** As Long

Description

Member of SelectionInfo

The **Count** property returns the number of objects selected.

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.DimensionControlShape

Property **DimensionControlShape** As Shape

Description

Member of SelectionInfo

The **DimensionControlShape** property returns the control shape of the selected dimension.

The **DimensionControlShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.DimensionGroup

Property **DimensionGroup** As Shape

Description

Member of SelectionInfo

The **DimensionGroup** property returns the selected dimension group.

The **DimensionGroup** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.DistortionShape

Property **DistortionShape** As Shape

Description

Member of SelectionInfo

The **DistortionShape** property returns the distortion state of the selected shape.

The **DistortionShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.DistortionType

Property **DistortionType** As cdrDistortionType

Description

Member of SelectionInfo

The **DistortionType** property returns the type of the selected distortion.

The **DistortionType** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.DropShadowControlShape

Property **DropShadowControlShape** As Shape

Description

Member of SelectionInfo

The **DropShadowControlShape** property returns the control shape of the selected drop shadow.

The **DropShadowControlShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.DropShadowGroup

Property **DropShadowGroup** As Shape

Description

Member of SelectionInfo

The **DropShadowGroup** property returns the selected drop-shadow group.

The **DropShadowGroup** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.ExtrudeBevelGroup

Property **ExtrudeBevelGroup** As Shape

Description

Member of SelectionInfo

The **ExtrudeBevelGroup** property returns the bevel group of the selected extrusion.

The **ExtrudeBevelGroup** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.ExtrudeFaceShape

Property **ExtrudeFaceShape** As Shape

Description

Member of SelectionInfo

The **ExtrudeFaceShape** property returns the face shape of the selected extrusion.

The **ExtrudeFaceShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.ExtrudeGroup

Property ExtrudeGroup As Shape

Description

Member of SelectionInfo

The **ExtrudeGroup** property returns the selected extrusion group.

The **ExtrudeGroup** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.FirstShape

Property **FirstShape** As Shape

Description

Member of SelectionInfo

The **FirstShape** property returns the first selected shape.

The **FirstShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.FirstShapeWithFill

Property **FirstShapeWithFill** As Shape

Description

Member of SelectionInfo

The **FirstShapeWithFill** property returns the first selected shape that has a fill.

The **FirstShapeWithFill** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.FirstShapeWithOutline

Property **FirstShapeWithOutline** As Shape

Description

Member of SelectionInfo

The **FirstShapeWithOutline** property returns the first selected shape that has an outline.

The **FirstShapeWithOutline** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.FittedText

Property **FittedText** As Shape

Description

Member of SelectionInfo

The **FittedText** property returns the selected fitted text.

The **FittedText** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.FittedTextControlShape

Property **FittedTextControlShape** As Shape

Description

Member of SelectionInfo

The **FittedTextControlShape** property returns the control shape of the selected fitted text.

The **FittedTextControlShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.HasAutoLabelText

Property **HasAutoLabelText** As Boolean

Description

Member of SelectionInfo

The **HasAutoLabelText** property returns whether the selected shape has automatically labelled text.

The **HasAutoLabelText** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsArtisticTextSelected

Property **IsArtisticTextSelected** As Boolean

Description

Member of SelectionInfo

The **IsArtisticTextSelected** property returns whether the selected shape is artistic text.

The **IsArtisticTextSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsAttachedToDimension

Property **IsAttachedToDimension** As Boolean

Description

Member of SelectionInfo

The **IsAttachedToDimension** property returns whether any of the selected shapes is attached to a dimension line.

The **IsAttachedToDimension** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsBevelGroup

Property **IsBevelGroup** As Boolean

Description

Member of SelectionInfo

The **IsBevelGroup** property returns whether the selected shape is a bevel group.

The **IsBevelGroup** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsBitmapPresent

Property **IsBitmapPresent** As Boolean

Description

Member of SelectionInfo

The **IsBitmapPresent** property returns whether any of the selected shapes contains a bitmap.

The **IsBitmapPresent** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsBitmapSelected

Property **IsBitmapSelected** As Boolean

Description

Member of SelectionInfo

The **IsBitmapSelected** property returns whether any of the selected shapes is a bitmap.

The **IsBitmapSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsBlendControl

Property **IsBlendControl** As Boolean

Description

Member of SelectionInfo

The **IsBlendControl** property returns whether the selected shape is a blend control.

The **IsBlendControl** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsBlendGroup

Property **IsBlendGroup** As Boolean

Description

Member of SelectionInfo

The **IsBlendGroup** property returns whether the selected shape is a blend group.

The **IsBlendGroup** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsCloneControl

Property **IsCloneControl** As Boolean

Description

Member of SelectionInfo

The **IsCloneControl** property returns whether the selected shape is a clone control.

The **IsCloneControl** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsConnector

Property **IsConnector** As Boolean

Description

Member of SelectionInfo

The **IsConnector** property returns whether the selected shape is a connector.

The **IsConnector** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsConnectorLine

Property **IsConnectorLine** As Boolean

Description

Member of SelectionInfo

The **IsConnectorLine** property returns whether the selected shape is a connector line.

The **IsConnectorLine** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsConnectorLineSelected

Property **IsConnectorLineSelected** As Boolean

Description

Member of SelectionInfo

The **IsConnectorLineSelected** property returns whether any of the selected shapes is a connector line.

The **IsConnectorLineSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsConnectorSelected

Property **IsConnectorSelected** As Boolean

Description

Member of SelectionInfo

The **IsConnectorSelected** property returns whether any of the selected shapes is a connector.

The **IsConnectorSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsContourControl

Property **IsContourControl** As Boolean

Description

Member of SelectionInfo

The **IsContourControl** property returns whether the selected shape is a contour control.

The **IsContourControl** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsContourGroup

Property **IsContourGroup** As Boolean

Description

Member of SelectionInfo

The **IsContourGroup** property returns whether the selected shape is a contour group.

The **IsContourGroup** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsControlSelected

Property **IsControlSelected** As Boolean

Description

Member of SelectionInfo

The **IsControlSelected** property returns whether a control is selected.

The **IsControlSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsControlShape

Property **IsControlShape** As Boolean

Description

Member of SelectionInfo

The **IsControlShape** property returns whether the selected shape is a link control.

The **IsControlShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsDimensionControl

Property **IsDimensionControl** As Boolean

Description

Member of SelectionInfo

The **IsDimensionControl** property returns whether the selected shape is a dimension control.

The **IsDimensionControl** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsDistortion

Property **IsDistortion** As Boolean

Description

Member of SelectionInfo

The **IsDistortion** property returns whether the selected shape is a distortion.

The **IsDistortion** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsDistortionPresent

Property **IsDistortionPresent** As Boolean

Description

Member of SelectionInfo

The **IsDistortionPresent** returns whether any of the selected shapes is a distortion.

The **IsDistortionPresent** returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsDropShadowControl

Property **IsDropShadowControl** As Boolean

Description

Member of SelectionInfo

The **IsDropShadowControl** propery returns whether the selected shape is a drop-shadow control.

The **IsDropShadowControl** propery returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsDropShadowGroup

Property **IsDropShadowGroup** As Boolean

Description

Member of SelectionInfo

The **IsDropShadowGroup** property returns whether the selected shape is a drop-shadow group.

The **IsDropShadowGroup** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsEditingRollOver

Property **IsEditingRollOver** As Boolean

Description

Member of SelectionInfo

The **IsEditingRollOver** property returns the rollover-editing state.

The **IsEditingRollOver** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsEditingText

Property **IsEditingText** As Boolean

Description

Member of SelectionInfo

The **IsEditingText** property returns the text-editing state.

The **IsEditingText** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsEnvelope

Property **IsEnvelope** As Boolean

Description

Member of SelectionInfo

The **IsEnvelope** property returns whether the selected shape is an envelope.

The **IsEnvelope** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsEnvelopePresent

Property **IsEnvelopePresent** As Boolean

Description

Member of SelectionInfo

The **IsEnvelopePresent** property returns whether any of the selected shapes is an envelope.

The **IsEnvelopePresent** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsExternalBitmapSelected

Property **IsExternalBitmapSelected** As Boolean

Description

Member of SelectionInfo

The **IsExternalBitmapSelected** property returns whether any of the selected shapes is an externally-linked bitmap.

The **IsExternalBitmapSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsExtrudeControl

Property **IsExtrudeControl** As Boolean

Description

Member of SelectionInfo

The **IsExtrudeControl** property returns whether the selected shape is an extrusion control.

The **IsExtrudeControl** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsExtrudeGroup

Property **IsExtrudeGroup** As Boolean

Description

Member of SelectionInfo

The **IsExtrudeGroup** property returns whether the selected shape is an extrusion group.

The **IsExtrudeGroup** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsFittedText

Property **IsFittedText** As Boolean

Description

Member of SelectionInfo

The **IsFittedText** property returns whether the selected shape is fitted text.

The **IsFittedText** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsFittedTextControl

Property **IsFittedTextControl** As Boolean

Description

Member of SelectionInfo

The **IsFittedTextControl** property returns whether the selected shape is a fitted-text control.

The **IsFittedTextControl** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsFittedTextSelected

Property **IsFittedTextSelected** As Boolean

Description

Member of SelectionInfo

The **IsFittedTextSelected** property returns whether any of the selected shapes is fitted text.

The **IsFittedTextSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsGroup

Property **IsGroup** As Boolean

Description

Member of SelectionInfo

The **IsGroup** property returns whether the selected shape is a group.

The **IsGroup** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsGroupSelected

Property **IsGroupSelected** As Boolean

Description

Member of SelectionInfo

The **IsGroupSelected** property returns whether any of the selected shapes is a group.

The **IsGroupSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsGuidelineSelected

Property **IsGuidelineSelected** As Boolean

Description

Member of SelectionInfo

The **IsGuidelineSelected** property returns whether any of the selected shapes is a guideline.

The **IsGuidelineSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsInternetObjectSelected

Property **IsInternetObjectSelected** As Boolean

Description

Member of SelectionInfo

The **IsInternetObjectSelected** property returns whether any of the selected shapes is an Internet object.

The **IsInternetObjectSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsLensPresent

Property **IsLensPresent** As Boolean

Description

Member of SelectionInfo

The **IsLensPresent** property returns whether any of the selected shapes contains a lens.

The **IsLensPresent** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsLinkControlSelected

Property **IsLinkControlSelected** As Boolean

Description

Member of SelectionInfo

The **IsLinkControlSelected** property returns whether any of the selected shapes is a link control.

The **IsLinkControlSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsLinkGroupSelected

Property **IsLinkGroupSelected** As Boolean

Description

Member of SelectionInfo

The **IsLinkGroupSelected** property returns whether any of the selected shapes is a link group.

The **IsLinkGroupSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsMaskedBitmapPresent

Property **IsMaskedBitmapPresent** As Boolean

Description

Member of SelectionInfo

The **IsMaskedBitmapPresent** property returns whether any of the selected shapes contains a masked bitmap.

The **IsMaskedBitmapPresent** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsMeshFillPresent

Property **IsMeshFillPresent** As Boolean

Description

Member of SelectionInfo

The **IsMeshFillPresent** property returns whether any of the selected shapes contains a mesh fill.

The **IsMeshFillPresent** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsMeshFillSelected

Property **IsMeshFillSelected** As Boolean

Description

Member of SelectionInfo

The **IsMeshFillSelected** property returns whether any of the selected shapes is a mesh fill.

The **IsMeshFillSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsNaturalMediaControl

Property **IsNaturalMediaControl** As Boolean

Description

Member of SelectionInfo

The **IsNaturalMediaControl** property returns whether the selected shape is a natural-media control.

The **IsNaturalMediaControl** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsNaturalMediaGroup

Property **IsNaturalMediaGroup** As Boolean

Description

Member of SelectionInfo

The **IsNaturalMediaGroup** property returns whether the selected shape is a natural-media group.

The **IsNaturalMediaGroup** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsNonExternalBitmapSelected

Property **IsNonExternalBitmapSelected** As Boolean

Description

Member of SelectionInfo

The **IsNonExternalBitmapSelected** property returns whether any of the selected shapes is a bitmap that is not externally linked.

The **IsNonExternalBitmapSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsOLESelected

Property **IsOLESelected** As Boolean

Description

Member of SelectionInfo

The **IsOLESelected** property returns whether the selected shape is an OLE object.

The **IsOLESelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsOnPowerClipContents

Property **IsOnPowerClipContents** As Boolean

Description

Member of SelectionInfo

The **IsOnPowerClipContents** property returns the editing state of a PowerClip object.

The **IsOnPowerClipContents** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsParagraphTextSelected

Property **IsParagraphTextSelected** As Boolean

Description

Member of SelectionInfo

The **IsParagraphTextSelected** property returns whether the selected shape is paragraph text.

The **IsParagraphTextSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsPerspective

Property **IsPerspective** As Boolean

Description

Member of SelectionInfo

The **IsPerspective** property returns whether the selected shape features a perspective effect.

The **IsPerspective** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsPerspectivePresent

Property **IsPerspectivePresent** As Boolean

Description

Member of SelectionInfo

The **IsPerspectivePresent** property returns whether any of the selected shapes is a perspective effect.

The **IsPerspectivePresent** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsRegularShape

Property **IsRegularShape** As Boolean

Description

Member of SelectionInfo

The **IsRegularShape** property returns whether the selected shape is a regular shape.

The **IsRegularShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsRollOverSelected

Property **IsRollOverSelected** As Boolean

Description

Member of SelectionInfo

The **IsRollOverSelected** property returns whether any of the selected shapes is a rollover.

The **IsRollOverSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsSecondContourControl

Property **IsSecondContourControl** As Boolean

Description

Member of SelectionInfo

The **IsSecondContourControl** property returns whether the second selected shape is a contour control.

The **IsSecondContourControl** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsSecondDropShadowControl

Property **IsSecondDropShadowControl** As Boolean

Description

Member of SelectionInfo

The **IsSecondDropShadowControl** property returns whether the second selected shape is a drop-shadow control.

The **IsSecondDropShadowControl** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsSecondExtrudeControl

Property **IsSecondExtrudeControl** As Boolean

Description

Member of SelectionInfo

The **IsSecondExturdeControl** property returns whether the second selected shape is an extrusion or bevel control.

The **IsSecondExturdeControl** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsSecondNaturalMediaControl

Property **IsSecondNaturalMediaControl** As Boolean

Description

Member of SelectionInfo

The **IsSecondNAturalMediaControl** property returns whether the second selected shape is a natural-media control.

The **IsSecondNaturalMediaControl** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsSoundObjectSelected

Property **IsSoundObjectSelected** As Boolean

Description

Member of SelectionInfo

The **IsSoundObjectSelected** property returns whether any of the selected shapes is a sound object.

The **IsSoundObjectSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsTextSelected

Property **IsTextSelected** As Boolean

Description

Member of SelectionInfo

The **IsTextSelected** property returns whether the selected shape is text.

The **IsTextSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.IsTextSelection

Property **IsTextSelection** As Boolean

Description

Member of SelectionInfo

The **IsTextSelection** property returns whether the selection is text.

The **IsTextSelection** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.NaturalMediaControlShape

Property **NaturalMediaControlShape** As Shape

Description

Member of SelectionInfo

The **NaturalMediaControlShape** property returns a natural-media control shape.

The **NaturalMediaControlShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.NaturalMediaGroup

Property **NaturalMediaGroup** As Shape

Description

Member of SelectionInfo

The **NaturalMediaGroup** property returns a natural-media group.

The **NaturalMediaGroup** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.Parent

Property **Parent** As Document

Description

Member of SelectionInfo

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

SelectionInfo.SecondShape

Property **SecondShape** As Shape

Description

Member of SelectionInfo

The **SecondShape** property returns the second selected shape.

The **SecondShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SeparationPlate

Properties

Description

The **SeparationPlate** class represents a separation-plate object.

Copyright 2014 Corel Corporation. All rights reserved.

SeparationPlate.Angle

Property **Angle** As Double

Description

Member of SeparationPlate

The **Angle** property returns the angle of a separation plate.

VBA example

The following VBA example displays the angle and frequency of each separation plate.

```
Sub Test()
 Dim intPlateCounter As Integer
 With ActiveDocument
  With .PrintSettings.Separations.Plates
   For intPlateCounter = 1 To .Count - 1
    MsgBox "The angle of the " & .Item(intPlateCounter).Color & _
     " plate is " & .Item(intPlateCounter).Angle & vbCr & _
     " The frequency is " & .Item(intPlateCounter).Frequency
   Next intPlateCounter
  End With
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SeparationPlate.Color

Property **Color** As String

Description

Member of SeparationPlate

The **Color** property returns the color of a separation plate.

The **Color** property returns a read-only value.

VBA example

The following VBA example displays the color of each separation plate.

```
Sub Test()
 Dim strPlates As String
 Dim Plate As SeparationPlate
 Dim intPlateCounter As Integer
 With ActiveDocument.PrintSettings.Separations
  For intPlateCounter = 1 To .Plates.Count - 1
   strPlates = strPlates & .Plates(intPlateCounter).Color & vbCr
  Next intPlateCounter
  MsgBox strPlates
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SeparationPlate.Enabled

Property **Enabled** As Boolean

Description

Member of SeparationPlate

The **Enabled** property allows a user to specify which separation plate to print.

VBA example

The following VBA example displays the disabled separation plates.

```
Sub Test()
 Dim intPlateCounter As Integer
 With ActiveDocument.PrintSettings.Separations
  For intPlateCounter = 1 To .Plates.Count - 1
   If .Plates(intPlateCounter).Enabled <> True Then
    MsgBox "The " & .Plates(intPlateCounter).Color & _
     " is not enabled."
   End If
  Next intPlateCounter
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SeparationPlate.Frequency

Property **Frequency** As Double

Description

Member of SeparationPlate

The **Frequency** property returns the screen frequency of a separation plate.

VBA example

The following VBA example displays the angle and frequency of each separation plate.

```
Sub Test()
 Dim intPlateCounter As Integer
 With ActiveDocument
  With .PrintSettings.Separations.Plates
   For intPlateCounter = 1 To .Count - 1
    MsgBox "The angle of the " & .Item(intPlateCounter).Color & _
     " plate is " & .Item(intPlateCounter).Angle & vbCr & _
     " The frequency is " & .Item(intPlateCounter).Frequency
   Next intPlateCounter
  End With
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SeparationPlate.OverprintGraphic

Property **OverprintGraphic** As Boolean

Description

Member of SeparationPlate

The **OverprintGraphic** property returns or specifies whether graphics are overprinted by the current separation plate.

VBA example

The following VBA example iterates through the collection of separation plates and sets the values of the **OverprintGraphic** and **OverprintText** properties to **False**.

```
Sub Test()
 Dim intPlateCounter As Integer
 With ActiveDocument.PrintSettings.Separations
  For intPlateCounter = 1 To .Plates.Count - 1
   .Plates(intPlateCounter).OverprintGraphic = False
   .Plates(intPlateCounter).OverprintText = False
  Next intPlateCounter
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SeparationPlate.OverprintText

Property **OverprintText** As Boolean

Description

Member of SeparationPlate

The **OverprintGraphic** property returns or specifies whether graphics are overprinted by the current separation plate.

VBA example

The following VBA example iterates through the collection of separation plates and sets the values of the **OverprintGraphic** and **OverprintText** properties to **False**.

```
Sub Test()
 Dim intPlateCounter As Integer
 With ActiveDocument.PrintSettings.Separations
  For intPlateCounter = 1 To .Plates.Count - 1
   .Plates(intPlateCounter).OverprintGraphic = False
   .Plates(intPlateCounter).OverprintText = False
  Next intPlateCounter
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SeparationPlate.Type

Property **Type** As PrnPlateType

Description

Member of SeparationPlate

The **Type** property returns the type of separation plate.

The **Type** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SeparationPlates

Properties

Description

The **SepartionPlates** class represents a collection of separation plates (or SeparationPlate objects).

Copyright 2014 Corel Corporation. All rights reserved.

SeparationPlates.Count

Property **Count** As Long

Description

Member of SeparationPlates

The **Count** property returns the number of items in a SeparationPlates collection.

The **Count** property returns a read-only value.

VBA example

The following VBA example displays the number of plates in the collection.

```
Sub Test()
 Select Case ActiveDocument.PrintSettings.Separations.Plates.Count
  Case 0
   MsgBox "There are no plates to print"
  Case 1
   MsgBox "There's 1 plate to print"
  Case Else
   MsgBox "There are " & _
    ActiveDocument.PrintSettings.Separations.Plates.Count & _
    " plates to print"
 End Select
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SeparationPlates.Item

Property **Item(***Index As Long***)** As SeparationPlate

Description

Member of SeparationPlates

The **Item** property returns a SeparationPlate value that represents the given color separation plate in a SeparationPlates collection.

Item is the default property of the **SeparationPlates** class, and its reference can be omitted when you are accessing items in a **SeparationPlates** collection. For example, **SeparationPlates.Item(2)** is the same as **SeparationPlates(2)** — they both reference the second segment object in the collection.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the separation plate by its index number

VBA example

The following VBA example lists the colors of the separation plates in the collection.

```
Sub Test()
 Dim strPlates As String
 Dim Plate As SeparationPlate
 Dim intPlateCounter As Integer
 With ActiveDocument.PrintSettings.Separations
  For intPlateCounter = 1 To .Plates.Count - 1
   If .Plates(intPlateCounter).Enabled = True Then
    strPlates = strPlates & .Plates(intPlateCounter).Color & vbCr
   End If
  Next intPlateCounter
  MsgBox strPlates
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape

Properties Methods

Description

The **Shape** class represents the settings for a CorelDRAW shape object (or “shape”), group, or selection.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.AbsoluteHScale

Property **AbsoluteHScale** As Double

Description

Member of Shape

The **AbsoluteHScale** property returns the absolute horizontal-scaling value of a shape. The returned value represents the total stretch transformation applied to the shape since its creation.

The **AbsoluteHScale** property returns a read-only value.

VBA example

The following VBA example displays a warning message if the active shape has been stretched horizontally or vertically (or both).

```
Sub Test()
 If ActiveShape.AbsoluteHScale <> 1 Or ActiveShape.AbsoluteVScale <> 1 Then
  MsgBox "The current shape is distored"
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.AbsoluteSkew

Property **AbsoluteSkew** As Double

Description

Member of Shape

The **AbsoluteSkew** property returns the absolute skew angle applied to a shape since its creation.

The **AbsoluteSkew** property returns a read-only value.

VBA example

The following VBA example displays the absolute skew angle of the selected shape.

```
Sub Test()
 If ActiveShape.AbsoluteSkew <> 0 Then
  MsgBox "The current shape is skewed. Skew angle is " & _
   ActiveShape.AbsoluteSkew
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.AbsoluteVScale

Property **AbsoluteVScale** As Double

Description

Member of Shape

The **AbsoluteVScale** property returns the absolute vertical-scaling value of a shape. The returned value represents the total stretch transformation applied to the shape since its creation.

The **AbsoluteVScale** property returns a read-only value.

VBA example

The following VBA example displays a warning message if the active shape has been stretched horizontally or vertically (or both).

```
Sub Test()
 If ActiveShape.AbsoluteHScale <> 1 Or ActiveShape.AbsoluteVScale <> 1 Then
  MsgBox "The current shape is distored"
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.AddToPowerClip

Sub **AddToPowerClip(**Shape As Shape**, [**CenterInContainer As cdrTriState = cdrUndefined**])**

Description

Member of Shape

The **AddToPowerClip** method adds the current shape object to a PowerClip container.

Parameter	Description
Shape	Specifies the PowerClip container
CenterInContainer	Specifies how to center the shape object in the PowerClip container. This parameter is optional, and its default value is cdrUndefined (**-2**).

VBA example

The following VBA example creates a rectangle and an ellipse, and it then places the ellipse inside the rectangle.

```
Sub Test()
 Dim rect As Shape, ell As Shape
 Set rect = ActiveLayer.CreateRectangle(0, 0, 4, 3)
 rect.Fill.UniformColor.RGBAssign 255, 0, 0
 Set ell = ActiveLayer.CreateEllipse(2, 1, 5, 4)
 ell.Fill.UniformColor.RGBAssign 255, 255, 0
 ell.AddToPowerClip rect
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.AddToSelection

Sub **AddToSelection()**

Description

Member of Shape

The **AddToSelection** method adds a shape to a selection.

- This method does not work with selection shapes.

VBA example

The following VBA example selects all ellipses and rectangles on the active page.

```
Sub Test()
 ActivePage.FindShapes(Type:=cdrEllipseShape).CreateSelection
 ActivePage.FindShapes(Type:=cdrRectangleShape).AddToSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.AffineTransform

Sub **AffineTransform(***d11 As Double*, *d12 As Double*, *d21 As Double*, *d22 As Double*, *CenterX As Double*, *CenterY As Double***)**

Description

Member of Shape

The **AffineTransform** method applies an affine transformation (as defined by the transformation-matrix components) to a shape, relative to the center point of the transformation.

- A transformation matrix is four numbers that include two transformations and two translations (or movements). Each matrix element is referred to as **d11**, **d12**, **d21**, and **d22** respectively, left to right, and top to bottom.

Parameter	Description
d11	Specifies the horizontal stretch factor multiplied by the cosine of the rotation angle
d12	Specifies the vertical stretch factor multiplied by the sine of the sum of the rotation and skew angles. This value is expressed as the negative of the resultant value.
d21	Specifies the horizontal stretch factor multiplied by the sine of the rotation angle
d22	Specifies the vertical stretch factor multiplied by the cosine of the sum of the rotation and skew angles
CenterX	Specifies the x-coordinate of the center
CenterY	Specifies the y-coordinate of the center

Copyright 2014 Corel Corporation. All rights reserved.

Shape.AlignAndDistribute

Sub **AlignAndDistribute**(MethodH As cdrAlignDistributeH, MethodV As cdrAlignDistributeV, [AlignTo As cdrAlignShapesTo = *cdrAlignShapesToLastSelected (0)*], [DistributeArea As cdrDistributeArea = *cdrDistributeToSelection (0)*], [UseOutline As Boolean = False], [TextAlignOrigin As cdrTextAlignOrigin = *cdrTextAlignBoundingBox (2)*], [PointX As Double = 0], [PointY As Double = 0], [DistributeRect As Rect = 0])

Description

Member of Shape

The **AlignAndDistribute** method aligns and/or distributes the shape or shapes in the selection.

Parameter	Description
MethodH	Specifies which method is used for aligning and distributing objects horizontally
MethodV	Specifies which method is used for aligning and distributing objects vertically
AlignTo	Specifies whether to align objects to the center or edge of the page, the grid, the last selected object, or to a defined point
DistributeArea	Specifies the area over which to distribute objects
UseOutline	Accounts for outline thickness when calculating object size and position
TextAlignOrigin	Specifies the origin for aligning text such as bounding box, first baseline, or last baseline
PointX	Specifies the x-coordinate of the reference point for aligning and distributing
PointY	Specifies the y-coordinate of the reference point for aligning and distributing
Distribute Rect	Distributes objects within a specified rectangle

Copyright 2014 Corel Corporation. All rights reserved.

Shape.AlignToGrid

Sub **AlignToGrid(**Type As cdrAlignType**, [**TextAlignOrigin As cdrTextAlignOrigin = cdrTextAlignBoundingBox**])**

Description

Member of Shape

The **AlignToGrid** method aligns a shape to the grid.

Parameter	Description
Type	Specifies the type of text alignment
TextAlignOrigin	Specifies the origin of the text alignment. This parameter is optional, and its default value is cdrTextAlignBoundingBox (**2**).

Copyright 2014 Corel Corporation. All rights reserved.

Shape.AlignToPage

Sub **AlignToPage(**Type As cdrAlignType**, [**TextAlignOrigin As cdrTextAlignOrigin = cdrTextAlignBoundingBox**])**

Description

Member of Shape

The **AlignToPage** method aligns a shape to the page.

Parameter	Description
Type	Specifies the type of text alignment
TextAlignOrigin	Specifies the origin of the text alignment. This parameter is optional, and its default value is cdrTextAlignBoundingBox (**2**).

Copyright 2014 Corel Corporation. All rights reserved.

Shape.AlignToPageCenter

Sub **AlignToPage(**Type As cdrAlignType**, [**TextAlignOrigin As cdrTextAlignOrigin = cdrTextAlignBoundingBox**])**

Description

Member of Shape

The **AlignToPageCenter** method aligns a shape to the page center.

Parameter	Description
Type	Specifies the type of text alignment
TextAlignOrigin	Specifies the origin of the text alignment. This parameter is optional, and its default value is cdrTextAlignBoundingBox (**2**).

Copyright 2014 Corel Corporation. All rights reserved.

Shape.AlignToPoint

Sub **AlignToPoint(**Type As cdrAlignType**,** *x As Double*, *y As Double*, **[**TextAlignOrigin As cdrTextAlignOrigin = cdrTextAlignBoundingBox**])**

Description

Member of Shape

The **AlignToPoint** method aligns a shape to the specified coordinates.

Parameter	Description
Type	Specifies the type of text alignment
x	Specifies the x-coordinate
y	Specifies the y-coordinate
TextAlignOrigin	Specifies the origin of the text alignment. This parameter is optional, and its default value is cdrTextAlignBoundingBox (**2**).

Copyright 2014 Corel Corporation. All rights reserved.

Shape.AlignToShape

Sub **AlignToShape(**Type As cdrAlignType**,** Shape As Shape**, [**TextAlignOrigin As cdrTextAlignOrigin = cdrTextAlignBoundingBox**])**

Description

Member of Shape

The **AlignToShape** method aligns a shape to another shape.

Parameter	Description
Type	Specifies the type of text alignment
Shape	Specifies the shape to which to align
TextAlignOrigin	Specifies the origin of the text alignment. This parameter is optional, and its default value is cdrTextAlignBoundingBox (**2**).

Copyright 2014 Corel Corporation. All rights reserved.

Shape.AlignToShapeRange

Sub **AlignToShapeRange(**Type As cdrAlignType**,** ShapeRange As ShapeRange**, [**TextAlignOrigin As cdrTextAlignOrigin = cdrTextAlignBoundingBox**])**

Description

Member of Shape

The **AlignToShapeRange** method aligns a shape to a shape range (or ShapeRange object).

Parameter	Description
Type	Specifies the type of text alignment
ShapeRange	Specifies the shape range to which to align
TextAlignOrigin	Specifies the origin of the text alignment. This parameter is optional, and its default value is cdrTextAlignBoundingBox (**2**).

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Application

Property **Application** As Application

Description

Member of Shape

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.ApplyEffectBCI

Sub **ApplyEffectBCI(***Brighness As Long*, *Contrast As Long*, *Intensity As Long***)**

Description

Member of Shape

The **ApplyEffectBCI** method applies a Brightness-Contrast-Intensity color effect to a shape.

Parameter	Description
Brighness	Specifies the brightness level
Contrast	Specifies the contrast level
Intensity	Specifies the intensity level

Copyright 2014 Corel Corporation. All rights reserved.

Shape.ApplyEffectColorBalance

Sub **ApplyEffectColorBalance(***CyanRed As Long*, *MagentaGreen As Long*, *YellowBlue As Long*, **[**ApplyToShadows As Boolean = True**],** **[**ApplyToMidtones As Boolean = True**],** **[**ApplyToHighlights As Boolean = True**],** **[**PreserveLuminance As Boolean = True**])**

Description

Member of Shape

The **ApplyEffectColorBalance** method applies a color-balance effect to a shape.

Parameter	Description
CyanRed	Specifies the cyan/red value
MagentaGreen	Specifies the magenta/green value
YellowBlue	Specifies the yellow/blue value
ApplyToShadows	Specifies whether to apply the effect to shadows. This parameter is optional, and its default value is **True**.
ApplyToMidtones	Specifies whether to apply the effect to midtones. This parameter is optional, and its default value is **True**.
ApplyToHighlights	Specifies whether to apply the effect to highlights. This parameter is optional, and its default value is **True**.
PreserveLuminance	Specifies whether to preserve luminance. This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.ApplyEffectGamma

Sub **ApplyEffectGamma**(*Gamma As Double*)

Description

Member of Shape

The **ApplyEffectGamma** method applies a gamma color correction to a shape.

Parameter	Description
Gamma	Specifes the gamma level

Copyright 2014 Corel Corporation. All rights reserved.

Shape.ApplyEffectHSL

Sub **ApplyEffectHSL(***Hue As Variant***,** *Saturation As Variant***,** *Lightness As Variant***)**

Description

Member of Shape

The **ApplyEffectHSL** method applies a Hue-Saturation-Lightness color effect to a shape.

Parameter	Description
Hue	Specifies the hue level
Saturation	Specifies the saturation level
Lightness	Specifies the lightness level

Copyright 2014 Corel Corporation. All rights reserved.

Shape.ApplyEffectInvert

Sub **ApplyEffectInvert()**

Description

Member of Shape

The **ApplyEffectInvert** method inverts the colors of a shape or selection.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.ApplyEffectPosterize

Sub **ApplyEffectPosterize(***Level As Long***)**

Description

Member of Shape

The **ApplyEffectPosterize** method applies a Posterize color effect to a shape.

Parameter	Description
Level	Specifies the effect level

Copyright 2014 Corel Corporation. All rights reserved.

Shape.ApplyStyle

Sub **ApplyStyle(***StyleName As String***)**

Description

Member of Shape

The **ApplyStyle** method applies a text or graphic style to a shape.

Parameter	Description
StyleName	Specifies the style by name

VBA example

The following VBA example creates an ellipse and fills it. It then applies the default graphic style (a hairline outline and no fill) to the ellipse.

```
Sub Test()
 Dim s1 As Shape
 Set s1 = ActiveLayer.CreateEllipse(0, 0, 2, 2)
 s1.Fill.ApplyUniformFill CreateRGBColor(255, 0, 0)
 s1.ApplyStyle "Default Graphic"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Bitmap

Property **Bitmap** As Bitmap

Description

Member of Shape

The **Bitmap** property returns a Bitmap object that represents the bitmap-related properties of a bitmap shape.

The **Bitmap** property returns a read-only value.

VBA example

The following VBA example creates a rectangle, converts it to a bitmap, and then shows the resulting bitmap size in pixels.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 s.Fill.ApplyTextureFill "Patches 5C"
 Set s = s.ConvertToBitmapEx(cdrRGBColorImage)
 MsgBox "The resulting bitmap is " & s.Bitmap.SizeWidth & "x" & _
  s.Bitmap.SizeHeight & " pixels"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.BottomY

Property **BottomY** As Double

Description

Member of Shape

The **BottomY** property returns the y-coordinate of the bottom edge of a shape.

The **BottomY** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.BoundingBox

Property **BoundingBox** As Rect

Description

Member of Shape

The **BoundingBox** property returns the bounding rectangle around a shape or shapes.

The **BoundingBox** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.BreakApart

Sub **BreakApart()**

Description

Member of Shape

The **BreakApart** method breaks curves into subpaths, or text objects into words or characters.

VBA example

The following VBA example creates the letter “O” and converts it to a curve. It breaks the two subpaths into separate objects. The inner path is then moved upwards by **0.2**", and the two paths are combined into a single curve shape.

```
Sub Test()
 Dim s As Shape, sr As ShapeRange
 Set s = ActiveLayer.CreateArtisticText(0, 0, "O")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 48
 End With
 s.ConvertToCurves
 s.BreakApart
 Set sr = ActiveSelectionRange
 sr(1).Move 0, 0.2
 sr.Combine
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.BreakApartEx

Function **BreakApartEx()** As ShapeRange

Description

Member of Shape

The **BreakApartEx** method breaks apart a curve and returns the objects as a shape range (or ShapeRange object).

VBA example

The following VBA example creates a letter “O” and converts it to a curve. The two subpaths are broken into separate objects, and the inner path is moved upwards by **0.2**". The two paths are then combined into a single curve shape.

```
Sub Test()
 Dim s As Shape, sr As ShapeRange
 Set s = ActiveLayer.CreateArtisticText(0, 0, "O", , , "Arial Black", 48)
 s.ConvertToCurves
 Set sr = s.BreakApartEx
 sr(1).Move 0, 0.2
 sr.Combine
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.BSpline

Property **BSpline** As BSpline

Description

Member of Shape

The **BSpline** property returns a read-only BSpline object.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CanHaveFill

Property **CanHaveFill** As Boolean

Description

Member of Shape

The **CanHaveFill** property returns **True** if a fill can be applied to a given shape.

The **CanHaveFill** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CanHaveOutline

Property **CanHaveOutline** As Boolean

Description

Member of Shape

The **CanHaveOutline** property returns **True** if an outline can be applied to a given shape.

The **CanHaveOutline** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CenterX

Property **CenterX** As Double

Description

Member of Shape

The **CenterX** property returns or specifies the horizontal position of the center of a shape.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CenterY

Property **CenterY** As Double

Description

Member of Shape

The **CenterY** property returns or specifies the vertical position of the center of a shape.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Chamfer

Sub **Chamfer(***DistanceA As Double***,** *DistanceB As Double***, [**CombineSmoothSegments As Boolean = True**])**

Description

Member of Shape

The **Chamfer** method creates a chamfer on each cusp corner of a shape.

Parameter	Description
DistanceA	
DistanceB	
CombineSmoothSegments	Specifies whether to combine smooth segments. This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.ClearEffect

Sub **ClearEffect(**Type As cdrEffectType**)**

Description

Member of Shape

The **ClearEffect** method removes an effect from a shape.

Parameter	Description
Type	Specifies the effect to remove, and returns cdrEffectType

VBA example

The following VBA example clears all contours applied to any shape on the page. Any grouped shapes are not processed.

```
Sub Test()
 ActivePage.Shapes.All.CreateSelection
 ActiveSelection.ClearEffect cdrContour
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.ClearTransformations

Sub **ClearTransformations()**

Description

Member of Shape

The **ClearTransformations** method clears all rotation, stretch, and skew transformations applied to a shape.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Clone

Function **Clone([***OffsetX As Double***], [***OffsetY As Double***])** As Shape

Description

Member of Shape

The **Clone** method clones a shape and returns a reference to that clone.

Parameter	Description
OffsetX	Specifies the horizontal distance to offset the cloned shape. This parameter is optional, and its default value is 0.
OffsetY	Specifies the vertical distance to offset the cloned shape. This parameter is optional, and its default value is 0.

VBA example

The following VBA example creates a red rectangle, clones it, and then changes the fill of the clone to green.

```
Sub Test()
 Dim rs As Shape, cs As Shape
 Set rs = ActiveLayer.CreateRectangle2(0, 0, 4, 2)
 rs.Fill.UniformColor.CMYKAssign 0, 100, 100, 0
 Set cs = rs.Clone(0, 3)
 cs.Fill.UniformColor.CMYKAssign 100, 0, 100, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CloneAsRange

Function **CloneAsRange([***OffsetX As Double***], [***OffsetY As Double***])** As ShapeRange

Description

Member of Shape

The **CloneAsRange** method clones a shape or selection and returns the cloned shape (or shapes) as a shape range.

Parameter	Description
OffsetX	Specifies the horizontal distance to offset the cloned shape. This parameter is optional, and its default value is **0**.
OffsetY	Specifies the vertical distance to offset the cloned shape. This parameter is optional, and its default value is **0**.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CloneLink

Property **CloneLink** As CloneLink

Description

Member of Shape

The **CloneLink** property returns a CloneLink object that represents the clone properties of a specified shape.

The **CloneLink** property returns a read-only value.

VBA example

The following VBA example creates a rectangle and then creates a clone of it. The original rectangle (control shape) is filled with a texture fill by referencing it through the **CloneLink** property.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 Set s = s.Clone(3, 0)
 s.CloneLink.CloneParent.Fill.ApplyTextureFill "Patches 5C"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Clones

Property **Clones** As ShapeRange

Description

Member of Shape

The **Clones** property returns a shape range (or ShapeRange object) containing all cloned shapes for the specified clone-control object.

The **Clones** property returns a read-only value.

VBA example

The following VBA example restores fill links for all clones of the currently selected shape.

```
Sub Test()
 Dim s As Shape
 For Each s In ActiveShape.Clones
  s.CloneLink.FillLinked = True
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Combine

Function **Combine()** As Shape

Description

Member of Shape

The **Combine** method combines shapes into a curve or text object.

- See also the ShapeRange.Combine method.

VBA example

The following VBA example creates two ellipses and combines them into a single curve.

```
Sub Test()
 Dim doc As Document
 Dim e1 As Shape, e2 As Shape
 Set doc = CreateDocument()
 Set e1 = doc.ActiveLayer.CreateEllipse2(4, 3, 2)
 Set e2 = doc.ActiveLayer.CreateEllipse2(4, 5, 3)
 ' Here e2 is selected. Just add e1 to selection
 e1.Selected = True
 Set e1 = doc.Selection.Combine
 e1.Fill.UniformColor.CMYKAssign 100, 0, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CompareTo

Function **CompareTo(**Shape As Shape**,** CompareType As cdrCompareType**, [Condition As** cdrCompareCondition = cdrCompareEquals**])** As Boolean

Description

Member of Shape

The **CompareTo** method compares the properties of two shapes.

Parameter	Description
Shape	Specifies the shape to which to compare
CompareType	Specifies the comparison type
Condition	Specifies the condition. This parameter is optional, and its default value is cdrCompareEquals (**0**).

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CompareToEx

Function **CompareToEx(**Shape2 As Shape**,** *Condition As String*, **[***Data***])** As Boolean

Description

Member of Shape

The **CompareToEx** method compares two shapes by using a Corel Query Language (CQL) expression as a condition. A value of **True** is returned if the condition is met.

- For information on CQL, see the section "Including queries in macros."

Parameter	Description
Shape2	Specifies the shape to which to compare
Condition	Specifies the CQL condition
Data	Specifies any data that can be referenced by the CQL expression as `@data`. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Connector

Property **Connector** As Connector

Description

Member of Shape

The **Connector** property returns a Connector object for connector shapes.

The **Connector** property returns a read-only value.

VBA example

The following VBA example creates a rectangle and an ellipse. It then creates a connector line and attaches it to the centers of the rectangle and ellipse.

```
Sub Test()
Dim r As Shape, e As Shape, c As Shape
Set r = ActiveLayer.CreateRectangle(0, 0, 2, 2)
Set e = ActiveLayer.CreateEllipse2(4, 2, 1)
Set c = ActiveLayer.CreateFreeConnector(1, 0, 4, 0)
c.Connector.StartPoint = r.SnapPoints(4) ' Center of rectangle
c.Connector.EndPoint = e.SnapPoints(3) ' Center of ellipse
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.ConvertToBitmap

Function **ConvertToBitmap([**BitDepth As Long = 24**], [***Grayscale As Boolean = False***], [**Dithered As Boolean = True**], [**TransparentBG As Boolean = True**], [**Resolution As Long = 72**], [**AntiAliasing As cdrAntiAliasingType = cdrNormalAntiAliasing**], [**UseColorProfile As Boolean = True**])** As Shape

Description

Member of Shape

The **ConvertToBitmap** method converts a shape to a bitmap.

- This method is obsolete and provided for backward compatibility only. It is recommended that you use the ConvertToBitmapEx method instead.

Parameter	Description
BitDepth	Specifies bit depth. This parameter is optional, and its default value is **24**.
Grayscale	Converts to grayscale if set to **True** (**-1**). This parameter is optional, and its default value is **False**.
Dithered	Enables dithering if set to **True** (**-1**). This parameter is optional, and its default value is **True**.
TransparentBG	Enables a transparent background if set to **True** (**-1**). This parameter is optional, and its default value is **True**.
Resolution	Specifies the resolution. This parameter is optional, and its default value is **72**.
AntiAliasing	Specifies the anti-aliasing type, and returns cdrAntiAliasingType. This parameter is optional, and its default value is cdrNormalAntiAliasing (**1**).
UseColorProfile	Uses a color profile if set to **True** (**-1**). This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.ConvertToBitmapEx

Function **ConvertToBitmapEx([**Mode As cdrImageType = cdrRGBColorImage**], [**Dithered As Boolean = False**], [**Transparent As Boolean = False**], [**Resolution As Long = 72**], [**AntiAliasing As cdrAntiAliasingType = cdrNormalAntiAliasing**], [**UseColorProfile As Boolean = True**])** As Shape

Description

Member of Shape

The **ConvertToBitmapEx** converts a shape to a bitmap.

Parameter	Description
Mode	Specifies the image type, and returns cdrImageType. This parameter is optional, and its default value is cdrRGBColorImage (**4**).
Dithered	Enables dithering if set to **True** (**-1**). This parameter is optional, and its default value is **False**.
Transparent	Enables a transparent background if set to **True** (**-1**). This parameter is optional, and its default value is **False**.
Resolution	Specifies the resolution. This parameter is optional, and its default value is **72**.
AntiAliasing	Specifies the anti-aliasing, and a value of returns cdrAntiAliasingType. This parameter is optional, and its default value is cdrNormalAntiAliasing (**1**).
UseColorProfile	Uses a color profile if set to True (**-1**). This parameter is optional, and its default value is **True**.

VBA example

The following VBA example creates a rectangle and an ellipse. Then it converts the ellipse to a CMYK bitmap with a transparent background, applies a dropshadow to it, and groups it with the rectangle.

```
Sub Test()
 Dim r As Shape, s As Shape
 Set r = ActiveLayer.CreateRectangle(0, 0, 5, 5)
 r.Fill.UniformColor.CMYKAssign 100, 0, 0, 0
 Set s = ActiveLayer.CreateEllipse2(3, 3, 2)
 s.Fill.UniformColor.CMYKAssign 0, 100, 100, 0
 Set s = s.ConvertToBitmapEx(cdrCMYKColorImage, False, True)
 s.CreateDropShadow cdrDropShadowFlat, 80, 10, 0.5, -0.5, CreateCMYKColor(0, 50, 50, 50)
 r.CreateSelection
 s.Selected = True
 ActiveSelection.Group
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.ConvertToCurves

Sub **ConvertToCurves()**

Description

Member of Shape

The **ConvertToCurves** method converts a shape to a curve.

VBA example

The following VBA example creates a jagged text object.

```
Sub Test()
 Dim s As Shape, n As Node
 Set s = ActiveLayer.CreateArtisticText(0, 0, "Jagged")
 With s.Text.FontProperties
  .Name = "Arial"
  .Style = cdrBoldFontStyle
  .Size = 140
 End With
 s.ConvertToCurves
 For Each n In s.Curve.Nodes
  n.Move (Rnd() - 0.5) * 0.2, (Rnd() - 0.5) * 0.2
 Next n
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.ConvertToSymbol

Function **ConvertToSymbol(***Name As String***)** As Shape

Description

Member of Shape

The **ConvertToSymbol** method converts a shape to a symbol.

Parameter	Description
Name	Specifies the name of the shape

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Copy

Sub **Copy()**

Description

Member of Shape

The **Copy** method copies a shape to the Clipboard.

VBA example

The following VBA example copies each shape from the active page to a separate page in a new document.

```
Sub Test()
 Dim s As Shape, bAddPage As Boolean
 Dim doc1 As Document, doc2 As Document
 Set doc1 = ActiveDocument
 Set doc2 = CreateDocument()
 bAddPage = False
 For Each s In doc1.ActivePage.Shapes()
  s.Copy
  If bAddPage Then doc2.AddPages 1
  doc2.ActiveLayer.Paste
  bAddPage = True
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CopyPropertiesFrom

Function **CopyPropertiesFrom(**Source As Shape**,** Properties As cdrCopyProperties**)** As Boolean

Description

Member of Shape

The **CopyPropertiesFrom** method specifies whether to copy fill, outline, or text properties — or some combination of those — from another shape.

Parameter	Description
Source	Specifies the shape
Properties	Specifies the properties to copy

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CopyToLayer

Function **CopyToLayer(**Layer As Layer**)** As Shape

Description

Member of Shape

The **CopyToLayer** method copies a shape to the specified layer.

Parameter	Description
Layer	Specifies the layer

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CopyToLayerAsRange

Function **CopyToLayerAsRange(**Layer As Layer**)** As ShapeRange

Description

Member of Shape

The **CopyToLayerAsRange** method copies the shape or selection to the specified layer and returns the duplicated shape (or shapes) as a shape range.

Parameter	Description
Layer	Specifies the layer

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreateArrowHead

Function **CreateArrowHead()** As ArrowHead

Description

Member of Shape

The **CreateArrowhead** method creates an arrowhead from a specified shape. The shape must be of a type that can be converted to a curve.

VBA example

The following VBA example creates an arrowhead from a six-sided star polygon and applies it to a line.

```
Sub Test()
 Dim s As Shape, ar As ArrowHead
 Set s = ActiveLayer.CreatePolygon(0, 0, 2, 2, 6, , , True)
 Set ar = s.CreateArrowHead()
 s.Delete
 Set s = ActiveLayer.CreateLineSegment(0, 0, 5, 5)
 s.Outline.Width = 0.1
 s.Outline.EndArrow = ar
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreateBlend

Function **CreateBlend(**Shape As Shape**, [**Steps As Integer = 20**], [**ColorBlendType As cdrFountainFillBlendType = cdrDirectFountainFillBlend**], [**Mode As cdrBlendMode = cdrBlendSteps**], [***Spacing As Double***], [***Angle As Double***], [**Loop As Boolean = False**], [**Path As Shape**], [**RotateShapes As Boolean = False**], [***SpacingAccel As Long***], [***ColorAccel As Long***], [**AccelSize As Boolean = False**]) As Effect

Description

Member of Shape

The **CreateBlend** method creates a blend between two shapes, returning an Effect object that represents the blend-effect properties.

Parameter	Description
Shape	Specifies the starting shape
Steps	Specifies the number of steps. This parameter is optional, and its default value is **20**.
ColorBlendType	Specifies the color-blend type, and returns cdrFountainFillBlendType. This parameter is optional, and its default value is cdrDirectFountainFillBlend (**0**).
Mode	Specifies the blend mode, and returns cdrBlendMode. This parameter is optional, and its default value is cdrBlendSteps (**0**).
Spacing	Specifies the blend spacing. This parameter is optional, and its default value is **0**.
Angle	Specifies the blend angle. This parameter is optional, and its default value is **0**.
Loop	Specifies whether the blend loops. This parameter is optional, and its default value is **False**.
Path	Specifies the blend path. This parameter is optional, and its default value is **Nothing**.
RotateShapes	Specifies whether the blend rotates its shape to follow a path. This parameter is optional, and its default value is **False**.
SpacingAccel	Specifies the rate of object acceleration. This parameter is optional, and its default value is **0**.
ColorAccel	Specifies the rate of color acceleration. Higher numbers allow the colors to move more quickly through the spectrum as they approach the end object. This parameter is optional, and its default value is **0**.
AccelSize	Specifies whether the size of the blend accelerates along the path. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example creates a blend on path between two ellipses.

```
Sub Test()
 Dim sPath As Shape, s1 As Shape, s2 As Shape
 Dim eff As Effect
 Set sPath = ActiveLayer.CreateCurveSegment(1, 6.5, 5, 8.5, 2, 72, 1.8, 180)
 Set s1 = ActiveLayer.CreateEllipse(0.953386, 6.731929, 1.838858, 6.027165)
 s1.Fill.UniformColor.CMYKAssign 0, 100, 100, 0
 Set s2 = ActiveLayer.CreateEllipse(4.838622, 9.045, 5.597598, 8.21374)
 s2.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
 Set eff = s2.CreateBlend(s1, 10)
 eff.Blend.Path = sPath
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreateBoundary

Function **CreateBoundary(***x As Double***,** *y As Double***,** [*PlaceOnTop As Boolean* = False], [*DeleteSource As Boolean* = False]**)** As Shape

Description

Member of Shape

The **CreateBoundary** method creates a closed Bézier curve based on the specified shapes and a user-specified bias point. If the bias point lies outside of the extent of the specified shapes, the boundary object is the common outline of the specified shapes. If the bias point lies within one or more of the specified shapes, the boundary object is the internal outline of the union of the specified shapes at the bias point.

If the operation fails, **Nothing** is returned.

Parameter	Description
x	Specifies the x-coordinate of the bias point
y	Specifies the y-coordinate of the bias point
PlaceOnTop	Specifies whether to place the boundary object in front of the shapes. A value of **True** places the boundary object in front of the shapes. This parameter is optional, and its default value is **False**.
DeleteSource	Specifies whether to delete the object upon which the boundary is based. A value of **True** deletes the original object. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example creates a circle and retrieves a user-specified point. If the point is valid, a boundary is created relative to the circle and is filled with red.

```
Sub Test()
Dim shpEllipse As Shape, shpBound As Shape
Dim x As Double, y As Double
Set shpEllipse = ActiveLayer.CreateEllipse2(0, 0, 6, 4)
b = ActiveDocument.GetUserClick(x, y, 0, 10, False, cdrCursorEyeDrop)
If b=0 Then
Set shpBound = shpEllipse.CreateBoundary(x, y, False, False)
shpBound.Fill.UniformColor.RGBAssign 255, 0, 0
End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreateContour

Function **CreateContour(**[*Direction As* cdrContourDirection = cdrContourOutside], [*Offset As Double*], [*Steps As Long* = 1], [*BlendType As* cdrFountainFillBlendType = cdrDirectFountainFillBlend], [*OutlineColor As* Color], [*FillColor As* Color], [*FillColor2 As* Color], [*SpacingAccel As Long*], [*ColorAccel As Long*]**)** As Effect

Description

Member of Shape

The **CreateContour** method applies a contour to a shape, returning an Effect object that represents contour properties.

Parameter	Description
Direction	Specifies the direction of the contour, and returns cdrContourDirection. This parameter is optional, and its default value is cdrContourOutside (**1**).
Offset	Specifies the offset distance, in document units, between contour lines, automatically adjusting the number of contour steps. This parameter is optional, and its default value is **0**.
Steps	Specifies the number of steps, which is linked to the number of lines that appear in the effect. This parameter is optional, and its default value is **1**.
BlendType	Specifies the color-blend type, and returns cdrFountainFillBlendType. This parameter is optional, and its default value is cdrDirectFountainFillBlend (**0**).
OutlineColor	Specifies the contour's outline color. This parameter is optional, and its default value is **Nothing**.
FillColor	Specifies the contour's fill color. This parameter is optional, and its default value is **Nothing**.
FillColor2	Specifies the EffectContour.FillColorTo color. This parameter is optional, and its default value is **Nothing**.
SpacingAccel	Specifies the change in step size. This parameter is optional, and its default value is **0**.
ColorAccel	Specifies the acceleration of the color change. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example creates a text string and applies a contour effect to it, resulting in blurred look.

```
Sub Test()
 Dim sText As Shape
 Set sText = ActiveLayer.CreateArtisticText(4, 5, "Blurred Text")
 sText.Fill.UniformColor.RGBAssign 0, 0, 0
 With sText.Text.FontProperties
  .Name = "Arial"
  .Size = 90
  .Style = cdrBoldFontStyle
 End With
 sText.Text.AlignProperties.Alignment = cdrCenterAlignment
 sText.CreateContour cdrContourOutside, 0.01, 10, , , CreateRGBColor(255, 255, 255)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreateCustomDistortion

Function **CreateCustomDistortion(***DistortionID As String***,** *Parameter() As Variant***)** As Effect

Description

Member of Shape

The **CreateCustomDistortion** method applies a custom distortion to a shape.

Parameter	Description
DistortionID	Specifies the ID of the distortion
Parameter	Specifies the distortion parameters

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreateCustomEffect

Function **CreateCustomEffect(***EffectID As String***,** *Parameter() As Variant***)** As Effect

Description

Member of Shape

The **CreateCustomEffect** method applies a custom effect to a shape.

Parameter	Description
EffectID	Specifies the ID of the effect
Parameter	Specifies the effect parameters

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreateDocumentFrom

Function **CreateDocumentFrom(**TemporaryDocument As Boolean = False**)** As Document

Description

Member of Shape

The **CreateDocumentFrom** method creates a copy of the document that contains a shape.

Parameter	Description
TemporaryDocument	Specifies whether the document is temporary. The default for this Boolean value is **False**.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreateDropShadow

Function **CreateDropShadow([**Type As cdrDropShadowType = cdrDropShadowFlat**], [**Opacity As Long = 50**], [**Feather As Long = 15**], [***OffsetX As Double***], [***OffsetY As Double***], [**Color As Color**], [**FeatherType As cdrFeatherType = cdrFeatherAverage**], [**FeatherEdge As cdrEdgeType = cdrEdgeLinear**], [**PerspectiveAngle As Double = -45**], [**PerspectiveStretch As Double = 1**], [**Fade As Long = 1**], [**MergeMode As cdrMergeMode = cdrMergeNormal**]) As Effect

Description

Member of Shape

The **CreateDropShadow** method applies a drop shadow to a shape, returning an Effect object that represents the drop-shadow properties.

Parameter	Description
Type	Specifies the type of drop shadow, and returns cdrDropShadowType. This parameter is optional, and its default value is cdrDropShadowFlat (**0**).
Opacity	Specifies the opacity value of the drop shadow. Values range from **0** to **100**. Low values create a less opaque drop shadow, while high values create a more opaque drop shadow. This parameter is optional, and its default value is **50**.
Feather	Specifies the feather length for the drop shadow. Values range from **0** to **100**. Low values create a more subtle feathering effect, while high values create a more pronounced effect. This parameter is optional, and its default value is **15**.
OffsetX	Specifies the horizontal offset of the drop shadow. This parameter is optional, and its default value is **0**.
OffsetY	Specifies the vertical offset of the drop shadow. This parameter is optional, and its default value is **0**.
Color	Specifies the color of the drop shadow. This parameter is optional, and its default value is **Nothing**.
FeatherType	Specifies the feather type for the drop shadow, and returns cdrFeatherType. Values range from **0** to **100**. Low values create a more subtle feathering effect, while high values create a more pronounced effect. This parameter is optional, and its default value is cdrFeatherAverage (**3**).
FeatherEdge	Specifies the feather edge for the drop shadow, and returns cdrEdgeType. Values range from **0** to **100**. This parameter is optional, and its default value is cdrEdgeLinear (**0**).
PerspectiveAngle	Specifies the feather perspective angle in the drop shadow. This parameter is optional, and its default value is **-45**.
PerspectiveStretch	Specifies the feather perspective stretch value in the drop shadow. This parameter is optional, and its default value is **1**.
Fade	Specifies the fade value of the drop shadow. The fade level of a drop shadow that has a **Flat** perspective cannot be changed. This parameter is optional, and its default value is **1**.
MergeMode	Specifies the merge mode for the drop shadow. This parameter is optional, and its default value is cdrMergeNormal (**0**).

VBA example

The following VBA example creates a cut-out effect.

```
Sub Test()
 Const Border As Double = 0.5
 Dim s As Shape, sRect As Shape, sShadow As Shape
 Dim eff As Effect, sr As New ShapeRange
 Dim x As Double, y As Double, sx As Double, sy As Double
 Set s = ActiveLayer.CreateArtisticText(4, 5, "Cut")
 With s.Text.FontProperties
  .Name = "Arial"
  .Size = 200
  .Style = cdrBoldFontStyle
 End With
 s.Text.AlignProperties.Alignment = cdrCenterAlignment
 s.GetBoundingBox x, y, sx, sy
 Set sRect = ActiveLayer.CreateRectangle2(x - Border, y - Border, sx + 2 * Border, sy + 2 * Border)
 s.Selected = True
 Set sRect = ActiveSelection.Combine
 sRect.Fill.UniformColor.CMYKAssign 30, 0, 0, 0
 Set eff = sRect.CreateDropShadow(cdrDropShadowFlat, 80, 10, 0.2, -0.2, CreateCMYKColor(0, 0, 0, 100))
 eff.Separate
 Set sShadow = sRect.Next
 Set s = ActiveLayer.CreateRectangle2(x, y, sx, sy)
 s.Fill.ApplyNoFill
 s.Outline.Type = cdrNoOutline
```

```
 sShadow.AddToPowerClip s
 s.OrderBackOf sRect
 sr.Add s
 sr.Add sRect
 sr.Group.CreateSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreateEnvelope

Function **CreateEnvelope(***PresetIndex As Long***, [**Mode As cdrEnvelopeMode = cdrEnvelopePutty**], [**KeepLines As Boolean = False**]) As** Effect

Description

Member of Shape

The **CreateEnvelope** method inserts a shape into a preset envelope, returning an Effect object that represents the envelope properties.

- Currently you can apply only a preset envelope shape, and node positions cannot be modified.

Parameter	Description
PresetIndex	Specifies the index number that uniquely identifies the preset envelope effect
Mode	Specifies the type of mapping mode for the envelope, and returns cdrEnvelopeMode. This parameter is optional, and its default value is cdrEnvelopePutty (**2**).
KeepLines	Specifies whether the envelope keeps its lines straight or converts them to curves. If the **KeepLines** property is set to **True**, the envelope keeps its lines straight. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example draws a magnifying glass.

```
Sub Test()
 Dim sText As Shape, sRect As Shape, sCircle1 As Shape, sCircle2 As Shape
 Set sText = ActiveLayer.CreateArtisticText(2.8, 7.5, "Magnify")
 With sText.Text.FontProperties
  .Name = "Arial"
  .Size = 64
 End With
 sText.Text.AlignProperties.Alignment = cdrCenterAlignment
 sText.CreateEnvelope 4, cdrEnvelopePutty, False
 ActiveDocument.ReferencePoint = cdrCenter
 sText.Stretch 1, 1.6
 Set sRect = ActiveLayer.CreateRectangle(2.164134, 5.358543, 6.338504, 4.798346)
 With sRect
  With .Fill.ApplyFountainFill(CreateRGBColor(255, 0, 0), CreateRGBColor(251, 0, 81), , -90)
   .Colors.Add CreateRGBColor(255, 0, 0), 1
   .Colors.Add CreateRGBColor(253, 253, 213), 23
   .StartX = 4.251319
   .StartY = 5.358543
   .EndX = 4.251319
   .EndY = 4.798346
  End With
  .Rotate -60
  .Move 0.469843, -0.397559
  .Outline.Type = cdrNoOutline
 End With
 Set sCircle1 = ActiveLayer.CreateEllipse(1.116024, 9.514843, 4.459134, 6.171732)
 sCircle1.Outline.SetProperties 0.3, OutlineStyles(0), CreateCMYKColor(0, 100, 100, 0)
 Set sCircle2 = sCircle1.Duplicate
 With sCircle2.Outline
  .Width = 0.05
  .Color.CMYKAssign 0, 0, 0, 0
 End With
 sCircle2.CreateBlend sCircle1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreateEnvelopeFromCurve

Function **CreateEnvelopeFromCurve(**Source As Curve**, [**Mode As cdrEnvelopeMode = cdrEnvelopePutty**], [**KeepLines As Boolean = False**], [**CopyMode As cdrEnvelopeCopyMode = cdrEnvelopeCenter**], [***CornerIndices***])** As Effect

Description

Member of Shape

The **CreateEnvelopeFromCurve** method creates an envelope by using the specified curve as a template.

Parameter	Description
Source	Specifies the source
Mode	Specifies the type of mapping mode for the envelope, and returns cdrEnvelopeMode. This parameter is optional, and its default value is cdrEnvelopePutty (**2**).
KeepLines	Specifies whether the envelope keeps its lines straight or converts them to curves. If the **KeepLines** property is set to **True**, the envelope keeps its lines straight. This parameter is optional, and its default value is **False**.
CopyMode	Specifies the copy mode, and returns cdrEnvelopeCopyMode. This parameter is optional, and its default value is cdrEnvelopeCenter
CornerIndices	Specifies the corner indices. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreateEnvelopeFromShape

Function **CreateEnvelopeFromShape(**Source As Shape**, [**Mode As cdrEnvelopeMode = cdrEnvelopePutty**], [**KeepLines As Boolean = False**], [**CopyMode As cdrEnvelopeCopyMode = cdrEnvelopeCenter**], [***CornerIndices***])** As Effect

Description

Member of Shape

The **CreateEnvelopeFromShape** method creates an envelope by using the specified shape as a template.

Parameter	Description
Source	Specifies the source
Mode	Specifies the type of mapping mode for the envelope, and returns cdrEnvelopeMode. This parameter is optional, and its default value is cdrEnvelopePutty (**2**).
KeepLines	Specifies whether the envelope keeps its lines straight or converts them to curves. If the **KeepLines** property is **True**, the envelope keeps its lines straight. This parameter is optional, and its default value is **False**.
CopyMode	Specifies the copy mode, and returns cdrEnvelopeCopyMode. This parameter is optional, and its default value is cdrEnvelopeCenter
CornerIndices	Specifies the corner indices. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreateExtrude

Function **CreateExtrude(**Type As cdrExtrudeType**,** VPType As cdrExtrudeVPType**,** *VPX As Double***,** *VPY As Double***, [**Depth As Double = 20**], [**Shading As cdrExtrudeShading = cdrExtrudeObjectFill**], [**BaseColor As Color**], [**ShadingColor As Color**], [***BevelDepth As Double***], [**BevelAngle As Double = 45**], [**BevelColor As Color**], [**BevelOnly As Boolean = False**])** As Effect

Description

Member of Shape

The **CreateExtrude** method extrudes a shape, returning an Effect object that represents the extrusion properties.

Parameter	Description
Type	Specifies the extrusion type, and returns cdrExtrudeType
VPType	Specifies the type of vanishing point
VPX	Specifies the x-coordinate of the vanishing point
VPY	Specifies the y-coordinate of the vanishing point
Depth	Specifies the extrusion depth. This parameter is optional, and its default value is **20**.
Shading	Specifies the shading type, and returns cdrExtrudeShading. This parameter is optional, and its default value is cdrExtrudeObjectFill (**0**).
BaseColor	Specifies the solid fill color or starting shading color. This parameter is optional, and its default value is **Nothing**.
ShadingColor	Specifies the ending shading color. This parameter is optional, and its default value is **Nothing**.
BevelDepth	Specifies the bevel depth. This parameter is optional, and its default value is **0**.
BevelAngle	Specifies the bevel angle. This parameter is optional, and its default value is **45**.
BevelColor	Specifies the bevel color. This parameter is optional, and its default value is **Nothing**.
BevelOnly	Specifies whether to use only a bevel. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example creates an extruded text object.

```
Sub Test()
 Dim sText As Shape, eff As Effect
 Set sText = ActiveLayer.CreateArtisticText(4.25, 7, "Extrude")
 With sText.Text.FontProperties
  .Name = "Arial"
  .Size = 120
  .Style = cdrBoldFontStyle
 End With
 sText.Text.AlignProperties.Alignment = cdrCenterAlignment
 sText.Fill.UniformColor.CMYKAssign 100, 0, 0, 0
 Set eff = sText.CreateExtrude(cdrExtrudeSmallBack, cdrVPLockedToShape, 4.25, 0.45, 40, _
   cdrExtrudeColorShading, CreateCMYKColor(0, 0, 0, 100), CreateCMYKColor(0, 0, 0, 0))
 eff.Extrude.UseFullColorRange = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreateLens

Function **CreateLens(**Type As cdrLensType**, [**RateOrMagnification As Double = 50**], [**Color1 As Color**], [**Color2 As Color**], [**ColorMapPalette As cdrFountainFillBlendType = cdrDirectFountainFillBlend**]) As** Effect

Description

Member of Shape

The **CreateLens** method applies a lens effect to a shape, returning an Effect object that represents the lens properties.

Parameter	Description
Type	Specifies the type of lens, and returns cdrLensType
RateOrMagnification	Specifies a value between **0** and **100**% that increases the degree of a lens effect. The **Rate** property applies to the following lens effects: **Brighten**, **Color add**, **Color limit**, **Fish eye**, and **Transparency**. This parameter is optional, and its default value is **50**.
Color1	Specifies the starting color in a **Custom Color Map** lens effect. This parameter is optional, and its default value is **Nothing**.
Color2	Specifies the ending color in a **Custom Color Map** lens effect. This parameter is optional, and its default value is **Nothing**.
ColorMapPalette	Specifies the type of color-map palette, and returns cdrFountainFillBlendType. This parameter is optional, and its default value is cdrDirectFountainFillBlend (**0**).

VBA example

The following VBA example creates a checkerboard and draws a **Fish eye** lens on top of it.

```
Sub Test()
 Dim sGrid As Shape, s As Shape
 Dim b As Boolean
 Set sGrid = ActiveLayer.CreateGridBoxes(1.748504, 8.41252, 4.712126, 5.430827, 5, 5)
 b = True
 For Each s In sGrid.Shapes
  If b Then
   s.Fill.UniformColor.RGBAssign 0, 0, 0
  Else
   s.Fill.UniformColor.RGBAssign 255, 255, 255
  End If
  b = Not b
 Next s
 Set s = ActiveLayer.CreateEllipse(1.748504, 8.41252, 4.712126, 5.430827, 90#, 90#, False)
 s.CreateLens cdrLensFishEye, 100
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreatePerspective

Function **CreatePerspective([***HorizVanishPointX As Variant***], [***HorizVanishPointY As Variant***], [***VertVanishPointX As Variant***], [***VertVanishPointY As Variant***])** As Effect

Description

Member of Shape

The **CreatePerspective** method applies a perspective to a shape, returning an Effect object that represents the perspective properties.

Parameter	Description
HorizVanishPointX	Specifies the x-coordinate of the horizontal vanishing point. This parameter is optional.
HorizVanishPointY	Specifies the y-coordinate of the horizontal vanishing point. This parameter is optional.
VertVanishPointX	Specifies the x-coordinate of the vertical vanishing point. This parameter is optional.
VertVanishPointY	Specifies the y-coordinate of the vertical vanishing point. This parameter is optional.

VBA example

The following VBA example creates a three-dimensional cube with checkerboard sides.

```
Sub Test()
 Dim sGrid As Shape, s As Shape
 Dim b As Boolean, n As Long
 Set sGrid = ActiveLayer.CreateGridBoxes(1.549724, 7.436693, 3.067677, 5.91874, 4, 4)
 b = True
 n = 0
 For Each s In sGrid.Shapes
  If b Then
   s.Fill.UniformColor.RGBAssign 0, 0, 0
  Else
   s.Fill.UniformColor.RGBAssign 255, 255, 255
  End If
  n = n + 1
  If (n Mod 4) <> 0 Then b = Not b
 Next s
 Set s = sGrid.Duplicate
 s.SetBoundingBox 1.549724, 7.436693, 1.517953, 0.451447
 s.CreatePerspective , , 6.984024, 9.839248
 Set s = sGrid.Duplicate
 s.SetBoundingBox 3.068583, 5.91874, 0.7395965, 1.517953
 s.CreatePerspective 6.984024, 9.839248
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreatePushPullDistortion

Function **CreatePushPullDistortion(***OriginX As Double***,** *OriginY As Double***,** *Amplitude As Long***)** As Effect

Description

Member of Shape

The **CreatePushPullDistortion** method applies a Push-and-pull distortion to a shape, returning an Effect object that represents the distortion properties.

Parameter	Description
OriginX	Specifies the x-coordinate around which the Push-and-pull distortion rotates
OriginY	Specifies the y-coordinate around which the Push-and-pull distortion rotates
Amplitude	Specifies the intensity of the Push-and-pull-distortion effect. Values range from **0** to **100;** higher values produce a more pronounced distortion.

VBA example

The following VBA example creates an ellipse in the middle of the page and applies a Push-and-pull distortion to it before converting the shape to a curve.

```
Sub Test()
 Dim s As Shape
 ActiveDocument.ResetSettings
 Set s = ActiveLayer.CreateEllipse2(ActivePage.SizeWidth / 2, _
  ActivePage.SizeHeight / 2, 2)
 s.CreatePushPullDistortion 0, 0, 60
 s.ConvertToCurves
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreateSelection

Sub **CreateSelection()**

Description

Member of Shape

The **CreateSelection** method selects a shape, automatically deselecting all other shapes on the page.

- See also the Shape.Selected property.

VBA example

The following VBA example selects a shape with the name **MyRectangle**.

```
Sub Test()
 Dim s As Shape
 Set s = ActivePage.FindShape("MyRectangle")
 If Not s Is Nothing Then
  s.CreateSelection
 Else
  ActiveDocument.ClearSelection
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreateTwisterDistortion

Function **CreateTwisterDistortion(***OriginX As Double***,** *OriginY As Double***,** *Angle As Double***)** As Effect

Description

Member of Shape

The **CreateTwisterDistortion** method applies a Twister distortion to a shape, returning an Effect object that represents the distortion properties.

Parameter	Description
OriginX	Specifies the x-coordinate around which the Twister distortion rotates
OriginY	Specifies the y-coordinate around which the Twister distortion rotates
Angle	Specifies the degree of the Twister rotation

VBA example

The following VBA example creates an ellipse and applies a Twister distortion to it before converting the shape to a curve.

```
Sub Test()
 Dim s As Shape
 ActiveDocument.ResetSettings
 Set s = ActiveLayer.CreateEllipse2(ActivePage.SizeWidth / 2, _
  ActivePage.SizeHeight / 2, 2)
 s.CreateTwisterDistortion 0, 3, 80
 s.ConvertToCurves
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CreateZipperDistortion

Function **CreateZipperDistortion(***OriginX As Double***,** *OriginY As Double***,** *Amplitude As Long***,** *Frequency As Long***, [**Random As Boolean = False**], [**Smooth As Boolean = False**], [**Local As Boolean = False**])** As Effect

Description

Member of Shape

The **CreateZipperDistortion** method applies a Zipper distortion to a shape, returning an Effect object that represents the distortion properties.

Parameter	Description
OriginX	Specifies the x-coordinate around which the Zipper distortion rotates
OriginY	Specifies the y-coordinate around which the Zipper distortion rotates
Amplitude	Specifies the intensity of the Zipper distortion. Values range from **0** to **100**; higher values produce a more pronounced Zipper distortion.
Frequency	Specifies the frequency of the Zipper distortion. Values range from **0** to **100**; a higher frequency value creates more zipper points in the distortion.
Random	Specifies whether the horizontal and vertical points follow a haphazard course. This parameter is optional, and its default value is **False**.
Smooth	Specifies whether the edges at the points are smooth or jagged. This parameter is optional, and its default value is **False**.
Local	Specifies whether the effect is emphasized in a specific area of the selected object. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example creates an ellipse and applies a Zipper distortion it before converting the shape to a curve.

```
Sub Test()
 Dim s As Shape
 ActiveDocument.ResetSettings
 Set s = ActiveLayer.CreateEllipse2(ActivePage.SizeWidth / 2, _
  ActivePage.SizeHeight / 2, 2)
 s.CreateZipperDistortion 0, 0, 6, 80
 s.ConvertToCurves
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Curve

Property **Curve** As Curve

Description

Member of Shape

The **Curve** property returns a Curve object for connector shapes.

The **Curve** property returns a read-only value.

VBA example

The following VBA example creates an ellipse and converts it to a curve shape. It then changes all curve segments to lines, resulting in a diamond shape.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(3, 3, 2, 1)
 s.ConvertToCurves
 s.Curve.Segments.All.SetType cdrLineSegment
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Custom

Property **Custom** As CustomShape

Description

Member of Shape

The **Custom** property returns the properties of a custom shape.

- CorelDRAW supports the automation of tables through the use of custom shapes. See the TableShape class for information on working with tables.

- For information on creating custom shapes, see the Layer.CreateCustomShape method.

The **Custom** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.CustomCommand

Function **CustomCommand(***ComponentID As String***,** *CommandID As String***,** *Parameter() As Variant***)** As Variant

Description

Member of Shape

The **CustomCommand** method executes a custom command on a given shape.

Parameter	Description
ComponentID	Specifies the ID of the component
CommandID	Specifies the ID of the command
Parameter	Specifies the command parameters

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Cut

Sub **Cut()**

Description

Member of Shape

The **Cut** method copies a shape to the Clipboard before deleting the shape from the document.

VBA example

The following VBA example cuts the active shape from the document.

```
Sub Test()
 ActiveShape.Cut
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Delete

Sub **Delete()**

Description

Member of Shape

The **Delete** method deletes a shape.

VBA example

The following VBA example creates a crescent by trimming one ellipse with another.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Set s1 = ActiveLayer.CreateEllipse(1.947283, 7.707756, 4.278425, 5.376614)
 Set s2 = s1.Duplicate(0.560197, 0)
 s2.Trim s1
 s2.Delete
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Dimension

Property **Dimension** As Dimension

Description

Member of Shape

The **Dimension** property returns a read-only dimension object.

The **Dimension** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.DisplayCurve

Property **DisplayCurve** As Curve

Description

Member of Shape

The **DisplayCurve** property returns a curve representing the current shape, letting you get a curve from a shape (such as a rectangle, ellipse, or polygon) without having to first convert the shape to a curve.

- The curve returned by this property is read-only, so you cannot modify it. However, you can retrieve a copy in memory by using the Curve.GetCopy method, after which you can modify the curve.

The **DisplayCurve** property returns a read-only value.

VBA example

The following VBA example creates a large circle and places **50** small circles along its path.

```
Sub Test()
 Const Steps As Long = 50
 Dim s As Shape, sp As SubPath
 Dim x As Double, y As Double
 Dim t As Double
 Set s = ActiveLayer.CreateEllipse(0, 0, 5, 5)
 For Each sp In s.DisplayCurve.Subpaths
  For t = 0 To Steps - 1
   sp.GetPointPositionAt x, y, t / Steps
   ActiveLayer.CreateEllipse2 x, y, 0.05
  Next t
 Next sp
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Distribute

Sub **Distribute(**Type As cdrDistributeType**, [**PageExtent As Boolean = False**])**

Description

Member of Shape

The **Distribute** method distributes the shapes evenly in a selection.

Parameter	Description
Type	Specifies the distribution type
PageExtent	Specifies whether to distribute the shapes to the extent of the page. This parameter is optional, and its default value is **False**.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.DrapeFill

Property **DrapeFill** As Boolean

Description

Member of Shape

The **DrapeFill** property returns or specifies whether to drape the fill of a group of objects in a vector extrusion.

VBA example

The following VBA example creates two ellipses, groups them together, and applies a two-color pattern fill that flows across both objects.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape, grp As Shape
 Set s1 = ActiveLayer.CreateEllipse(1.003717, 9.103496, 3.012929, 7.580724, 90#, 90#, False)
 s1.Outline.Type = cdrNoOutline
 Set s2 = ActiveLayer.CreateEllipse(4.683748, 6.332898, 2.103496, 8.574756, 90#, 90#, False)
 s2.Outline.Type = cdrNoOutline
 s1.Selected = True
 Set grp = ActiveSelection.Group
 With grp.Fill.ApplyPatternFill(cdrTwoColorPattern, "%%['$'UH$[UH", 0, _
    CreateCMYKColor(0, 100, 100, 0), CreateCMYKColor(0, 0, 100, 0), False)
  .TransformWithShape = False
  .TileHeight = 1
  .TileWidth = 1
  .OriginX = 0
  .OriginY = 0
 End With
 grp.DrapeFill = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Duplicate

Function **Duplicate([***OffsetX As Double***], [***OffsetY As Double***])** As Shape

Description

Member of Shape

The **Duplicate** method duplicates a shape and places the duplicate at the specified offset relative to the original shape position, returning a Shape object for the duplicated shape.

Parameter	Description
OffsetX	Specifies the horizontal distance to offset the duplicated shape. This parameter is optional, and its default value is **0**.
OffsetY	Specifies the vertical distance to offset the duplicated shape. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example creates an ellipse, duplicates it, and creates a blend between the two shapes.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Set s1 = ActiveLayer.CreateEllipse(2, 7, 4, 5)
 Set s2 = s1.Duplicate(3, -5)
 s1.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
 s2.Fill.UniformColor.CMYKAssign 0, 100, 100, 0
 s2.CreateBlend s1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.DuplicateAsRange

Function **DuplicateAsRange([***OffsetX As Double***], [***OffsetY As Double***])** As ShapeRange

Description

Member of Shape

The **DuplicateAsRange** method duplicates a shape or selection and returns the duplicated shape (or shapes) as a shape range.

Parameter	Description
OffsetX	Specifies the horizontal offset of the duplicate. This parameter is optional, and its default value is **0**.
OffsetY	Specifies the vertical offset of the duplicate. This parameter is optional, and its default value is **0**.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Effect

Property **Effect** As Effect

Description

Member of Shape

The **Effect** property represents the Effect object for shapes generated by an effect (contour or blend groups, extrusion facets, and so on).

The **Effect** property represents a read-only value.

VBA example 1

The following VBA example creates a blend between two ellipses. It iterates through all shapes on the page to locate the blend group and changes some blend parameters. This example is just a demonstration of the **Effect** property; you can use the **Effect** object returned by the CreateBlend method directly if you want to set properties of the created blend.

```
Sub Test()
 Dim doc As Document
 Dim e1 As Shape, e2 As Shape, s As Shape
 Set doc = CreateDocument
 Set e1 = doc.ActiveLayer.CreateEllipse(0, 0, 2, 2)
 e1.Fill.UniformColor.RGBAssign 255, 0, 0
 Set e2 = doc.ActiveLayer.CreateEllipse(4, 4, 5, 5)
 e2.Fill.UniformColor.RGBAssign 0, 0, 255
 e1.CreateBlend e2
 For Each s In doc.ActivePage.Shapes
  If s.Type = cdrBlendGroupShape Then
   With s.Effect.Blend
    .Steps = 5
    .ColorBlendType = cdrRainbowCWFountainFillBlend
   End With
  End If
 Next s
End Sub
```

VBA example 2

The following VBA example changes the blend-effect properties immediately after creating the blend. Alternatively, you can set most of the parameters for the blend directly in the CreateBlend method.

```
Sub Test()
 Dim doc As Document
 Dim e1 As Shape, e2 As Shape, eff As Effect
 Set doc = CreateDocument
 Set e1 = doc.ActiveLayer.CreateEllipse(0, 0, 2, 2)
 e1.Fill.UniformColor.RGBAssign 255, 0, 0
 Set e2 = doc.ActiveLayer.CreateEllipse(4, 4, 5, 5)
 e2.Fill.UniformColor.RGBAssign 0, 0, 255
 Set eff = e1.CreateBlend(e2)
 eff.Blend.Steps = 5
 eff.Blend.ColorBlendType = cdrRainbowCWFountainFillBlend
End Sub
```

VBA example 3

The following VBA example runs more efficiently, setting all blend parameters in a single command.

```
Sub Test()
 Dim doc As Document
 Dim e1 As Shape, e2 As Shape, eff As Effect
 Set doc = CreateDocument
 Set e1 = doc.ActiveLayer.CreateEllipse(0, 0, 2, 2)
 e1.Fill.UniformColor.RGBAssign 255, 0, 0
 Set e2 = doc.ActiveLayer.CreateEllipse(4, 4, 5, 5)
 e2.Fill.UniformColor.RGBAssign 0, 0, 255
 e1.CreateBlend e2, 5, cdrRainbowCWFountainFillBlend
End Sub
```

VBA example 4

The following VBA example changes the number of steps in all blends found on a page and removes any extrusions.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  Select Case s.Type
   Case cdrExtrudeGroupShape
    s.Effect.Clear
   Case cdrBlendGroupShape
    s.Effect.Blend.Steps = 50
  End Select
 Next s
End Sub
```

The usefulness of the **Shape.Effect** property is apparent when working with many effects in a document.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Effects

Property **Effects** As Effects

Description

Member of Shape

The **Effects** property returns a collection of all the Effects applied to a shape.

The **Effects** property returns a read-only value.

VBA example

The following VBA example creates three ellipses and two blends between them. One ellipse, referenced by the **s2** variable, is part of both blends. The **Effects** collection is then applied to that ellipse, to access both blends and adjust their spacing-acceleration properties.

```
Sub Test()
 Dim doc As Document
 Dim s1 As Shape, s2 As Shape, s3 As Shape
 Dim e As Effect
 Set doc = CreateDocument
 Set s1 = doc.ActiveLayer.CreateEllipse(0, 0, 2, 2)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 Set s2 = doc.ActiveLayer.CreateEllipse(4, 4, 5, 5)
 s2.Fill.UniformColor.RGBAssign 0, 0, 255
 Set s3 = doc.ActiveLayer.CreateEllipse(0, 7, 1, 8)
 s3.Fill.UniformColor.RGBAssign 0, 255, 0
 s2.CreateBlend s1
 s2.CreateBlend s3
 For Each e In s2.Effects
  e.Blend.SpacingAcceleration = -100
 Next e
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Ellipse

Property **Ellipse** As Ellipse

Description

Member of Shape

The **Ellipse** property returns an Ellipse object that represents the settings for an ellipse shape.

The **Ellipse** property returns a read-only value.

VBA example

The following VBA example converts all ellipses on the current page into pies.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Type = cdrEllipseShape Then
   With s.Ellipse
    .StartAngle = 0
    .EndAngle = 90
    .Clockwise = True
    .Type = cdrPie
   End With
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.EPS

Property **EPS** As EPS

Description

Member of Shape

The **EPS** property returns the properties of an Embedded PostScript object.

The **EPS** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.EqualDivide

Function **EqualDivide([**Divisions As Long = 2**], [**Gap As Double = -1**], [**Group As Boolean = False**], [**Combine As Boolean = True**], [**DeleteSource As Boolean = True**])** As ShapeRange

Description

Member of Shape

The **EqualDivide** method divides a shape into divisions of equal length, separated by gaps of equal size (including zero). The divisions can be combined into a single compound-path object, or they can be left as individual shapes that can be grouped.

Parameter	Description
Divisions	Specifies the desired number of equal divisions for the shape. Values range from **2** to **360**. This parameter is optional, and its default value is **2**.
Gap	Specifies, in document units, the length of the gap between divisions. A value of **0** is permitted. This parameter is optional, and its default value is **-1**.
Group	Specifies whether to group the divisions. This parameter is optional, and its default value is **False**.
Combine	Specifies whether to combine the divisions into a single compound path. A value of **False** leaves the divisions as separate. This parameter is optional, and its default value is **True**.
DeleteSource	Specifies whether to delete the original shape. A value of **False** retains the original shape. This parameter is optional, and its default value is **True**.

This method returns a value of ShapeRange, but results may vary based on how many objects are selected prior to the operation and whether they are combined:

- If a single shape is specified and the **Combine** parameter is set to **True**, the resultant shape range contains a single shape: the compound path created by combining the equally divided segments.
- If a single shape is specified and the **Combine** pararmeter is set to **False**, the resultant shape range contains several shapes: one shape reference for each equally divided segment.

VBA example

The following VBA example creates an ellipse and divides it into seven equal segments that are separated by a gap. The segments are combined into a single shape, and the source object is deleted by default.

```
Sub Test()
Dim shpEllipse As Shape
Dim shrRange As ShapeRange
Set shpEllipse = ActiveLayer.CreateEllipse2(0,0,6,4)
Set shrRange = shpEllipse.EqualDivide(7, 0.015, False, True)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Evaluate

Function **Evaluate(***Expression As String***)** As Variant

Description

Member of Shape

The Evaluate method evaluates a given expression by using the properties of the current shape, returning the result of the expression.

- You can use this method to perform queries with the Corel Query Language (CQL). For information on queries, see the section "Including queries in macros."

Parameter	Description
Expression	Specifies the CQL expression

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Fill

Property **Fill** As Fill

Description

Member of Shape

The **Fill** property returns a Fill object that represents the fill properties of a shape.

VBA example

The following VBA example creates a rectangle and applies a fountain fill that progresses from red to yellow.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 5, 5)
 s.Fill.ApplyFountainFill CreateRGBColor(255, 0, 0), CreateRGBColor(255, 255, 0)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Fillet

Sub **Fillet(***Radius As Double***, [**CombineSmoothSegments As Boolean = True**])**

Description

Member of Shape

The **Fillet** method creates a fillet on each cusp corner of a shape.

Parameter	Description
Radius	Specifies the fillet radius
CombineSmoothSegments	Specifies whether to combine smooth segments. This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.FillMode

Property **FillMode** As cdrFillMode

Description

Member of Shape

The **FillMode** property returns or specifies the fill mode for a shape.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.FindSnapPoint

Property **FindSnapPoint(***ReferenceData As String***)** As SnapPoint

Description

Member of Shape

The **FindSnapPoint** method finds a snap point by using the given reference data.

Parameter	Description
ReferenceData	Specifies the reference data

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Flip

Sub **Flip(**Axes As cdrFlipAxes**)**

Description

Member of Shape

The **Flip** method flips a shape along one or two axes.

- To flip the object along both axes in one step, you can combine the two axes.

Parameter	Description
Axes	Specifies the flip type, and returns cdrFlipAxes

VBA example

The following VBA example creates an illusion of a text object reflected in a mirror.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Set s1 = ActiveLayer.CreateArtisticText(2, 5, "Some Text")
 With s1.Text.FontProperties
  .Name = "Arial"
  .Size = 48
  .Style = cdrBoldFontStyle
 End With
 Set s2 = s1.Duplicate(0, 0.5)
 s1.Flip cdrFlipHorizontal
 s1.Fill.ApplyFountainFill CreateCMYKColor(0, 0, 0, 100), CreateCMYKColor(0, 0, 0, 0), , -90
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.GetBoundingBox

Sub **GetBoundingBox(***x As Double***,** *y As Double***,** *Width As Double***,** *Height As Double***, [**UseOutline As Boolean = False**])**

Description

Member of Shape

The **GetBoundingBox** method returns the size of a shape and the position of its lower-left corner.

Parameter	Description
x	Specifies the horizontal, or x-, coordinate of the lower-left corner. This value is measured in document units.
y	Specifies the vertical, or y-, coordinate of the lower-left corner. This value is measured in document units.
Width	Specifies the horizontal length, measured in document units
Height	Specifies the vertical length, measured in document units
UseOutline	Specifies whether the outline is included in any measurements. This parameter is optional, and its default value is **False**.

- If the **UseOutline** parameter is set to **True**, then the outline width and shape are accounted for when calculating the bounding-box dimensions. Otherwise, the shape is treated as if it has no outline.

VBA example

The following VBA example creates a rectangle around each shape on the active page.

```
Sub Test()
 Dim s As Shape
 Dim x As Double, y As Double, w As Double, h As Double
 ActiveDocument.ReferencePoint = cdrBottomLeft
 For Each s In ActivePage.Shapes
  s.GetBoundingBox x, y, w, h
  ActiveLayer.CreateRectangle2 x, y, s.SizeWidth, s.SizeHeight
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.GetLinkedShapes

Function **GetLinkedShapes(**LinkType As cdrShapeLinkType**)** As ShapeRange

Description

Member of Shape

The **GetLinkedShapes** method returns all the shapes linked in some way to the current shape.

Parameter	Description
LinkType	Specifies the type of link, and returns cdrShapeLinkType

Copyright 2014 Corel Corporation. All rights reserved.

Shape.GetMatrix

Sub **GetMatrix(***d11 As Double*, *d12 As Double*, *d21 As Double*, *d22 As Double*, *tx As Double*, *ty As Double***)**

Description

Member of Shape

The **GetMatrix** method returns the values of the transformation matrix of a shape.

- A transformation matrix is four numbers that include two transformations and two translations (or movements). Each matrix element is referred to as **d11**, **d12**, **d21**, and **d22** respectively, left to right and top to bottom.

Parameter	Description
d11	Specifies the horizontal stretch factor multiplied by the cosine of the rotation angle
d12	Specifies the vertical stretch factor multiplied by the sine of the sum of the rotation and skew angles. This value is expressed as the negative of the resultant value.
d21	Specifies the horizontal stretch factor multiplied by the sine of the rotation angle
d22	Specifies the vertical stretch factor multiplied by the cosine of the sum of the rotation and skew angles
tx	
ty	

VBA example

The following VBA example stretches each object along their x-axis by **200**%. When applied to rotated objects, it causes the stretch along the rotated axes; for example, a rotated text object is stretched along its baseline without skewing it.

```
Sub Test()
 Dim d11 As Double, d12 As Double, d21 As Double, d22 As Double
 Dim tx As Double, ty As Double, s As Shape
 For Each s In ActivePage.Shapes
  s.GetMatrix d11, d12, d21, d22, tx, ty
  s.SetMatrix d11 * 2, d12, d21 * 2, d22, tx, ty
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.GetOverprintFillState

Function **GetOverprintFillState()** As cdrOverprintState

Description

Member of Shape

The **GetOverprintFillState** method returns the overprint fill-state flags for a shape.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.GetOverprintOutlineState

Function **GetOverprintOutlineState()** As cdrOverprintState

Description

Member of Shape

The **GetOverprintFillState** method returns the overprint outline-state flags for a shape.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.GetPosition

Sub **GetPosition(***PositionX As Double***,** *PositionY As Double***)**

Description

Member of Shape

The **GetPosition** method returns the coordinates of a point on a shape as specified by the Document.ReferencePoint property.

- See also the Shape.PositionX and Shape.PositionY properties.

Parameter	Description
PositionX	Specifies, in document units, the horizontal position of the shape
PositionY	Specifies, in document units, the vertical position of the shape

VBA example

The following VBA example creates a small circle in the center of each shape on the page.

```
Sub Test()
 Dim x As Double, y As Double
 Dim s As Shape
 ActiveDocument.ReferencePoint = cdrCenter
 For Each s In ActivePage.Shapes
  s.GetPosition x, y
  ActiveLayer.CreateEllipse2 x, y, 0.03
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.GetPositionEx

Sub **GetPositionEx(**ReferencePoint As cdrReferencePoint**,** *x As Double*, *y As Double***)**

Description

Member of Shape

The **GetPositionEx** method returns the coordinates of a specified point.

Parameter	Description
ReferencePoint	Specifies the reference point
x	Specifies the x-coordinate
y	Specifies the y-coordinate

Copyright 2014 Corel Corporation. All rights reserved.

Shape.GetSize

Sub **GetSize(***Width As Double***,** *Height As Double***)**

Description

Member of Shape

The **GetSize** method returns the horizontal and vertical size of a shape.

- See also the Shape.SizeWidth and Shape.SizeHeight properties.

Parameter	Description
Width	Specifies the width of the shape object, in document units
Height	Specifies the height of the shape object, in document units

VBA example

The following VBA example returns the width and height of each shape on the active page, and it creates a rectangle with the same dimensions.

```
Sub Test()
 Dim s As Shape
 Dim x As Double, y As Double
 ActiveDocument.ReferencePoint = cdrBottomLeft
 For Each s In ActivePage.Shapes
  s.GetSize x, y
  ActiveLayer.CreateRectangle2 0, 0, x, y
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Group

Function **Group()** As Shape

Description

Member of Shape

The **Group** method groups the shapes that are part of the current shape and returns the group.

- This method is applicable for selection shapes only (that is, shapes whose Shape.Type property is cdrSelectionShape).

VBA example

The following VBA example groups the current selection and moves the group to the current layer.

```
Sub Test()
 Dim g As Shape
 Set g = ActiveSelection.Group
 g.Layer = ActiveLayer
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Guide

Property **Guide** As Guide

Description

Member of Shape

The **Guide** property returns a Guide object that represents the guideline properties of a guideline shape.

The **Guide** property returns a read-only value.

VBA example

The following VBA example shows how many guidelines of each type exist on the master page.

```
Sub Test()
 Dim s As Shape
 Dim hg As Long, vg As Long, sg As Long
 vg = 0: sg = 0: hg = 0
 For Each s In ActiveDocument.Pages(0).Guides(cdrAllGuides)
  Select Case s.Guide.Type
   Case cdrVerticalGuide
    vg = vg + 1
   Case cdrSlantedGuide
    sg = sg + 1
   Case cdrHorizontalGuide
    hg = hg + 1
  End Select
 Next s
 MsgBox "The document contains:" & vbCr & _
  "Horizontal guides: " & hg & vbCr & _
  "Vertical guides: " & vg & vbCr & _
  "Slanted guides: " & sg
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Intersect

Function **Intersect(**TargetShape As Shape**, [**LeaveSource As Boolean = True**], [**LeaveTarget As Boolean = True**])** As Shape

Description

Member of Shape

The **Intersect** method creates a shape consisting of an intersection of two shapes.

Parameter	Description
TargetShape	Specifies the shape with which to intersect
LeaveSource	Specifies whether to keep the intersected shape after the intersection is complete. This parameter is optional, and its default value is **True**.
LeaveTarget	Specifies whether to keep the intersecting shape after the intersection is complete. This parameter is optional, and its default value is **True**.

VBA example

The following VBA example creates a color diagram for the additive color model (RGB). Three circles are filled, each with red, green, and blue. At the intersections of the circles, the resulting color blend fills the areas: white in the middle, and cyan, magenta, and yellow in the areas between each pair of circles.

```
Sub Test()
 Dim s(0 To 2) As Shape
 Dim si(0 To 2) As Shape
 Dim sm As Shape
 Dim x As Double, y As Double
 Dim i As Long, n As Long
 Dim r As Long, g As Long, b As Long
 Dim c1 As Color, c2 As Color
 For i = 0 To 2
  x = ActivePage.SizeWidth / 2 + 1 * Cos(i * 2.09439507)
  y = ActivePage.SizeHeight / 2 + 1 * Sin(i * 2.09439507)
  Set s(i) = ActiveLayer.CreateEllipse2(x, y, 1.5)
  r = -255 * (i = 0)
  g = -255 * (i = 1)
  b = -255 * (i = 2)
  s(i).Fill.UniformColor.RGBAssign r, g, b
 Next i
 For i = 0 To 2
  n = (i + 1) Mod 3
  Set si(i) = s(i).Intersect(s(n))
  Set c1 = s(i).Fill.UniformColor
  Set c2 = s(n).Fill.UniformColor
  r = c1.RGBRed + c2.RGBRed
  g = c1.RGBGreen + c2.RGBGreen
  b = c1.RGBBlue + c2.RGBBlue
  si(i).Fill.UniformColor.RGBAssign r, g, b
 Next i
 Set sm = si(1).Intersect(si(2))
 sm.Fill.UniformColor.RGBAssign 255, 255, 255
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.IsOnShape

Function **IsOnShape(***x As Double***,** *y As Double***, [**HotArea As Double = -1**])** As cdrPositionOfPointOverShape

Description

Member of Shape

The **IsOnShape** method determines whether a given point lies inside a shape or on its outline.

This method returns cdrPositionOfPointOverShape.

Parameter	Description
x	Specifies the horizontal position of the point in the active document
y	Specifies the vertical position of the point in the active document
HotArea	Specifies the tolerance radius in which to evaluate the presence of the shape. This parameter is optional, and its default value is **-1**.

VBA example

The following VBA example lets the user click anywhere in the document and determine whether any shape's outline or fill area was clicked. If so, the color of the outline or fill is changed to yellow. This script runs until **Esc** is pressed.

```
Sub Test()
 Dim s As Shape
 Dim x As Double, y As Double
 While ActiveDocument.GetUserClick(x, y, 0, 100, False, cdrCursorPickOvertarget) = 0
  For Each s In ActivePage.Shapes
   Select Case s.IsOnShape(x, y)
    Case cdrOnMarginOfShape
     If s.Outline.Type = cdrOutline Then
      s.Outline.Color.RGBAssign 255, 255, 0
      Exit For
     End If
    Case cdrInsideShape
     s.Fill.UniformColor.RGBAssign 255, 255, 0
     Exit For
   End Select
  Next s
 Wend
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.IsSimpleShape

Property **IsSimpleShape** As Boolean

Description

Member of Shape

The **IsSimpleShape** property returns **True** if a shape is not a group shape of any type.

The **IsSimpleShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.IsTypeAnyOf

Function **IsTypeAnyOf(***ParamArray TypeList() As Variant***)** As Boolean

Description

Member of Shape

The **IsTypeAnyOf** method returns **True** if a shape is of any type specified in a given list.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Layer

Property **Layer** As Layer

Description

Member of Shape

The **Layer** property returns or specifies the document layer on which the active shape resides.

VBA example

The following VBA example moves all rectangles to a separate layer.

```
Sub Test()
 Dim s As Shape
 Dim lr As Layer
 Set lr = ActivePage.CreateLayer("Rectangles")
 For Each s In ActivePage.FindShapes(Type:=cdrRectangleShape)
  s.Layer = lr
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.LeftX

Property **LeftX** As Double

Description

Member of Shape

The **LeftX** property returns the x-coordinate of the left edge of a shape.

The **LeftX** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Locked

Property **Locked** As Boolean

Description

Member of Shape

The **Locked** property determines whether the position of a shape is locked on a page.

VBA example

The following VBA example calculates how many shapes are locked on the active page in the current document.

```
Sub Test()
 Dim s As Shape
 Dim n As Long
 n = 0
 For Each s In ActivePage.Shapes
  If s.Locked Then n = n + 1
 Next s
 MsgBox "There are " & n & " shapes locked on the current page"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Move

Sub **Move(***DeltaX As Double***,** *DeltaY As Double***)**

Description

Member of Shape

The **Move** method moves a shape by a specified offset, relative to its previous position. Positive values of offset move the shape to the right and upwards, while negative values move it to the left and downwards.

Parameter	Description
DeltaX	Specifies the horizontal distance to move the shape
DeltaY	Specifies the vertical distance to move the shape

VBA example

The following VBA example creates a blend between two circles, separates the blend group, and scatters all intermediate blend steps randomly.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Dim e As Effect, sr As ShapeRange
 Dim s As Shape
 Set s1 = ActiveLayer.CreateEllipse(0, 10, 2, 8)
 Set s2 = s1.Duplicate(5, -7)
 s1.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
 s2.Fill.UniformColor.CMYKAssign 0, 100, 100, 0
 Set e = s2.CreateBlend(s1)
 Set sr = e.Separate
 For Each s In sr(1).Shapes
  s.Move Rnd() - 0.5, Rnd() - 0.5
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.MoveToLayer

Sub **MoveToLayer(**Layer As Layer**)**

Description

Member of Shape

The **MoveToLayer** method moves a shape to a specified layer.

Parameter	Description
Layer	Specifies the layer

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Name

Property **Name** As String

Description

Member of Shape

The **Name** property returns or specifies the name (string) associated with a shape. If this property was not changed, an empty string is returned.

VBA example

The following VBA example gives each polygon a consecutively numbered name.

```
Sub Test()
 Dim s As Shape
 Dim n As Long
 n = 1
 For Each s In ActivePage.Shapes
  If s.Type = cdrPolygonShape Then s.Name = "Polygon " & n: n = n + 1
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Next

Property **Next([**Level As cdrShapeLevel = cdrLevelPage**], [**EnterGroups As Boolean = False**], [**Loop As Boolean = True**])** As Shape

Description

Member of Shape

The **Next** property returns the next shape in a document.

The **Next** property returns a read-only value.

Parameter	Description
Level	Specifies whether to limit the scope to the current group, layer, page, or document. This parameter is optional, and its default value is cdrLevelPage (**3**).
EnterGroups	Specifies how to handle grouped shapes. If this value is set to **False**, groups are treated as separate shapes, ignoring any shapes within the group. If it is set to **True**, group shapes are still returned. This parameter is optional, and its default value is **False**.
Loop	Specifies how to loop during the search. If this value is set to **True** and the last shape in the scope is reached, the first shape of the group, layer, or document is returned. Otherwise, **Nothing** is returned. This parameter is optional, and its default value is **True**.

VBA example

The following VBA example selects the next shape on a current layer, entering groups as necessary.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveShape
 If s Is Nothing Then
  MsgBox "Nothing is selected."
 Else
  s.Next(cdrLevelLayer, True, True).CreateSelection
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.ObjectData

Property **ObjectData** As DataItems

Description

Member of Shape

The **ObjectData** property returns a DataItems collection, which represents the object data associated with a shape.

- Object data can also be manipulated through the **Object Data Manager** in CorelDRAW.

The **ObjectData** property returns a read-only value.

VBA example

The following VBA example creates a new data field and sets it to the area of a shape for each shape encountered on the active page.

```
Sub Test()
 Dim s As Shape, x As Double, y As Double
 ActiveDocument.DataFields.Add "Area", "0.000"
 For Each s In ActivePage.Shapes
  s.GetSize x, y
  s.ObjectData("Area").Value = x * y
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.OLE

Property **OLE** As OLE

Description

Member of Shape

The **OLE** property returns an OLE object.

The **OLE** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.OrderBackOf

Sub **OrderBackOf(**Shape As Shape**)**

Description

Member of Shape

The **OrderBackOf** method places a shape behind a specified shape in the stacking order of the same layer.

Parameter	Description
Shape	Specifies the shape to have another shape placed behind it in the stacking order

VBA example

The following VBA example creates a gray rectangle behind the selected shape.

```
Sub Test()
 Dim s As Shape, r As Shape
 Dim x As Double, y As Double, sx As Double, sy As Double
 If ActiveSelection.Shapes.Count = 1 Then
  Set s = ActiveShape
  s.GetBoundingBox x, y, sx, sy
  Set r = ActiveLayer.CreateRectangle2(x, y, sx, sy)
  r.Fill.UniformColor.RGBAssign 225, 225, 225
  r.OrderBackOf s
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.OrderBackOne

Sub **OrderBackOne()**

Description

Member of Shape

The **OrderBackOne** method moves a shape one step backward in the stacking order.

VBA example

The following VBA example creates a gray rectangle behind the selected shape, and it then moves the selected shape behind the rectangle.

```
Sub Test()
 Dim s As Shape, r As Shape
 Dim x As Double, y As Double, sx As Double, sy As Double
 If ActiveSelection.Shapes.Count = 1 Then
  Set s = ActiveShape
  s.GetBoundingBox x, y, sx, sy
  Set r = ActiveLayer.CreateRectangle2(x, y, sx, sy)
  r.Fill.UniformColor.RGBAssign 225, 225, 225
  r.OrderBackOf s
  s.OrderBackOne
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.OrderForwardOne

Sub **OrderForwardOne()**

Description

Member of Shape

The **OrderForwardOne** method moves a shape one step forward in the stacking order.

VBA example

The following VBA example moves the active shape one step forward.

```
Sub Test()
 ActiveShape.OrderForwardOne
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.OrderFrontOf

Sub **OrderFrontOf(**Shape As Shape**)**

Description

Member of Shape

The **OrderFrontOf** method places a shape in front of a specified shape in the stacking order of the same layer.

Parameter	Description
Shape	Specifies the shape to have another shape placed in front of it in the stacking order

VBA example

The following VBA example creates a gray rectangle in front of the selected shape, and it then moves the selected shape in front of the rectangle.

```
Sub Test()
 Dim s As Shape, r As Shape
 Dim x As Double, y As Double, sx As Double, sy As Double
 If ActiveSelection.Shapes.Count = 1 Then
  Set s = ActiveLayer.CreateEllipse(2, 2, 5, 5)
  s.GetBoundingBox x, y, sx, sy
  Set r = ActiveLayer.CreateRectangle2(x, y, sx, sy)
  r.Fill.UniformColor.RGBAssign 225, 225, 225
  s.OrderFrontOf r
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.OrderIsInFrontOf

Function **OrderIsInFrontOf(**Shape As Shape**)** As Boolean

Description

Member of Shape

The **OrderIsInFrontOf** method determines whether a shape is in front of a specified shape in the stacking order.

Parameter	Description
Shape	Specifies the shape to be checked, to determine whether another shape is in front of it (that is, above it) in the stacking order

VBA example

The following VBA example fills, with red, all shapes above the selected one.

```
Sub Test()
 Dim s As Shape, ss As Shape
 Set s = ActiveShape
 For Each ss In ActiveLayer.Shapes
  If ss.OrderIsInFrontOf(s) And Not ss Is s Then
   ss.Fill.UniformColor.RGBAssign 255, 0, 0
  End If
 Next ss
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.OrderReverse

Sub **OrderReverse()**

Description

Member of Shape

The **OrderReverse** method reverses the stacking order of all selected shapes.

- This method can be applied only to a selection shape.

VBA example

The following VBA example reverses the order of the selected shapes in the active document.

```
Sub Test()
 ActiveSelection.OrderReverse
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.OrderToBack

Sub **OrderToBack()**

Description

Member of Shape

The **OrderToBack** method moves a shape to the front of the stacking order.

VBA example

The following VBA example creates a page frame rectangle and places it behind all other shapes on the current layer.

```
Sub Test()
 Dim Frame As Shape
 Set Frame = ActiveLayer.CreateRectangle(0, 0, ActivePage.SizeWidth, ActivePage.SizeHeight)
 Frame.Fill.ApplyFountainFill CreateRGBColor(255, 0, 0), CreateRGBColor(0, 0, 0)
 Frame.OrderToBack
 Frame.Locked = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.OrderToFront

Sub **OrderToFront()**

Description

Member of Shape

The **OrderToFront** method moves a shape to the front of the stacking order.

VBA example

The following VBA example creates a page frame rectangle and places it in front of all other shapes on the active layer.

```
Sub Test()
 Dim Frame As Shape
 Set Frame = ActiveLayer.CreateRectangle(0, 0, ActivePage.SizeWidth, _
  ActivePage.SizeHeight)
 Frame.Fill.ApplyFountainFill CreateRGBColor(255, 0, 0), _
  CreateRGBColor(0, 0, 0)
 Frame.OrderToFront
 Frame.Locked = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.OriginalHeight

Property **OriginalHeight** As Double

Description

Member of Shape

The **OriginalHeight** property returns the height of a shape at creation, before any transformations were applied to it.

The **OriginalHeight** property returns a read-only value.

VBA example

The following VBA example creates a rectangle that copies all the transformations of the currently selected shape.

```
Sub Test()
 Const g2rad As Double = 1.74532925199433E-02
 Dim s As Shape, r As Shape
 Dim x As Double, y As Double
 Set s = ActiveShape
 If s Is Nothing Then
  MsgBox "Nothing selected. Please try again", vbCritical
  Exit Sub
 End If
 ActiveDocument.ReferencePoint = cdrCenter
 s.GetPosition x, y
 x = x - s.OriginalWidth / 2
 y = y - s.OriginalHeight / 2
 Set r = ActiveLayer.CreateRectangle2(x, y, s.OriginalWidth, s.OriginalHeight)
 r.Stretch s.AbsoluteHScale, s.AbsoluteVScale * Cos(s.AbsoluteSkew * g2rad)
 r.Skew s.AbsoluteSkew, 0
 r.Rotate s.RotationAngle
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.OriginalWidth

Property **OriginalWidth** As Double

Description

Member of Shape

The **OriginalWidth** property returns the width of a shape at creation, before any transformations were applied to it.

The **OriginalWidth** property returns a read-only value.

VBA example

The following VBA example creates a rectangle that copies all the transformations of the currently selected shape.

```
Sub Test()
 Const g2rad As Double = 1.74532925199433E-02
 Dim s As Shape, r As Shape
 Dim x As Double, y As Double
 Set s = ActiveShape
 If s Is Nothing Then
  MsgBox "Nothing selected. Please try again", vbCritical
  Exit Sub
 End If
 ActiveDocument.ReferencePoint = cdrCenter
 s.GetPosition x, y
 x = x - s.OriginalWidth / 2
 y = y - s.OriginalHeight / 2
 Set r = ActiveLayer.CreateRectangle2(x, y, s.OriginalWidth, s.OriginalHeight)
 r.Stretch s.AbsoluteHScale, s.AbsoluteVScale * Cos(s.AbsoluteSkew * g2rad)
 r.Skew s.AbsoluteSkew, 0
 r.Rotate s.RotationAngle
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Outline

Property **Outline** As Outline

Description

Member of Shape

The **Outline** property returns an Outline object that represents the outline properties of a shape.

The **Outline** property returns a read-only value.

VBA example

The following VBA example applies a **0.1**" wide outline to the selected object if it does not already have an outline.

```
Sub Test()
 If ActiveShape.Outline.Type = cdrNoOutline Then
  ActiveShape.Outline.Width = 0.1
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.OverprintBitmap

Property **OverprintBitmap** As Boolean

Description

Member of Shape

The **OverprintBitmap** property returns or specifies whether to overprint a bitmap.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.OverprintFill

Property **OverprintFill** As Boolean

Description

Member of Shape

The **OverprintFill** property returns or specifies whether to overprint the fill of an object.

VBA example

The following VBA example previews overprinted fills in the drawing by creating additional objects where two or more shapes intersect. These new objects are filled with the appropriate resultant colors. There must be at least two overlapping shapes in the document.

```
' Previews fill overprints on screen
Public Sub CreateOverprint()
 Dim n1 As Long
 Dim n2 As Long
 Dim s1 As Shape
 Dim s2 As Shape
 Dim s As Shape
 Dim shps As Shapes
 Dim c1 As New color
 Dim c2 As New color
 ActiveDocument.ReferencePoint = cdrBottomLeft
 ActiveDocument.ShapeEnumDirection = cdrShapeEnumBottomFirst
 ' Look through all shapes from bottom to top
 Set shps = ActivePage.Shapes
 For n1 = 1 To shps.Count - 1
  Set s1 = shps(n1)
  If s1.Fill.Type = cdrUniformFill Then
   ' If the shape has a uniform fill, get its color
   c1.CopyAssign s1.Fill.UniformColor
   ' Check all shapes above it
   For n2 = n1 + 1 To shps.Count
    Set s2 = shps(n2)
    If s2.Fill.Type = cdrUniformFill And s2.OverprintFill Then
     ' If the shape has a uniform fill has Overprint fill specified,
     ' get its color
     c2.CopyAssign s2.Fill.UniformColor
     If Overlap(s1, s2) Then
      ' If the shapes may overlap, mix the two colors and ...
      MixColors c1, c2
      ' ... create the intersecting shape
      Set s = s1.Intersect(s2)
      If Not s Is Nothing Then
       ' If anything was generated during intersection,
       ' apply the resulting color to it and mark the shape with
       ' overprint fill attribute for future processing
       s.Fill.ApplyUniformFill c2
       s.OverprintFill = True
      End If
     End If
    End If
   Next n2
  End If
 Next n1
End Sub
' Determines if the two shapes may overlap
Private Function Overlap(s1 As Shape, s2 As Shape) As Boolean
 Dim x1 As Double, y1 As Double, w1 As Double, h1 As Double
 Dim x2 As Double, y2 As Double, w2 As Double, h2 As Double
 s1.GetBoundingBox x1, y1, w1, h1
 s2.GetBoundingBox x2, y2, w2, h2
 Overlap = Not (x1 + w1 < x2 Or x2 + w2 < x1 Or y1 + h1 < y2 Or y2 + h2 < y1)
End Function
' Mixes two colors according to their inks
Private Sub MixColors(c1 As color, c2 As color)
 Dim cc1 As New color
 Dim bSpot As Boolean
 cc1.CopyAssign c1
 If cc1.Type <> cdrColorCMYK Then cc1.ConvertToCMYK
 bSpot = (c1.Type = cdrColorSpot Or c1.Type = cdrColorPantone Or _
    c2.Type = cdrColorSpot Or c2.Type = cdrColorPantone)
 If c2.Type <> cdrColorCMYK Then c2.ConvertToCMYK
 If Not bSpot Then
  ' If we are mixing process colors, only replace the color channels that
  ' have no color in the top shape
  If c2.CMYKBlack = 0 Then c2.CMYKBlack = cc1.CMYKBlack
  If c2.CMYKCyan = 0 Then c2.CMYKCyan = cc1.CMYKCyan
  If c2.CMYKMagenta = 0 Then c2.CMYKMagenta = cc1.CMYKMagenta
  If c2.CMYKYellow = 0 Then c2.CMYKYellow = cc1.CMYKYellow
 Else
  ' If we are mixing spot colors, just add inks
  c2.CMYKBlack = GetMaxInk(cc1.CMYKBlack + c2.CMYKBlack)
  c2.CMYKCyan = GetMaxInk(cc1.CMYKCyan + c2.CMYKCyan)
  c2.CMYKMagenta = GetMaxInk(cc1.CMYKMagenta + c2.CMYKMagenta)
  c2.CMYKYellow = GetMaxInk(cc1.CMYKYellow + c2.CMYKYellow)
 End If
End Sub
' Makes sure the ink level doesn't exceed 100%
Private Function GetMaxInk(Ink As Long) As Long
 Dim n As Long
 n = Ink
```

```
 If n > 100 Then n = 100
 GetMaxInk = n
End Function
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.OverprintOutline

Property **OverprintOutline** As Boolean

Description

Member of Shape

The **OverprintOutline** property returns or specifies whether to overprint the outline of an object.

VBA example

The following VBA example creates a rectangle and specifies that its fill is overprinted by its outline.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 3, 3)
 s.Fill.ApplyUniformFill CreateRGBColor(155, 0, 155)
 s.OverprintOutline = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Page

Property **Page** As Page

Description

Member of Shape

The **Page** property returns a read-only value that is associated with the page to which a shape belongs.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Parent

Property **Parent** As Object

Description

Member of Shape

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.ParentGroup

Property **ParentGroup** As Shape

Description

Member of Shape

The **ParentGroup** property returns a Shape object that represents the group shape to which the active shape belongs. If the shape is not part of a group, **Nothing** is selected.

The **ParentGroup** property returns a read-only value.

VBA example

The following VBA example extracts an object from a group and places it at the same level as the group object.

```
Sub Test()
 Dim s As Shape, g As Shape
 Set s = ActiveShape
 If s Is Nothing Then
  MsgBox "Please select an object", vbCritical
  Exit Sub
 End If
 Set g = s.ParentGroup
 If g Is Nothing Then
  MsgBox "Please select an object within a group", vbCritical
  Exit Sub
 End If
 ActiveDocument.PreserveSelection = False
 g.CreateSelection
 g.Ungroup
 s.Selected = False
 ActiveSelection.Group
 s.CreateSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.PixelAlignedRendering

Property **PixelAlignedRendering** As Boolean

Description

Member of Shape

The **PixelAlignedRendering** property returns or specifies the alignment-to-pixel property for a shape.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.PlaceTextInside

Function **PlaceTextInside(**TextShape As Shape**)** As Shape

Description

Member of Shape

The **PlaceTextInside** method places specified text inside a shape.

Parameter	Description
TextShape	Specifies the shape in which to place the text

VBA example

The following VBA example places the text inside the ellipse.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Set s1 = ActiveLayer.CreateEllipse(0, 0, 2, 2)
 Set s = ActiveLayer.CreateArtisticText(0, 0, "My Text", , , "Arial Black", 24)
 s1.PlaceTextInside s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Polygon

Property **Polygon** As Polygon

Description

Member of Shape

The **Polygon** property returns a Polygon object that represents the settings for a symmetrical polygon shape.

The **Polygon** property returns a read-only value.

VBA example

The following VBA example converts all symmetrical polygon shapes on the active page to five-point star polygons.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Type = cdrPolygonShape Then
   s.Polygon.Sides = 5
   s.Polygon.Type = cdrStar
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.PositionX

Property **PositionX** As Double

Description

Member of Shape

The **PositionX** property returns or specifies the horizontal, or x-, coordinate of a shape. The position is relative to a reference point specified by the Document.ReferencePoint property.

- See also the Shape.GetPosition, Shape.SetPosition, and Shape.Move methods.

VBA example

The following VBA example moves objects, as needed, so that they are all within the current page boundaries.

```
Sub Test()
 Dim s As Shape
 Dim pw As Double, ph As Double
 ActivePage.GetSize pw, ph
 For Each s In ActivePage.Shapes
  If s.Type <> cdrGuidelineShape Then
   ActiveDocument.ReferencePoint = cdrBottomLeft
   If s.PositionX < 0 Then s.PositionX = 0
   If s.PositionY < 0 Then s.PositionY = 0
   ActiveDocument.ReferencePoint = cdrTopRight
   If s.PositionX > pw Then s.PositionX = pw
   If s.PositionY > ph Then s.PositionY = ph
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.PositionY

Property **PositionY** As Double

Description

Member of Shape

The **PositionY** property returns or specifies the vertical, or y-, coordinate of a shape. The position is relative to a reference point specified by the Document.ReferencePoint property.

- See also the Shape.GetPosition, Shape.SetPosition, and Shape.Move methods.

VBA example

The following VBA example moves objects, as needed, so that they are all within the current page boundaries.

```
Sub Test()
 Dim s As Shape
 Dim pw As Double, ph As Double
 ActivePage.GetSize pw, ph
 For Each s In ActivePage.Shapes
  If s.Type <> cdrGuidelineShape Then
   ActiveDocument.ReferencePoint = cdrBottomLeft
   If s.PositionX < 0 Then s.PositionX = 0
   If s.PositionY < 0 Then s.PositionY = 0
   ActiveDocument.ReferencePoint = cdrTopRight
   If s.PositionX > pw Then s.PositionX = pw
   If s.PositionY > ph Then s.PositionY = ph
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.PowerClip

Property **PowerClip** As PowerClip

Description

Member of Shape

The **PowerClip** property returns a PowerClip object that represents the properties for a PowerClip container. You can use this object to access the shapes in a PowerClip container, or to change the properties of a PowerClip object.

The **PowerClip** property returns a read-only value.

VBA example

The following VBA example extracts shapes from all PowerClip containers on the current page.

```
Sub Test()
 Dim s As Shape
 Dim pwc As PowerClip
 For Each s In ActivePage.Shapes
  Set pwc = Nothing
  On Error Resume Next
  Set pwc = s.PowerClip
  On Error GoTo 0
  If Not pwc Is Nothing Then
   s.CreateSelection
   pwc.ExtractShapes
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.PowerClipParent

Property **PowerClipParent** As Shape

Description

Member of Shape

The **PowerClipParent** property returns a shape that represents the PowerClip container for a given shape.

The **PowerClipParent** property returns a read-only value.

VBA example

The following VBA example fills each shape in the current PowerClip container with a lighter tint of the color of the PowerClip container.

```
Sub Test()
 Dim s As Shape
 Dim c As New Color
 If ActiveShape Is Nothing Then
  MsgBox "Select a powerclip container"
  Exit Sub
 End If
 If ActiveShape.Fill.Type <> cdrUniformFill Then
  MsgBox "Powerclip container must have a uniform fill"
  Exit Sub
 End If
 For Each s In ActiveShape.PowerClip.Shapes
  c.CopyAssign s.PowerClipParent.Fill.UniformColor
  Select Case c.Type
   Case cdrColorRGB
    c.RGBBlue = (c.RGBBlue + 255) \ 2
    c.RGBGreen = (c.RGBGreen + 255) \ 2
    c.RGBRed = (c.RGBRed + 255) \ 2
   Case cdrColorCMYK
    c.CMYKBlack = c.CMYKBlack \ 2
    c.CMYKCyan = c.CMYKCyan \ 2
    c.CMYKMagenta = c.CMYKMagenta \ 2
    c.CMYKYellow = c.CMYKYellow \ 2
   Case Else
    c.ConvertToHLS
    c.HLSLightness = (c.HLSLightness + 255) \ 2
  End Select
  s.Fill.ApplyUniformFill c
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Previous

Property **Previous([**Level As cdrShapeLevel = cdrLevelPage**], [**EnterGroups As Boolean = False**], [**Loop As Boolean = True**])** As Shape

Description

Member of Shape

The **Previous** property returns the previous shape in a document.

The **Previous** property returns a read-only value.

Parameter	Description
Level	Specifies whether to limit the scope to the current group, layer, page, or document. This parameter is optional, and its default value is cdrLevelPage (**3**).
EnterGroups	Specifies how to handle groups. If this value is set to **False**, groups are treated as separate shapes, ignoring any shapes within the group. If it is set to **True**, group shapes are still returned. This parameter is optional, and its default value is **False**.
Loop	Specifies how to loop through the search. If this value is set to **True** and the last shape in the scope is reached, the first shape of the group, layer, or document is returned. Otherwise, **Nothing** is returned. This parameter is optional, and its default value is **True**.

VBA example

The following VBA example selects the next shape on the current layer. There must be at least two shapes in the document, and one shape must be selected.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveShape
 If s Is Nothing Then
  MsgBox "Nothing is selected."
 Else
  s.Previous(cdrLevelLayer, True, True).CreateSelection
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Project

Function **Project(**Plane As cdrProjectPlane**, [**ReferencePoint As cdrReferencePoint = cdrCenter**], [**ApplyToDuplicate As Boolean = False**])** As Shape

Description

Member of Shape

The **Project** method converts a two-dimensional shape into a three-dimensional shape.

Parameter	Description
Plane	Specifies the isometric view
ReferencePoint	Specifies the reference point for the conversion. This parameter is optional, and its default value is cdrCenter.
ApplyToDuplicate	Specifies whether to apply the conversion to a duplicate, leaving the original shape unchanged. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example projects a rectangle to the top isometric plane, using the upper-right corner of the rectangle as the reference point.

```
Sub Test()
Dim shp1 As Shape
Set shp1 = ActiveLayer.CreateRectangle2(0,0,10,20)
shp1.Project cdrProjectTop, cdrProjectRight
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Properties

Property **Properties** As Properties

Description

Member of Shape

The **Properties** property returns a Properties collection, which allows you to specify and manipulate custom data associated with a given shape. Data stored using the **Properties** collection is not accessible to the CorelDRAW user and can be retrieved only programmatically. You can use this property as an advanced way of storing custom data with a shape.

- See also the Shape.ObjectData property.

The **Properties** property returns a read-only value.

VBA example

The following VBA example stores all uniform fill colors with each shape so that each fill can be restored later.

```
Sub StoreFills()
 Dim s As Shape
 Dim c(0 To 7) As Long, i As Long
 For Each s In ActivePage.Shapes
  If s.Fill.Type = cdrUniformFill Then
   s.Fill.UniformColor.CorelScriptGetComponent c(0), c(1), c(2), c(3), c(4), c(5), c(6), c(7)
   For i = 0 To 7
    s.Properties("StoredFillColor", i) = c(i)
   Next i
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Rectangle

Property **Rectangle** As Rectangle

Description

Member of Shape

The **Rectangle** property returns a Rectangle object that represents the settings for a rectangle shape.

The **Rectangle** property returns a read-only value.

VBA example

The following VBA example sets the roundness of all rectangles on a page to **30**%.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Type = cdrRectangleShape Then
   s.Rectangle.SetRoundness 30
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.RemoveFromContainer

Sub **RemoveFromContainer([***Level As Long***])**

Description

Member of Shape

The **RemoveFromContainer** method removes a shape from its PowerClip container.

- If there are several nested PowerClip objects, you can remove a shape from several containers at a time by specifying the **Level** parameter value.

Parameter	Description
Level	Specifies the lowest level from which to remove the shape. The shape is removed from this level and all levels above it. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example removes all ellipses from all PowerClip objects on the current page.

```
Sub Test()
 Dim s As Shape, ss As Shape
 Dim p As PowerClip
 On Error Resume Next
 For Each s In ActivePage.Shapes
  Set p = Nothing
  Set p = s.PowerClip
  If Not p Is Nothing Then
   For Each ss In p.Shapes
    If ss.Type = cdrEllipseShape Then
     ActiveDocument.ClearSelection
     ss.RemoveFromContainer
    End If
   Next ss
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.RemoveFromSelection

Sub **RemoveFromSelection()**

Description

Member of Shape

The **RemoveFromSelection** method removes a shape from a selection.

- This method does not work if the shape is a selection shape.

VBA example

The following VBA example removes all text objects from the selection.

```
Sub Test()
 Dim sr As ShapeRange
 Dim s As Shape
 Set sr = ActiveDocument.SelectionRange
 For Each s In sr
  If s.Type = cdrTextShape Then s.RemoveFromSelection
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.ReplaceWith

Sub **ReplaceWith(**VirtualShape As Shape**)**

Description

Member of Shape

The **ReplaceWith** method logs a shape-replacement transaction that can be undone if desired.

Parameter	Description
VirtualShape	Specifies the replacement shape

Copyright 2014 Corel Corporation. All rights reserved.

Shape.RightX

Property **RightX** As Double

Description

Member of Shape

The **RightX** property returns the x-coordinate of the right edge of a shape.

The **RightX** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Rotate

Sub **Rotate(***Angle As Double***)**

Description

Member of Shape

The **Rotate** method rotates a shape. The center of rotation is specified by the Shape.RotationCenterX and Shape.RotationCenterY properties of the shape.

Parameter	Description
Angle	Specifies the number of degrees to rotate the shape

VBA example

The following VBA example creates a flower with randomly colored petals.

```
Sub Test()
 Const NumLeafs As Long = 11
 Dim pal As Palette
 Dim s As Shape
 Dim i As Long, NumColors As Long
 Set s = Nothing
 If ActivePalette Is Nothing Then
  Set pal = Palettes.Open(Application.SetupPath & "Custom\coreldrw.xml")
 Else
  Set pal = ActivePalette
 End If
 NumColors = pal.ColorCount
 For i = 1 To NumLeafs
  If s Is Nothing Then
   Set s = ActiveLayer.CreateEllipse(5, 5, 7, 6)
   s.RotationCenterX = 4
   s.RotationCenterY = 5.5
  Else
   s.Duplicate
  End If
  s.Fill.ApplyUniformFill pal.Color(Rnd() * NumColors + 1)
  s.Rotate 360 / NumLeafs
 Next i
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.RotateEx

Sub **RotateEx(***Angle As Double*, *CenterX As Double*, *CenterY As Double***)**

Description

Member of Shape

The **RotateEx** method rotates a shape around a specified center of rotation.

Parameter	Description
Angle	Specifies the angle measurement, in degrees, in which to rotate the shape
CenterX	Specifies the x-coordinate for the center of rotation
CenterY	Specifies the y-coordinate for the center of rotation

VBA example

The following VBA example creates a flower with randomly colored petals.

```
Sub Test()
 Const NumLeafs As Long = 11
 Dim pal As Palette
 Dim s As Shape
 Dim i As Long, NumColors As Long
 Set s = Nothing
 If ActivePalette Is Nothing Then
  Set pal = Palettes.Open(Application.SetupPath & "Custom\coreldrw.xml")
 Else
  Set pal = ActivePalette
 End If
 NumColors = pal.ColorCount
 For i = 1 To NumLeafs
  If s Is Nothing Then
   Set s = ActiveLayer.CreateEllipse(5, 5, 7, 6)
   s.RotationCenterX = 4
   s.RotationCenterY = 5.5
  Else
   s.Duplicate
  End If
  s.Fill.ApplyUniformFill pal.Color(Rnd() * NumColors + 1)
  s.RotateEx 360 / NumLeafs, ActivePage.SizeHeight / 2, ActivePage.SizeWidth / 2
 Next i
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.RotationAngle

Property **RotationAngle** As Double

Description

Member of Shape

The **RotationAngle** property returns or specifies the angle at which a shape was rotated. Assigning a value to this property rotates the shape so that its resulting rotation angle equals the specified value.

VBA example

The following VBA example removes any rotation from the shapes on a page.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.RotationAngle <> 0 Then
   s.RotationAngle = 0
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.RotationCenterX

Property **RotationCenterX** As Double

Description

Member of Shape

The **RotationCenterX** returns or specifies the x-coordinate of the center of rotation for a shape.

- See also the Shape.SetRotationCenter method.

VBA example

The following VBA example creates a flower with randomly colored petals.

```
Sub Test()
 Const NumLeafs As Long = 11
 Dim pal As Palette
 Dim s As Shape
 Dim i As Long, NumColors As Long
 If ActivePalette Is Nothing Then
  Set pal = Palettes.Open(Application.SetupPath & "Custom\coreldrw.xml")
 Else
  Set pal = ActivePalette
 End If
 NumColors = pal.ColorCount
 For i = 1 To NumLeafs
  If s Is Nothing Then
   Set s = ActiveLayer.CreateEllipse(5, 5, 7, 6)
   s.RotationCenterX = 4
   s.RotationCenterY = 5.5
  Else
   s.Duplicate
  End If
  s.Fill.ApplyUniformFill pal.Color(Rnd() * NumColors + 1)
  s.Rotate 360 / NumLeafs
 Next i
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.RotationCenterY

Property **RotationCenterY** As Double

Description

Member of Shape

The **RotationCenterY** returns or specifies the y-coordinate of the center of rotation for a shape.

- See also the Shape.SetRotationCenter method.

VBA example

The following VBA example creates a flower with randomly-colored petals.

```
Sub Test()
 Const NumLeafs As Long = 11
 Dim pal As Palette
 Dim s As Shape
 Dim i As Long, NumColors As Long
 Set s = Nothing
 If ActivePalette Is Nothing Then
  Set pal = Palettes.Open(Application.SetupPath & "Custom\coreldrw.xml")
 Else
  Set pal = ActivePalette
 End If
 NumColors = pal.ColorCount
 For i = 1 To NumLeafs
  If s Is Nothing Then
   Set s = ActiveLayer.CreateEllipse(5, 5, 7, 6)
   s.RotationCenterX = 4
   s.RotationCenterY = 5.5
  Else
   s.Duplicate
  End If
  s.Fill.ApplyUniformFill pal.Color(Rnd() * NumColors + 1)
  s.Rotate 360 / NumLeafs
 Next i
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Scallop

Sub **Scallop(***Radius As Double***, [**CombineSmoothSegments As Boolean = True**])**

Description

Member of Shape

The **Scallop** method creates scallops on each cusp corner of a shape.

Parameter	Description
Radius	Specifies the radius of the scallops
CombineSmoothSegments	Specifies whether to combine smooth segments. This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Selectable

Property **Selectable** As Boolean

Description

Member of Shape

The **Selectable** property determines whether the shape is both visible and unlocked.

The **Selectable** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Selected

Property **Selected** As Boolean

Description

Member of Shape

The **Selected** property returns or specifies whether a shape is selected.

- Changing the value of this property adds or removes the shape to or from the current selection.

- See also the Shape.CreateSelection, Document.ClearSelection, ShapeRange.AddToSelection, and ShapeRange.RemoveFromSelection methods.

VBA example

The following VBA example removes any rectangles from the current selection.

```
Sub Test()
 Dim s As Shape
 For Each s In ActiveSelection.Shapes
  If s.Type = cdrRectangleShape Then s.Selected = False
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Separate

Sub **Separate()**

Description

Member of Shape

The **Separate** method separates effect shapes (that is, combined shapes or linked groups, such as blend groups or drop shadows).

- This method is provided for compatibility reasons. The suggested method is Effect.Separate.

VBA example 1

The following VBA example creates a blend between two ellipses and separates it.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Set s1 = ActiveLayer.CreateEllipse(0, 10, 2, 8)
 Set s2 = s1.Duplicate(5, -7)
 s1.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
 s2.Fill.UniformColor.CMYKAssign 0, 100, 100, 0
 s2.CreateBlend(s1).Blend.BlendGroup.CreateSelection
 s2.Selected = True
 s1.Selected = True
 ActiveSelection.Separate
End Sub
```

VBA example 2

The following VBA example performs the same procedure as the previous example but using the Effect.Separate method.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Set s1 = ActiveLayer.CreateEllipse(0, 10, 2, 8)
 Set s2 = s1.Duplicate(5, -7)
 s1.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
 s2.Fill.UniformColor.CMYKAssign 0, 100, 100, 0
 s2.CreateBlend(s1).Separate
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.SetBoundingBox

Sub **SetBoundingBox(***x As Double***,** *y As Double***,** *Width As Double***,** *Height As Double***, [**KeepAspect As Boolean = False**], [**ReferencePoint As cdrReferencePoint = cdrCenter**])**

Description

Member of Shape

The **SetBoundingBox** method moves and resizes a shape so that it fits the specified bounding box.

- You can resize a shape with or without maintaining its proportions. The default shape position within the bounding box can be specified.

Parameter	Description
x	Specifies, in document units, the horizontal position, or x-coordinate, of the center of the bounding box
y	Specifies, in document units, the vertical position, or y-coordinate, of the center of the bounding box
Width	Specifies, in document units, the width of the bounding box
Height	Specifies, in document units, the height of the bounding box
KeepAspect	Specifies whether the size proportions of the bounding box are maintained relative to its contents. This parameter is optional, and its default value is **False**.
ReferencePoint	Specifies the reference point. This parameter is optional, and its default value is cdrCenter (**9**).

VBA example

The following VBA example creates a new document and imports all images from the specified folder, arranging them in an array of thumbnails on the page.

```
Sub Test()
 Const NumX As Long = 4 ' Number of thumbnails horizontally
 Const NumY As Long = 5 ' Number of thumbnails vertically
 Const Margin As Double = 0.5 ' Page margin in inches
 Const Gutter As Double = 0.1 ' Thumbnail gutter in inches
 Const Caption As Double = 0.2 ' Image caption size in inches
 Const Folder As String = "C:\Temp\Images\" ' Folder path
 Dim s As Shape, doc As Document
 Dim nx As Long, ny As Long
 Dim x As Double, y As Double, sx As Double, sy As Double
 Dim f As String
 nx = 0
 ny = 0
 Set doc = CreateDocument()
 sx = (doc.ActivePage.SizeWidth - 2 * Margin - (NumX - 1) * Gutter) / NumX
 sy = (doc.ActivePage.SizeHeight - 2 * Margin - (NumY - 1) * Gutter) / NumY
 ' Find first file in the folder
 f = Dir(Folder & "*.*")
 While f <> ""
  x = Margin + nx * (Gutter + sx)
  y = Margin + ny * (Gutter + sy)
  ' Create a rectangle to hold a thumbnail
  doc.ActiveLayer.CreateRectangle2 x, y + Caption, sx, sy - Caption
  ' Place a file name caption below the rectangle
  With doc.ActiveLayer.CreateArtisticText(x + sx / 2, y, f).Text
   .AlignProperties.Alignment = cdrCenterAlignment
   With .FontProperties
    .Name = "Arial"
    .Size = 10
   End With
  End With
  doc.ClearSelection
  ' Import the file
  doc.ActiveLayer.Import Folder & f
  If Not doc.ActiveShape Is Nothing Then
   ' If anything is imported, place it inside the rectangle
   ActiveShape.SetBoundingBox x, y + Caption, sx, sy - Caption, True, cdrCenter
  End If
  nx = nx + 1
  If nx = NumX Then
   nx = 0
   ny = ny + 1
   If ny = NumY Then
    doc.AddPages 1 ' Add the page if the current one is full
    ny = 0
   End If
  End If
  ' Find next file
```

```
  f = Dir()
 Wend
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.SetMatrix

Sub **SetMatrix(***d11 As Double*, *d12 As Double*, *d21 As Double*, *d22 As Double*, *tx As Double*, *ty As Double***)**

Description

Member of Shape

The **SetMatrix** method sets the values for the transformation matrix of a shape.

- A transformation matrix is four numbers that include two transformations and two translations (or movements). Each matrix element is referred to as **d11**, **d12**, **d21**, and **d22** respectively, left to right and top to bottom.

Parameter	Description
d11	Specifies the horizontal stretch factor multiplied by the cosine of the rotation angle
d12	Specifies the vertical stretch factor multiplied by the sine of the sum of the rotation and skew angles. This value is expressed as the negative of the resultant value.
d21	Specifies the horizontal stretch factor multiplied by the sine of the rotation angle
d22	Specifies the vertical stretch factor multiplied by the cosine of the sum of the rotation and skew angles
tx	
ty	

VBA example

The following VBA example stretches each object along its x-axis by **200**%. When applied to rotated objects, it causes the stretch along the rotated axes; for example, a rotated text object is stretched along its baseline without skewing it.

```
Sub Test()
 Dim d11 As Double, d12 As Double, d21 As Double, d22 As Double
 Dim tx As Double, ty As Double, s As Shape
 For Each s In ActivePage.Shapes
  s.GetMatrix d11, d12, d21, d22, tx, ty
  s.SetMatrix d11 * 2, d12, d21 * 2, d22, tx, ty
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.SetPosition

Sub **SetPosition(***PositionX As Double***,** *PositionY As Double***)**

Description

Member of Shape

The **SetPosition** method moves a shape to a given position on the page. The specified coordinates of the new position are relative to the shape's reference point, as specified by the Document.ReferencePoint property.

Parameter	Description
PositionX	Specifies, in document units, the horizontal position of the shape
PositionY	Specifies, in document units, the vertical position of the shape

VBA example

The following VBA example sets the current position of each shape on the page to the bottom-left corner of the page.

```
Sub Test()
 Dim s As Shape
 Dim x As Double, y As Double
 For Each s In ActivePage.Shapes
  s.SetPosition 0, 0
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.SetPositionEx

Sub **SetPositionEx(**ReferencePoint As cdrReferencePoint**,** *x As Double*, *y As Double***)**

Description

Member of Shape

The **SetPositionEx** method moves a shape to the coordinates of a specified point.

Parameter	Description
ReferencePoint	Specifies the reference point
x	Specifies the x-coordinate of the point
y	Specifies the y-coordinate of the point

Copyright 2014 Corel Corporation. All rights reserved.

Shape.SetRotationCenter

Sub **SetRotationCenter(***x As Double***,** *y As Double***)**

Description

Member of Shape

The **SetRotationCenter** method specifies the horizontal and veritcal positions of the center of rotation for a shape.

- See also Shape.RotationCenterX and Shape.RotationCenterY properties

Parameter	Description
x	Specifies the x-coordinate of the center of rotation
y	Specifies the y-coordinate of the center of rotation

VBA example

The following VBA example creates a flower with randomly colored petals.

```
Sub Test()
 Const NumLeafs As Long = 11
 Dim pal As Palette
 Dim s As Shape
 Dim i As Long, NumColors As Long
 Set s = Nothing
 If ActivePalette Is Nothing Then
 Set pal = Palettes.Open(Application.SetupPath & "Custom\coreldrw.xml")
 Else
  Set pal = ActivePalette
 End If
 NumColors = pal.ColorCount
 For i = 1 To NumLeafs
  If s Is Nothing Then
   Set s = ActiveLayer.CreateEllipse(5, 5, 7, 6)
   s.SetRotationCenter 4, 5.5
  Else
   s.Duplicate
 End If
  s.Fill.ApplyUniformFill pal.Color(Rnd() * NumColors + 1)
  s.Rotate 360 / NumLeafs
 Next i
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.SetSize

Sub **SetSize([***Width As Double***], [***Height As Double***])**

Description

Member of Shape

The **SetSize** method stretches a shape to fit a specified width and height.

- The shape is stretched relative to the reference point specified by the Document.ReferencePoint property. If either parameter is omitted, the other parameter is calculated based on the other dimension to maintain proportions. You cannot omit both parameters, however.

- See also the Shape.SetBoundingBox method, as well as the Shape.SizeWidth and Shape.SizeHeight properties.

Parameter	Description
Width	Specifies, in document units, the width of the shape. This parameter is optional, and its default value is **0**.
Height	Specifies, in document units, the height of the shape. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example resizes all shapes on the active page.

```
Sub Test()
 Dim s As Shape
 ActiveDocument.ReferencePoint = cdrBottomLeft
 For Each s In ActivePage.Shapes
  s.SetSize 1, 1
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.SetSizeEx

Sub **SetSizeEx**(*CenterX As Double*, *CenterY As Double*, **[***Width As Double***]**, **[***Height As Double***])**

Description

Member of Shape

The **SetSizeEx** method stretches a shape to a specified width and height, relative to the coordinates specified as the anchor point. The anchor point remains stationary, and it therefore represents the center of the distortion.

- Omitting a parameter calculates the size to maintain the proportions of the shape.

- See also the Shape.SetBoundingBox method, as well as the Shape.SizeWidth and Shape.SizeHeight properties.

Parameter	Description
CenterX	Specifies the x-coordinate of the anchor point
CenterY	Specifies the y-coordinate of the anchor point
Width	Specifies the horizontal measurement, in document units. This parameter is optional, and its default value is **0**.
Height	Specifies the vertical measurement, in document units. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example stretches all shapes on the active layer proportionally so that their horizontal size is **2**".

```
Sub Test()
 Dim x As Double, y As Double
 Dim sr As ShapeRange
 Set sr = ActiveLayer.Shapes.All
 If sr.Count > 0 Then
  ActiveDocument.ReferencePoint = cdrCenter
  sr.GetPosition x, y
  sr.SetSizeEx x, y, 2
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Shapes

Property **Shapes** As Shapes

Description

Member of Shape

The **Shapes** property returns a Shapes collection.

This property is valid only for a group shape. The returned collection contains all shapes that are part of the group.

The **Shapes** property returns a read-only value.

VBA example

The following VBA example converts all uniform fill colors to grayscale.

```
Sub Test()
 ConvertFills ActivePage.Shapes
End Sub
Private Sub ConvertFills(ss As Shapes)
 Dim s As Shape
 For Each s In ss
  If s.Type = cdrGroupShape Then
   'If this is a group shape, then all the shapes in this group
   'are processed by calling the function recursively.
   ConvertFills s.Shapes
  Else
   If s.Fill.Type = cdrUniformFill Then
    s.Fill.UniformColor.ConvertToGray
   End If
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.SizeHeight

Property **SizeHeight** As Double

Description

Member of Shape

The **SizeHeight** property returns or specifies the vertical size of a shape. Changing this property stretches the shape to accommodate the specified size.

- See also the Shape.GetSize, Shape.SetSize, and Shape.GetBoundingBox methods.

VBA example

The following VBA example creates a rectangle around each shape on a page.

```
Sub Test()
 Dim s As Shape
 Dim x As Double, y As Double
 ActiveDocument.ReferencePoint = cdrBottomLeft
 For Each s In ActivePage.Shapes
  s.GetPosition x, y
  ActiveLayer.CreateRectangle2 x, y, s.SizeWidth, s.SizeHeight
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.SizeWidth

Property **SizeWidth** As Double

Description

Member of Shape

The **SizeWidth** property returns or specifies the horizontal size of a shape. Changing this property stretches the shape to accommodate the specified size.

- See also the Shape.GetSize, Shape.SetSize, and Shape.GetBoundingBox methods.

VBA example

The following VBA example creates a rectangle around each shape on a page.

```
Sub Test()
 Dim s As Shape
 Dim x As Double, y As Double
 ActiveDocument.ReferencePoint = cdrBottomLeft
 For Each s In ActivePage.Shapes
  s.GetPosition x, y
  ActiveLayer.CreateRectangle2 x, y, s.SizeWidth, s.SizeHeight
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Skew

Sub **Skew(***AngleX As Double***,** *AngleY As Double***)**

Description

Member of Shape

The **Skew** method skews a shape relative to the reference point specified by the Document.ReferencePoint property.

Parameter	Description
AngleX	Specifies the degree by which to slant the shape horizontally
AngleY	Specifies the degree by which to slant the shape vertically

VBA example

The following VBA example creates an isometric cube.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape, s3 As Shape
 Set s1 = ActiveLayer.CreateRectangle(2.5, 8.5, 4.5, 6.5)
 s1.Fill.UniformColor.CMYKAssign 0, 100, 100, 0
 Set s2 = s1.Duplicate
 s2.Fill.UniformColor.CMYKAssign 100, 0, 0, 0
 ActiveDocument.ReferencePoint = cdrTopLeft
 s2.Stretch 0.866025, 1
 s2.Skew 0, -30
 s2.Move -0.866025, 0.5
 Set s3 = s1.Duplicate
 s3.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
 s3.Stretch 0.866025, 1
 s3.Skew 0, 30
 s3.Move 0.866025, -0.5
 s1.Stretch 0.866025, 1
 s1.Skew 0, 30
 s1.Rotate -60
 s1.Move 0, 1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.SkewEx

Sub **SkewEx(***AngleX As Double***,** *AngleY As Double***,** *CenterX As Double***,** *CenterY As Double***)**

Description

Member of Shape

The **SkewEx** method skews a shape by using the point coordinates specified as the center of distortion.

Parameter	Description
AngleX	Specifies the horizontal angle, in degrees, by which to skew the object
AngleY	Specifies the vertical angle, in degrees, by which to skew the object
CenterX	Specifies the x-coordinate for the center of distortion
CenterY	Specifies the y-coordinate for the center of distortion

VBA example

The following VBA example creates an isometric cube.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape, s3 As Shape
 Set s1 = ActiveLayer.CreateRectangle(2.5, 8.5, 4.5, 6.5)
 s1.Fill.UniformColor.CMYKAssign 0, 100, 100, 0
 Set s2 = s1.Duplicate
 s2.Fill.UniformColor.CMYKAssign 100, 0, 0, 0
 ActiveDocument.ReferencePoint = cdrTopLeft
 s2.Stretch 0.866025, 1
 s2.SkewEx 0, 30, 1, 1
 s2.Move -0.866025, 0.5
 Set s3 = s1.Duplicate
 s3.Fill.UniformColor.CMYKAssign 0, 0, 100, 0
 s3.Stretch 0.866025, 1
 s3.SkewEx 0, 30, 1, 1
 s3.Move 0.866025, -0.5
 s1.Stretch 0.866025, 1
 s1.SkewEx 0, 30, 1, 1
 s1.Rotate -60
 s1.Move 0, 1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.SnapPoints

Property **SnapPoints** As SnapPoints

Description

Member of Shape

The **SnapPoints** property returns a SnapPoints collection, which represents connection points for the **Connector** tool.

The **SnapPoints** property returns a read-only value.

VBA example 1

The following VBA example creates an ellipse at the position of each connection point of the active shape.

```
Sub Test()
 Dim sp As SnapPoint
 For Each sp In ActiveShape.SnapPoints
  ActiveLayer.CreateEllipse2 sp.PositionX, sp.PositionY, 0.1
 Next sp
End Sub
```

VBA example 2

The following VBA example creates a rectangle and an ellipse, and it connects their centers with a connector line.

```
Sub Test()
Dim rect As Shape, ell As Shape
Dim lr As Layer
Set lr = ActiveLayer
Set rect = lr.CreateRectangle(0, 0, 3, 3)
Set ell = lr.CreateEllipse2(5, 5, 1, 1)
lr.CreateConnector rect.SnapPoints(2), ell.SnapPoints(4)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.SnapPointsOfType

Property **SnapPointsOfType(**TypeSet As cdrPointType**)** As SnapPoints

Description

Member of Shape

The **SnapPointsOfType** method returns a collection of snap points of a given type.

Parameter	Description
TypeSet	Specifies, through a value of cdrPointType, the snap-point type

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Spread

Property **Spread** As Spread

Description

Member of Shape

The **Spread** property returns a read-only value that is associated with the spread to which a shape belongs.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.StaticID

Property **StaticID** As Long

Description

Member of Shape

The **StaticID** property returns an integer representing a unique ID number assigned to each shape. This number does not change and can therefore be used throughout the lifetime of the shape.

The **StaticID** property returns a read-only value.

VBA example 1

The following VBA example stores the current selection in the array of the active page properties.

```
Sub SaveSelection()
 Dim s As Shape, n As Long
 ActivePage.Properties("StoredSelection", 0) = ActiveSelection.Shapes.Count
 n = 1
 For Each s In ActiveSelection.Shapes
  ActivePage.Properties("StoredSelection", n) = s.StaticID ' Store the current shape's ID number
  n = n + 1
 Next s
End Sub
```

VBA example 2

The following VBA example restores the selection that was saved in the properties of the active page in the previous example.

```
Sub RestoreSelection()
 Dim s As Shape, sr As New ShapeRange
 Dim v As Variant
 Dim Num As Long, i As Long, id As Long
 v = ActivePage.Properties("StoredSelection", 0) ' Retrieving the total number of shape references stored
 If Not IsNull(v) Then
  ActivePage.Properties.Delete "StoredSelection", 0 ' Delete the property
  Num = v
  For i = 1 To Num
   id = ActivePage.Properties("StoredSelection", i) ' Getting the current shape's ID to find
   Set s = ActivePage.FindShape(StaticID:=id)
   If Not s Is Nothing Then sr.Add s ' Add the shape to the shape range if it still exists in document
   ActivePage.Properties.Delete "StoredSelection", i ' Delete the property
  Next i
  sr.CreateSelection ' Selects all shapes found
 Else
  MsgBox "No selection stored in the active page"
 End If
End Sub
```

- You can use the Page.FindShape or Layer.FindShape methods to locate a shape based on its unique ID.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.StepAndRepeat

Function **StepAndRepeat(***NumCopies As Long***,** *DistanceX As Double***,** *DistanceY As Double***,** **[**ModeX As cdrDistanceMode = cdrModeOffset**],** **[**DirectionX As cdrDirection = cdrRight**],** **[**ModeY As cdrDistanceMode = cdrModeOffset**],** **[**DirectionY As cdrDirection = cdrDown**])** As ShapeRange

Description

Member of Shape

The **StepAndRepeat** method creates multiple copies of a shape.

Parameter	Description
NumCopies	Specifies the number of copies to create
DistanceX	Specifies the horizontal distance by which to offset the copies
DistanceY	Specifies the vertical distance by which to offset the copies
ModeX	This parameter is optional, and its default value is cdrModeOffset (**0**).
DirectionX	This parameter is optional, and its default value is cdrRight (**1**).
ModeY	This parameter is optional, and its default value is cdrModeOffset (**0**).
DirectionY	This parameter is optional, and its default value is cdrDown (**3**).

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Stretch

Sub **Stretch(***StretchX As Double***, [***StretchY As Double***], [**StretchCharactersSize As Boolean = False**])**

Description

Member of Shape

The **Stretch** method stretches a shape relative to the reference point specified by the Document.ReferencePoint property.

Parameter	Description
StretchX	Specifies the distance to stretch the shape horizontally
StretchY	Specifies the distance to stretch the shape vertically. If this value is omitted, it is assumed to be the same as the **StretchX** parameter value, resulting in a proportional stretch. This parameter is optional, and its default value is **0**.
StretchCharactersSize	Specifies whether characters are stretched with the shape. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example stretches each shape on the current layer by **200**%, relative to the center of each shape.

```
Sub Test()
 Dim s As Shape
 ActiveDocument.ReferencePoint = cdrCenter
 For Each s In ActiveLayer.Shapes
  s.CreateSelection
  s.Stretch 2
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.StretchEx

Sub **StretchEx(***CenterX As Double***,** *CenterY As Double***,** *StretchX As Double***, [***StretchY As Double***], [**StretchCharactersSize As Boolean = False**])**

Description

Member of Shape

The **StretchEx** method stretches a shape to a specified width and height, relative to the coordinates specified as the center of distortion.

Parameter	Description
CenterX	Specifies the x-coordinate of the center of distortion
CenterY	Specifies the y-coordinate of the center of distortion
StretchX	Specifies the horizontal stretch factor
StretchY	Specifies the vertical stretch factor. If this value is omitted, it is assumed to be the same as the **StretchX** parameter value, resulting in a proportional stretch. This parameter is optional, and its default value is **0**.
StretchCharactersSize	Specifies whether characters are stretched with the shape. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example stretches all shapes on the page by **200**%, using the center of the page as the center of the distortion.

```
Sub Test()
 ActiveDocument.ReferencePoint = cdrBottomLeft
 With ActivePage
  .Shapes.All.StretchEx .CenterX, .CenterY, 2
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Style

Property **Style** As Style

Description

Member of Shape

The **Style** property returns the style applied to a shape. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Symbol

Property **Symbol** As Symbol

Description

Member of Shape

The **Symbol** property returns the Symbol property of a shape.

The **Symbol** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Text

Property **Text** As Text

Description

Member of Shape

The **Text** property returns a Text object that represents the settings for a text shape.

The **Text** property returns a read-only value.

VBA example

The following VBA example displays the type of the text.

```
Sub Test()
 Dim s As Shape
 Dim TextType As String
 Set s = ActiveLayer.CreateArtisticText(1, 2, "This is a shape.")
 s.Text.ConvertToParagraph
 Select Case s.Text.Type
  Case 0
   TextType = "Artistic Text"
  Case 1
   TextType = "Paragraph Text"
  Case 2
   TextType = "Artistic Fitted Text"
  Case 3
   TextType = "Paragraph Fitted Text"
 End Select
 MsgBox TextType
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.TextWrapOffset

Property **TextWrapOffset** As Double

Description

Member of Shape

The **TextWrapOffset** property returns or specifies the offset of wrapped text from its object.

VBA example

The following VBA example wraps the paragraph text around the ellipse and offsets the text **0.5**" from the ellipse.

```
Sub Test()
 Dim ell As Shape
 ActiveLayer.CreateParagraphText 1, 1, ActivePage.SizeWidth - 1, _
  ActivePage.SizeHeight - 1, String$(2000, "a"), , , , 24
 Set ell = ActiveLayer.CreateEllipse(2, 9, 6, 4)
 ell.WrapText = cdrWrapContourStraddle
 ell.TextWrapOffset = 0.5
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.TopY

Property **TopY** As Double

Description

Member of Shape

The **TopY** property returns the y-coordinate of the top edge of a shape.

The **TopY** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.TransformMatrix

Sub **TransformMatrix(***d11 As Double*, *d12 As Double*, *d21 As Double*, *d22 As Double*, *tx As Double*, *ty As Double***)**

Description

Member of Shape

The **TransformMatrix** method modifies the transformation matrix of a shape by multiplying it by the given matrix.

- A transformation matrix is four numbers that include two transformations and two translations (or movements). Each matrix element is referred to as **d11**, **d12**, **d21**, and **d22** respectively, left to right and top to bottom.

Parameter	Description
d11	Specifies the horizontal stretch factor multiplied by the cosine of the rotation angle
d12	Specifies the vertical stretch factor multiplied by the sine of the sum of the rotation and skew angles. This value is expressed as the negative of the resultant value.
d21	Specifies the horizontal stretch factor multiplied by the sine of the rotation angle
d22	Specifies the vertical stretch factor multiplied by the cosine of the sum of the rotation and skew angles
tx	
ty	

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Transparency

Property **Transparency** As Transparency

Description

Member of Shape

The **Transparency** property returns a Transparency object that represents the transparency settings for the active shape.

The **Transparency** property returns a read-only value.

VBA example

The following VBA example applies a **40**% uniform transparency to all rectangles and a fountain transparency to all ellipses on a page.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  Select Case s.Type
   Case cdrRectangleShape
    s.Transparency.ApplyUniformTransparency 40
    ' Working around the ApplyUnifromTransparency method
    If s.Transparency.Uniform <> 40 Then
     s.Transparency.Uniform = 40
    End If
   Case cdrEllipseShape
    s.Transparency.ApplyFountainTransparency Angle:=45
   Case Else
    If s.Transparency.Type <> cdrNoTransparency Then
     s.Transparency.ApplyNoTransparency
    End If
  End Select
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.TreeNode

Property **TreeNode** As TreeNode

Description

Member of Shape

The **TreeNode** property returns the tree node corresponding to a given shape.

The **TreeNode** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Trim

Function **Trim(**TargetShape As Shape**, [**LeaveSource As Boolean = True**], [**LeaveTarget As Boolean = False**])** As Shape

Description

Member of Shape

The **Trim** method trims a shape.

Parameter	Description
TargetShape	Specifies the shape with which to trim
LeaveSource	Specifies whether to keep an original of the trimmed shape. This parameter is optional, and its default value is **True**.
LeaveTarget	Specifies whether to keep the shape with which the trim was performed. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example creates text embossed on a texturized surface.

```
Sub Test()
 Const Offset As Double = 0.05
 Dim sBase As Shape, sLight As Shape, sDark As Shape
 Dim sRect As Shape
 Set sRect = ActiveLayer.CreateRectangle2(0.75, 4, 7, 3)
 Set sBase = ActiveLayer.CreateArtisticText(4.25, 4.75, "Bevel")
 With sBase.Text
  With .FontProperties
   .Name = "Arial"
   .Size = 150
   .Style = cdrBoldFontStyle
  End With
  .AlignProperties.Alignment = cdrCenterAlignment
 End With
 Set sLight = sBase.Duplicate(-Offset, Offset)
 Set sLight = sBase.Trim(sLight)
 sLight.Fill.UniformColor.CMYKAssign 20, 0, 20, 0
 Set sDark = sBase.Duplicate(Offset, -Offset)
 sDark.Fill.UniformColor.CMYKAssign 100, 0, 100, 80
 sBase.Trim sDark, False, False
 sRect.Fill.ApplyTextureFill "Ivy on a Wall", "Samples 7"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Type

Property **Type** As cdrShapeType

Description

Member of Shape

The **Type** property returns the type of a shape. You can use this property to distinguish among shape types (rectangles, ellipses, text, curves, and so on).

The **Type** property returns a read-only value.

VBA example

The following VBA example distorts a curve by moving each of its nodes by a random offset.

```
Sub Test()
 Dim x As Double, y As Double, max As Double
 Dim n As Node
 If ActiveShape Is Nothing Then
  MsgBox "Select an object first", vbCritical
  Exit Sub
 End If
 If ActiveShape.Type <> cdrCurveShape Then ActiveShape.ConvertToCurves
 If ActiveShape.Type <> cdrCurveShape Then
  MsgBox "Unable to convert the object to curve", vbCritical
  Exit Sub
 End If
 ActiveShape.GetSize x, y
 If x < y Then max = y / 10 Else max = x / 10
 For Each n In ActiveShape.Curve.Nodes
  n.Move (Rnd() - 0.5) * max, (Rnd() - 0.5) * max
 Next n
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Ungroup

Sub **Ungroup()**

Description

Member of Shape

The **Ungroup** method ungroups all shapes in a given group.

VBA example

The following VBA example creates two circles and builds a blend between them. It then separates the blend, ungroups the blend steps, and scatters them randomly.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Dim s As Shape
 Dim g As ShapeRange, stps As ShapeRange
 Set s1 = ActiveLayer.CreateEllipse(0, 0, 2, 2)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 Set s2 = ActiveLayer.CreateEllipse(6, 6, 7, 7)
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 s1.CreateBlend s2
 Set g = s1.Effects(1).Separate
 Set stps = g(1).Shapes.All
 g(1).Ungroup
 For Each s In stps
  s.Move (Rnd() - 0.5) * s.SizeWidth, (Rnd() - 0.5) * s.SizeHeight
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.UngroupAll

Sub **UngroupAll()**

Description

Member of Shape

The **UngroupAll** method ungroups all shapes in a given group and in any subgroups contained by it.

VBA example

The following VBA example ungroups any nested groups on the active page. Top-level groups remain unchanged, while nested groups are ungrouped.

```
Sub Test()
 Dim s As Shape, sg As Shape
 For Each s In ActivePage.Shapes
  If s.Type = cdrGroupShape Then
   For Each sg In s.Shapes
    If sg.Type = cdrGroupShape Then
     sg.UngroupAll
    End If
   Next sg
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeUngroupAllEx

Function **UngroupAllEx()** As ShapeRange

Description

Member of Shape

The **UngroupAllEx** method ungroups all shapes in a specified group and in any subgroups contained by it. The shapes are returned as a shape range (or ShapeRange object).

VBA example

The following VBA example fills each subgroup with a random RGB color.

```
Sub Test()
 Dim s As Shape, sg As Shape, sr As ShapeRange
 For Each s In ActivePage.Shapes
  If s.Type = cdrGroupShape Then
   For Each sg In s.Shapes
    If sg.Type = cdrGroupShape Then
     Set sr = sg.UngroupAllEx
     sr.ApplyUniformFill CreateRGBColor(255 * (Rnd() * 255), 255 * (Rnd * 255), 255 * (Rnd * 255))
    End If
   Next sg
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.UngroupEx

Function **UngroupEx()** As ShapeRange

Description

Member of Shape

The **UngroupEx** method ungroups all shapes in a specified group and returns the ungrouped shapes as a shape range (or ShapeRange object).

VBA example

The following VBA example creates two circles and builds a blend between them. The blend is separated, while the blend steps are ungrouped and scattered randomly.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Dim s As Shape
 Dim g As ShapeRange, stps As ShapeRange
 Set s1 = ActiveLayer.CreateEllipse(0, 0, 2, 2)
 s1.Fill.UniformColor.RGBAssign 255, 0, 0
 Set s2 = ActiveLayer.CreateEllipse(6, 6, 7, 7)
 s2.Fill.UniformColor.RGBAssign 255, 255, 0
 s1.CreateBlend s2
 Set g = s1.Effects(1).Separate
 Set stps = g(1).UngroupEx
 For Each s In stps
  s.Move (Rnd() - 0.5) * s.SizeWidth, (Rnd() - 0.5) * s.SizeHeight
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Unproject

Function **Unproject(**Plane As cdrProjectPlane**, [**ReferencePoint As cdrReferencePoint = cdrCenter**], [**ApplyToDuplicate As Boolean = False**])** As Shape

Description

Member of Shape

The **Unproject** method converts a three-dimensional shape into a two-dimensional shape.

Parameter	Description
Plane	Specifies the isometric view
ReferencePoint	Specifies the reference point for the conversion. This parameter is optional, and its default value is cdrCenter.
ApplyToDuplicate	Specifies whether to apply the conversion to a duplicate, leaving the original shape unchanged. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example projects a rectangle to the top isometric plane, using the upper-right corner of the rectangle as the reference point.

```
Sub Test()
Dim shp1 As Shape
Set shp1 = ActiveLayer.CreateRectangle2(0,0,10,20)
shp1.Project cdrProjectTop, cdrProjectRight
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.URL

Property **URL** As URL

Description

Member of Shape

The **URL** property returns a URL object that represents the hyperlink properties associated with a shape.

The **URL** property returns a read-only value.

VBA example

The following VBA example sets a bookmark for each rectangle on the page and links each ellipse to each rectangle.

```
Sub Test()
 Dim s As Shape
 Dim col As New Collection
 Dim n As Long
 For Each s In ActivePage.FindShapes(Type:=cdrRectangleShape)
  col.Add s.StaticID
  s.URL.BookMark = "Rectangle" & s.StaticID
 Next s
 n = 1
 For Each s In ActivePage.FindShapes(Type:=cdrEllipseShape)
  If n > col.Count Then Exit For
  s.URL.Address = "Rectangle" & col(n)
  s.URL.AltComment = "Link to the rectangle shape"
  n = n + 1
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Virtual

Property **Virtual** As Boolean

Description

Member of Shape

The **Virtual** property returns **True** if a shape is a temporary object.

The **Virtual** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shape.Weld

Function **Weld(**TargetShape As Shape**, [**LeaveSource As Boolean = False**], [**LeaveTarget As Boolean = False**])** As Shape

Description

Member of Shape

The **Weld** method welds shapes together.

Parameter	Description
TargetShape	Specifies the shape with which to weld
LeaveSource	Specifies whether to keep an original of the welded shape. This parameter is optional, and its default value is **False**.
LeaveTarget	Specifies whether to keep the shape with which the weld was performed. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example creates a circle and a square, and it then welds them together.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Dim s As Shape
 Set s1 = ActiveLayer.CreateEllipse2(4, 5, 2)
 Set s2 = ActiveLayer.CreateRectangle2(2, 1, 4, 4)
 Set s = s1.Weld(s2)
 s.Fill.UniformColor.CMYKAssign 100, 0, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.WrapText

Property **WrapText** As cdrWrapStyle

Description

Member of Shape

The **WrapText** property returns or specifies a style when wrapping paragraph text.

VBA example

The following VBA example wraps the paragraph text around the ellipse.

```
Sub Test()
 Dim ell As Shape
 ActiveLayer.CreateParagraphText 1, 1, ActivePage.SizeWidth - 1, _
  ActivePage.SizeHeight - 1, String$(2000, "a"), , , , 24
 Set ell = ActiveLayer.CreateEllipse(2, 9, 6, 4)
 ell.WrapText = cdrWrapContourStraddle
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shape.ZOrder

Property **ZOrder** As Long

Description

Member of Shape

The **ZOrder** property returns the index number of a shape in the collection for its parent.

The ZOrder property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange

Properties Methods

Description

The **ShapeRange** class represents a dynamic array (or range) of Shape objects. Shape-specific properties and methods can be applied to each shape in a shape range.

- You can create a **ShapeRange** object by using the **New** keyword in Visual Basic.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Add

Sub **Add(**Shape As Shape**)**

Description

Member of ShapeRange

The **Add** method adds a specified shape to a shape range.

Parameter	Description
Shape	Specifies the shape to add

VBA example

The following VBA example creates a registration mark consisting of a circle and two lines, groups the objects, and then moves them to the center of the page.

```
Sub Test()
 Dim sGroup As Shape
 Dim sr As New ShapeRange
 sr.Add ActiveLayer.CreateEllipse2(0, 0, 0.25)
 sr.Add ActiveLayer.CreateLineSegment(-0.5, 0, 0.5, 0)
 sr.Add ActiveLayer.CreateLineSegment(0, -0.5, 0, 0.5)
 sr.SetOutlineProperties 0.03
 Set sGroup = sr.Group
 sGroup.Move ActivePage.SizeWidth / 2, ActivePage.SizeHeight / 2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AddRange

Sub **AddRange(**ShapeRange As ShapeRange**)**

Description

Member of ShapeRange

The **AddRange** method adds a specified shape range to the current range.

Parameter	Description
ShapeRange	Specifies the shape range to add

VBA example

The following VBA example finds all the ellipses and rectangles on a page, and it then fills the shapes with a radial fountain fill.

```
Sub Test()
 Dim sr As ShapeRange
 Set sr = ActivePage.FindShapes(Type:=cdrEllipseShape)
 sr.AddRange ActivePage.FindShapes(Type:=cdrRectangleShape)
 sr.ApplyFountainFill CreateRGBColor(255, 0, 0), CreateRGBColor(255, 255, 0), cdrRadialFountainFill
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AddToPowerClip

Sub **AddToPowerClip(**Shape As Shape**, [**CenterInContainer As cdrTriState **=** cdrUndefined**])**

Description

Member of ShapeRange

The **AddToPowerClip** method adds a shape range to a specified PowerClip container.

Parameter	Description
Shape	Specifies the shape range to add
CenterInContainer	Specifies whether to center the shape range in the PowerClip container. This parameter is optional, and its default value is cdrUndefined (**-2**).

VBA example

The following VBA example places **150** randomly-sized and randomly-colored circles inside a text object.

```
Sub Test()
 Dim sr As New ShapeRange
 Dim s As Shape, n As Long
 For n = 1 To 150
  Set s = ActiveLayer.CreateEllipse2(Rnd() * 4, Rnd() * 2, Rnd() * 0.3)
  s.Fill.UniformColor.RGBAssign Rnd() * 256, Rnd() * 256, Rnd() * 256
  sr.Add s
 Next n
 Set s = ActiveLayer.CreateArtisticText(0, 0, "Clip")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 150
 End With
 sr.AddToPowerClip s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AddToSelection

Sub **AddToSelection()**

Description

Member of ShapeRange

The **AddToSelection** method adds all the shapes in a shape range to the current selection.

- See also the ShapeRange.CreateSelection and ShapeRange.RemoveFromSelection methods

VBA example

The following VBA example selects all the ellipses and rectangles on the current page.

```
Sub Test()
 ActivePage.FindShapes(Type:=cdrEllipseShape).CreateSelection
 ActivePage.FindShapes(Type:=cdrRectangleShape).AddToSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AffineTransform

Sub **AffineTransform(***d11 As Double*, *d12 As Double*, *d21 As Double*, *d22 As Double*, *CenterX As Double*, *CenterY As Double***)**

Description

Member of ShapeRange

The **AffineTransform** method applies an affine transformation — as defined by the transformation-matrix components — to a shape range, relative to the center point of the transformation.

- A transformation matrix is four numbers that include two transformations and two translations (or movements). Each matrix element is referred to as **d11**, **d12**, **d21**, and **d22** respectively, left to right and top to bottom.

Parameter	Description
d11	Specifies the horizontal stretch factor multiplied by the cosine of the rotation angle
d12	Specifies the vertical stretch factor multiplied by the sine of the sum of the rotation and skew angles. This value is expressed as the negative of the resultant value.
d21	Specifies the horizontal stretch factor multiplied by the sine of the rotation angle
d22	Specifies the vertical stretch factor multiplied by the cosine of the sum of the rotation and skew angles
CenterX	Specifies the x-coordinate of the center point of the transformation
CenterY	Specifies the y-coordinate of the center point of the transformation

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AlignAndDistribute

Sub **AlignAndDistribute**(MethodH As cdrAlignDistributeH, *MethodV As cdrAlignDistributeV*, [*AlignTo As* cdrAlignShapesTo = *cdrAlignShapesToLastSelected (0)*], [*DistributeArea As* cdrDistributeArea = *cdrDistributeToSelection (0)*], [*UseOutline As Boolean = False*], [*TextAlignOrigin As* cdrTextAlignOrigin = *cdrTextAlignBoundingBox (2)*], [*PointX As Double = 0*], [*PointY As Double = 0*], [*DistributeRect As Rect = 0*])

Description

Member of ShapeRange

The **AlignAndDistribute** method aligns and/or distributes the shape or shapes in the shape range.

Parameter	Description
MethodH	Specifies which method is used for aligning and distributing objects horizontally
MethodV	Specifies which method is used for aligning and distributing objects vertically
AlignTo	Specifies whether to align objects to the center or edge of the page, the grid, the last selected object, or to a defined point
DistributeArea	Specifies the area over which to distribute objects
UseOutline	Accounts for outline thickness when calculating object size and position
TextAlignOrigin	Specifies the origin for aligning text such as bounding box, first baseline, or last baseline
PointX	Specifies the x-coordinate of the reference point for aligning and distributing
PointY	Specifies the y-coordinate of the reference point for aligning and distributing objects
DistributeRect	Distributes shapes within the area of a specified rectangle

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AlignRangeToGrid

Sub **AlignRangeToGrid(**Type As cdrAlignType**)**

Description

Member of ShapeRange

The **AlignRangeToGrid** method aligns a shape range to the grid.

Parameter	Description
Type	Specifies the type of alignment

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AlignRangeToPage

Sub **AlignRangeToPage(**Type As cdrAlignType**)**

Description

Member of ShapeRange

The **AlignRangeToPage** method aligns a shape range to the edges of the page.

Parameter	Description
Type	Specifies the type of alignment

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AlignRangeToPageCenter

Sub **AlignRangeToPageCenter(**Type As cdrAlignType**)**

Description

Member of ShapeRange

The **AlignRangeToPageCenter** method aligns a shape range to the center of the page.

Parameter	Description
Type	Specifies the type of alignment

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AlignRangeToPoint

Sub **AlignRangeToPoint(**Type As cdrAlignType**,** *x As Double***,** *y As Double***)**

Description

Member of ShapeRange

The **AlignRangeToPoint** method aligns a shape range to the specified coordinates.

Parameter	Description
Type	Specifies the type of alignment
x	Specifies the x-coordinate
y	Specifies the y-coordinate

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AlignRangeToShape

Sub **AlignRangeToShape(**Type As cdrAlignType**,** Shape As Shape**)**

Description

Member of ShapeRange

The **AlignRangeToShape** method aligns a shape range to a specified shape.

Parameter	Description
Type	Specifies the type of alignment
Shape	Specifies the shape

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AlignRangeToShapeRange

Sub **AlignRangeToShapeRange(**Type As cdrAlignType**,** ShapeRange As ShapeRange**)**

Description

Member of ShapeRange

The **AlignRangeToShapeRange** method aligns a shape range to the bounding box of another shape range.

Parameter	Description
Type	Specifies the type of alignment
ShapeRange	Specifies the shape range with which to align

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AlignToGrid

Sub **AlignToGrid(**Type As cdrAlignType**, [**TextAlignOrigin As cdrTextAlignOrigin = cdrTextAlignBoundingBox**])**

Description

Member of ShapeRange

The **AlignToGrid** method aligns all the shapes in a shape range to the grid.

Parameter	Description
Type	Specifies the type of alignment
TextAlignOrigin	Specifies the origin for text alignment. This parameter is optional, and its default value is cdrTextAlignBoundingBox (**2**).

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AlignToPage

Sub **AlignToPage(**Type As cdrAlignType**, [**TextAlignOrigin As cdrTextAlignOrigin = cdrTextAlignBoundingBox**])**

Description

Member of ShapeRange

The **AlignToPage** method aligns all the shapes in a shape range to the edges of the page.

Parameter	Description
Type	Specifies the type of alignment
TextAlignOrigin	Specifies the origin for text alignment. This parameter is optional, and its default value is cdrTextAlignBoundingBox (**2**).

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AlignToPageCenter

Sub **AlignToPageCenter(**Type As cdrAlignType**, [**TextAlignOrigin As cdrTextAlignOrigin = cdrTextAlignBoundingBox**])**

Description

Member of ShapeRange

The **AlignToPageCenter** method aligns all the shapes in a shape range to the center of the page.

Parameter	Description
Type	Specifies the type of alignment
TextAlignOrigin	Specifies the origin for text alignment. This parameter is optional, and its default value is cdrTextAlignBoundingBox (**2**).

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AlignToPoint

Sub **AlignToPoint(**Type As cdrAlignType**,** *x As Double*, *y As Double*, **[**TextAlignOrigin As cdrTextAlignOrigin = cdrTextAlignBoundingBox**])**

Description

Member of ShapeRange

The **AlignToPoint** method aligns all the shapes in a shape range to the specified coordinates.

Parameter	Description
Type	Specifies the type of alignment
x	Specifies the x-coordinate
y	Specifies the y-coordinate
TextAlignOrigin	Specifies the origin for text alignment. This parameter is optional, and its default value is cdrTextAlignBoundingBox (**2**).

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AlignToShape

Sub **AlignToShape(**Type As cdrAlignType**,** Shape As Shape**, [**TextAlignOrigin As cdrTextAlignOrigin = cdrTextAlignBoundingBox**])**

Description

Member of ShapeRange

The **AlignToShape** method aligns all the shapes in a shape range to a specified shape.

Parameter	Description
Type	Specifies the type of alignment
Shape	Specifies the shape
TextAlignOrigin	Specifies the origin for text alignment. This parameter is optional, and its default value is cdrTextAlignBoundingBox (**2**).

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AlignToShapeRange

Sub **AlignToShapeRange(**Type As cdrAlignType**,** ShapeRange As ShapeRange**, [**TextAlignOrigin As cdrTextAlignOrigin = cdrTextAlignBoundingBox**])**

Description

Member of ShapeRange

The **AlignToShapeRange** method aligns all the shapes in a shape range to the bounding box of another shape range.

Parameter	Description
Type	Specifies the type of alignment
ShapeRange	Specifies the shape range with which to align
TextAlignOrigin	Specifies the origin for text alignment. This parameter is optional, and its default value is cdrTextAlignBoundingBox (**2**).

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.All

Function **All()** As ShapeRange

Description

Member of ShapeRange

The **All** method returns a copy of the current shape range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.AllExcluding

Function **AllExcluding(***IndexArray() As Variant***)** As ShapeRange

Description

Member of ShapeRange

The **AllExcluding** method creates a new shape range from all the shapes in the current range, except for the specified shapes.

Parameter	Description
IndexArray	Specifies the index number of the excluded shape range

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Application

Property **Application** As Application

Description

Member of ShapeRange

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ApplyCustomHatchFill

Sub **ApplyCustomHatchFill(***Angle As Double***,** *Spacing As Double***, [***Shift As Double***], [***OriginX As Double***], [***OriginY As Double***], [**Width As Double = -1**], [**Color As Color**], [**Style As OutlineStyle**], [**DashDotLength As Double = -1**], [***PenWidth As Double***], [**BackColor As Color**], [**TransformWithShape As Boolean = False**], [**ScaleLinesWithShape As Boolean = False**], [**UseWorldCoordinates As Boolean = False**], [***FillScale As Double***], [***LineScale As Double***], [***FillAngle As Double***], [***FillSkew As Double***])**

Description

Member of ShapeRange

The **ApplyCustomHatchFill** method applies a custom hatch fill to the shapes in a shape range.

Parameter	Description
Angle	Specifies the rotation angle of the lines in the hatch-fill pattern
Spacing	Specifies the line spacing in the hatch-fill pattern
Shift	Specifies an additional relative horizontal shift of the lines in the hatch-fill pattern. This parameter is optional, and its default value is **0**.
OriginX	Specifies the horizontal offset of the start of the first line in the hatch-fill pattern. This parameter is optional, and its default value is **0**.
OriginY	Specifies the vertical offset of the start of the first line in the hatch-fill pattern. This parameter is optional, and its default value is **0**.
Width	Specifies the width at which to apply the hatch fill. This parameter is optional, and its default value is **-1**.
Color	Specifies the color for the hatch fill. This parameter is optional, and its default value is **Nothing**.
Style	Specifies the outline style for the hatch fill. This parameter is optional, and its default value is **Nothing**.
DashDotLength	Specifies the dash-dot length of the lines in the hatch fill. This parameter is optional, and its default value is **-1**.
PenWidth	Specifies the pen width of the lines in the hatch fill. This parameter is optional, and its default value is **0**.
BackColor	Specifies a background color for the hatch fill. This parameter is optional, and its default value is **Nothing**.
TransformWithShape	Specifies whether to transform the hatch fill with the shape to which the hatch fill is applied. This parameter is optional, and its default value is **False**.
ScaleLinesWithShape	Specifies whether to scale the hatch-fill lines with the shape to which the hatch fill is applied. This parameter is optional, and its default value is **False**.
UseWorldCoordinates	Specifies whether local or world coordinates are used to align the hatch fills that are applied to different objects. This parameter is optional, and its default value is **False**.
FillScale	Specifies the average scale factor for the hatch fill. This parameter is optional, and its default value is **0**.
LineScale	Specifies the average line-thickness scale factor for the hatch fill. This parameter is optional, and its default value is **0**.
FillAngle	Specifies the rotation angle for the hatch fill. This parameter is optional, and its default value is **0**.
FillSkew	Specifies the skew angle for the hatch fill. This parameter is optional, and its default value is **0**.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ApplyEffectBCI

Sub **ApplyEffectBCI**(*Brighness As Long*, *Contrast As Long*, *Intensity As Long*)

Description

Member of ShapeRange

The **ApplyEffectBCI** method applies the Brightness-Contrast-Intensity color effect to the shapes in a shape range.

Parameter	Description
Brighness	Specifies the brightness level
Contrast	Specifies the contrast level
Intensity	Specifies the intensity level

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ApplyEffectColorBalance

Sub **ApplyEffectColorBalance(***CyanRed As Long*, *MagentaGreen As Long*, *YellowBlue As Long*, **[**ApplyToShadows As Boolean = True**],** **[**ApplyToMidtones As Boolean = True**],** **[**ApplyToHighlights As Boolean = True**],** **[**PreserveLuminance As Boolean = True**])**

Description

Member of ShapeRange

The **ApplyEffectColorBalance** method applies a color-balance effect to the shapes in a shape range.

Parameter	Description
CyanRed	Specifies the cyan/red level
MagentaGreen	Specifies the magenta/green level
YellowBlue	Specifies the yellow/blue level
ApplyToShadows	Specifies whether to apply the effect to shadows. This parameter is optional, and its default value is **True**.
ApplyToMidtones	Specifies whether to apply the effect to midtones. This parameter is optional, and its default value is **True**.
ApplyToHighlights	Specifies whether to apply the effect to highlights. This parameter is optional, and its default value is **True**.
PreserveLuminance	Specifies whether to preserve luminance. This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ApplyEffectGamma

Sub **ApplyEffectGamma**(*Gamma As Double*)

Description

Member of ShapeRange

The ApplyEffectGamma method applies a gamma color-correction effect to the shapes in a shape range.

Parameter	Description
Gamma	Specifies the gamma level

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ApplyEffectHSL

Sub **ApplyEffectHSL(***Hue As Variant***,** *Saturation As Variant***,** *Lightness As Variant***)**

Description

Member of ShapeRange

The **ApplyEffectHSL** method applies the Hue-Saturation-Lightness color effect to the shapes in a shape range.

Parameter	Description
Hue	Specifies the hue level
Saturation	Specifies the saturation level
Lightness	Specifies the lightness level

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ApplyEffectInvert

Sub **ApplyEffectInvert()**

Description

Member of ShapeRange

The **ApplyEffectInvert** method inverts the colors of the shapes in a shape range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ApplyEffectPosterize

Sub **ApplyEffectPosterize(***Level As Long***)**

Description

Member of ShapeRange

The **ApplyEffectPosterize** method applies the Posterize color effect to the shapes in a shape range.

Parameter	Description
Level	Specifies the effect level

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ApplyFill

Sub **ApplyFill(**Fill As Fill**)**

Description

Member of ShapeRange

The **ApplyFill** method applies the specified fill to the shapes in a shape range.

Parameter	Description
Fill	Specifies the fill

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ApplyFountainFill

Sub **ApplyFountainFill([**StartColor As Color**], [**EndColor As Color**], [**Type As cdrFountainFillType = cdrLinearFountainFill**], [***Angle As Double***], [***Steps As Long***], [***EdgePad As Long***], [**MidPoint As Long = 50**], [**BlendType As cdrFountainFillBlendType = cdrDirectFountainFillBlend**], [***CenterOffsetX As Double***], [***CenterOffsetY As Double***])**

Description

Member of ShapeRange

The **ApplyFountainFill** method applies a specified fountain fill to the shapes in a shape range.

Parameter	Description
StartColor	Specifes the color to appear at the beginning of the fountain fill. This parameter is optional, and its default value is **Nothing**.
EndColor	Specifies the color to appear at the end of the fountain fill. This parameter is optional, and its default value is **Nothing**.
Type	Specifies the type of fountain fill, and returns cdrFountainFillType. This parameter is optional, and its default value is cdrLinearFountainFill (**1**).
Angle	Specifies the degree of the angle in a linear, conical, or square fountain fill. Changing the angle of gradation affects the slant of the fountain fill. Positive values rotate the fill counterclockwise; negative values rotate it clockwise. This parameter is optional, and its default value is **0**.
Steps	Specifies the number of bands (steps) used to display the fountain fill. This parameter is optional, and its default value is **0**.
EdgePad	Specifies the length of solid colors at the beginning and end of the fountain fill before they start blending with the next color in the fountain fill. You can change the edge pad of linear, radial, and square fountain fills. Higher values let the colors remain solid longer before blending, causing the colors to spread more quickly; lower values result in a smooth transformation between the two colors. This parameter is optional, and its default value is **0**.
MidPoint	Specifies an imaginary line between two colors in the fountain fill, letting you set the point at which two colors in the fill converge. This parameter is optional, and its default value is **50**.
BlendType	Specifies the type of blend for the fountain fill. This parameter is optional, and its default value is cdrDirectFountainFillBlend (**0**).
CenterOffsetX	Specifies the horizontal offset of the fountain fill. This parameter is optional, and its default value is **0**.
CenterOffsetY	Specifies the vertical offset of the fountain fill. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example applies a conical fountain fill to each text shape on the page.

```
Sub Test()
 Dim sr As ShapeRange
 Set sr = ActivePage.FindShapes(Type:=cdrTextShape)
 sr.ApplyFountainFill CreateRGBColor(255, 0, 0), CreateRGBColor(255, 255, 0), cdrConicalFountainFill, 45
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ApplyHatchFill

Sub **ApplyHatchFill(***LibraryName As String***,** *HatchNameOrIndex As Variant***, [**BackColor As Color**], [**TransformWithShape As Boolean = False**], [**ScaleLinesWithShape As Boolean = False**], [**UseWorldCoordinates As Boolean = False**], [***FillScale As Double***], [***LineScale As Double***], [***FillAngle As Double***], [***FillSkew As Double***])**

Description

Member of ShapeRange

The **ApplyHatchFill** method applies a preset (library) hatch fill to the shapes in a shape range.

Parameter	Description
LibraryName	Specifies the library name for the hatch-fill pattern
HatchNameOrIndex	Specifies the name or index number of the hatch-fill pattern
BackColor	Specifies the background color for the hatch fill. This parameter is optional, and its default value is **Nothing**.
TransformWithShape	Specifies whether to transform the hatch fill with the shape to which the hatch fill is applied. This parameter is optional, and its default value is **False**.
ScaleLinesWithShape	Specifies whether to scale the hatch-fill lines with the shape to which the hatch fill is applied. This parameter is optional, and its default value is **False**.
UseWorldCoordinates	Specifies whether local or world coordinates are used to align the hatch fills that are applied to different objects. This parameter is optional, and its default value is **False**.
FillScale	Specifies the average scale factor for the hatch fill. This parameter is optional, and its default value is **0**.
LineScale	Specifies the average line-thickness scale factor for the hatch fill. This parameter is optional, and its default value is **0**.
FillAngle	Specifies the rotation angle for the hatch fill. This parameter is optional, and its default value is **0**.
FillSkew	Specifies the skew angle for the hatch fill. This parameter is optional, and its default value is **0**.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ApplyNoFill

Sub **ApplyNoFill()**

Description

Member of ShapeRange

The **ApplyNoFill** method removes the fill from each shape in a shape range.

VBA example

The following VBA example removes all the fountain fills on the page.

```
Sub Test()
 Dim sr As New ShapeRange
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Fill.Type = cdrFountainFill Then sr.Add s
 Next s
 sr.ApplyNoFill
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ApplyOutline

Sub **ApplyOutline(**Outline As Outline**)**

Description

Member of ShapeRange

The **ApplyOutline** method applies the specified outline to shapes in a shape range.

Parameter	Description
Outline	Specifies the outline

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ApplyPatternFill

Sub **ApplyPatternFill(**Type As cdrPatternFillType**, [***FileName As String***], [**PatternCanvasIndex As Long = 1**], [**FrontColor As Color**], [**EndColor As Color**], [**TransformWithShape As Boolean = False**])**

Description

Member of ShapeRange

The **ApplyPatternFill** method applies the specified pattern fill to all the shapes in a shape range.

Parameter	Description
Type	Specifies the type of pattern fill, and returns cdrPatternFillType
FileName	Specifies the full path name of the graphic to import for use as a pattern fill. The value must contain both the computer's path and the name of the graphic file. This parameter is optional.
PatternCanvasIndex	Specifies the index number of the pattern canvas. This parameter is optional, and its default value is **1**.
FrontColor	Specifies the foreground color in a pattern fill. This parameter is optional, and its default value is **Nothing**.
EndColor	Specifies the background color in a pattern fill. This parameter is optional, and its default value is **Nothing**.
TransformWithShape	Specifies whether the pattern fill changes to fit its shape when the shape is altered. If the value is **True**, the pattern fill changes according to changes in its shape. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example applies a two-color pattern fill and an outline to each text shape on the page.

```
Sub Test()
 Dim sr As ShapeRange
 Set sr = ActivePage.FindShapes(Type:=cdrTextShape)
 sr.ApplyPatternFill cdrTwoColorPattern, , 4, CreateRGBColor(255, 0, 0)
 sr.SetOutlineProperties 0.05
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ApplyPostscriptFill

Sub **ApplyPostscriptFill(***IndexOrName As Variant***)**

Description

Member of ShapeRange

The **ApplyPostscriptFill** method applies a specified PostScript fill to all the shapes in a shape range.

Parameter	Description
IndexOrName	Specifies the PostScript fill by its index number or name: • **Index** — Specifies the preset placeholder that uniquely identifies each fill • **Name** — Specifies the string that uniquely identifies each fill

VBA example

The following VBA example applies a PostScript fill to each text shape on the page.

```
Sub Test()
 Dim sr As ShapeRange
 Set sr = ActivePage.FindShapes(Type:=cdrTextShape)
 sr.ApplyPostscriptFill "Bricks"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ApplyTextureFill

Sub **ApplyTextureFill(***TextureName As String***, [***LibraryName As String***])**

Description

Member of ShapeRange

The **ApplyTextureFill** method applies a specified texture fill to all the shapes in a shape range.

Parameter	Description
TextureName	Specifies the texture-fill pattern
LibraryName	Specifies the texture-fill library for the texture-fill pattern. This parameter is optional.

VBA example

The following VBA example applies a texture fill to each shape that has an Overprint fill.

```
Sub Test()
 Dim sr As New ShapeRange
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.OverprintFill Then sr.Add s
 Next s
 sr.ApplyTextureFill "Cement", "Samples 8"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ApplyUniformFill

Sub **ApplyUniformFill(**Color As Color**)**

Description

Member of ShapeRange

The **ApplyUniformFill** method applies a uniform-fill color to all the shapes in a shape range.

Parameter	Description
Color	Specifies the fill color by referencing an existing color component in a palette or a **Create...Color** method (for example, CreateCMYKColor or CreateRGBColor)

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.BottomY

Property **BottomY** As Double

Description

Member of ShapeRange

The **BottomY** property returns the y-coordinate of the bottom edge of the bounding box for the shapes in a range.

The **BottomY** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.BoundingBox

Property **BoundingBox** As Rect

Description

Member of ShapeRange

The **BoundingBox** property returns the bounding box around the shapes in a range.

The **BoundingBox** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.BreakApart

Sub **BreakApart()**

Description

Member of ShapeRange

The **BreakApart** method breaks apart all the shapes in a shape range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.BreakApartEx

Function **BreakApartEx()** As ShapeRange

Description

Member of ShapeRange

The **BreakApartEx** method breaks apart all the shapes in a shape range and returns those shapes as a new shape range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.CenterX

Property **CenterX** As Double

Description

Member of ShapeRange

The **CenterX** property returns or specifies the horizontal position of the center of the shapes in a range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.CenterY

Property **CenterY** As Double

Description

Member of ShapeRange

The **CenterY** property returns or specifies the vertical position of the center of the shapes in a range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Chamfer

Sub **Chamfer(***DistanceA As Double***,** *DistanceB As Double***, [***CombineSmoothSegments As Boolean = True***])**

Description

Member of ShapeRange

The **Chamfer** method creates a chamfer on each cusp corner of the shapes in a shape range.

Parameter	Description
DistanceA	
DistanceB	
CombineSmoothSegments	Specifies whether to combine smooth segments. This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ClearEffect

Sub **ClearEffect(**Type As cdrEffectType**)**

Description

Member of ShapeRange

The **ClearEffect** method removes effects from the shapes in a shape range.

Parameter	Description
Type	Specifies the type of effect to remove

VBA example

The following VBA example removes the contour effect from all rectangles.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(2, 2, 4, 4)
 s.Fill.ApplyUniformFill CreateRGBColor(255, 0, 0)
 s.CreateContour cdrContourOutside
 Set s = ActiveLayer.CreateRectangle2(1, 4, 5, 5)
 s.Fill.ApplyUniformFill CreateRGBColor(0, 255, 0)
 s.CreateContour cdrContourInside
 ActivePage.FindShapes(, cdrRectangleShape).CreateSelection
 ActiveSelection.ClearEffect cdrContour
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ClearTransformations

Sub **ClearTransformations()**

Description

Member of ShapeRange

The **ClearTransformations** method clears all rotations, stretch transformations, and skew transformations applied to the shapes in a shape range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Clone

Function **Clone([***OffsetX As Double***], [***OffsetY As Double***])** As ShapeRange

Description

Member of ShapeRange

The **Clone** method clones each shape in a shape range and returns a new shape range containing all of the clones.

Parameter	Description
OffsetX	Specifies the horizontal distance to offset the cloned shape range. This parameter is optional, and its default value is **0**.
OffsetY	Specifies the vertical distance to offset the cloned shape range. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example creates two rectangles and clones them.

```
Sub Test()
 Dim sr As New ShapeRange
 Dim srClone As ShapeRange
 sr.Add ActiveLayer.CreateRectangle(0, 0, 1, 1)
 sr.Add ActiveLayer.CreateRectangle(2, 0, 3, 1)
 sr.ApplyUniformFill CreateRGBColor(255, 0, 0)
 Set srClone = sr.Clone(0, 2)
 sr.ApplyUniformFill CreateRGBColor(0, 0, 255)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Combine

Function **Combine()** As Shape

Description

Member of ShapeRange

The **Combine** method combines all the shapes in a shape range into a single curve.

VBA example

The following VBA example creates a single shape by combining a set of circles.

```
Sub Test()
 Const Num As Long = 15
 Dim sr As New ShapeRange
 Dim s As Shape, n As Long
 Set s = ActiveLayer.CreateEllipse2(4, 4, 1)
 s.SetRotationCenter 4, 5
 For n = 1 To Num - 1
  sr.Add s.Duplicate
  s.Rotate 360 / Num
 Next n
 sr.Add s
 Set s = sr.Combine
 s.Fill.UniformColor.RGBAssign 255, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ConvertOutlineToObject

Function **ConvertOutlineToObject()** As ShapeRange

Description

Member of ShapeRange

The **ConvertOutlineToObject** method converts the outline of each shape in a shape range to a separate fillable object.

VBA example

The following VBA example converts the outline of each curve to a closed curve shape.

```
Sub Test()
 Dim sr As ShapeRange
 Dim n As Long
 Set sr = ActivePage.FindShapes(Type:=cdrCurveShape)
 For n = sr.Count To 1 Step -1
  If sr(n).Outline.Type = cdrNoOutline Then sr.Remove n
 Next n
 sr.ConvertOutlineToObject
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ConvertToBitmap

Function **ConvertToBitmap([**BitDepth As Long = 24**], [**Grayscale As Boolean = False**], [**Dithered As Boolean = True**], [**TransparentBG As Boolean = True**], [**Resolution As Long = 72**], [**AntiAliasing As cdrAntiAliasingType = cdrNormalAntiAliasing**], [**UseColorProfile As Boolean = True**])** As Shape

Description

Member of ShapeRange

The **ConvertToBitmap** method converts each shape in a shape range to a bitmap.

- This method is obsolete and provided for backward compatibility only. It is recommended that you use the ConvertToBitmapEx method instead.

Parameter	Description
BitDepth	Specifies the bit depth. This parameter is optional, and its default value is **24**.
Grayscale	Converts to grayscale if set to **True** (**-1**). This parameter is optional, and its default value is **False**.
Dithered	Enables dithering if set to **True** (**-1**). This parameter is optional, and its default value is **True**.
TransparentBG	Specifies the background to transparent if set to **True** (**-1**). This parameter is optional, and its default value is **True**.
Resolution	Specifies the resolution. This parameter is optional, and its default value is **72**.
AntiAliasing	Specifies the type of anti-aliasing, and returns cdrAntiAliasingType. This parameter is optional, and its default value is cdrNormalAntiAliasing (**1**).
UseColorProfile	Uses the color profile if set to **True** (**-1**). This parameter is optional, and its default value is **True**.

VBA example

The following VBA example converts each selected shape to a grayscale bitmap with a transparent background.

```
Sub Test()
 ActiveSelectionRange.ConvertToBitmapEx cdrGrayscaleImage, False, True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ConvertToBitmapEx

Function **ConvertToBitmapEx([**Mode As cdrImageType = cdrRGBColorImage**], [**Dithered As Boolean = False**], [**Transparent As Boolean = False**], [**Resolution As Long = 72**], [**AntiAliasing As cdrAntiAliasingType = cdrNormalAntiAliasing**], [**UseColorProfile As Boolean = True**])** As Shape

Description

Member of ShapeRange

The **ConvertToBitmapEx** method converts each shape in a shape range to a bitmap.

Parameter	Description
Mode	Specifies the type of image, and returns cdrImageType. This parameter is optional, and its default value is cdrRGBColorImage (4).
Dithered	Specifies whether the image is dithered when exported. This parameter is optional, and its default value is **False**.
Transparent	Specifies the transparency of the background. This parameter is optional, and its default value is **False**.
Resolution	Specifies the resolution. This parameter is optional, and its default value is **72**.
AntiAliasing	Specifies the type of anti-aliasing, and returns cdrAntiAliasingType. This parameter is optional, and its default value is cdrNormalAntiAliasing (**1**).
UseColorProfile	Uses the color profile if set to **True** (**-1**). This parameter is optional, and its default value is **True**.

VBA example

The following VBA example converts each selected shape to a grayscale bitmap with a transparent background.

```
Sub Test()
 ActiveSelectionRange.ConvertToBitmapEx cdrGrayscaleImage, False, True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ConvertToCurves

Sub **ConvertToCurves()**

Description

Member of ShapeRange

The **ConvertToCurves** method converts each shape in a shape range to a curve.

VBA example

The following VBA example converts all artistic-text objects to curves.

```
Sub Test()
 Dim sr As ShapeRange
 Set sr = ActivePage.FindShapes(Type:=cdrTextShape)
 sr.ConvertToCurves
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ConvertToSymbol

Function **ConvertToSymbol(***Name As String***)** As Shape

Description

Member of ShapeRange

The **ConvertToSymbol** method converts a shape range to a symbol.

Parameter	Description
Name	Specifies the name

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Copy

Sub **Copy()**

Description

Member of ShapeRange

The **Copy** method copies all the shapes in a shape range to the Clipboard.

VBA example

The following VBA example copies, page by page, all the shapes from the current document into a new document.

```
Sub Test()
 Dim p1 As Page, p2 As Page, bAddPage As Boolean
 Dim doc1 As Document, doc2 As Document
 Set doc1 = ActiveDocument
 Set doc2 = CreateDocument()
 bAddPage = False
 Set p2 = doc2.Pages(1)
 For Each p1 In doc1.Pages
  p1.Activate
  p1.Shapes.All.Copy
  If bAddPage Then Set p2 = doc2.AddPages(1)
  p2.ActiveLayer.Paste
  bAddPage = True
 Next p1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.CopyPropertiesFrom

Function **CopyPropertiesFrom(**Source As Shape**,** Properties As cdrCopyProperties**)** As Boolean

Description

Member of ShapeRange

The **CopyPropertiesFrom** method specifies whether to copy fill, outline, or text properties — or some combination of those — from a shape range.

Parameter	Description
Source	Specifies the shape range
Properties	Specifies the properties to copy

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.CopyToLayer

Function **CopyToLayer(**Layer As Layer**)** As ShapeRange

Description

Member of ShapeRange

The **CopyToLayer** method copies all the shapes in a shape range to a specified layer.

Parameter	Description
Layer	Specifies the layer

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Count

Property **Count** As Long

Description

Member of ShapeRange

The **Count** property returns the number of shapes in a shape range.

The **Count** property returns a read-only value.

VBA example

The following VBA example displays the number of ellipses on the active page.

```
Sub Test()
 Dim sr As ShapeRange
 Set sr = ActivePage.FindShapes(Type:=cdrEllipseShape)
 MsgBox "There are " & sr.Count & " ellipse(s) on the current page"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.CountAnyOfType

Function **CountAnyOfType(***ParamArray TypeList() As Variant***)** As Long

Description

Member of ShapeRange

The **CountAnyOfType** method returns the number of shapes of specific types in a shape range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.CreateBoundary

Function **CreateBoundary(***x As Double***,** *y As Double***, [**PlaceOnTop As Boolean = False**], [**DeleteSource As Boolean = False**])** As Shape

Description

Member of ShapeRange

The **CreateBoundary** method creates a closed Bézier curve based on the specified shapes and a user-specified bias point. If the bias point lies outside of the extent of the specified shapes, the boundary object is the common outline of the specified shapes. If the bias point lies within one or more of the specified shapes, the boundary object is the internal outline of the union of the specified shapes at the bias point.

If the operation fails, **Nothing** is returned.

Parameter	Description
x	Specifies the x-coordinate of the bias point
y	Specifies the y-coordinate of the bias point
PlaceOnTop	Specifies whether to place the boundaryobject in front of the shapes. A value of **True** places the boundary object in front of the shape range. This parameter is optional, and its default value is **False**.
DeleteSource	Specifies whether to delete the object upon which the boundary is based. A value of **True** deletes the original object. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example creates a shape range consisting of a circle and a rectangle, and it retrieves a user-specified point. If the point is valid, a boundary is created relative to the shapes in the shape range and is filled with red.

```
Sub Test()
Dim sr As New ShapeRange, shpBoundary As Shape
Dim x As Double, y As Double
sr.Add ActiveLayer.CreateEllipse(3, 5, 6, 2)
sr.Add ActiveLayer.CreateRectangle(5, 6, 7, 4)
If ActiveDocument.GetUserClick(x, y, 0, 10, False, cdrCursorEyeDrop) = 0 Then
Set shpBoundary = sr.CreateBoundary(x, y, True)
shpBoundary.Fill.UniformColor.RGBAssign 255, 0, 0
End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.CreateDocumentFrom

Function **CreateDocumentFrom(**TemporaryDocument As Boolean = False**)** As Document

Description

Member of ShapeRange

The **CreateDocumentFrom** method creates a copy of the document that contains a shape range.

Parameter	Description
TemporaryDocument	Specifies whether the document is temporary. The default for this Boolean value is **False**.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.CreateSelection

Sub **CreateSelection()**

Description

Member of ShapeRange

The **CreateSelection** method creates a selection from the shapes in a shape range.

- Unlike the AddToSelection method, the **CreateSelection** method destroys any previous selection.

VBA example

The following VBA example selects all the ellipses on the current page.

```
Sub Test()
 ActivePage.FindShapes(Type:=cdrEllipseShape).CreateSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.CustomCommand

Function **CustomCommand(***ComponentID As String***,** *CommandID As String***,** *Parameter() As Variant***)** As Variant

Description

Member of ShapeRange

The **CustomCommand** method executes a custom command on a given shape range.

Parameter	Description
ComponentID	Specifies the ID of the component
CommandID	Specifies the ID of the command
Parameter	Specifies any parameters

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Cut

Sub **Cut()**

Description

Member of ShapeRange

The **Cut** method copies all the shapes in a shape range to the Clipboard and deletes the copied shapes from the document.

VBA example

The following VBA example creates a rectangle and an ellipse on the active page. It then adds a new page, cuts the shapes from the first page, and pastes them in the new page.

```
Sub Test()
 Dim p1 As Page, p2 As Page
 Dim s As Shape
 Dim doc As Document
 Set doc = ActiveDocument
 Set s = doc.ActiveLayer.CreateRectangle(2, 2, 4, 4)
 Set s = doc.ActiveLayer.CreateEllipse(1, 2, 3, 4)
 For Each p1 In doc.Pages
  p1.Activate
  p1.Shapes.All.Cut
  Set p2 = doc.AddPages(1)
  p2.ActiveLayer.Paste
 Next p1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Delete

Sub **Delete()**

Description

Member of ShapeRange

The **Delete** method removes all shapes from a shape range (thereby emptying the range) and deletes them from the document.

VBA example

The following VBA example deletes all of the shapes from the active page.

```
Sub Test()
 ActivePage.Shapes.All.Delete
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.DeleteItem

Sub **DeleteItem(***Index As Long***)**

Description

Member of ShapeRange

The **DeleteItem** method removes a specified shape from a shape range and deletes it from the document.

Parameter	Description
Index	Specifies the shape by its index number

VBA example

The following VBA example deletes the first shape from the shape range.

```
Sub Test()
 Dim s As Shape
 Dim sr As ShapeRange
 Set s = ActiveLayer.CreateRectangle(2, 2, 4, 4)
 s.Fill.ApplyUniformFill CreateRGBColor(255, 0, 0)
 Set s = ActiveLayer.CreateRectangle2(1, 4, 5, 5)
 s.Fill.ApplyUniformFill CreateRGBColor(0, 255, 0)
 Set s = ActiveLayer.CreatePolygon(1, 2, 3, 4, 6)
 Set sr = ActivePage.FindShapes(, cdrRectangleShape)
 sr.DeleteItem 1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Distribute

Sub **Distribute(**Type As cdrDistributeType**, [**PageExtent As Boolean = False**])**

Description

Member of ShapeRange

The **Distribute** method distributes the shapes in a shape range.

Parameter	Description
Type	Specifies the type of distribution
PageExtent	Specifies whether to distribute the shapes to the extent of the page. This parameter is optional, and its default value is **False**.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Duplicate

Function **Duplicate([***OffsetX As Double***], [***OffsetY As Double***])** As ShapeRange

Description

Member of ShapeRange

The **Duplicate** method duplicates each shape in a shape range, returning another shape range that contains all the duplicates.

Parameter	Description
OffsetX	Specifies the horizontal distance to offset the duplicated shape range. This parameter is optional, and its default value is **0**.
OffsetY	Specifies the vertical distance to offset the duplicated shape range. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example duplicates each curve shape, removes any fills in the range, assigns a thick outline to each duplicate, and groups all the duplicated curves.

```
Sub Test()
 Dim sr As ShapeRange
 Set sr = ActiveLayer.FindShapes(, cdrCurveShape)
 Set sr = sr.Duplicate
 sr.ApplyNoFill
 sr.SetOutlineProperties 0.1
 sr.Group
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.EqualDivide

Function **EqualDivide([**Divisions As Long = 2**], [**Gap As Double = -1**], [**Group As Boolean = False**], [**Combine As Boolean = True**], [**DeleteSource As Boolean = True**])** As ShapeRange

Description

Member of ShapeRange

The **EqualDivide** method divides a shape range into parts of equal length, separated by gaps of equal size. The divisions can be combined into a single compound-path object, or they can be left as individual shapes that can be grouped.

Parameter	Description
Divisions	Specifies the desired number of equal divisions. Values range from **2** to **360**. This parameter is optional, and its default value is **2**.
Gap	Specifies, in document units, the desired gap between the divisions. A value of **0** is permitted. This parameter is optional, and its default value is **-1**.
Group	Specifies whether to group the divisions. This parameter is optional, and its default value is **False**.
Combine	Specifies whether to combine the divisions into a single compound path. A value of **True** combines the divisions. This parameter is optional, and its default value is **True**.
DeleteSource	Specifies whether to delete the original shape range. A value of **True** deletes the original shape range. This parameter is optional, and its default value is **True**.

This method returns a shape range, but results may vary based on how many objects are selected prior to the operation and whether they are combined:

- If a single shape is specified and the **Combine** parameter is set to **True**, the resultant shape range contains a single shape: the compound path created by combining the equally divided segments.
- If a single shape is specified and the **Combine** pararmeter is set to **False**, the resultant shape range contains several shapes: one shape reference for each equally divided segment.
- If multiple objects (that is, a shape range) are selected and the **Combine** parameter is set to **True**, the resultant shape range contains several shapes: one shape (the compound path) for each specified shape. The specified shapes are not combined into a single compound path.
- If multiple objects (that is, a shape range) are selected and the **Combine** parameter is set to **False**, the resultant shape range contains numerous shapes: one shape reference for each equally divided segment of each specified shape.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Exists

Function **Exists(**Shape As Shape**)** As Boolean

Description

Member of ShapeRange

The **Exists** method determines whether a given shape is present in a shape range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ExistsAnyOfType

Function **ExistsAnyOfType(***ParamArray TypeList() As Variant***)** As Boolean

Description

Member of ShapeRange

The **ExistsAnyOfType** method determines whether a shape range contains any shapes of specific types.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Fillet

Sub **Fillet(Radius As Double, [**CombineSmoothSegments As Boolean = True**])**

Description

Member of ShapeRange

The **Fillet** method creates a fillet on each cusp corner of the shapes in a shape range.

Parameter	Description
Radius	Specifies the radius of the fillet
CombineSmoothSegments	Specifies whether to combine smooth segments. This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.FindAnyOfType

Function **FindAnyOfType(***ParamArray TypeList() As Variant***)** As ShapeRange

Description

Member of ShapeRange

The **FindAnyOfType** method returns a list of shapes of specific types that are contained in a shape range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.FirstShape

Property **FirstShape** As Shape

Description

Member of ShapeRange

The **FirstShape** property returns the first shape in a shape range.

The **FirstShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Flip

Sub **Flip(**Axes As cdrFlipAxes**)**

Description

Member of ShapeRange

The **Flip** method flips all the shapes in a shape range. Shapes can be flipped horizontally or vertically, or in both directions.

Parameter	Description
Axes	Specifies the manner of the flip, and returns cdrFlipAxes.

VBA example

The following VBA example flips, upside-down, all the shapes on the active page.

```
Sub Test()
 ActivePage.Shapes.All.Flip cdrFlipHorizontal + cdrFlipVertical
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.GetBoundingBox

Sub **GetBoundingBox(***x As Double***,** *y As Double***,** *Width As Double***,** *Height As Double***, [**UseOutline As Boolean = False**])**

Description

Member of ShapeRange

The **GetBoundingBox** method returns the position of the lower-left corner of all the objects in a shape range, treating the range as a single shape. It also returns the total size of all the shapes in the range.

- See also the ShapeRange.PositionX, ShapeRange.PositionY, ShapeRange.SizeWidth, and ShapeRange.SizeHeight properties, as well as the ShapeRange.GetPosition, ShapeRange.SetPosition, ShapeRange.GetSize, ShapeRange.SetSize, ShapeRange.SetSizeEx, and ShapeRange.Move methods.

Parameter	Description
x	Specifies the x-coordinate of the lower-left corner
y	Specifies the y-coordinate of the lower-left corner
Width	Specifies the width of all objects
Height	Specifies the height of all objects
UseOutline	Specifies whether outlines are considered when calculating the size of the bounding box. If this value is set to **True**, shape outlines are taken into account when calculating the dimensions of the bounding box; otherwise, the shapes are treated as though they have no outline. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example creates a rectangle that surrounds an ellipse.

```
Sub Test()
 Dim s As Shape
 Dim sr As ShapeRange
 Dim x As Double, y As Double, w As Double, h As Double
 Set s = ActiveLayer.CreateEllipse(1, 2, 3, 4)
 ActiveDocument.ReferencePoint = cdrCenter
 Set sr = ActivePage.Shapes.All
 sr.GetBoundingBox x, y, w, h
 ActiveLayer.CreateRectangle2 x, y, w, y
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.GetLinkedShapes

Function **GetLinkedShapes(***LinkType As cdrShapeLinkType***)** As ShapeRange

Description

Member of ShapeRange

The **GetLinkedShapes** method returns all the shapes that are linked in some way to the shapes in a shape range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.GetOverprintFillState

Function **GetOverprintFillState()** As cdrOverprintState

Description

Member of ShapeRange

The **GetOverprintFillState** method returns the overprint fill-state flags for a shape range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.GetOverprintOutlineState

Function **GetOverprintOutlineState()** As cdrOverprintState

Description

Member of ShapeRange

The **GetOverprintFillState** method returns the overprint outline-state flags for a shape range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.GetPosition

Sub **GetPosition(***PositionX As Double***,** *PositionY As Double***)**

Description

Member of ShapeRange

The **GetPosition** method retrieves the horizontal and vertical positions of all the shapes in a shape range, treating the range as a single object.

- The position of the shape range is set relative to the reference point specified by the Document.ReferencePoint property.

Parameter	Description
PositionX	Specifies, in document units, the horizontal position of the shape range
PositionY	Specifies, in document units, the vertical position of the shape range

VBA example

The following VBA example creates an ellipse with the dimensions of the active selection range.

```
Sub Test()
 Dim x As Double, y As Double
 ActiveDocument.ReferencePoint = cdrCenter
 ActiveSelectionRange.GetPosition x, y
 ActiveLayer.CreateEllipse2 x, y, 0.05
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.GetPositionEx

Sub **GetPositionEx(**ReferencePoint As cdrReferencePoint**,** *x As Double*, *y As Double***)**

Description

Member of ShapeRange

The **GetPositionEx** method returns the coordinates of a specified point.

Parameter	Description
ReferencePoint	Specifies the reference point
x	Specifies the x-coordinate
y	Specifies the y-coordinate

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.GetSize

Sub **GetSize(***Width As Double***,** *Height As Double***)**

Description

Member of ShapeRange

The **GetSize** method retrieves the size of the shapes in a shape range, treating the range as a single object.

- See also the ShapeRange.SizeWidth and ShapeRange.SizeHeight properties, as well as the ShapeRange.GetBoundingBox and ShapeRange.SetBoundingBox methods.

Parameter	Description
Width	Specifies the width, in document units, of the shape range
Height	Specifies the height, in document units, of the shape range

VBA example

The following VBA example stretches all the shapes on the active layer so that the vertical size of each shape is **1**.

```
Sub Test()
 Dim x As Double, y As Double
 Dim sr As ShapeRange
 Set sr = ActiveLayer.Shapes.All
 If sr.Count > 0 Then
  ActiveDocument.ReferencePoint = cdrCenter
  sr.GetSize x, y
  sr.SetSize x, 1
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Group

Function **Group()** As Shape

Description

Member of ShapeRange

The **Group** method groups all the shapes in a shape range and returns a Shape object as the reference to the group.

VBA example

The following VBA example creates a jigsaw puzzle.

```
Sub Test()
 Dim s As Shape, sp As SubPath, sbmp As Shape
 Dim sr As New ShapeRange, n As Long
 Dim x As Double, y As Double, sx As Double, sy As Double
 Set s = ActiveLayer.CreateCurve
 Set sp = s.Curve.CreateSubPath(1.351, 8.545)
 sp.AppendCurveSegment False, 1.351, 8.926, 0.127, 89.901, 0.127, -64.56
 sp.AppendCurveSegment False, 1.156, 8.952, 0.066, 115.44, 0.066, -48.906
 sp.AppendCurveSegment False, 1.156, 9.15, 0.065, 131.09, 0.065, -133.149
 sp.AppendCurveSegment False, 1.351, 9.163, 0.065, 46.846, 0.065, -116.315
 sp.AppendCurveSegment False, 1.351, 9.545, 0.127, 63.683, 0.127, -89.902
 sp.AppendCurveSegment False, 0.976, 9.545, 0.125, 179.951, 0.125, 25.612
 sp.AppendCurveSegment False, 0.96, 9.342, 0.063, -154.391, 0.063, 40.943
 sp.AppendCurveSegment False, 0.767, 9.339, 0.067, -139.06, 0.067, -41.987
 sp.AppendCurveSegment False, 0.752, 9.547, 0.063, 138.014, 0.065, -33.906
 sp.AppendCurveSegment False, 0.351, 9.545, 0.134, 146.087, 0.134, 0.045
 sp.AppendCurveSegment False, 0.351, 9.163, 0.127, -90#, 0.127, 63.681
 sp.AppendCurveSegment False, 0.156, 9.15, 0.065, -116.317, 0.065, 46.846
 sp.AppendCurveSegment False, 0.156, 8.952, 0.065, -133.152, 0.065, 131.093
 sp.AppendCurveSegment False, 0.351, 8.926, 0.066, -48.906, 0.066, 115.439
 sp.AppendCurveSegment False, 0.351, 8.545, 0.127, -64.561, 0.127, 90#
 sp.AppendCurveSegment False, 0.752, 8.547, 0.134, 0.002, 0.134, 146.087
 sp.AppendCurveSegment False, 0.767, 8.339, 0.065, -33.908, 0.063, 138.012
 sp.AppendCurveSegment False, 0.96, 8.342, 0.067, -41.987, 0.067, -139.058
 sp.AppendCurveSegment False, 0.976, 8.545, 0.063, 40.943, 0.063, -154.388
 sp.AppendCurveSegment False, 1.351, 8.545, 0.125, 25.613, 0.125, 179.998
 sp.Closed = True
 For n = 1 To 7
  sr.Add s.Duplicate
  s.Move 1, 0
 Next n
 sr.Add s
 sr.AddRange sr.Duplicate(0, -1)
 sr.AddRange sr.Duplicate(0, -2)
 Set s = sr.Group
 s.GetBoundingBox x, y, sx, sy
 Set sbmp = ActiveLayer.CreateRectangle2(x, y, sx, sy)
 sbmp.Fill.ApplyTextureFill "Gouache wash", "Samples"
 Set sbmp = sbmp.ConvertToBitmapEx(cdrRGBColorImage, , , 120)
 sbmp.AddToPowerClip s
 s.Ungroup
 For Each s In sr
  s.Move (Rnd() - 0.5) * 0.25, (Rnd() - 0.5) * 0.25
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.IndexOf

Function **IndexOf(**Shape As Shape**)** As Long

Description

Member of ShapeRange

The **IndexOf** method returns the index number of a specified shape in a shape range. If the shape is not in the range, **0** is returned.

Parameter	Description
Shape	Specifies the shape

VBA example

The following VBA example determines whether the selected shape is a curve residing on the active layer of the document.

```
Sub Test()
 Dim sr As ShapeRange
 Set sr = ActiveLayer.FindShapes(, cdrCurveShape)
 If sr.IndexOf(ActiveShape) = 0 Then
  MsgBox "The selected shape is not a curve residing on the current layer"
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Item

Property **Item(***IndexOrName As Variant***)** As Shape

Description

Member of ShapeRange

The **Item** property returns a specified shape in a shape range. It is the default property of the ShapeRange class.

The **Item** property returns a read-only value.

Parameter	Description
IndexOrName	Specifies the index number or name of the shape in the shape range: • **Index** — Specifies the preset placeholder that uniquely identifies each shape in the shape range • **Name** — Specifies the string that uniquely identifies each shape in the shape range

VBA example 1

The following VBA example finds the shape named **MyRectangle** from the selection and fills it with a uniform red fill.

```
Sub Test()
 ActiveSelectionRange("MyRectangle").Fill.UniformColor.RGBAssign 255, 0, 0
End Sub
```

VBA example 2

The following VBA example fills every ellipse on the active page with a uniform blue fill:

```
Sub Test()
 Dim i As Long
 Dim sr As ShapeRange
 Set sr = ActivePage.FindShapes(Type:=cdrEllipseShape)
 For i = 1 To sr.Count
  sr(i).Fill.UniformColor.RGBAssign 0, 0, 255
 Next i
End Sub
```

VBA example 3

The following VBA example performs the same procedure as the previous example. However, instead of using a **For Next** command, it uses the **For Each** command in Visual Basic to iterate through all the shapes in the collection.

```
Sub Test()
 Dim s As Shape
 Dim sr As ShapeRange
 Set sr = ActivePage.FindShapes(Type:=cdrEllipseShape)
 For Each s In sr
  s.Fill.UniformColor.RGBAssign 0, 0, 255
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.LastShape

Property **LastShape** As Shape

Description

Member of ShapeRange

The **LastShape** property returns the last shape in a shape range.

The **LastShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.LeftX

Property **LeftX** As Double

Description

Member of ShapeRange

The **LeftX** property returns the x-coordinate of the left edge of the bounding box for the shapes in a shape range.

The **LeftX** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Lock

Sub **Lock()**

Description

Member of ShapeRange

The **Lock** method locks all the shapes in a shape range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Move

Sub **Move(***DeltaX As Double***,** *DeltaY As Double***)**

Description

Member of ShapeRange

The **Move** method moves all the shapes in a shape range according to the specified offset.

Parameter	Description
DeltaX	Specifies the horizontal distance to move the shape range
DeltaY	Specifies the vertical distance to move the shape range

VBA example

The following VBA example moves all the shapes on the active page by **2**" to the right.

```
Sub Test()
 ActivePage.Shapes.All.Move 2, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.MoveToLayer

Sub **MoveToLayer(**Layer As Layer**)**

Description

Member of ShapeRange

The **MoveToLayer** method moves all the shapes in a shape range to the specified layer.

Parameter	Description
Layer	Specifies the layer

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.OrderBackOf

Sub **OrderBackOf(**Shape As Shape**)**

Description

Member of ShapeRange

The **OrderBackOf** method moves all the shapes in a shape range. The shapes are moved behind the specified shape in the stacking order of the current layer.

Parameter	Description
Shape	Specifies the shape behind which to place the shapes

VBA example

The following VBA example creates a set of circles behind the outline of the selected curve.

```
Sub Test()
Dim s As Shape, sr As New ShapeRange
Dim crv As Shape, sp As SubPath, lr As Layer
Dim x As Double, y As Double, i As Long
Set crv = ActiveShape
If crv.Type <> cdrCurveShape Then
MsgBox "Please select a curve"
Exit Sub
End If
Set sp = crv.Curve.SubPaths(1)
Set lr = crv.Layer
For i = 0 To 10
sp.GetPointPositionAt x, y, i / 10, cdrRelativeSegmentOffset
Set s = lr.CreateEllipse2(x, y, 0.3)
s.Fill.UniformColor.RGBAssign 255, 255, 0
sr.Add s
Next i
sr.OrderBackOf crv
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.OrderBackOne

Sub **OrderBackOne()**

Description

Member of ShapeRange

The **OrderBackOne** method moves all the shapes in a shape range. The shapes are moved one step backward in the stacking order of the current layer.

VBA example

The following VBA example creates a shadow for each selected object by duplicating the objects, offsets the duplicates by a small distance, and fills the duplicates with gray.

```
Sub Test()
 Dim srOld As ShapeRange, srNew As ShapeRange
 Set srOld = ActiveSelectionRange
 If srOld.Count <> 0 Then
  Set srNew = srOld.Duplicate(0.05, -0.05)
  srNew.ApplyUniformFill CreateRGBColor(50, 50, 50)
  srNew.OrderBackOne
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.OrderForwardOne

Sub **OrderForwardOne()**

Description

Member of ShapeRange

The **OrderForwardOne** method moves all the shapes in a shape range. The shapes are moved one step forward in the stacking order of the current layer.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.OrderFrontOf

Sub **OrderFrontOf(**Shape As Shape**)**

Description

Member of ShapeRange

The **OrderFrontOf** method moves all the shapes in a shape range. The shapes are moved in front of the specified shape in the stacking order of the current layer.

Parameter	Description
Shape	Specifies the shape in front of which to place the shapes

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.OrderReverse

Sub **OrderReverse()**

Description

Member of ShapeRange

The **OrderReverse** method reverses the stacking order of the shapes in a shape range.

VBA example

The following VBA example reverses the order of the selected shapes in the active document.

```
Sub Test()
 ActiveSelectionRange.OrderReverse
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.OrderToBack

Sub **OrderToBack()**

Description

Member of ShapeRange

The **OrderToBack** method moves a shape range to the back of the stacking order of the current layer.

VBA example

The following VBA example creates four rectangles and places them in front of all the other shapes of the current layer.

```
Sub Test()
 Dim s As Shape, sr As New ShapeRange
 Dim w As Double, h As Double
 Dim c1 As New Color, c2 As New Color
 w = ActivePage.SizeWidth / 2
 h = ActivePage.SizeHeight / 2
 c1.RGBAssign 255, 0, 0
 c2.RGBAssign 255, 255, 255
 Set s = ActiveLayer.CreateRectangle2(0, 0, w, h)
 s.Fill.ApplyFountainFill c1, c2, , 45
 sr.Add s
 Set s = ActiveLayer.CreateRectangle2(w, 0, w, h)
 s.Fill.ApplyFountainFill c1, c2, , 135
 sr.Add s
 Set s = ActiveLayer.CreateRectangle2(0, h, w, h)
 s.Fill.ApplyFountainFill c1, c2, , -45
 sr.Add s
 Set s = ActiveLayer.CreateRectangle2(w, h, w, h)
 s.Fill.ApplyFountainFill c1, c2, , -135
 sr.Add s
 sr.OrderToBack
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.OrderToFront

Sub **OrderToFront()**

Description

Member of ShapeRange

The **OrderToFront** method moves a shape range to the front of the stacking order of the current layer.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Parent

Property **Parent** As Application

Description

Member of ShapeRange

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.PositionX

Property **PositionX** As Double

Description

Member of ShapeRange

The **PositionX** property returns or specifies the x-coordinate of the position of a shape range, treating the range as a single object. This coordinate is relative to the anchor point specified by the Document.ReferencePoint property.

- See also the ShapeRange.GetPosition, ShapeRange.SetPosition, ShapeRange.Move, ShapeRange.GetBoundingBox, and ShapeRange.SetBoundingBox methods.

VBA example

The following VBA example creates a shape range containing all the ellipses on the page and it then duplicates the range. The duplicated shapes are placed in the lower-left corner of the page, treating the shape range as a group.

```
Sub Test()
 Dim sr1 As ShapeRange, sr2 As ShapeRange
 Set sr1 = ActivePage.FindShapes(Type:=cdrEllipseShape)
 Set sr2 = sr1.Duplicate
 ActiveDocument.ReferencePoint = cdrBottomLeft
 sr2.PositionX = 0
 sr2.PositionY = 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.PositionY

Property **PositionY** As Double

Description

Member of ShapeRange

The **PositionY** property returns or specifies the y-coordinate of the position of a shape range, treating the range as a single object. This coordinate is relative to the anchor point specified by the Document.ReferencePoint property.

- See also the ShapeRange.GetPosition, ShapeRange.SetPosition, ShapeRange.Move, ShapeRange.GetBoundingBox, and ShapeRange.SetBoundingBox methods.

VBA example

The following VBA example creates a shape range containing all the ellipses on the page, and it then duplicates the range. The duplicated shapes are placed in the lower-left corner of the page, treating the shape range as a group.

```
Sub Test()
 Dim sr1 As ShapeRange, sr2 As ShapeRange
 Set sr1 = ActivePage.FindShapes(Type:=cdrEllipseShape)
 Set sr2 = sr1.Duplicate
 ActiveDocument.ReferencePoint = cdrBottomLeft
 sr2.PositionX = 0
 sr2.PositionY = 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Project

Function **Project(**Plane As cdrProjectPlane**, [**ReferencePoint As cdrReferencePoint = cdrCenter**], [**ApplyToDuplicate As Boolean = False**])** As ShapeRange

Description

Member of ShapeRange

The **Project** method converts a two-dimensional shape range into a three-dimensional shape range.

Parameter	Description
Plane	Specifies the isometric view
ReferencePoint	Specifies the reference point for the conversion. This parameter is optional, and its default value is cdrCenter.
ApplyToDuplicate	Specifies whether to apply the conversion to a duplicate, leaving the original shape range unchanged. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example projects the shape range to the top isometric plane, using the upper-right corner of the bounding box of the shape range as the reference point.

```
Sub Test()
Dim shp1 As Shape
Dim shp2 As Shape
Dim shpRng As ShapeRange
Set shp1 = ActiveLayer.CreateRectangle2(0,0,3,6)
Set shp2 = ActiveLayer.CreateRectangle2(2,2,5,3)
Set shpRng = ActiveLayer.FindShapes(Type:=cdrRectangleShape)
shpRng.Project cdrProjectTop, cdrProjectRight
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Range

Function **Range(***IndexArray() As Variant***)** As **ShapeRange**

Description

Member of ShapeRange

The **Range** method creates a new shape range out of the specified list of shapes from the current range.

Parameter	Description
IndexArray	Specifies the shapes

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Remove

Sub **Remove(***Index As Long***)**

Description

Member of ShapeRange

The **Remove** method removes a specified shape from a shape range.

- The specified shape is removed only from the specified shape range and not from any other ranges of which it may be a part.
- The specified shape is not deleted from the document.

Parameter	Description
Index	Specifies the index number of the shape to be removed from the shape range

VBA example

The following VBA example moves the selected rectangles by **1**" to the right. Any other selected shapes that are not rectangles are not moved.

```
Sub Test()
 Dim sr As ShapeRange
 Dim i As Long
 Set sr = ActiveSelectionRange
 For i = sr.Count To 1 Step -1
  If sr(i).Type <> cdrRectangleShape Then sr.Remove i
 Next i
 sr.Move 1, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.RemoveAll

Sub **RemoveAll()**

Description

Member of ShapeRange

The **RemoveAll** method removes all shapes from a specified shape range.

- The specified shapes are removed only from the specified shape range and not from any other ranges of which they may be a part.
- The specified shapes are not deleted from the document.

VBA example

The following VBA example creates ten circles and randomly places them on a page. It fills them with red and groups them. It then creates **10** more rectangles, fills them with yellow, and groups them.

```
Sub Test()
 Dim sr As New ShapeRange
 Dim n As Long
 For n = 1 To 10
  sr.Add ActiveLayer.CreateEllipse2(Rnd() * 8, Rnd() * 11, 0.5)
 Next n
 sr.ApplyUniformFill CreateRGBColor(255, 0, 0)
 sr.Group
 sr.RemoveAll
 For n = 1 To 10
  sr.Add ActiveLayer.CreateRectangle2(Rnd() * 8, Rnd() * 11, 1, 1)
 Next n
 sr.ApplyUniformFill CreateRGBColor(255, 255, 0)
 sr.Group
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.RemoveFromContainer

Sub **RemoveFromContainer([***Level As Long***])**

Description

Member of ShapeRange

The **RemoveFromContainer** method removes all the shapes in a shape range from their PowerClip containers.

- If there are several nested PowerClip objects, you can remove the shapes from several containers at one time by specifying the **Level** parameter value.

Parameter	Description
Level	Specifies the lowest level from which you want to remove the shapes. The shapes are removed from this level and all levels above them. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example removes all shapes from their PowerClip container.

```
Sub Test()
 Dim s As Shape
 Dim p As PowerClip
 On Error Resume Next
 For Each s In ActivePage.Shapes
  Set p = Nothing
  Set p = s.PowerClip
  If Not p Is Nothing Then
   ActiveDocument.ClearSelection
   p.Shapes.All.RemoveFromContainer
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.RemoveFromSelection

Sub **RemoveFromSelection()**

Description

Member of ShapeRange

The **RemoveFromSelection** method removes a shape range from a selection..

VBA example

The following VBA example removes all rectangles from the current selection.

```
Sub Test()
 ActivePage.FindShapes(Type:=cdrRectangleShape).RemoveFromSelection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.RemoveRange

Sub **RemoveRange(**Range As ShapeRange**)**

Description

Member of ShapeRange

The **RemoveRange** method removes a shape range from another shape range.

Parameter	Description
Range	Specifies the shape range to be removed

VBA example

The following VBA example creates two shape ranges and then removes the rectangles from them.

```
Sub Test()
 Dim s As Shape
 Dim sr As ShapeRange, sr2 As ShapeRange, sr3 As ShapeRange
 Set s = ActiveLayer.CreateRectangle(2, 2, 4, 4)
 s.Fill.ApplyUniformFill CreateRGBColor(255, 0, 0)
 Set s = ActiveLayer.CreateRectangle2(1, 4, 5, 5)
 s.Fill.ApplyUniformFill CreateRGBColor(0, 255, 0)
 Set s = ActiveLayer.CreatePolygon(1, 2, 3, 4, 6)
 Set sr = ActivePage.FindShapes(, cdrRectangleShape)
 Set sr2 = ActivePage.FindShapes(, cdrPolygonShape)
 Set sr3 = ActivePage.FindShapes(, cdrNoShape, True)
 sr3.RemoveRange sr
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.RestoreCloneLink

Sub **RestoreCloneLink(**LinkToRestore As cdrCloneLinkType**)**

Description

Member of ShapeRange

The **RestoreCloneLink** method restores clone links of a specified property for the shapes in a shape range.

Parameter	Description
LinkToRestore	Specifies the link to be restored

VBA example

The following VBA example creates a shape range, clones it, and fills the clone. The clone link is then restored.

```
Sub Test()
 Dim s As Shape
 Dim sr1 As ShapeRange
 Dim sr2 As ShapeRange
 Set s = ActiveLayer.CreateRectangle(2, 2, 4, 4)
 s.Fill.ApplyUniformFill CreateRGBColor(255, 0, 0)
 Set s = ActiveLayer.CreateRectangle2(1, 4, 5, 5)
 s.Fill.ApplyUniformFill CreateRGBColor(0, 255, 0)
 Set s = ActiveLayer.CreatePolygon(1, 2, 3, 4, 6)
 Set sr = ActivePage.FindShapes(, cdrRectangleShape)
 Set sr2 = sr.Clone
 sr2.ApplyUniformFill CreateRGBColor(0, 0, 255)
 sr2.RestoreCloneLink cdrCloneFill
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.ReverseRange

Property **ReverseRange** As ShapeRange

Description

Member of ShapeRange

The **ReverseRange** property returns a shape range that contains, in reverse order, all the shapes from a given range.

The **ReverseRange** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.RightX

Property **RightX** As Double

Description

Member of ShapeRange

The **RightX** property returns the x-coordinate of the right edge of the bounding box for a shape range.

The **RightX** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Rotate

Sub **Rotate(***Angle As Double***)**

Description

Member of ShapeRange

The **Rotate** method rotates all of shapes in a shape range, treating the group as a single object.

- The center of rotation is specified by the RotationCenterX and RotationCenterY properties, while RotateEx allows specifies the center of rotation directly.

Parameter	Description
Angle	Specifies, in degrees, the amount to rotate the shape range

VBA example

The following VBA example creates a “flower” by duplicating circles. It then creates a larger flower by duplicating this group of six circles five more times to form six petals of different colors.

```
Sub Test()
 Dim n As Long
 Dim sr As New ShapeRange, sr1 As ShapeRange
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(0, 0, 0.5)
 s.SetRotationCenter 1, 1
 For n = 1 To 5
  sr.Add s.Duplicate
  s.Rotate 60
 Next n
 sr.Add s
 sr.ApplyUniformFill CreateRGBColor(255, 0, 0)
 sr.SetRotationCenter ActivePage.SizeWidth / 2, ActivePage.SizeHeight / 2
 For n = 0 To 4
  Set sr1 = sr.Duplicate
  sr1.ApplyUniformFill CreateRGBColor(255, 255 * (1 - n / 5), 0)
  sr.Rotate 60
 Next n
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.RotateEx

Sub **RotateEx(***Angle As Double***,** *CenterX As Double***,** *CenterY As Double***)**

Description

Member of ShapeRange

The **RotateEx** method rotates all the shapes in a shape range, treating the group as a single object. The range is rotated around a specified center of rotation.

Parameter	Description
Angle	Specifies the angle, in degrees, in which the range is rotated
CenterX	Specifies the x-coordinate for the center of rotation
CenterY	Specifies the y-coordinate for the center of rotation

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.RotationCenterX

Property **RotationCenterX** As Double

Description

Member of ShapeRange

The **RotationCenterX** returns or specifies the x-coordinate for the center of rotation for a shape range.

- See also the ShapeRange.SetRotationCenter method.

VBA example

The following VBA example creates a “flower” by duplicating circles. It then creates a larger flower by duplicating this group of six circles five more times, to form six petals of different colors.

```
Sub Test()
 Dim n As Long
 Dim sr As New ShapeRange, sr1 As ShapeRange
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(0, 0, 0.5)
 s.RotationCenterX = 1
 s.RotationCenterY = 1
 For n = 1 To 5
  sr.Add s.Duplicate
  s.Rotate 60
 Next n
 sr.Add s
 sr.ApplyUniformFill CreateRGBColor(255, 0, 0)
 sr.RotationCenterX = ActivePage.SizeWidth / 2
 sr.RotationCenterY = ActivePage.SizeHeight / 2
 For n = 0 To 4
  Set sr1 = sr.Duplicate
  sr1.ApplyUniformFill CreateRGBColor(255, 255 * (1 - n / 5), 0)
  sr.Rotate 60
 Next n
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.RotationCenterY

Property **RotationCenterY** As Double

Description

Member of ShapeRange

The **RotationCenterY** returns or specifies the y-coordinate for the center of rotation for a shape range.

- See also the ShapeRange.SetRotationCenter method.

VBA example

The following VBA example creates a “flower” by duplicating circles. It then creates a larger flower by duplicating this group of six circles five more times to form six petals of different colors.

```
Sub Test()
 Dim n As Long
 Dim sr As New ShapeRange, sr1 As ShapeRange
 Dim s As Shape
 Set s = ActiveLayer.CreateEllipse2(0, 0, 0.5)
 s.RotationCenterX = 1
 s.RotationCenterY = 1
 For n = 1 To 5
  sr.Add s.Duplicate
  s.Rotate 60
 Next n
 sr.Add s
 sr.ApplyUniformFill CreateRGBColor(255, 0, 0)
 sr.RotationCenterX = ActivePage.SizeWidth / 2
 sr.RotationCenterY = ActivePage.SizeHeight / 2
 For n = 0 To 4
  Set sr1 = sr.Duplicate
  sr1.ApplyUniformFill CreateRGBColor(255, 255 * (1 - n / 5), 0)
  sr.Rotate 60
 Next n
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Scallop

Sub **Scallop(***Radius As Double***, [**CombineSmoothSegments As Boolean = True**])**

Description

Member of ShapeRange

The **Scallop** method creates scallops on each cusp corner of the shapes in a shape range.

Parameter	Description
Radius	Specifies the radius of the scallop
CombineSmoothSegments	Specifies whether to combine smooth segments. This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.SetBoundingBox

Sub **SetBoundingBox(***x As Double***,** *y As Double***,** *Width As Double***,** *Height As Double***, [**KeepAspect As Boolean = False**], [**ReferencePoint As cdrReferencePoint = cdrCenter**])**

Description

Member of ShapeRange

The **SetBoundingBox** method moves and resizes a shape range so that it fits the specified bounding box.

- See also the ShapeRange.PositionX, ShapeRange.PositionY, ShapeRange.SizeWidth, and ShapeRange.SizeHeight properties, as well as the ShapeRange.GetPosition, ShapeRange.SetPosition, ShapeRange.GetSize, ShapeRange.SetSize, ShapeRange.SetSizeEx, and ShapeRange.Move methods.

Parameter	Description
x	Specifies, in document units, the horizontal position of the center of the bounding box
y	Specifies, in document units, the vertical position of the center of the bounding box
Width	Specifies, in document units, the width of the bounding box
Height	Specifies, in document units, the height of the bounding box
KeepAspect	Specifies whether to maintain the proportions of the bounding box relative to its contents. This parameter is optional, and its default value is **False**.
ReferencePoint	Specifies the reference point. This parameter is optional, and its default value is cdrCenter (**9**).

VBA example

The following VBA example imports a specified file and places it inside the selected shape (or shapes) while maintaining proportions.

```
Sub Test()
 Dim x As Double, y As Double, sx As Double, sy As Double
 Dim FileName As String, sr As ShapeRange
 If Documents.Count = 0 Then
  MsgBox "No document is open", vbCritical
  Exit Sub
 End If
 Set sr = ActiveSelectionRange
 If sr.Count = 0 Then
  MsgBox "No shapes selected", vbCritical
  Exit Sub
 End If
 sr.GetBoundingBox x, y, sx, sy
 FileName = CorelScriptTools.GetFileBox("All Files(*.*)|*.*", "Select a file to import")
 If FileName <> "" Then
  ActiveLayer.Import FileName
  Set sr = ActiveSelectionRange
  If sr.Count > 0 Then
   sr.SetBoundingBox x, y, sx, sy, True
  End If
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.SetFillMode

Sub **SetFillMode(**Mode As cdrFillMode**)**

Description

Member of ShapeRange

The **SetFillMode** method specifies a fill mode for the shapes in a shape range.

Parameter	Description
Mode	Specifies the fill mode

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.SetOutlineProperties

Sub **SetOutlineProperties([**Width As Double = -1**], [**Style As OutlineStyle**], [**Color As Color**], [**StartArrow As ArrowHead**], [**EndArrow As ArrowHead**], [**BehindFill As cdrTriState = cdrUndefined**], [**ScaleWithShape As cdrTriState = cdrUndefined**], [**LineCaps As cdrOutlineLineCaps = cdrOutlineUndefinedLineCaps**], [**LineJoin As cdrOutlineLineJoin = cdrOutlineUndefinedLineJoin**], [**NibAngle As Double = -9999**], [***NibStretch As Long***], [**DashDotLength As Double = -1**], [***PenWidth As Double***])**

Description

Member of ShapeRange

The **SetOutlineProperties** method sets the outline properties of each shape in a shape range.

Parameter	Description
Width	Specifies the width of the outline, measured in points. This parameter is optional, and its default value is **-1**.
Style	Specifies the outline style. This parameter is optional, and its default value is **Nothing**.
Color	Specifies the outline color. This parameter is optional, and its default value is **Nothing**.
StartArrow	Specifies a start arrow for the outline. This parameter is optional, and its default value is **Nothing**.
EndArrow	Specifies an end arrow for the outline. This parameter is optional, and its default value is **Nothing**.
BehindFill	Specifies whether the fill is behind the outline. This parameter is optional, and its default value is cdrUndefined (**-2**).
ScaleWithShape	Specifies whether the outline maintains the size proportions of the shape. This parameter is optional, and its default value is cdrUndefined (**-2**).
LineCaps	Specifies the endpoint style of an open-path outline. This parameter is optional, and its default value is cdrOutlineUndefinedLineCaps (**-1**).
LineJoin	Specifies the appearance of lines that intersect each other in an outline, and returns cdrOutlineLineJoin. This parameter is optional, and its default value is cdrOutlineUndefinedLineJoin (**-1**).
NibAngle	Specifies the orientation of the pen nib, relative to the drawing surface, for a calligraphic outline. This parameter is optional, and its default value is **-9999**.
NibStretch	Specifies the thickness of the pen nib for a calligraphic outline. This parameter is optional, and its default value is **0**.
DashDotLength	Specifies the dash-dot length of the outline. This parameter is optional, and its default value is **-1**.
PenWidth	Specifies the pen width of the outline. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example applies blue, dashed outlines with a width of **0.05"** to all the ellipses on the active page.

```
Sub Test()
 Dim sr As ShapeRange
 Set sr = ActivePage.FindShapes(, cdrEllipseShape)
 sr.SetOutlineProperties 0.05, OutlineStyles(5), CreateRGBColor(0, 0, 255)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.