ShapeRange.SetOutlinePropertiesEx

Sub **SetOutlinePropertiesEx([**Width As Double = -1**], [**Style As OutlineStyle**], [**Color As Color**], [**StartArrow As ArrowHead**], [**EndArrow As ArrowHead**], [**BehindFill As cdrTriState = cdrUndefined**], [**ScaleWithShape As cdrTriState = cdrUndefined**], [**LineCaps As cdrOutlineLineCaps = cdrOutlineUndefinedLineCaps**], [**LineJoin As cdrOutlineLineJoin = cdrOutlineUndefinedLineJoin**], [**NibAngle As Double = -9999**], [***NibStretch As Long***], [**DashDotLength As Double = -1**], [***PenWidth As Double***], [**Justification As cdrOutlineJustification=cdrOutlineJustificationUndefined**])

Description

Member of ShapeRange

The **SetOutlinePropertiesEx** method sets the outline properties of each shape, including outline justification, in a shape range.

Parameter	Description
Width	Specifies the width of the outline, measured in points. This parameter is optional, and its default value is **-1**.
Style	Specifies the outline style. This parameter is optional, and its default value is **Nothing**.
Color	Specifies the outline color. This parameter is optional, and its default value is **Nothing**.
StartArrow	Specifies a start arrow for the outline. This parameter is optional, and its default value is **Nothing**.
EndArrow	Specifies an end arrow for the outline. This parameter is optional, and its default value is **Nothing**.
BehindFill	Specifies whether the fill is behind the outline. This parameter is optional, and its default value is cdrUndefined (**-2**).
ScaleWithShape	Specifies whether the outline maintains the size proportions of the shape. This parameter is optional, and its default value is cdrUndefined (**-2**).
LineCaps	Specifies the endpoint style of an open-path outline. This parameter is optional, and its default value is cdrOutlineUndefinedLineCaps (**-1**).
LineJoin	Specifies the appearance of lines that intersect each other in an outline, and returns cdrOutlineLineJoin. This parameter is optional, and its default value is cdrOutlineUndefinedLineJoin (**-1**).
NibAngle	Specifies the orientation of the pen nib, relative to the drawing surface, for a calligraphic outline. This parameter is optional, and its default value is **-9999**.
NibStretch	Specifies the thickness of the pen nib for a calligraphic outline. This parameter is optional, and its default value is **0**.
DashDotLength	Specifies the dash-dot length of the outline. This parameter is optional, and its default value is **-1**.
PenWidth	Specifies the pen width of the outline. This parameter is optional, and its default value is **0**.
Justification	Specifies the outline justification settings. This parameter is optional, and its default value is **-1**.

VBA example

The following VBA example applies blue, dashed outlines with a width of **0.05**" to all the ellipses on the active page.

```
Sub Test()
 Dim sr As ShapeRange
 Set sr = ActivePage.FindShapes(, cdrEllipseShape)
 sr.SetOutlinePropertiesEx 0.15, Justification: = cdrOutlineJustificationOutside
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.SetPixelAlignedRendering

Sub **SetPixelAlignedRendering(***PixelAligned As Boolean***)**

Description

Member of ShapeRange

The **SetPixelAlignedRendering** method sets the alignment-to-pixel property for the shapes in a range.

Parameter	Description
PixelAligned	Specifies whether the alignment-to-pixel property is enabled

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.SetPosition

Sub **SetPosition(***PositionX As Double***,** *PositionY As Double***)**

Description

Member of ShapeRange

The **SetPosition** method sets the horizontal and vertical positions of all the shapes in a shape range, treating the range as a single object.

- The position of the range is set relative to a reference point specified by the Document.ReferencePoint property.

Parameter	Description
PositionX	Specifies, in document units, the horizontal position of the range
PositionY	Specifies, in document units, the vertical position of the range

VBA example

The following VBA example aligns the selected shapes to the upper-right corner of the page.

```
Sub Test()
 ActiveDocument.ReferencePoint = cdrTopRight
 ActiveSelectionRange.SetPosition ActivePage.SizeWidth, ActivePage.SizeHeight
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.SetPositionEx

Sub **SetPositionEx(**ReferencePoint As cdrReferencePoint**,** *x As Double*, *y As Double***)**

Description

Member of ShapeRange

The **SetPositionEx** method moves a shape range to the coordinates of a specified point.

Parameter	Description
ReferencePoint	Specifies the reference point
x	Specifies the x-coordinate
y	Specifies the y-coordinate

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.SetRotationCenter

Sub **SetRotationCenter(***x As Double***,** *y As Double***)**

Description

Member of ShapeRange

The **SetRotationCenter** method sets the x- and y-coordinates of the center of rotation for a shape range.

- See also the ShapeRange.RotationCenterX and ShapeRange.RotationCenterY properties.

Parameter	Description
x	Specifies the x-coordinate of the center of rotation
y	Specifies the y-coordinate of the center of rotation

VBA example

The following VBA example rotates all rectangles by **45**°. The rectangles are rotated relative to the center of the page.

```
Sub Test()
 Dim sr As ShapeRange
 Set sr = ActivePage.FindShapes(, cdrRectangleShape)
 sr.SetRotationCenter ActivePage.SizeWidth / 2, ActivePage.SizeHeight / 2
 sr.Rotate 45
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.SetSize

Sub **SetSize([***Width As Double***], [***Height As Double***])**

Description

Member of ShapeRange

The **SetSize** method sets the size of the shapes in a shape range, treating the range as a single object.

- The reference point around which to stretch the range is specified by the Document.ReferencePoint property.

- See also the ShapeRange.SizeWidth and ShapeRange.SizeHeight properties, as well as the ShapeRange.GetBoundingBox and ShapeRange.SetBoundingBox methods.

Parameter	Description
Width	Specifies, in document units, the width of the range. This parameter is optional, and its default value is **0**.
Height	Specifies, in document units, the height of the range. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example stretches all the shapes on the active layer so that the vertical size of each shape is **1**.

```
Sub Test()
 Dim x As Double, y As Double
 Dim sr As ShapeRange
 Set sr = ActiveLayer.Shapes.All
 If sr.Count > 0 Then
  ActiveDocument.ReferencePoint = cdrCenter
  sr.GetPosition x, y
  sr.SetSize x, 1
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.SetSizeEx

Sub **SetSizeEx(***CenterX As Double***,** *CenterY As Double***, [***Width As Double***], [***Height As Double***])**

Description

Member of ShapeRange

The **SetSizeEx** method sets the size of the shapes in a shape range, treating the range as a single object. You can specify the reference point around which the range is stretched.

- See also the ShapeRange.SizeWidth and ShapeRange.SizeHeight properties, as well as the ShapeRange.GetBoundingBox and ShapeRange.SetBoundingBox methods.

Parameter	Description
CenterX	Specifies the x-coordinate of the reference point
CenterY	Specifies the y-coordinate of the reference point
Width	Specifies the horizontal size of the shape range after the stretch. This parameter is optional, and its default value is **0**.
Height	Specifies the vertical size of the shape range after the stretch. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example stretches the shape range on the active layer proportionally, so that its width is **2**".

```
Sub Test()
 Dim x As Double, y As Double
 Dim sr As ShapeRange
 Set sr = ActiveLayer.Shapes.All
 If sr.Count > 0 Then
  ActiveDocument.ReferencePoint = cdrCenter
  sr.GetPosition x, y
  sr.SetSizeEx x, y, 2
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Shapes

Property **Shapes** As Shapes

Description

Member of ShapeRange

The **Shapes** property returns a collection of Shapes from a shape range.

The **Shapes** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.SizeHeight

Property **SizeHeight** As Double

Description

Member of ShapeRange

The **SizeHeight** property returns or specifies the vertical size of the shapes in a shape range, treating the range as a single object.

- See also the ShapeRange.GetSize, ShapeRange.SetSize, ShapeRange.SetSizeEx, ShapeRange.GetBoundingBox, and ShapeRange.SetBoundingBox methods.

VBA example

The following VBA example stretches all shapes on the active layer so that the shape range is **2**" high.

```
Sub Test()
 ActiveLayer.Shapes.All.SizeHeight = 2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.SizeWidth

Property **SizeWidth** As Double

Description

Member of ShapeRange

The **SizeWidth** property returns or specifies the horizontal size of the shapes in a shape range, treating the range as a single object.

- See also the ShapeRange.GetSize, ShapeRange.SetSize, ShapeRange.SetSizeEx, ShapeRange.GetBoundingBox, and ShapeRange.SetBoundingBox methods.

VBA example

The following VBA example stretches all shapes on the active layer so that the shape range is **2**" wide.

```
Sub Test()
 ActiveLayer.Shapes.All.SizeWidth = 2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Skew

Sub Skew(AngleX As Double**,** AngleY As Double**)**

Description

Member of ShapeRange

The **Skew** method skews the shapes in a shape range, treating the range as a single object.

- The range is distorted relative to the reference point specified by the Document.ReferencePoint property.

- The SkewEx method lets you specify the center of distortion directly.

Parameter	Description
AngleX	Specifies the degree in which to slant the shape range horizontally
AngleY	Specifies the degree in which to slant the shape range vertically

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.SkewEx

Sub **SkewEx(***AngleX As Double***,** *AngleY As Double***,** *CenterX As Double***,** *CenterY As Double***)**

Description

Member of ShapeRange

The **SkewEx** method skews the shapes in a shape range, treating the range as a single object. The range is distorted relative to the specified center of distortion.

Parameter	Description
AngleX	Specifies, in degrees, the horizontal angle in which the range is skewed
AngleY	Specifies, in degrees, the vertical angle in which the range is skewed
CenterX	Specifies the x-coordinate for the center of distortion
CenterY	Specifies the y-coordinate for the center of distortion

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Sort

Sub **Sort**(*CompareExpression As String*, **[***StartIndex As Long***]**, **[***EndIndex As Long***]**, **[***Data***])**

Description

Member of ShapeRange

The **Sort** method sorts the shapes in a range based on a Corel Query Language (CQL) condition expression.

- For information on CQL, see the section "Including queries in macros."

Parameter	Description
CompareExpression	Specifies the query expression. For help with creating query expressions, see the section "Understanding the available query criteria."
StartIndex	Specifies the index number of the first shape object in the shape range. This parameter is optional, and its default value is **1**.
EndIndex	Specifies the index number of the last shape object in the shape range. This parameter is optional, and its default value is that of the last shape object in the shape range.

Data	Specifies any data that can be referenced by the CQL expression as `@data`. For example,
	`ShapeRange.Sort "@shape1.width > @shape2.height + @data",,,4`
	is equivalent to
	`ShapeRange.Sort "@shape1.width > @shape2.height + 4".`
	This parameter is optional.

VBA example

The following VBA example demonstrates how to use the **ShapeRange.Sort** method:

```
Sub ShapeRange_Sort()
Dim d As Document
Dim sr As New ShapeRange 'Holds all the text shapes / numbers
Dim s As Shape, s1 As Shape, s2 As Shape
Dim y As Integer 'Holds the y position value of the rectangle
Dim x As Integer 'Holds the x position value of the rectangle
Dim i As Integer 'Holds the brick counter
Set d = CreateDocument
'Create Bricks
For y = 1 To 9
For x = 1 To 6
i = i + 1
Set s1 = d.ActiveLayer.CreateRectangle2(x, y, 1, 0.5)
'Creates a Rectangle Shape
Set s2 = d.ActiveLayer.CreateArtisticText(0, 0, i)
'Creates a Number for the Brick Shape
s2.AlignToShape cdrAlignVCenter, s1
'Aligns the Text Vertically to the rectangle
s2.AlignToShape cdrAlignHCenter, s1
'Aligns the Text Horizontally to the rectangle
sr.Add s2
Next x
Next y
For y = 1 To 9
For x = 1 To 6
i = i + 1
Set s1 = d.ActiveLayer.CreateRectangle2(x, y + 0.5, 1, 0.5)
Set s2 = d.ActiveLayer.CreateArtisticText(0, 0, i)
s2.AlignToShape cdrAlignVCenter, s1
s2.AlignToShape cdrAlignHCenter, s1
sr.Add s2
Next x
Next y
'Sort the numbers from the upper left to the lower right
'(going right and then down). To do this, give the highest value
'to the upper-left shape by multiplying its top position by 100
'and subtracting its left position.
'Example Shape 1 has a top value of 10 and a left value of 1 so ...
'Shape 1 (Upper Left Shape) -> 10 X 100 - 1 = 999
'Shape 2 (to the right of Shape 1) -> 10 x 100 - 2 = 998
'Bottom right Shape would be 1.5 x 100 - 6 = 144
MsgBox "Click OK to Sort the Bricks", vbOKOnly, "ShapeRange.Sort Example"
sr.Sort " @shape1.Top * 100 - @shape1.Left > @shape2.Top * 100 - @shape2.Left"
i = 0
For Each s In sr.Shapes
i = i + 1
s.Text.Story.Text = i
Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.StepAndRepeat

Function **StepAndRepeat(NumCopies As Long, DistanceX As Double, DistanceY As Double, [ModeX As cdrDistanceMode = cdrModeOffset], [DirectionX As cdrDirection = cdrRight], [ModeY As cdrDistanceMode = cdrModeOffset], [DirectionY As cdrDirection = cdrDown])** As ShapeRange

Description

Member of ShapeRange

The **StepAndRepeat** method creates multiple copies of the shapes in a shape range.

Parameter	Description
NumCopies	Specifies the number of copies
DistanceX	Specifies the horizontal offset of the copies
DistanceY	Specifies the vertical offset of the copies
ModeX	This parameter is optional, and its default value is cdrModeOffset (**0**).
DirectionX	This parameter is optional, and its default value is cdrRight (**1**).
ModeY	This parameter is optional, and its default value is cdrModeOffset (**0**).
DirectionY	This parameter is optional, and its default value is cdrDown (**3**).

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Stretch

Sub **Stretch(***StretchX As Double***, [***StretchY As Double***], [**StretchCharactersSize As Boolean = False**])**

Description

Member of ShapeRange

The **Stretch** method stretches the shapes in a shape range, treating the range as a single object.

- The shape range is distorted relative to the reference point specified by the Document.ReferencePoint property.

Parameter	Description
StretchX	Specifies the horizontal stretch factor
StretchY	Specifies the vertical stretch factor. If not specified, this value assigned the same value as the **StretchX** parameter, resulting in a proportional stretch. This parameter is optional, and its default value is **0**.
StretchCharactersSize	Specifies whether to stretch characters. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example proportionally stretches all the shapes on the page by **200**%. The position of the shape range is relative to the upper-right corner of the bounding box of the range.

```
Sub Test()
 ActiveDocument.ReferencePoint = cdrTopRight
 ActivePage.Shapes.All.Stretch 2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.StretchEx

Sub **StretchEx(***CenterX As Double***,** *CenterY As Double***,** *StretchX As Double***, [***StretchY As Double***], [**StretchCharactersSize As Boolean = False**])**

Description

Member of ShapeRange

The **StretchEx** method stretches the shapes in a shape range, treating the range as a single object. The range is distorted relative to a point that is specified as the center of distortion.

Parameter	Description
CenterX	Specifies the x-coordinate of the center of distortion
CenterY	Specifies the y-coordinate of the center of distortion
StretchX	Specifies the horizontal stretch factor
StretchY	Specifies the vertical stretch factor. If not specified, this value is assigned the same value as the **StretchX** parameter, resulting in a proportional stretch. This parameter is optional, and its default value is **0**.
StretchCharactersSize	Specifies whether to stretch characters. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example stretches all of shapes on the page by **200**%, using the center of the page as the center of the distortion.

```
Sub Test()
 ActiveDocument.ReferencePoint = cdrBottomLeft
 With ActivePage
  .Shapes.All.StretchEx .CenterX, .CenterY, 2
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.TopY

Property **TopY** As Double

Description

Member of ShapeRange

The **TopY** property returns the y-coordinate of the top edge of the bounding box for a shape range.

The **TopY** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Ungroup

Sub **Ungroup()**

Description

Member of ShapeRange

The **Ungroup** method ungroups one level of groups in a shape range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.UngroupAll

Sub **UngroupAll()**

Description

Member of ShapeRange

The **UngroupAll** method ungroups all the groups in a shape range.

VBA example

The following VBA example ungroups any groups on the active page.

```
Sub Test()
 ActivePage.Shapes.All.UngroupAll
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.UngroupAllEx

Function **UngroupAllEx()** As ShapeRange

Description

Member of ShapeRange

The **UngroupAllEx** method ungroups all grouped shapes and returns the ungrouped shapes as a shape range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.UngroupEx

Function **UngroupEx()** As ShapeRange

Description

Member of ShapeRange

The **UngroupEx** method ungroups one level of groups in a shape range and returns the ungrouped shapes as another shape range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Unlock

Sub **Unlock()**

Description

Member of ShapeRange

The **Unlock** method unlocks all the shapes in a shape range.

Copyright 2014 Corel Corporation. All rights reserved.

ShapeRange.Unproject

Function **Unroject(**Plane As cdrProjectPlane**, [**ReferencePoint As cdrReferencePoint = cdrCenter**], [**ApplyToDuplicate As Boolean = False**])** As ShapeRange

Description

Member of ShapeRange

The **Unproject** method converts a a three-dimensional shape range into a two-dimensional shape range.

Parameter	Description
Plane	Specifies the isometric view
ReferencePoint	Specifies the reference point for the conversion. This parameter is optional, and its default value is cdrCenter.
ApplyToDuplicate	Specifies whether to apply the conversion to a duplicate, leaving the original shape range unchanged. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example projects the shape range to the top isometric plane, using the upper-right corner of the bounding box of the shape range as the reference point.

```
Sub Test()
Dim shp1 As Shape
Dim shp2 As Shape
Dim shpRng As ShapeRange
Set shp1 = ActiveLayer.CreateRectangle2(0,0,3,6)
Set shp2 = ActiveLayer.CreateRectangle2(2,2,5,3)
Set shpRng = ActiveLayer.FindShapes(Type:=cdrRectangleShape)
shpRng.Project cdrProjectTop, cdrProjectRight
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shapes

Properties Methods

Description

The **Shapes** class represents a collection of shapes (or Shape objects).

Copyright 2014 Corel Corporation. All rights reserved.

Shapes.All

Function **All()** As ShapeRange

Description

Member of Shapes

The **All** method returns a or sets a shape range that contains all the shapes from a Shapes collection.

VBA example

The following VBA example selects all the shapes in the **Shapes** collection by using the **All** method, and it then applies a two-pattern fill to the shapes.

```
Sub ShapesAll()
 ActiveLayer.Shapes.All.ApplyPatternFill cdrTwoColorPattern
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shapes.AllExcluding

Function **AllExcluding(***IndexArray() As Variant***)** As ShapeRange

Description

Member of Shapes

The **AllExcluding** method returns a shape range that contains all the shapes (except any specified ones) from a Shapes collection.

- This function accepts a variable number of arguments. It also accepts arrays.

Parameter	Description
IndexArray	Specifies the range of index numbers that identify and group the desired shapes

VBA example

The following VBA example deletes all the shapes in the **Shapes** collection, except the two shapes that were most recently created. To run this example, there must be at least three shapes on the active layer.

```
Sub Test()
 With ActiveLayer.Shapes
  .AllExcluding(Array(1, 2)).Delete
  MsgBox "There are " & .Count & " shapes in the Shapes collection."
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shapes.Application

Property **Application** As Application

Description

Member of Shapes

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Shapes.Count

Property **Count** As Long

Description

Member of Shapes

The **Count** property returns the number of shapes in a Shapes collection.

The **Count** property returns a read-only value.

VBA example

The following VBA example displays the number of shapes in the **Shapes** collection.

```
Sub ShapesCount()
 With ActiveLayer.Shapes
  MsgBox "There are " & .Count & " shapes in the Shapes collection."
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shapes.FindShape

Function **FindShape([***Name As String***], [**Type As cdrShapeType = cdrNoShape**], [***StaticID As Long***], [**Recursive As Boolean = True**], [***Query As String***])** As Shape

Description

Member of Shapes

The **FindShape** method returns a shape based upon the specified properties.

Parameter	Description
Name	Specifies the shape by name. This parameter is optional.
Type	Specifies the shape by type. This parameter is optional, and its default value is cdrNoShape (**0**).
StaticID	Specifies the unique ID of the shape. This parameter is optional, and its default value is **0**.
Recursive	Specifies whether to iterate through all shapes. This parameter is optional, and its default value is **True**.
Query	Specifies a query through the Corel Query Language (CQL). This parameter is optional. For information on queries, see the section "Including queries in macros." For specific information on searching for objects, see the section "Searching for objects."

VBA example

The following VBA example finds a rectangle named **Frame** and selects it if it exists.

```
Sub Test()
 Dim s As Shape
 Set s = ActivePage.FindShape(Name:="Frame", Type:=cdrRectangleShape)
 If s Is Nothing Then
  MsgBox "The rectange 'Frame' cannot be found on page " & ActivePage.Index
 Else
  s.CreateSelection
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shapes.FindShapes

Function **FindShapes([***Name As String***], [**Type As cdrShapeType = cdrNoShape**], [**Recursive As Boolean = True**], [***Query As String***])** As ShapeRange

Description

Member of Shapes

The **FindShapes** method finds all shapes with the specified properties and returns them as a shape range.

Parameter	Description
Name	Specifies the shape by name This parameter is optional.
Type	Specifies the shape by type. This parameter is optional, and its default value is cdrNoShape (**0**).
Recursive	Specifies whether to iterate through all shapes. This parameter is optional, and its default value is **True**.
Query	Specifies a query through the Corel Query Language (CQL). This parameter is optional. For information on queries, see the section "Including queries in macros." For specific information on searching for objects, see the section "Searching for objects."

VBA example

The following VBA example finds all the rectangles on the current page and fills them with red.

```
Sub Test()
 Dim sr As ShapeRange
 Set sr = ActivePage.FindShapes(Type:=cdrRectangleShape)
 If sr.Count <> 0 Then
  sr.ApplyUniformFill CreateRGBColor(255, 0, 0)
 Else
  MsgBox "There are no rectangles on the current page"
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shapes.First

Property **First** As Shape

Description

Member of Shapes

The **First** property returns the first shape in a Shapes collection.

The **First** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shapes.Item

Property **Item(***IndexOrName As Variant***)** As Shape

Description

Member of Shapes

The **Item** property returns a specified shape. It is the default property of the Shapes class.

The **Item** property returns a read-only value.

Parameter	Description
IndexOrName	Specifies the shape by its index number or name: • **Index** — Specifies the preset placeholder that uniquely identifies each member of the **Shapes** collection • **Name** — Specifies the string that uniquely identifies each shape

VBA example

The following VBA example removes any fill from the first shape object in the **Shapes** collection.

```
Sub ShapesItem()
 ActiveLayer.Shapes.Item(1).Fill.ApplyNoFill
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Shapes.Last

Property **Last** As Shape

Description

Member of Shapes

The **Last** property returns the last shape in a Shapes collection.

The **Last** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Shapes.Parent

Property **Parent** As Object

Description

Member of Shapes

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Shapes.Range

Function **Range(***IndexArray() As Variant***)** As ShapeRange

Description

Member of Shapes

The **Range** method returns a shape range that contains all the specified shapes from a Shapes collection.

- This method accepts a variable number of arguments. It also accepts arrays.

Parameter	Description
IndexArray	Specifies the range of index numbers that identify and group the desired shapes

VBA example

The following VBA example deletes a shape range from the active document. The first (**1**) and the fourth (**4**) shapes are deleted from the Shapes collection. A message box displays the number of shapes in the collection before and after the deletion, to confirm that the shapes were removed from the collection.

```
Sub ShapesRange()
 With ActiveLayer.Shapes
  MsgBox "There are " & .Count & " shapes in the Shapes collection."
  .Range(Array(1, 4)).Delete
  MsgBox "There are " & .Count & " shapes in the Shapes collection."
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint

Properties Methods

Description

The **SnapPoint** class represents the settings for a snap point on a shape.

Basic shapes have several snap points — for example, a rectangle has snap points at the middle of each side. Additional snap points can be added to a shape by using the SnapPoints.AddUserSnapPoint method or the SnapPoints.AddUserSnapPointEx method.

- You can create a **SnapPoint** object by using the **New** keyword in Visual Basic.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.Application

Property **Application** As Application

Description

Member of SnapPoint

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.BBox

Property **BBox** As BBoxSnapPoint

Description

Member of SnapPoint

The **BBox** property returns a read-only value that is associated with the properties specific to a bounding-box snap point.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.CanChangeDirection

Property **CanChangeDirection** As Boolean

Description

Member of SnapPoint

The **CanChangeDirection** property returns a read-only value that indicates whether a snap point can change direction.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.CreateSelection

Sub **CreateSelection()**

Description

Member of SnapPoint

The **CreateSelection** method selects a snap point, deselecting all others.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.Delete

Sub **Delete()**

Description

Member of SnapPoint

The **Delete** method deletes a snap point.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.Direction

Property **Direction** As Double

Description

Member of SnapPoint

The **Direction** property specifies the default direction for a snap point.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.Edge

Property **Edge** As EdgeSnapPoint

Description

Member of SnapPoint

The **Edge** property returns a read-only value that is associated with the properties of an edge snap point.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.GetPosition

Sub **GetPosition(***PositionX As Double***,** *PositionY As Double***)**

Description

Member of SnapPoint

The **GetPosition** method returns the position of a snap point.

Parameter	Description
PositionX	Specifies the x-coordinate
PositionY	Specifies the y-coordinate

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.IsDeletable

Property **IsDeletable** As Boolean

Description

Member of SnapPoint

The **IsDeletable** property returns a read-only value that indicates whether a snap point can be deleted.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.IsMovable

Property **IsMovable** As Boolean

Description

Member of SnapPoint

The **IsMovable** property returns a read-only value that indicates whether a snap point can be moved.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.IsSelectable

Property **IsSelectable** As Boolean

Description

Member of SnapPoint

The **IsSelectable** property returns a read-only value that indicates whether a snap point can be selected.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.Move

Sub **Move(***OffsetX As Double*, *OffsetY As Double***)**

Description

Member of SnapPoint

The **Move** method moves a snap point by a specified offset.

Parameter	Description
OffsetX	Specifies the horizontal offset
OffsetY	Specifies the vertical offset

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.Object

Property **Object** As ObjectSnapPoint

Description

Member of SnapPoint

The **Object** property returns a read-only value that is associated with the properties specific to an object snap point.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.Parent

Property **Parent** As Shape

Description

Member of SnapPoint

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

VBA example

The following VBA example selects one of the shapes to which the selected connector line is attached.

```
Sub Test()
 Dim sp As New SnapPoint
 If ActiveShape.Type <> cdrConnectorShape Then
  MsgBox "Select a connector line."
  Exit Sub
 End If
 Set sp = ActiveShape.Connector.StartPoint
 If sp.Type = cdrSnapPoint Then
  sp.Parent.CreateSelection
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.PositionX

Property **PositionX** As Double

Description

Member of SnapPoint

The **PositionX** property returns or specifies the horizontal position of a snap point. If the point is on a shape, its position cannot be changed.

VBA example

The following VBA example creates a star and attaches a connector line to its center. The other end of the connector line is placed on the page at the coordinates (**1**", **2**").

```
Sub Test()
Dim s1 As Shape, sCon As Shape
Dim sp As New SnapPoint
Set s1 = ActiveLayer.CreatePolygon(1.6, 10, 4.5, 7, 5, 1, 2)
sp.PositionX = 1
sp.PositionY = 2
Set sCon = ActiveLayer.CreateConnector(s1.SnapPoints(2), sp)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.PositionY

Property **PositionY** As Double

Description

Member of SnapPoint

The **PositionY** property returns or specifies the vertical position of a snap point. If the point is on a shape, its position cannot be changed.

VBA example

The following VBA example creates a star and attaches a connector line to its center. The other end of the connector line is placed on the page at the coordinates (**1**", **2**").

```
Sub Test()
Dim s1 As Shape, sCon As Shape
Dim sp As New SnapPoint
Set s1 = ActiveLayer.CreatePolygon(1.6, 10, 4.5, 7, 5, 1, 2)
sp.PositionX = 1
sp.PositionY = 2
Set sCon = ActiveLayer.CreateConnector(s1.SnapPoints(2), sp)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.ReferenceData

Property **ReferenceData** As String

Description

Member of SnapPoint

The **ReferenceData** property returns a read-only value that is associated with the unique identifier of a snap point.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.Selected

Property **Selected** As Boolean

Description

Member of SnapPoint

The **Selected** property specifies whether a snap point is selected by the user.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.SetPosition

Sub **SetPosition(***PositionX As Double*, *PositionY As Double***)**

Description

Member of SnapPoint

The **SetPosition** method moves a snap point to a specified position.

Parameter	Description
PositionX	Specifies the x-coordinate
PositionY	Specifies the y-coordinate

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.Shape

Property **Shape** As Shape

Description

Member of SnapPoint

The **Shape** property returns a read-only value that is associated with the shape to which a snap point belongs.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.Type

Property **Type** As cdrPointType

Description

Member of SnapPoint

The **Type** property returns the type for a snap point, regardless of whether it belongs to a shape or is “free-floating” on the page.

The **Type** property returns a read-only value of cdrPointType.

VBA example

The following VBA example selects one of the shapes to which the selected connector line is attached.

```
Sub Test()
 Dim sp As New SnapPoint
 If ActiveShape.Type <> cdrConnectorShape Then
  MsgBox "Select a connector line."
  Exit Sub
 End If
 Set sp = ActiveShape.Connector.StartPoint
 If sp.Type = cdrSnapPoint Then
  sp.Parent.CreateSelection
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.User

Property **User** As UserSnapPoint

Description

Member of SnapPoint

The **User** property returns a read-only value that is associated with the properties specific to a user-created snap point.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoint.UsesDirection

Property **UsesDirection** As Boolean

Description

Member of SnapPoint

The **UsesDirection** property specifies whether a snap point uses its associated direction.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPointRange

Properties Methods

Description

The **SnapPointRange** class represents a range of snap points (or SnapPoint objects).

Copyright 2014 Corel Corporation. All rights reserved.

SnapPointRange.Add

Function **Add(**SnapPoint As SnapPoint**)** As Boolean

Description

Member of SnapPointRange

The **Add** method adds the specified snap point to a list.

Parameter	Description
SnapPoint	Specifies the snap point

Copyright 2014 Corel Corporation. All rights reserved.

SnapPointRange.AddToSelection

Sub **AddToSelection()**

Description

Member of SnapPointRange

The **AddToSelection** method adds snap points to the current selection.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPointRange.ChangeDirection

Sub **ChangeDirection([**Direction As Double = -9999**], [**UsesDirection As cdrTriState = cdrUndefined**])**

Description

Member of SnapPointRange

The **ChangeDirection** method changes the default direction of connection for all snap points in a list.

Parameter	Description
Direction	Specifies the direction. This parameter is optional, and its default value is **-9999**.
UsesDirection	Specifies, through a value of cdrTriState, how to use the specified direction. This parameter is optional, and its default value is cdrUndefined.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPointRange.Count

Property **Count** As Long

Description

Member of SnapPointRange

The **Count** property returns the total number of snap points in a list.

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPointRange.CreateSelection

Sub **CreateSelection()**

Description

Member of SnapPointRange

The **CreateSelection** method creates a selection from the snap points in a list.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPointRange.Delete

Sub **Delete()**

Description

Member of SnapPointRange

The **Delete** method deletes all the snap points in a list.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPointRange.Find

Function **Find(***ReferenceData As String***)** As SnapPoint

Description

Member of SnapPointRange

The **Find** method finds a snap point in a list.

Parameter	Description
ReferenceData	Specifies the reference data

Copyright 2014 Corel Corporation. All rights reserved.

SnapPointRange.Item

Property **Item(***Index As Long***)** As SnapPoint

Description

Member of SnapPointRange

The **Item** property returns the specified SnapPoint object from a list.

Item is the default property of the **SnapPointRange** class, and it returns a read-only value.

Parameter	Description
Index	Specifies the snap point by its index number

Copyright 2014 Corel Corporation. All rights reserved.

SnapPointRange.Move

Sub **Move(***OffsetX As Double***,** *OffsetY As Double***)**

Description

Member of SnapPointRange

The **Move** method moves, by a given offset, all the snap points in a list.

Parameter	Description
OffsetX	Specifies the horizontal offset
OffsetY	Specifies the vertical offset

Copyright 2014 Corel Corporation. All rights reserved.

SnapPointRange.Remove

Function **Remove(***Index As Long***)** As Boolean

Description

Member of SnapPointRange

The **Remove** method removes a specified snap point from a list (without deleting the snap point itself).

Parameter	Description
Index	Specifies the index number of the snap point

Copyright 2014 Corel Corporation. All rights reserved.

SnapPointRange.RemoveByReference

Function **RemoveByReference(***ReferenceData As String***) As Boolean**

Description

Member of SnapPointRange

The **RemoveByReference** method removes a snap point — as identified by the given reference data — from a list.

Parameter	Description
ReferenceData	Specifies the reference data

Copyright 2014 Corel Corporation. All rights reserved.

SnapPointRange.RemoveFromSelection

Sub **RemoveFromSelection()**

Description

Member of SnapPointRange

The **RemoveFromSelection** method removes snap points from the current selection.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPointRange.SetAutoSnap

Sub **SetAutoSnap(***AutoSnap As Boolean***)**

Description

Member of SnapPointRange

The **SetAutoSnap** method changes whether automatic snapping is applied to all the snap points in a list.

Parameter	Description
AutoSnap	Specifies whether automatic snapping is enabled

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoints

Properties Methods

Description

The **SnapPoints** class represents a collection of snap points (or SnapPoint objects).

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoints.AddUserSnapPoint

Function **AddUserSnapPoint(***PositionX As Double***,** *PositionY As Double***, [***Direction As Double***], [**UseDirection As Boolean = False**]) As** SnapPoint

Description

Member of SnapPoints

The **AddUserSnapPoint** method adds a user-created snap point.

Parameter	Description
PositionX	Specifies the x-coordinate of the snap point
PositionY	Specifies the y-coordinate of the snap point
Direction	Specifies a direction. This parameter is optional, and its default value is **0**.
UseDirection	Specifies how to use the specified direction. This parameter is optional, and its default value is **False**.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoints.AddUserSnapPointEx

Function **AddUserSnapPointEx(***ID As String*, *PositionX As Double*, *PositionY As Double*, **[***Direction As Double***]**, **[**UseDirection As Boolean = False**])** As SnapPoint

Description

Member of SnapPoints

The **AddUserSnapPointEx** method adds a user-created snap point.

Parameter	Description
ID	Specifies the ID of the snap point. This ID must be a generated UUID or GUID.
PositionX	Specifies the x-coordinate of the snap point
PositionY	Specifies the y-coordinate of the snap point
Direction	Specifies a direction. This parameter is optional, and its default value is **0**.
UseDirection	Specifies how to use the specified direction. This parameter is optional, and its default value is **False**.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoints.All

Property **All** As SnapPointRange

Description

Member of SnapPoints

The **All** property returns a read-only value consisting of a list of all the snap points in a SnapPoints collection.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoints.Application

Property **Application** As Application

Description

Member of SnapPoints

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoints.Auto

Function **Auto()** As SnapPoint

Description

Member of SnapPoints

The **Auto** method returns the automatic snap point for a shape.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoints.BBox

Function **BBox(**Type As cdrReferencePoint**)** As SnapPoint

Description

Member of SnapPoints

The **BBox** method finds a bounding-box snap point of a specified type.

Parameter	Description
Type	Specifies the type of bounding-box snap point

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoints.ClearSelection

Sub **ClearSelection()**

Description

Member of SnapPoints

The **ClearSelection** method deselects all snap points.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoints.Count

Property **Count** As Long

Description

Member of SnapPoints

The **Count** property returns the total number of snap points in a SnapPoints collection.

The **Count** property returns a read-only value.

VBA example

The following VBA example creates a rectangle with rounded corners and displays the number of snap points available for this type of shape.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle2(0, 0, 2, 2, 0.5, 0.5, 0.5, 0.5)
 MsgBox s.SnapPoints.Count
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoints.Edge

Function **Edge(***SegmentIndex As Long***,** *SegmentOffset As Double***)** As SnapPoint

Description

Member of SnapPoints

The **Edge** method finds an edge snap point by using the given parameters.

Parameter	Description
SegmentIndex	Specifies the index number of the segment
SegmentOffset	Specifies the time parameter (offset) along the segment

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoints.FindClosest

Function **FindClosest(**TypeSet As cdrPointType**,** *PositionX As Double*, *PositionY As Double***)** As SnapPoint

Description

Member of SnapPoints

The **FindClosest** method finds the closest snap point of a given type.

Parameter	Description
TypeSet	Specifies the type of snap point
PositionX	Specifies the x-coordinate of the reference point
PositionY	Specifies the y-coordinate of the reference point

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoints.Item

Property **Item(***Index As Long***)** As SnapPoint

Description

Member of SnapPoints

The **Item** property returns the specified SnapPoint object from a SnapPoints collection.

Item is the default property of the **SnapPoints** class, and its reference can be omitted when you are accessing items in a **SnapPoints** collection. For example, **SnapPoints.Item(5)** is the same as **SnapPoints(5)** — they both reference the fifth point in the collection.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the snap point by its index number

VBA example 1

The following VBA example creates a rectangle with rounded corners and marks each snap point with a small circle.

```
Sub Test()
 Dim s As Shape
 Dim sp As SnapPoint, i As Long
 Set s = ActiveLayer.CreateRectangle2(0, 0, 2, 2, 0.5, 0.5, 0.5, 0.5)
 For i = 1 To s.SnapPoints.Count
  Set sp = s.SnapPoints(i)
  ActiveLayer.CreateEllipse2 sp.PositionX, sp.PositionY, 0.05
 Next i
End Sub
```

VBA example 2

The following VBA example performs the same procedure as the previous example. However, instead of using a **For Next** command, it uses the **For Each** command in Visual Basic to iterate through all the snap points in the collection.

```
Sub Test()
 Dim s As Shape
 Dim sp As SnapPoint
 Set s = ActiveLayer.CreateRectangle2(0, 0, 2, 2, 0.5, 0.5, 0.5, 0.5)
 For Each sp In s.SnapPoints
  ActiveLayer.CreateEllipse2 sp.PositionX, sp.PositionY, 0.05
 Next sp
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoints.Object

Function **Object(**Type As cdrObjectSnapPointType**)** As SnapPoint

Description

Member of SnapPoints

The **Object** method finds an object snap point of a specified type.

Parameter	Description
Type	Specifies the type of object snap point

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoints.Parent

Property **Parent** As Shape

Description

Member of SnapPoints

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoints.Range

Function **Range(***ParamArray References() As Variant***)** As SnapPointRange

Description

Member of SnapPoints

The **Range** method creates a list of snap point, as referenced by the given IDs.

Parameter	Description
ParamArray References	Specifies the IDs of the snap points

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoints.Selection

Property **Selection** As SnapPointRange

Description

Member of SnapPoints

The **Selection** property returns a read-only value consisting of a list of selected snap points.

Copyright 2014 Corel Corporation. All rights reserved.

SnapPoints.User

Function **User(***ID As String***)** As SnapPoint

Description

Member of SnapPoints

The **User** method finds a user-created snap point by its ID.

Parameter	Description
ID	Specifies the ID of the snap point

Copyright 2014 Corel Corporation. All rights reserved.

Spread

Properties Methods

Description

The **Spread** class represents the settings of a page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.ActiveLayer

Property **ActiveLayer** As Layer

Description

Member of Spread

The **ActiveLayer** property returns the active layer of the current page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.AllLayers

Property **AllLayers** As Layers

Description

Member of Spread

The **AllLayers** property returns a read-only value that is associated with all the layers of the current page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.BottomY

Property **BottomY** As Double

Description

Member of Spread

The **BottomY** property returns a read-only value that is associated with the y-coordinate of the bottom edge of a page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.BoundingBox

Property **BoundingBox** As Rect

Description

Member of Spread

The **BoundingBox** property returns a read-only value that is associated with the bounding box of a page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.CenterX

Property **CenterX** As Double

Description

Member of Spread

The **CenterX** property returns a read-only value that is associated with the x-coordinate of the center of a page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.CenterY

Property **CenterY** As Double

Description

Member of Spread

The **CenterY** property returns a read-only value that is associated with the y-coordinate of the center of a page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.CreateLayer

Function **CreateLayer(***LayerName As String***)** As Layer

Description

Member of Spread

The **CreateLayer** method creates a layer on a page spread.

Parameter	Description
LayerName	Specifies the name of the layer

Copyright 2014 Corel Corporation. All rights reserved.

Spread.DesktopLayer

Property **DesktopLayer** As Layer

Description

Member of Spread

The **DesktopLayer** property returns a read-only value that is associated with the desktop layer from a page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.GetBoundingBox

Sub **GetBoundingBox(***x As Double*, *y As Double*, *Width As Double*, *Height As Double***)**

Description

Member of Spread

The **GetBoundingBox** method returns the bounding box of a page spread.

Parameter	Description
x	Specifies the x-coordinate
y	Specifies the y-coordinate
Width	Specifies the width
Height	Specifies the height

Copyright 2014 Corel Corporation. All rights reserved.

Spread.GridLayer

Property GridLayer As Layer

Description

Member of Spread

The **GridLayer** property returns a read-only value that is associated with the grid layer from a page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.Guides

Property **Guides([**Type As cdrGuideType = cdrAllGuides**])** As ShapeRange

Description

Member of Spread

The **Guides** property returns a read-only value that is associated with all the guidelines from a page spread.

Parameter	Description
Type	Specifies, as cdrGuideType, the guideline type. This parameter is optional, and its default value is cdrAllGuides.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.GuidesLayer

Property **GuidesLayer** As Layer

Description

Member of Spread

The **GuidesLayer** property returns a read-only value that is associated with the guideline layer from a page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.Index

Property **Index** As Long

Description

Member of Spread

The **Index** property returns a read-only value that is associated with the index number of the current page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.Layers

Property **Layers** As Layers

Description

Member of Spread

The **Layers** property returns a read-only value that is associated with the non-master layers of the current page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.LeftX

Property **LeftX** As Double

Description

Member of Spread

The **LeftX** property returns a read-only value that is associated with the x-coordinate of the left edge of a page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.Next

Property **Next** As Spread

Description

Member of Spread

The **Next** property returns a read-only value that is associated with the next page spread in a document.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.Pages

Property **Pages** As Pages

Description

Member of Spread

The **Pages** property returns a read-only value that is associated with a collection of pages belonging to a given page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.Previous

Property **Previous** As Spread

Description

Member of Spread

The **Previous** property returns a read-only value that is associated with the previous page spread in a document.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.RightX

Property **RightX** As Double

Description

Member of Spread

The **RightX** property returns a read-only value that is associated with the x-coordinate of the right edge of a page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.SelectableShapes

Property **SelectableShapes** As Shapes

Description

Member of Spread

The **SelectableShapes** property returns a read-only value that is associated with the selectable shapes stored on a page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.Shapes

Property **Shapes** As Shapes

Description

Member of Spread

The **Shapes** property returns a read-only value that is associated with the shapes stored on a page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.SizeHeight

Property **SizeHeight** As Double

Description

Member of Spread

The **SizeHeight** property returns a read-only value that is associated with the height of the current page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.SizeWidth

Property **SizeWidth** As Double

Description

Member of Spread

The **SizeWidth** property returns a read-only value that is associated with the width of the current page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.TopY

Property **TopY** As Double

Description

Member of Spread

The **TopY** property returns a read-only value that is associated with the y-coordinate of the top edge of a page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spread.TreeNode

Property **TreeNode** As TreeNode

Description

Member of Spread

The **TreeNode** property returns a read-only value that is associated with the tree node representing a page spread.

Copyright 2014 Corel Corporation. All rights reserved.

Spreads

Properties

Description

The **Spreads** class represents a collection of page spreads (or Spread objects).

Copyright 2014 Corel Corporation. All rights reserved.

Spreads.Count

Property **Count** As Long

Description

Member of Spreads

The **Count** property returns a read-only value that is associated with the number of page spreads in a document.

Copyright 2014 Corel Corporation. All rights reserved.

Spreads.First

Property **First** As Spread

Description

Member of Spreads

The **First** property returns a read-only value that is associated with the first page spread in a document.

Copyright 2014 Corel Corporation. All rights reserved.

Spreads.Item

Property **Item(***Index As Long***)** As Spread

Description

Member of Spreads

The **Item** property returns a read-only value that is associated with a given page spread from a Spreads collection.

Item is the default property of the **Spreads** class.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each member of the **Spreads** collection

Copyright 2014 Corel Corporation. All rights reserved.

Spreads.Last

Property **Last** As Spread

Description

Member of Spreads

The **Last** property returns a read-only value that is associated with the last page spread in a document.

Copyright 2014 Corel Corporation. All rights reserved.

StructAlignProperties

Properties

Description

The **StructAlignProperties** class represents the alignment settings of a text object.

Copyright 2014 Corel Corporation. All rights reserved.

StructAlignProperties.Alignment

Property **Alignment** As cdrAlignment

Description

Member of StructAlignProperties

The **Alignment** property returns or specifies the alignment (that is, justification) of a text object.

The **Alignment** property returns a value of cdrAlignment.

VBA example

The following VBA example creates a text object in the center of the page.

```
Sub Test()
 Dim s As Shape
 Dim x As Double, y As Double
 x = ActivePage.SizeWidth / 2
 y = ActivePage.SizeHeight / 2
 Set s = ActiveLayer.CreateArtisticText(x, y, "A Text String" & vbCr & _
  "With Two Lines")
 s.Text.AlignProperties.Alignment = cdrCenterAlignment
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructAlignProperties.CharacterRotation

Property **CharacterRotation** As Single

Description

Member of StructAlignProperties

The **CharacterRotation** property returns or specifies the rotation angle for the characters in a text object. This property is measured in degrees and has a maximum value of **360**.

VBA example

The following VBA example creates a text object and rotates each character at a random angle.

```
Sub Test()
 Dim s As Shape, i As Long
 Dim sText As String
 sText = "Random Text"
 Set s = ActiveLayer.CreateArtisticText(0, 0, sText)
 For i = 1 To Len(sText)
  s.Text.AlignPropertiesInRange(i, 1).CharacterRotation = (Rnd() - 0.5) * 90
 Next i
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructAlignProperties.FirstLineIndent

Property **FirstLineIndent** As Double

Description

Member of StructAlignProperties

The **FirstLineIndent** property returns or specifies the indentation of the first line text in a paragraph. This value is measured in document units.

VBA example

The following VBA example indents the first line of the second paragraph of the selected paragraph by **1**". It also indents the left and right margins of the selected paragraph by **0.5**".

```
Sub Test()
 If ActiveShape Is Nothing Then Exit Sub
 If ActiveShape.Type = cdrTextShape Then
  If ActiveShape.Text.Type = cdrParagraphText Then
   With ActiveShape.Text.AlignPropertiesInRange(2, 1, cdrParagraphIndexing)
    .FirstLineIndent = 1
    .LeftIndent = 0.5
    .RightIndent = 0.5
   End With
  End If
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructAlignProperties.HorizontalCharacterShift

Property **HorizontalCharacterShift** As Long

Description

Member of StructAlignProperties

The **HorizontalCharacterShift** property returns or specifies the amount by which to horizontally shift the characters in a text object.

- The value of a horizontal character shift is measured as a percentage of the character's point size. For example, if **.HorizontalCharacterShift** equals **50**, the character is horizontally shifted a distance that is **50**% of the character's point size.

VBA example

The following VBA example specifies a horizontal character shift of **10**% for the second and third words of the text object.

```
Sub Test()
 ActiveShape.Text.AlignPropertiesInRange(2, 2, cdrWordIndexing).HorizontalCharacterShift = 10
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructAlignProperties.LeftIndent

Property **LeftIndent** As Double

Description

Member of StructAlignProperties

The **LeftIndent** property returns or specifies the indentation for the left side of a paragraph. This value is measured in document units.

VBA example

The following VBA example indents the first line of the second paragraph of the selected paragraph by **1**". It also indents the left and right margins of the selected paragraph by **0.5**".

```
Sub Test()
 If ActiveShape Is Nothing Then Exit Sub
 If ActiveShape.Type = cdrTextShape Then
  If ActiveShape.Text.Type = cdrParagraphText Then
   With ActiveShape.Text.AlignPropertiesInRange(2, 1, cdrParagraphIndexing)
    .FirstLineIndent = 1
    .LeftIndent = 0.5
    .RightIndent = 0.5
   End With
  End If
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructAlignProperties.MaxCharacterSpacing

Property **MaxCharacterSpacing** As Single

Description

Member of StructAlignProperties

The **MaxCharacterSpacing** property returns or specifies the maximum amount of space that can exist between characters. This value represents a percentage of the **Space** character (that is, the character inserted when you press the **Spacebar**). The maximum percentage value is **2000**, and the minimum percentage value is **-100**.

VBA example

The following VBA example specifies the adjustment range for character and word spacing in the selected text object.

```
Sub Test()
 With ActiveShape.Text.AlignProperties
  .MaxCharacterSpacing = 200
  .MinWordSpacing = 50
  .MaxWordSpacing = 150
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructAlignProperties.MaxWordSpacing

Property MaxWordSpacing As Single

Description

Member of StructAlignProperties

The **MaxWordSpacing** property returns or specifies the maximum amount of space that can exist between words. This value represents a percentage of the **Space** character (that is, the character inserted when you press the **Spacebar**). The maximum value is **2000**; the minimum value is **0**.

VBA example

The following VBA example specifies the adjustment range for character and word spacing in the selected text object.

```
Sub Test()
 With ActiveShape.Text.AlignProperties
  .MaxCharacterSpacing = 200
  .MinWordSpacing = 50
  .MaxWordSpacing = 150
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructAlignProperties.MinWordSpacing

Property **MinWordSpacing** As Single

Description

Member of StructAlignProperties

The **MinWordSpacing** property returns or specifies the minimum amount of space that can exist between words. This value represents a percentage of the **Space** character (that is, the character inserted when you press the **Spacebar**). The maximum value is **2000**; the minimum value is 0.

VBA example

The following VBA example specifies the adjustment range for character and word spacing in the selected text object.

```
Sub Test()
 With ActiveShape.Text.AlignProperties
  .MaxCharacterSpacing = 200
  .MinWordSpacing = 50
  .MaxWordSpacing = 150
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructAlignProperties.RightIndent

Property **RightIndent** As Double

Description

Member of StructAlignProperties

The **RightIndent** property returns or specifies the indentation for the left side of a paragraph. This value is measured in document units.

VBA example

The following VBA example indents the first line of the second paragraph of the selected paragraph by **1**". It also indents the left and right margins of the selected paragraph by **0.5**".

```
Sub Test()
 If ActiveShape Is Nothing Then Exit Sub
 If ActiveShape.Type = cdrTextShape Then
  If ActiveShape.Text.Type = cdrParagraphText Then
   With ActiveShape.Text.AlignPropertiesInRange(2, 1, cdrParagraphIndexing)
    .FirstLineIndent = 1
    .LeftIndent = 0.5
    .RightIndent = 0.5
   End With
  End If
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructAlignProperties.VerticalCharacterShift

Property **VerticalCharacterShift** As Long

Description

Member of StructAlignProperties

The **VerticalCharacterShift** property returns or specifies the amount by which to vertically shift the characters in a text object.

- The value of a vertical character shift is measured as a percentage of the character's point size. For example, if **.VerticalCharacterShift** equals **50**, the character is vertically shifted a distance that is **50**% of the character's point size.

VBA example

The following VBA example specifies a vertical character shift of **-10**% for the second and third words of the text object.

```
Sub Test()
 ActiveShape.Text.AlignPropertiesInRange(2, 2, cdrWordIndexing).VerticalCharacterShift = -10
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructColorConversionOptions

Properties

Description

The **StructColorConversionOptions** class represents color-conversion settings.

Copyright 2014 Corel Corporation. All rights reserved.

StructColorConversionOptions.ColorConversionHandler

Property **ColorConversionHandler** As IColorConversionHandler

Description

Member of StructColorConversionOptions

The **ColorConversionHandler** property specifies a custom call-back interface to be used when missing or mismatched profiles are encountered when opening, importing, or pasting a graphic.

Copyright 2014 Corel Corporation. All rights reserved.

StructColorConversionOptions.ColorPolicy

Property **ColorPolicy** As ColorManagementPolicy

Description

Member of StructColorConversionOptions

The **ColorPolicy** property specifies the default color-management policies to use when opening, importing, or pasting a graphic.

Copyright 2014 Corel Corporation. All rights reserved.

StructColorConversionOptions.SourceColorProfileList

Property **SourceColorProfileList** As String

Description

Member of StructColorConversionOptions

The **SourceColorProfileList** property rsecifies the list of profile names to be used as the source color context for converting the color information of objects being opened, imported, or pasted.

Copyright 2014 Corel Corporation. All rights reserved.

StructColorConversionOptions.TargetColorProfileList

Property **TargetColorProfileList** As String

Description

Member of StructColorConversionOptions

The **TargetColorProfileList** property specifies the list of profile names to which to convert document colors after opening, importing, or pasting objects. The color context of the whole document is changed.

Copyright 2014 Corel Corporation. All rights reserved.

StructCreateOptions

Properties

Description

The **StructCreateOptions** class represents document-creation settings.

Copyright 2014 Corel Corporation. All rights reserved.

StructCreateOptions.ColorContext

Property **ColorContext** As ColorContext

Description

Member of StructCreateOptions

The **ColorContext** property specifies the document color context for a new document.

Copyright 2014 Corel Corporation. All rights reserved.

StructCreateOptions.Name

Property **Name** As String

Description

Member of StructCreateOptions

The **Name** property specifies the name of a new document.

Copyright 2014 Corel Corporation. All rights reserved.

StructCreateOptions.PageHeight

Property **PageHeight** As Double

Description

Member of StructCreateOptions

The **PageHeight** property specifies the page height of a new document.

Copyright 2014 Corel Corporation. All rights reserved.

StructCreateOptions.PageWidth

Property **PageWidth** As Double

Description

Member of StructCreateOptions

The **PageWidth** property specifies the page width of a new document.

Copyright 2014 Corel Corporation. All rights reserved.

StructCreateOptions.Resolution

Property **Resolution** As Double

Description

Member of StructCreateOptions

The **Resolution** property specifies the rendering resolution of a new document.

Copyright 2014 Corel Corporation. All rights reserved.

StructCreateOptions.Units

Property **Units** As cdrUnit

Description

Member of StructCreateOptions

The **Units** property specifies both the unit of page-size measurement and the default unit of measurement for a new document.

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions

Properties

Description

The **StructExportOptions** class represents export settings. This class is used in conjunction with the Document.ExportEx method.

- You can create a **StructExportOptions** object by using the **New** keyword in Visual Basic.
- Most of the settings specified in this object are bitmap-related. You can use the Document.ExportBitmap method to specify these parameters as direct arguments of the function call.

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.AlwaysOverprintBlack

Property **AlwaysOverprintBlack** As Boolean

Description

Member of StructExportOptions

The **AlwaysOverprintBlack** property specifies whether black is always overprinted.

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.AntiAliasingType

Property **AntiAliasingType** As cdrAntiAliasingType

Description

Member of StructExportOptions

The **AntiAliasingType** property returns or specifies an anti-aliasing algorithm when exporting to bitmap-image formats.

This property returns a value of cdrAntiAliasingType**.**

VBA example

The following VBA example exports the current page as a GIF file without anti-aliasing.

```
Sub Test()
 Dim opt As New StructExportOptions
 Dim flt As ExportFilter
 opt.AntiAliasingType = cdrNoAntiAliasing
 Set flt = ActiveDocument.ExportEx("C:\Temp\img.gif", cdrGIF, cdrCurrentPage, opt)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.Compression

Property **Compression** As cdrCompressionType

Description

Member of StructExportOptions

The **Compression** property specifies a compression type when exporting to certain bitmap-image formats. These image formats include export filters that do not provide their own built-in interfaces,such as BMP and TIF. This property is not used with filters that do not support compression or that have a single compression method (such as GIF, PNG, JPG, and CPT).

- When using the FPX filter, the compression type must be specified through the filter's interface as returned by the Document.ExportEx or Document.ExportBitmap methods.

VBA example

The following VBA example exports the current page to a TIFF bitmap by using the CCITT4 compression method.

```
Sub Test()
 Dim opt As New StructExportOptions
 Dim flt As ExportFilter
 opt.ImageType = cdrBlackAndWhiteImage
 opt.Compression = cdrCompressionCCITT4
 Set flt = ActiveDocument.ExportEx("C:\Temp\img.tif", cdrTIFF, cdrCurrentPage, opt)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.Dithered

Property **Dithered** As Boolean

Description

Member of StructExportOptions

The **Dithered** property specifies whether a bitmap image is dithered upon export.

- This property applies only when exporting to black-and-white bitmaps. You can specify the dithering method for paletted bitmaps by using the StructPaletteOptions.DitherType property.

VBA example

The following VBA example exports the drawing as a black-and-white dithered BMP file.

```
Sub Test()
 Dim opt As New StructExportOptions
 Dim flt As ExportFilter
 opt.ImageType = cdrBlackAndWhiteImage
 opt.Compression = cdrCompressionPackBits
 opt.Dithered = True
 Set flt = ActiveDocument.ExportEx("C:\Temp\img.bmp", cdrBMP, cdrCurrentPage, opt)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.ExportArea

Property **ExportArea** As Rect

Description

Member of StructExportOptions

The **ExportArea** property specifies the drawing area to export.

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.ImageType

Property **ImageType** As cdrImageType

Description

Member of StructExportOptions

The **ImageType** property returns or specifies the color model for an exported image.

- You must use only the color models supported by the filter. Specifying an incorrect color model may result in export failure.

- When the Paletted color model is specified, you can use the Document.ExportEx or Document.ExportBitmap methods to specify palette- generation options through the **PaletteOptions** parameter, which returns a StructPaletteOptions object.

This property returns a value of cdrImageType.

VBA example

The following VBA example exports the shapes on the current page to a GIF file. The file is exported by using a 16-color optimized palette and the Stucki algorithm for dithering.

```
Sub Test()
 Dim opt As New StructExportOptions
 Dim pal As New StructPaletteOptions
 Dim flt As ExportFilter
 opt.ImageType = cdrPalettedImage
 pal.DitherType = cdrDitherStucki
 pal.DitherIntensity = 100
 pal.NumColors = 16
 pal.PaletteType = cdrPaletteOptimized
 Set flt = ActiveDocument.ExportEx("C:\Temp\img.gif", cdrGIF, cdrCurrentPage, opt, pal)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.MaintainAspect

Property **MaintainAspect** As Boolean

Description

Member of StructExportOptions

The **MaintainAspect** property returns or specifies whether to maintain the aspect ratio of a drawing upon export.

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.MaintainLayers

Property **MaintainLayers** As Boolean

Description

Member of StructExportOptions

The **MaintainLayers** property returns or specifies whether to maintain the layers of a drawing upon export.

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.MatteColor

Property **MatteColor** As Color

Description

Member of StructExportOptions

The **MatteColor** property uses a Color object to specify the matte color.

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.Matted

Property **Matted** As Boolean

Description

Member of StructExportOptions

The **Matted** property uses a Boolean value to specify whether the document uses a matte color.

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.MatteMaskedOnly

Property **MatteMaskedOnly** As Boolean

Description

Member of StructExportOptions

The **MatteMaskedOnly** property uses a Boolean value to specify whether only the masked areas in a document use a matte color.

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.Overwrite

Property **Overwrite** As Boolean

Description

Member of StructExportOptions

The **Overwrite** property returns or specifies whether an existing file with the specified name is overwritten. The default value of this property is **True**. If a file with the given name already exists and this property is set to **False**, the export operation fails.

VBA example

The following VBA example fails while exporting the active document if the file **img.gif** already exists in the folder **C:\Temp**.

```
Sub Test()
 Dim opt As New StructExportOptions
 Dim flt As ExportFilter
 opt.Overwrite = False
 Set flt = ActiveDocument.ExportEx("C:\Temp\img.gif", cdrGIF, cdrCurrentPage, opt)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.ProofColorSettings

Property **ProofColorSettings** As ProofColorSettings

Description

Member of StructExportOptions

The **ProofColorSettings** property specifies the color-proofing settings to be used on export.

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.ResolutionX

Property **ResolutionX** As Long

Description

Member of StructExportOptions

The **ResolutionX** property returns or specifies the horizontal resolution of an exported bitmap.

VBA example

The following VBA example exports the current selection to a CMYK TIFF image with **300** dpi resolution.

```
Sub Test()
 Dim opt As New StructExportOptions
 Dim flt As ExportFilter
 opt.ResolutionX = 300
 opt.ResolutionY = 300
 opt.ImageType = cdrCMYKColorImage
 opt.Compression = cdrCompressionLZW
 Set flt = ActiveDocument.ExportEx("C:\Temp\img.tif", cdrTIFF, cdrSelection, opt)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.ResolutionY

Property **ResolutionY** As Long

Description

Member of StructExportOptions

The **ResolutionY** property returns or specifies the vertical resolution of an exported bitmap.

VBA example

The following VBA example exports the current selection to a CMYK TIFF image with **300** dpi resolution.

```
Sub Test()
 Dim opt As New StructExportOptions
 Dim flt As ExportFilter
 opt.ResolutionX = 300
 opt.ResolutionY = 300
 opt.ImageType = cdrCMYKColorImage
 opt.Compression = cdrCompressionLZW
 Set flt = ActiveDocument.ExportEx("C:\Temp\img.tif", cdrTIFF, cdrSelection, opt)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.SizeX

Property **SizeX** As Long

Description

Member of StructExportOptions

The **SizeX** property returns or specifies the horizontal size of an exported bitmap. This property is measured in pixels.

- If neither **SizeX** nor **SizeY** is specified, the size of the bitmap is calculated based on the size of the objects being exported and the specified bitmap resolution.

VBA example

The following VBA example exports the current selection to a **100 × 100** pixel TIFF image.

```
Sub Test()
 Dim opt As New StructExportOptions
 Dim flt As ExportFilter
 opt.SizeX = 100
 opt.SizeY = 100
 opt.ImageType = cdrCMYKColorImage
 opt.Compression = cdrCompressionLZW
 Set flt = ActiveDocument.ExportEx("C:\Temp\img.tif", cdrTIFF, cdrSelection, opt)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.SizeY

Property **SizeY** As Long

Description

Member of StructExportOptions

The **SizeY** property returns or specifies the vertical size of an exported bitmap. This property is measured in pixels.

- If neither **SizeX** nor **SizeY** is specified, the size of the bitmap is calculated based on the size of the objects being exported and the specified bitmap resolution.

VBA example

The following VBA example exports the current selection to a **100 × 100** pixel TIFF image.

```
Sub Test()
 Dim opt As New StructExportOptions
 Dim flt As ExportFilter
 opt.SizeX = 100
 opt.SizeY = 100
 opt.ImageType = cdrCMYKColorImage
 opt.Compression = cdrCompressionLZW
 Set flt = ActiveDocument.ExportEx("C:\Temp\img.tif", cdrTIFF, cdrSelection, opt)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.Transparent

Property **Transparent** As Boolean

Description

Member of StructExportOptions

The **Transparent** property specifies whether a bitmap has no background — that is, has a transparent background — when exported.

- You can use this property only with formats that support transparency (such as CPT, PSD, and TIFF). This property cannot be used with any other filters, including GIF and PNG. (For the GIF or PNG filter, you can use the filter's interface to specify a transparent color.)

VBA example

The following VBA example exports the selected objects to the Corel PHOTO-PAINT (CPT) format without a background.

```
Sub Test()
 Dim opt As New StructExportOptions
 Dim flt As ExportFilter
 opt.ImageType = cdrRGBColorImage
 opt.Transparent = True
 Set flt = ActiveDocument.ExportEx("C:\Temp\img.cpt", cdrCPT10, cdrSelection, opt)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructExportOptions.UseColorProfile

Property **UseColorProfile** As Boolean

Description

Member of StructExportOptions

The **UseColorProfile** property specifies whether the current color profile is used when converting colors during export.

VBA example

The following VBA example exports the selection to an RGB-based BMP image, with colors corrected by using the current color profile.

```
Sub Test()
 Dim opt As New StructExportOptions
 Dim flt As ExportFilter
 opt.ImageType = cdrRGBColorImage
 opt.UseColorProfile = True
 Set flt = ActiveDocument.ExportEx("C:\Temp\img.bmp", cdrBMP, cdrSelection, opt)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructFontProperties

Properties

Description

The **StructFontProperties** class represents the font properties of a text object.

Copyright 2014 Corel Corporation. All rights reserved.

StructFontProperties.Fill

Property **Fill** As Fill

Description

Member of StructFontProperties

The **Fill** property returns or specifies the fill of individual characters in a text object.

Copyright 2014 Corel Corporation. All rights reserved.

StructFontProperties.Name

Property **Name** As String

Description

Member of StructFontProperties

The **Name** property returns or specifies the name of a font face.

VBA example

The following VBA example creates a centered text shape and applies **18**-point **Arial** font to it.

```
Sub Test()
 Dim s As Shape
 Dim x As Double, y As Double
 x = ActivePage.SizeWidth / 2
 y = ActivePage.SizeHeight / 2
 Set s = ActiveLayer.CreateArtisticText(x, y, "Some Text String" & vbCr & "With Two Lines")
 s.Text.AlignProperties.Alignment = cdrCenterAlignment
 With s.Text.FontProperties
  .Name = "Arial"
  .Size = 18
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructFontProperties.Outline

Property **Outline** As Outline

Description

Member of StructFontProperties

The **Outline** property returns or specifies the outline of individual characters in a text object.

Copyright 2014 Corel Corporation. All rights reserved.

StructFontProperties.Overscore

Property **Overscore** As cdrFontLine

Description

Member of StructFontProperties

The **Overscore** property returns or specifies the type of line to appear above the characters in a text object.

The **Overscore** property returns a value of cdrFontLine.

VBA example

The following VBA example creates a text object and applies double lines above and below it.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateArtisticText(4, 5, "A Text String")
 With s.Text.FontProperties
  .Underline = cdrDoubleThinFontLine
  .Overscore = cdrDoubleThinFontLine
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructFontProperties.Position

Property **Position** As cdrFontPosition

Description

Member of StructFontProperties

The **Position** property returns or specifies the position of the characters in a text object.

The **Position** property returns a value of cdrFontPosition.

VBA example

The following VBA example creates a text object with a subscript character.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateArtisticText(4, 5, "H2O")
 s.Text.FontPropertiesInRange(2, 1).Position = cdrSubscriptFontPosition
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructFontProperties.RangeKerning

Property **RangeKerning** As Long

Description

Member of StructFontProperties

The **RangeKerning** property returns or specifies the amount of white space between the characters in a text object.

- This value represents a percentage of the **Space** character (that is, the character inserted when you press the **Spacebar**). The maximum value is **1000**; the minimum value is **-100**.

VBA example

The following VBA example creates a text string and adjusts the kerning of the second word in it.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateArtisticText(4, 5, "Some loose text")
 s.Text.FontPropertiesInRange(2, 1, cdrWordIndexing).RangeKerning = 100
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructFontProperties.Size

Property **Size** As Single

Description

Member of StructFontProperties

The **Size** property returns or specifies the size of a font, in points.

VBA example

The following VBA example creates a centered text shape and applies **18**-point **Arial** font to it.

```
Sub Test()
 Dim s As Shape
 Dim x As Double, y As Double
 x = ActivePage.SizeWidth / 2
 y = ActivePage.SizeHeight / 2
 Set s = ActiveLayer.CreateArtisticText(x, y, "Some Text String" & vbCr & "With Two Lines")
 s.Text.AlignProperties.Alignment = cdrCenterAlignment
 With s.Text.FontProperties
  .Name = "Arial"
  .Size = 18
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructFontProperties.Strikethru

Property **Strikethru** As cdrFontLine

Description

Member of StructFontProperties

The **Strikethru** property returns or specifies the type of line that appears through the sharacters in a text object.

The **Strikethru** property returns a value of cdrFontLine.

VBA example

The following VBA example creates a text object and applies a thin double line through it.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateArtisticText(4, 5, "A Text String")
 s.Text.FontProperties.Strikethru = cdrDoubleThinFontLine
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructFontProperties.Style

Property **Style** As cdrFontStyle

Description

Member of StructFontProperties

The **Style** property returns or specifies the style of a font.

The **Style** property returns a value of cdrFontStyle.

VBA example

The following VBA example creates a text string and applies a bold, italic style to the first word.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateArtisticText(4, 5, "Highlight your ideas!")
 s.Text.FontPropertiesInRange(1, 1, cdrWordIndexing).Style = cdrBoldItalicFontStyle
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructFontProperties.Underline

Property **Underline** As cdrFontLine

Description

Member of StructFontProperties

The **Underline** property returns or specifies the type of line that appears under the characters in a text object.

The **Underline** property returns a value of cdrFontLine.

VBA example

The following VBA example creates a text object and applies double underline to it.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateArtisticText(4, 5, "Some Text String")
 s.Text.FontProperties.Underline = cdrDoubleThinFontLine
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructFontProperties.Uppercase

Property **Uppercase** As cdrFontCase

Description

Member of StructFontProperties

The **Uppercase** property returns or specifies the case of the characters in a text object.

The **Uppercase** property returns a value of cdrFontCase.

VBA example

The following VBA example creates a text object and applies “small caps” to it.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateArtisticText(4, 5, "Small Caps Text")
 s.Text.FontProperties.Uppercase = cdrSmallCapsFontCase
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructHyphenationSettings

Properties

Description

The **StructHyphenationSettings** class represents the hyphenation settings of a text object.

- You can create a **StructHyphenationSettings** object by using the **New** keyword in Visual Basic.

Copyright 2014 Corel Corporation. All rights reserved.

StructHyphenationSettings.BreakAllCapWords

Property **BreakAllCapWords** As Boolean

Description

Member of StructHyphenationSettings

The **BreakAllCapWords** property returns or specifies whether to allow automatic hyphenation for words containing only capital letters. Specifying **True** automatically hyphenates words containing only capital letters.

To return or set the **BreakAllCapWords** property, the StructHyphenationSettings.UseAutomaticHyphenation property must be set to **True**.

Copyright 2014 Corel Corporation. All rights reserved.

StructHyphenationSettings.BreakCapitalized

Property **BreakCapitalized** As Boolean

Description

Member of StructHyphenationSettings

The **BreakCapitalized** property returns or specifies whether to allow automatic hyphenation for capitalized words. Specifying **True** automatically hyphenates both words with an initial capital and words containing only capital letters.

- For the **BreakCapitalized** property to work, the StructHyphenationSettings.UseAutomaticHyphenation property must be set to **True**.

VBA example

The following VBA example disables the hyphenation of capitalized words for the whole text object.

```
Sub Test()
 ActiveShape.Text.HyphenationSettings.BreakCapitalized = False
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructHyphenationSettings.HotZone

Property **HotZone** As Double

Description

Member of StructHyphenationSettings

The **HotZone** property returns or specifies the distance between the last word in a line and the right margin before hyphenation occurs.

- For the **HotZone** property to work, the StructHyphenationSettings.UseAutomaticHyphenation property must be set to **True**.

VBA example

The following VBA example specifies a hyphenation hot-zone of **7 millimeters** for the selected text object.

```
Sub Test()
 ActiveDocument.Unit = cdrMillimeter
 ActiveShape.Text.HyphenationSettings.HotZone = 7
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructHyphenationSettings.MinCharactersAfter

Property **MinCharactersAfter** As Long

Description

Member of StructHyphenationSettings

The **MinCharactersAfter** property returns or specifies the minimum number of characters (including spaces) to appear in the hot-zone after a hyphen. For example, if **MinCharactersAfter** is set to **4**, the only words that receive hyphenation are the ones that would have at least four characters after the hyphen.

- For the **MinCharactersAfter** property to work, the StructHyphenationSettings.UseAutomaticHyphenation property must be set to **True**.

VBA example

The following VBA example enables automatic hyphenation for the selected text object, specifying a minimum of **2** characters to be left on a line or carried to the next line following a hyphen.

```
Sub Test()
 With ActiveShape.Text.HyphenationSettings
  .UseAutomaticHyphenation = True
  .MinCharactersBefore = 2
  .MinCharactersAfter = 2
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructHyphenationSettings.MinCharactersBefore

Property **MinCharactersBefore** As Long

Description

Member of StructHyphenationSettings

The **MinCharactersBefore** property returns or specifies the minimum number of characters (including spaces) that must appear in the hot-zone before a hyphen. For example, if **MinCharactersBefore** is set to **3**, the only words that receive hyphenation are the ones that would have at least three characters before the hyphen.

- For the **MinCharactersBefore** property to work, the StructHyphenationSettings.UseAutomaticHyphenation property must be set to **True**.

VBA example

The following VBA example enables automatic hyphenation for the selected text object, specifying a minimum of **2** characters to be left on a line or carried to the next line following a hyphen.

```
Sub Test()
 With ActiveShape.Text.HyphenationSettings
  .UseAutomaticHyphenation = True
  .MinCharactersBefore = 2
  .MinCharactersAfter = 2
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructHyphenationSettings.MinWordLength

Property **MinWordLength** As Long

Description

Member of StructHyphenationSettings

The **MinWordLength** property returns or specifies the minimum number of characters required for a word to receive automatic hyphenation.

- For the **MinWordLength** property to work, the StructHyphenationSettings.UseAutomaticHyphenation property must be set to **True**.

VBA example

The following VBA example enables automatic hyphenation for the selected text object, specifying a minimum word length of **6** characters for hyphenation.

```
Sub Test()
 With ActiveShape.Text.HyphenationSettings
  .UseAutomaticHyphenation = True
  .MinWordLength = 6
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructHyphenationSettings.UseAutomaticHyphenation

Property **UseAutomaticHyphenation** As Boolean

Description

Member of StructHyphenationSettings

The **UseAutomaticHyphenation** property returns or specifies whether to enable automatic hyphenation for a portion of text. Specifying **True** automatically hyphenates text.

VBA example

The following VBA example enables automatic hyphenation for the selected text object, specifying that a minimum of **2** characters are to be left on a line or carried to the next line following a hyphen.

```
Sub Test()
 With ActiveShape.Text.HyphenationSettings
  .UseAutomaticHyphenation = True
  .MinCharactersBefore = 2
  .MinCharactersAfter = 2
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportCropOptions

Properties

Description

TheStructImportCropOptions class represents crop settings on import.

Copyright 2014 Corel Corporation. All rights reserved.

StructImportCropOptions.CustomData

Property **CustomData** As Long

Description

Member of StructImportCropOptions

The **CustomData** property specifies customized crop options.

The **CustomData** property returns a read-only value.

VBA example

The following VBA example creates a new crop-options class. It then imports a JPEG file and crops it depending on the value for **CustomData**. Before the crop is applied, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cCrop**:

```
Option Explicit
Implements IImportCropHandler
Private Function IImportCropHandler_Crop(Options As IStructImportCropOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 s = s & "ImageHeight: " & Options.ImageHeight & vbCr
 s = s & "ImageWidth: " & Options.ImageWidth & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 7 then crop half of the original; otherwise, subtract 0.5 units from the height
and width.
 If Options.CustomData = 7 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
  Options.Top = Options.Top / 2
  Options.Left = Options.Left / 2
 Else
  Options.Height = Options.Height - 0.5
  Options.Width = Options.Width - 0.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testCrop()
 ' Declare a new crop class.
 Dim MyCrop As New cCrop
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to crop.
 io.Mode = cdrImportCrop
 ' Set the custom data.
 io.CustomData = 7
 ' Set the import options crop handler to the one created.
 Set io.CropHandler = MyCrop
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportCropOptions.DpiX

Property **DpiX** As Long

Description

Member of StructImportCropOptions

The **DpiX** property specifies the horizontal resolution of a crop on import.

The **DpiX** property returns a read-only value.

VBA example

The following VBA example creates a new crop-options class. It then imports a JPEG file and crops it depending on the value for StructImportCropOptions.CustomData. Before the crop is applied, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cCrop**:

```
Option Explicit
Implements IImportCropHandler
Private Function IImportCropHandler_Crop(Options As IStructImportCropOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 s = s & "ImageHeight: " & Options.ImageHeight & vbCr
 s = s & "ImageWidth: " & Options.ImageWidth & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 7 then crop half of the original; otherwise, subtract 0.5 units from the height
and width.
 If Options.CustomData = 7 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
  Options.Top = Options.Top / 2
  Options.Left = Options.Left / 2
 Else
  Options.Height = Options.Height - 0.5
  Options.Width = Options.Width - 0.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testCrop()
 ' Declare a new crop class.
 Dim MyCrop As New cCrop
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to crop.
 io.Mode = cdrImportCrop
 ' Set the custom data.
 io.CustomData = 7
 ' Set the import options crop handler to the one created.
 Set io.CropHandler = MyCrop
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportCropOptions.DpiY

Property **DpiY** As Long

Description

Member of StructImportCropOptions

The **DpiY** property specifies the vertical resolution of a crop on import.

The **DpiY** property returns a read-only value.

VBA example

The following VBA example creates a new crop-options class. It then imports a JPEG file and crops it depending on the value for StructImportCropOptions.CustomData. Before the crop is applied, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cCrop**:

```
Option Explicit
Implements IImportCropHandler
Private Function IImportCropHandler_Crop(Options As IStructImportCropOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 s = s & "ImageHeight: " & Options.ImageHeight & vbCr
 s = s & "ImageWidth: " & Options.ImageWidth & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 7 then crop half of the original; otherwise, subtract 0.5 units from the height
and width.
 If Options.CustomData = 7 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
  Options.Top = Options.Top / 2
  Options.Left = Options.Left / 2
 Else
  Options.Height = Options.Height - 0.5
  Options.Width = Options.Width - 0.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testCrop()
 ' Declare a new crop class.
 Dim MyCrop As New cCrop
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to crop.
 io.Mode = cdrImportCrop
 ' Set the custom data.
 io.CustomData = 7
 ' Set the import options crop handler to the one created.
 Set io.CropHandler = MyCrop
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportCropOptions.FileName

Property **FileName** As String

Description

Member of StructImportCropOptions

The **FileName** property specifies a filename when cropping on import.

The **FileName** property returns a read-only value.

VBA example

The following VBA example creates a new crop-options class. It then imports a JPEG file and crops it depending on the value for StructImportCropOptions.CustomData. Before the crop is applied, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cCrop**:

```
Option Explicit
Implements IImportCropHandler
Private Function IImportCropHandler_Crop(Options As IStructImportCropOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 s = s & "ImageHeight: " & Options.ImageHeight & vbCr
 s = s & "ImageWidth: " & Options.ImageWidth & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 7 then crop half of the original; otherwise, subtract 0.5 units from the height
and width.
 If Options.CustomData = 7 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
  Options.Top = Options.Top / 2
  Options.Left = Options.Left / 2
 Else
  Options.Height = Options.Height - 0.5
  Options.Width = Options.Width - 0.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testCrop()
 ' Declare a new crop class.
 Dim MyCrop As New cCrop
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to crop.
 io.Mode = cdrImportCrop
 ' Set the custom data.
 io.CustomData = 7
 ' Set the import options crop handler to the one created.
 Set io.CropHandler = MyCrop
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportCropOptions.FilterID

Property **FilterID** As Long

Description

Member of StructImportCropOptions

The **FilterID** property specifies the filter ID of a crop on import.

The **FilterID** property returns a read-only value.

VBA example

The following VBA example creates a new crop-options class. It then imports a JPEG file and crops it depending on the value for StructImportCropOptions.CustomData. Before the crop is applied, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cCrop**:

```
Option Explicit
Implements IImportCropHandler
Private Function IImportCropHandler_Crop(Options As IStructImportCropOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 s = s & "ImageHeight: " & Options.ImageHeight & vbCr
 s = s & "ImageWidth: " & Options.ImageWidth & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 7 then crop half of the original; otherwise, subtract 0.5 units from the height
and width.
 If Options.CustomData = 7 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
  Options.Top = Options.Top / 2
  Options.Left = Options.Left / 2
 Else
  Options.Height = Options.Height - 0.5
  Options.Width = Options.Width - 0.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testCrop()
 ' Declare a new crop class.
 Dim MyCrop As New cCrop
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to crop.
 io.Mode = cdrImportCrop
 ' Set the custom data.
 io.CustomData = 7
 ' Set the import options crop handler to the one created.
 Set io.CropHandler = MyCrop
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportCropOptions.Height

Property **Height** As Long

Description

Member of StructImportCropOptions

The **Height** property specifies the height of a crop on import.

VBA example

The following VBA example creates a new crop-options class. It then imports a JPEG file and crops it depending on the value for StructImportCropOptions.CustomData. Before the crop is applied, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cCrop**:

```
Option Explicit
Implements IImportCropHandler
Private Function IImportCropHandler_Crop(Options As IStructImportCropOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 s = s & "ImageHeight: " & Options.ImageHeight & vbCr
 s = s & "ImageWidth: " & Options.ImageWidth & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 7 then crop half of the original; otherwise, subtract 0.5 units from the height
and width.
 If Options.CustomData = 7 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
  Options.Top = Options.Top / 2
  Options.Left = Options.Left / 2
 Else
  Options.Height = Options.Height - 0.5
  Options.Width = Options.Width - 0.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testCrop()
 ' Declare a new crop class.
 Dim MyCrop As New cCrop
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to crop.
 io.Mode = cdrImportCrop
 ' Set the custom data.
 io.CustomData = 7
 ' Set the import options crop handler to the one created.
 Set io.CropHandler = MyCrop
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportCropOptions.ImageHeight

Property **ImageHeight** As Long

Description

Member of StructImportCropOptions

The **ImageHeight** property specifies the image height of a crop on import.

The **ImageHeight** property returns a read-only value.

VBA example

The following VBA example creates a new crop-options class. It then imports a JPEG file and crops it depending on the value for StructImportCropOptions.CustomData. Before the crop is applied, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cCrop**:

```
Option Explicit
Implements IImportCropHandler
Private Function IImportCropHandler_Crop(Options As IStructImportCropOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 s = s & "ImageHeight: " & Options.ImageHeight & vbCr
 s = s & "ImageWidth: " & Options.ImageWidth & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 7 then crop half of the original; otherwise, subtract 0.5 units from the height
and width.
 If Options.CustomData = 7 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
  Options.Top = Options.Top / 2
  Options.Left = Options.Left / 2
 Else
  Options.Height = Options.Height - 0.5
  Options.Width = Options.Width - 0.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testCrop()
 ' Declare a new crop class.
 Dim MyCrop As New cCrop
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to crop.
 io.Mode = cdrImportCrop
 ' Set the custom data.
 io.CustomData = 7
 ' Set the import options crop handler to the one created.
 Set io.CropHandler = MyCrop
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportCropOptions.ImageWidth

Property **ImageWidth** As Long

Description

Member of StructImportCropOptions

The **ImageWidth** property specifies the image width of a crop on import.

The **ImageWidth** property returns a read-only value.

VBA example

The following VBA example creates a new crop-options class. It then imports a JPEG file and crops it depending on the value for StructImportCropOptions.CustomData. Before the crop is applied, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cCrop**:

```
Option Explicit
Implements IImportCropHandler
Private Function IImportCropHandler_Crop(Options As IStructImportCropOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 s = s & "ImageHeight: " & Options.ImageHeight & vbCr
 s = s & "ImageWidth: " & Options.ImageWidth & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 7 then crop half of the original; otherwise, subtract 0.5 units from the height
and width.
 If Options.CustomData = 7 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
  Options.Top = Options.Top / 2
  Options.Left = Options.Left / 2
 Else
  Options.Height = Options.Height - 0.5
  Options.Width = Options.Width - 0.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testCrop()
 ' Declare a new crop class.
 Dim MyCrop As New cCrop
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to crop.
 io.Mode = cdrImportCrop
 ' Set the custom data.
 io.CustomData = 7
 ' Set the import options crop handler to the one created.
 Set io.CropHandler = MyCrop
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportCropOptions.Left

Property **Left** As Long

Description

Member of StructImportCropOptions

The **Left** property specifies the left value of a crop on import.

VBA example

The following VBA example creates a new crop-options class. It then imports a JPEG file and crops it depending on the value for StructImportCropOptions.CustomData. Before the crop is applied, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cCrop**:

```
Option Explicit
Implements IImportCropHandler
Private Function IImportCropHandler_Crop(Options As IStructImportCropOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 s = s & "ImageHeight: " & Options.ImageHeight & vbCr
 s = s & "ImageWidth: " & Options.ImageWidth & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 7 then crop half of the original; otherwise, subtract 0.5 units from the height
and width.
 If Options.CustomData = 7 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
  Options.Top = Options.Top / 2
  Options.Left = Options.Left / 2
 Else
  Options.Height = Options.Height - 0.5
  Options.Width = Options.Width - 0.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testCrop()
 ' Declare a new crop class.
 Dim MyCrop As New cCrop
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to crop.
 io.Mode = cdrImportCrop
 ' Set the custom data.
 io.CustomData = 7
 ' Set the import options crop handler to the one created.
 Set io.CropHandler = MyCrop
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportCropOptions.Top

Property **Top** As Long

Description

Member of StructImportCropOptions

The **Top** property specifies the top value of a crop on import.

VBA example

The following VBA example creates a new crop-options class. It then imports a JPEG file and crops it depending on the value for StructImportCropOptions.CustomData. Before the crop is applied, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cCrop**:

```
Option Explicit
Implements IImportCropHandler
Private Function IImportCropHandler_Crop(Options As IStructImportCropOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 s = s & "ImageHeight: " & Options.ImageHeight & vbCr
 s = s & "ImageWidth: " & Options.ImageWidth & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 7 then crop half of the original; otherwise, subtract 0.5 units from the height
and width.
 If Options.CustomData = 7 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
  Options.Top = Options.Top / 2
  Options.Left = Options.Left / 2
 Else
  Options.Height = Options.Height - 0.5
  Options.Width = Options.Width - 0.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testCrop()
 ' Declare a new crop class.
 Dim MyCrop As New cCrop
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to crop.
 io.Mode = cdrImportCrop
 ' Set the custom data.
 io.CustomData = 7
 ' Set the import options crop handler to the one created.
 Set io.CropHandler = MyCrop
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportCropOptions.Width

Property **Width** As Long

Description

Member of StructImportCropOptions

The **Width** property specifies the width of a crop on import.

VBA example

The following VBA example creates a new crop-options class. It then imports a JPEG file and crops it depending on the value for StructImportCropOptions.CustomData. Before the crop is applied, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cCrop**:

```
Option Explicit
Implements IImportCropHandler
Private Function IImportCropHandler_Crop(Options As IStructImportCropOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 s = s & "ImageHeight: " & Options.ImageHeight & vbCr
 s = s & "ImageWidth: " & Options.ImageWidth & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 7 then crop half of the original; otherwise, subtract 0.5 units from the height
and width.
 If Options.CustomData = 7 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
  Options.Top = Options.Top / 2
  Options.Left = Options.Left / 2
 Else
  Options.Height = Options.Height - 0.5
  Options.Width = Options.Width - 0.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testCrop()
 ' Declare a new crop class.
 Dim MyCrop As New cCrop
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to crop.
 io.Mode = cdrImportCrop
 ' Set the custom data.
 io.CustomData = 7
 ' Set the import options crop handler to the one created.
 Set io.CropHandler = MyCrop
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions

Properties

Description

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.CodePage

Property **CodePage** As Long

Description

Member of StructImportOptions

The **CodePage** property specifies a code page on import.

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.ColorConversionOptions

Property **ColorConversionOptions** As ColorConversionOptions

Description

Member of StructImportOptions

The **ColorConversionOptions** property specifies color-conversion settings for import.

The **ColorConversionOptions** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.CombineMultilayerBitmaps

Property **CombineMultilayerBitmaps** As Boolean

Description

Member of StructImportOptions

The **CombineMultilayerBitmaps** property specifies whether to combine multilayer bitmaps on import.

VBA example

The following VBA example sets import options for a StructImportOptions object and then imports a JPEG file by using those options.

```
Sub testImportOptions()
 ' Declare a new import options structure
 Dim io As New StructImportOptions
 With io
  .Mode = cdrImportFull
  .CombineMultilayerBitmaps = False
  .DetectWatermark = True
  .ExtractICCProfile = False
  .ICCFileName = "C:\Test.icc"
  .ImageIndex = 3
  .LinkBitmapExternally = False
  .MaintainLayers = True
  .UseOPILinks = False
 End With
 ' Import the jpeg file passing the import option structure
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.ConvertTablesToText

Property **ConvertTablesToText** As Boolean

Description

Member of StructImportOptions

The **ConvertTablesToText** property converts tables to text on import.

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.CropHandler

Property **CropHandler** As IImportCropHandler

Description

Member of StructImportOptions

VBA example

The following VBA example creates a new crop-options class. It then imports a JPEG file and crops it depending on the value for StructImportCropOptions.CustomData. Before the crop is applied, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cCrop**:

```
Option Explicit
Implements IImportCropHandler
Private Function IImportCropHandler_Crop(Options As IStructImportCropOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 s = s & "ImageHeight: " & Options.ImageHeight & vbCr
 s = s & "ImageWidth: " & Options.ImageWidth & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 7 then crop half of the original; otherwise, subtract 0.5 units from the height
and width.
 If Options.CustomData = 7 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
  Options.Top = Options.Top / 2
  Options.Left = Options.Left / 2
 Else
  Options.Height = Options.Height - 0.5
  Options.Width = Options.Width - 0.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testCrop()
 ' Declare a new crop class.
 Dim MyCrop As New cCrop
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to crop.
 io.Mode = cdrImportCrop
 ' Set the custom data.
 io.CustomData = 7
 ' Set the import options crop handler to the one created.
 Set io.CropHandler = MyCrop
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.CropHeight

Property **CropHeight** As Long

Description

Member of StructImportOptions

The **CropHeight** property specifies a crop height on import.

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.CropLeft

Property **CropLeft** As Long

Description

Member of StructImportOptions

The **CropHeight** property specifies a left crop value on import.

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.CropTop

Property **CropTop** As Long

Description

Member of StructImportOptions

The **CropHeight** property specifies a top crop value on import.

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.CropWidth

Property **CropWidth** As Long

Description

Member of StructImportOptions

The **CropHeight** property specifies a crop width on import.

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.CustomData

Property **CustomData** As Long

Description

Member of StructImportOptions

The **CustomData** property specifies a customized set of import settings.

VBA example

The following VBA example creates a new resample-options class. It then imports a JPEG file and resamples it depending on the value for StructImportResampleOptions.CustomData. Before it applies the resampling, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cResample**:

```
Option Explicit
Implements IImportResampleHandler
Private Function IImportResampleHandler_Resample(Options As IStructImportResampleOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 8, then resample half of the original; otherwise 1.5
 If Options.CustomData = 8 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
 Else
  Options.Height = Options.Height / 1.5
  Options.Width = Options.Width / 1.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testResample()
 ' Declare a new resample class.
 Dim MyResampler As New cResample
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to resample.
 io.Mode = cdrImportResample
 ' Set the custom data.
 io.CustomData = 8
 ' Set the import options resample handler to the one created.
 Set io.ResampleHandler = MyResampler
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.DetectWatermark

Property **DetectWatermark** As Boolean

Description

Member of StructImportOptions

The **DetectWatermark** property specifies whether to detect watermarks on import.

VBA example

The following VBA example sets import options for a StructImportOptions object and then imports a JPEG file by using those options.

```
Sub testImportOptions()
 ' Declare a new import options structure
 Dim io As New StructImportOptions
 With io
  .Mode = cdrImportFull
  .CombineMultilayerBitmaps = False
  .DetectWatermark = True
  .ExtractICCProfile = False
  .ICCFileName = "C:\Test.icc"
  .ImageIndex = 3
  .LinkBitmapExternally = False
  .MaintainLayers = True
  .UseOPILinks = False
 End With
 ' Import the jpeg file passing the import option structure
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.ExtractICCProfile

Property **ExtractICCProfile** As Boolean

Description

Member of StructImportOptions

The **ExtractICCProfile** property specifies whether to extract an International Color Consortium (ICC) profile on import.

VBA example

The following VBA example sets import options for a StructImportOptions object and then imports a JPEG file by using those options.

```
Sub testImportOptions()
 ' Declare a new import options structure
 Dim io As New StructImportOptions
 With io
  .Mode = cdrImportFull
  .CombineMultilayerBitmaps = False
  .DetectWatermark = True
  .ExtractICCProfile = False
  .ICCFileName = "C:\Test.icc"
  .ImageIndex = 3
  .LinkBitmapExternally = False
  .MaintainLayers = True
  .UseOPILinks = False
 End With
 ' Import the jpeg file passing the import option structure
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.ForceCMYKBlackText

Property **ForceCMYKBlackText** As Boolean

Description

Member of StructImportOptions

The **ForceCMYKBlackText** property specifies whether to render text as CMYK black on import.

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.ICCFileName

Property **ICCFileName** As String

Description

Member of StructImportOptions

The **ICCFileName** property specifies the filename of an International Color Consortium (ICC) profile on import.

VBA example

The following VBA example sets import options for a StructImportOptions object and then imports a JPEG file by using those options:

```
Sub testImportOptions()
 ' Declare a new import options structure
 Dim io As New StructImportOptions
 With io
  .Mode = cdrImportFull
  .CombineMultilayerBitmaps = False
  .DetectWatermark = True
  .ExtractICCProfile = False
  .ICCFileName = "C:\Test.icc"
  .ImageIndex = 3
  .LinkBitmapExternally = False
  .MaintainLayers = True
  .UseOPILinks = False
 End With
 ' Import the jpeg file passing the import option structure
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.ImageIndex

Property **ImageIndex** As Long

Description

Member of StructImportOptions

The **ImageIndex** property specifies the index number of an image on import.

VBA example

The following VBA example sets import options for a StructImportOptions object and then imports a JPEG file by using those options.

```
Sub testImportOptions()
 ' Declare a new import options structure
 Dim io As New StructImportOptions
 With io
  .Mode = cdrImportFull
  .CombineMultilayerBitmaps = False
  .DetectWatermark = True
  .ExtractICCProfile = False
  .ICCFileName = "C:\Test.icc"
  .ImageIndex = 3
  .LinkBitmapExternally = False
  .MaintainLayers = True
  .UseOPILinks = False
 End With
 ' Import the jpeg file passing the import option structure
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.LinkBitmapExternally

Property **LinkBitmapExternally** As Boolean

Description

Member of StructImportOptions

The **LinkBitmapExternally** property specifies whether to link bitmaps externally on import.

VBA example

The following VBA example sets import options for a StructImportOptions object and then imports a JPEG file by using those options.

```
Sub testImportOptions()
 ' Declare a new import options structure
 Dim io As New StructImportOptions
 With io
  .Mode = cdrImportFull
  .CombineMultilayerBitmaps = False
  .DetectWatermark = True
  .ExtractICCProfile = False
  .ICCFileName = "C:\Test.icc"
  .ImageIndex = 3
  .LinkBitmapExternally = False
  .MaintainLayers = True
  .UseOPILinks = False
 End With
 ' Import the jpeg file passing the import option structure
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.MaintainLayers

Property **MaintainLayers** As Boolean

Description

Member of StructImportOptions

The **MaintainLayers** property specifies whether to maintain layers on import.

VBA example

The following VBA example sets import options for a StructImportOptions object and then imports a JPEG file by using those options.

```
Sub testImportOptions()
 ' Declare a new import options structure
 Dim io As New StructImportOptions
 With io
  .Mode = cdrImportFull
  .CombineMultilayerBitmaps = False
  .DetectWatermark = True
  .ExtractICCProfile = False
  .ICCFileName = "C:\Test.icc"
  .ImageIndex = 3
  .LinkBitmapExternally = False
  .MaintainLayers = True
  .UseOPILinks = False
 End With
 ' Import the jpeg file passing the import option structure
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.Mode

Property **Mode** As cdrImportMode

Description

Member of StructImportOptions

The **Mode** property specifies an import mode.

VBA example

The following VBA example sets import options for a StructImportOptions object and then imports a JPEG file by using those options.

```
Sub testImportOptions()
 ' Declare a new import options structure
 Dim io As New StructImportOptions
 With io
  .Mode = cdrImportFull
  .CombineMultilayerBitmaps = False
  .DetectWatermark = True
  .ExtractICCProfile = False
  .ICCFileName = "C:\Test.icc"
  .ImageIndex = 3
  .LinkBitmapExternally = False
  .MaintainLayers = True
  .UseOPILinks = False
 End With
 ' Import the jpeg file passing the import option structure
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.ResampleDpiX

Property **ResampleDpiX** As Long

Description

Member of StructImportOptions

The **ResampleDpiX** property specifies the horizontal resolution for resampling on import.

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.ResampleDpiY

Property **ResampleDpiY** As Long

Description

Member of StructImportOptions

The **ResampleDpiX** property specifies the vertical resolution for resampling on import.

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.ResampleHandler

Property **ResampleHandler** As IImportResampleHandler

Description

Member of StructImportOptions

The **ResampleHandler** property specifies a handler for resampling on import.

VBA example

The following VBA example creates a new resample-options class. It then imports a JPEG file and resamples it depending on the value for StructImportResampleOptions.CustomData. Before it applies the resampling, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cResample**:

```
Option Explicit
Implements IImportResampleHandler
Private Function IImportResampleHandler_Resample(Options As IStructImportResampleOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 8, then resample half of the original; otherwise 1.5
 If Options.CustomData = 8 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
 Else
  Options.Height = Options.Height / 1.5
  Options.Width = Options.Width / 1.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testResample()
 ' Declare a new resample class.
 Dim MyResampler As New cResample
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to resample.
 io.Mode = cdrImportResample
 ' Set the custom data.
 io.CustomData = 8
 ' Set the import options resample handler to the one created.
 Set io.ResampleHandler = MyResampler
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.ResampleHeight

Property **ResampleHeight** As Long

Description

Member of StructImportOptions

The **ResampleHeight** property specifies the resampling height on import.

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.ResampleWidth

Property **ResampleWidth** As Long

Description

Member of StructImportOptions

The **ResampleWidth** property specifies the resampling width on import.

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.TableColumnDelimiter

Property **TableColumnDelimiter** As String

Description

Member of StructImportOptions

The **TableColumnDelimiter** property specifies a table-column delimiter on import.

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.TextFormatting

Property **TextFormatting** As cdrImportTextFormatting

Description

Member of StructImportOptions

The **TableColumnDelimiter** property specifies text formatting on import.

Copyright 2014 Corel Corporation. All rights reserved.

StructImportOptions.UseOPILinks

Property **UseOPILinks** As Boolean

Description

Member of StructImportOptions

The **UseOPILinks** property specifies whether to use Open Prepress Interface (OPI) links on import.

VBA example

The following VBA example sets import options for a StructImportOptions object and then imports a JPEG file by using those options.

```
Sub testImportOptions()
 ' Declare a new import options structure
 Dim io As New StructImportOptions
 With io
  .Mode = cdrImportFull
  .CombineMultilayerBitmaps = False
  .DetectWatermark = True
  .ExtractICCProfile = False
  .ICCFileName = "C:\Test.icc"
  .ImageIndex = 3
  .LinkBitmapExternally = False
  .MaintainLayers = True
  .UseOPILinks = False
 End With
 ' Import the jpeg file passing the import option structure
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportResampleOptions

Properties

Description

The **StructImportResampleOptions** class represents resampling options on import.

Copyright 2014 Corel Corporation. All rights reserved.

StructImportResampleOptions.CustomData

Property **CustomData** As Long

Description

Member of StructImportResampleOptions

The **CustomData** property specifies a customized set of resampling options.

The **CustomData** property returns a read-only value.

VBA example

The following VBA example creates a new resample-options class. It then imports a JPEG file and resamples it depending on the value for **CustomData**. Before it applies the resampling, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cResample**:

```
Option Explicit
Implements IImportResampleHandler
Private Function IImportResampleHandler_Resample(Options As IStructImportResampleOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 8, then resample half of the original; otherwise 1.5
 If Options.CustomData = 8 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
 Else
  Options.Height = Options.Height / 1.5
  Options.Width = Options.Width / 1.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testResample()
 ' Declare a new resample class.
 Dim MyResampler As New cResample
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to resample.
 io.Mode = cdrImportResample
 ' Set the custom data.
 io.CustomData = 8
 ' Set the import options resample handler to the one created.
 Set io.ResampleHandler = MyResampler
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportResampleOptions.DpiX

Property **DpiX** As Long

Description

Member of StructImportResampleOptions

The **DpiX** property specifies a horizontal resolution for resampling on import.

VBA example

The following VBA example creates a new resample-options class. It then imports a JPEG file and resamples it depending on the value for StructImportResampleOptions.CustomData. Before it applies the resampling, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cResample**:

```
Option Explicit
Implements IImportResampleHandler
Private Function IImportResampleHandler_Resample(Options As IStructImportResampleOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 8, then resample half of the original; otherwise 1.5
 If Options.CustomData = 8 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
 Else
  Options.Height = Options.Height / 1.5
  Options.Width = Options.Width / 1.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testResample()
 ' Declare a new resample class.
 Dim MyResampler As New cResample
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to resample.
 io.Mode = cdrImportResample
 ' Set the custom data.
 io.CustomData = 8
 ' Set the import options resample handler to the one created.
 Set io.ResampleHandler = MyResampler
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportResampleOptions.DpiY

Property **DpiY** As Long

Description

Member of StructImportResampleOptions

The **DpiY** property specifies a vertical resolution for resampling on import.

VBA example

The following VBA example creates a new resample-options class. It then imports a JPEG file and resamples it depending on the value for StructImportResampleOptions.CustomData. Before it applies the resampling, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cResample**:

```
Option Explicit
Implements IImportResampleHandler
Private Function IImportResampleHandler_Resample(Options As IStructImportResampleOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 8, then resample half of the original; otherwise 1.5
 If Options.CustomData = 8 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
 Else
  Options.Height = Options.Height / 1.5
  Options.Width = Options.Width / 1.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testResample()
 ' Declare a new resample class.
 Dim MyResampler As New cResample
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to resample.
 io.Mode = cdrImportResample
 ' Set the custom data.
 io.CustomData = 8
 ' Set the import options resample handler to the one created.
 Set io.ResampleHandler = MyResampler
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportResampleOptions.FileName

Property **FileName** As String

Description

Member of StructImportResampleOptions

The **FileName** property specifies a filename when resampling on import.

The **FileName** property returns a read-only value.

VBA example

The following VBA example creates a new resample-options class. It then imports a JPEG file and resamples it depending on the value for StructImportResampleOptions.CustomData. Before it applies the resampling, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cResample**:

```
Option Explicit
Implements IImportResampleHandler
Private Function IImportResampleHandler_Resample(Options As IStructImportResampleOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 8, then resample half of the original; otherwise 1.5
 If Options.CustomData = 8 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
 Else
  Options.Height = Options.Height / 1.5
  Options.Width = Options.Width / 1.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testResample()
 ' Declare a new resample class.
 Dim MyResampler As New cResample
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to resample.
 io.Mode = cdrImportResample
 ' Set the custom data.
 io.CustomData = 8
 ' Set the import options resample handler to the one created.
 Set io.ResampleHandler = MyResampler
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportResampleOptions.FilterID

Property **FilterID** As Long

Description

Member of StructImportResampleOptions

The **FilterID** property specifies a filter ID for resampling on import.

The **FilterID** property returns a read-only value.

VBA example

The following VBA example creates a new resample-options class. It then imports a JPEG file and resamples it depending on the value for StructImportResampleOptions.CustomData. Before it applies the resampling, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cResample**:

```
Option Explicit
Implements IImportResampleHandler
Private Function IImportResampleHandler_Resample(Options As IStructImportResampleOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 8, then resample half of the original; otherwise 1.5
 If Options.CustomData = 8 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
 Else
  Options.Height = Options.Height / 1.5
  Options.Width = Options.Width / 1.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testResample()
 ' Declare a new resample class.
 Dim MyResampler As New cResample
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to resample.
 io.Mode = cdrImportResample
 ' Set the custom data.
 io.CustomData = 8
 ' Set the import options resample handler to the one created.
 Set io.ResampleHandler = MyResampler
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportResampleOptions.Height

Property **Height** As Long

Description

Member of StructImportResampleOptions

The **Height** property specifies the resampling height on import.

VBA example

The following VBA example creates a new resample-options class. It then imports a JPEG file and resamples it depending on the value for StructImportResampleOptions.CustomData. Before it applies the resampling, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cResample**:

```
Option Explicit
Implements IImportResampleHandler
Private Function IImportResampleHandler_Resample(Options As IStructImportResampleOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 8, then resample half of the original; otherwise 1.5
 If Options.CustomData = 8 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
 Else
  Options.Height = Options.Height / 1.5
  Options.Width = Options.Width / 1.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testResample()
 ' Declare a new resample class.
 Dim MyResampler As New cResample
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to resample.
 io.Mode = cdrImportResample
 ' Set the custom data.
 io.CustomData = 8
 ' Set the import options resample handler to the one created.
 Set io.ResampleHandler = MyResampler
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructImportResampleOptions.Width

Property **Width** As Long

Description

Member of StructImportResampleOptions

The **Width** property specifies the resampling width on import.

VBA example

The following VBA example creates a new resample-options class. It then imports a JPEG file and resamples it depending on the value for StructImportResampleOptions.CustomData. Before it applies the resampling, the original settings of the image are displayed.

To try out this code example, copy the following lines of code into a new class module named **cResample**:

```
Option Explicit
Implements IImportResampleHandler
Private Function IImportResampleHandler_Resample(Options As IStructImportResampleOptions) As Boolean
 Dim s As String
 s = "Original Settings: " & vbCr
 s = s & "DpiX: " & Options.DpiX & vbCr
 s = s & "DpiY: " & Options.DpiY & vbCr
 s = s & "FileName: " & Options.FileName & vbCr
 s = s & "Filter: " & Options.FilterID & vbCr
 ' Display the original settings in a message box
 MsgBox s
 ' If the custom data is set to 8, then resample half of the original; otherwise 1.5
 If Options.CustomData = 8 Then
  Options.Height = Options.Height / 2
  Options.Width = Options.Width / 2
 Else
  Options.Height = Options.Height / 1.5
  Options.Width = Options.Width / 1.5
 End If
End Function
```

Next, copy the following subroutine into a regular module or **ThisDocument**:

```
Sub testResample()
 ' Declare a new resample class.
 Dim MyResampler As New cResample
 ' Declare a new import options structure.
 Dim io As New StructImportOptions
 ' Change the mode to resample.
 io.Mode = cdrImportResample
 ' Set the custom data.
 io.CustomData = 8
 ' Set the import options resample handler to the one created.
 Set io.ResampleHandler = MyResampler
 ' Import the jpeg file passing the import option structure.
 ActiveLayer.Import "C:\Test.jpg", , io
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructOpenOptions

Properties

Description

The **StructOpenOptions** class represents the settings for opening an existing document.

Copyright 2014 Corel Corporation. All rights reserved.

StructOpenOptions.CodePage

Property **CodePage** As Long

Description

Member of StructOpenOptions

The **CodePage** property specifies the code page to use when opening documents that were created in earlier versions of the application.

Copyright 2014 Corel Corporation. All rights reserved.

StructOpenOptions.ColorConversionOptions

Property **ColorConversionOptions** As StructColorConversionOptions

Description

Member of StructOpenOptions

The **ColorConversionOptions** property specifies color-conversion options for opening documents.

The **ColorConversionOptions** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

StructPaletteOptions

Properties

Description

The **StructPaletteOptions** class represents the set of export options used when converting a full-color image into a paletted bitmap. This class is used in conjunction with the Document.ExportEx and Document.ExportBitmap methods.

- You can create a new **StructPaletteOptions** object by using the **New** keyword in Visual Basic.

Copyright 2014 Corel Corporation. All rights reserved.

StructPaletteOptions.ColorSensitive

Property **ColorSensitive** As Boolean

Description

Member of StructPaletteOptions

The **ColorSensitive** property specifies whether color sensitivity is considered when building a palette.

VBA example

The following VBA example exports the current page to a GIF image and ensures that the color blue is in the resulting palette:

```
Sub Test()
 Dim pal As New StructPaletteOptions
 Dim flt As ExportFilter
 pal.NumColors = 10
 pal.PaletteType = cdrPaletteOptimized
 pal.ColorSensitive = True
 pal.TargetColor = RGB(0, 0, 255)
 pal.Importance = 200
 pal.Lightness = 300
 pal.ToleranceA = 100
 pal.ToleranceB = 100
 Set flt = ActiveDocument.ExportBitmap("C:\Temp\img.gif", cdrGIF, , cdrPalettedImage, PaletteOptions:=pal)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructPaletteOptions.DitherIntensity

Property **DitherIntensity** As Long

Description

Member of StructPaletteOptions

The **DitherIntensity** property specifies the dithering intensity when converting a bitmap to a paletted mode.

VBA example

The following VBA example exports the image using Floyd dithering:

```
Sub Test()
 Dim pal As New StructPaletteOptions
 Dim flt As ExportFilter
 pal.NumColors = 10
 pal.PaletteType = cdrPaletteOptimized
 pal.DitherType = cdrDitherFloyd
 pal.DitherIntensity = 100
 Set flt = ActiveDocument.ExportBitmap("C:\Temp\img.gif", cdrGIF, , cdrPalettedImage, PaletteOptions:=pal)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructPaletteOptions.DitherType

Property **DitherType** As cdrDitherType

Description

Member of StructPaletteOptions

The **DitherType** property specifies the type of dithering algorithm when converting a bitmap to a paletted mode.

VBA example

The following VBA example exports the image using Floyd dithering:

```
Sub Test()
 Dim pal As New StructPaletteOptions
 Dim flt As ExportFilter
 pal.NumColors = 10
 pal.PaletteType = cdrPaletteOptimized
 pal.DitherType = cdrDitherFloyd
 pal.DitherIntensity = 100
 Set flt = ActiveDocument.ExportBitmap("C:\Temp\img.gif", cdrGIF, , cdrPalettedImage, PaletteOptions:=pal)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructPaletteOptions.Importance

Property **Importance** As Long

Description

Member of StructPaletteOptions

The **Importance** property specifies the target-color importance when generating a palette.

VBA example

The following VBA example exports the current page to a GIF image and ensures that the color blue is in the resulting palette:

```
Sub Test()
 Dim pal As New StructPaletteOptions
 Dim flt As ExportFilter
 pal.NumColors = 10
 pal.PaletteType = cdrPaletteOptimized
 pal.ColorSensitive = True
 pal.TargetColor = RGB(0, 0, 255)
 pal.Importance = 200
 pal.Lightness = 300
 pal.ToleranceA = 100
 pal.ToleranceB = 100
 Set flt = ActiveDocument.ExportBitmap("C:\Temp\img.gif", cdrGIF, , cdrPalettedImage, PaletteOptions:=pal)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructPaletteOptions.Lightness

Property **Lightness** As Long

Description

Member of StructPaletteOptions

The **Lightness** property specifies sensitivity for lightness when generating a palette.

VBA example

The following VBA example exports the current page to a GIF image and ensures that the color blue is in the resulting palette:

```
Sub Test()
 Dim pal As New StructPaletteOptions
 Dim flt As ExportFilter
 pal.NumColors = 10
 pal.PaletteType = cdrPaletteOptimized
 pal.ColorSensitive = True
 pal.TargetColor = RGB(0, 0, 255)
 pal.Importance = 200
 pal.Lightness = 300
 pal.ToleranceA = 100
 pal.ToleranceB = 100
 Set flt = ActiveDocument.ExportBitmap("C:\Temp\img.gif", cdrGIF, , cdrPalettedImage, PaletteOptions:=pal)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructPaletteOptions.NumColors

Property **NumColors** As Long

Description

Member of StructPaletteOptions

The **NumColors** property specifies the maximum number of colors that can be added to the image palette. (The actual number of colors may be less than the specified number.)

VBA example

The following VBA example exports the image using a 16-color optimized palette:

```
Sub Test()
 Dim pal As New StructPaletteOptions
 Dim flt As ExportFilter
 pal.NumColors = 16
 pal.PaletteType = cdrPaletteOptimized
 Set flt = ActiveDocument.ExportBitmap("C:\Temp\img.gif", cdrGIF, , cdrPalettedImage, PaletteOptions:=pal)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructPaletteOptions.Palette

Property **Palette** As Variant

Description

Member of StructPaletteOptions

The **Palette** property specifies the palette when exporting a full-color image to a paletted bitmap.

VBA example 1

The following VBA example exports a document with the new custom color palette:

```
Sub Test()
 Dim d As Document
 Dim e As ExportFilter
 Dim s As Shape
 Dim sp As New StructPaletteOptions
 Dim p As Palette
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateRectangle(3, 3, 7, 7)
 s.Fill.ApplyFountainFill CreateRGBColor(255, 0, 0), CreateRGBColor(0, 0, 255)
 ' Change the palette type to custom.
 sp.PaletteType = cdrPaletteCustom
 ' Create a new palette and add some colors.
 Set p = Palettes.Create("Temp")
 p.AddColor CreateRGBColor(255, 0, 0)
 p.AddColor CreateRGBColor(0, 0, 255)
 p.AddColor CreateRGBColor(0, 255, 0)
 ' Set the palette to use for the export to the newly created palette.
 sp.Palette = p
 d.Export "C:\Test_ExportPalette_Passing_a_Palette.gif", cdrGIF, , , sp
End Sub
```

VBA example 2

The following VBA example exports a document with a custom palette that is identified by its path and filename:

```
Sub Test()
 Dim d As Document
 Dim e As ExportFilter
 Dim s As Shape
 Dim sp As New StructPaletteOptions
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateRectangle(3, 3, 7, 7)
 s.Fill.ApplyFountainFill CreateRGBColor(255, 0, 0), CreateRGBColor(0, 0, 255)
 ' Change the palette type to custom.
 sp.PaletteType = cdrPaletteCustom
 ' Set the palette to use for the export to the filename of the existing palette.
 sp.Palette = SetupPath & "Custom Data\Palettes\CMYK\Nature\cEarthy.xml"
 d.Export "C:\Test_ExportPalette_Passing_a_Filename.gif", cdrGIF, , , sp
End Sub
```

VBA example 3

The following VBA example exports a document with a custom palette that is defined by an array of long values (which represent colors):

```
Sub Test()
 Dim d As Document
 Dim e As ExportFilter
 Dim s As Shape
 Dim sp As New StructPaletteOptions
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateRectangle(3, 3, 7, 7)
 s.Fill.ApplyFountainFill CreateRGBColor(255, 0, 0), CreateRGBColor(0, 0, 255)
 ' Change the palette type to custom.
 sp.PaletteType = cdrPaletteCustom
 ' Set the palette to use for the export to an array of longs which represent the colors to use.
 sp.Palette = Array(RGB(255, 0, 0), RGB(0, 0, 255), RGB(125, 0, 0), RGB(0, 0, 125), RGB(155, 0, 0), RGB(0, 0,
155), RGB(175, 32, 175))
 d.Export "C:\Test_ExportPalette_Passing_an_array_of_longs.gif", cdrGIF, , , sp
End Sub
```

VBA example 4

The following VBA example exports a document with a custom palette that is defined by an array of colors:

```
Sub Test()
 Dim d As Document
 Dim e As ExportFilter
 Dim s As Shape
 Dim sp As New StructPaletteOptions
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateRectangle(3, 3, 7, 7)
 s.Fill.ApplyFountainFill CreateRGBColor(255, 0, 0), CreateRGBColor(0, 0, 255)
 ' Change the palette type to custom
 sp.PaletteType = cdrPaletteCustom
 ' Set the palette to use for the export to an array of colors
 sp.Palette = Array(CreateCMYKColor(0, 77, 23, 23), CreateCMYKColor(10, 23, 43, 54), CreateCMYKColor(54, 12, 88,
12))
 d.Export "C:\Test_ExportPalette_Passing_an_array_of_colors.gif", cdrGIF, , , sp
```

```
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructPaletteOptions.PaletteType

Property **PaletteType** As cdrImagePaletteType

Description

Member of StructPaletteOptions

The **PaletteType** property specifies the type of palette to use.

You can specify one of the predefined palettes (**Windows**, **Internet Explorer**, **Netscape**, **Black Body**, or **VGA**), or you can generate a new optimized, uniform, or adaptive palette.

VBA example

The following VBA example exports the drawing using the **Netscape** Web-safe palette:

```
Sub Test()
 Dim pal As New StructPaletteOptions
 Dim flt As ExportFilter
 pal.PaletteType = cdrPaletteNetscape
 Set flt = ActiveDocument.ExportBitmap("C:\Temp\img.gif", cdrGIF, , cdrPalettedImage, PaletteOptions:=pal)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructPaletteOptions.Smoothing

Property **Smoothing** As Long

Description

Member of StructPaletteOptions

The **Smoothing** property specifies the amount of smoothing of color transitions to minimize abrupt color changes.

VBA example

The following VBA example exports the drawing to a GIF file using a 32-color optimized palette, and it applies a smoothing of 50% to the image:

```
Sub Test()
 Dim pal As New StructPaletteOptions
 Dim flt As ExportFilter
 pal.NumColors = 32
 pal.PaletteType = cdrPaletteOptimized
 pal.Smoothing = 50
 Set flt = ActiveDocument.ExportBitmap("C:\Temp\img.gif", cdrGIF, , cdrPalettedImage, PaletteOptions:=pal)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructPaletteOptions.TargetColor

Property **TargetColor** As Long

Description

Member of StructPaletteOptions

The **TargetColor** property is a value that represents an RGB color to be used as a color target when generating a palette. You can use the **RGB** function in Visual Basic to build the color value.

VBA example

The following VBA example exports the current page to a GIF image and ensures that the color blue is in the resulting palette:

```
Sub Test()
 Dim pal As New StructPaletteOptions
 Dim flt As ExportFilter
 pal.NumColors = 10
 pal.PaletteType = cdrPaletteOptimized
 pal.ColorSensitive = True
 pal.TargetColor = RGB(0, 0, 255)
 pal.Importance = 200
 pal.Lightness = 300
 pal.ToleranceA = 100
 pal.ToleranceB = 100
 Set flt = ActiveDocument.ExportBitmap("C:\Temp\img.gif", cdrGIF, , cdrPalettedImage, PaletteOptions:=pal)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructPaletteOptions.ToleranceA

Property **ToleranceA** As Long

Description

Member of StructPaletteOptions

The **ToleranceA** property specifies the sensitivity for the A color component when generating a palette.

VBA example

The following VBA example exports the current page to a GIF image and ensures that the color blue is in the resulting palette:

```
Sub Test()
 Dim pal As New StructPaletteOptions
 Dim flt As ExportFilter
 pal.NumColors = 10
 pal.PaletteType = cdrPaletteOptimized
 pal.ColorSensitive = True
 pal.TargetColor = RGB(0, 0, 255)
 pal.Importance = 200
 pal.Lightness = 300
 pal.ToleranceA = 100
 pal.ToleranceB = 100
 Set flt = ActiveDocument.ExportBitmap("C:\Temp\img.gif", cdrGIF, , cdrPalettedImage, PaletteOptions:=pal)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructPaletteOptions.ToleranceB

Property **ToleranceB** As Long

Description

Member of StructPaletteOptions

The **ToleranceB** property specifies the sensitivity for the B color component when generating a palette.

VBA example

The following VBA example exports the current page to a GIF image and ensures that the color blue is in the resulting palette:

```
Sub Test()
 Dim pal As New StructPaletteOptions
 Dim flt As ExportFilter
 pal.NumColors = 10
 pal.PaletteType = cdrPaletteOptimized
 pal.ColorSensitive = True
 pal.TargetColor = RGB(0, 0, 255)
 pal.Importance = 200
 pal.Lightness = 300
 pal.ToleranceA = 100
 pal.ToleranceB = 100
 Set flt = ActiveDocument.ExportBitmap("C:\Temp\img.gif", cdrGIF, , cdrPalettedImage, PaletteOptions:=pal)
 flt.Finish
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructPasteOptions

Properties

Description

The **StructPasteOptions** class represents paste settings.

Copyright 2014 Corel Corporation. All rights reserved.

StructPasteOptions.ColorConversionOptions

Property **ColorConversionOptions** As StructColorConversionOptions

Description

Member of StructPasteOptions

The **ColorConversionOptions** property specifies the color-conversion subset of paste settings.

The **ColorConversionOptions** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

StructSaveAsOptions

Properties

Description

The **StructSaveAsOptions** class represents the settings used when saving a document. This class is used in conjunction with the Document.SaveAs method.

- You can create a **StructSaveAsOptions** object by using the **New** keyword in Visual Basic.

Copyright 2014 Corel Corporation. All rights reserved.

StructSaveAsOptions.EmbedICCProfile

Property **EmbedICCProfile** As Boolean

Description

Member of StructSaveAsOptions

The **EmbedICCProfile** property returns or specifies whether an International Color Consortium (ICC) profile is embedded when saving a document.

VBA example

The following VBA example saves the active document to a file. The macro project is included in the file; however, an ICC color profile and a CMX data stream are not saved.

```
Sub Test()
 Dim so As New StructSaveAsOptions
 so.EmbedICCProfile = False
 so.EmbedVBAProject = True
 so.IncludeCMXData = False
 ActiveDocument.SaveAs "C:\Temp\File.cdr", so
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructSaveAsOptions.EmbedVBAProject

Property **EmbedVBAProject** As Boolean

Description

Member of StructSaveAsOptions

The **EmbedVBAProject** property returns or specifies whether the macro project associated with a document is saved when the document is saved.

VBA example

The following VBA example saves the active document to a file. The macro project is included in the file; however, an ICC color profile and a CMX data stream are not saved.

```
Sub Test()
 Dim so As New StructSaveAsOptions
 so.EmbedICCProfile = False
 so.EmbedVBAProject = True
 so.IncludeCMXData = False
 ActiveDocument.SaveAs "C:\Temp\File.cdr", so
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructSaveAsOptions.Filter

Property **Filter** As cdrFilter

Description

Member of StructSaveAsOptions

The **Filter** property returns or specifies the format used when saving a document.

- For saving documents in formats other than CDR or CMX, use the Document.ExportEx or Document.ExportBitmap methods.

The **Filter** property returns a value of cdrFilter.

VBA example

The following VBA example saves the current document as a CMX file with a 5K-color thumbnail.

```
Sub Test()
 Dim so As New StructSaveAsOptions
 so.Filter = cdrCMX6
 so.ThumbnailSize = cdr5KColorThumbnail
 ActiveDocument.SaveAs "C:\Temp\File.cmx", so
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructSaveAsOptions.IncludeCMXData

Property **IncludeCMXData** As Boolean

Description

Member of StructSaveAsOptions

The **IncludeCMXData** property returns or specifies whether a saved document includes a duplicate data stream in CMX format.

VBA example

The following VBA example saves the active document to a file. The macro project is included in the file; however, an ICC color profile and a CMX data stream are not saved.

```
Sub Test()
 Dim so As New StructSaveAsOptions
 so.EmbedICCProfile = False
 so.EmbedVBAProject = True
 so.IncludeCMXData = False
 ActiveDocument.SaveAs "C:\Temp\File.cdr", so
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructSaveAsOptions.Overwrite

Property **Overwrite** As Boolean

Description

Member of StructSaveAsOptions

The **Overwrite** property returns or specifies wheter to overwrite an existing file having the specified name. The default value of this property is **True**. If the file with the given name already exists and this property is set to **False**, the save operation fails.

VBA example

If the file **file.cdr** already exists in the folder **C:\Temp**, the following code example fails while saving the active document.

```
Sub Test()
 Dim so As New StructSaveAsOptions
 so.Overwrite = False
 ActiveDocument.SaveAs "C:\Temp\File.cdr", so
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructSaveAsOptions.Range

Property **Range** As cdrExportRange

Description

Member of StructSaveAsOptions

The **Range** property returns or specifies which part or parts of the document are saved. The available options for this property are as follows: current selection, current page, and whole document.

The **Range** property returns a value of cdrExportRange.

VBA example

The following VBA example saves only the selected objects.

```
Sub Test()
 Dim so As New StructSaveAsOptions
 so.Range = cdrSelection
 ActiveDocument.SaveAs "C:\Temp\File.cdr", so
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructSaveAsOptions.Version

Property **Version** As cdrFileVersion

Description

Member of StructSaveAsOptions

The **Version** property returns or specifies the CorelDRAW file-format version when saving a document. You can save the file in the format for CorelDRAW 5 or later.

This property returns a value of cdrFileVersion**.**

VBA example

The following VBA example saves the active document as a CorelDRAW 7 document.

```
Sub Test()
 Dim so As New StructSaveAsOptions
 so.Version = cdrVersion7
 ActiveDocument.SaveAs "C:\Temp\File7.cdr", so
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructSpaceProperties

Properties

Description

The **StructSpaceProperties** class represents the spacing settings of a text object.

- You can create a **StructSpaceProperties** object by using the **New** keyword in Visual Basic.

Copyright 2014 Corel Corporation. All rights reserved.

StructSpaceProperties.AfterParagraphSpacing

Property **AfterParagraphSpacing** As Single

Description

Member of StructSpaceProperties

The **AfterParagraphSpacing** property returns or specifies the amount of space after the last line of a paragraph. This value varies depending on the type of paragraph spacing specifies with the StructSpaceProperties.LineSpacingType property — for example, spacing can be measured as a percentage of character height, in points, or as a percentage of point size.

VBA example

The following VBA example sets the spacing of lines at **120**% of the font size, the spacing before paragraphs of **100**%, and the spacing after paragraphs of **50**%.

```
Sub Test()
 With ActiveShape.Text.Selection
  .LineSpacingType = cdrPercentOfPointSizeLineSpacing
  .LineSpacing = 120
  .BeforeParagraphSpacing = 100
  .AfterParagraphSpacing = 50
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructSpaceProperties.BeforeParagraphSpacing

Property **BeforeParagraphSpacing** As Single

Description

Member of StructSpaceProperties

The **BeforeParagraphSpacing** property returns or specifies the amount of space before the first line of a paragraph. This value varies depending on the type of paragraph spacing specified by the StructSpaceProperties.LineSpacingType property; for example, spacing can be measured as a percentage of character height, in points, or as a percentage of point size.

VBA example

The following VBA example sets the spacing of lines at **120**% of the font size, the spacing before paragraphs of **100**%, and the spacing after paragraphs of **50**%.

```
Sub Test()
 With ActiveShape.Text.Selection
  .LineSpacingType = cdrPercentOfPointSizeLineSpacing
  .LineSpacing = 120
  .BeforeParagraphSpacing = 100
  .AfterParagraphSpacing = 50
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructSpaceProperties.CharacterSpacing

Property **CharacterSpacing** As Single

Description

Member of StructSpaceProperties

The **CharacterSpacing** property returns or specifies the amount of space between the characters in a text object. This value represents a percentage of the **Space** character (that is, the character inserted when you press the **Spacebar**). The maximum percentage value is **2000**; the minimum percentage value is **-100**.

- The value set with the **CharacterSpacing** property cannot exceed the maximum character-spacing limit specified by the StructAlignProperties.MaxCharacterSpacing property.

Copyright 2014 Corel Corporation. All rights reserved.

StructSpaceProperties.LineSpacing

Property **LineSpacing** As Single

Description

Member of StructSpaceProperties

The **LineSpacing** property returns or specifies the amount of space between the lines (that is, the leading) of a paragraph. This value varies depending on the type of line spacing specified by the StructSpaceProperties.LineSpacingType property; for example, line spacing can be measured as a percentage of character height, in points, or as a percentage of point size.

VBA example

The following VBA example sets the spacing of lines at **120**% of the font size, the spacing before paragraphs of **100**%, and the spacing after paragraphs of **50**%.

```
Sub Test()
 With ActiveShape.Text.Selection
  .LineSpacingType = cdrPercentOfPointSizeLineSpacing
  .LineSpacing = 120
  .BeforeParagraphSpacing = 100
  .AfterParagraphSpacing = 50
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructSpaceProperties.LineSpacingType

Property **LineSpacingType** As cdrLineSpacingType

Description

Member of StructSpaceProperties

The **LineSpacingType** property returns or specifies the units used by the StructSpaceProperties.BeforeParagraphSpacing, StructSpaceProperties.AfterParagraphSpacing, and StructSpaceProperties.LineSpacing properties.

The **LineSpacingType** property returns a value of cdrLineSpacingType**.**

VBA example

The following VBA example sets the spacing of lines at **120**% of the font size, the spacing before paragraphs of **100**%, and the spacing after paragraphs of **50**%.

```
Sub Test()
 With ActiveShape.Text.Selection
  .LineSpacingType = cdrPercentOfPointSizeLineSpacing
  .LineSpacing = 120
  .BeforeParagraphSpacing = 100
  .AfterParagraphSpacing = 50
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

StructSpaceProperties.WordSpacing

Property **WordSpacing** As Single

Description

Member of StructSpaceProperties

The **WordSpacing** property returns or specifies the amount of space between the words in a text object. This value represents a percentage of the **Space** character (that is, the character inserted when you press **Spacebar**). The maximum percentage value is **2000**; the minimum percentage value is **0**.

- The value set with the **WordSpacing** property cannot exceed the maximum or minimum word-spacing limits specified by the StructAlignProperties.MaxWordSpacing and StructAlignProperties.MinWordSpacing properties.

Copyright 2014 Corel Corporation. All rights reserved.

Style

Properties Methods

Description

The **Style** class represents object styles and style sets in a document.

Copyright 2014 Corel Corporation. All rights reserved.

Style.BasedOn

Property **BasedOn** As Style

Description

Member of Style

The **BasedOn** property returns the style or style set on which the style is based or returns Nothing if the style is not based on another style.

Copyright 2014 Corel Corporation. All rights reserved.

Style.CategoryName

Property **CategoryName** As String

Description

Member of Style

The **CategoryName** property returns the category name for the style or style set.

Copyright 2014 Corel Corporation. All rights reserved.

Style.Character

Property **Character** As StyleCharacter

Description

Member of Style

The **Character** property returns the character style properties.

Copyright 2014 Corel Corporation. All rights reserved.

Style.ClearProperty

Function **ClearProperty**(*N*ame As String) As Boolean

Description

Member of Style

The **ClearProperty** function removes the local override of a given property.

Parameter	Description
Name	Specifies the name of the property

Copyright 2014 Corel Corporation. All rights reserved.

Style.Delete

Function **Delete()** As Boolean

Description

Member of Style

The **Delete** function deletes the style and returns True if the style is deleted successfully.

Copyright 2014 Corel Corporation. All rights reserved.

Style.DerivedStyles

Property **DerivedStyles** As Styles

Description

Member of Style

The **DerivedStyles** property returns a list of styles or style sets that are derived from this style or style set.

Copyright 2014 Corel Corporation. All rights reserved.

Style.DisplayCategoryName

Property **DisplayCategoryName** As String

Description

Member of Style

The **DisplayCategoryName** property returns a UI-friendly category name for the style or style set.

Copyright 2014 Corel Corporation. All rights reserved.

Style.DisplayName

Property **DisplayName** As String

Description

Member of Style

The **DisplayName** property returns a UI-friendly name for the style or style set.

Copyright 2014 Corel Corporation. All rights reserved.

Style.Fill

Property **Fill** As StyleFill

Description

Member of Style

The **Fill** property returns the fill style properties.

Copyright 2014 Corel Corporation. All rights reserved.

Style.Frame

Property **Frame** As StyleFrame

Description

Member of Style

The **Frame** property returns the frame style properties.

Copyright 2014 Corel Corporation. All rights reserved.

Style.GetAllPropertyNames

Function **GetAllPropertyNames()** As String**()**

Description

Member of Style

The **GetAllPropertyNames** function returns a list of all the property names in the style category.

Copyright 2014 Corel Corporation. All rights reserved.

Style.GetOverridePropertyNames

Function **GetOverridePropertyNames()** As String**()**

Description

Member of Style

The **GetOverridePropertyNames** function returns a list of the names of properties that are locally overriden in the style or style set.

Copyright 2014 Corel Corporation. All rights reserved.

Style.GetProperty

Function **GetProperty(**Name As String**)** As Variant

Description

Member of Style

The **GetProperty** function returns a property value by name.

Parameter	Description
Name	Specifies the name of the property

Copyright 2014 Corel Corporation. All rights reserved.

Style.GetPropertyAsString

Function **GetPropertyAsString(**Name As String**)** As String

Description

Member of Style

The **Style.GetPropertyAsString** function retrieves a style property as a string.

Parameter	Description
Name	Specifies the name of the property

Copyright 2014 Corel Corporation. All rights reserved.

Style.IsObjectDefaults

Property **IsObjectDefaults** As Boolean

Description

Member of Style

The **IsObjectDefaults** property returns **True** if this style set represents the default style properties for a particular object type.

Copyright 2014 Corel Corporation. All rights reserved.

Style.IsPropertyInherited

Function **IsPropertyInherited(**Name As String**)** As Boolean

Description

Member of Style

The **IsPropertyInherited** function returns True if the property is inherited from a parent style or style set.

Parameter	Description
Name	Specifies the name of the property

Copyright 2014 Corel Corporation. All rights reserved.

Style.IsStyleSet

Property **IsStyleSet** As Boolean

Description

Member of Style

The **IsStyleSet** property returns **True** if this is a style set.

Copyright 2014 Corel Corporation. All rights reserved.

Style.Name

Property **Name** As String

Description

Member of Style

The **Name** property returns the name of the style or style set.

Copyright 2014 Corel Corporation. All rights reserved.

Style.Outline

Property **Outline** As StyleOutline

Description

Member of Style

The **Outline** property returns the style properties of the outline.

Copyright 2014 Corel Corporation. All rights reserved.

Style.Paragraph

Property **Paragraph** As StyleParagraph

Description

Member of Style

The **Paragraph** property returns the paragraph style properties.

Copyright 2014 Corel Corporation. All rights reserved.

Methods

The Style class contains the following methods:

- ClearProperty
- Delete
- GetAllPropertyNames
- GetOverridePropertyNames
- GetProperty
- GetPropertyAsString
- IsPropertyInherited
- Rename
- SetBasedOn
- SetProperty
- SetPropertyAsString
- StringAssign
- ToString

Copyright 2014 Corel Corporation. All rights reserved.

Style.Rename

Function **Rename(**NewName As String**)** As Boolean

Description

Member of Style

The **Rename** function renames the style. This function returns False if a style cannot be renamed: for example, when a file with the same name already exists.

Parameter	Description
NewName	Specifies the new name of the style

Copyright 2014 Corel Corporation. All rights reserved.

Style.SetBasedOn

Function **SetBasedOn(**NewParent As String**)** As Boolean

Description

Member of Style

The **SetBasedOn** function changes the parent style from which the style is derived. This function returns True when the change is successful.

Parameter	Description
NewParent	Specifies the name of the new parent style

Copyright 2014 Corel Corporation. All rights reserved.

Style.SetProperty

Sub **SetProperty**(Name As String, Value As Variant)

Description

Member of Style

The **SetProperty** function sets a value of a property by name.

Parameter	Description
Name	Specifies the name of the property
Value	Specifies the value

Copyright 2014 Corel Corporation. All rights reserved.

Style.SetPropertyAsString

Function **SetPropertyAsString(**Name As String,V*alue As String***)** As Boolean

Description

Member of Style

The **SetPropertyAsString** function sets a property value as a string.

Parameter	Description
Name	Specifies the name of the property
Value	Specifies the value

Copyright 2014 Corel Corporation. All rights reserved.

Style.StringAssign

Function **StringAssign(***StyleString As String***)** As Boolean

Description

Member of Style

The **StringAssign** function restores the style properties from a string.

Parameter	Description
StyleString	Specifies the name of the property

Copyright 2014 Corel Corporation. All rights reserved.

Style.ToString

Function **ToString()** As String

Description

Member of Style

The **ToString** function converts all style properties to a string.

Copyright 2014 Corel Corporation. All rights reserved.

StyleCharacter

Properties

Description

The **StyleCharacter** class represents the character properties of a style.

Copyright 2014 Corel Corporation. All rights reserved.

StyleCharacter.Style

Property **Style** As Style

Description

Member of StyleCharacter

The **Style** property returns a generic object style for the character style.

The **Style** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill

Properties Methods

Description

The **StyleFill** class represents the fill properties of a style.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.FlipColors

Property **FlipColors** As Boolean

Description

Member of StyleFill

The **FlipColors** property reverses the colors of a fountain fill.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.FountainAnisotropic

Property **FountainAnisotropic** As Boolean

Description

Member of StyleFill

The **FountainAnisotropic** property specifies whether the fountain fill can be stretched and skewed nonproportionally.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.FountainBlendAcceleration

Property **FountainBlendAcceleration** As Double

Description

Member of StyleFill

The **FountainBlendAcceleration** property specifies the color blend acceleration.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.FountainBlendType

Property **FountainBlendType** As cdrFountainFillBlendType

Description

Member of StyleFill

The **FountainBlendType** property returns or sets the blend type of a fountain fill.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.FountainCenterXOffset

Property **FountainCenterXOffset** As Double

Description

Member of StyleFill

The **FountainCenterXOffset** property specifies the horizontal offset of a fountain fill's center.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.FountainCenterYOffset

Property **FountainCenterYOffset** As Double

Description

Member of StyleFill

The **FountainCenterYOffset** property specifies the vertical offset of a fountain fill's center.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.FountainFillType

Property **FountainFillType** As cdrFountainFillType

Description

Member of StyleFill

The **FountainFillType** property returns or sets the fill type of a fountain fill.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.FountainScaleX

Property **FountainScaleX** As Double

Description

Member of StyleFill

The **FountainScaleX** property specifies the horizontal scaling factor for fountain fills.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.FountainScaleY

Property **FountainScaleY** As Double

Description

Member of StyleFill

The **FountainScaleY** property specifies the vertical scaling factor for fountain fills.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.FountainSpreadMethod

Property **FountainSpreadMethod** As cdrFountainFillSpreadMethod

Description

Member of StyleFill

The **FountainSpreadMethod** property specifies the spread method of a fountain fill.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.FountainSteps

Property **FountainSteps** As Long

Description

Member of StyleFill

The **FountainSteps** property returns or sets the number of steps used to display or print a fountain fill.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.LoadFill

Function **LoadFill**(FileName As String, [*Metadata As* FillMetadata]**)** As Boolean

Description

Member of StyleFill

The **LoadFill** method loads a fill from a file and applies it to the style.

Parameter	Description
FileName	Specifies the filename
Metadata	Specifies the metadata associated with the file

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.MidPoint

Property **MidPoint** As Long

Description

Member of StyleFill

The **MidPoint** property returns or sets the point where the first and last colors of a fountain fill meet.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.MirrorFill

Property **MirrorFill** As Boolean

Description

Member of StyleFill

The **MirrorFill** property specifies whether to mirror the fill by making alternating tiles reflections of each other.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.MirrorFillX

Property **MirrorFillX** As Boolean

Description

Member of StyleFill

The **MirrorFillX** property specifies whether to mirror the fill tiles horizontally.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.MirrorFillY

Property **MirrorFillY** As Boolean

Description

Member of StyleFill

The **MirrorFillY** property specifies whether to mirror the fill tiles vertically.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.Overprint

Property **Overprint** As Boolean

Description

Member of StyleFill

The **Overprint** property specifies if the fill has overprint settings.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.PostScript

Property **PostScriptName** As String

Description

Member of StyleFill

The **PostScriptName** property returns or specifies a post script fill name as a string.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.PrimaryColor

Property **PrimaryColor** As Color

Description

Member of StyleFill

The **PrimaryColor** property returns the primary color of the fill. The primary color is used as the fill color of a uniform fill, the foreground color of a two-color bitmap fill, and the first color of a fountain fill.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.PrimaryOpacity

Property **PrimaryOpacity** As Byte

Description

Member of StyleFill

The **PrimaryOpacity** property specifies the opacity of the first color stop.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.RotationAngle

Property **RotationAngle** As Double

Description

Member of StyleFill

The **RotationAngle** property returns or specifies the angle of rotation of a fountain fill.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.SaveFill

Function **SaveFill**(FileName As String, [*Metadata As* FillMetadata]**)** As Boolean

Description

Member of StyleFill

The **SaveFill** method saves the fill style to a file.

Parameter	Description
FileName	Specifies the filename
Metadata	Specifies the metadata associated with the file

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.SecondaryColor

Property **SecondaryColor** As Color

Description

Member of StyleFill

The **SecondaryColor** property returns the secondary color of the fill. The secondary color is used as the background color of a two-color bitmap fill and the last color of a fountain fill.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.SecondaryOpacity

Property **SecondaryOpacity** As Byte

Description

Member of StyleFill

The **SecondaryOpacity** property specifies the opacity of the last color stop.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.SkewAngle

Property **SkewAngle** As Double

Description

Member of StyleFill

The **SkewAngle** property specifies the skew angle of a fill tile.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.Style

Property **Style** As Style

Description

Member of StyleFill

The **Style** property returns a generic style object for the fill style.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.TileHeight

Property **TileHeight** As Double

Description

Member of StyleFill

The **TileHeight** property specifies the height of a tile in a fill.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.TileOffset

Property **TileOffset** As Long

Description

Member of StyleFill

The **TileOffset** property specifies the tile offset in a fill.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.TileOffsetType

Property **TileOffsetType** As cdrTileOffsetType

Description

Member of StyleFill

The **TileOffsetType** property specifies whether to offset rows or columns in a fill.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.TileOriginX

Property **TileOriginX** As Double

Description

Member of StyleFill

The **TileOriginX** property returns or specifies the x-coordinate of a fill tile.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.TileOriginY

Property **TileOriginY** As Double

Description

Member of StyleFill

The **TileOriginY** property returns or specifies the y-coordinate of a fill tile.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.TileWidth

Property **TileWidth** As Double

Description

Member of StyleFill

The **TileWidth** property returns or specifies the width of a fill tile.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.TransformWithShape

Property **TransformWithShape** As Boolean

Description

Member of StyleFill

The **TransformWithShape** property specifies whether to transform a fill together with the shape to which the fill is applied.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.Type

Property **Type** As cdrFillStyleType

Description

Member of StyleFill

The **Type** property specifies what type of fill to apply or returns the type of fill that is applied.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFill.WindingFill

Property **WindingFill** As Boolean

Description

Member of StyleFill

The **WindingFill** property controls the way a fill is applied to the overlapping portions of a curve.

Copyright 2014 Corel Corporation. All rights reserved.

Methods

The **StyleFill** class contains the following methods:

- LoadFill
- SaveFill

Copyright 2014 Corel Corporation. All rights reserved.

StyleFrame

Properties

Description

The **StyleFrame** class represents the settings of a frame style.

Copyright 2014 Corel Corporation. All rights reserved.

StyleFrame.Style

Property **Style** As Style

Description

Member of StyleFrame

The **Style** property returns a generic style object for the frame style.

Copyright 2014 Corel Corporation. All rights reserved.

StyleOutline

Properties

Description

The **StyleOutline** class represents the settings of an outline style.

Copyright 2014 Corel Corporation. All rights reserved.

StyleOutline.BehindFill

Property **BehindFill** As Boolean

Description

Member of StyleOutline

The **BehindFill** property specifies whether the outline should be drawn behind the fill.

Copyright 2014 Corel Corporation. All rights reserved.

StyleOutline.Color

Property **Color** As Color

Description

Member of StyleOutline

The **Color** property specifies the color of the outline.

Copyright 2014 Corel Corporation. All rights reserved.

StyleOutline.Justification

Property **Justification** As cdrOutlineJustification

Description

Member of StyleOutline

The **Justification** property specifies how the outline is placed in relation to the object edge — centered along the edge, on the inside, or on the outside.

Copyright 2014 Corel Corporation. All rights reserved.

StyleOutline.LineCaps

Property **LineCaps** As cdrOutlineLineCaps

Description

Member of StyleOutline

The **LineCaps** property returns or specifies the endpoint style of an open-path outline.

Copyright 2014 Corel Corporation. All rights reserved.

StyleOutline.LineJoin

Property **LineJoin** As cdrOutlineLineJoin

Description

Member of StyleOutline

The **LineJoin** property returns or specifies the type of joints for lines that intersect in an outline.

Copyright 2014 Corel Corporation. All rights reserved.

StyleOutline.MiterLimit

Property **MiterLimit** As Double

Description

Member of StyleOutline

The **MiterLimit** property returns or specifies the miter limit, which determines the joint type — pointed (mitered) or beveled — for lines that meet at a sharp anlge in an outline.

Copyright 2014 Corel Corporation. All rights reserved.

StyleOutline.NibAngle

Property **NibAngle** As Double

Description

Member of StyleOutline

The **NibAngle** property returns or specifies the angle of the brush nib in a calligraphic outline.

Copyright 2014 Corel Corporation. All rights reserved.

StyleOutline.NibStretch

Property **NibStretch** As Long

Description

Member of StyleOutline

The **NibStretch** property returns or specifies the width of the brush nib in a calligraphic outline.

Copyright 2014 Corel Corporation. All rights reserved.

StyleOutline.OverlapArrow

Property **OverlapArrow** As Boolean

Description

Member of StyleOutline

The **OverlapArrow** property specifies whether the arrowhead overlaps with the curve segment or is appended at the endpoint.

Copyright 2014 Corel Corporation. All rights reserved.

StyleOutline.Overprint

Property **Overprint** As Boolean

Description

Member of StyleOutline

The **Overprint** property specifies whether the outline color should be printed on top of underlying colors.

Copyright 2014 Corel Corporation. All rights reserved.

StyleOutline.ScaleWithShape

Property **ScaleWithShape** As Boolean

Description

Member of StyleOutline

The **ScaleWithShape** property specifies whether to change the outline thickness when changing the shape size.

Copyright 2014 Corel Corporation. All rights reserved.

StyleOutline.ShareArrow

Property **ShareArrow** As Boolean

Description

Member of StyleOutline

The **ShareArrow** property specifies whether to start and end an open-path outline with the same arrowheads.

Copyright 2014 Corel Corporation. All rights reserved.

StyleOutline.Style

Property **Style** As Style

Description

Member of StyleOutline

The **Style** property returns a generic style object for the outline style.

Copyright 2014 Corel Corporation. All rights reserved.

StyleOutline.Type

Property **Type** As cdrOutlineType

Description

Member of StyleOutline

The **Type** property specifies the type of outline defined in the style.

Copyright 2014 Corel Corporation. All rights reserved.

StyleOutline.WidelineWidth

Property **WidelineWidth** As Double

Description

Member of StyleOutline

The **WidelineWidth** property specifies the width of the outline pattern in an enhanced outline style.

Copyright 2014 Corel Corporation. All rights reserved.

StyleOutline.Width

Property **Width** As Double

Description

Member of StyleOutline

The **Width** property specifies the outline width in the style.

Copyright 2014 Corel Corporation. All rights reserved.

StyleParagraph

Properties

Description

The **StyleParagraph** class represents the settings of a paragraph text style in a document.

Copyright 2014 Corel Corporation. All rights reserved.

StyleParagraph.Style

Property **Style** As Style

Description

Member of StyleParagraph

The **Style** property returns a generic style object for the paragraph text style.

The **Style** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Styles

Properties Methods

Description

The **Styles** class represents the styles included in a document.

Copyright 2014 Corel Corporation. All rights reserved.

Styles.Count

Property **Count** As Long

Description

Member of Styles

The **Count** property returns the number of styles in the style sheet.

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Styles.Find

Function **Find(**Name *As String***)** As Style

Description

Member of Styles

The **Find** method finds a style by name.

Parameter	Description
Name	Specifies the name of the style

Copyright 2014 Corel Corporation. All rights reserved.

Styles.First

Property **First** As Style

Description

Member of Styles

The **First** property returns the first style in the collection.

The **First** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Styles.Item

Property **Item**(*Index As Long*) As Style

Description

Member of Styles

The **Item** property returns a style from a style collection by index.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the index

Copyright 2014 Corel Corporation. All rights reserved.

Styles.Last

Property **Last** As Style

Description

Member of Styles

The **Last** property returns the last style in the collection.

The **Last** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

StyleSheet

Properties Methods

Description

The **StyleSheet** class represents the styles and style sets included in a style sheet.

Copyright 2014 Corel Corporation. All rights reserved.

StyleSheet.AllStyles

Property **AllStyles** As Styles

Description

Member of StyleSheet

The **AllStyles** property returns a list of all the styles in the style sheet.

The **AllStyles** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

StyleSheet.AllStyleSets

Property **AllStyleSets** As Styles

Description

Member of StyleSheet

The **AllStyleSets** property returns a list of all the style sets in the style sheet.

The **AllStyleSets** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

StyleSheet.CreateStyle

Function **CreateStyle(***Category As String***, [***BasedOn As String***], [***Name As String***], [**ReplaceExisting As Boolean = False**])** As Style

Description

Member of StyleSheet

The **CreateStyle** method creates a style.

Parameter	Description
Category	Specifies the style category
BasedOn	Specifies the name of the style on which the new style is based. This parameter is optional.
Name	Specifies the name of the new style. This parameter is optional.
ReplaceExisting	Specifies whether to replace an existing style that has the same name. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

StyleSheet.CreateStyleFromShape

Function **CreateStyleFromShape(**Shape *As* Shape*, Category As String,* [*Name As String*]**, [**ReplaceExisting As Boolean = False]**)** As Styles

Description

Member of StyleSheet

The **CreateStyleFromShape** method creates styles from a shape.

Parameter	Description
Shape	Specifies the shape from which to create the style
Category	Specifies the category of the new style
Name	Specifies the name of the new style. This parameter is optional.
ReplaceExisting	Specifies whether to replace an existing style that has the same name. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

StyleSheet.CreateStyleFromShapeRange

Function **CreateStyleFromShapeRange(**ShapeRange As ShapeRange, Category As String, [Name As String], [ReplaceExisting As Boolean = False]**)** As Styles

Description

Member of StyleSheet

The **CreateStyleFromShapeRange** method creates styles from a shape range.

Parameter	Description
ShapeRange	Specifies the shape range
Category	Specifies the style category
Name	Specifies the name of the new style. This parameter is optional.
ReplaceExisting	Specifies whether to replace an existing style that has the same name. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

StyleSheet.CreateStyleFromTextRange

Function **CreateStyleFromTextRange(**TextRange As TextRange, Category As String, [Name As String], [ReplaceExisting As Boolean = False]**)** As Styles

Description

Member of StyleSheet

The **CreateStyleFromTextRange** method creates styles from a range of text characters.

Parameter	Description
TextRange	Specifies a text range
Category	Specifies the category of the new style
Name	Specifies the name of the new style. This parameter is optional.
ReplaceExisting	Specifies whether to replace an existing style that has the same name. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

StyleSheet.CreateStyleSet

Function CreateStyleSet([BasedOn As String], [Name As String], [ReplaceExisting As Boolean = False]**)** As Style

Description

Member of StyleSheet

The **CreateStyleSet** method creates a style set.

Parameter	Description
BasedOn	Specifies the name of the style set on which the new style set is based. This parameter is optional.
Name	Specifies the name of the new style set. This parameter is optional.
ReplaceExisting	Specifies whether to replace an existing style that has the same name. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

StyleSheet.CreateStyleSetFromShape

Function **CreateStyleSetFromShape(**Shape As Shape, [*Name As String*]**, [**ReplaceExisting As Boolean = False]**)** As Styles

Description

Member of StyleSheet

The **CreateStyleFromShape** method creates style sets from a shape.

Parameter	Description
Shape	Specifies the shape from which to create the style set
Name	Specifies the name of the new style set. This parameter is optional.
ReplaceExisting	Specifies whether to replace an existing style that has the same name. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

StyleSheet.CreateStyleSetFromShapeRange

Function **CreateStyleSetFromShapeRange(**ShapeRange As ShapeRange, [*Name As String*], [*ReplaceExisting As Boolean* = False]**)** As Styles

Description

Member of StyleSheet

The **CreateStyleFromShapeRange** method creates style sets from a shape range.

Parameter	Description
ShapeRange	Specifies the shape range
Name	Specifies the name of the new style set. This parameter is optional.
ReplaceExisting	Specifies whether to replace an existing style that has the same name. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

StyleSheet.CreateStyleSetFromTextRange

Function **CreateStyleSetFromTextRange(**TextRange As TextRange, [*Name As String*], [*ReplaceExisting As Boolean* = False]**)** As Styles

Description

Member of StyleSheet

The **CreateStyleSetFromTextRange** method creates style sets from a range of text characters.

Parameter	Description
TextRange	Specifies a text range
Name	Specifies the name of the new style set. This parameter is optional.
ReplaceExisting	Specifies whether to replace an existing style that has the same name. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

StyleSheet.Export

Function **Export(**FileName As String, [*Styles As Boolean* = False], [*StyleSets As Boolean* = False], [*ObjectDefaults As Boolean* = False], [*ColorStyles As Boolean* = False]**)** As Boolean

Description

Member of StyleSheet

The **Export** method exports styles from the style sheet.

Parameter	Description
FileName	Specifies the file name
Styles	Specifies whether to export styles
StyleSets	Specifies whether to export style sets
ObjectDefaults	Specifies whether to export object default styles
ColorStyles	Specifies whether to export color styles

Copyright 2014 Corel Corporation. All rights reserved.

StyleSheet.FindStyle

Function **FindStyle(***Name As String***)** As Style

Description

Member of StyleSheet

The **FindStyle** method finds a style by name.

Parameter	Description
Name	Specifies the style name

Copyright 2014 Corel Corporation. All rights reserved.

StyleSheet.Import

Function **Import(**FileName As String, [*MergeStyles As Boolean* = False], [*Styles As Boolean* = False], [*StyleSets As Boolean* = False], [*ObjectDefaults As Boolean* = False], [*ColorStyles As Boolean* = False]**)** As Boolean

Description

Member of StyleSheet

The **Import** method imports styles and style sets in a style sheet.

Parameter	Description
FileName	Specifies the file name
MergeStyles	Specifies whether to merge styles
Styles	Specifies whether to import styles
StyleSets	Specifies whether to import style sets
ObjectDefaults	Specifies whether to import object default styles
ColorStyles	Specifies which color styles to import

Copyright 2014 Corel Corporation. All rights reserved.

StyleSheet.ObjectDefaults

Property **ObjectDefaults** As Styles

Description

Member of StyleSheet

The **ObjectDefaults** property returns the default object style sets.

The **ObjectDefaults** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

StyleSheet.Styles

Property **Styles** As Styles

Description

Member of StyleSheet

The **Styles** property returns the top-level styles defined in the style sheet.

The **Styles** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

StyleSheet.StyleSets

Property **StyleSets** As Styles

Description

Member of StyleSheet

The **StyleSets** property returns top-level style sets defined in a style sheet.

The **StyleSets** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Methods

The StyleSheet class contains the following methods:

- CreateStyle
- CreateStyleFromShape
- CreateStyleFromShapeRange
- CreateStyleFromTextRange
- CreateStyleSet
- CreateStyleSetFromShape
- CreateStyleSetFromShapeRange
- CreateStyleSetFromTextRange
- Export
- FindStyle
- Import

Copyright 2014 Corel Corporation. All rights reserved.

SubPath

Properties Methods

Description

The **Subpath** class represents the settings for a subpath in a curve.

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.AddNodeAt

Function **AddNodeAt([**Offset As Double = 0.5**], [**OffsetType As cdrSegmentOffsetType = cdrRelativeSegmentOffset**])** As Node

Description

Member of SubPath

The **AddNodeAt** method inserts a node at a given point on a subpath. An absolute or relative offset from the beginning of the subpath can be specified.

Parameter	Description
Offset	Specifies the offset distance, in document units, of the new node. This parameter is optional, and its default value is **0.5**.
OffsetType	Specifies the offset type, and returns cdrSegmentOffsetType. This parameter is optional, and its default value is cdrRelativeSegmentOffset (**1**).

VBA example

The following VBA example adds a new node to the middle of each subpath.

```
Sub Test()
 Dim sp As SubPath
 For Each sp In ActiveShape.Curve.Subpaths
  sp.AddNodeAt 0.5, cdrRelativeSegmentOffset
 Next sp
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.AppendCurveSegment

Function **AppendCurveSegment(***x As Double***,** *y As Double***, [**StartingControlPointLength As Double = -1**], [***StartingControlPointAngle As Double***], [**EndingControlPointLength As Double = -1**], [***EndingControlPointAngle As Double***], [**AppendAtBeginning As Boolean = False**])** As Segment

Description

Member of SubPath

The **AppendCurveSegment** method joins a new curve segment to the beginning or the end of a subpath.

Parameter	Description
x	Specifies, in document units, the horizontal position of the new line segment to append to the subpath
y	Specifies, in document units, the vertical position of the new line segment to append to the subpath
StartingControlPointLength	Specifies, in document units, the distance from the node that lies between the new appended curve segment and the existing curve's subpath. This parameter is optional, and its default value is **-1**.
StartingControlPointAngle	Specifies the angle, measured in degrees, of the starting control point. This parameter is optional, and its default value is **0**.
EndingControlPointLength	Specifies, in document units, the distance from the node that lies between the new appended curve segment and the existing curve's subpath. This parameter is optional, and its default value is **-1**.
EndingControlPointAngle	Specifies the angle, measured in degrees, of the ending control point. This parameter is optional, and its default value is **0**.
AppendAtBeginning	Specifies whether the new line segment joins the subpath at the head of the subpath. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example creates a closed curve and applies a fountain fill to it.

```
Sub Test()
 Dim s As Shape
 Dim crv As Curve
 Dim sp As SubPath
 Dim c As New Color
 Set crv = CreateCurve(ActiveDocument)
 Set sp = crv.CreateSubPath(0, 0)
 sp.AppendLineSegment 3.6, 0, False
 sp.AppendCurveSegment 3.6, 0.8, 0.43, 160, 0.43, -160, False
 sp.AppendLineSegment 0, 0.8, False
 sp.AppendCurveSegment 0, 0, 0.43, -20, 0.43, 20, False
 sp.Closed = True
 Set s = ActiveLayer.CreateCurve(crv)
 c.CMYKAssign 0, 0, 0, 100
 With s.Fill.ApplyFountainFill(c, c, , 90, , , , cdrCustomFountainFillBlend).Colors
  .Add CreateCMYKColor(0, 0, 0, 0), 70
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.AppendCurveSegment2

Function **AppendCurveSegment2(***x As Double***,** *y As Double***,** *StartingControlPointX As Double***,** *StartingControlPointY As Double***,** *EndingControlPointX As Double***,** *EndingControlPointY As Double***, [**AppendAtBeginning As Boolean = False**])** As Segment

Description

Member of SubPath

The **AppendCurveSegment2** method appends a new curve segment to a subpath.

Parameter	Description
x	Specifies, in document units, the horizontal position of the new line segment to append to the subpath
y	Specifies, in document units, the vertical position of the new line segment to append to the subpath
StartingControlPointX	Specifies the horizontal position of the starting control point
StartingControlPointY	Specifies the vertical position of the starting control point
EndingControlPointX	Specifies the horizontal position of the ending control point
EndingControlPointY	Specifies the vertical position of the ending control point
AppendAtBeginning	Specifies whether the new line segment joins the subpath at the head of the subpath. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example creates a closed curve and applies a fountain fill to it.

```
Sub Test()
 Dim s As Shape
 Dim crv As Curve
 Dim sp As SubPath
 Dim c As New Color
 Set crv = CreateCurve(ActiveDocument)
 Set sp = crv.CreateSubPath(0, 0)
 sp.AppendLineSegment 3.6, 0, False
 sp.AppendCurveSegment2 3.6, 0.8, 4.6, 3.1, 5.43, -1.6, False
 sp.AppendLineSegment 0, 0.8, False
 sp.AppendCurveSegment2 5, 4.8, 5, -2, 2, -5, False
 sp.Closed = True
 Set s = ActiveLayer.CreateCurve(crv)
 c.CMYKAssign 0, 0, 0, 100
 With s.Fill.ApplyFountainFill(c, c, , 90, , , , cdrCustomFountainFillBlend).Colors
  .Add CreateCMYKColor(0, 0, 0, 0), 70
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.AppendLineSegment

Function **AppendLineSegment(***x As Double***,** *y As Double***, [**AppendAtBeginning As Boolean = False**])** As Segment

Description

Member of SubPath

The **AppendLineSegment** method joins a new line segment to the beginning or the end of an open subpath.

Parameter	Description
x	Specifies, in document units, the horizontal position of the new line segment to append to the subpath
y	Specifies, in document units, the vertical position of the new line segment to append to the subpath
AppendAtBeginning	Specifies whether the new line segment joins the subpath at the head of the subpath. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example creates a closed curve and applies a fountain fill to it.

```
Sub Test()
 Dim s As Shape
 Dim crv As Curve
 Dim sp As SubPath
 Dim c As New Color
 Set crv = CreateCurve(ActiveDocument)
 Set sp = crv.CreateSubPath(0, 0)
 sp.AppendLineSegment 3.6, 0, False
 sp.AppendCurveSegment 3.6, 0.8, 0.43, 160, 0.43, -160, False
 sp.AppendLineSegment 0, 0.8, False
 sp.AppendCurveSegment 0, 0, 0.43, -20, 0.43, 20, False
 sp.Closed = True
 Set s = ActiveLayer.CreateCurve(crv)
 c.CMYKAssign 0, 0, 0, 100
 With s.Fill.ApplyFountainFill(c, c, , 90, , , , cdrCustomFountainFillBlend).Colors
  .Add CreateCMYKColor(0, 0, 0, 0), 70
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.Application

Property **Application** As Application

Description

Member of SubPath

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.Area

Property **Area** As Double

Description

Member of SubPath

The **Area** property returns the area of a closed path.

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.BoundingBox

Property **BoundingBox** As Rect

Description

Member of SubPath

The **BoundingBox** property returns the bounding rectangle around a subpath.

The **BoundingBox** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.BreakApartAt

Function **BreakApartAt([**Offset As Double = 0.5**], [**OffsetType As cdrSegmentOffsetType = cdrRelativeSegmentOffset**])** As Node

Description

Member of SubPath

The **BreakApartAt** method divides a subpath in two at the specified offset from its beginning.

Parameter	Description
Offset	Specifies the offset distance, in document units. This parameter is optional, and its default value is **0.5**.
OffsetType	Specifies the offset type, and returns cdrSegmentOffsetType. This parameter is optional, and its default value is cdrRelativeSegmentOffset (**1**).

VBA example

The following VBA example breaks the subpath apart at **1.2**" from its beginning.

```
Sub Test()
 ActiveShape.Curve.Subpaths(1).BreakApartAt 1.2, cdrAbsoluteSegmentOffset
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.Closed

Property **Closed** As Boolean

Description

Member of SubPath

The **Closed** property returns or specifies whether a curve's subpath is open or closed. If this property is set to **True**, the subpath is closed, and an enclosure is formed by connecting the path's starting and ending points.

VBA example

The following VBA example closes all subpaths in the selected curve.

```
Sub Test()
 Dim spath As SubPath
 For Each spath In ActiveShape.Curve.Subpaths
  spath.Closed = True
 Next spath
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.Delete

Sub **Delete()**

Description

Member of SubPath

The **Delete** method removes a subpath from a curve.

- Removing the last subpath from a curve destroys the entire curve.

VBA example

The following VBA example creates a large letter “B” on the page, converts it to curves, and then deletes its inner “holes,” leaving only the outside contour.

```
Sub Test()
 Dim s As Shape
 Dim sgr As SegmentRange
 Set s = ActiveLayer.CreateArtisticText(0, 0, "B")
 With s.Text.FontProperties
  .Name = "Arial Black"
  .Size = 200
 End With
 s.ConvertToCurves
 s.Curve.Subpaths(3).Delete
 s.Curve.Subpaths(2).Delete
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.EndNode

Property **EndNode** As Node

Description

Member of SubPath

The **EndNode** property returns the first node of a subpath.

The **EndNode** property returns a read-only value.

VBA example

The following VBA example connects all open subpaths to each other, forming a single and larger closed subpath.

```
Sub Test()
 Dim crv As Curve
 Dim spath As SubPath, spath1 As SubPath
 Set crv = ActiveShape.Curve
 Set spath = crv.Subpaths(1)
 Do
  If Not spath.Closed Then
   Set spath1 = spath.Next
   Do
    If Not spath1.Closed Then Exit Do
    Set spath1 = spath1.Next
   Loop
   spath.EndNode.ConnectWith spath1.StartNode
  Else
   Set spath = spath.Next
   If spath.Index = 1 Then Exit Do
  End If
 Loop
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.Extract

Function **Extract([**OldCurve As Shape**])** As Shape

Description

Member of SubPath

The **Extract** method removes a subpath from a curve and creates a separate shape from the extracted subpath.

- The original curve is modified and cannot be accessed through its previous reference. A new reference to the original curve is returned though the **OldCurve** parameter after the extraction takes place.

Parameter	Description
OldCurve	References the original curve after the extraction by returning a shape. This parameter is optional, and its default value is **Nothing**.

VBA example

The following VBA example extracts each subpath from a curve and changes the outline color of each extracted curve.

```
Sub Test()
 Dim spath As SubPath
 Dim s As Shape, sExt As Shape
 Dim i As Long
 Set s = ActiveShape
 If s.Curve.Subpaths.Count < 2 Then Exit Sub
 For i = s.Curve.Subpaths.Count To 1 Step -1
  Set spath = s.Curve.Subpaths(i)
  Set sExt = spath.Extract(s)
  sExt.Outline.Width = 0.01
  sExt.Outline.Color = ActivePalette.Color(13 + i)
 Next i
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.FindClosestSegment

Function **FindClosestSegment(***x As Double***,** *y As Double***,** *ParamOffset As Double***)** As Segment

Description

Member of SubPath

The **FindClosestSegment** method finds the segment closest to a specified point on a subpath.

Parameter	Description
x	Specifies the x-coordinate of the point
y	Specifies the y-coordinate of the point
ParamOffset	Specifies the parametric offset for the subpath

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.FindNodeAtPoint

Function **FindNodeAtPoint(***x As Double*, *y As Double*, **[**HotArea As Double = -1**])** As Node

Description

Member of SubPath

The **FindNodeAtPoint** method finds a node on a subpath at the specified point.

Parameter	Description
x	Specifies the x-coordinate of the point
y	Specifies the y-coordinate of the point
HotArea	Specifies a restricted area on the subpath in which to evaluate the position of the point

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.FindSegmentAtPoint

Function **FindSegmentAtPoint(***x As Double*, *y As Double*, *ParamOffset As Double*, **[**HotArea As Double = -1**])** As Segment

Description

Member of SubPath

The **FindNodeAtPoint** method finds a segment on a subpath at the specified point.

Parameter	Description
x	Specifies the x-coordinate of the point
y	Specifies the y-coordinate of the point
ParamOffset	Specifies the parametric offset
HotArea	Specifies a restricted area on the subpath in which to evaluate the position of the point

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.FindSegmentOffset

Function **FindSegmentOffset(***AbsoluteOffset As Double***,** Segment As Segment**,** *ParamOffset As Double***, [***Remainder As Double***])** As Boolean

Description

Member of SubPath

The **FindSegmentOffset** method finds the offset of a specified point on a segment subpath.

- If the offset is longer than the length of the subpath, the function returns **False**, and the remaining offset is returned in the **Remainder** parameter. Otherwise, the function returns **True**, and the **ParamOffset** parameter returns the parametric offset for the subpath.

Parameter	Description
AbsoluteOffset	Specifies the value of the absolute offset
Segment	Specifies the segment
ParamOffset	Specifies the value of the parametric offset for the subpath
Remainder	Specifies the value of the remainder. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example finds the segment that contains a point **3**" from the beginning of the first subpath, and it then converts the segment to a line.

```
Sub Test()
 Dim seg As Segment
 Dim t As Double
 If ActiveShape.Curve.Subpaths(1).FindSegmentOffset(3, seg, t) Then
  seg.Type = cdrLineSegment
 Else
  MsgBox "The first subpath is less than 3"" long."
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.FirstSegment

Property **FirstSegment** As Segment

Description

Member of SubPath

The **FirstSegment** property returns the first segment of a subpath.

The **FirstSegment** property returns a read-only value.

VBA example

The following VBA example converts, to a line, the first segment of the first subpath of the selected curve.

```
Sub Test()
 ActiveShape.Curve.Subpaths(1).FirstSegment.Type = cdrLineSegment
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.GetBoundingBox

Function **GetBoundingBox(***x As Double*, *y As Double*, *Width As Double*, *Height As Double***)** As Boolean

Description

Member of SubPath

The **GetBoundingBox** method returns the bounding box around a subpath.

Parameter	Description
x	Specifies the x-coordinate
y	Specifies the y-coordinate
Width	Specifies the width
Height	Specifies the height

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.GetCopy

Function **GetCopy()** As Curve

Description

Member of SubPath

The **GetCopy** method returns a copy of the current subpath as a separate curve.

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.GetCurvatureAt

Function **GetCurvatureAt([**Offset As Double = 0.5**], [**OffsetType As cdrSegmentOffsetType = cdrRelativeSegmentOffset**])** As Double

Description

Member of SubPath

The **GetCurvatureAt** method returns the curvature of a subpath at a given point. The value of the curvature is the inverse of curvature radius, and it depends on the current document units.

Parameter	Description
Offset	Specifies the offset, in document units. This parameter is optional, and its default value is **0.5**.
OffsetType	Specifies the offset type of the point, and returns cdrSegmentOffsetType. This parameter is optional, and its default value is cdrRelativeSegmentOffset (**1**).

VBA example

The following VBA example draws a circle that touches the selected curve at the point that is **25**% of the length of its first subpath and that has the same curvature as the curve in this point (thereby showing the curvature radius).

```
Sub Test()
Dim c As Double, r As Double
Dim x As Double, y As Double, pa As Double
Dim sp As SubPath
Set sp = ActiveShape.Curve.SubPaths(1)
c = sp.GetCurvatureAt(0.25, cdrRelativeSegmentOffset)
If Abs(c) < 0.00001 Then
MsgBox "The curve is almost straight at this point", vbCritical
Exit Sub
End If
sp.GetPointPositionAt x, y, 0.25, cdrRelativeSegmentOffset
pa = sp.GetPerpendicularAt(0.25, cdrRelativeSegmentOffset)
pa = pa * 3.1415926 / 180
r = 1 / c
x = x + r * Cos(pa)
y = y + r * Sin(pa)
ActiveLayer.CreateEllipse2 x, y, r
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.GetCurveInfo

Function **GetCurveInfo()** As CurveElement()

Description

Member of SubPath

The **GetCurveInfo** method retrieves low-level curve information from a subpath.

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.GetCurveSpeedAt

Function **GetCurveSpeedAt([**Offset As Double = 0.5**], [**OffsetType As cdrSegmentOffsetType = cdrRelativeSegmentOffset**])** As Double

Description

Member of SubPath

The **GetCurveSpeedAt** method returns a value indicating the rate at which the curvature of a subpath changes at a given point. A value close to **0** means that the curvature is steady — for example, in a circle. A value greater than **0** means that the curvature increases — for example, in a spiral. A value of less than **0** value means that the curvature decreases — for example, in an unwinding spiral.

Parameter	Description
Offset	Specifies the offset, in document units, of the point. This parameter is optional, and its default value is **0.5**.
OffsetType	Specifies the offset type of the point, and returns cdrSegmentOffsetType. This parameter is optional, and its default value is cdrRelativeSegmentOffset (**1**).

VBA example

The following VBA example shows how the curvature changes in the middle of the first subpath of the selected curve.

```
Sub Test()
 Dim c As Double
 Dim sp As SubPath
 Set sp = ActiveShape.Curve.Subpaths(1)
 c = sp.GetCurveSpeedAt(0.5, cdrRelativeSegmentOffset)
 If Abs(c) < 0.01 Then
  MsgBox "Curvature is steady: " & c
 Else
  If c > 0 Then
   MsgBox "Curvature is increasing: " & c
  Else
   MsgBox "Curvature is decreasing: " & c
  End If
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.GetIntersections

Function **GetIntersections(**Target As SubPath**, [**OffsetType As cdrSegmentOffsetType = cdrRelativeSegmentOffset**])** As CrossPoints

Description

Member of SubPath

The **GetIntersections** method finds all the points of intersection for two subpaths.

Parameter	Description
Target	Specifies the subpath with which to intersect
OffsetType	Specifies the offset type of the intersection point, and returns cdrSegmentOffsetType. This parameter is optional, and its default value is cdrRelativeSegmentOffset (**1**).

VBA example

The following VBA example displays the number of times the two selected curves intersect and marks each intersection point with a small circle.

```
Sub Test()
 Dim sr As ShapeRange
 Dim sp1 As SubPath, sp2 As SubPath
 Dim cps As CrossPoints, cp As CrossPoint
 Dim x As Double, y As Double, n As Long
 Set sr = ActiveSelectionRange
 If sr.Count <> 2 Then
  MsgBox "Please select two curves", vbCritical
  Exit Sub
 End If
 If sr(1).Type <> cdrCurveShape Or sr(2).Type <> cdrCurveShape Then
  MsgBox "One of the selected shapes is not a curve", vbCritical
  Exit Sub
 End If
 n = 0
 For Each sp1 In sr(1).Curve.Subpaths
  For Each sp2 In sr(2).Curve.Subpaths
   Set cps = sp1.GetIntersections(sp2)
   For Each cp In cps
    ActiveLayer.CreateEllipse2 cp.PositionX, cp.PositionY, 0.05
   Next cp
   n = n + cps.Count
  Next sp2
 Next sp1
 MsgBox n & " intersection point(s) found"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.GetPerpendicularAt

Function **GetPerpendicularAt([**Offset As Double = 0.5**], [**OffsetType As cdrSegmentOffsetType = cdrRelativeSegmentOffset**])** As Double

Description

Member of SubPath

The **GetPerpendicularAt** method returns the perpendicular to a point on a curve's subpath.

Parameter	Description
Offset	Specifies the offset, in document units, of the perpendicular. This parameter is optional, and its default value is **0.5**.
OffsetType	Specifies the offset type, and returns cdrSegmentOffsetType. This parameter is optional, and its default value is cdrRelativeSegmentOffset (**1**).

VBA example

The following VBA example draws perpendicular and tangent vectors for several points uniformly distributed along the subpaths of the selected curve.

```
Sub Test()
 Dim sp As SubPath
 Dim t As Double
 For Each sp In ActiveShape.Curve.Subpaths
  For t = 0 To 0.9 Step 0.1
   MarkPoint sp, t
  Next t
 Next sp
End Sub
Private Sub MarkPoint(sp As SubPath, t As Double)
 Dim x As Double, y As Double
 Dim dx As Double, dy As Double
 Dim a1 As Double, a2 As Double
 sp.GetPointPositionAt x, y, t, cdrRelativeSegmentOffset
 a1 = sp.GetTangentAt(t, cdrRelativeSegmentOffset) * 3.1415926 / 180
 a2 = sp.GetPerpendicularAt(t, cdrRelativeSegmentOffset) * 3.1415926 / 180
 dx = 0.5 * Cos(a1)
 dy = 0.5 * Sin(a1)
 With ActiveLayer.CreateLineSegment(x, y, x + dx, y + dy)
  .Outline.EndArrow = ArrowHeads(1)
 End With
 dx = 0.5 * Cos(a2)
 dy = 0.5 * Sin(a2)
 With ActiveLayer.CreateLineSegment(x, y, x + dx, y + dy)
  .Outline.EndArrow = ArrowHeads(1)
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.GetPointPositionAt

Sub **GetPointPositionAt**(*x As Double*, *y As Double*, **[**Offset As Double = 0.5**]**, **[**OffsetType As cdrSegmentOffsetType = cdrRelativeSegmentOffset**])**

Description

Member of SubPath

The **GetPointPositionAt** method returns the coordinates of a point on a curve's subpath.

Parameter	Description
x	Specifies, in document units, the horizontal position of the point
y	Specifies, in document units, the vertical position of the point
Offset	Specifies, in document units, the offset distanceof the point
OffsetType	Specifies, in document units, the offset type of the point, and returns cdrSegmentOffsetType. This parameter is optional, and its default value is cdrRelativeSegmentOffset (1).

VBA example

The following VBA example creates five small ellipses distributed evenly along each subpath of the selected curve.

```
Sub Test()
Dim sp As SubPath
Dim t As Double, x As Double, y As Double
For Each sp In ActiveShape.Curve.SubPaths
For t = 0 To 0.9 Step 0.1
sp.GetPointPositionAt x, y, t, cdrRelativeSegmentOffset
ActiveLayer.CreateEllipse2 x, y, 0.03
Next t
Next sp
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.GetPolyline

Function **GetPolyline([***CurvePrecision As Long***])** As Curve

Description

Member of SubPath

The **GetPolyline** method returns a curve consisting of line segments approximating the current subpath.

Parameter	Description
CurvePrecision	Specifies the precision level of the curve

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.GetPosition

Sub **GetPosition(***PositionX As Double***,** *PositionY As Double***)**

Description

Member of SubPath

The **GetPosition** method returns the horizontal and vertical positions of a subpath head, treating the subpath a separate object.

Parameter	Description
PositionX	Specifies, in document units, the x-coordinate of the subpath's starting point
PositionY	Specifies, in document units, the y-coordinate of the subpath's starting point

VBA example

The following VBA example draws a bounding rectangle around each subpath in the selected curve.

```
Sub Test()
 Dim sp As SubPath
 Dim x As Double, y As Double
 ActiveDocument.ReferencePoint = cdrBottomLeft
 For Each sp In ActiveShape.Curve.Subpaths
  sp.GetPosition x, y
  ActiveLayer.CreateRectangle2 x, y, sp.SizeWidth, sp.SizeHeight
 Next sp
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.GetSegmentAt

Function **GetSegmentAt([**Offset As Double = 0.5**], [**OffsetType As cdrSegmentOffsetType = cdrRelativeSegmentOffset**], [***SegmentOffset As Double***])** As Segment

Description

Member of SubPath

The **GetSegmentAt** method returns a segment that contains the specified point on a subpath. Optionally, it returns the offset of the specified point within the returned segment.

Parameter	Description
Offset	Specifies, in document units, the offset of the point. This parameter is optional, and its default value is **0.5**.
OffsetType	Specifies the offset type, and returns cdrSegmentOffsetType. This parameter is optional, and its default value is cdrRelativeSegmentOffset (**1**).
SegmentOffset	Specifies the offset of the subpath segment. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example converts, to a line, the segment that is in the middle of the subpath.

```
Sub Test()
 Dim seg As Segment
 Set seg = ActiveShape.Curve.Subpaths(1).GetSegmentAt(0.5, cdrRelativeSegmentOffset)
 seg.Type = cdrLineSegment
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.GetTangentAt

Function **GetTangentAt([**Offset As Double = 0.5**], [**OffsetType As cdrSegmentOffsetType = cdrRelativeSegmentOffset**])** As Double

Description

Member of SubPath

The **GetTangentAt** method returns the tangent to a point on a curve's subpath.

Parameter	Description
Offset	Specifies, in document units, the offset of the tangent. This parameter is optional, and its default value is **0.5**.
OffsetType	Specifies the offset type, and returns cdrSegmentOffsetType. This parameter is optional, and its default value is cdrRelativeSegmentOffset (**1**).

VBA example

The following VBA example draws perpendicular and tangent vectors for several points uniformly distributed along the subpaths of the selected curve.

```
Sub Test()
 Dim sp As SubPath
 Dim t As Double
 For Each sp In ActiveShape.Curve.Subpaths
  For t = 0 To 0.9 Step 0.1
   MarkPoint sp, t
  Next t
 Next sp
End Sub
Private Sub MarkPoint(sp As SubPath, t As Double)
 Dim x As Double, y As Double
 Dim dx As Double, dy As Double
 Dim a1 As Double, a2 As Double
 sp.GetPointPositionAt x, y, t, cdrRelativeSegmentOffset
 a1 = sp.GetTangentAt(t, cdrRelativeSegmentOffset) * 3.1415926 / 180
 a2 = sp.GetPerpendicularAt(t, cdrRelativeSegmentOffset) * 3.1415926 / 180
 dx = 0.5 * Cos(a1)
 dy = 0.5 * Sin(a1)
 With ActiveLayer.CreateLineSegment(x, y, x + dx, y + dy)
  .Outline.EndArrow = ArrowHeads(1)
 End With
 dx = 0.5 * Cos(a2)
 dy = 0.5 * Sin(a2)
 With ActiveLayer.CreateLineSegment(x, y, x + dx, y + dy)
  .Outline.EndArrow = ArrowHeads(1)
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.Index

Property **Index** As Long

Description

Member of SubPath

The **Index** property returns the index number of a curve's subpath.

The **Index** property returns a read-only value.

VBA example

The following VBA example place a number next to each subpath.

```
Sub Test()
Dim spath As SubPath
Dim x As Double, y As Double, a As Double
Dim s As Shape
For Each spath In ActiveShape.Curve.SubPaths
spath.GetPointPositionAt x, y, 0.5, cdrRelativeSegmentOffset
a = spath.GetPerpendicularAt(0.5, cdrRelativeSegmentOffset)
If a < 0 Or a > 180 Then a = a + 180
a = a * 3.1415926 / 180
x = x + 0.2 * Cos(a)
y = y + 0.2 * Sin(a)
Set s = ActiveLayer.CreateArtisticText(x, y, CStr(spath.Index))
With s.Text
.AlignProperties.Alignment = cdrCenterAlignment
.FontProperties.Name = "Arial"
.FontProperties.Size = 18
End With
Next spath
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.IsClockwise

Property **IsClockwise** As Boolean

Description

Member of SubPath

The **IsClockwise** property returns **True** if a subpath's direction is predominantly clockwise.

The **IsClockwise** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.IsOnSubPath

Function **IsOnSubPath(***x As Double***,** *y As Double***, [**HotArea As Double = -1**])** As cdrPositionOfPointOverShape

Description

Member of SubPath

The **IsOnSubPath** method returns the position of a point relative to a subpath. The coordinate can be inside or outside the subpath, or it can be over the outline of the subpath.

The **IsOnSubPath** method returns a value of cdrPositionOfPointOverShape.

Parameter	Description
x	Specifies, in document units, the horizontal position of the point
y	Specifies, in document units, the vertical position of the point
HotArea	Specifies a restricted area on the subpath in which to evaluate the position of the point. This parameter is optional, and its default value is **-1**.

VBA example

The following VBA example creates a rectangle and tests where various point coordinates are located relative to that rectangle.

```
Public Sub Test()
 Dim s As Shape, spath As SubPath
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 s.ConvertToCurves
 Set spath = s.Curve.Subpaths(1)
 ShowOnCurve 1, 1, spath.IsOnSubPath(1, 1)
 ShowOnCurve 1, 0, spath.IsOnSubPath(1, 0)
 ShowOnCurve 1, 3, spath.IsOnSubPath(1, 3)
End Sub
Private Function ShowOnCurve(x As Double, y As Double, v As cdrPositionOfPointOverShape)
 Dim s As String
 s = "Point (" & x & "," & y & ") is "
 Select Case v
  Case cdrOutsideShape
   s = s & "outside the subpath"
  Case cdrOnMarginOfShape
   s = s & "over the outline"
  Case cdrInsideShape
   s = s & "inside the subpath"
 End Select
 MsgBox s
End Function
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.IsPointInside

Function **IsPointInside(***x As Double***,** *y As Double***)** As Boolean

Description

Member of SubPath

The **IsPointInside** method determines whether a specified point lies inside a closed subpath.

Parameter	Description
x	Specifies, in document units, the horizontal position of the point
y	Specifies, in document units, the vertical position of the point

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.IsRectOnEdge

Function **IsRectOnEdge(***x1 As Double*, *y1 As Double*, *x2 As Double*, *y2 As Double***)** As Boolean

Description

Member of SubPath

The **IsRectOnEdge** method determines whether a specified rectangle intersects the subpath.

Parameter	Description
x1	Specifies the first x-coordinate
y1	Specifies the first y-coordinate
x2	Specifies the second x-coordinate
y2	Specifies the second y-coordinate

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.LastSegment

Property **LastSegment** As Segment

Description

Member of SubPath

The **LastSegment** property returns the last **segment** of a subpath.

The **LastSegment** property returns a read-only value.

VBA example

The following VBA example converts, to a line, the last segment of the first subpath of the selected curve.

```
Sub Test()
 ActiveShape.Curve.Subpaths(1).LastSegment.Type = cdrLineSegment
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.Length

Property **Length** As Double

Description

Member of SubPath

The **Length** property returns the length, in document units, of a curve's subpath.

The **Length** property returns a read-only value.

VBA example

The following VBA example identifies the first subpath in the active shape. The length of this subpath, in document units, is displayed in a message box.

```
Sub App()
 MsgBox ActiveShape.Curve.Subpaths(1).Length
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.Move

Sub **Move([***DeltaX As Double***], [***DeltaY As Double***])**

Description

Member of SubPath

The **Move** method changes the position of a curve's subpath by applying the specified offset.

Parameter	Description
DeltaX	Specifies the horizontal offset. This parameter is optional, and its default value is **0**.
DeltaY	Specifies the vertical offset. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example moves each subpath of the selected curve randomly.

```
Sub Test()
 Dim spath As SubPath
 For Each spath In ActiveShape.Curve.Subpaths
  spath.Move Rnd() * 2 - 1, Rnd() * 2 - 1
 Next spath
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.Next

Function **Next()** As SubPath

Description

Member of SubPath

The **Next** method returns the next subpath of a curve.

VBA example

The following VBA example connects all open subpaths to each other, forming one larger closed subpath.

```
Sub Test()
 Dim crv As Curve
 Dim spath As SubPath, spath1 As SubPath
 Set crv = ActiveShape.Curve
 Set spath = crv.Subpaths(1)
 Do
  If Not spath.Closed Then
   Set spath1 = spath.Next
   Do
    If Not spath1.Closed Then Exit Do
    Set spath1 = spath1.Next
   Loop
   spath.EndNode.ConnectWith spath1.StartNode
  Else
   Set spath = spath.Next
   If spath.Index = 1 Then Exit Do
  End If
 Loop
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.Nodes

Property **Nodes** As Nodes

Description

Member of SubPath

The **Nodes** property returns a Nodes collection that contains all the nodes on a subpath.

The **Nodes** property returns a read-only value.

VBA example

The following VBA example converts the type of all the nodes on the first subpath to symmetrical.

```
Sub Test()
 Dim n As Node
 For Each n In ActiveShape.Curve.Subpaths(1).Nodes
  n.Type = cdrSymmetricalNode
 Next n
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.Parent

Property **Parent** As Curve

Description

Member of SubPath

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.PositionX

Property **PositionX** As Double

Description

Member of SubPath

The **PositionX** property returns or specifies the horizontal position, or x-coordinate, of a subpath's starting point, treating the subpath as a separate object. This position is relative to the reference point specified by the Document.ReferencePoint property.

VBA example

The following VBA example aligns all subpaths horizontally so that their left sides are **2**" from the left edge of the page.

```
Sub Test()
 Dim sp As SubPath
 ActiveDocument.ReferencePoint = cdrTopLeft
 For Each sp In ActiveShape.Curve.Subpaths
  sp.PositionX = 2
 Next sp
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.PositionY

Property **PositionY** As Double

Description

Member of SubPath

The **PositionY** property returns or specifies the vertical position, or y-coordinate, of a subpath's starting point, treating the subpath as a separate object. The position is relative to the reference point specified by the Document.ReferencePoint property.

VBA example

The following VBA example aligns all subpaths vertically so that their top sides are **3** document units from the bottom of the page:

```
Sub Test()
 Dim sp As SubPath
 ActiveDocument.ReferencePoint = cdrTopLeft
 For Each sp In ActiveShape.Curve.Subpaths
  sp.PositionY = 3
 Next sp
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.Previous

Function **Previous()** As SubPath

Description

Member of SubPath

The **Previous** method returns the previous subpath in a curve.

VBA example

The following VBA example connects all open subpaths to each other, forming one larger closed subpath.

```
Sub Test()
 Dim crv As Curve
 Dim spath As SubPath, spath1 As SubPath
 Set crv = ActiveShape.Curve
 Set spath = crv.Subpaths(1)
 Do
  If Not spath.Closed Then
   Set spath1 = spath.Next
   Do
    If Not spath1.Closed Then Exit Do
    Set spath1 = spath1.Next
   Loop
   spath.EndNode.ConnectWith spath1.StartNode
  Else
   Set spath = spath.Next
   If spath.Index = 1 Then Exit Do
  End If
 Loop
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.PutCurveInfo

Function **PutCurveInfo(**Source() As CurveElement**, [**NumElements As Long = -1**])** As Long

Description

Member of SubPath

The **PutCurveInfo** method replaces the current subpath with specified node information.

Parameter	Description
Source	Specifies the source
NumElements	Specifies the number of valid elements to use. If nothing is specified, then all valid elements are used. This parameter is optional, and its default value is **-1**.

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.ReverseDirection

Sub **ReverseDirection()**

Description

Member of SubPath

The **ReverseDirection** method reverses the direction of a subpath without affecting other subpaths in the curve. This is accomplished by reversing the order of the index numbers associated with the nodes.

VBA example

The following VBA example creates a curve object containing **10** subpaths. It applies end arrowheads to them and then reverses the direction of the third subpath.

```
Sub Test()
 Dim sr As New ShapeRange
 Dim s As Shape
 Dim n As Long
 For n = 1 To 10
  sr.Add ActiveLayer.CreateLineSegment(0, n / 2, 5, n / 2)
 Next n
 Set s = sr.Combine
 s.Outline.EndArrow = ArrowHeads(2)
 s.Curve.Subpaths(3).ReverseDirection
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.Segments

Property **Segments** As Segments

Description

Member of SubPath

The **Segments** property returns a Segments collection, which contains all the segments of a subpath.

The **Segments** property returns a read-only value.

VBA example

The following VBA example converts, to lines, all segments in the first subpath.

```
Sub Test()
 Dim seg As Segment
 For Each seg In ActiveShape.Curve.Subpaths(1).Segments
  seg.Type = cdrLineSegment
 Next seg
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.Selection

Function **Selection()** As NodeRange

Description

Member of SubPath

The **Selection** method returns a node range (or NodeRange object) containing all the selected nodes on a subpath.

- The **Shape** tool must be selected.

VBA example

The following VBA example displays the number of nodes selected in the first subpath of the active curve.

```
Sub Test()
 Dim nr As NodeRange
 Set nr = ActiveShape.Curve.Subpaths(1).Selection
 MsgBox "There are " & nr.Count & " nodes selected in the first subpath"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.SetPosition

Sub **SetPosition(***PositionX As Double***,** *PositionY As Double***)**

Description

Member of SubPath

The **SetPosition** method sets the horizontal and vertical positions of a subpath head, treating the subpath as a separate object.

Parameter	Description
PositionX	Specifies, in document units, the x-coordinate of the subpath's starting point
PositionY	Specifies, in document units, the y-coordinate of the subpath's starting point

VBA example

The following VBA example sets the horizontal and vertical positions of the first subpath in the active curve.

```
Sub App()
 With ActiveShape.Curve.Subpaths(1)
  .SetPosition 4, 4
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.SizeHeight

Property **SizeHeight** As Double

Description

Member of SubPath

The **SizeHeight** property returns, in document units, the vertical size of a subpath, treating the subpath as a separate object.

The **SizeHeight** property returns a read-only value.

VBA example

The following VBA example draws a bounding rectangle around each subpath in the selected curve.

```
Sub Test()
 Dim sp As SubPath
 Dim x As Double, y As Double
 ActiveDocument.ReferencePoint = cdrBottomLeft
 For Each sp In ActiveShape.Curve.Subpaths
  sp.GetPosition x, y
  ActiveLayer.CreateRectangle2 x, y, sp.SizeWidth, sp.SizeHeight
 Next sp
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.SizeWidth

Property **SizeWidth** As Double

Description

Member of SubPath

The **SizeWidth** property returns, in document units, the horizontal size of a subpath, treating the subpath as a separate object.

The **SizeWidth** property returns a read-only value.

VBA example

The following VBA example draws a bounding rectangle around each subpath in the selected curve.

```
Sub Test()
 Dim sp As SubPath
 Dim x As Double, y As Double
 ActiveDocument.ReferencePoint = cdrBottomLeft
 For Each sp In ActiveShape.Curve.Subpaths
  sp.GetPosition x, y
  ActiveLayer.CreateRectangle2 x, y, sp.SizeWidth, sp.SizeHeight
 Next sp
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPath.StartNode

Property **StartNode** As Node

Description

Member of SubPath

The **StartNode** property returns the first node of a subpath.

The **StartNode** property returns a read-only value.

VBA example

The following VBA example connects all open subpaths to each other, forming a single and larger closed subpath.

```
Sub Test()
 Dim crv As Curve
 Dim spath As SubPath, spath1 As SubPath
 Set crv = ActiveShape.Curve
 Set spath = crv.Subpaths(1)
 Do
  If Not spath.Closed Then
   Set spath1 = spath.Next
   Do
    If Not spath1.Closed Then Exit Do
    Set spath1 = spath1.Next
   Loop
   spath.EndNode.ConnectWith spath1.StartNode
  Else
   Set spath = spath.Next
   If spath.Index = 1 Then Exit Do
  End If
 Loop
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPaths

Properties

Description

The **SubPaths** class represents a collection of subpaths (or SubPath objects) in a curve.

Copyright 2014 Corel Corporation. All rights reserved.

SubPaths.Application

Property **Application** As Application

Description

Member of SubPaths

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

SubPaths.Count

Property **Count** As Long

Description

Member of SubPaths

The **Count** property returns the number of subpaths in a SubPaths collection.

The **Count** property returns a read-only value.

VBA example

The following VBA example extracts each subpath from a curve and changes the color of each extracted subpath.

```
Sub Test()
 Dim spath As SubPath
 Dim s As Shape, sExt As Shape
 Dim i As Long
 Set s = ActiveShape
 If s.Curve.Subpaths.Count < 2 Then Exit Sub
 For i = s.Curve.Subpaths.Count To 1 Step -1
  Set spath = s.Curve.Subpaths(i)
  Set sExt = spath.Extract(s)
  sExt.Outline.Width = 0.01
  sExt.Outline.Color = ActivePalette.Color(13 + i)
 Next i
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPaths.First

Property **First** As SubPath

Description

Member of SubPaths

The **First** property returns the first subpath in a SubPaths collection.

The **First** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SubPaths.Item

Property **Item(***Index As Long***)** As SubPath

Description

Member of SubPaths

The **Item** property returns a specified subpath.

Item is the default property of the SubPaths class, and its reference can be omitted when you are accessing items in a **SubPaths** collection. For example, **SubPaths.Item(2)** is the same as **SubPaths(2)** — they both reference the second subpath in the collection.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each member of the **SubPaths** collection

VBA example 1

The following VBA example randomly moves each subpath in the selected curve.

```
Sub Test()
 Dim spath As SubPath
 Dim s As Shape
 Dim i As Long
 Set s = ActiveShape
 For i = 1 To s.Curve.Subpaths.Count
  Set spath = s.Curve.Subpaths(i)
  spath.Move Rnd() * 2 - 1, Rnd() * 2 - 1
 Next i
End Sub
```

VBA example 2

The following VBA example performs the same procedure as the previous example. However, instead of using a **For Next** command, it uses the **For Each** command in Visual Basic to iterate through all subpaths in the shape.

```
Sub Test()
 Dim spath As SubPath
 For Each spath In ActiveShape.Curve.Subpaths
  spath.Move Rnd() * 2 - 1, Rnd() * 2 - 1
 Next spath
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SubPaths.Last

Property **Last** As SubPath

Description

Member of SubPaths

The **Last** property returns the last subpath in a SubPaths collection.

The **Last** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SubPaths.Parent

Property **Parent** As Curve

Description

Member of SubPaths

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Symbol

Properties Methods

Description

Copyright 2014 Corel Corporation. All rights reserved.

Symbol.Definition

Property **Definition** As SymbolDefinition

Description

Member of Symbol

The **Definition** property specifies the definition of a symbol.

The **Definition** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Symbol.RevertToShapes

Function **RevertToShapes()** As ShapeRange

Description

Member of Symbol

The **RevertToShapes** method converts a symbol instance into one or more shapes.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition

Properties Methods

Description

The **SymbolDefinition** class represents the definition of a symbol.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.BreakLink

Sub **BreakLink()**

Description

Member of SymbolDefinition

The **BreakLink** method breaks the link to an external library, making the symbol definition local.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.Copy

Sub **Copy()**

Description

Member of SymbolDefinition

The **Copy** method copies a symbol definition to the Clipboard.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.Delete

Sub **Delete()**

Description

Member of SymbolDefinition

The **Delete** method deletes a symbol definition from the current library

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.Description

Property **Description** As String

Description

Member of SymbolDefinition

The **Description** property specifies the description of a symbol definition.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.Duplicate

Function **Duplicate([***Name As String***])** As SymbolDefinition

Description

Member of SymbolDefinition

The **Duplicate** method duplicates a symbol definition.

Parameter	Description
Name	Specifies the name of the symbol. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.Editable

Property **Editable** As Boolean

Description

Member of SymbolDefinition

The **Editable** property returns **True** if a symbol definition can be modified.

The **Editable** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.EnterEditMode

Sub **EnterEditMode()**

Description

Member of SymbolDefinition

The **EnterEditMode** method initiates the mode for editing a symbol definition.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.FixLink

Sub **FixLink(***LibraryPath As String***)**

Description

Member of SymbolDefinition

The **FixLink** method restores a broken link from a symbol to an external library.

Parameter	Description
LibraryPath	Specifies the path of the external library

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.HasBrokenLinks

Property **HasBrokenLinks** As Boolean

Description

Member of SymbolDefinition

The **HasBrokenLinks** property returns **True** if any (nested) sub-symbol has a broken link to its external library.

The **HasBrokenLinks** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.HasLinks

Property **HasLinks** As Boolean

Description

Member of SymbolDefinition

The **HasLinks** property returns **True** if any (nested) sub-symbol is linked to an external library.

The **HasLinks** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.HasUpdatedLinks

Property **HasUpdatedLinks** As Boolean

Description

Member of SymbolDefinition

The **HasUpdatedLinks** property returns **True** if a symbol is linked to an external library that needs to be updated.

returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.InstanceCount

Property **InstanceCount** As Long

Description

Member of SymbolDefinition

The **InstanceCount** property returns the number of instances of a symbol that are inserted into the current document.

The **InstanceCount** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.Instances

Property **Instances** As ShapeRange

Description

Member of SymbolDefinition

The **Instances** property returns a collection of all instances of a symbol in the current document.

The **Instances** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.IsLinkBroken

Property **IsLinkBroken** As Boolean

Description

Member of SymbolDefinition

The **IsLinkBroken** property returns **True** if the external library for a symbol is missing.

The **IsLinkBroken** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.IsLinkUpdated

Property **IsLinkUpdated** As Boolean

Description

Member of SymbolDefinition

The **IsLinkUpdated** property returns **True** if a symbol definition must be updated from its external library.

The **IsLinkUpdated** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.LeaveEditMode

Sub **LeaveEditMode()**

Description

Member of SymbolDefinition

The **LeaveEditMode** method exits the mode for editing a symbol definition.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.Linked

Property **Linked** As Boolean

Description

Member of SymbolDefinition

The **Linked** property returns **True** if a symbol belongs to an external library.

The **Linked** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.LinkLibraryPath

Property **LinkLibraryPath** As String

Description

Member of SymbolDefinition

The **LinkLibraryPath** property returns the path to the library from which a symbol is inserted.

The **LinkLibraryPath** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.Name

Property **Name** As String

Description

Member of SymbolDefinition

The **Name** property specifies the name of a symbol definition.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.Nested

Property **Nested** As Boolean

Description

Member of SymbolDefinition

The **Nested** property returns **True** if a symbol is nested (that is, if it contains sub-symbols).

The **Nested** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.NestedSymbols

Property **NestedSymbols** As SymbolDefinitions

Description

Member of SymbolDefinition

The **NestedSymbols** property returns a collection of all (nested) sub-symbols. This collection is returned as a SymbolDefinitions object.

The **NestedSymbols** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.Type

Property **Type** As cdrSymbolType

Description

Member of SymbolDefinition

The **Type** property returns the type for a symbol.

The **Type** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinition.UpdateLinks

Sub **UpdateLinks()**

Description

Member of SymbolDefinition

The **UpdateLinks** method updates a symbol definition from its external library.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinitions

Properties

Description

The **SymbolDefinitions** class represents a collection of all symbol definitions (or SymbolDefinition objects) in a document.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinitions.Count

Property **Count** As Long

Description

Member of SymbolDefinitions

The **Count** property returns the number of symbol definitions (or SymbolDefinition objects) in a SymbolDefinitions collection.

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolDefinitions.Item

Property **Item(***IndexOrName As Variant***)** As SymbolDefinition

Description

Member of SymbolDefinitions

The **Item** property returns the specified symbol definition (or SymbolDefinition object) from a SymbolDefinitions collection. It is the default property of the **SymbolDefinitions** class.

The **Item** property returns a read-only value.

Parameter	Description
IndexOrName	Specifies the symbol definition by its index number or name: • **Index** — Specifies the preset placeholder that uniquely identifies each member of the **SymbolDefinitions** collection • **Name** — Specifies the string that uniquely identifies each symbol definition

Copyright 2014 Corel Corporation. All rights reserved.

SymbolLibraries

Properties Methods

Description

The **SymbolLibraries** class represents a collection of all the symbol libraries (or SymbolLibrary objects) in a document.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolLibraries.Add

Function **Add(***FileName As String***, [**CopyLocally As Boolean = False**])** As SymbolLibrary

Description

Member of SymbolLibraries

The **Add** method adds a new symbol library to a SymbolLibraries collection.

Parameter	Description
FileName	Specifies the filename
CopyLocally	Specifies whether to make a local copy. This parameter is optional, and its default value is **False**.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolLibraries.AddFromFolder

Function **AddFromFolder(***Folder As String***, [**Recursive As Boolean = False**], [**CopyLocally As Boolean = False**])** As Long

Description

Member of SymbolLibraries

The **AddFromFolder** method adds the symbol libraries in a specified folder to a SymbolLibraries collection.

Parameter	Description
Folder	Specifies the folder
Recursive	Specifies whether to make the addition recursively. This parameter is optional, and its default value is **False**.
CopyLocally	Specifies whether to make a local copy. This parameter is optional, and its default value is **False**.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolLibraries.Count

Property **Count** As Long

Description

Member of SymbolLibraries

The **Count** property returns the number of symbol libraries in a SymbolLibraries collection

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolLibraries.Item

Property **Item(***IndexOrName As Variant***)** As SymbolLibrary

Description

Member of SymbolLibraries

The **Item** property returns a specified symbol library from a SymbolLibraries collection. It is the default property of the **SymbolLibraries** class.

The **Item** property returns a read-only value.

Parameter	Description
IndexOrName	Specifies the symbol library by its index number or name: • **Index** — Specifies the preset placeholder that uniquely identifies each member of the **SymbolLibraries** collection • **Name** — Specifies the string that uniquely identifies each symbol library

Copyright 2014 Corel Corporation. All rights reserved.

SymbolLibrary

Properties Methods

Description

The **SymbolLibrary** class represents a symbol library.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolLibrary.Delete

Sub **Delete()**

Description

Member of SymbolLibrary

The **Delete** method deletes an external symbol library.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolLibrary.FilePath

Property **FilePath** As String

Description

Member of SymbolLibrary

The **FilePath** property returns the full filename of and the path to a symbol-library file.

The **FilePath** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolLibrary.Name

Property **Name** As String

Description

Member of SymbolLibrary

The **Name** property returns the name of a symbol library.

The **Name** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolLibrary.Paste

Function **Paste([***Name As String***])** As SymbolDefinition

Description

Member of SymbolLibrary

The **Paste** method pastes a copied symbol from the Clipboard into the current (local) symbol library.

Parameter	Description
Name	Specifies the name. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolLibrary.PurgeUnusedSymbols

Sub **PurgeUnusedSymbols()**

Description

Member of SymbolLibrary

The **PurgeUnusedSymbols** method removes from a local symbol library all the symbols not used in the current document.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolLibrary.ReadOnly

Property **ReadOnly** As Boolean

Description

Member of SymbolLibrary

The **ReadOnly** property returns **True** if a symbol library is read-only.

The **ReadOnly** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SymbolLibrary.Symbols

Property **Symbols** As SymbolDefinitions

Description

Member of SymbolLibrary

The **Symbols** property returns a collection of all of the symbols in a symbol library.

The **Symbols** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

SystemPrinters

Properties

Description

The **SystemPrinters** class represents all installed printers.

Copyright 2014 Corel Corporation. All rights reserved.

SystemPrinters.Count

Property **Count** As Long

Description

Member of SystemPrinters

The **Count** property returns the number of printers in a SystemPrinters collection.

The **Count** property returns a read-only value.

VBA example

The following VBA example displays the number of installed printers.

```
Sub Test()
 MsgBox "There are " & Printers.Count & " printers installed on your system"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SystemPrinters.Default

Property **Default** As Printer

Description

Member of SystemPrinters

The **Default** property returns a read-only reference to the default printer.

VBA example

The following VBA example displays the name of the default printer.

```
Sub Test()
 Dim Prn As Printer
 Set Prn = Printers.Default
 MsgBox "Your default printer is: " & Prn.Name
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

SystemPrinters.Item

Property **Item(***nIndex As Long***)** As Printer

Description

Member of SystemPrinters

The **Item** property returns a Printer value, which specifies one of the printers in a SystemPrinters collection.

Item is the default property of the **SystemPrinters** class, and its reference can be omitted when you are accessing items in a **SystemPrinters** collection. For example, **Printers.Item(2)** is the same as **Printers(2)** — they both reference the second printer in the collection.

The **Item** property returns a read-only value.

Parameter	Description
nIndex	Specifies the printer by its index number

VBA example

The following VBA example lists all installed printers.

```
Sub Test()
 Dim intCounter As Integer
 Dim Prn As Printer
 Dim s As String
  For intCounter = 1 To Printers.Count
   Set Prn = Printers(intCounter)
   s = s & Prn.Name & vbCr
  Next intCounter
 MsgBox "The following printers are installed on your system: " & vbCr & vbCr & s
 Set Prn = Nothing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TableBorders

Properties Methods

Description

The **TableBorders** class represents the border settings of a table.

Copyright 2014 Corel Corporation. All rights reserved.

TableBorders.All

Property **All** As IVGOutline

Description

Member of TableBorders

The **All** property returns all table borders.

The **All** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableBorders.AreIdentical

Property **AreIdentical([**BorderKind As cdrTableBorder = cdrTableBorderAll**])** As Boolean

Description

Member of TableBorders

The **AreIdentical** property specifies whether specified table borders are identical.

The **AreIdentical** property returns a read-only value.

Parameter	Description
BorderKind	Specifies the border type. This is parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

TableBorders.Bottom

Property **Bottom** As IVGOutline

Description

Member of TableBorders

The **Bottom** property returns the bottom of a table border.

The **Bottom** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableBorders.Combined

Property **Combined(**BorderKind As cdrTableBorder = cdrTableBorderAll**)** As Boolean

Description

Member of TableBorders

The **Combined** property returns combined table borders.

The **Combined** property returns a read-only value.

Parameter	Description
BorderKind	Specifies the border type

Copyright 2014 Corel Corporation. All rights reserved.

TableBorders.Horizontal

Property **Horizontal** As IVGOutline

Description

Member of TableBorders

The **Horizontal** property returns the horizontal table border.

The **Horizontal** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableBorders.Left

Property **Left** As IVGOutline

Description

Member of TableBorders

The **Left** property returns the left table border.

The **Left** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableBorders.Right

Property **Right** As IVGOutline

Description

Member of TableBorders

The **Right** property returns the right table border.

The **Right** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableBorders.SetBorders

Sub **SetBorders**(BorderKind As cdrTableBorder, *Border As IVGOutline*)

Description

Member of TableBorders

The **SetBorder** method adjusts a table border.

Parameter	Description
BorderKind	Specifies the border type
Border	Specifies the border settings

Copyright 2014 Corel Corporation. All rights reserved.

TableBorders.Top

Property **Top** As IVGOutline

Description

Member of TableBorders

The **Top** property returns the top table border.

The **Top** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableBorders.Vertical

Property **Vertical** As IVGOutline

Description

Member of TableBorders

The **Vertical** property specifies the vertical table border.

The **Vertical** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell

Properties Methods

Description

The **TableCell** class represents the settings of a table cell.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.AddToSelection

Sub **AddToSelection()**

Description

Member of TableCell

The **AddToSelection** method adds a table cell to a selection.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.BorderCurve

Property **BorderCurve** As IVGCurve

Description

Member of TableCell

The **BorderCurve** property returns the curve of a cell border.

The **BorderCurve** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.Borders

Property **Borders** As TableBorders

Description

Member of TableCell

The **Borders** property returns the borders of a table cell.

The **Borders** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.BottomMargin

Property **BottomMargin** As Double

Description

Member of TableCell

The BottomMargin property returns the bottom margin of a table cell.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.CellAbove

Property **CellAbove** As TableCell

Description

Member of TableCell

The **CellAbove** property returns the table cell above a given cell.

The **CellAbove** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.CellBelow

Property **CellBelow** As TableCell

Description

Member of TableCell

The **CellBelow** property returns the table cell below a given cell.

The **CellBelow** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.CellToLeft

Property **CellToLeft** As TableCell

Description

Member of TableCell

The **CellToLeft** property returns the table cell to the left of a given cell.

The **CellToLeft** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.CellToRight

Property **CellToRight** As TableCell

Description

Member of TableCell

The **CellToRight** property returns the table cell to the right of a given cell.

The **CellToRight** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.Column

Property **Column** As TableColumn

Description

Member of TableCell

The **Column** property returns the column to which a table cell belongs.

The **Column** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.ColumnIndex

Property **ColumnIndex** As Long

Description

Member of TableCell

The **ColumnIndex** property returns the index number of the column to which a table cell belongs.

The **ColumnIndex** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.ColumnSpan

Property **ColumnSpan** As Long

Description

Member of TableCell

The **ColumnSpan** property returns the column span of a table cell.

The **ColumnSpan** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.EqualMargins

Property **EqualMargins** As Boolean

Description

Member of TableCell

The **EqualMargins** property specifies equal-sized margins for a table cell.

The **EqualMargins** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.Fill

Property **Fill** As IVGFill

Description

Member of TableCell

The **Fill** property specifies the fill of a table cell.

The **Fill** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.Height

Property **Height** As Double

Description

Member of TableCell

The **Height** property returns the height of a table cell.

The **Height** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.LeftMargin

Property **LeftMargin** As Double

Description

Member of TableCell

The **LeftMargin** property returns the left margin of a table cell.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.Merged

Property **Merged** As Boolean

Description

Member of TableCell

The **Merged** property returns whether a table cell is merged.

The **Merged** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.PlaceShape

Sub **PlaceShape(***Shape As IVGShape***, [**CenterInCell As Boolean = False**])**

Description

Member of TableCell

The **PlaceShape** method places a shape in a table cell.

Parameter	Description
Shape	Specifies the shape
CenterInCell	Specifies whether to center the shape in the cell. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.PlaceShapeRange

Sub **PlaceShapeRange(***ShapeRange As IVGShapeRange***, [**CenterInCell As Boolean = False**])**

Description

Member of TableCell

The **PlaceShapeRange** method places a shape range in a table cell.

Parameter	Description
ShapeRange	Specifies the shape range
CenterInCell	Specifies whether to center the shape in the cell This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.RightMargin

Property **RightMargin** As Double

Description

Member of TableCell

The **RightMargin** property returns the right margin of a table cell.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.Row

Property **Row** As TableRow

Description

Member of TableCell

The **Row** property returns the row to which a table cell belongs.

The **Row** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.RowIndex

Property **RowIndex** As Long

Description

Member of TableCell

The **RowIndex** property specifies the index number of the row to which a table cell belongs.

The **RowIndex** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.RowSpan

Property **RowSpan** As Long

Description

Member of TableCell

The **RowSpan** property returns the row span of a table cell.

The **RowSpan** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.Select

Sub **Select()**

Description

Member of TableCell

The **Select** method selects a table cell.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.Selected

Property **Selected** As Boolean

Description

Member of TableCell

The **Selected** property returns whether a table cell is selected.

The **Selected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.SetAllMargins

Sub **SetAllMargins**(*Margin As Double*)

Description

Member of TableCell

The **SetAllMargins** method simultaneously sets all margins for a table cell.

Parameter	Description
Margin	Specifies the margin value

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.SetMargins

Sub **SetMargins**(*Left As Double*, *Top As Double*, *Right As Double*, *Bottom As Double*)

Description

Member of TableCell

The SetMargins method individually sets each margin for a table cell.

Parameter	Description
Left	Specifies the left margin value
Top	Specifies the top margin value
Right	Specifies the right margin value
Bottom	Specifies the bottom margin value

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.Shapes

Property **Shapes** As IVGShapes

Description

Member of TableCell

The **Shapes** property associates a shape with a table cell.

The **Shapes** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.SpanningCell

Property **SpanningCell** As TableCell

Description

Member of TableCell

The **SpanningCell** property returns whether a table cell is a spanning cell.

The **SpanningCell** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.Split

Sub **Split**(*NumColumns As Long*, *NumRows As Long*)

Description

Member of TableCell

The **Split** method splits a table cell.

Parameter	Description
NumColumns	Specifies the number of columns in which to split the cell
NumRows	Specifies the number of rows in which to split the cell

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.TextShape

Property **TextShape** As IVGShape

Description

Member of TableCell

The **TextShape** property associates a text shape with a table cell.

The **TextShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.TopMargin

Property **TopMargin** As Double

Description

Member of TableCell

The **TopMargin** property returns the top margin of a table cell.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.Unmerge

Sub **Unmerge()**

Description

Member of TableCell

The **Unmerge** method unmerges a table cell.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.Visible

Property **Visible** As Boolean

Description

Member of TableCell

The **Visible** property returns whether a table cell is visible.

The **Visible** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCell.Width

Property **Width** As Double

Description

Member of TableCell

The **Width** property returns the width of a table cell.

The **Width** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange

Properties Methods

Description

The **TableCellRange** class represents the settings for an array (or range) of table cells.

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.AddCell

Sub **AddCell(**Cell As TableCell**)**

Description

Member of TableCellRange

The **AddCell** method adds a cell to a range of table cells.

Parameter	Description
Cell	Specifies the cell to add

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.AddColumn

Sub **AddColumn(**Column As TableColumn**)**

Description

Member of TableCellRange

The **AddColumn** method adds a column to a range of table cells.

Parameter	Description
Column	Specifies the column to add

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.AddRange

Sub **AddRange(**Range As TableCellRange**)**

Description

Member of TableCellRange

The **AddRange** method adds a range of table cells to another cell range

Parameter	Description
Range	Specifies the range to add

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.AddRow

Sub **AddRow(**Row As TableRow**)**

Description

Member of TableCellRange

The **AddRow** method adds a row to a range of table cells.

Parameter	Description
Row	Specifies the row to add

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.AddToSelection

Sub **AddToSelection()**

Description

Member of TableCellRange

The **AddToSelection** method adds a range of table cells to a selection.

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.ApplyFill

Sub **ApplyFill(***Fill As IVGFill***)**

Description

Member of TableCellRange

The **ApplyFill** method applies a fill to a range of table cells.

Parameter	Description
Fill	Specifies the fill

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.Borders

Property **Borders** As TableBorders

Description

Member of TableCellRange

The **Borders** property returns the borders for a range of table cells.

The **Borders** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.CanMerge

Property **CanMerge** As Boolean

Description

Member of TableCellRange

The **CanMerge** property returns whether a range of table cells can be merged.

The **CanMerge** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.Columns

Property **Columns** As TableColumns

Description

Member of TableCellRange

The **Columns** property returns the columns in which a range of table cells are located.

The **Columns** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.Count

Property **Count** As Long

Description

Member of TableCellRange

The **Count** property returns the number of table cells in a cell range.

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.IsRectangular

Property **IsRectangular** As Boolean

Description

Member of TableCellRange

The **IsRectangular** property returns whether a range of table cells is rectangular.

The **IsRectangular** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.Item

Property **Item(***Index As Long***)** As TableCell

Description

Member of TableCellRange

The **Item** property returns the index number of a table cell in a cell range. Each table cell is identified by an index number represented in base 1. For example, **TableCellRange(5)** refers to the fifth table cell in the cell range.

Item is the default property of the TableCellRange class, and its reference can be omitted when you are accessing items in a cell range. For example, **TableCellRange.Item(5)** is the same as **TableCellRange(5)** — they both reference the fifth table cell in the cell range.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each member of the cell range

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.Merge

Sub **Merge()**

Description

Member of TableCellRange

The **Merge** method merges a range of table cells.

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.Remove

Sub **Remove(***Index As Long***)**

Description

Member of TableCellRange

The **Remove** method deletes a range of table cells.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each cell range

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.RemoveCell

Sub **RemoveCell(**Cell As TableCell**)**

Description

Member of TableCellRange

The **RemoveCell** method removes a table cell from a cell range.

Parameter	Description
Cell	Specifies the table cell to remove

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.RemoveRange

Sub **RemoveRange(**Range As TableCellRange**)**

Description

Member of TableCellRange

The **RemoveRange** method deletes a range of table cells from a cell range.

Parameter	Description
Range	Specifies the range of table cells to remove

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.Rows

Property **Rows** As TableRows

Description

Member of TableCellRange

The **Rows** property specifies the rows in which a range of table cells are located.

The **Rows** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.Select

Sub **Select()**

Description

Member of TableCellRange

The **Select** method selects a range of table cells.

Copyright 2014 Corel Corporation. All rights reserved.

TableCellRange.Unmerge

Sub **Unmerge()**

Description

Member of TableCellRange

The **Unmerge** method unmerges a range of table cells.

Copyright 2014 Corel Corporation. All rights reserved.

TableCells

Properties Methods

Description

The **TableCells** class represents a collection of table cells (or TableCell objects).

Copyright 2014 Corel Corporation. All rights reserved.

TableCells.All

Property **All** As TableCellRange

Description

Member of TableCells

The **All** property returns a collection of all table cells.

The **All** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCells.AllExcluding

Function **AllExcluding(***IndexArray() As Variant***)** As TableCellRange

Description

Member of TableCells

The **AllExcluding** method specifies all table cells except the specified cell range.

Parameter	Description
IndexArray	Specifies the index number of the cell range

Copyright 2014 Corel Corporation. All rights reserved.

TableCells.Count

Property **Count** As Long

Description

Member of TableCells

The **Count** property returns the number of table cells in a TableCells collection.

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableCells.Item

Property **Item(***Index As Long***)** As TableCell

Description

Member of TableCells

The **Item** property returns the index number of a table cell in a TableCells collection. Each table cell is identified by an index number represented in base 1. For example, **TableCells(5)** refers to the fifth table cell in a **TableCells** collection.

Item is the default property of the **TableCells** class, and its reference can be omitted when you are accessing items in a **TableCells** collection. For example, **TableCells.Item(5)** is the same as **TableCells(5)** — they both reference the fifth table cell in the collection.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each member of the **TableCells** collection

Copyright 2014 Corel Corporation. All rights reserved.

TableCells.Range

Function **Range(***IndexArray() As Variant***)** As TableCellRange

Description

Member of TableCells

The **Range** method specifies a range of table cells.

Parameter	Description
IndexArray	Specifies the range of table cells

Copyright 2014 Corel Corporation. All rights reserved.

TableColumn

Properties Methods

Description

The **TableColumn** class represents the settings for a table column.

Copyright 2014 Corel Corporation. All rights reserved.

TableColumn.AddToSelection

Sub **AddToSelection()**

Description

Member of TableColumn

The **AddToSelection** method adds a table column to a selection.

Copyright 2014 Corel Corporation. All rights reserved.

TableColumn.Cells

Property **Cells** As TableCells

Description

Member of TableColumn

The **Cells** property returns the cells in a table column.

The **Cells** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableColumn.Delete

Sub **Delete()**

Description

Member of TableColumn

The **Delete** method deletes a column from a table.

Copyright 2014 Corel Corporation. All rights reserved.

TableColumn.Index

Property **Index** As Long

Description

Member of TableColumn

The **Index** property returns the index number of a table column.

The **Index** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableColumn.IsFirst

Property **IsFirst** As Boolean

Description

Member of TableColumn

The **IsFirst** property returns whether a column is the first one in a table.

The **IsFirst** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableColumn.IsLast

Property **IsLast** As Boolean

Description

Member of TableColumn

The **IsLast** property returns whether a column is the last one in a table.

The **IsLast** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableColumn.Next

Property **Next** As TableColumn

Description

Member of TableColumn

The **Next** property returns the next column in a table.

The **Next** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableColumn.Previous

Property **Previous** As TableColumn

Description

Member of TableColumn

The **Previous** property returns the previous column in a table.

The **Previous** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableColumn.Select

Sub **Select()**

Description

Member of TableColumn

The **Select** method selects a table column.

Copyright 2014 Corel Corporation. All rights reserved.

TableColumn.SetWidth

Sub **SetWidth(***Width As Double***,** *ResizeTable As Boolean***)**

Description

Member of TableColumn

The **SetWidth** method sets the width of a table column.

Parameter	Description
Width	Specifies the width of the column
ResizeTable	Specifies whether to resize the table

Copyright 2014 Corel Corporation. All rights reserved.

TableColumn.Width

Property **Width** As Double

Description

Member of TableColumn

The **Width** property returns or sets the width of a table column.

Copyright 2014 Corel Corporation. All rights reserved.

TableColumns

Properties Methods

Description

The **TableColumns** class represents a collection of table columns (or TableColumn objects).

Copyright 2014 Corel Corporation. All rights reserved.

TableColumns.AddToSelection

Sub **AddToSelection()**

Description

Member of TableColumns

The **AddToSelection** method adds multiple table columns to a selection.

Copyright 2014 Corel Corporation. All rights reserved.

TableColumns.Cells

Property **Cells** As TableCells

Description

Member of TableColumns

The **Cells** property returns all the cells in a TableColumns collection.

The **Cells** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableColumns.Count

Property **Count** As Long

Description

Member of TableColumns

The **Count** property returns the number of table columns in a TableColumns collection.

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableColumns.DistributeWidth

Sub **DistributeWidth()**

Description

Member of TableColumns

The **DistributeWidth** method evenly distributes the width of a table among the table columns.

Copyright 2014 Corel Corporation. All rights reserved.

TableColumns.First

Property **First** As TableColumn

Description

Member of TableColumns

The **First** property returns the first column in a TableColumns collection.

The **First** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableColumns.Item

Property **Item(***Index As Long***)** As TableColumn

Description

Member of TableColumns

The **Item** property returns the index number of a table column in a TableColumns collection. Each table column is identified by an index number represented in base 1. For example, **TableColumns(5)** refers to the fifth table column in the collection.

Item is the default property of the **TableColumns** class, and its reference can be omitted when you are accessing items in a **TableColumns** collection. For example, **TableColumns.Item(5)** is the same as **TableColumns(5)** — they both reference the fifth table column in the collection.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each member of the **TableColumns** collection

Copyright 2014 Corel Corporation. All rights reserved.

TableColumns.Last

Property **Last** As TableColumn

Description

Member of TableColumns

The **Last** property returns the last column in a TableColumns collection.

The **Last** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableColumns.Select

Sub **Select()**

Description

Member of TableColumns

The **TableColumns** method selects multiple table columns.

Copyright 2014 Corel Corporation. All rights reserved.

TableRow

Properties Methods

Description

The **TableRow** class represents the settings for a table row.

Copyright 2014 Corel Corporation. All rights reserved.

TableRow.AddToSelection

Sub **AddToSelection()**

Description

Member of TableRow

The **AddToSelection** method adds a table row to a selection.

Copyright 2014 Corel Corporation. All rights reserved.

TableRow.Cells

Property **Cells** As TableCells

Description

Member of TableRow

The **Cells** property returns the cells in a table row.

The **Cells** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableRow.Delete

Sub **Delete()**

Description

Member of TableRow

The **Delete** method deletes a row from a table.

Copyright 2014 Corel Corporation. All rights reserved.

TableRow.Height

Property **Height** As Double

Description

Member of TableRow

The **Height** property returns the height of a table row.

Copyright 2014 Corel Corporation. All rights reserved.

TableRow.Index

Property **Index** As Long

Description

Member of TableRow

The **Index** property returns the index number of a table row.

The **Index** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableRow.IsFirst

Property **IsFirst** As Boolean

Description

Member of TableRow

The **IsFirst** property returns whether a row is the first one in a table.

The **IsFirst** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableRow.IsLast

Property **IsLast** As Boolean

Description

Member of TableRow

The **IsLast** property returns whether a row is the last one in a table.

The **IsLast** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableRow.Next

Property **Next** As TableRow

Description

Member of TableRow

The **Next** property returns the next row in a table.

The **Next** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableRow.Previous

Property **Previous** As TableRow

Description

Member of TableRow

The **Previous** property returns the previous row in a table.

The **Previous** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableRow.Select

Sub **Select()**

Description

Member of TableRow

The **Select** method selects a table row.

Copyright 2014 Corel Corporation. All rights reserved.

TableRow.SetHeight

Sub **SetHeight(***Height As Double***,** *ResizeTable As Boolean***)**

Description

Member of TableRow

The **SetHeight** method sets the height of a table row.

Parameter	Description
Height	Specifies the height
ResizeTable	Specifies whether to resize the table to fit the new row height

Copyright 2014 Corel Corporation. All rights reserved.

TableRows

Properties Methods

Description

The **TableRows** class represents a collection of table rows (or TableRow objects).

Copyright 2014 Corel Corporation. All rights reserved.

TableRows.AddToSelection

Sub **AddToSelection()**

Description

Member of TableRows

The AddToSelection method adds a multiple table rows to a selection.

Copyright 2014 Corel Corporation. All rights reserved.

TableRows.Cells

Property **Cells** As TableCells

Description

Member of TableRows

The Cells property returns all the cells in a TableRows collection.

The **Cells** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableRows.Count

Property **Count** As Long

Description

Member of TableRows

The **Count** property returns the number of table rows in a TableRows collection.

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableRows.DistributeHeight

Sub **DistributeHeight()**

Description

Member of TableRows

The **DistributeHeight** method evenly distributes the height of a table among the table rows.

Copyright 2014 Corel Corporation. All rights reserved.

TableRows.First

Property **First** As TableRow

Description

Member of TableRows

The **First** property returns the first row in a TableRows collection.

The **First** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableRows.Item

Property **Item(***Index As Long***)** As TableRow

Description

Member of TableRows

The **Item** property returns the index number of a table row in a TableRows collection. Each table row is identified by an index number represented in base 1. For example, **TableRows(5)** refers to the fifth table row in the collection.

Item is the default property of the **TableRows** class, and its reference can be omitted when you are accessing items in a **TableRows** collection. For example, **TableRows.Item(5)** is the same as **TableRows(5)** — they both reference the fifth table row in the collection.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each member of the **TableRows** collection

Copyright 2014 Corel Corporation. All rights reserved.

TableRows.Last

Property **Last** As TableRow

Description

Member of TableRows

The **Last** property returns the last row in a TableRows collection.

The **Last** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableRows.Select

Sub **Select()**

Description

Member of TableRows

The **Select** method selects multiple table rows.

Copyright 2014 Corel Corporation. All rights reserved.

TableShape

Properties Methods

Description

The **TableShape** class represents the table-specific settings for a shape (or Shape object).

- Tables are created through the Layer.CreateCustomShape method. The **TableShape** class, and the following table-related classes, are available to you, although they are not directly integrated into the CorelDRAW object model:
  - TableBorders
  - TableCell
  - TableCellRange
  - TableCells
  - TableColumn
  - TableColumns
  - TableRow
  - TableRows
- The properties and methods of the **TableShape** class are accessed through the Shape.Custom property.

- For a relevant code example, see Layer.CreateCustomShape.

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.AddColumn

Function **AddColumn([***ColumnIndex As Long***])** As TableColumn

Description

Member of TableShape

The **AddColumn** method adds a column to a table.

Parameter	Description
ColumnIndex	Specifies the index number of the column. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.AddRow

Function **AddRow([***RowIndex As Long***])** As TableRow

Description

Member of TableShape

The **AddRow** method adds a row to a table.

Parameter	Description
RowIndex	Specifies the index number of the row. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.Borders

Property **Borders** As TableBorders

Description

Member of TableShape

The Borders property returns the borders of a table.

The **Borders** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.Cell

Function **Cell(***Column As Long*, *Row As Long***)** As TableCell

Description

Member of TableShape

The **Cell** method specifies a table cell.

Parameter	Description
Column	Specifies the column in which the cell is located
Row	Specifies the row in which the cell is located

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.CellRange

Function **CellRange(***ColumnStart As Long*, *RowStart As Long*, *ColumnEnd As Long*, *RowEnd As Long***)** As TableCellRange

Description

Member of TableShape

The **CellRange** method specifies a range of table cells.

Parameter	Description
ColumnStart	Specifies the first column in the range
RowStart	Specifies the first row in the range
ColumnEnd	Specifies the last column in the range
RowEnd	Specifies the last row in the range

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.Cells

Property **Cells** As TableCells

Description

Member of TableShape

The **Cells** property returns the cells of a table.

The **Cells** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.CellSpacingX

Property **CellSpacingX** As Double

Description

Member of TableShape

The **CellSpacingX** property returns the horizontal cell spacing of a table.

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.CellSpacingY

Property **CellSpacingY** As Double

Description

Member of TableShape

The **CellSpacingY** property returns the vertical cell spacing of a table.

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.ClearSelection

Sub **ClearSelection()**

Description

Member of TableShape

The **ClearSelection** method clears a selection in a table.

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.Columns

Property **Columns** As TableColumns

Description

Member of TableShape

The **Columns** property returns the columns in a table.

The **Columns** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.ConvertToText

Function **ConvertToText([***ColumnSeparator As Variant***], [***RowSeparator As Variant***], [**TextBeforeCell As String = ""**], [**TextAfterCell As String = ""**], [**AddTextOnlyIfDelimitersPresent As Boolean = True**], [**OmitPlacedShapes As Boolean = False**], [**DeleteTable As Boolean = True**])** As IVGShapeRange

Description

Member of TableShape

The **ConvertToText** method converts a table to text.

Parameter	Description
ColumnSeparator	Specifies how to mark columns in the outputted text. This parameter is optional.
RowSeparator	Specifies how to mark rows in the outputted text. This parameter is optional.
TextBeforeCell	Specifies a string to appear before the contents of each original cell in the outputted text. This parameter is optional.
TextAfterCell	Specifies a string to appear after the contents of each original cell in the outputted text. This parameter is optional.
AddTextOnlyIfDelimitersPresent	Specifies whether to add specified strings to the outputted text only if delimiters are present. This parameter is optional, and its default value is **True**.
OmitPlacedShapes	Specifies whether to omit any shapes in the original table. This parameter is optional, and its default value is **False**.
DeleteTable	Specifies whether to delete the original table. This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.CreateEmptyCellRange

Function **CreateEmptyCellRange()** As TableCellRange

Description

Member of TableShape

The **CreateEmptyCellRange** method creates an empty range of cells in a table.

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.Delete

Sub **Delete()**

Description

Member of TableShape

The **Delete** method deletes a table.

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.Rows

Property **Rows** As TableRows

Description

Member of TableShape

The **Rows** property returns the rows in a table.

The **Rows** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.Select

Sub **Select()**

Description

Member of TableShape

The **Select** method selects a table.

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.Selection

Property **Selection** As TableCellRange

Description

Member of TableShape

The **Selection** property returns a selection containing a range of table cells.

The **Selection** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.SeparatedBorders

Property **SeparatedBorders** As Boolean

Description

Member of TableShape

The **Selection** property returns whether the borders in a table are separated.

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.SetCellSpacing

Sub **SetCellSpacing**(*SpacingX As Double*, *SpacingY As Double*)

Description

Member of TableShape

The **SetCellSpacing** method sets the cell spacing for a table.

Parameter	Description
SpacingX	Specifies the horizontal cell spacing of a table
SpacingY	Specifies the vertical cell spacing of a table

Copyright 2014 Corel Corporation. All rights reserved.

TableShape.TypeID

Property **TypeID** As String

Description

Member of TableShape

The **TypeID** property returns the type ID of a table.

The **TypeID** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Text

Properties Methods

Description

The **Text** class represents the text-specific settings for a Shape object.

Copyright 2014 Corel Corporation. All rights reserved.

Text.BeginEdit

Sub **BeginEdit()**

Description

Member of Text

The **BeginEdit** method sets the editing state for text.

VBA example

The following VBA example creates paragraph text and places the text in the editing mode.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 7, 7, "This is a test.")
 Set t = s.Text
 t.BeginEdit
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.ConvertToArtistic

Sub **ConvertToArtistic()**

Description

Member of Text

The **ConvertToArtistic** method changes paragraph text to artistic text.

VBA example

The following VBA example converts all paragraph-text objects to curves by converting them to artistic text first.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.FindShapes(, cdrTextShape)
  If s.Text.Type = cdrParagraphText Then
   s.Text.ConvertToArtistic
   s.ConvertToCurves
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.ConvertToParagraph

Sub **ConvertToParagraph()**

Description

Member of Text

The **ConvertToParagraph** method changes artistic text to paragraph text.

VBA example

The following VBA example converts the artistic text in the active shape to paragraph text and then makes the paragraph text HTML-compatible.

```
Sub Test()
 With ActiveShape.Text
  .ConvertToParagraph
  .MakeHTMLCompatible
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.ExportToFile

Sub **ExportToFile(***FileName As String*, *StartIndex As Long*, *Count As Long*, **[**IndexingType As cdrTextIndexingType = cdrCharacterIndexing**])**

Description

Member of Text

The **ExportToFile** method saves a portion of a text object to a text file.

Parameter	Description
FileName	Specifies the full path and filename of the file
StartIndex	Specifies the first text object in the text range
Count	Specifies the number of items in the text range
IndexingType	Specifies the type of text to be indexed, and returns a value of cdrTextIndexingType. The indexing type can be character, word, or paragraph. This parameter is optional, and its default value is cdrCharacterIndexing (**0**).

VBA example

The following VBA example saves the second-to-fifth paragraphs to a text file, and it then inserts that text at the beginning of the text object.

```
Sub Test()
 ActiveShape.Text.ExportToFile "C:\Temp.txt", 2, 4, cdrParagraphIndexing
 ActiveShape.Text.ImportFromFile "C:\Temp.txt", 1, cdrParagraphIndexing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.Find

Function **Find(***Text As String***,** *CaseSensitive As Boolean***, [**StartIndex As Long = 1**], [**WrapAround As Boolean = False**], [**IndexingType As cdrTextIndexingType = cdrCharacterIndexing**])** As Long

Description

Member of Text

The **Find** method locates a specified text string in a text stream.

Parameter	Description
Text	Specifies the text to find
CaseSensitive	Specifies whether to match the case of the text in the **Text** parameter
StartIndex	Specifies the first text object in a text range. If the index type is set to word, and the start index is **3**, the **StartIndex** parameter begins the range at the third word in the selected text frame. This parameter is optional, and its default value is **1**.
WrapAround	Specifies whether the text follows the path of an object's shape or bounding box. This parameter is optional, and its default value is **False**.
IndexingType	Specifies, through a value of cdrTextIndexingType, the type of text to find. The indexing type can be character, word, or paragraph. This parameter is optional, and its default value is cdrCharacterIndexing (**0**).

VBA example

The following VBA example creates a paragraph-text object containing the text **Lorem Dolor Sit**. It then looks for the word **Dolor** and inserts the word **Ipsum** (plus a space) in front of the text, resulting in the string **Lorem Ipsum Dolor Sit**.

```
Sub Test()
 Dim s As Shape, n As Long
 Set s = ActiveLayer.CreateParagraphText(0, 0, 2, 1, "Lorem Dolor Sit")
 n = s.Text.Find("Dolor", False)
 If n <> 0 Then s.Text.Characters(n, 0) = "Ipsum "
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.FitTextToFrame

Sub **FitTextToFrame()**

Description

Member of Text

The **FitTextToFrame** method fits text to a frame.

VBA example

The following VBA example creates paragraph text and fits the text to the frame.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 4, 6, 9, _
  "This is a test for the frames.")
 Set t = s.Text
 t.FitTextToFrame
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.FitToPath

Sub **FitToPath(**Path As Shape**)**

Description

Member of Text

The **FitToPath** method positions artistic text along a path.

- Text cannot be fitted to the path of another text object.

Parameter	Description
Path	Specifies the path

VBA example

The following VBA example places a text object on an ellipse.

```
Sub Test()
 Dim sText As Shape, sEllipse As Shape
 Set sText = ActiveLayer.CreateArtisticText(0, 0, "Text On Path")
 Set sEllipse = ActiveLayer.CreateEllipse2(4, 5, 2)
 sText.Text.FitToPath sEllipse
 sText.Effects(1).TextOnPath.Quadrant = cdrBottomQuadrant
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.Frame

Property **Frame** As TextFrame

Description

Member of Text

The **Frame** property returns the active paragraph-text frame.

The **Frame** property returns a read-only value.

VBA example

The following VBA example creates two paragraph-text frames and links them together.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim d As Document
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, String$(400, "T"))
 Set s1 = d.ActiveLayer.CreateParagraphText(6, 6, 8, 8)
 Set t = s.Text
 t.Frame.LinkTo s1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.Frames

Property **Frames** As TextFrames

Description

Member of Text

The **Frames** property returns all the paragraph-text frames in a text range.

The **Frames** property returns a read-only value.

VBA example

The following VBA example creates two paragraph-text frames and links them together. It then displays the number of frames in the collection.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim d As Document
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, String$(400, "T"))
 Set s1 = d.ActiveLayer.CreateParagraphText(6, 6, 8, 8)
 Set t = s.Text
 ' Link the frames together
 t.Frame.LinkTo s1
 ' Display frames count
 MsgBox t.Frames.Count
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.FramesInLink

Property **FramesInLink** As Long

Description

Member of Text

The **FramesInLink** property returns the total number of paragraph-text frames in a chain of linked frames.

The **FramesInLink** property returns a read-only value.

VBA example

The following VBA example displays the total number of paragraph-text frames in the text chain and the number of empty (that is, unused) frames.

```
Sub Test()
 If ActiveShape Is Nothing Then
  MsgBox "Nothing Selected"
  Exit Sub
 End If
 If ActiveShape.Type <> cdrTextShape Then
  MsgBox "Please select a text object."
  Exit Sub
 End If
 If ActiveShape.Text.Type <> cdrParagraphText And ActiveShape.Text.Type <> cdrParagraphFittedText Then
  MsgBox "Please select a paragraph text object."
  Exit Sub
 End If
 MsgBox "The number of frames in the text chain is: " & _
  ActiveShape.Text.FramesInLink & vbCr & _
  "Unused frames: " & ActiveShape.Text.UnusedFramesInLink
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.ImportFromFile

Sub **ImportFromFile(***FileName As String***,** *StartIndex As Long***, [**IndexingType As cdrTextIndexingType = cdrCharacterIndexing**])**

Description

Member of Text

The **ImportFromFile** method inserts the contents of a text file into a text object at specified position.

Parameter	Description
FileName	Specifies the full path and filename of the file
StartIndex	Specifies the position of the inserted text file
IndexingType	Specifies the type of text to be indexed in the **StartIndex** parameter, and returns a value of cdrTextIndexingType. The indexing type can be character, word, or paragraph. This parameter is optional, and its default value is cdrCharacterIndexing (**0**).

VBA example

The following VBA example saves the second-to-fifth paragraphs to a text file, and it then inserts that text at the beginning of the text object.

```
Sub Test()
 ActiveShape.Text.ExportToFile "C:\Temp.txt", 2, 4, cdrParagraphIndexing
 ActiveShape.Text.ImportFromFile "C:\Temp.txt", 1, cdrParagraphIndexing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.IsArtisticText

Property **IsArtisticText** As Boolean

Description

Member of Text

The **IsArtisticText** property returns whether a text object is artistic text.

The **IsArtisticText** property returns a read-only value.

VBA example

The following VBA example displays a message box if the text object is artistic text.

```
Sub Test()
 Dim s As Shape
 Dim d As Document
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateArtisticText(3, 3, "This is a test")
 Set t = s.Text
 If t.IsArtisticText Then
  MsgBox "Artistic Text"
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.IsEditing

Property **IsEditing** As Boolean

Description

Member of Text

The **IsEditing** property returns the editing state of text.

The **IsEditing** property returns a read-only value.

VBA example

The following VBA example creates paragraph text, places the text in the editing mode, and displays a message box confirming that the text is in the editing mode.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 7, 7, "This is a test.")
 Set t = s.Text
 t.BeginEdit
 If t.IsEditing Then
  MsgBox "The text shape is in edit mode."
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.IsHTMLCompatible

Property **IsHTMLCompatible** As Boolean

Description

Member of Text

The **IsHTMLCompatible** property returns **True** if the specified paragraph-text object can be exported to HTML with the current formatting.

The **IsHTMLCompatible** property returns a read-only value.

VBA example

The following VBA example ensures that all paragraph-text objects on the page are HTML-compatible.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.FindShapes(Type:=cdrTextShape)
  If s.Text.Type = cdrParagraphText Then
   If Not s.Text.IsHTMLCompatible Then s.Text.MakeHTMLCompatible True
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.MakeHTMLCompatible

Function **MakeHTMLCompatible(***HTML As Boolean***)** As Boolean

Description

Member of Text

The **MakeHTMLCompatible** property ensures that a paragraph-text object is HTML-compatible.

- Artistic text cannot be converted to HTML text and is always treated as a bitmap. However, you can convert artistic text to paragraph text and then make it Web-compatible.

Parameter	Description
HTML	Specifies whether the text is made HTML-compatible

VBA example

The following VBA example ensures that all paragraph-text objects on the page are HTML-compatible.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.FindShapes(Type:=cdrTextShape)
  If s.Text.Type = cdrParagraphText Then
   If Not s.Text.IsHTMLCompatible Then s.Text.MakeHTMLCompatible True
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.Overflow

Property **Overflow** As Boolean

Description

Member of Text

The **Overflow** property returns **True** if the amount of text in a chain of linked paragraph-text frames exceeds the space available.

The **Overflow** property returns a read-only value.

VBA example

The following VBA example adjusts the height of a paragraph-text frame to accommodate any overflowing text.

```
Sub Test()
 Dim s As Shape
 ActiveDocument.ReferencePoint = cdrTopLeft
 For Each s In ActiveDocument.ActivePage.Shapes
  If s.Type = cdrTextShape Then
   If s.Text.Type = cdrParagraphText Then
    If s.Text.Overflow Then AdjustFrame s
   End If
  End If
 Next s
End Sub
Private Sub AdjustFrame(s As Shape)
 Dim h As Double
 h = s.SizeHeight / 10
 While s.Text.Overflow
  s.SizeHeight = s.SizeHeight + h
 Wend
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.Range

Function **Range(***Start As Long*, *End As Long***)** As TextRange

Description

Member of Text

The **Range** method returns a range of text characters.

Parameter	Description
Start	Specifies the starting character in the text range
End	Specifies the ending character in the text range

VBA example

The following VBA example creates an artistic-text object and displays the first-to-fifth characters in a message box. The ninth-to-fourteenth characters are capitalized.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateArtisticText(4, 5, "This is a test.")
 Set t = s.Text
 MsgBox "The text between characters 1 and 5 is: " & vbCr & t.Range(1, 5).Text
 t.Range(9, 14).Case = cdrAllCapsFontCase
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.Replace

Sub **Replace(***OldText As String***,** *NewText As String***,** *CaseSensitive As Boolean***, [**StartIndex As Long = 1**], [**ReplaceAll As Boolean = False**], [**WrapAround As Boolean = False**], [**IndexingType As cdrTextIndexingType = cdrCharacterIndexing**])**

Description

Member of Text

The **Replace** method replaces one text string with another in a text object.

Parameter	Description
OldText	Specifies the text to be replaced
NewText	Specifies the text that replaces the text in the **OldText** parameter
CaseSensitive	Specifies whether to match the case of the text in the **Text** parameter
StartIndex	Specifies the first text object in the text range. If the index type is set to word and the start index is **3**, the **StartIndex** parameter begins the range at the third word in the selected text frame. This parameter is optional, and its default value is **1**.
ReplaceAll	Specifies whether all instances of old text found in the text range are replaced with new text. This parameter is optional, and its default value is **False**.
WrapAround	Specifies whether the text follows the path of an object's shape or bounding box. This parameter is optional, and its default value is **False**.
IndexingType	Specifies, through a value of cdrTextIndexingType, the type of text to find. The indexing type can be character, word, or paragraph. This parameter is optional, and its default value is cdrCharacterIndexing (**0**).

VBA example

The following VBA example replaces all occurrences of **#** on the page with the current date.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.FindShapes(, cdrTextShape)
  s.Text.Replace "#", CStr(Date), False, ReplaceAll:=True
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.Selection

Property **Selection** As TextRange

Description

Member of Text

The **Selection** property returns the selected text in a text stream as a TextRange object.

The **Selection** property returns a read-only value.

VBA example

The following VBA example displays the selected text if the active shape is a text shape.

```
Sub Test()
 If ActiveShape.Type = cdrTextShape Then
  MsgBox ActiveShape.Text.Selection.Text
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.Story

Property **Story** As TextRange

Description

Member of Text

The **Story** property returns all text from all text frames.

The **Story** property returns a read-only value.

VBA example

The following VBA example creates artistic text and displays all of the text.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateArtisticText(3, 3, "This is a test.")
 Set t = s.Text
 MsgBox "The entire text is:" & vbCr & t.Story
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.Type

Property **Type** As cdrTextType

Description

Member of Text

The **Type** property returns the type of a text object, indicating whether the object is artistic text or paragraph text and whether it is fitted to a curve.

The **Type** property returns a read-only value of cdrTextType.

VBA example

The following VBA example converts all paragraph-text objects to curves by first converting them to artistic text.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.FindShapes(, cdrTextShape)
  If s.Text.Type = cdrParagraphText Then
   s.Text.ConvertToArtistic
   s.ConvertToCurves
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Text.UnusedFramesInLink

Property **UnusedFramesInLink** As Long

Description

Member of Text

The **UnusedFramesInLink** property returns the total number of empty frames in a chain of linked paragraph-text frames.

The **UnusedFramesInLink** property returns a read-only value.

VBA example

The following VBA example displays the total number of frames in the text chain and the number of empty (or unused) frames.

```
Sub Test()
 If ActiveShape Is Nothing Then
  MsgBox "Nothing Selected"
  Exit Sub
 End If
 If ActiveShape.Type <> cdrTextShape Then
  MsgBox "Please select a text object"
  Exit Sub
 End If
 If ActiveShape.Text.Type <> cdrParagraphText And ActiveShape.Text.Type <> cdrParagraphFittedText Then
  MsgBox "Please select a paragraph text object"
  Exit Sub
 End If
 MsgBox "The number of frames in the text chain is: " & _
  ActiveShape.Text.FramesInLink & vbCr & _
  "Unused frames: " & ActiveShape.Text.UnusedFramesInLink
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextCharacters

Properties

Description

The **TextCharacters** class represents a collection of text characters.

Copyright 2014 Corel Corporation. All rights reserved.

TextCharacters.All

Property **All** As TextRange

Description

Member of TextCharacters

The **All** property returns a TextRange object containing all the characters in a collection.

The **All** property returns a read-only value.

VBA example

The following VBA example creates paragraph text and then changes all of its characters to uppercase.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, _
  "This is a test.")
 Set t = s.Text
 t.Story.Characters.All.Case = cdrAllCapsFontCase
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextCharacters.Count

Property **Count** As Long

Description

Member of TextCharacters

The **Count** property returns the number of characters in a collection, including paragraph breaks.

The **Count** property returns a read-only value.

VBA example

The following VBA example creates paragraph text and then displays the number of characters it contains.

```
Sub Test()
 Dim s As Shape
 Dim d As Document
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, _
  "This is a test.")
 Set t = s.Text
 MsgBox t.Story.Characters.Count
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextCharacters.First

Property **First** As TextRange

Description

Member of TextCharacters

The **First** property returns a text range (or TextRange object) containing the first character in a collection.

The **First** property returns a read-only value.

VBA example

The following VBA example creates paragraph text and then fills its first character with red.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, _
  "This is a test.")
 Set t = s.Text
 t.Story.Characters.First.Fill.UniformColor.RGBAssign 155, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextCharacters.Item

Property **Item(***Index As Long***, [**Count As Long = 1**])** As TextRange

Description

Member of TextCharacters

The **Item** property returns a text range (or TextRange object) containing the specified characters. It is the default property of the TextCharacters class.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the index number of the character
Count	Specifies the number of characters to include. This parameter is optional, and its default value is **1**.

VBA example

The following VBA example creates paragraph text, applies bold formatting to its third character, and fills its tenth-to-fifteenth characters with red.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Dim strText As String
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, "This is a test.")
 Set t = s.Text
 t.Story.Characters.Item(3).Bold = True
 t.Story.Characters.Item(10, 5).Fill.UniformColor.RGBAssign 155, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextCharacters.Last

Property **Last** As TextRange

Description

Member of TextCharacters

The **Last** property returns a text range (or TextRange object) containing the last character in a collection.

The **Last** property returns a read-only value.

VBA example

The following VBA example creates paragraph text and then fills its last character red.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, _
  "This is a test.")
 Set t = s.Text
 t.Story.Characters.Last.Fill.UniformColor.RGBAssign 155, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextColumns

Properties

Description

The **TextColumns** class represents a collection of text columns.

Copyright 2014 Corel Corporation. All rights reserved.

TextColumns.All

Property **All** As TextRange

Description

Member of TextColumns

The **All** property returns a text range (or TextRange object) containing all the columns in a collection.

The **All** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text. It then creates three columns in the first frame, applying bold formatting to all text in the columns.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim d As Document
 Dim t As Text
 Dim strText As String
 strText = "This is a test. This text must be long enough to span " & _
  "across multiple columns in this frame. By adding this sentence, " &_
  "this text is now long enough."
 strText = strText & " This is the next sentence. " & strText
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, strText)
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 ' Set columns
 t.Frame.SetColumns 3, False, Array(0.7, 0.1, 1, 0.1, 1)
 t.Frame.Range.Columns.All.Bold = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextColumns.Count

Property **Count** As Long

Description

Member of TextColumns

The **Count** property returns the number of text columns in a collection.

The **Count** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text. In the first frame, it then creates three columns displays the number of columns.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim d As Document
 Dim t As Text
 Dim strText As String
 strText = "This is a test. This sentence must be long enough " & _
  "to span across multiple columns in this frame. I am sure " & _
  "that it will cross multiple columns now."
 strText = strText & " This is the next sentence. " & strText
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, strText)
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 ' Set the columns
 t.Frame.SetColumns 3, False, Array(0.7, 0.1, 1, 0.1, 1)
 MsgBox "The column count for the frame is " & t.Frame.Range.Columns.Count
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextColumns.First

Property **First** As TextRange

Description

Member of TextColumns

The **First** property returns a text range (or TextRange object) containing the first column in a collection.

The **First** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text. It then creates three columns in the first frame, applying bold formatting to the first column.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim d As Document
 Dim t As Text
 Dim strText As String
 strText = "This is a test. This sentence must be long enough " & _
  "to span across multiple columns in this frame. I am sure " & _
  "that it will cross multiple columns now."
 strText = strText & " This is next part " & strText
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, strText)
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 ' Set the columns
 t.Frame.SetColumns 3, False, Array(0.7, 0.1, 1, 0.1, 1)
 t.Frame.Range.Columns.First.Bold = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextColumns.Item

Property **Item(***Index As Long***, [**Count As Long = 1**])** As TextRange

Description

Member of TextColumns

The **Item** property returns a read-only reference to a specified column in a TextColumns collection. It is the default property of the **TextColumns** class.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each column in the **TextColumns** collection
Count	Specifies the number of columns. This parameter is optional, and its default value is **1**.

VBA example

The following VBA example links frames of paragraph text. It then creates three columns in the first frame, applying italics to the third column, strikethrough formatting to the second, and a red fill to the first.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim d As Document
 Dim t As Text
 Dim tr As TextRange
 Dim strText As String
 strText = "This is a test. This sentence must be long enough " & _
  "to span across multiple columns in this frame. I am sure " & _
  "that it will cross multiple columns now."
 strText = strText & " This is next part " & strText
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, strText)
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 ' Set the columns
 t.Frame.SetColumns 3, False, Array(0.7, 0.1, 1, 0.1, 1)
 t.Frame.Range.Columns.Item(3).Italic = True
 t.Frame.Range.Columns.Item(2).Strikethru = cdrDoubleThinFontLine
 t.Frame.Range.Columns.Item(1).Fill.ApplyUniformFill CreateRGBColor(155, 0, 0)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextColumns.Last

Property **Last** As TextRange

Description

Member of TextColumns

The **Last** property returns a text range (or TextRange object) containing the last column in a collection.

The **Last** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text. It then creates three columns in the first frame, applying bold formatting to the third column.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim d As Document
 Dim t As Text
 Dim strText As String
 strText = "This is a test. This sentence must be long enough " & _
  "to span across multiple columns in this frame. I am sure " & _
  "that it will cross multiple columns now."
 strText = strText & " This is next part " & strText
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, strText)
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 ' Set the columns
 t.Frame.SetColumns 3, False, Array(0.7, 0.1, 1, 0.1, 1)
 t.Frame.Range.Columns.Last.Bold = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame

Properties Methods

Description

The **TextFrame** class represents the settings for a paragraph-text frame.

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.ColumnCount

Property **ColumnCount** As Long

Description

Member of TextFrame

The **ColumnCount** property returns the number of columns in a paragraph-text frame.

The **ColumnCount** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text. It then creates three columns in the first frame, displaying the number of columns in the frame for each multicolumned frame.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim f As TextFrame
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(750, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 ' Get the first frame
 Set f = t.Frames(1)
 ' Set the columns
 f.SetColumns 3, False, Array(1, 0.3, 2, 0.3, 3)
 For Each f In t.Frames
  If f.Multicolumn Then
   MsgBox "There are " & f.ColumnCount & _
    " columns in frame " & f.Index
  End If
 Next f
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.ColumnGutter

Property **ColumnGutter(***Index As Long***)** As Double

Description

Member of TextFrame

The **ColumnGutter** property returns the amount of space between paragraph-text columns.

The **ColumnGutter** property returns a read-only value.

Parameter	Description
Index	Specifies the gutter by its index number

VBA example

The following VBA example links frames of paragraph text. It then creates three columns in the first frame, displaying the amount of space between columns.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim f As TextFrame
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(750, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 ' Get the first frame
 Set f = t.Frames(1)
 ' Set the columns
 f.SetColumns 3, False, Array(1, 0.25, 2, 0.3, 3)
 MsgBox "Gutter 1: " & f.ColumnGutter(1) & vbCr & _
  "Gutter 2: " & f.ColumnGutter(2)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.ColumnWidth

Property **ColumnWidth(***Index As Long***)** As Double

Description

Member of TextFrame

The **ColumnWidth** property returns the width of a specified paragraph-text column.

The **ColumnWidth** property returns a read-only value.

Parameter	Description
Index	Specifies the column by its index number

VBA example

The following VBA example links frames of paragraph text. It then creates three columns in the first frame, displaying the width of each column.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim f As TextFrame
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(750, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 ' Get the first frame
 Set f = t.Frames(1)
 ' Set the columns
 f.SetColumns 3, False, Array(1, 0.3, 1.4, 0.3, 1.5)
 MsgBox "Column 1 Width: " & f.ColumnWidth(1) & vbCr & _
  "Column 2 Width: " & f.ColumnWidth(2) & vbCr & _
  "Column 3 Width: " & f.ColumnWidth(3)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.Container

Property **Container** As Shape

Description

Member of TextFrame

The **Container** property returns a read-only reference to the container for a paragraph-text frame.

VBA example

The following VBA example links frames of paragraph text, placing the first paragraph text inside an ellipse and the second inside a rectangle, and then displaying the index number of each frame inside a container.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim s3 As Shape
 Dim t As Text
 Dim f As TextFrame
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(1000, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateEllipse(8, 8, 10, 10)
 Set s3 = d.ActiveLayer.CreateRectangle(1, 1, 4, 4)
 Set t = s.Text
 ' Link the frames together
 t.Frame.LinkTo s1
 ' Place the text inside the shapes
 s2.PlaceTextInside s
 s3.PlaceTextInside s1
 ' Go through the frames
 For Each f In t.Frames
  If f.IsInsideContainer = True Then
   Select Case f.Container.Type
    Case 1
     MsgBox "Frame " & f.Index & " is inside a rectangle"
    Case 2
     MsgBox "Frame " & f.Index & " is inside a ellipse"
    Case Else
     MsgBox "Frame " & f.Index & " is inside a shape"
   End Select
  End If
 Next f
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.Empty

Property **Empty** As Boolean

Description

Member of TextFrame

The **Empty** property returns **True** if a paragraph-text frame is empty.

The **Empty** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text together and displays which frames are empty.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim f As TextFrame
 Dim d As Document
 Dim st As String
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(1000, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 For Each f In t.Frames
  If f.Empty Then
   st = st & "Frame " & f.Index & vbCr
  End If
 Next f
 MsgBox st
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.Fill

Property **Fill** As Fill

Description

Member of TextFrame

The **Fill** property specifies the background fill for a text frame.

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.FrameShape

Property **FrameShape** As Shape

Description

Member of TextFrame

The **FrameShape** property returns the Shape object that hosts a given paragraph-text frame.

The **FrameShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.Index

Property **Index** As Long

Description

Member of TextFrame

The **Index** property returns the index number of a paragraph-text frame.

The **Index** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text, placing the first paragraph text inside an ellipse and the second inside a rectangle, and then displaying the index number of each frame inside a container.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim s3 As Shape
 Dim t As Text
 Dim f As TextFrame
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(1000, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateEllipse(8, 8, 10, 10)
 Set s3 = d.ActiveLayer.CreateRectangle(1, 1, 4, 4)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 ' Place the text inside the shapes.
 s2.PlaceTextInside s
 s3.PlaceTextInside s1
 ' Iterate through the frames.
 For Each f In t.Frames
  If f.IsInsideContainer = True Then
   Select Case f.Container.Type
    Case 1
     MsgBox "Frame " & f.Index & " is inside a rectangle"
    Case 2
     MsgBox "Frame " & f.Index & " is inside a ellipse"
    Case Else
     MsgBox "Frame " & f.Index & " is inside a shape"
   End Select
  End If
 Next f
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.IsFirst

Property **IsFirst** As Boolean

Description

Member of TextFrame

The **IsFirst** property returns **True** if a paragraph-text frame is the first frame.

The **IsFirst** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text. It then creates three columns of equal width and spacing.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim f As TextFrame
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(1000, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 ' Iterate through each frame.
 For Each f In t.Frames
  If f.IsFirst Then
   f.SetColumns 3, True, 1, 0.3
   Exit For
  End If
 Next f
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.IsFittedToPath

Property **IsFittedToPath** As Boolean

Description

Member of TextFrame

The **IsFittedToPath** property returns **True** if a paragraph-text frame is fitted to a path.

The **IsFittedToPath** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text. It fits text to an ellipse and then displays the index number of each frame that is fitted to a shape.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim f As TextFrame
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(1000, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateEllipse(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 ' Fit the text to the ellipse.
 s.Text.FitToPath s2
 ' Iterate through the frames.
 For Each f In t.Frames
  If f.IsFittedToPath = True Then
   Select Case f.Path.Type
    Case 2
     MsgBox "Frame " & f.Index & " is fitted to an ellipse."
    Case Else
     MsgBox "Frame " & f.Index & " is fitted to a shape."
   End Select
  End If
 Next f
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.IsInsideContainer

Property **IsInsideContainer** As Boolean

Description

Member of TextFrame

The **IsInsideContainer** property returns **True** if a paragraph-text frame is inside a container shape.

The **IsInsideContainer** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text, placing the first paragraph text inside an ellipse and the second inside a rectangle, and then displaying the index number of each frame inside a container.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim s3 As Shape
 Dim t As Text
 Dim f As TextFrame
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(1000, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateEllipse(8, 8, 10, 10)
 Set s3 = d.ActiveLayer.CreateRectangle(1, 1, 4, 4)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 ' Place the text inside the shapes.
 s2.PlaceTextInside s
 s3.PlaceTextInside s1
 ' Iterate through the frames.
 For Each f In t.Frames
  If f.IsInsideContainer = True Then
   Select Case f.Container.Type
    Case 1
     MsgBox "Frame " & f.Index & " is inside a rectangle"
    Case 2
     MsgBox "Frame " & f.Index & " is inside a ellipse"
    Case Else
     MsgBox "Frame " & f.Index & " is inside a shape"
   End Select
  End If
 Next f
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.IsLast

Property **IsLast** As Boolean

Description

Member of TextFrame

The **IsLast** property returns **True** if a paragraph-text frame is the last frame.

The **IsLast** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text, creating three columns of equal width and spacing in the last frame.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim f As TextFrame
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, String$(1200, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 7, 7)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link frames together
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 ' Go through each frame
 For Each f In t.Frames
  If f.IsLast Then
   f.SetColumns 3, True, 1, 0.3
   Exit For
  End If
 Next f
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.LinkTo

Sub **LinkTo(**Shape As Shape**)**

Description

Member of TextFrame

The **LinkTo** method links a paragraph-text frame to a specified shape.

Parameter	Description
Shape	Specifies the shape

VBA example

The following VBA example links frames of paragraph text.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 5, 7, 9, "This is a test")
 Set s1 = d.ActiveLayer.CreateParagraphText(0, 0, 4, 4)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.Multicolumn

Property **Multicolumn** As Boolean

Description

Member of TextFrame

The **Multicolumn** property returns **True** if a paragraph-text frame has more than one column.

The **Multicolumn** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text. The text in the first frame is fitted to a path and is divided into three columns, and then the number of columns in each multicolumned frame is displayed.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim f As TextFrame
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(750, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateEllipse(1, 1, 3, 3)
 Set t = s.Text
 ' Fit the text to path.
 s1.Text.FitToPath s2
 ' Link the frames together.
 t.Frame.LinkTo s1
 ' Get the first frame.
 Set f = t.Frames(1)
 ' Set the columns
 f.SetColumns 3, False, Array(1, 0.3, 2, 0.3, 3)
 For Each f In t.Frames
  If f.Multicolumn Then
   MsgBox "There are " & f.ColumnCount & " columns in frame " & f.Index
  End If
 Next f
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.Next

Property **Next** As TextFrame

Description

Member of TextFrame

The **Next** property returns the next paragraph-text frame, if any.

The **Next** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text, displaying the index number of the frame following the first frame.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim f As TextFrame
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(750, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 ' Get the first frame.
 Set f = t.Frames(1)
 MsgBox "The index number of the next frame is: " & f.Next.Index
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.Path

Property **Path** As Shape

Description

Member of TextFrame

The **Path** property returns a read-only reference to the path to which text is fitted.

VBA example

The following VBA example links frames of paragraph text. It then fits text to an ellipse and displays the index number of each frame that is fitted to a shape.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim f As TextFrame
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(1000, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateEllipse(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 ' Fit the text to the ellipse.
 s.Text.FitToPath s2
 ' Go through the frames.
 For Each f In t.Frames
  If f.IsFittedToPath = True Then
   Select Case f.Path.Type
    Case 2
     MsgBox "Frame " & f.Index & " is fitted to an ellipse."
    Case Else
     MsgBox "Frame " & f.Index & " is fitted to a shape."
   End Select
  End If
 Next f
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.Previous

Property **Previous** As TextFrame

Description

Member of TextFrame

The **Previous** property returns the previous paragraph-text frame, if any.

The **Previous** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text, displaying the index number of the frame before the last frame.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim f As TextFrame
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(750, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 ' Get the first frame.
 Set f = t.Frames(3)
 MsgBox "The index number of the previous frame is: " & f.Previous.Index
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.Range

Property **Range** As TextRange

Description

Member of TextFrame

The **Range** property returns a text range (or TextRange object) containing the text in a paragraph-text frame. It is the default property of the **TextRange** class.

The **Range** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text, applying bold formatting to all text in the first frame.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim f As TextFrame
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(1000, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 Set f = t.Frames(1)
 f.Range.Bold = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.SetColumns

Sub **SetColumns(***NumColumns As Long*, *EqualColumns As Boolean*, *WidthsAndGutters() As Variant***)**

Description

Member of TextFrame

The **SetColumns** property creates columns within a paragraph-text frame.

Parameter	Description
NumColumns	Specifies the number of columns
EqualColumns	Specifies whether the columns are equal in width
WidthsAndGutters	Specifies the sizes of the column and gutter, respectively, for each column and gutter

VBA example 1

The following VBA example links frames of paragraph text. In the first frame, and by using an array, it creates three columns of varying widths and equal spacing.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim f As TextFrame
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(750, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 ' Get the first frame.
 Set f = t.Frames(1)
 ' Set the columns
 f.SetColumns 3, False, Array(1, 0.3, 2, 0.3, 3)
End Sub
```

VBA example 2

The following VBA example links frames of paragraph text. In the first frame, it creates three columns of equal width and spacing.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim f As TextFrame
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(750, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 Set f = t.Frames(1)
 ' Set the columns.
 f.SetColumns 3, True, Array(1, 0.3)
End Sub
```

VBA example 3

The following VBA example links frames of paragraph text. In the first frame, and without using an array, it creates four columns of varying widths.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim f As TextFrame
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(750, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link frames together.
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
```

```
 Set f = t.Frames(1)
 ' Set the columns.
 f.SetColumns 4, False, 1, 0.3, 1, 0.2, 0.5, 0.1, 0.4
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.UnLink

Sub **UnLink()**

Description

Member of TextFrame

The **UnLink** method unlinks a paragraph-text frame.

VBA example

The following VBA example links frames of paragraph text and then unlinks the first frame from the second.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 5, 7, 9, "This is a test.")
 Set s1 = d.ActiveLayer.CreateParagraphText(0, 0, 4, 4)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 s1.Text.Frame.UnLink
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrame.VerticalAlignment

Property **VerticalAlignment** As cdrVerticalAlignment

Description

Member of TextFrame

The **VerticalAlignment** property returns or specifies the vertical alignment of a paragraph-text frame.

VBA example

The following VBA example links frames of paragraph text and sets the vertical alignment of the first frame.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim f As TextFrame
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(1000, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 ' Get the first frame.
 Set f = t.Frames(1)
 ' Set the vertical alignment to Bottom Justify.
 f.VerticalAlignment = cdrBottomJustify
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrames

Properties

Description

The **TextFrames** class represents a collection of text frames (or TextFrame objects).

Copyright 2014 Corel Corporation. All rights reserved.

TextFrames.All

Property **All** As TextRange

Description

Member of TextFrames

The **All** property returns a text range (or TextRange object) containing all the frames in a TextFrames collection.

The **All** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text, applying bold formatting to the text in each frame.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(750, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 t.Frames.All.Bold = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrames.Count

Property **Count** As Long

Description

Member of TextFrames

The **Count** property returns the number of text frames in a TextFrames collection.

The **Count** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text and displays the number of frames in the collection.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(750, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 MsgBox "The number of frames in the collection is " & t.Frames.Count
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrames.First

Property **First** As TextFrame

Description

Member of TextFrames

The **First** property returns a text frame (or TextFrame object) containing the first frame in a TextFrames collection.

The **First** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text, applying bold formatting to the text in the first frame.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(750, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 t.Frames.First.Range.Bold = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrames.Item

Property **Item(***Index As Long***)** As TextFrame

Description

Member of TextFrames

The **Item** property returns a read-only reference to a specified frame in a TextFrames collection. It is the default property of the **TextFrames** class.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each member of the **TextFrames** collection

VBA example

The following VBA example links paragraph text and displays whether the first item in the collection is inside a container.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(750, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 MsgBox t.Frames.Item(1).IsInsideContainer
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrames.Last

Property **Last** As TextFrame

Description

Member of TextFrames

The **Last** property returns a text frame (or TextFrame object) containing the last frame in a TextFrames collection.

The **Last** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text, applying bold formatting to the text in the last frame.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, String$(750, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 7, 7)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 t.Frames.Last.Range.Bold = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextFrames.Range

Property **Range(***Index As Long***, [**Count As Long = 1**])** As TextRange

Description

Member of TextFrames

The **Range** property returns a text range (or TextRange) object containing specified frames.

The **Range** property returns a read-only value.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each member of the TextFrames collection
Count	Specifies the number of frames. This parameter is optional, and its default value is **1**.

VBA example

The following VBA example links frames of paragraph text, applying bold formatting to the text in the second frame.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, String$(750, "Z"))
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 t.Frames.Range(2).Bold = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextLines

Properties

Description

The **TextLines** class represents a collection of text lines.

Copyright 2014 Corel Corporation. All rights reserved.

TextLines.All

Property **All** As TextRange

Description

Member of TextLines

The **All** property returns a text range (or TextRange object) containing all the lines in a TextLines collection.

The **All** property returns a read-only value.

VBA example

The following VBA example creates paragraph text and applies bold formatting to all the lines.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Dim strText As String
 strText = "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. This is a test."
 strText = strText & " This is the next sentence. " & strText
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, strText)
 Set t = s.Text
 t.Story.Lines.All.Bold = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextLines.Count

Property **Count** As Long

Description

Member of TextLines

The **Count** property returns the number of lines in a TextLines collection.

The **Count** property returns a read-only value.

VBA example

The following VBA example creates paragraph text and displays the number of lines in the paragraph.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Dim strText As String
 strText = "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. This is a test."
 strText = strText & " This is the next sentence. " & strText
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, strText)
 Set t = s.Text
 MsgBox "The number of lines in the text is " & t.Story.Lines.Count
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextLines.First

Property **First** As TextRange

Description

Member of TextLines

The **First** property returns a text range (or TextRange object) containing the first line in a TextLines collection.

The **First** property returns a read-only value.

VBA example

The following VBA example creates paragraph text, filling the first line with red.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Dim strText As String
 strText = "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. This is a test."
 strText = strText & " This is the next sentence. " & strText
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, strText)
 Set t = s.Text
 t.Story.Lines.First.Fill.UniformColor.RGBAssign 155, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextLines.Item

Property **Item(***Index As Long***, [**Count As Long = 1**])** As TextRange

Description

Member of TextLines

The **Item** property returns a text range (or TextRange object) containing specified lines. It is the default property of the TextLines class.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each member of the **TextLines** collection
Count	Specifies the number of lines. This parameter is optional, and its default value is **1**.

VBA example

The following VBA example creates paragraph text, applying bold formatting to the first line and filling the second and third lines with red.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Dim strText As String
 strText = "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. This is a test."
 strText = strText & " This is the next sentence. " & strText
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, strText)
 Set t = s.Text
 t.Story.Lines.Item(1).Bold = True
 t.Story.Lines.Item(2, 2).Fill.UniformColor.RGBAssign 155, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextLines.Last

Property **Last** As TextRange

Description

Member of TextLines

The **Last** property returns a text range (or TextRange object) containing the last line in a TextLines collection.

The **Last** property returns a read-only value.

VBA example

The following VBA example creates paragraph text, filling the last line with red.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Dim strText As String
 strText = "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. This is a test."
 strText = strText & " This is the next sentence. " & strText
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, strText)
 Set t = s.Text
 t.Story.Lines.Last.Fill.UniformColor.RGBAssign 155, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextParagraphs

Properties

Description

The **TextParagraphs** class represents a collection of text paragraphs.

Copyright 2014 Corel Corporation. All rights reserved.

TextParagraphs.All

Property **All** As TextRange

Description

Member of TextParagraphs

The **All** property returns a text range (or TextRange object) containing all the paragraphs in a TextParagraphs collection.

The **All** property returns a read-only value.

VBA example

The following VBA example creates paragraph text, applying bold formatting to all paragraphs.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Dim strText As String
 strText = "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. " & vbCr & _
  "This is still a test. This is still a test. This is still a test. " & _
  "This is still a test. This is still a test. " & vbCr & _
  "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. " & vbCr & _
  "This is still a test. This is still a test. This is still a test. " & _
  "This is still a test. This is still a test. " & vbCr & _
  "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. " & vbCr & _
  "This is still a test. This is still a test. This is still a test. " & _
  "This is still a test. This is still a test. " & vbCr & _
  "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. "
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, strText)
 Set t = s.Text
 t.Story.Paragraphs.All.Bold = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextParagraphs.Count

Property **Count** As Long

Description

Member of TextParagraphs

The **Count** property returns the number of paragraphs in a TextParagraphs collection.

The **Count** property returns a read-only value.

VBA example

The following VBA example creates paragraph text and displays the number of paragraphs in it.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Dim strText As String
 strText = "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. " & vbCr & _
  "This is still a test. This is still a test. This is still a test. " & _
  "This is still a test. This is still a test. " & vbCr & _
  "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. " & vbCr & _
  "This is still a test. This is still a test. This is still a test. " & _
  "This is still a test. This is still a test. " & vbCr & _
  "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. " & vbCr & _
  "This is still a test. This is still a test. This is still a test. " & _
  "This is still a test. This is still a test. " & vbCr & _
  "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. "
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, strText)
 Set t = s.Text
 MsgBox "The number of paragraphs is: " & t.Story.Paragraphs.Count
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextParagraphs.First

Property **First** As TextRange

Description

Member of TextParagraphs

The **First** property returns a text range (or TextRange object) containing the first paragraph in a TextRange collection.

The **First** property returns a read-only value.

VBA example

The following VBA example creates paragraph text, filling the first paragraph with red.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Dim strText As String
 strText = "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. " & vbCr & _
  "This is still a test. This is still a test. This is still a test. " & _
  "This is still a test. This is still a test. " & vbCr & _
  "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. " & vbCr & _
  "This is still a test. This is still a test. This is still a test. " & _
  "This is still a test. This is still a test. " & vbCr & _
  "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. " & vbCr & _
  "This is still a test. This is still a test. This is still a test. " & _
  "This is still a test. This is still a test. " & vbCr & _
  "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. "
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, strText)
 Set t = s.Text
 t.Story.Paragraphs.First.Fill.UniformColor.RGBAssign 155, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextParagraphs.Item

Property **Item(***Index As Long***, [**Count As Long = 1**])** As TextRange

Description

Member of TextParagraphs

The **Item** property returns a text range (or TextRange object) containing specified paragraphs. It is the default property of the TextParagraphs class.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each member of the **TextParagraphs** collection
Count	Specifies the number of paragraphs. This parameter is optional, and its default value is **1**.

VBA example

The following VBA example creates paragraph text, applying bold formatting to the second paragraph and filling the fifth and sixth paragraphs with uniform red.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Dim strText As String
 strText = "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. " & vbCr & _
  "This is still a test. This is still a test. This is still a test. " & _
  "This is still a test. This is still a test. " & vbCr & _
  "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. " & vbCr & _
  "This is still a test. This is still a test. This is still a test. " & _
  "This is still a test. This is still a test. " & vbCr & _
  "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. " & vbCr & _
  "This is still a test. This is still a test. This is still a test. " & _
  "This is still a test. This is still a test. " & vbCr & _
  "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. "
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, strText)
 Set t = s.Text
 t.Story.Paragraphs.Item(2).Bold = True
 t.Story.Paragraphs.Item(5, 2).Fill.UniformColor.RGBAssign 155, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextParagraphs.Last

Property **Last** As TextRange

Description

Member of TextParagraphs

The **Last** property returns a text range (or TextRange object) containing the last paragraph in a TextParagraphs collection.

The **Last** property returns a read-only value.

VBA example

The following VBA example creates paragraph text, filling the last paragraph with red.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Dim strText As String
 strText = "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. " & vbCr & _
  "This is still a test. This is still a test. This is still a test. " & _
  "This is still a test. This is still a test. " & vbCr & _
  "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. " & vbCr & _
  "This is still a test. This is still a test. This is still a test. " & _
  "This is still a test. This is still a test. " & vbCr & _
  "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. " & vbCr & _
  "This is still a test. This is still a test. This is still a test. " & _
  "This is still a test. This is still a test. " & vbCr & _
  "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. "
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, strText)
 Set t = s.Text
 t.Story.Paragraphs.Last.Fill.UniformColor.RGBAssign 155, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange

Properties Methods

Description

The **TextRange** class represents a text range.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Alignment

Property **Alignment** As cdrAlignment

Description

Member of TextRange

The **Alignment** property returns or specifies the alignment of the text in a text range.

VBA example

The following VBA example aligns the text in the paragraph to the center of each line.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, "This is an example.")
 Set t = s.Text
 t.Story.Alignment = cdrCenterAlignment
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.AlignToBaseline

Sub **AlignToBaseline()**

Description

Member of TextRange

The **AlignToBaseline** method removes vertical character shifts.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.ApplyBulletEffect

Sub **ApplyBulletEffect([***Symbol As String***], [***Font As String***], [***Size As Single***], [***BaselineShift As Single***], [***HorizontalPosition As Double***], [**HangingIndent As Boolean = True**])**

Description

Member of TextRange

The **ApplyBulletEffect** method applies a bullet effect to the paragraphs in a text range.

Parameter	Description
Symbol	Specifies the bullet symbol. This parameter is optional.
Font	Specifies the bullet font. This parameter is optional.
Size	Specifies the bullet size. This parameter is optional, and its default value is **0**.
BaselineShift	Specifies the vertical shift, in points, of the bullet symbol from the baseline. This parameter is optional, and its default value is **0**.
HorizontalPosition	Specifies the horizontal offset of the bullet symbol from the left text margin. This parameter is optional, and its default value is **0**.
HangingIndent	Specifies the hanging indentation This parameter is optional, and its default value is **True**.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.ApplyDropCapEffect

Sub **ApplyDropCapEffect([**LinesDropped As Long = 3**], [***DistanceFromText As Double***], [**HangingIndent As Boolean = False**])**

Description

Member of TextRange

The **ApplyDropCapEffect** method applies a drop-cap effect to the paragraphs in a text range.

Parameter	Description
LinesDropped	Specifies the number of lines that the drop-cap effect drops. This parameter is optional, and its default value is **3**.
DistanceFromText	Specifies the distance between the drop cap and the rest of the text. This parameter is optional, and its default value is **0**.
HangingIndent	Specifies the hanging indentation for paragraphs when the drop-cap effect is applied. This parameter is optional, and its default value is **False**.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.ApplyNoEffect

Sub **ApplyNoEffect()**

Description

Member of TextRange

The **ApplyNoEffect** method removes any paragraph formatting effect (such as a drop cap or bullets) from a text range.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.ApplyStyle

Sub **ApplyStyle(***StyleName As String***)**

Description

Member of TextRange

The **ApplyStyle** method applies a style to the text in the text range.

Parameter	Description
StyleName	Specifies the name of the style to be applied

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.AutoHyphenate

Property **AutoHyphenate** As cdrTriState

Description

Member of TextRange

The **AutoHyphenate** property returns or specifies whether automatic hyphenation is enabled for a text range.

VBA example

The following VBA example enables automatic hyphenation.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, "This is an example.")
 Set t = s.Text
 t.Story.AutoHyphenate = cdrTrue
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Baselines

Property **Baselines** As Curve

Description

Member of TextRange

The **Baselines** property returns a curve consisting of a set of line segments that represent the placement and direction of the baseline of each text line in a text range.

The **Baselines** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Bold

Property **Bold** As Boolean

Description

Member of TextRange

The **Bold** property returns or specifies whether bold formatting is applied to a text range.

VBA example

The following VBA example applies bold formatting to all the text in the paragraph.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, "This is an example.")
 Set t = s.Text
 t.Story.Bold = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.BulletBaselineShift

Property **BulletBaselineShift** As Single

Description

Member of TextRange

The **BulletBaselineShift** property returns or specifies the vertical shift, in points, of the bullet symbol from the baseline in a text range.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.BulletFont

Property **BulletFont** As String

Description

Member of TextRange

The **BulletFont** property returns or specifies the font face of the bullet symbol in a text range.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.BulletHangingIndent

Property **BulletHangingIndent** As Boolean

Description

Member of TextRange

The **BulletHangingIndent** property returns or specifies the hanging indentation for paragraphs when a bullet effect is applied to a text range.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.BulletHorizontalPosition

Property **BulletHorizontalPosition** As Double

Description

Member of TextRange

The **BulletHorizontalPosition** property returns or specifies the horizontal offset of the bullet symbol from the left text margin in a text range.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.BulletSize

Property **BulletSize** As Single

Description

Member of TextRange

The **BulletSize** property returns or specifies the font size, in points, of the bullet symbol in a text range.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.BulletSymbol

Property **BulletSymbol** As String

Description

Member of TextRange

The **BulletSymbol** property returns or specifies the character to use as the bullet in a text range.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Case

Property **Case** As cdrFontCase

Description

Member of TextRange

The **Case** property returns or specifies the case of the text in a text range.

VBA example

The following VBA example capitalizes all characters in the paragraph.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, "This is an example.")
 Set t = s.Text
 t.Story.Case = cdrAllCapsFontCase
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.ChangeCase

Sub **ChangeCase(**Case As cdrTextChangeCase**)**

Description

Member of TextRange

The **ChangeCase** method changes the case of the text in a text range.

Parameter	Description
Case	Specifies the case

VBA example

The following VBA example converts the text to uppercase.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, _
  "This is an example.")
 Set t = s.Text
 t.Story.ChangeCase cdrTextUpperCase
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Characters

Property **Characters** As TextCharacters

Description

Member of TextRange

The **Characters** property returns all the characters in a text range.

The **Characters** property returns a read-only value.

VBA example

The following VBA example applies bold formatting to all the characters in the paragraph-text object.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, "This is an example.")
 Set t = s.Text
 t.Story.Characters.All.Bold = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.CharAngle

Property **CharAngle** As Single

Description

Member of TextRange

The **CharAngle** property returns or specifies the rotation angle of a text range.

VBA example

The following VBA example sets the rotation angle for the text range to **77**°.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, "This is an example.")
 Set t = s.Text
 t.Story.CharAngle = 77
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.CharBackFill

Property **CharBackFill** As Fill

Description

Member of TextRange

The **CharBackFill** property returns a read-only value that is associated with the background color of the characters in a text range.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.CharSet

Property **CharSet** As cdrTextCharSet

Description

Member of TextRange

The **CharSet** property returns or specifies the character set of a text range.

VBA example

The following VBA example changes the character set and the language to Greek, and it adds characters to be typed in Greek.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Dim tr As TextRange
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, "This is an example: ", Font:="Arial")
 Set t = s.Text
 Set tr = t.Story.InsertAfter("áâãäåæçèéêëìíîïðñòóôõö")
 tr.CharSet = cdrCharSetGreek
 tr.LanguageID = cdrGreek
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.CharSpacing

Property **CharSpacing** As Single

Description

Member of TextRange

The **CharSpacing** property returns or specifies the spacing between the characters in a text range.

VBA example

The following VBA example sets the character spacing to **1.3**.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, "This is an example.")
 Set t = s.Text
 t.Story.CharSpacing = 1.3
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Collapse

Sub **Collapse([**ToEnd As Boolean = True**])**

Description

Member of TextRange

The **Collapse** method collapses a text range.

Parameter	Description
ToEnd	This parameter is optional, and its default value is **True**.

VBA example

The following VBA example displays the positions of the starting and ending characters of the text range before and after the text is collapsed. It then inserts text and applies bold formatting to the inserted text.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim tr As TextRange
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, "This is an example.")
 Set t = s.Text
 Set tr = t.Story.Words(2, 2)
 MsgBox "The text range is from " & tr.Start & " to " & tr.End & " Characters"
 tr.Collapse
 MsgBox "The text range is from " & tr.Start & " to " & tr.End & " Characters"
 tr.Text = " This will be inserted at the current position. "
 tr.Bold = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Columns

Property **Columns** As TextColumns

Description

Member of TextRange

The **Columns** property returns all the text columns in a text range.

The **Columns** property returns a read-only value.

VBA example

The following VBA example links frames of paragraph text. Three columns are created in the first frame, and the second column is filled with red.

```
Sub Test()
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim d As Document
 Dim t As Text
 Dim strText As String
 strText = "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. This is a test."
 strText = strText & " This is the next sentence. " & strText
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, strText)
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 ' set the columns
 t.Frame.SetColumns 3, False, Array(0.7, 0.1, 1, 0.1, 1)
 t.Story.Columns.Item(2).Fill.UniformColor.RGBAssign 155, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Combine

Sub **Combine(**Range As TextRange**)**

Description

Member of TextRange

The **Combine** method combines the current text range with a specified range.

Parameter	Description
Range	Specifies the text range to be combined

VBA example

The following VBA example stores the fourth word and the second line in separate text ranges. It duplicates the fourth word and combines it with the text range for the second line. Bold formatting is applied to the fourth word, and the second line is underlined. The combined text range is then filled with red.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim trLine As TextRange
 Dim trWord As TextRange
 Dim tr As TextRange
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, _
  "This is a line 1." & vbCr & "This is line 2.")
 Set t = s.Text
 Set trWord = t.Story.Words(4)
 Set trLine = t.Story.Lines(2)
 Set tr = trWord.Duplicate
 tr.Combine trLine
 trWord.Bold = True
 trLine.Underline = cdrSingleThickFontLine
 tr.Fill.UniformColor.RGBAssign 155, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Copy

Sub **Copy()**

Description

Member of TextRange

The **Copy** method copies a text range to the Clipboard.

VBA example

The following VBA example creates paragraph text, applies bold formatting to the fourth and fifth words, and italicizes the first word. It then copies the text range and pastes it in the second paragraph.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim s1 As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, _
  "This is an example.")
 Set s1 = d.ActiveLayer.CreateParagraphText(7, 7, 9, 9)
 Set t = s.Text
 t.Story.Words(4, 2).Bold = True
 t.Story.Words(1).Italic = True
 t.Story.Copy
 s1.Text.Story.Paste
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.CopyAttributes

Sub **CopyAttributes(**SourceRange As TextRange**)**

Description

Member of TextRange

The **CopyAttributes** method copies the text attributes from the specified text range and applies them to the current text range.

Parameter	Description
SourceRange	Specifies the text range from which to copy attributes

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Delete

Sub **Delete()**

Description

Member of TextRange

The **Delete** method removes specified characters from a text range.

VBA example

The following VBA example deletes the first word in the text range.

```
Sub Test()
 Dim d As Document
 Dim t As Text
 Dim s As Shape
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 t.Story.Words.First.Delete
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.DropCapDistanceFromText

Property **DropCapDistanceFromText** As Double

Description

Member of TextRange

The **DropCapDistanceFromText** property returns or specifies the distance between a drop cap and the rest of the text in a text range.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.DropCapHangingIndent

Property **DropCapHangingIndent** As Boolean

Description

Member of TextRange

The **DropCapHangingIndent** property returns or specifies the hanging indentation for paragraphs when a drop-cap effect is applied to a text range.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.DropCapLinesDropped

Property **DropCapLinesDropped** As Long

Description

Member of TextRange

The **DropCapLinesDropped** property returns or specifies the number of lines that a drop-cap effect drops in a text range.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Duplicate

Function **Duplicate()** As TextRange

Description

Member of TextRange

The **Duplicate** method returns a copy of a text range.

VBA example

The following VBA example duplicates the first five characters of the paragraph and displays them in a message box.

```
Sub Test()
 Dim d As Document
 Dim t As Text
 Dim s As Shape
 Dim tr As TextRange
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 Set tr = t.Story.Characters(1, 5).Duplicate
 MsgBox "The text that is duplicated is: " & vbCr & tr.Text
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Effect

Property **Effect** As cdrTextEffect

Description

Member of TextRange

The **Effect** property returns the type of effect applied to a text range.

The **Effect** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.End

Property **End** As Long

Description

Member of TextRange

The **End** property returns the position of the ending character in a text range.

VBA example

The following VBA example displays the ending position of the first word in the paragraph.

```
Sub Test()
 Dim s As Shape
 Dim d As Document
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 MsgBox "The end position of the first word is " & t.Story.Words.First.End
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.EnumRanges

Function **EnumRanges([**PropertyFilter As cdrTextPropertySet = cdrTextPropertyAll**])** As TextRanges

Description

Member of TextRange

The **EnumRanges** method returns a collection of text ranges that share the same character attributes.

Parameter	Description
PropertyFilter	Specifies the character attributes

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Evaluate

Function **Evaluate(***Expression As String***)**

Description

Member of TextRange

The **Evaluate** method evaluates a given Corel Query Language (CQL) expression by using the properties of a text range and returns the result of the expression.

- For information on CQL, see the section "Including queries in macros."

Parameter	Description
Expression	Specifies the CQL expression

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Fill

Property **Fill** As Fill

Description

Member of TextRange

The **Fill** property returns the fill (or Fill object) applied to a text range.

The **Fill** property returns a read-only value.

VBA example

The following VBA example applies a conical fountain fill to the last word of the paragraph text.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, "This is an example")
 Set t = s.Text
 t.Story.Words.Last.Fill.ApplyFountainFill CreateRGBColor(255, 0, 0), CreateRGBColor(0, 0, 255),
cdrConicalFountainFill
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.FindRanges

Function **FindRanges(***Query As String***)** As TextRanges

Description

Member of TextRange

The **FindRanges** method finds text-character ranges by using the supplied query condition in Corel Query Language (CQL).

- For information on CQL, see the section "Including queries in macros."

Parameter	Description
Query	Specifies the CQL query

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.FirstLineIndent

Property **FirstLineIndent** As Double

Description

Member of TextRange

The **FirstLineIndent** property returns or specifies the amount by which the first line of each paragraph is indented in a text range.

VBA example

The following VBA example indents the first line of the paragraph text by **0.5**".

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example. This is an example. This is an
example.")
 Set t = s.Text
 t.Story.FirstLineIndent = 0.5
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Font

Property **Font** As String

Description

Member of TextRange

The **Font** property returns of sets the name of the font for a text range.

VBA example

The following VBA example sets the paragraph font to **24**-point **Arial**.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 t.Story.Font = "Arial"
 t.Story.Size = 24
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Frames

Property **Frames** As TextFrames

Description

Member of TextRange

The **Frames** property returns all the text frames in a text range.

The **Frames** property returns a read-only value.

VBA example

The following VBA example applies bold formatting to the text of the first frame.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim s1 As Shape
 Dim s2 As Shape
 Dim t As Text
 Dim strText As String
 strText = "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. This is a test. "
 strText = strText & " This is the next part " & strText & strText
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, strText)
 Set s1 = d.ActiveLayer.CreateParagraphText(5, 5, 8, 8)
 Set s2 = d.ActiveLayer.CreateParagraphText(8, 8, 10, 10)
 Set t = s.Text
 ' Link the frames together.
 t.Frame.LinkTo s1
 s1.Text.Frame.LinkTo s2
 ' Bold the first frame.
 t.Frames.First.Range.Bold = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.GetOpenTypeFeature

Function **GetOpenTypeFeature(***Feature As String***)** As Long

Description

Member of TextRange

The **GetOpenTypeFeature** method returns the current state of the OpenType feature applied to the text range.

Parameter	Description
Feature	Specifies the OpenType feature

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.HorizShift

Property **HorizShift** As Long

Description

Member of TextRange

The **HorizShift** properety returns or specifies the amount by which the text in a text range is shifted horizontally.

VBA example

The following VBA example shifts the paragraph text horizontally.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 t.Story.HorizShift = 3
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.HyphenateAllCapWords

Property **HyphenateAllCapWords** As Boolean

Description

Member of TextRange

The **HyphenateAllCapWords** property returns or specifies whether to hyphenate all the uppercase words in a text range.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.HyphenateCapitals

Property **HyphenateCapitals** As Boolean

Description

Member of TextRange

The **HyphenateCapitals** property returns or specifies whether to hyphenate the capitalized words in a text range.

VBA example

The following VBA example enables the hypenation of capitalized words.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 t.Story.HyphenateCapitals = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.HyphenHotZone

Property **HyphenHotZone** As Double

Description

Member of TextRange

The **HyphenHotZone** property returns or specifies the distance from the right margin at which hyphenation begins in a text range.

VBA example

The following VBA example displays the value of the hot-zone for hyphenation.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 MsgBox t.Story.HyphenHotZone
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.HyphenMinCharsAfter

Property **HyphenMinCharsAfter** As Long

Description

Member of TextRange

The **HyphenMinCharsAfter** property returns or specifies the minimum number of characters that must appear in the hot-zone after a hyphen in a text range.

VBA example

The following VBA example displays the minimum number of characters that must appear in the hot-zone after a hyphen.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 MsgBox t.Story.HyphenMinCharsAfter
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.HyphenMinCharsBefore

Property **HyphenMinCharsBefore** As Long

Description

Member of TextRange

The **HyphenMinCharsBefore** property returns or specifies the minimum number of characters that must appear in the hot-zone before a hyphen in a text range.

VBA example

The following VBA example displays the minimum number of characters that must appear in the hot-zone before a hyphen.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 MsgBox t.Story.HyphenMinCharsBefore
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.HyphenMinWordLength

Property **HyphenMinWordLength** As Long

Description

Member of TextRange

The **HyphenMinWordLength** property returns or specifies the minimum number of characters that a word must have for it to be included in automatic hyphenation in a text range.

VBA example

The following VBA example displays the minimum number of characters that a word must have for it to be included in automatic hyphenation.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 MsgBox t.Story.HyphenMinWordLength
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.InRange

Function **InRange(**Range As TextRange**)** As Boolean

Description

Member of TextRange

The **InRange** method returns whether the current text range is within a specified range.

Parameter	Description
Range	Specifies the range

VBA example

The following VBA example displays whether the second word is in the first frame.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, _
  "This is an example")
 Set t = s.Text
 If t.Story.Words(2).InRange(t.Frames(1).Range) Then
  MsgBox "The second word is in the first frame."
 Else
  MsgBox "The second word is not in the first frame."
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.InsertAfter

Function **InsertAfter(***Text As String***, [**LanguageID As cdrTextLanguage = cdrLanguageNone**], [**CharSet As cdrTextCharSet = cdrCharSetMixed**], *[Font As String***]**) As TextRange

Description

Member of TextRange

The **InsertAfter** method inserts text after the last character in a text range, returning a text range that contains only the inserted characters.

Parameter	Description
Text	Specifies the text to insert
LanguageID	Specifies the language code. This parameter is optional, and its default value is cdrLanguageNone (**0**).
CharSet	Specifies the character set. This parameter is optional, and its default value is cdrCharSetMixed (**-1**)
Font	Specifies the font. This parameter is optional.

VBA example

The following VBA example inserts the sentence **This will be inserted last.** after the paragraph text **This is an example.**

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, _
  "This is an example.")
 Set t = s.Text
 t.Story.InsertAfter ("This will be inserted last. ")
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.InsertAfterWide

Function **InsertAfterWide(***Text As String***, [**LanguageID As cdrTextLanguage = cdrLanguageNone**], [**CharSet As cdrTextCharSet = cdrCharSetMixed**], [***Font As String***]) As TextRange**

The **InsertAfterWide** method inserts Unicode text after the last character in a text range, returning a text range that contains only the inserted characters.

Parameter	Description
Text	Specifies the text to insert
LanguageID	Specifies the language code. This parameter is optional, and its default value is cdrLanguageNone (**0**).
CharSet	Specifies the character set. This parameter is optional, and its default value is cdrCharSetMixed (**-1**).
Font	Specifies the font. This parameter is optional.

VBA example

The following VBA example creates two Japanese characters by using their character codes, and it then inserts the same two characters after the first ones.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphTextWide(2, 2, 8, 8, _
  ChrW$(-32022) & ChrW$(-32072), cdrJapanese, cdrCharSetShiftJIS, _
  Font:="MS Gothic")
 Set t = s.Text
 t.Story.InsertAfterWide " " & t.Story.WideText
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.InsertBefore

Function **InsertBefore(***Text As String***, [**LanguageID As cdrTextLanguage = cdrLanguageNone**], [**CharSet As cdrTextCharSet = cdrCharSetMixed**], [***Font As String***]) As TextRange

Description

Member of TextRange

The **InsertBefore** method inserts new text before the first character in the text range, returning a text range that contains only the inserted characters.

Parameter	Description
Text	Specifies the text to insert
LanguageID	Specifies the language code. This parameter is optional, and its default value is cdrLanguageNone (**0**).
CharSet	Specifies the character set. This parameter is optional, and its default value is cdrCharSetMixed (**-1**).
Font	Specifies the font. This parameter is optional.

VBA example

The following VBA example inserts the sentence **This will be inserted first.** before the paragraph text **This is an example.**

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, _
  "This is an example.")
 Set t = s.Text
 t.Story.InsertBefore ("This will be inserted first. ")
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.InsertBeforeWide

Function **InsertBeforeWide(***Text As String***, [**LanguageID As cdrTextLanguage = cdrLanguageNone**], [**CharSet As cdrTextCharSet = cdrCharSetMixed**], [***Font As String***]) As** TextRange

Description

Member of TextRange

The **InsertBeforeWide** method inserts Unicode text before the first character in a text range, returning a text range that contains only the inserted characters.

Parameter	Description
Text	Specifies the text to insert
LanguageID	Specifies the language code. This parameter is optional, and its default value is cdrLanguageNone (**0**).
CharSet	Specifies the character set. This parameter is optional, and its default value is cdrCharSetMixed (**-1**).
Font	Specifies the font. This parameter is optional.

VBA example

The following VBA example creates two Japanese characters by using their character codes, and it then inserts the same two characters before the first ones.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphTextWide(2, 2, 8, 8, _
  ChrW$(-32022) & ChrW$(-32072), cdrJapanese, cdrCharSetShiftJIS, _
  Font:="MS Gothic")
 Set t = s.Text
 t.Story.InsertBeforeWide " " & t.Story.WideText
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.IsEmpty

Property **IsEmpty** As Boolean

Description

Member of TextRange

The **IsEmpty** property returns **True** if a text range is of zero length (that is, if it has no characters in it).

The **IsEmpty** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.IsSame

Function **IsSame(**Range As TextRange**)** As Boolean

Description

Member of TextRange

The **IsSame** method returns whether the current text range is the same as a specified range.

Parameter	Description
Range	Specifies the range with which to compare

VBA example

The following VBA example displays whether all the words are in the first frame.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, "This is an example.")
 Set t = s.Text
 If t.Story.Words.All.IsSame(t.Frames(1).Range) Then
  MsgBox "All of the words are in the first range."
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Italic

Property **Italic** As Boolean

Description

Member of TextRange

The **Italic** propertey returns or specifies whether italics are applied to a text range.

VBA example

The following VBA example applies italics to all text in the paragraph.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, "This is an example.")
 Set t = s.Text
 t.Story.Italic = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.LanguageID

Property **LanguageID** As cdrTextLanguage

Description

Member of TextRange

The **LanguageID** property returns or specifies the language code for a text range.

VBA example

The following VBA example changes the character set and the language code to Greek, and it adds characters that are to be typed in Greek.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Dim tr As TextRange
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, _
  "This is an example: ", Font:="Arial")
 Set t = s.Text
 Set tr = t.Story.InsertAfter("áâãäåæçèéêëìíîïðñòóôõö")
 tr.CharSet = cdrCharSetGreek
 tr.LanguageID = cdrGreek
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.LeftIndent

Property **LeftIndent** As Double

Description

Member of TextRange

The **LeftIndent** property returns or specifies the amount by which text is indented from the left side of the frame in a text range. All lines except for the first line of each paragraph are indented.

VBA example

The following VBA example sets the hanging indentation of the paragraph to **0.5**".

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, _
  "This is an example. This is an example. This is an "_& _
  "example. This is an example. This is an example.")
 Set t = s.Text
 t.Story.LeftIndent = 0.5
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Length

Property **Length** As Long

Description

Member of TextRange

The **Length** property returns the number of characteres in a text range.

VBA example

The following VBA example displays the number of characters in the paragraph.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, _
  "This is an example for length")
 Set t = s.Text
 MsgBox "The length of the characters in the paragraph text is " & _
  t.Story.Length
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Lines

Property **Lines** As TextLines

Description

Member of TextRange

The **Lines** property returns all the lines in a text range.

The **Lines** property returns a read-only value.

VBA example

The following VBA example fills the second and third lines of the paragraph with red.

```
Sub Test
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Dim strText As String
 strText = "This is a test. This is a test. This is a test. " & _
  "This is a test. This is a test. This is a test. "
 strText = strText & " This is the next sentence. " & strText
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 5, 5, strText)
 Set t = s.Text
 t.Story.Lines.Item(2, 2).Fill.UniformColor.RGBAssign 155, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.LineSpacing

Property **LineSpacing** As Single

Description

Member of TextRange

The **LineSpacing** property returns or specifies the line spacing in a text range.

VBA example

The following VBA example displays the line spacing in the text range.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 MsgBox t.Story.LineSpacing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.LineSpacingType

Property **LineSpacingType** As cdrLineSpacingType

Description

Member of TextRange

The **LineSpacingType** property returns or specifies the type of line spacing in a text range.

The **LineSpacingType** property returns a read-only value.

VBA example

The following VBA example sets the line spacing to a percentage of the character height, verifying that the option was applied.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is " & _
  "sample text to illustrate the line spacing in the " & _
  "TextRange object.")
 Set t = s.Text
 t.Story.SetLineSpacing cdrPercentOfCharacterHeightLineSpacing, 0.3, 0.2, 0.4
 If t.Story.LineSpacingType = cdrPercentOfCharacterHeightLineSpacing Then
  MsgBox "The line spacing is set to a percentage of the " & _
   "character height."
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.MaxCharSpacing

Property **MaxCharSpacing** As Single

Description

Member of TextRange

The **MaxCharSpacing** property returns or specifies the maximum amount of spacing between each character in a text range.

VBA example

The following VBA example displays the maximum amount of spacing between each character.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 MsgBox t.Story.MaxCharSpacing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.MaxWordSpacing

Property **MaxWordSpacing** As Single

Description

Member of TextRange

The **MaxWordSpacing** property returns or specifies the maximum amount of spacing between each word in a text range.

VBA example

The following VBA example displays the maximum amount of spacing between each word.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 MsgBox t.Story.MaxWordSpacing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.MinWordSpacing

Property **MinWordSpacing** As Single

Description

Member of TextRange

The **MinWordSpacing** property returns or specifies the minimum amount of spacing between each word in a text range.

VBA example

The following VBA example displays the minimum amount of spacing between each word.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 MsgBox t.Story.MinWordSpacing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.ObjectStyle

Property **ObjectStyle** As Style

Description

Member of TextRange

The **ObjectStyle** property returns the style that is currently applied to the text in a text range. This property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Outline

Property **Outline** As Outline

Description

Member of TextRange

The **Outline** property returns the outline (or Outline object) applied to a text range.

The **Outline** property returns a read-only value.

VBA example

The following VBA example changes the width of the last word of the paragraph to **2** inches.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, "This is an example.")
 Set t = s.Text
 t.Story.Words.Last.Outline.Width = 2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Overscore

Property **Overscore** As cdrFontLine

Description

Member of TextRange

The **Overscore** property returns or specifies whether an overline is applied to a text range.

VBA example

The following VBA example applies an overline to all the text in the paragraph.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, "This is an example.")
 Set t = s.Text
 t.Story.Overscore = cdrDoubleThinFontLine
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Paragraphs

Property **Paragraphs** As TextParagraphs

Description

Member of TextRange

The **Paragraphs** property returns all the paragraphs in a text range.

The **Paragraphs** property returns a read-only value.

VBA example

The following VBA example applies bold formatting and underlining to the third paragraph.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Dim strText As String
 strText = "This is a paragraph. " & vbCr & _
  "This is a paragraph. " & vbCr & _
  "This is a paragraph. " & vbCr & _
  "This is a paragraph. " & vbCr & _
  "This is a paragraph."
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, strText)
 Set t = s.Text
 t.Story.Paragraphs.Item(3).Bold = True
 t.Story.Paragraphs.Item(3).Underline = cdrDoubleThinFontLine
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.ParaSpacingAfter

Property **ParaSpacingAfter** As Single

Description

Member of TextRange

The **ParaSpacingAfter** propertey returns or specifies the amount of spacing after a paragraph in a text range.

VBA example

The following VBA example displays the amount of spacing after the paragraph.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example")
 Set t = s.Text
 MsgBox t.Story.ParaSpacingAfter
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.ParaSpacingBefore

Property **ParaSpacingBefore** As Single

Description

Member of TextRange

The **ParaSpacingBefore** property returns or specifies the amount of spacing before a paragraph in a text range.

VBA example

The following VBA example displays the amount of spacing before the paragraph.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 MsgBox t.Story.ParaSpacingBefore
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Paste

Function **Paste()** As TextRange

Description

Member of TextRange

The **Paste** method replaces a text range and returns the new one.

VBA example

The following VBA example creates paragraph text, applies bold formatting to the fourth and fifth words, and italicizes the first word. It then copies the text range and pastes it in the second paragraph.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim s1 As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, _
  "This is an example.")
 Set s1 = d.ActiveLayer.CreateParagraphText(7, 7, 9, 9)
 Set t = s.Text
 t.Story.Words(4, 2).Bold = True
 t.Story.Words(1).Italic = True
 t.Story.Copy
 s1.Text.Story.Paste
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Position

Property **Position** As cdrFontPosition

Description

Member of TextRange

The **Position** property returns or specifies the font position of a text range.

VBA example

The following VBA example changes the position of the first word of the paragraph to subscript.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, "This is an example.")
 Set t = s.Text
 t.Story.Words.First.Position = cdrSubscriptFontPosition
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Range

Function **Range(***Start As Long*, *End As Long***)** As TextRange

Description

Member of TextRange

The **Range** method returns a range of characters from a text range.

Parameter	Description
Start	Specifies the first character in the range
End	Specifies the last character in the range

VBA example

The following VBA example applies bold formatting to the fourth to seventh characters in the range.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, _
  "This is an example.")
 Set t = s.Text
 t.Story.Range(4, 7).Bold = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.RangeKerning

Property **RangeKerning** As Long

Description

Member of TextRange

The **RangeKerning** property returns or specifies the character-range kerning of a text range.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Replace

Function **Replace(***Text As String***, [**LanguageID As cdrTextLanguage = cdrLanguageNone**], [**CharSet As cdrTextCharSet = cdrCharSetMixed**], [***Font As String***]) As TextRange

Description

Member of TextRange

The **Replace** method replaces a text range with a text string and returns the new range.

Parameter	Description
Text	Specifies the text to insert
LanguageID	Specifies the language code. This parameter is optional, and its default value is cdrLanguageNone (**0**).
CharSet	Specifies the character set. This parameter is optional, and its default value is cdrCharSetMixed (**-1**).
Font	Specifies the font. This parameter is optional.

VBA example

The following VBA example replaces the first word with new text.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, _
  "This is an example.")
 Set t = s.Text
 t.Story.Words.First.Replace "This will replace the first word " & _
  "with this text "
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.ReplaceWide

Function **ReplaceWide(***Text As String***, [**LanguageID As cdrTextLanguage = cdrLanguageNone**], [**CharSet As cdrTextCharSet = cdrCharSetMixed**], [***Font As String***]) As TextRange**

Description

Member of TextRange

The **ReplaceWide** method replaces a text range with Unicode text and returns the new range.

Parameter	Description
Text	Specifies the text to insert
LanguageID	Specifies the language code. This parameter is optional, and its default value is cdrLanguageNone (**0**).
CharSet	Specifies the character set. This parameter is optional, and its default value is cdrCharSetMixed (**-1**).
Font	Specifies the font. This parameter is optional.

VBA example

The following VBA example creates two Japanese characters by using their character codes, and it then replaces the first character with the two that were first created.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphTextWide(2, 2, 8, 8,
  ChrW$(-32022) & ChrW$(-32072), cdrJapanese, cdrCharSetShiftJIS, _
  Font:="MS Gothic")
 Set t = s.Text
 t.Story.Characters.First.ReplaceWide ChrW$(-32022) & ChrW$(-32072)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.RightIndent

Property **RightIndent** As Double

Description

Member of TextRange

The **RightIndent** property returns or specifies the amount by which the text is indented on the right side in a text range.

VBA example

The following VBA example indents the right side of the paragraph by **0.2**".

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, _
  "This is an example. This is an example. This is an "_& _
  "example. This is an example.")
 Set t = s.Text
 t.Story.RightIndent = 0.2
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Select

Sub **Select()**

Description

Member of TextRange

The **Select** method selects the characters in a text range.

VBA example

The following VBA example places the text in editing mode and selects the first word.

```
Sub Test()
 Dim d As Document
 Dim t As Text
 Dim s As Shape
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 t.BeginEdit
 t.Story.Words.First.Select
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.SetLineSpacing

Sub **SetLineSpacing(**Type As cdrLineSpacingType**, [**LineSpacing As Single = -1**], [**ParaBefore As Single = -1**], [**ParaAfter As Single = -1**])**

Description

Member of TextRange

The **SetLineSpacing** method sets the line-spacing properties for a text range.

Parameter	Description
Type	Specifies how to measure the line spacing
LineSpacing	Specifies the value for line spacing. This parameter is optional, and its default value is **-1**.
ParaBefore	This parameter is optional, and its default value is **-1**.
ParaAfter	This parameter is optional, and its default value is **-1**.

VBA example

The following VBA example sets the line spacing to a percentage of the character height, verifying that the option was applied.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is " & _
  "sample text to illustrate the line spacing in the " & _
  "TextRange object.")
 Set t = s.Text
 t.Story.SetLineSpacing cdrPercentOfCharacterHeightLineSpacing, 0.3, 0.2, 0.4
 If t.Story.LineSpacingType = cdrPercentOfCharacterHeightLineSpacing Then
 If t.Story.LineSpacingType = cdrPercentOfCharacterHeightLineSpacing Then
  MsgBox "The line spacing is set to a percentage of the " & _
   "character height."
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.SetOpenTypeFeature

Function **SetOpenTypeFeature(***Feature As String, State As Long***)**

Description

Member of TextRange

The **SetOpenTypeFeature** method changes the state of the OpenType feature applied to the text range.

Parameter	Description
Feature	Specifies the OpenType feature
State	Specifies the state of the OpenType feature

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.SetRange

Sub **SetRange(***Start As Long*, *End As Long***)**

Description

Member of TextRange

The **SetRange** method sets the starting and ending positions of a text range.

Parameter	Description
Start	Specifies the starting position
End	Specifies the ending position

VBA example

The following VBA example underlines the text range that includes the third-to-tenth characters.

```
Sub Test()
 Dim s As Shape
 Dim tr As TextRange
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, _
  "This is an example")
 Set tr = s.Text.Story
 tr.SetRange 3, 10
 tr.Underline = cdrDoubleThinFontLine
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Size

Property **Size** As Single

Description

Member of TextRange

The **Size** property returns or specifies the font size for a text range..

VBA example

The following VBA example sets the font of the paragraph to **24**-point **Arial**.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 t.Story.Font = "Arial"
 t.Story.Size = 24
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Start

Property **Start** As Long

Description

Member of TextRange

The **Start** property returns the position of the starting character in a text range.

VBA example

The following VBA example displays the starting position of the last word.

```
Sub Test()
 Dim s As Shape
 Dim d As Document
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 MsgBox "The last word starts at the following position: " & _
  t.Story.Words.Last.Start
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Straighten

Sub **Straighten()**

Description

Member of TextRange

The **Straighten** method removes horizontal and vertical character shifts and rotations.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Strikethru

Property **Strikethru** As cdrFontLine

Description

Member of TextRange

The **Strikethru** property returns or specifies whether a strikethrough line is applied to a text range.

VBA example

The following VBA example applies a strikethrough line to all the text in the paragraph.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, "This is an example.")
 Set t = s.Text
 t.Story.Strikethru = cdrDoubleThinFontLine
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Style

Property **Style** As cdrFontStyle

Description

Member of TextRange

The **Style** property returns of sets the font style of a text range.

VBA example

The following VBA example applies bold formatting to the paragraph:

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, "This is an example.")
 Set t = s.Text
 t.Story.Style = cdrBoldFontStyle
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Tabs

Property **Tabs** As TextTabPositions

Description

Member of TextRange

The **Table** property returns all the tabs stops defined for a text range.

The **Table** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Text

Property **Text** As String

Description

Member of TextRange

The **Text** property returns or specifies the text string in a text range. It is the default property of the TextRange class.

VBA example

The following VBA example displays the text in the paragraph.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, "This is an example.")
 Set t = s.Text
 MsgBox t.Story.Text
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.TextFormatter

Property **TextFormatter** As Long

Description

Member of TextRange

The **TextFormatter** property returns or specifies the text formatter version for the text range. A value of 1500 indicates that the text formatter is used for product versions X5 and earlier. A value of 1600 indicates that the text formatter is used in version X6.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.TextLineRects

Property **TextLineRects** As Curve

Description

Member of TextRange

The **TextLineRects** property returns a curve consisting of a set of rectangular subpaths that represent the bounding box of each text line in a text range.

The **TextLineRects** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Underline

Property **Underline** As cdrFontLine

Description

Member of TextRange

The **Underline** property returns or specifies whether an underline is applied to a text range.

VBA example

The following VBA example underlines all text in the paragraph with a thin double line.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, "This is an example.")
 Set t = s.Text
 t.Story.Underline = cdrDoubleThinFontLine
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.VertShift

Property **VertShift** As Long

Description

Member of TextRange

The **VertShift** property returns or specifies the amount by which the text in a text range is shifted vertically.

VBA example

The following VBA example shifts the paragraph vertically.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 t.Story.VertShift = 3
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.WideText

Property **WideText** As String

Description

Member of TextRange

The **WideText** property returns or specifies a Unicode text string for a text range.

VBA example

The following VBA example creates two Japanese characters by using their character codes, and it then appends the same two characters to the text string.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphTextWide(2, 2, 8, 8, _
  ChrW$(-32022) & ChrW$(-32072), cdrJapanese, cdrCharSetShiftJIS, _
  Font:="MS Gothic")
 Set t = s.Text
 t.Story.InsertAfterWide " " & t.Story.WideText
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.Words

Property **Words** As TextWords

Description

Member of TextRange

The **Words** property returns all the words in a text range.

The **Words** property returns a read-only value.

VBA example

The following VBA example underlines the last word of the paragraph and applies bold formatting to the first word.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 4, 4, "This is an example.")
 Set t = s.Text
 t.Story.Words.Last.Underline = cdrDoubleThinFontLine
 t.Story.Words.First.Bold = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRange.WordSpacing

Property **WordSpacing** As Single

Description

Member of TextRange

The **WordSpacing** property returns or specifies the amount of spacing between each word in a text range.

VBA example

The following VBA example displays the word spacing.

```
Sub Test()
 Dim d As Document
 Dim s As Shape
 Dim t As Text
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(3, 3, 5, 5, "This is an example.")
 Set t = s.Text
 MsgBox t.Story.WordSpacing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextRanges

Properties Methods

Description

The **TextRanges** class represents a collection of text ranges (or TextRange objects).

Copyright 2014 Corel Corporation. All rights reserved.

TextRanges.Count

Property **Count** As Long

Description

Member of TextRanges

The **Count** property returns a read-only value that is associated with the number of text ranges (or TextRange objects) in a TextRanges collection.

Copyright 2014 Corel Corporation. All rights reserved.

TextRanges.First

Property **First** As TextRange

Description

Member of TextRanges

The **First** property returns a read-only value that is associated with the first text range (or TextRange object) in a TextRanges collection.

Copyright 2014 Corel Corporation. All rights reserved.

TextRanges.Item

Property **Item(***Index As Long***)** As TextRange

Description

Member of TextRanges

The **Item** property returns a read-only value that is associated with a specified text range (or TextRange object) in a TextRanges collection.

Item is the default property of the **TextRanges** class.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each member of the **TextRanges** collection

Copyright 2014 Corel Corporation. All rights reserved.

TextRanges.Last

Property **Last** As TextRange

Description

Member of TextRanges

The **Last** property returns a read-only value that is associated with the last text range (or TextRange object) in a TextRanges collection.

Copyright 2014 Corel Corporation. All rights reserved.

TextRanges.Reverse

Function **Reverse()** As TextRanges

Description

Member of TextRanges

The **Reverse** method returns a specified TextRanges collection with the order of its text ranges reversed.

Copyright 2014 Corel Corporation. All rights reserved.

TextTabPosition

Properties Methods

Description

The **TextTabPosition** class represents the position of a text tab.

Copyright 2014 Corel Corporation. All rights reserved.

TextTabPosition.Alignment

Property **Alignment** As cdrTextTabAlignment

Description

Member of TextTabPosition

The **Alignment** property returns or specifies the alignment for a tab-stop position.

Copyright 2014 Corel Corporation. All rights reserved.

TextTabPosition.Delete

Sub **Delete()**

Description

Member of TextTabPosition

The **Delete** method deletes a tab stop.

Copyright 2014 Corel Corporation. All rights reserved.

TextTabPosition.Index

Property **Index** As Long

Description

Member of TextTabPosition

The **Index** property returns a tab stop, among all available tab stops, as specified by its index number.

The **Index** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TextTabPosition.Leadered

Property **Leadered** As Boolean

Description

Member of TextTabPosition

The **Leadered** property specifies whether a tab-stop position uses a leader character to fill the empty space.

Copyright 2014 Corel Corporation. All rights reserved.

TextTabPosition.Position

Property **Position** As Double

Description

Member of TextTabPosition

The **Position** property returns or specifies the horizontal position of a tab stop in a text frame. It is the default property of the TextTabPosition class.

Copyright 2014 Corel Corporation. All rights reserved.

TextTabPositions

Properties Methods

Description

The **TextTabPositions** class represents a collection of text tab positions (or TextTabPosition objects).

Copyright 2014 Corel Corporation. All rights reserved.

TextTabPositions.Add

Function **Add(***Position As Double***, [**Alignment As cdrTextTabAlignment = cdrTextTabLeft**], [**Leadered As Boolean = False**])** As TextTabPosition

Description

Member of TextTabPositions

The **Add** method adds a new tab stop to the text in a text range.

Parameter	Description
Position	Specifies the horizontal position of a tab stop
Alignment	Specifies the alignment for a tab-stop position. This parameter is optional, and its default value is cdrTextTabLeft (**0**).
Leadered	Specifies whether a tab-stop position uses a leader character to fill the empty space. This parameter is optional, and its default value is **False**.

Copyright 2014 Corel Corporation. All rights reserved.

TextTabPositions.AddEvery

Sub **AddEvery(***Position As Double***, [**Alignment As cdrTextTabAlignment = cdrTextTabLeft**], [**Leadered As Boolean = False**])** As TextTabPosition

Description

Member of TextTabPositions

The **AddEvery** method adds, to the text in a text range, new tab stops placed at a given distance from each other.

Parameter	Description
Position	Specifies the horizontal position of a tab stop
Alignment	Specifies the alignment for a tab-stop position. This parameter is optional, and its default value is cdrTextTabLeft (**0**).
Leadered	Specifies whether a tab-stop position uses a leader character to fill the empty space. This parameter is optional, and its default value is **False**.

Copyright 2014 Corel Corporation. All rights reserved.

TextTabPositions.Clear

Sub **Clear()**

Description

Member of TextTabPositions

The **Clear** method deletes all tab-stop positions from a text range.

Copyright 2014 Corel Corporation. All rights reserved.

TextTabPositions.Count

Property **Count** As Long

Description

Member of TextTabPositions

The **Count** property returns the number of tab positions defined for a text range.

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TextTabPositions.Item

Property **Item(***Index As Long***)** As TextTabPosition

Description

Member of TextTabPositions

The **Item** property returns a specified tab position from a TextTabPositions collection. It is the default property of the **TextTabPositions** class.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each member of the **TextTabPositions** collection

Copyright 2014 Corel Corporation. All rights reserved.

TextTabPositions.LeaderCharacter

Property **LeaderCharacter** As String

Description

Member of TextTabPositions

The **LeaderCharacter** property returns or specifies the leader character to be used with the tab stops in a text range.

Copyright 2014 Corel Corporation. All rights reserved.

TextTabPositions.LeaderSpacing

Property **LeaderSpacing** As Long

Description

Member of TextTabPositions

The **LeaderSpacing** property returns or specifies the leader spacing for all tab stops in a text range.

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill

Properties Methods

Description

The **TextureFill** class represents the settings for a texture-fill pattern.

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.LibraryName

Property **LibraryName** As String

Description

Member of TextureFill

The **LibraryName** property returns the name of the texture library for a texture-fill pattern.

The **LibraryName** property returns a read-only value.

VBA example

The following VBA example displays the names of the texture-pattern fill and the texture library for each texture fill found in the drawing.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Dim ss As String
 Dim r As VbMsgBoxResult
 For Each s In ActivePage.Shapes
  If s.Fill.Type = cdrTextureFill Then
   Set tf = s.Fill.Texture
   s.CreateSelection ' Select the shape
   ss = "Texture Name: " & tf.TextureName & vbCr & "Library Name: "
   If tf.LibraryName = "" Then
    ss = ss & "Styles"
   Else
    ss = ss & tf.LibraryName
   End If
   ss = ss & vbCr & "Style Name: " & tf.StyleName & vbCr
   ss = ss & vbCr & "Press OK to continue"
   r = MsgBox(ss, vbOKCancel)
   If r = vbCancel Then Exit For
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.MaximumTileWidth

Property **MaximumTileWidth** As Long

Description

Member of TextureFill

The **MaximumTileWidth** property returns or specifies the maximum size, in pixels, of a tile in a texture-fill pattern.

VBA example

The following VBA example applies a texture fill to a rectangle and displays the maximum size of tiles in the texture.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set tf = s.Fill.ApplyTextureFill("Leather 3C")
 MsgBox "Max tile width = " & tf.MaximumTileWidth
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.MirrorFill

Property **MirrorFill** As Boolean

Description

Member of TextureFill

The **MirrorFill** property returns or specifies whether the pattern tiles in a texture fill should be mirrored to conceal seams.

VBA example

The following VBA example applies a symmetrical texture fill to a rectangle.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set tf = s.Fill.ApplyTextureFill("CMYK", "Samples 9")
 tf.TileWidth = 2
 tf.TileHeight = 2
 tf.MirrorFill = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.MirrorFillX

Property **MirrorFillX** As Boolean

Description

Member of TextureFill

The **MirrorFillX** property returns or specifies whether the pattern tiles in a texture fill should be mirrored horizontally to conceal seams.

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.MirrorFillY

Property **MirrorFillY** As Boolean

Description

Member of TextureFill

The **MirrorFillY** property returns or specifies whether the pattern tiles in a texture fill should be mirrored vertically to conceal seams.

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.OriginX

Property **OriginX** As Double

Description

Member of TextureFill

The **OriginX** property returns or specifies the horizontal offset of a texture-fill tile from the lower-left corner of its parent shape.

The **OriginX** property is measured in document units.

VBA example

The following VBA example applies a texture fill to a rectangle and offsets the tile by **1**" to the left.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set tf = s.Fill.ApplyTextureFill("Above the Storm", "Samples 9")
 tf.OriginX = 1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.OriginY

Property **OriginY** As Double

Description

Member of TextureFill

The **OriginY** property returns or specifies the vertical offset of a texture-fill tile from the lower-left corner of its parent shape.

The **OriginY** property is measured in document units.

VBA example

The following VBA example applies a texture fill to a rectangle and offsets the tile by **1**" from the bottom of the page.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set tf = s.Fill.ApplyTextureFill("Above the Storm", "Samples 9")
 tf.OriginY = 1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.Properties

Property **Properties** As TextureFillProperties

Description

Member of TextureFill

The **Properties** property returns a TextureFillProperties object, which lets you return and modify the parameters of a texture-fill pattern. Each texture-fill pattern has a range of properties, and some textures have more properties than others — for example, the texture **Heavenly Clouds** has nine properties, while the **Midday Clouds** texture has six.

The **Properties** property returns a read-only value.

VBA example

The following VBA example applies a texture fill and changes two of its parameters.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set tf = s.Fill.ApplyTextureFill("Banded malachite", "Samples")
 tf.Properties("Softness %:").Value = 80
 tf.Properties("1st mineral:").Value = CreateRGBColor(255, 0, 0)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.Resolution

Property **Resolution** As Long

Description

Member of TextureFill

The **Resolution** property returns or specifies, in pixels per inch, the resolution of a texture-fill pattern.

VBA example

The following VBA example applies a texture to a rectangle and displays the texture's resolution.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set tf = s.Fill.ApplyTextureFill("Circuit board", "Samples 6")
 MsgBox "Texture resolution: " & tf.Resolution
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.RotationAngle

Property **RotationAngle** As Double

Description

Member of TextureFill

The **RotationAngle** property returns or specifies the angle of rotation of the tile in a texture-pattern fill.

VBA example

The following VBA example creates a texture pattern that is rotated by **45**° and skewed by **10**°.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set tf = s.Fill.ApplyTextureFill("Scribbles")
 tf.SetProperties 14430, 5, 90
 tf.RotationAngle = 45
 tf.SkewAngle = 10
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.Select

Sub **Select(***Texture As String***, [***Library As String***])**

Description

Member of TextureFill

The **Select** method replaces a texture fill in a shape with another texture fill.

Parameter	Description
Texture	Specifies the name of the new texture to be applied
Library	Specifies the name of the texture library to which the new texture belongs. This parameter is optional.

VBA example

The following VBA example loops though all shapes on a page and searches for a modified texture fill that is based on a preset library. When found, the fill is replaced with the original style pattern upon which the current fill is based.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 For Each s In ActivePage.Shapes
  If s.Fill.Type = cdrTextureFill Then
   Set tf = s.Fill.Texture
   If tf.LibraryName <> "" Then
    tf.Select tf.StyleName
   End If
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.SetProperties

Sub **SetProperties(***SettingArray() As Variant***)**

Description

Member of TextureFill

The **SetProperties** method allows you to set all the properties of a texture fill with a single command.

Parameter	Description
SettingArray	Specifies the new parameter for a TextureFillProperty object

VBA example

The following VBA example applies the **Vapor 2** texture to a rectangle and modifies the following properties in the following ways: **Texture #** = **20611**, **Density** = **30**%, **Softness** = **75**%, **Background** = **Black**, **Vapor** = **40**% **Cyan**, and **Brightness** = **20**%.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 Set tf = s.Fill.ApplyTextureFill("Vapor 2C")
 tf.SetProperties 20611, 30, 75, CreateRGBColor(0, 0, 0), CreateRGBColor(117, 197, 240), 20
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.SkewAngle

Property **SkewAngle** As Double

Description

Member of TextureFill

The **SkewAngle** property returns or specifies the slant angle of the tile in a texture-fill pattern.

VBA example

The following VBA example creates a texture pattern that is rotated by **45**° and skewed by **10**°.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set tf = s.Fill.ApplyTextureFill("Scribbles")
 tf.SetProperties 14430, 5, 90
 tf.RotationAngle = 45
 tf.SkewAngle = 10
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.StyleName

Property **StyleName** As String

Description

Member of TextureFill

The **StyleName** property returns the name of the style upon which a texture-fill pattern is based.

The **StyleName** property returns a read-only value.

VBA example

The following VBA example displays the names of the texture-pattern fill and the texture library for each texture fill found in the drawing.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Dim ss As String
 Dim r As VbMsgBoxResult
 For Each s In ActivePage.Shapes
  If s.Fill.Type = cdrTextureFill Then
   Set tf = s.Fill.Texture
   s.CreateSelection ' Select the shape
   ss = "Texture Name: " & tf.TextureName & vbCr & "Library Name: "
   If tf.LibraryName = "" Then
    ss = ss & "Styles"
   Else
    ss = ss & tf.LibraryName
   End If
   ss = ss & vbCr & "Style Name: " & tf.StyleName & vbCr
   ss = ss & vbCr & "Press OK to continue"
   r = MsgBox(ss, vbOKCancel)
   If r = vbCancel Then Exit For
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.TextureName

Property **TextureName** As String

Description

Member of TextureFill

The **TextureName** property returns the name of a texture-fill pattern.

The **TextureName** property returns a read-only value.

VBA example

The following VBA example displays the names of the texture-pattern fill and the texture library for each texture fill found in the drawing.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Dim ss As String
 Dim r As VbMsgBoxResult
 For Each s In ActivePage.Shapes
  If s.Fill.Type = cdrTextureFill Then
   Set tf = s.Fill.Texture
   s.CreateSelection ' Select the shape
   ss = "Texture Name: " & tf.TextureName & vbCr & "Library Name: "
   If tf.LibraryName = "" Then
    ss = ss & "Styles"
   Else
    ss = ss & tf.LibraryName
   End If
   ss = ss & vbCr & "Style Name: " & tf.StyleName & vbCr
   ss = ss & vbCr & "Press OK to continue"
   r = MsgBox(ss, vbOKCancel)
   If r = vbCancel Then Exit For
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.TileHeight

Property **TileHeight** As Double

Description

Member of TextureFill

The **TileHeight** property returns or specifies the vertical size of the tile in a texture-fill pattern.

The **TileHeight** property is measured in document units.

VBA example

The following VBA example applies a texture pattern to a rectangle such that the tile is repeated twice horizontally and three times vertically.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set tf = s.Fill.ApplyTextureFill("Water Color")
 tf.TileHeight = s.SizeWidth / 2
 tf.TileWidth = s.SizeHeight / 3
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.TileOffset

Property **TileOffset** As Long

Description

Member of TextureFill

The **TileOffset** property returns or specifies the tile offset, measured as a percentage of the size of the tile, of a texture-fill pattern.

- You can use the **TileOffsetType** to specify whether a pattern is offset by row or by column.

VBA example

The following VBA example applies a texture pattern to a rectangle and offsets each row of tiles by **20**%, relative to each other.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set tf = s.Fill.ApplyTextureFill("Water Color")
 tf.TileHeight = 0.5
 tf.TileWidth = 0.5
 tf.TileOffsetType = cdrTileOffsetRow
 tf.TileOffset = 20
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.TileOffsetType

Property **TileOffsetType** As cdrTileOffsetType

Description

Member of TextureFill

The **TileOffsetType** property returns or specifies the offest type of the tile in a texture-fill pattern.

- A texture-fill pattern can be offset by row or by column.
- You can use the TextureFill.TileOffsetType property to specify the percentage of offset for adjacent rows or columns.

The **TileOffsetType** property returns a value of cdrTileOffsetType.

VBA example

The following VBA example applies a texture pattern to a rectangle and offsets each row of tiles by **20**%, relative to each other.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set tf = s.Fill.ApplyTextureFill("Water Color")
 tf.TileHeight = 0.5
 tf.TileWidth = 0.5
 tf.TileOffsetType = cdrTileOffsetRow
 tf.TileOffset = 20
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.TileWidth

Property **TileWidth** As Double

Description

Member of TextureFill

The **TileWidth** property returns or specifies the horizontal size, in document units, of the tile in a texture-fill pattern.

VBA example

The following VBA example applies a texture-fill pattern to a rectangle, such that the tile is repeated twice horizontally and three times vertically.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set tf = s.Fill.ApplyTextureFill("Water Color")
 tf.TileHeight = s.SizeWidth / 2
 tf.TileWidth = s.SizeHeight / 3
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFill.TransformWithShape

Property **TransformWithShape** As Boolean

Description

Member of TextureFill

The **TransformWithShape** property returns or specifies whether a texture-fill pattern is transformed when its parent shape is altered. If this property is set to **True**, the texture-fill pattern changes according to transformations of its parent shape; if it is set to **False**, the texture-fill pattern remains the same, despite changes to the parent shape.

VBA example

The following VBA example applies a texture fill to a rectangle and specifies that no transformations are made to the fill when the shape is transformed. It then duplicates the shape and stretches it by **200**%.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 4, 4)
 Set tf = s.Fill.ApplyTextureFill("Water Color")
 tf.TileHeight = 2
 tf.TileWidth = 2
 tf.TransformWithShape = False
 Set s = s.Duplicate(4, 0)
 s.StretchEx 2, 3, 4, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFillProperties

Properties

Description

The **TextureFillProperties** class represents a collection of texture-fill parameters (or TextureFillProperty objects).

- For more information on texture-fill properties, see the TextureFill class.

Copyright 2014 Corel Corporation. All rights reserved.

TextureFillProperties.Count

Property **Count** As Long

Description

Member of TextureFillProperties

The **Count** property returns the number of parameters that are available to a particular type of texture fill.

The **Count** property returns a read-only value.

VBA example

The following VBA example applies a texture fill to a rectangle and displays the number of parameters available to the fill.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 Set tf = s.Fill.ApplyTextureFill("Vapor 2C")
 MsgBox "Texture '" & tf.TextureName & "' has " & _
  tf.Properties.Count & " parameters"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFillProperties.Item

Property **Item**(*IndexOrName As Variant*) As TextureFillProperty

Description

Member of TextureFillProperties

The **Item** property returns a TextureFillProperty object that represents a single parameter of a texture fill. It is the default property of the TextureFillProperties class.

- Parameter names are localized in international versions of CorelDRAW. If you choose to use parameter names, your macros may need to be revised for localized builds of CorelDRAW.

The **Item** property returns a read-only value.

Parameter	Description
IndexOrName	Specifies the texture-fill property by its index number or name: • **Index** — Specifies the preset placeholder that uniquely identifies each member of the **TextureFillProperties** collection • **Name** — Specifies the string that uniquely identifies each texture-fill property

VBA example

The following VBA example displays detailed information about the texture fill of a selected shape, including its list of parameters and their values.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Dim prop As TextureFillProperty
 Dim ss As String, i As Long
 Set s = ActiveShape
 If s Is Nothing Then
  MsgBox "Nothing selected"
  Exit Sub
 End If
 If s.Fill.Type <> cdrTextureFill Then
  MsgBox "Select a shape with texture fill"
  Exit Sub
 End If
 Set tf = s.Fill.Texture
 ss = "Texture Name: " & tf.TextureName & vbCr & "Library Name: "
 If tf.LibraryName = "" Then
  ss = ss & "Styles"
 Else
  ss = ss & tf.LibraryName
 End If
 ss = ss & vbCr & "Style Name: " & tf.StyleName & vbCr
 ss = ss & vbCr & "Parameter: "
 For i = 1 To tf.Properties.Count
  Set prop = tf.Properties(i)
  ss = ss & vbCr & prop.Name & " "
  If prop.Type = cdrTexturePropertyNumeric Then
   ss = ss & prop.Value
  Else
   ss = ss & "Color(" & prop.Value.Name(True) & ")"
  End If
 Next i
 MsgBox ss
End Sub
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 Set tf = s.Fill.ApplyTextureFill("Dark Cloud", "Samples 8")
 tf.Properties("Texture #:").Value = 78
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFillProperty

Properties

Description

The **TextureFillProperty** class represents a single texture-fill property.

- For more information on texture-fill properties, see the TextureFill and TextureFillProperties classes.

Copyright 2014 Corel Corporation. All rights reserved.

TextureFillProperty.Name

Property **Name** As String

Description

Member of TextureFillProperty

The **Name** property returns the name of a texture-fill parameter.

The **Name** property returns a read-only value.

VBA example

The following VBA example displays the name of the third parameter of the texture **Fire Flies** from the library **Samples 9**.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 Set tf = s.Fill.ApplyTextureFill("Fire Flies", "Samples 9")
 MsgBox tf.Properties(3).Name
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFillProperty.Type

Property **Type** As cdrTexturePropertyType

Description

Member of TextureFillProperty

The **Type** property returns the type (numeric or color) of a property of a texture fill.

This property returns a read-only value of cdrTexturePropertyType.

VBA example

The following VBA example displays detailed information about the texture fill of a selected shape, including a list of its parameters and their values.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Dim prop As TextureFillProperty
 Dim ss As String
 Set s = ActiveShape
 If s Is Nothing Then
  MsgBox "Nothing selected"
  Exit Sub
 End If
 If s.Fill.Type <> cdrTextureFill Then
  MsgBox "Select a shape with texture fill"
  Exit Sub
 End If
 Set tf = s.Fill.Texture
 ss = "Texture Name: " & tf.TextureName & vbCr & "Library Name: "
 If tf.LibraryName = "" Then
  ss = ss & "Styles"
 Else
  ss = ss & tf.LibraryName
 End If
 ss = ss & vbCr & "Style Name: " & tf.StyleName & vbCr
 ss = ss & vbCr & "Parameter: "
 For Each prop In tf.Properties
  ss = ss & vbCr & prop.Name & " "
  If prop.Type = cdrTexturePropertyNumeric Then
   ss = ss & prop.Value
  Else
   ss = ss & "Color(" & prop.Value.Name(True) & ")"
  End If
 Next prop
 MsgBox ss
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextureFillProperty.Value

Property **Value** As Variant

Description

Member of TextureFillProperty

The **Value** property returns or specifies the value (numeric or color) of a property of a texture fill. It is the default property of the TextureFillProperty class.

VBA example

The following VBA example creates a rectangle, applies a texture fill to it, and then modifies two parameters of the fill.

```
Sub Test()
 Dim s As Shape
 Dim tf As TextureFill
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 Set tf = s.Fill.ApplyTextureFill("Dark Cloud", "Samples 8")
 tf.Properties("Texture #:").Value = 150
 tf.Properties("Top left:").Value = CreateRGBColor(255, 0, 0)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextWords

Properties

Description

The **TextWords** class represents a collection of text words.

Copyright 2014 Corel Corporation. All rights reserved.

TextWords.All

Property **All** As TextRange

Description

Member of TextWords

The **All** property returns a text range (or TextRange object) containing all the words in a collection.

The **All** property returns a read-only value.

VBA example

The following VBA example creates paragraph text and applies bold formatting to its words.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, _
  "This is an example for the TextWords class.")
 Set t = s.Text
 t.Story.Words.All.Bold = True
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextWords.Count

Property **Count** As Long

Description

Member of TextWords

The **Count** property returns the number of words in a collection.

The **Count** property returns a read-only value.

VBA example

The following VBA example creates paragraph text and displays the number of words it contains.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, _
  "This is an example for the TextWords Class")
 Set t = s.Text
 MsgBox "The total number of words is " & t.Story.Words.Count
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextWords.First

Property **First** As TextRange

Description

Member of TextWords

The **First** property returns a text range (or TextRange object) containing the first word in a collection.

The **First** property returns a read-only value.

VBA example

The following VBA example creates paragraph text and fills its first word with red.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, _
  "This is an example for the TextWords class.")
 Set t = s.Text
 t.Story.Words.First.Fill.UniformColor.RGBAssign 155, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextWords.Item

Property **Item(***Index As Long***, [**Count As Long = 1**])** As TextRange

Description

Member of TextWords

The **Item** property returns a read-only reference to a specified word. It is the default property of the TextWords class.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each member of the **TextWords** collection
Count	Specifies the number of words. This parameter is optional, and its default value is **1**.

VBA example

The following VBA example creates paragraph text and applies bold formatting to the first word, underlines the fourth word, and fills the seventh and eighth words with red.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, _
  "This is an example for the TextWords Class")
 Set t = s.Text
 t.Story.Words.Item(1).Bold = True
 t.Story.Words.Item(4).Underline = cdrSingleThickFontLine
 t.Story.Words.Item(7, 2).Fill.UniformColor.RGBAssign 155, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TextWords.Last

Property **Last** As TextRange

Description

Member of TextWords

The **Last** property returns a text range (or TextRange object) containing the last word in a collection.

The **Last** propertey returns a read-only value.

VBA example

The following VBA example creates paragraph text and fills its last word with red.

```
Sub Test()
 Dim t As Text
 Dim s As Shape
 Dim d As Document
 Set d = CreateDocument
 Set s = d.ActiveLayer.CreateParagraphText(2, 2, 8, 8, _
  "This is an example for the TextWords Class")
 Set t = s.Text
 t.Story.Words.Last.Fill.UniformColor.RGBAssign 155, 0, 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings

Properties Methods

Description

The **TraceSettings** class represents the PowerTRACE feature, which lets you convert bitmaps into vector images.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.ApplyChanges

Sub **ApplyChanges()**

Description

Member of TraceSettings

The **ApplyChanges** method applies any changes made to trace parameters and recalculates the trace.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.BackgroundColor

Property **BackgroundColor** As Color

Description

Member of TraceSettings

The **BackgroundColor** property returns the currently selected background color for a trace.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.BackgroundRemovalMode

Property **BackgroundRemovalMode** As cdrTraceBackgroundMode

Description

Member of TraceSettings

The **BackgroundRemovalMode** property specifies whether the background color for a trace is detected automatically or specified by the user.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.BitmapHeight

Property **BitmapHeight** As Long

Description

Member of TraceSettings

The **BitmapHeight** property returns the height of the original bitmap in pixels.

The **BitmapHeight** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.BitmapWidth

Property **BitmapWidth** As Long

Description

Member of TraceSettings

The **BitmapWidth** property returns the width of the original bitmap in pixels.

The **BitmapWidth** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.Color

Property **Color(***Index As Long***)** As Color

Description

Member of TraceSettings

The **Color** property returns a given color from the generated color palette.

The **Color** property returns a read-only value.

Parameter	Description
Index	Specifies the color by its index number

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.ColorCount

Property **ColorCount** As Long

Description

Member of TraceSettings

The **ColorCount** property returns the number of colors in a generated color palette.

The **ColorCount** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.ColorMode

Property **ColorMode** As cdrColorType

Description

Member of TraceSettings

The **ColorMode** property specifies the color model of the resulting vector image.

The **ColorMode** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.CornerSmoothness

Property **CornerSmoothness** As Integer

Description

Member of TraceSettings

The **CornerSmoothness** property specifies corner smoothness.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.CurveCount

Property **CurveCount** As Long

Description

Member of TraceSettings

The **CurveCount** property returns the number of curves that are generated during a trace.

The **CurveCount** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.DeleteOriginalObject

Property **DeleteOriginalObject** As Boolean

Description

Member of TraceSettings

The **DeleteOriginalObject** property specifies whether the original image is deleted after a trace.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.DetailLevel

Property **DetailLevel** As Integer

Description

Member of TraceSettings

The **DetailLevel** property specifies the level of detail in the resulting trace.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.DetailLevelPercent

Property **DetailLevelPercent** As Integer

Description

Member of TraceSettings

The **DetailLevelPercent** property specifies the percentage value of the maximum allowed level of detail for a trace.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.Finish

Sub **Finish()** As ShapeRange

Description

Member of TraceSettings

The **Finish** method completes the trace process, generating a vector image.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.GroupObjectsByColor

Property **GroupObjectsByColor** As Boolean

Description

Member of TraceSettings

The **GroupObjectsByColor** property specifies whether to group objects of the same color.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.MaxDetailLevel

Property **MaxDetailLevel** As Integer

Description

Member of TraceSettings

The **MaxDetailLevel** property returns the maximum level of detail attainable with the current image.

The **MaxDetailLevel** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.MergeAdjacentObjects

Property **MergeAdjacentObjects** As Boolean

Description

Member of TraceSettings

The **MergeAdjacentObjects** property specifies whether to merge adjacent objects of the same color.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.MinDetailLevel

Property **MinDetailLevel** As Integer

Description

Member of TraceSettings

The **MinDetailLevel** property returns the minumum allowed level of detail for tracing the current image.

The **MinDetailLevel** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.NodeCount

Property **NodeCount** As Long

Description

Member of TraceSettings

The **NodeCount** property returns the number of curve nodes that are generated during a trace.

The **NodeCount** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.PaletteID

Property **PaletteID** As cdrPaletteID

Description

Member of TraceSettings

The **PaletteID** property specifies the fixed palette to use if the spot-color mode is selected.

The **PaletteID** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.RemoveBackground

Property **RemoveBackground** As Boolean

Description

Member of TraceSettings

The **RemoveBackground** property specifies whether the background objects are deleted from a trace.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.RemoveEntireBackColor

Property **RemoveEntireBackColor** As Boolean

Description

Member of TraceSettings

The **RemoveEntireBackColor** property specifies whether all objects having the background color are deleted from the traced image.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.RemoveOverlap

Property **RemoveOverlap** As Boolean

Description

Member of TraceSettings

The **RemoveOverlap** property specifies whether to remove object overlap.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.SetColorCount

Sub **SetColorCount(***ColorCount As Long***)** As Long

Description

Member of TraceSettings

The **SetColorCount** method changes the number of colors in the resulting trace.

Parameter	Description
ColorCount	Specifies the number of colors to use

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.SetColorMode

Sub **SetColorMode(**ColorMode As cdrColorType**, [**PaletteID As cdrPaletteID = cdrCustom**])**

Description

Member of TraceSettings

The **SetColorMode** method changes the color model of the resulting vector image and resets the generated color palette.

Parameter	Description
ColorMode	Specifies the color model. This parameter returns cdrColorType.
PaletteID	Specifies the ID of the palette, and returns cdrPaletteID. This parameter is optional, and its default value is cdrCustom.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.ShowDialog

Sub **ShowDialog([***ParentWindowHandle As Long***])** As Boolean

Description

Member of TraceSettings

The **ShowDialog** method displays the **PowerTRACE** dialog box.

The **ShowDialog** method returns **True** if the **OK** button was pressed.

Parameter	Description
ParentWindowHandle	Specifies the handle of the parent window. This parameter is optional.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.Smoothing

Property **Smoothing** As Integer

Description

Member of TraceSettings

The **Smoothing** property specifies the smoothing level for a trace.

Copyright 2014 Corel Corporation. All rights reserved.

TraceSettings.TraceType

Property **TraceType** As cdrTraceType

Description

Member of TraceSettings

The **TraceType** property specifies the type of trace to perform.

Copyright 2014 Corel Corporation. All rights reserved.

Transparency

Properties Methods

Description

The **Transparency** class represents the transparency of a shape.

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.Application

Property **Application** As Object

Description

Member of Transparency

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.AppliedTo

Property **AppliedTo** As cdrTransparencyAppliedTo

Description

Member of Transparency

The **AppliedTo** property returns or specifies whether a transparency is applied to the fill or outline of a shape, or to both.

VBA example

The following VBA example creates a rectangle with a fill and an outline, applying a fountain transparency to its outline.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle2(0, 0, 2, 2, 0.5, 0.5, 0.5, 0.5)
 s.Fill.ApplyFountainFill CreateRGBColor(255, 0, 0), CreateRGBColor(255, 255, 0), , 45
 s.Outline.Width = 0.3
 s.Outline.Color.RGBAssign 0, 128, 0
 s.Transparency.ApplyFountainTransparency 0, 100, cdrLinearFountainFill
 s.Transparency.AppliedTo = cdrApplyToOutline
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.ApplyFountainTransparency

Function **ApplyFountainTransparency([***Start As Long***], [**End As Long = 100**], [**Type As cdrFountainFillType = cdrLinearFountainFill**], [***Angle As Double***], [***Steps As Long***], [***EdgePad As Long***], [**MidPoint As Long = 50**], [***CenterOffsetX As Double***], [***CenterOffsetY As Double***])** As FountainFill

Description

Member of Transparency

The **ApplyFountainTransparency** method applies a fountain-fill transparency to a shape.

Parameter	Description
Start	Specifies a percentage value indicating the level of transparency in the beginning of the fountain transparency. Higher values indicate a greater degree of transparency. This parameter is optional, and its default value is **0**.
End	Specifies a percentage value indicating the level of transparency in the end of the fountain transparency. Higher values indicate a greater degree of transparency. This parameter is optional, and its default value is **100**.
Type	Specifies, through a value of cdrFountainFillType, the type of fountain fill in the transparency. This parameter is optional, and its default value is cdrLinearFountainFill (**1**).
Angle	Specifies the degree of the slant in linear, conical, or square fountain-fill transparencies. Positive values rotate the fill counterclockwise; negative values rotate it clockwise. This parameter is optional, and its default value is **0**.
Steps	Specifies the number of bands (steps) used to display the fountain fill. This parameter is optional, and its default value is **0**.
EdgePad	Specifies the length of solid colors at the beginning and end of the fountain transparency before they start blending with the next color in the fountain fill. You can change the edge pad of linear, radial, and square fountain fills. This parameter is optional, and its default value is **0**.
MidPoint	Specifies the position of the mid-point, the point at which two colors in the fountain fill converge. This parameter is optional, and its default value is **50**.
CenterOffsetX	Specifies the horizontal offset from the center. This parameter is optional, and its default value is **0**.
CenterOffsetY	Specifies the vertical offset from the center. This parameter is optional, and its default value is **0**.

VBA example

The following VBA example applies a radial fountain-fill transparency to each shape that has a fill.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Fill.Type <> cdrNoFill Then
   s.Transparency.ApplyFountainTransparency 0, 90, cdrRadialFountainFill
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.ApplyNoTransparency

Sub **ApplyNoTransparency**()

Description

Member of Transparency

The **ApplyNoTransparency** method removes all transparencies from a shape.

VBA example

The following VBA example removes all transparencies from all shapes on the active page.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Transparency.Type <> cdrNoTransparency Then
   s.Transparency.ApplyNoTransparency
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.ApplyPatternTransparency

Function **ApplyPatternTransparency(**Type As cdrPatternFillType**, [***FileName As String***], [**PatternCanvasIndex As Long = 1**], [***Front As Long***], [**Back As Long = 100**], [**TransformWithShape As Boolean = False**])** As PatternFill

Description

Member of Transparency

The **ApplyPatternTransparency** method applies a pattern-fill transparency to a shape.

Parameter	Description
Type	Specifies, through a value of cdrPatternFillType, the type of pattern-fill transparency
FileName	Specifies the full path name of the graphic to import as the pattern-fill transparency. This parameter is optional.
PatternCanvasIndex	Specifies the pattern canvas in the pattern-fill transparency. This parameter is optional, and its default value is **1**.
Front	This parameter is optional, and its default value is **0**.
Back	This parameter is optional, and its default value is **100**.
TransformWithShape	Specifies whether to transform the pattern-fill transparency along with any changes made to the shape. A value of **True** changes the pattern-fill transparency along with its shape. This parameter is optional, and its default value is **False**.

VBA example

The following VBA example applies a two-color pattern-fill transparency to a rectangle.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 s.Fill.UniformColor.RGBAssign 0, 0, 255
 s.Transparency.ApplyPatternTransparency cdrTwoColorPattern, , 6
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.ApplyTextureTransparency

Function **ApplyTextureTransparency(***TextureName As String***, [***LibraryName As String***])** As TextureFill

Description

Member of Transparency

The **ApplyTextureTransparency** method applies a texture-fill transparency to a shape.

Parameter	Description
TextureName	Specifies the name of the texture fill to apply
LibraryName	Specifies the name of the texture library. This parameter is optional.

VBA example

The following VBA example applies a texture-fill transparency to a rectangle.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 s.Fill.UniformColor.RGBAssign 0, 128, 0
 s.Outline.Type = cdrNoOutline
 s.Transparency.ApplyTextureTransparency "Cosmic Energy", ""
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.ApplyUniformTransparency

Sub **ApplyUniformTransparency(***Value As Long***)**

Description

Member of Transparency

The **ApplyUniformTransparency** method applies a uniform-fill transparency to a shape.

Parameter	Description
Value	Specifies the level of transparency, measured as a percentage from **0** to **100** (where higher values indicate a greater degree of transparency)

VBA example

The following VBA example applies a uniform-fill transparency of **50**% to a rectangle.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 s.Fill.ApplyFountainFill CreateRGBColor(255, 0, 0), CreateRGBColor(255, 255, 0)
 s.Outline.Type = cdrNoOutline
 s.Transparency.ApplyUniformTransparency 50
 s.Transparency.Uniform = 50 ' a workaround
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.End

Property **End** As Long

Description

Member of Transparency

The **End** property returns or specifies a percentage value that indicates the level of transparency at the end of a fountain transparency. Higher values indicate a greater degree of transparency.

VBA example

The following VBA example creates a rectangle and applies a radial fountain transparency to it. It then duplicates the rectangle and inverts its transparency.

```
Sub Test()
 Dim s As Shape, s1 As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 s.Fill.UniformColor.RGBAssign 255, 0, 0
 s.Transparency.ApplyFountainTransparency , , cdrRadialFountainFill
 Set s1 = s.Duplicate(2, 0)
 s1.Transparency.Start = 100
 s1.Transparency.End = 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.Fountain

Property **Fountain** As FountainFill

Description

Member of Transparency

The **Fountain** property returns a fountain fill (or FountainFill object) representing the settings for a fountain-fill transparency.

VBA example

The following VBA example sets the direction angle of all fountain-fill transparencies to **45**°.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Transparency.Type = cdrFountainTransparency Then
   s.Transparency.Fountain.SetAngle 45
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.Freeze

Sub **Freeze()**

Description

Member of Transparency

The **Freeze** method freezes a transparency.

VBA example

The following VBA example creates a circle and adds a rectangle on top of it. It then applies a transparency to the rectangle, freezes the transparency, and moves the resulting frozen transparency group diagonally.

```
Sub Test()
 Dim s1 As Shape, s2 As Shape
 Set s1 = ActiveLayer.CreateEllipse2(0, 0, 1)
 s1.Fill.UniformColor.RGBAssign 0, 128, 0
 Set s2 = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 s2.Fill.ApplyFountainFill CreateRGBColor(255, 0, 0), CreateRGBColor(255, 255, 0)
 s2.Outline.Type = cdrNoOutline
 s2.Transparency.ApplyTextureTransparency "Cosmic Energy", ""
 s2.Transparency.Freeze
 s2.ParentGroup.Move 1, 1
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.Frozen

Property **Frozen** As Boolean

Description

Member of Transparency

The **Frozen** property returns **True** if a transparency is frozen.

The **Frozen** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.MergeMode

Property **MergeMode** As cdrMergeMode

Description

Member of Transparency

The **MergeMode** property returns or specifies the merge mode for a transparency.

VBA example

The following VBA example creates a polygon and applies a merge mode to the transparency.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(1, 1, 3, 3)
 s.Transparency.ApplyUniformTransparency (10)
 Set s = ActiveLayer.CreatePolygon(1, 4, 5, 6, 6)
 s.Transparency.ApplyTextureTransparency "Above the storm"
 For Each s In ActivePage.Shapes
  If s.Transparency.Type = cdrTextureTransparency Then
   s.Transparency.MergeMode = cdrMergeBlue
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.Parent

Property **Parent** As Object

Description

Member of Transparency

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.Pattern

Property **Pattern** As PatternFill

Description

Member of Transparency

The **Pattern** property returns a PatternFill object representing the settings for a pattern-fill transparency.

VBA example

The following VBA example creates a rectangle and applies a two-color pattern-fill transparency to it. It then skews the pattern by **20**°.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 s.Fill.UniformColor.RGBAssign 255, 0, 0
 s.Transparency.ApplyPatternTransparency cdrTwoColorPattern, , 1
 s.Transparency.Pattern.BackColor.GrayAssign 255
 s.Transparency.Pattern.SkewAngle = 20
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.Start

Property **Start** As Long

Description

Member of Transparency

The **Start** property returns or specifies a percentage value that indicates the level of transparency at the beginning of a fountain transparency. Higher values indicate a greater degree of transparency.

VBA example

The following VBA example creates a rectangle and applies a radial fountain transparency to it. It then duplicates the rectangle and inverts its transparency.

```
Sub Test()
 Dim s As Shape, s1 As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 s.Fill.UniformColor.RGBAssign 255, 0, 0
 s.Transparency.ApplyFountainTransparency , , cdrRadialFountainFill
 Set s1 = s.Duplicate(2, 0)
 s1.Transparency.Start = 100
 s1.Transparency.End = 0
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.Texture

Property **Texture** As TextureFill

Description

Member of Transparency

The **Texture** property returns a texture fill (or TextureFill object) representing the settings for a texture-fill transparency.

VBA example

The following VBA example creates a rectangle and applies a texture-fill transparency to it.

```
Sub Test()
 Dim s As Shape
 Set s = ActiveLayer.CreateRectangle(0, 0, 2, 2)
 s.Fill.UniformColor.RGBAssign 0, 0, 255
 s.Transparency.ApplyTextureTransparency "Water Color2 2C", ""
 s.Transparency.Texture.Properties("Background:").Value = CreateRGBColor(0, 0, 0)
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.Type

Property **Type** As cdrTransparencyType

Description

Member of Transparency

The **Type** property returns or specifies the type of a transparency.

The **Type** property returns a read-only value of cdrTransparencyType.

VBA example

The following VBA example removes all fountain transparencies.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Transparency.Type <> cdrFountainTransparency Then
   s.Transparency.ApplyNoTransparency
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.Unfreeze

Sub **Unfreeze()**

Description

Member of Transparency

The **UnFreeze** method unfreezes a transparency.

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.Uniform

Property **Uniform** As Long

Description

Member of Transparency

The **Uniform** property returns or specifies a percentage value indicating the level of a uniform transparency. Higher values indicate a greater degree of transparency.

VBA example

The following VBA example sets the transparency of all objects with a uniform transparency to 50%.

```
Sub Test()
 Dim s As Shape
 For Each s In ActivePage.Shapes
  If s.Transparency.Type = cdrUniformTransparency Then
   s.Transparency.Uniform = 50
  End If
 Next s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Transparency.UserAssign

Function **UserAssign([**TransparencyType As cdrTransparencyType = cdrNoTransparency**], [**PatternType As cdrPatternFillType = cdrTwoColorPattern**], [***ParentWindowHandle As Long***])** As Boolean

Description

Member of Transparency

The **UserAssign** method displays the corresponding **Transparency Properties** dialog box.

Parameter	Description
TransparencyType	Specifies the type of transparency. This parameter is optional, and its default value is cdrNoTransparency (**0**).
PatternType	Specifies the pattern type. This parameter is optional, and its default value is cdrTwoColorPattern (**0**).
ParentWindowHandle	Specifies the handle of the parent window. This parameter is optional, and its default value is **0**.

Copyright 2014 Corel Corporation. All rights reserved.

TrapLayer

Properties

Description

The **TrapLayer** class represents a plate for color trapping.

Copyright 2014 Corel Corporation. All rights reserved.

TrapLayer.Color

Property **Color** As String

Description

Member of TrapLayer

The **Color** property returns the color of a plate.

The **Color** property returns a read-only value.

VBA example

The following VBA example displays a list of colors for trap layers.

```
Sub Test()
 Dim intCounter As Integer
 Dim s As String
 With ActiveDocument.PrintSettings.Trapping
  For intCounter = 1 To .Layers.Count - 1
   s = s & .Layers.Item(intCounter).Color & vbCr
  Next intCounter
 End With
 MsgBox s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TrapLayer.Density

Property **Density** As Double

Description

Member of TrapLayer

The **Density** property returns or specifies the neutral density of a color.

VBA example

The following VBA example displays the density of the yellow plate.

```
Sub Test()
 Dim intCounter As Integer
 With ActiveDocument.PrintSettings.Trapping
  For intCounter = 1 To .Layers.Count - 1
   If .Layers.Item(intCounter).Color = "Yellow" Then
    MsgBox "The density of the yellow plate is " & _
     .Layers.Item(intCounter).Density
   End If
  Next intCounter
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TrapLayer.Order

Property **Order** As Long

Description

Member of TrapLayer

The **Order** property returns or specifies the order in which separations are printed.

VBA example

The following VBA example lists the order of the plates.

```
Sub Test()
 Dim intCounter As Integer
 Dim s As String
 s = "Color - Order" & vbCr & vbCr
 With ActiveDocument.PrintSettings.Trapping.Layers
  For intCounter = 1 To .Count - 1
   s = s & .Item(intCounter).Color & " - " & .Item(intCounter).Order & vbCr
  Next intCounter
 End With
 MsgBox s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TrapLayer.TrapType

Property **TrapType** As PrnTrapType

Description

Member of TrapLayer

The **TrapType** property controls the opacity of a trap.

VBA example

The following VBA example sets each trap layer as transparent.

```
Sub Test()
 Dim intCounter As Integer
 With ActiveDocument.PrintSettings.Trapping.Layers
  For intCounter = 1 To .Count - 1
   .Item(intCounter).TrapType = prnLayerTransparent
  Next intCounter
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TrapLayer.Type

Property **Type** As PrnPlateType

Description

Member of TrapLayer

The **Type** parameter returns the type for a plate.

The **Type** parameter returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TrapLayers

Properties

Description

The **TrapLayers** class represents a collection of plates for color trapping (or TrapLayer objects).

Copyright 2014 Corel Corporation. All rights reserved.

TrapLayers.Count

Property **Count** As Long

Description

Member of TrapLayers

The **Count** property returns the number of plates for color trapping that are in a TrapLayers collection.

The **Count** property returns a read-only value.

VBA example

The following VBA example displays the number of trap layers in the collection.

```
Sub Test()
 With ActiveDocument
  With .PrintSettings.Trapping.Layers
   MsgBox "There are " & .Count & " trap layers in the collection."
  End With
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TrapLayers.Item

Property **Item(***Index As Long***)** As TrapLayer

Description

Member of TrapLayers

The **Item** property returns a read-only reference to a specified plate in a TrapLayers collection.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each member of the **TrapLayers** collection

VBA example

The following VBA example displays a list of all the trap layers in the collection.

```
Sub Test()
 Dim intCounter As Integer
 Dim s As String
 With ActiveDocument.PrintSettings.Trapping
  For intCounter = 1 To .Layers.Count - 1
   s = s & .Layers.Item(intCounter).Color & vbCr
  Next intCounter
 End With
 MsgBox s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

TreeManager

Properties Methods

Description

The **TreeManager** class represents the settings for a tree.

Copyright 2014 Corel Corporation. All rights reserved.

TreeManager.CleanGroupNode

Function **CleanGroupNode(**GroupNode As TreeNode**)** As TreeNode

Description

Member of TreeManager

The **CleanGroupNode** method eliminates empty groups, as well as groups containing only one child node.

Parameter	Description
GroupNode	Specifies a tree node

Copyright 2014 Corel Corporation. All rights reserved.

TreeManager.CreateGroupNode

Function **CreateGroupNode()** As TreeNode

Description

Member of TreeManager

The **CreateGroupNode** method creates an unlinked group node.

Copyright 2014 Corel Corporation. All rights reserved.

TreeManager.FirstSelectedNode

Property **FirstSelectedNode** As TreeNode

Description

Member of TreeManager

The **FirstSelectedNode** property returns the first selected tree node.

The **FirstSelectedNode** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeManager.SelectedNodeCount

Property **SelectedNodeCount** As Long

Description

Member of TreeManager

The **SelectedNodeCount** property returns the number of selected tree nodes in a document.

The **SelectedNodeCount** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeManager.VirtualLayer

Property **VirtualLayer** As Layer

Description

Member of TreeManager

The **VirtualLayer** property returns a virtual Layer object that can be used solely to create unlinked virtual shapes.

The **VirtualLayer** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode

Properties Methods

Description

The **TreeNode** class represents the settings for a tree node.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.Children

Property **Children** As TreeNodes

Description

Member of TreeNode

The **Children** property returns a collection of all the child nodes in a document tree.

The **Children** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.Delete

Sub **Delete()**

Description

Member of TreeNode

The **Delete** method physcially destroys a tree node.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.Document

Property **Document** As Document

Description

Member of TreeNode

The **Document** property returns the document (or Document object) in which a tree node resides.

The **Document** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.FirstChild

Property **FirstChild** As TreeNode

Description

Member of TreeNode

The FirstChild property returns the first child node in a document tree.

The FirstChild property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.GetCopy

Function **GetCopy()** As TreeNode

Description

Member of TreeNode

The **GetCopy** method creates a temporary copy of a tree node and all of its properties.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.Handle

Property **Handle** As Long

Description

Member of TreeNode

The **Handle** property returns the unique ID of a tree node.

The **Handle** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.IsDescendentOf

Function **IsDescendentOf(**TreeNode As TreeNode**)** As Boolean

Description

Member of TreeNode

The **IsDescendentOf** method returns **True** if a tree node is a direct or indirect child of the specified node.

Parameter	Description
TreeNode	Specifies the suspected parent node

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.IsGroupChild

Property **IsGroupChild** As Boolean

Description

Member of TreeNode

The **IsGroupChild** property returns **True** if a tree node is inside a group.

The **IsGroupChild** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.LastChild

Property **LastChild** As TreeNode

Description

Member of TreeNode

The **LastChild** property returns the last child node in a document tree.

The **LastChild** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.Layer

Property **Layer** As Layer

Description

Member of TreeNode

The **Layer** property returns the layer (or Layer object) on which a tree node resides.

The **Layer** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.LinkAfter

Function **LinkAfter(**TreeNode As TreeNode**)** As Boolean

Description

Member of TreeNode

The **LinkAfter** method inserts a tree node into the document tree after the specified node.

Parameter	Description
TreeNode	Specifies the tree node after which to insert the node into the document

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.LinkAsChildOf

Function **LinkAsChildOf(**TreeNode As TreeNode**)** As Boolean

Description

Member of TreeNode

The **LinkAsChildOf** method inserts a tree node into the document tree as the first child of the specified node.

Parameter	Description
TreeNode	Specifies the tree node into which to insert the node into the document

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.LinkBefore

Function **LinkBefore(**TreeNode As TreeNode**)** As Boolean

Description

Member of TreeNode

The **LinkBefore** method inserts a tree node into the document tree before the specified node.

Parameter	Description
TreeNode	Specifies the tree node before which to insert the specified node into the document

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.MoveAfter

Function **MoveAfter(**TreeNode As TreeNode**)** As Boolean

Description

Member of TreeNode

The **MoveAfter** method moves a tree node after the specified node.

Parameter	Description
TreeNode	Specifies the tree node after which to move the node

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.MoveBefore

Function **MoveBefore(**TreeNode As TreeNode**)** As Boolean

Description

Member of TreeNode

The **MoveBefore** method moves a tree node before the specified node.

Parameter	Description
TreeNode	Specifies the tree node before which to move the node

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.MoveToFirst

Function **MoveToFirst()** As Boolean

Description

Member of TreeNode

The **MoveToFirst** method moves a tree node to the top of the sibling-node list.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.MoveToLast

Function **MoveToLast()** As Boolean

Description

Member of TreeNode

The **MoveToLast** method moves a tree node to the bottom of the sibling-node list.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.Name

Property **Name** As String

Description

Member of TreeNode

The **Name** property returns or specifies the name of a tree node.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.Next

Property **Next** As TreeNode

Description

Member of TreeNode

The **Next** property returns the next sibling node in a document tree.

The **Next** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.NextSelected

Property **NextSelected** As TreeNode

Description

Member of TreeNode

The **NextSelected** property returns the next selected tree node in a selection chain.

The **NextSelected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.Page

Property **Page** As Page

Description

Member of TreeNode

The **Page** property returns the page (or Page object) on which a tree node resides.

The **Page** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.Parent

Property **Parent** As TreeNode

Description

Member of TreeNode

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.Previous

Property **Previous** As TreeNode

Description

Member of TreeNode

The **Previous** property returns the previous sibling node in thae document tree.

The **Previous** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.Selected

Property **Selected** As Boolean

Description

Member of TreeNode

The **Selected** property returns **True** if the tree node is selected in the document.

The **Selected** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.Shape

Property **Shape** As Shape

Description

Member of TreeNode

The **Shape** property returns the real document Shape object represented by a tree node.

The **Shape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.ShapeType

Property **ShapeType** As cdrShapeType

Description

Member of TreeNode

The **ShapeType** property returns the type of shape represented by a shape-tree node.

The **ShapeType** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.SwapData

Sub **SwapData(**TreeNode As TreeNode**)**

Description

Member of TreeNode

The **SwapData** method swaps all tree-node data between two tree nodes.

Parameter	Description
TreeNode	Specifies the tree node with which to swap data

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.SwapGroupData

Sub **SwapGroupData(**GroupNode As TreeNode**)**

Description

Member of TreeNode

The **SwapGroupData** method swaps all children between two group tree nodes.

Parameter	Description
GroupNode	Specifies the group with which to swap children

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.Type

Property **Type** As cdrTreeNodeType

Description

Member of TreeNode

The **Type** property returns the type of tree node.

The **Type** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.UnLink

Function **UnLink()** As Boolean

Description

Member of TreeNode

The **Unlink** method removes a tree node from the document tree.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNode.VirtualShape

Property **VirtualShape** As Shape

Description

Member of TreeNode

The **VirtualShape** property returns the virtual Shape object represented by a tree node.

The **VirtualShape** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNodes

Properties

Description

The **TreeNodes** class represents a collection of tree nodes (or TreeNode objects).

Copyright 2014 Corel Corporation. All rights reserved.

TreeNodes.Count

Property **Count** As Long

Description

Member of TreeNodes

The **Count** property returns the number of child nodes (or TreeNode objects) for a given parent node (or TreeNodes object).

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

TreeNodes.Item

Property **Item(***Index As Long***)** As TreeNode

Description

Member of TreeNodes

The **Item** property returns a specified child node (or TreeNode object) for a parent node (or TreeNodes object). It is the default property of the **TreeNodes** class.

The **Item** property returns a read-only value.

Parameter	Description
Index	Specifies the preset placeholder that uniquely identifies each member of the **TreeNodes** collection

Copyright 2014 Corel Corporation. All rights reserved.

UICategories

The **UICategories** module has the following constants:

Constant	Value	Description
cdrCMDCategoryMacros	**2cc24a3e-fe24-4708-9a74-9c75406eebcd**	Specifies macros
cdrCMDCategoryPlugins	**ab489730-8791-45d2-a825-b78bbe0d6a5d**	Specifies plug-ins

Copyright 2014 Corel Corporation. All rights reserved.

URL

Properties

Description

The **URL** class represents the settings for a Uniform Resource Locator (URL) object.

Copyright 2014 Corel Corporation. All rights reserved.

URL.Address

Property **Address** As String

Description

Member of URL

The **Address** property returns or specifies the address of a URL.

VBA example

The following VBA example displays all URLs contained in the active page.

```
Sub Test()
 Dim sh As Shape, s As String
 For Each sh In ActivePage.Shapes
  s = s & sh.URL.Address & vbCr
 Next sh
 MsgBox "The current page contains the following URL addresses: " & vbCr & s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

URL.AltComment

Property **AltComment** As String

Description

Member of URL

The **AltComment** property returns or specifies the alternative (“Alt”) comment of a URL.

VBA example

The following VBA example displays all alternative comments contained in the active page.

```
Sub Test()
 Dim sh As Shape, s As String
 For Each sh In ActivePage.Shapes
  If sh.URL.AltComment <> "" Then
   s = s & sh.URL.AltComment & vbCr
  End If
 Next sh
 MsgBox "The current page contains the following URL alternative comments: " & _
  vbCr & s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

URL.BookMark

Property **BookMark** As String

Description

Member of URL

The **BookMark** property returns or specifies a bookmark for a URL.

VBA example

The following VBA example creates an ellipse on the active layer and assigns a bookmark to that ellipse.

```
Sub Test()
 ActivePage.ActiveLayer.CreateEllipse 2, 3, 4, 5
 ActiveShape.URL.BookMark = "Page 1"
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

URL.Region

Property **Region** As cdrURLRegion

Description

Member of URL

The **Region** property returns or specifies the region for a URL.

VBA example

The following VBA example sets the region for the URL to the bounding box of each shape on the page.

```
Sub Test()
 Dim sh As Shape
 For Each sh In ActivePage.Shapes
  sh.URL.Region = cdrURLRegionRectangle
 Next sh
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

URL.TargetFrame

Property **TargetFrame** As String

Description

Member of URL

The **TargetFrame** property returns or specifies the name of the target frame for a URL.

VBA example

The following VBA example displays the names of all targeted frames for the shapes on the page.

```
Sub Test()
 Dim sh As Shape, s As String
 For Each sh In ActivePage.Shapes
  If sh.URL.TargetFrame <> "" Then
   s = s & sh.URL.TargetFrame & vbCr
  End If
 Next sh
 MsgBox "The current page contains the following URL target frames: " & vbCr & s
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

UserSnapPoint

Properties

Description

The **UserSnapPoint** class represents user-created snap points.

Copyright 2014 Corel Corporation. All rights reserved.

UserSnapPoint.AutoSnap

Property **AutoSnap** As Boolean

Description

Member of UserSnapPoint

The **SegmentIndex** property specifies whether user-created snap points are included in automatic snapping for connectors.

Copyright 2014 Corel Corporation. All rights reserved.

UserSnapPoint.ID

Property **ID** As String

Description

Member of UserSnapPoint

The **SegmentIndex** property returns a read-only value that is associated with the unique ID (or GUID) of a user-created snap point.

Copyright 2014 Corel Corporation. All rights reserved.

View

Properties Methods

Description

The **View** class represents the view settings that are saved in the **View Manager**.

Copyright 2014 Corel Corporation. All rights reserved.

View.Activate

Sub **Activate()**

Description

Member of View

The **Activate** method makes a view active in a document.

VBA example

The following VBA example creates and activates a view.

```
Sub Test()
 Dim Vw As View
 Dim intCounter As Integer
 Set Vw = ActiveDocument.Views.AddActiveView("Test1")
 Vw.Activate
 Set Vw = Nothing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

View.Application

Property **Application** As Application

Description

Member of View

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

View.Delete

Sub **Delete()**

Description

Member of View

The **Delete** method deletes a saved view from the **View Manager**.

VBA example

The following VBA example deletes all views in the document.

```
Sub Test()
 Dim Vw As View
 Dim intCounter As Integer
 For intCounter = ActiveDocument.Views.Count To 1 Step -1
  Set Vw = ActiveDocument.Views(intCounter)
  Vw.Delete
 Next intCounter
 Set Vw = Nothing
End Sub
Sub Test()
 Dim Vws As Views
 Set Vws = ActiveDocument.Views
 While Vws.Count <> 0
  Vws(Vws.Count).Delete
 Wend
 Set Vws = Nothing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

View.Name

Property **Name** As String

Description

Member of View

The **Name** property returns or specifies the name of a view.

VBA example

The following VBA example sets the name of the first view in the Views collection and displays the new name.

```
Sub ViewName()
 With ActiveDocument.Views(1)
  .Name = "My New View"
  MsgBox .Name
 End With
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

View.OriginX

Property **OriginX** As Double

Description

Member of View

The **OriginX** property returns or specifies the value of the horizontal origin of a view.

VBA example

The following VBA example checks for views in the Views collection. If there is a view, it prints the horizontal origin of the view. If not, it adds a view and prints the horizontal origin.

```
Sub Test()
 Dim Vw As View
 Dim VwCollection As Views
 Set VwCollection = ActiveDocument.Views
  If VwCollection.Count > 0 Then
   Set Vw = VwCollection.Item(1)
   MsgBox "The horizontal origin of the active view is: " & Vw.OriginX
  Else
   Set Vw = VwCollection.AddActiveView("TestView")
   MsgBox "The horizontal origin of the active view is: " & Vw.OriginX
  End If
 Set Vw = Nothing
 Set VwCollection = Nothing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

View.OriginY

Property **OriginY** As Double

Description

Member of View

The **OriginY** property returns or specifies the value of the vertical origin of a view.

VBA example

The following VBA example adds a view if there are no saved views. The vertical origins of all saved views are then displayed.

```
Sub Test()
 Dim Vw As View
 Dim VwCollection As Views
 Dim s As String
 Set VwCollection = ActiveDocument.Views
 If ActiveDocument.Views.Count = 0 Then
  VwCollection.AddActiveView "test"
  For Each Vw In VwCollection
   s = s & Vw.OriginY & vbCr
  Next Vw
 Else
  For Each Vw In VwCollection
   s = s & Vw.OriginY & vbCr
  Next Vw
 End If
 MsgBox "The vertical origin's of the saved views are: " & vbCr & s
 Set Vw = Nothing
 Set VwCollection = Nothing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

View.Page

Property **Page** As Page

Description

Member of View

The **Page** property returns a reference to the page. When a custom view is created, it is associated with a specific document page.

- The **Page** property is applicable only if the UsePage property is set to **True**.

VBA example

The following VBA example adds a view, returns a reference to the page in the view, and displays the name of the page.

```
Sub Test()
 Dim Vw As View
 Dim VwCollection As Views
 Dim Pg As Page
 Dim s As String
 Set VwCollection = ActiveDocument.Views
 Set Vw = VwCollection.AddActiveView("TestView")
 Set Pg = Vw.Page
 s = s & Pg.Name & vbCr
 MsgBox "The page name of the chosen view is: " & vbCr & s
 Set Vw = Nothing
 Set VwCollection = Nothing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

View.Parent

Property **Parent** As Views

Description

Member of View

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

View.UsePage

Property **UsePage** As Boolean

Description

Member of View

The **UsePage** property returns or specifies whether to revert to a page when switching between views.

If the **UsePage** property is set to **True**, the page associated with the view appears in the drawing window when the view is activated. If the property is set to **False**, the view's page does not appear when the view is active.

VBA example

The following VBA example creates five pages and adds a view for each page. The zoom is incremented by **10** for each page, and the **UsePage** property is set to **False**.

```
Sub Test()
 Dim Vw As View
 Dim VwCollection As Views
 Dim intCounter As Integer
 Set VwCollection = ActiveDocument.Views
  For intCounter = 1 To 5
   ActiveDocument.AddPages (1)
   Set Vw = VwCollection.AddActiveView("TestView" & intCounter)
   Vw.Zoom = CDbl(intCounter * 10)
   Vw.UsePage = False
  Next intCounter
 Set Vw = Nothing
 Set VwCollection = Nothing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

View.UseZoom

Property **UseZoom** As Boolean

Description

Member of View

The **UseZoom** property returns or specifies whether the zoom value taken by a view affects when that view becomes active.

If the **UseZoom** property is set to **True**, the zoom value in a view is applied when the view becomes active. If the property is set to **False**, the view's zoom setting is not applied when the view is active.

VBA example

The following VBA example creates five pages and adds a view for each page. The zoom level is incremented by **50** for each page, and the **UseZoom** property is set to **False**.

```
Sub Test()
 Dim Vw As View
 Dim VwCollection As Views
 Dim intCounter As Integer
 Set VwCollection = ActiveDocument.Views
  For intCounter = 1 To 5
   ActiveDocument.AddPages (1)
   Set Vw = VwCollection.AddActiveView("TestView" & intCounter)
   Vw.Zoom = CDbl(intCounter * 50)
   Vw.UseZoom = False
  Next intCounter
 Set Vw = Nothing
 Set VwCollection = Nothing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

View.Zoom

Property **Zoom** As Double

Description

Member of View

The **Zoom** property returns or specifies the magnification level for a view.

- The **Zoom** property of a custom view is applicable only if the View.UseZoom property of the view is set to **True**.

VBA example

The following VBA example increases the zoom level by **50** for each view in the collection. The zoom level is set at **100** for the first view.

```
Sub Test()
 Dim Vw As View
 Dim VwCollection As Views
 Dim intCounter As Integer
 Set VwCollection = ActiveDocument.Views
 intCounter = 1
  For Each Vw In VwCollection
   intCounter = intCounter + 1
   Vw.Zoom = CDbl(intCounter * 50)
  Next Vw
 Set Vw = Nothing
 Set VwCollection = Nothing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

ViewHost

Properties Methods

Description

The **ViewHost** class represents a docking region that can host one or more views.

For an example that uses this class, see Cascading views.

Copyright 2014 Corel Corporation. All rights reserved.

ViewHost.DockHost

Property **DockHost** As DockHost

Description

Member of ViewHost

The **DockHost** property returns the DockHost that contains the view host.

The **DockHost** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ViewHost.DockItem

Property **DockItem** As DockItem

Description

Member of DockHost

The **DockItem** property returns the DockItem object representation of the view host.

The **DockItem** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ViewHost.ID

Property **ID** As String

Description

Member of ViewHost

The **ID** property returns the ID of the view host.

The **ID** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ViewHost.InsertView

Sub **InsertView**(*ViewToInsert As* ViewWindow, *Index As Long*)

Description

Member of ViewHost

The **InsertView** method inserts a view in the view host at the specified position.

Parameter	Description
ViewToInsert	Specifies the view
Index	Specifies where to insert the view

Copyright 2014 Corel Corporation. All rights reserved.

ViewHost.InsertViewHost

Sub **InsertViewHost**(*ViewHostToInsert As* ViewHost, *Index As Long*)

Description

Member of ViewHost

The **InsertViewHost** method inserts all views from the view host into the view host at the specified position.

Parameter	Description
ViewHostToInsert	Specifies the view host
Index	Specifies where exactly to insert the views

For an example that usese this method, see Combining views.

Copyright 2014 Corel Corporation. All rights reserved.

ViewHost.Position

Property **Position** As ScreenRect

Description

Member of ViewHost

The **Position** property returns the position and size of the view host on the screen.

The **Position** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ViewHost.Views

Property **Views** As ViewWindows

Description

Member of ViewHost

The **Views** property returns the collection of views in the view host.

The **Views** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ViewHosts

Properties Methods

Description

The **ViewHosts** class represents a collection of view hosts.

Copyright 2014 Corel Corporation. All rights reserved.

ViewHosts.Count

Property **Count** As Long

Description

Member of ViewHosts

The **Count** property returns the number of available view hosts.

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ViewHosts.Find

Function **Find**(ID As String) As ViewHost

Description

Member of ViewHosts

The **Find** method finds a view host by using its ID.

Parameter	Description
ID	Specifies the ID

The return value of this method is ViewHost.

Copyright 2014 Corel Corporation. All rights reserved.

ViewHosts.First

Property **First** As ViewHost

Description

Member of ViewHosts

The **First** property returns the first view host.

The **First** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ViewHosts.Item

Property **Item**(Index As Long) As ViewHost

Description

Member of ViewHosts

The **Item** property returns a view host by index.

The **Item** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ViewHosts.Last

Property **Last** As ViewHost

Description

Member of ViewHosts

The **Last** property returns the last view host.

The **Last** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

Views

Properties Methods

Description

The **Views** class represents a collection of document views (or View objects).

Copyright 2014 Corel Corporation. All rights reserved.

Views.AddActiveView

Function **AddActiveView(***Name As String***)** As View

Description

Member of Views

The **AddActiveView** method adds the current view to a collection.

Parameter	Description
Name	Specifies the name of the new view

VBA example

The following VBA example adds five views to the collection and increments the zoom level by **25** for each view.

```
Sub Test()
 Dim intCounter As Integer
 For intCounter = 1 To 5
  ActiveDocument.Views.AddActiveView "Test" & intCounter
  ActiveDocument.ActiveWindow.ActiveView.Zoom = (intCounter * 25)
 Next intCounter
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Views.Application

Property **Application** As Application

Description

Member of Views

The Application object defines properties of the main CorelDRAW application. It is the top-level object in the CorelDRAW hierarchy of objects, and you can access all other features of the application through its functions, methods, and properties.

It is not necessary to explicitly specify an **Application** object; it is always available in VBA, and its properties and methods are global.

The **Application** property returns a read-only value that is associated with the main CorelDRAW application.

Copyright 2014 Corel Corporation. All rights reserved.

Views.Count

Property **Count** As Long

Description

Member of Views

The **Count** property returns the number of views in a collection.

The **Count** property returns a read-only value.

VBA example

The following VBA example displays a message box if there are no views in the active document.

```
Sub Test()
 If ActiveDocument.Views.Count > 1 Then
  MsgBox "There are no views in the current document", vbCritical
 End If
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Views.Item

Property **Item(***IndexOrName As Variant***)** As View

Description

Member of Views

The **Item** property returns a read-only reference to a view in a Views collection. It is the default property of the **Views** class.

Parameter	Description
IndexOrName	Specifies the view by its index number or name: • **Index** — Specifies the preset placeholder that uniquely identifies each member of the **Views** collection • **Name** — Specifies the string that uniquely identifies each view

VBA example

The following VBA example displays the names of all views in the active document.

```
Sub Test()
 Dim intCounter As Integer
 Dim Vw As View
 Dim s As String
  For intCounter = 1 To ActiveDocument.Views.Count
   Set Vw = ActiveDocument.Views(intCounter)
   s = s & Vw.Name & vbCr
  Next intCounter
 MsgBox "The current document contains the following views: " & vbCr & s
 Set Vw = Nothing
End Sub
Sub Test()
 Dim Vw As View
 Dim s As String
  For Each Vw In ActiveDocument.Views
   s = s & Vw.Name & vbCr
  Next Vw
 MsgBox "The current document contains the following views: " & vbCr & s
 Set Vw = Nothing
End Sub
```

Copyright 2014 Corel Corporation. All rights reserved.

Views.Parent

Property **Parent** As Document

Description

Member of Views

The **Parent** property returns a read-only value that is associated with the properties, methods, and controls of an object's parent in the CorelDRAW hierarchy of objects. The application object refers to the CorelDRAW application.

A parent object acts as a container for child objects. For example, a form (as a container) is the parent object of a check box on that form.

Most objects have either a **Parent** property or a **Collection** property, pointing to the object's parent object in the object model. The **Collection** property is used if the parent object is a collection.

Copyright 2014 Corel Corporation. All rights reserved.

ViewWindow

Properties Methods

Description

The **ViewWindow** class represents a view.

For an examples that uses this class, see Cascading views.

Copyright 2014 Corel Corporation. All rights reserved.

ViewWindow.Activate

Sub **Activate()**

Description

Member of ViewWindow

The **Activate** method activates the view.

Copyright 2014 Corel Corporation. All rights reserved.

ViewWindow.AppView

Property **AppView** As Object

Description

Member of ViewWindow

The **AppView** property returns the application view object.

The **AppView** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ViewWindow.Close

Sub **Close()**

Description

Member of ViewWindow

The **Close** method closes the view.

Copyright 2014 Corel Corporation. All rights reserved.

ViewWindow.Description

Property **Description** As String

Description

Member of ViewWindow

The **Description** property returns the description or tooltip text of the view window.

The **Description** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ViewWindow.ID

Property **ID** As String

Description

Member of ViewWindow

The **ID** property returns the ID of the view.

The **ID** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ViewWindow.Index

Property **Index** As Long

Description

Member of ViewWindow

The **Index** property returns the tab index of the view in the view host.

The **Index** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ViewWindow.Kind

Property **Kind** As String

Description

Member of ViewWindow

The **Kind** property returns the type of application view contained in the view window.

The **Kind** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ViewWindow.Position

Property **Position** As ScreenRect

Description

Member of ViewWindow

The **Position** property returns the position and size of the view window on the screen.

The **Position** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ViewWindow.Title

Property **Title** As String

Description

Member of ViewWindow

The **Title** property returns the title of the view window.

The **Title** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ViewWindow.ViewHost

Property **ViewHost** As ViewHost

Description

Member of ViewWindow

The **ViewHost** property returns view host that contains the view.

The **ViewHosts** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ViewWindows

Properties Methods

Description

The **ViewWindows** class represents an array of view windows.

Copyright 2014 Corel Corporation. All rights reserved.

ViewWindows.Count

Property **Count** As Long

Description

Member of ViewWindows

The **Count** property returns the number of available views.

The **Count** property returns a read-only value.

Copyright 2014 Corel Corporation. All rights reserved.

ViewWindows.Find

Function **Find**(ID As String) As ViewHost

Description

Member of ViewWindows

The **Find** method finds a view host by using its ID.

Parameter	Description
ID	Specifies the ID

The return value of this method is ViewHost.

Copyright 2014 Corel Corporation. All rights reserved.