

Index of implementation-defined behavior

The entries in this section are rough descriptions; exact specifications are at the indicated page in the general text.

- `#pragma`, 412
- additional formats for `time_get::do_get_date`, 716
- alignment, 76
- alignment additional values, 77
- alignment of bit-fields within a class object, 226
- allocation of bit-fields within a class object, 226
- argument values to construct `basic_ios::failure`, 1015
- assignability of placeholder objects, 578
- behavior of attribute scoped token, 176
- behavior of `iostream` classes when `traits::pos_type` is not `streampos` or when `traits::off_type` is not `streamoff`, 996
- behavior of non-standard attributes, 177
- bits in a byte, 6
- choice of larger or smaller value of floating literal, 27
- concatenation of some types of string literals, 29
- conversions between pointers and integers, 106
- converting characters from source character set to execution character set, 17
- converting function pointer to object pointer and vice versa, 106
- default number of buckets in `unordered_map`, 813
- default number of buckets in `unordered_multimap`, 817
- default number of buckets in `unordered_multiset`, 824, 825
- default number of buckets in `unordered_set`, 821
- defining `main` in freestanding environment, 59
- definition and meaning of `__STDC__`, 412
- definition and meaning of `__STDC_VERSION__`, 413
- derived type for `typeid`, 103
- diagnostic message, 2
- distinctness of string literals, 29
- dynamic initialization of static objects before `main`, 61
- dynamic initialization of thread-local objects before entry, 61
- effect of calling `basic_filebuf::setbuf` with non-zero arguments, 1075
- effect of calling `basic_filebuf::sync` when a get area exists, 1076
- effect of calling `basic_streambuf::setbuf` with non-zero arguments, 1063
- effect of calling `ios_base::sync_with_stdio` after any input or output operation on standard streams, 1008
- effect on C locale of calling `locale::global`, 683
- encoding of universal character name not in execution character set, 26
- `error_category` for errors originating outside the operating system, 441
- exception type when `shared_ptr` constructor fails, 548, 549
- exceptions thrown by standard library functions that do not have an exception specification, 441
- execution character-set and execution wide-character set, 18
- exit status, 456
- extended signed integer types, 72
- formatted character sequence generated by `time_put::do_put` in C locale, 718
- headers for freestanding implementation, 425
- interactive device, 8
- linkage of `main`, 59
- linkage of names from Standard C library, 426
- locale names, 681
- manner of search for included source file, 405
- mapping from name to catalog when calling `messages::do_open`, 726
- mapping header name to header or external source file, 21

- mapping physical source file characters to basic source character set, [16](#)
- mapping to message when calling `messages::do_get`, [726](#)
- meaning of `asm` declaration, [173](#)
- meaning of attribute declaration, [140](#)
- negative value of character literal in preprocessor, [405](#)
- nesting limit for `#include` directives, [406](#)
- number of threads in a program under a freestanding implementation, [11](#)
- numeric values of character literals in `#if` directives, [405](#)
- parameters to `main`, [59](#)
- passing argument of class type through ellipsis, [99](#)
- physical source file characters, [16](#)
- presence and meaning of `native_handle_type` and `native_handle`, [1151](#)
- rank of extended signed integer type, [83](#)
- representation of `char`, [71](#)
- required libraries for freestanding implementation, [5](#)
- result of `exception::what`, [466](#)
- result of inexact floating-point conversion, [82](#)
- result of right shift of negative value, [120](#)
- return value of `bad_alloc::what`, [462](#)
- return value of `bad_cast::what`, [464](#)
- return value of `bad_exception::what`, [467](#)
- return value of `bad_typeid::what`, [465](#)
- return value of `char_traits<char16_t>::eof`, [635](#)
- return value of `char_traits<char32_t>::eof`, [636](#)
- return value of `type_info::name()`, [464](#)
- search locations for `"` header, [406](#)
- search locations for `<>` header, [405](#)
- semantics of linkage specification on templates, [317](#)
- semantics of linkage specifiers, [173](#)
- semantics of non-standard escape sequences, [26](#)
- sequence of places searched for a header, [405](#)
- signedness of `char`, [71](#)
- `sizeof` applied to fundamental types other than `char`, `signed char`, and `unsigned char`, [109](#)
- stack unwinding before call to `std::terminate()`, [396](#), [401](#)
- start-up and termination in freestanding environment, [59](#)
- string resulting from `__func__`, [197](#)
- support for extended alignment, [602](#)
- support for over-aligned types, [110](#), [530](#), [532](#)
- supported multibyte character encoding rules, [634](#), [636](#)
- text of `__DATE__` when date of translation is not available, [412](#)
- text of `__TIME__` when time of translation is not available, [412](#)
- type of `ios_base::streamoff`, [1248](#)
- type of `ios_base::streampos`, [1248](#)
- type of `ptrdiff_t`, [119](#), [444](#)
- type of `regex_constants::error_type`, [1097](#)
- type of `size_t`, [444](#)
- type of `streamoff`, [634](#)
- type of `streampos`, [634](#)
- type of `u16streampos`, [635](#)
- type of `u32streampos`, [636](#)
- type of `wstreampos`, [636](#)
- type of `array::const_iterator`, [763](#)
- type of `array::iterator`, [763](#)
- underlying source of random numbers for `random_shuffle`, [1267](#)
- underlying type for enumeration, [159](#)
- use of non-POF function as signal handler, [472](#)
- value of `ctype<char>::table_size`, [694](#)
- value of character literal outside range of corresponding type, [26](#)
- value of multicharacter literal, [25](#)
- value of result of inexact integer to floating-point conversion, [82](#)
- value of result of unsigned to signed conversion, [81](#)
- value of wide-character literal containing multiple characters, [26](#)
- value of wide-character literal with single c-char that is not in execution wide-character set, [26](#)
- value representation of floating-point types, [72](#)
- value representation of pointer types, [73](#)
- values of a trivially copyable type, [70](#)
- values of various `ATOMIC..._LOCK_FREE` macros, [1139](#)
- whether `get_pointer_safety` returns `pointer_safety::relaxed` or `pointer_safety::preferred` if the implementation has relaxed pointer safety, [525](#)
- whether `time_get::do_get_year` accepts two-digit year numbers, [716](#)

whether an implementation has relaxed or strict
pointer safety, [66](#)
whether locale object is global or per-thread, [678](#)
whether sequence pointers are copied by `basic_-
filebuf` move constructor, [1071](#)
whether sequence pointers are copied by `basic_-
stringbuf` move constructor, [1060](#)
whether source of translation units must be avail-
able to locate template definitions, [17](#)
whether stack is unwound before calling `std::terminate()`
when a `noexcept` specification is violated,
[401](#)
whether values are rounded or truncated to the
required precision when converting be-
tween `time_t` values and `time_point` ob-
jects., [621](#)
which functions in Standard C++ library may be
recursively reentered, [440](#)