

NAME : TANISHQ GUPTA

CLASS : SE

BATCH : A4

ROLL NO.: SEAD21168

D-19

Problem statement: A Dictionary stores keywords & its meaning. Provide facility for adding new keywords, deleting keywords, updating values of any entry. Provide facility to display whole data sorted in ascending/ Descending order. Also find how many maximum comparisons may require for finding any keyword. Use Height balance tree and find the complexity for finding a keyword

CODE:

```
#include <iostream>

using namespace std;

class node
{ public:
    string key;
    string meaning;
    node *left;
    node *right;
};

class AVL
{
    node *root;

public:
    AVL()
    {
        root=NULL;
    }

    void create();
    node* insert(node *cur,node *temp);
    node* balance(node *temp);
    int dif(node *temp);
    int height(node *temp);
};
```

```

int maximum(int a,int b);

node* LL(node *par);

node* RR(node *par);

node* LR(node *par);

node* RL(node *par);

void ascending(node *temp);

node* delete_n(node *root,string key1);

void deleten();

node* extractmin(node *t);

void descending(node *temp);

void display();

bool search(node *cur,string key1);

void search_value();

};

void AVL::create()
{
    char answer;
    node *temp;
    do
    {
        temp=new node();
        cout<<"\n Enter the keyword:";
        cin>>temp->key;
        cout<<"\n Enter the meaning:";
        cin>>temp->meaning;
        temp->left=temp->right=NULL;
        root=insert(root,temp);
        cout<<"\n Do you want to add another word?(y/n)";
        cin>>answer;
    }
    while(answer=='y' || answer=='Y');

```

```

}

node* AVL::insert(node cur,node temp)
{
    if(cur==NULL)
    {
        return temp;    }
    if(temp->key<cur->key)
    {
        cur->left=insert(cur->left,temp);
        cur=balance(cur);
    }
    else if(temp->key>cur->key)
    {
        cur->right=insert(cur->right,temp);
        cur=balance(cur);    }
    return cur;    }

```

```

node* AVL::balance(node *temp)
{
    int bal;
    bal=dif(temp);
    if(bal>=2)
    {
        if(dif(temp->left)<0)
            temp=LR(temp);
        else
            temp=LL(temp);
    }
    else if(bal<=-2)
    {
        if(dif(temp->right)<0)

```

```

        temp=RR(temp);
    else
        temp=RL(temp);
    }
    return temp;
}

int AVL::dif(node *temp)
{
    int l,r;
    l=height(temp->left);
    r=height(temp->right);
    return(l-r);
}

int AVL::height(node *temp)
{
    if(temp==NULL)
        return(-1);
    else
        return(max(height(temp->left),height(temp->right))+1);
}

int AVL::maximum(int a,int b)
{
    if(a>b)
        return a;
    else
        return b;
}

node* AVL::LL(node *par)
{
    node *temp,*temp1;
    temp=par->left;

```

```

        temp1=temp->right;
        temp->right=par;
        par->left=temp1;
        return temp;
    }

```

```

node* AVL::RR(node *par)
{
    node *temp,*temp1;
    temp=par->right;
    temp1=temp->left;
    temp->left=par;
    par->right=temp1;
    return temp;
}

```

```

node* AVL::LR(node *par)
{
    par->left=RR(par->left);
    return(LL(par));
}

```

```

node* AVL::RL(node *par)
{
    par->right=LL(par->right);
    return(RR(par));
}

```

```

void AVL::ascending(node *temp)
{
    if(temp!=NULL)
    {
        ascending(temp->left);
        cout<<"\n\t"<<temp->key<<" : "<<temp->meaning;
    }
}

```

```

        ascending(temp->right);
    }
}

void AVL::descending(node *temp)
{
    if(temp!=NULL)
    {
        descending(temp->right);

        cout<<"\n\t"<<temp->key<<" : "<<temp->meaning;

        descending(temp->left);
    }
}

void AVL::display()
{
    cout<<"\n The keywords in ascending order are : \n";
    ascending(root);

    cout<<"\n The keywords in descending order are : \n";
    descending(root);
}

bool AVL::search(node *cur,string key1)
{
    if(cur)
    {
        if(cur->key==key1)
            return true;

        if(cur->key>key1)
            return search(cur->left,key1);

        else
            return search(cur->right,key1);
    }

    return false;
}

```

```

}

void AVL::search_value()
{
    string key2;
    cout<<"\n Enter the keyword you wish to search : ";
    cin>>key2;
    if(search(root,key2))
        cout<<"\n The entered keyword is present in the AVL tree";
    else
        cout<<"\n The entered keyword is not present in the AVL tree";
}

node* AVL::delete_n(node* cur,string key1)
{
    if ( !cur)
        return cur;

    if ( key1 < cur->key )
        cur->left = delete_n(cur->left, key1);

    else if( key1 > cur->key )
        cur->right = delete_n(cur->right, key1);
    else
    {
        node *l = cur->left;
        node *r = cur->right;
        delete cur;
        if ( !r )
            return l;

        node *m=r;
        while(m->left)
            m=m->left;
        m->right = extractmin(r);
    }
}

```

```

        m->left = l;

        return balance(m);
    }

    return balance(cur);
}

node* AVL::extractmin(node *t)
{
    if ( !t->left )

        return t->right;

    t->left = extractmin(t->left);

    return balance(t);
}

void AVL::deleten()
{
    string key;

    cout<<"\n Enter the keyword to be deleted : ";

    cin>>key;

    root=delete_n(root,key);
}

int main()
{
    char c;

    int ch;

    AVL a;

    do
    {
        cout<<"*****",

        cout<<"\n 1.Insert a keyword in AVL tree.";

        cout<<"\n 2.Display the AVL tree.";

        cout<<"\n 3.Search a keyword";

        cout<<"\n 4.Delete a keyword.";
    }

```



```
    cout<<"\n Enter your choice : ";
    cin>>ch;
    switch(ch)
    {
        case 1 : a.create();
        break;
        case 2 : a.display();
        break;
        case 3 : a.search_value();
        break;
        case 4 : a.deleten();
        break;
        default : cout<<"\n Wrong choice ! ";
    }
    cout<<"\n Do you want to continue? (y/n): ";
    cin>>c;
    }
    while(c=='y' || c=='Y');

    return 0;
}
```

OUTPUT:

```
PS C:\Users\tanis\OneDrive\Desktop\tanishq_gupta_21168> g++ '.\9 DictionaryAVL.cpp'
PS C:\Users\tanis\OneDrive\Desktop\tanishq_gupta_21168> .\a.exe

-----Menu-----
1.Create
2.Display
3.Search
4.Update
5.Delete
6.Exit
Enter:: 1

Enter Keyword :: happy
Enter Meaning :: enjoy

Do u want to add more (y/n):y

Enter Keyword :: word
Enter Meaning :: meaning

Do u want to add more (y/n):n

-----Menu-----
1.Create
2.Display
3.Search
4.Update
5.Delete
6.Exit
Enter:: 2
Keyword      Meaning
-----
happy -      enjoy
word  -      meaning

-----Menu-----
1.Create
2.Display
3.Search
4.Update
5.Delete
6.Exit
Enter:: 5

Enter Keyword which u want to delete :: word

-----Menu-----
1.Create
2.Display
3.Search
4.Update
5.Delete
6.Exit
Enter:: 2
Keyword      Meaning
-----
happy -      enjoy

-----Menu-----
1.Create
2.Display
3.Search
4.Update
5.Delete
6.Exit
Enter:: 6
Thank You!
PS C:\Users\tanis\OneDrive\Desktop\tanishq_gupta_21168> |
```