

CSCE 240 INTRO. TO SOFTWARE ENGINEERING

VOTER SIMULATION: SYSTEM GUIDE

Hadrian Buckner, Nicholas Grah, Brian Griffin, Peter
Sanders, Tahir Warid

2016-12-01

Abstract

The purpose of this program is to simulate voter wait-times and determine how many voting booths are necessary in any given precinct in order to ensure voters do not wait inordinately long amounts of time to cast their vote.

1 Input Files

1.1 Configuration File

The configuration begins with a one-line header containing the following input data:

int Some arbitrary random number seed.

int⁺ The length (in hours) of the election day.

int⁺ The best-guess mean service time of a voter in minutes.

int⁺ The minimum number of voters-per-precinct that will be supported by this simulation.

int⁺ The maximum number of voters-per-precinct that will be supported by this simulation.

int⁺ The maximum acceptable amount of time for a voter to wait.

int⁺ The number of iterations of the simulation to run. As more iterations are run, the data becomes asymptotically more “complete” with respect to consideration of outliers, but the execution time grows linearly.

The following line(s) should contain one (1) more whitespace-delimited entries than the number of hours in the election day. These should be percent (%) values and should sum to one hundred (100). The first value represents the fraction of voters who voted absentee or otherwise in advance. The subsequent values represent the fraction of voters arriving in each hour of the election day.

1.2 Data File

This file is hard-coded into the program. The program must be executed from two directories below a directory containing **dataallsorted.txt**. In other words, **../../dataallsorted.txt** must contain the data file.

This file should contain space-delimited integer values that represent voter service times in seconds. These values should be sorted in non-decreasing order.

1.3 Precinct File

The precinct file contains the definitions of arbitrarily many precincts.

Note: The file must contain nothing but complete precincts. Any superfluous text, any incomplete entries, or any invalid entries will cause the program to exit.

A Precinct is defined by the following information:

int Precinct ID. This is a *unique* numeric identifier for the precinct.

text Precinct Name. *Note: Must NOT contain whitespace.*

real Precinct Turnout. The percentage of registered voters in a given precinct who actually voted.

int⁺ Actual number of voters.

int⁺ Number of voters expected.

int⁺ Expected rate of voters (voters per hour).

int⁺ Number of voting booths.

real Percent of minority voters.

int⁺ The last three items are used to set breakpoints. Detailed statistics are given as a histogram when the number of simulated voting booths is equal to the number given in these positions. Zero (0) is used to indicate the breakpoint is not used.

int⁺

int⁺

Only the number of expected voters and the precinct ID are used by the simulation. The other values are statistics that should be presented to the end user along with the simulation data.

1.4 Output Files

The last two arguments passed in the program call should be two file locations. The user executing this program must have write privileges at the specified location. The system must have on the order of megabytes of free space. Any files already existing at these locations will be overwritten.

The first file is used for the output of the program. The second file will also contain the output of the program, but if debugging options are turned on at compile-time, it will also contain log information. See Chapter 2 for detailed information on their contents.

2 Output Files

First, **MAIN** records the time and begins execution. Messages are printed to indicate the names of the output files.

Next, the configuration data is printed with the tag **CONFIG**. See §1.1 for more information.

SIM will be the next tag encountered. This is the **Simulation** class. It prints out the canonical string form of the **Precinct** being simulated. See §6.2.3 for more details on this string. As execution is passed off to this precinct, the next tag encountered is **OnePct**.

First, the canonical string form of the precinct is printed again. Next, the canonical string forms of the simulations for that precinct with one voting booth are printed. The number of simulations corresponds to the number of iterations specified in the configuration file. The canonical string form of a simulation may be found in Table 2.1. An example string follows, with superfluous whitespace omitted for the sake of space.

```
0 1 XXX00100 100 1 stations, mean/dev wait (mins) 0.43 0.95 toolong 0
0.00 0 0.00 0 0.00
```

This is repeated for as many iterations as were specified in the config file.

If the current number of voting booths was specified as a breakpoint in the Precinct File (See §1.3), a histogram is printed. One star on the histogram represents a computed value between one (1) and fifty (50) of voters. The histogram has a resolution of minutes and relates to the probability distribution function of voter wait time.

This, in turn, is repeated with incrementally more voting stations until there are no voters waiting too long.

Finally, this is repeated by **SIM** over the set of all precincts before returning execution to **MAIN**, printing the ending execution time.

Table 2.1: Canonical String Form of a Precinct Simulation

Simulation Number	
Precinct ID	
Precinct Name	
Expected Voters	
Number of Stations	This is followed by the text “stations,”
Mean time to vote (mins)	This is preceded by the text “mean/dev wait (mins)”
Standard Deviation of time to vote	
Number of voters waiting too long	This is preceded by the text “toolong”
Percent of voters waiting too long	
Number of voters waiting much too long	This is defined as ten (10) minutes longer than simply “too long”
Percent of voters waiting much too long	
Number of voters waiting very much too long	This is defined as twenty (20) minutes longer than simply “too long”
Percent of voters waiting very much too long	

3 MyRandom

The MyRandom class is used to generate pseudo random numbrs from a seed provided. The functions contained in MyRandom are used by this program to generate voter data.

3.1 Constructor

The MyRandom class contains overloaded constructor functions. The first instance uses the integer 1 as the seed value, while the second takes an integer parameter value that is used for the seed. If a seed value is provided, MyRandom will use that value, but if a seed value is not provided, MyRandom will use a seed value of 1.

3.1.1 Seed Not Provided

```
MyRandom::MyRandom() {  
    seed_ = 1;  
    generator_.seed(seed_);  
}
```

3.1.2 Seed Provided

```
MyRandom::MyRandom(unsigned seed) {  
    seed_ = seed;  
    generator_.seed(seed_);  
}
```

3.2 General Functions

3.2.1 RandomExponentialInt

Parameters double lambda

Returns int r

Usage This function takes a double lambda as input, and returns an integer r. The lambda is the is the lambda value of the exponentially distributed

real numbers. This function generates a double value based on the lambda constraint, rounds the double to the nearest integer, and returns this integer value. This function is used in the Simulation Program to calculate the interval of voter arrival times.

3.2.2 RandomNormal

Parameters double mean, double dev

Returns double r

Usage This function takes in doubles mean and dev for input, and generates a pseudo random number from a set with the provided mean and standard deviation.

3.2.3 RandomUniformInt

Parameters int lower, int upper

Returns int r

Usage This function takes in two integer s as parameters, describing the maximum and minimum values that can be generated. This function returns a pseudo-randomly generated value that falls between the upper and lower limits provided. In the Simulation Program, this function is used to calculate the time taken for a voter to finish voting. This function works well time taking to vote must be greater than zero, and less than the maximum service time specified in the config file.

3.3 Private Members

unsigned int seed_ The value given to start pseudo-random number generation. This number can be provided when MyRandom is declared, or will be the default value 1.

std::mt19937 generator_ Pseudo-random number generator provided by the random library.

4 OneVoter

The OneVoter class is used to represent a single voter to be used in the voting simulation.

4.1 Constructor

The Constructor for the OneVoter class takes in three integers as parameters. These integers assign values to the Voter's `sequence_`, `time_arrival_seconds_`, and `time_vote_duration_seconds_` variables. The `Time_Start_voting_seconds_` and `which_station` variables are set to default values 0 and -1 by the constructor.

4.2 General Functions

4.2.1 AssignStation

Parameters `int station_number`, `int start_time_seconds`

Returns `void`

Usage This function takes in `station_number` and `Start_time_seconds`, and uses the data to calculate which station the voter will use, total time spent voting, and total time spent waiting to vote.

4.2.2 GetTimeDoneVoting

Parameters `none`

Returns returns the time spent voting as `int`

Usage calculates time spent voting by adding `time_start_voting_seconds_` and `time_vote_duration_seconds_`.

4.2.3 GetTimeInQ

Parameters `none`

Returns returns time spent in voting que as `int`

Usage calculates time spent in the voting que for a single voter by subtracting `time_arrival_seconds_` from `time_start_voting_seconds_`.

4.2.4 GetTOD

Parameters `int time_in_seconds`

Returns Returns the time of day that a voter voted as a string.

Usage Uses `time_in_seconds` and `offset_hours` to calculate when the voting took place.

4.2.5 ConvertTime

Parameters `int time_in_seconds`

Returns returns a time as a string

Usage uses time in seconds to calculate time with hours, minutes, and seconds. This function is called by GetTOD.

4.2.6 ToString

Usage Standard ToString function for an instance of OneVoter.

4.2.7 int time_in_seconds

Usage Returns a string of shortened variable names to act as a header for a table of voter data.

4.3 Private Variables

int sequence Voters place in the que of voters.

int time_arrival_seconds_ Time voter arrived at polling station after station opened.

int time_done_voting_seconds_ Time the voter has completed voting process.

int time_start_voting_seconds_ The time a voter begins the voting process.

int time_vote_duration_seconds_ Time a voter spends voting.

int time_waiting_seconds_ Time a voter spends waiting to vote.

int which_station_ The voting station at which a voter votes.

5 Configuration

The Configuration class is dedicated to reading in the input files detailed in Chapter 1. All variables are publically accessible, so maintainers should take care to ensure that they are not inadvertently modified.

```
static const int kDefaultSeed = 19;
static const int kDummyConfigInt = -111;
static const double kDummyConfigDouble = -22.22;

// This is the seed to be used for the Random Number Generator
int seed_ = kDefaultSeed;

int election_day_length_hours_ = kDummyConfigInt;
int election_day_length_seconds_ = kDummyConfigInt;
int time_to_vote_mean_seconds_ = kDummyConfigInt;
int max_expected_to_simulate_ = kDummyConfigInt;
int min_expected_to_simulate_ = kDummyConfigInt;
int wait_time_minutes_that_is_too_long_ = kDummyConfigInt;
int number_of_iterations_ = kDummyConfigInt;
vector<int> actual_service_times_;

// This is the percentage of voters already in line when pools
// opened.
double arrival_zero_ = kDummyConfigDouble;

// This array will contain |election_day_length_hours_| elements
// which shall correspond to the percentage of voters arriving
// during each hour of the election day
vector<double> arrival_fractions_;
```

6 OnePct

The OnePct class is used to represent a single voting precinct during the simulation. This class is used by the Simulation class.

6.1 Member Variables

- int** `pct_expected_voters_` Number of voters expected to vote at this precinct.
- int** `pct_expected_per_hour_` Number of voters expected to vote at this precinct over a one hour period.
- double** `pct_minority_` Percentage of a precinct's voters who identified as a minority.
- string** `pct_name_` Name of an individual precinct.
- int** `pct_number_` Number assigned as an identifier to an individual precinct.
- double** `pct_turnout_` Percentage of the number of expected voters who showed up to vote at a precinct. This is not used in calculations.
- int** `pct_stations_` Number of voting stations at a single precinct.
- int** `pct_num_voters_` Total number of voters who voted in a precinct.
- double** `wait_dev_seconds_` The standard deviation of the wait times of the voters in a precinct in seconds.
- double** `wait_mean_seconds_` The mean wait time of the voters in a precinct in seconds.
- set<int>** `stations_to_histo_` Set containing the number of voting stations used in the simulation. This is meant to be displayed as part of a histogram of the data.
- vector<int>** `free_stations_` Vector containing the stations not currently in use. This is used in the RunSimulationPct2 function.

multimap<int, OneVoter> voters_backup_ This is a map containing all of the voters created by the CreateVoters function. This map is populated before the real work of the simulation begins.

multimap<int, OneVoter> voters_done_voting_ This map contains the voters who have already voted in the simulation. Voters in voters_voting_ are moved here when they have finished voting.

multimap<int, OneVoter> voters_pending_ This map begins as a copy of voters_backup_ before any voting has occurred. Voters are removed from this map as they finish voting, and are added voters_done_voting_.

multimap<int, OneVoter> voters_voting_ This map contains voters who are currently at a voting station. Once a voter finishes voting, they are moved to voters_done_voting_.

6.2 General Functions

6.2.1 ReadData

Parameters Scanner& infile

Returns void

Usage ReadData is passed in a reference to a scanner as input. The data read by the scanner is used to provide values for the member variables of an instance of OnePct.

6.2.2 RunSimulationPct

Parameters const Configuration& config, MyRandom& random, ofstream& out_stream

Returns void

Usage RunSimulationPct does the real work when simulating a single voting precinct. This function generates voters, simulates voting for a precinct, and collects and stores the data from the simulation.

6.2.3 ToString

Parameters none

Returns string s

Usage ToString Formats the information collected during the voting simulation, as well as the expected voters and expected voters per hour, and stores it to a string s. String s is returned.

Format pct_number pct_name_ pct_turnout_ pct_num_voters_ pct_expected_voters_
pct_expected_per_hour_ pct_stations_ pct_minority_ "HH" Stations_to_histo_
"HH"

Example 1 XXX00100 20.20 10101 100 235 8 10.30 HH 0 HH

6.2.4 ToStringVoterMap

Parameters string label, multimap<int, OneVoter> themap

Returns string s

Usage Takes a map of instances of voters as input. This function iterates through the map of voters, calling ToString for each, and storing the returned string into string s. This function then returns string s.

6.3 General Private Functions

6.3.1 CreateVoters

Parameters const Configuration& config, MyRandom& random, ofstream& out_stream

Returns void

Usage This function is called by RunSimulationPct. This function uses input from the config file, number of expected voters, and the random number generator to generate all the instances of voters used to simulate voting in a single precinct.

6.3.2 DoStatistics

Parameters int iteration, const Configuration& config, int station_count, map<int, int>& map_for_histo, ofstream& out_stream

Returns toolongcount (Number of voters who waited for too long)

Usage This function is called by RunSimulation.pct to determine the mean and standard deviation of vote times, and the number of voters who waited for too long at a single precinct.

6.3.3 ComputeMeanAndDev

Parameters none

Returns void

Usage This function is called by the DoStatistics function. This function calculates the mean and standard deviation of the wait times of voters for a single precinct.

6.3.4 RunSimulationPct2

Parameters int stations_count

Returns void

Usage This function is called by the RunSimulationPct function. This function takes the number of open voting stations as input, and simulates moving the line of waiting voters through the voting stations.

7 Simulation

This class begins performing the simulation by creating the voting precincts from the input file, and calling the `RunSimulationPct` function for each precinct.

7.1 General Functions

7.1.1 ReadPrecincts

Parameters `Scanner& infile`

Returns `void`

Usage Using a reference to the scanner reading from the input file, this function generates instances of `OnePct` and calls `ReadData` for that precinct, to populate it's member variables with values. This continues until the scanner stops providing input. These precincts are stored in the `pcts_` map.

7.1.2 RunSimulation

Parameters `const Configuration& config, MyRandom& random, ofstream& out_stream`

Returns `void`

Usage This function iterates through the `pcts_` map, and, if the precinct has an appropriate number of voters for the simulation, calls `RunSimulationPct` for that precinct.

7.1.3 ToString

Usage Standard `ToString` function; Returns `ToString` of precincts stored in `pcts_` map.

7.2 Private Variables

map<int, OnePct> pcts_ This map contains all instances of `OnePct` that will be used in the simulation.

8 Main

The Main class is the entry point in the Voting Simulation program. Main is responsible for gathering input and checking that arguments passed in are of the correct type. Main also opens the Utils log file before passing execution to the Simulation class.

Main does not contain any member functions or variables.

Main supplies input data to the configuration class and the MyRandom class, and passes data to the Simulation class that will be used to create the voting precincts.

Once Input files have been properly handles, an instance of the Simulation class is created, and RunSimulation is called for that instance of simulation.

9 Execution Trace

The execution begins at an entry point referred to here as **Main** and proceeds, most distally, to **OneVoter** through a topology described in Figure 9.1.

Execution begins at **Main**. First, all variables used by **Main** are declared. First, boilerplate program entry is taken care of: Arguments are validated, files are opened, system state is recorded, etc.

An instance of **Configuration** is initialized from the corresponding stream, which is then closed.

9.1 Configuration

Configuration is a *Singleton* collection of public variables that will be used throughout the program. It accepts an open stream for the configuration file, which should be of the format described in §1.1. Next, a log-normal data set is read in by the same call. This stream is opened in context by the **Configuration::ReadConfiguration** function. *NOTE: The program will crash if the file is not found.* The conditions for this file are given in §1.2.

From here, execution returns to **Main** and proceeds to **Simulation**.

9.2 Simulation

Simulation does very little work and exists only to group **Precincts** into batches. **Precincts** are read in from a file first, then execution is passed off to each precinct in turn to run its simulation.

9.3 OnePct

This is the “meat” of the program. Execution first enters **OnePct** at **RunSimulationPct**.

A simulation runs through a day of voting in order to determine the number of voting booths required to handle voters efficiently. The purpose of **OnePct::RunSimulationPct** is to regulate the number of voting booths being simulated. Given a mean voting time in seconds (*MVT*) and a number of

voters (NV) on an election day (L) hours long, the initial number of voting booths (VB_0) is given by Equation 9.1 below.

$$VB_0 = \begin{cases} \lfloor \frac{MVT \times NV}{3600 \times L} \rfloor & MVT \times NV \geq 3600 \times L \\ 1 & \text{otherwise} \end{cases} \quad (9.1)$$

Beginning with this number and iterating upwards until no voters are waiting “too long,” the program runs the number of iterations indicated by §1.1. After all iterations have run, a histogram is printed if this number of voting machines is a breakpoint number for this precinct.

9.3.1 CreateVoters

Each single iteration consists of three parts. First, voters are created. This includes a set of voters waiting at the door when the polls open and exponential random voters at the hourly rates indicated by the configuration file.

9.3.2 RunSimulationPct2

Next, simulation is passed off to another function. This manages the processing of voters through the queue.

9.3.3 DoStatistics

Finally, some statistics are run to determine if any voters waited too long, among other things.




Figure 9.1: Execution Topology by Class