

1 Syntax

1.1 Source Syntax

Types	$T ::= \alpha \mid \top \mid \tau_1 \rightarrow \tau_2 \mid \forall \alpha. \tau \mid \tau_1 \& \tau_2 \mid \{l : \tau\}$
Expressions	$E ::= x \mid \top \mid \lambda(x : \tau). e \mid e_1 \ e_2 \mid \Lambda \alpha. e \mid e \ \tau \mid e_1, e_2 \mid \{l = e\} \mid e.l \mid e \setminus l$ $\mid \text{sig } s[\bar{\alpha}] \text{ where } \bar{l} : \tau \text{ in } e$ $\mid \text{sig } s_1[\bar{\alpha}_1] \text{ extends } \overline{s_2[\bar{\alpha}]}$ where $\bar{l} : \tau \text{ in } e$ $\mid \text{algebra } x \text{ implements } \overline{s[\bar{\tau}]}$ where $\bar{l} @ (l_1 \ \bar{x}_1) = e_1 \text{ in } e$ $\mid \text{algebra } x \text{ extends } \bar{x}_0 \text{ implements } \overline{s[\bar{\tau}]}$ where $\bar{l} @ (l_1 \ \bar{x}_1) = e_1 \text{ in } e$ $\mid \text{data } d \text{ from } s[\bar{\alpha}_0].\alpha_1 \text{ in } e$ $\mid \text{let } x \ (\bar{x}_1 : \bar{\tau}_1) \ (\bar{x}_2 : d[\bar{\tau}]) : d[\bar{\tau}] = e_1 \text{ in } e$ $\mid e[\bar{\tau}] < \bar{x} >$
Contexts	$\Gamma ::= \epsilon \mid \Gamma, \alpha \mid \Gamma, x : \tau$ $\mid \Gamma, s[\bar{\alpha}] \rightarrow \bar{l} : \tau$ $\mid \Gamma, x \multimap \overline{s[\bar{\tau}]}$ $\mid \Gamma, d \rightsquigarrow s[\bar{\alpha}_0].\alpha_1 : \tau$
Labels	l (fields) s (interfaces) d (datatypes)
Syntactic sugars	$\circ ::= s[\bar{\alpha}_0]$ $\bullet ::= [\bar{\alpha}_0 / \bar{\alpha}] \Gamma(s)$ $\circ ::= d(\bar{\tau}_0)$ $\bullet ::= [\bar{\tau}_0 / (\bar{\alpha}_0 \setminus \alpha_1)] \Gamma(d)$

1.2 Target Syntax

Types	$T ::= \alpha \mid \top \mid \tau_1 \rightarrow \tau_2 \mid \forall \alpha. \tau \mid \tau_1 \& \tau_2 \mid \{l : \tau\}$
Expressions	$E ::= x \mid \top \mid \lambda(x : \tau). e \mid e_1 \ e_2 \mid \Lambda \alpha. e \mid e \ \tau \mid e_1, e_2 \mid \{l = e\} \mid e.l \mid e \setminus l$
Contexts	$\Gamma ::= \epsilon \mid \Gamma, \alpha \mid \Gamma, x : \tau$
Labels	l
Syntactic sugars	$\circ ::= \text{let } x : \tau = e_1 \text{ in } e_2$ $\bullet ::= (\lambda(x : \tau). e_2) \ e_1$

2 Translation Rules

$\boxed{\Gamma \vdash e : \tau \Rightarrow E}$	$\frac{\Gamma, s[\bar{\alpha}] \rightarrow \bar{l} : \tau \vdash e : \tau_* \Rightarrow E}{\Gamma \vdash \text{sig } s[\bar{\alpha}] \text{ where } \bar{l} : \tau \text{ in } e : \tau_* \Rightarrow \text{let merge}_s : \dots = \dots \text{ in } E}$
	$\frac{\overline{\Gamma \vdash s_2[\bar{\alpha}_2]} \quad \Gamma, s_1[\bar{\alpha}_1] \rightarrow \mathbf{U}_{\emptyset} [\bar{\alpha} / \bar{\alpha}_2] \Gamma(s_2) \ \mathbf{U}_{\leftarrow} \bar{l} : \tau \vdash e : \tau_* \Rightarrow E}{\Gamma \vdash \text{sig } s_1[\bar{\alpha}_1] \text{ extends } \overline{s_2[\bar{\alpha}]}$ where $\bar{l} : \tau \text{ in } e : \tau_* \Rightarrow \text{let merge}_{s_1} : \dots = \dots \text{ in } E$
$\overline{\Gamma \vdash s[\bar{\alpha}]}$	$\frac{\overline{\Gamma, \bar{x}_1 : \text{gen2}_A(l_1) \vdash e_1 : \tau_1 \Rightarrow E_1} \quad \Gamma, x : \&[\bar{\tau} / \bar{\alpha}] \Gamma(s), x \multimap \overline{s[\bar{\tau}]} \vdash e : \tau_* \Rightarrow E}{\Gamma \vdash \text{algebra } x \text{ implements } \overline{s[\bar{\tau}]}$ where $\bar{l} @ (l_1 \ \bar{x}_1) = e_1 \text{ in } e : \tau_* \Rightarrow \text{let } x : \&[\bar{\tau} / \bar{\alpha}] \Gamma(s) = \{l_1 = \lambda(\bar{x}_1 : \text{gen2}_A(l_1)). \{l = E_1\}\} \text{ in } E$ NEED TCHECK
$\overline{\Gamma \vdash s[\bar{\alpha}]}$	$\frac{\overline{\Gamma \vdash x_0} \quad \overline{\Gamma, \bar{x}_1 : \text{gen2}_A(l_1) \vdash e_1 : \tau_1 \Rightarrow E_1} \quad \Gamma, x : \&[\bar{\tau} / \bar{\alpha}] \Gamma(s), x \multimap \overline{s[\bar{\tau}]} \vdash e : \tau_* \Rightarrow E}{\Gamma \vdash \text{algebra } x \text{ extends } \bar{x}_0 \text{ implements } \overline{s[\bar{\tau}]}$ where $\bar{l} @ (l_1 \ \bar{x}_1) = e_1 \text{ in } e : \tau_* \Rightarrow \text{let } x : \&[\bar{\tau} / \bar{\alpha}] \Gamma(s) = \bar{x}_0, \{l_1 = \lambda(\bar{x}_1 : \text{gen2}_A(l_1)). \{l = E_1\}\} \text{ in } E$ NEED TCHECK
$\overline{\Gamma \vdash s[\bar{\alpha}] \rightarrow \bar{l} : \tau}$	$\frac{\Gamma, d \rightsquigarrow s[\bar{\alpha}_0].\alpha_1 : \{\text{accept} : \forall \alpha_1. s[\bar{\alpha}_0] \rightarrow \alpha_1\} \vdash e : \tau_* \Rightarrow E}{\Gamma \vdash \text{data } d \text{ from } s[\bar{\alpha}_0].\alpha_1 \text{ in } e : \tau_* \Rightarrow \text{let gen3}(l) = \dots \text{ in } E}$ NOT REVISED YET
$\overline{\Gamma \vdash d}$	$\frac{\overline{\Gamma, \bar{x}_1 : \bar{\tau}_1, \bar{x}_2 : d[\bar{\tau}] \vdash e_1 : d[\bar{\tau}] \Rightarrow E_1} \quad \Gamma, x : \bar{\tau}_1 \rightarrow \overline{d[\bar{\tau}]} \rightarrow d[\bar{\tau}] \vdash e : \tau_* \Rightarrow E}{\Gamma \vdash \text{let } x \ (\bar{x}_1 : \bar{\tau}_1) \ (\bar{x}_2 : d[\bar{\tau}]) : d[\bar{\tau}] = e_1 \text{ in } e : \tau_* \Rightarrow \text{let } x = [\text{gen4}(d)] E_1 \text{ in } E}$ NOT REVISED YET
	$\frac{\overline{\Gamma \vdash x \multimap \overline{s[\bar{\tau}]}} \quad \overline{\Gamma \vdash s[\bar{\alpha}]} \quad \overline{\Gamma \vdash e : \tau_0 \Rightarrow E}}{\Gamma \vdash e[\bar{\tau}] < \bar{x} > : \tau_* \Rightarrow E.\text{accept}[\&\bar{\tau}] (\text{merge}_s \ \bar{x})}$ NEED TCHECK

merge_s : the merge algebra for object algebra interface s .

$\text{merge}_s : \forall \overline{\alpha_A}. \forall \overline{\alpha_B}. s[\overline{\alpha_A}] \rightarrow s[\overline{\alpha_B}] \rightarrow s[\overline{\alpha_A} \& \alpha_B] = \Lambda \overline{\alpha_A}. \Lambda \overline{\alpha_B}. \lambda(\text{alg}_1 : s[\overline{\alpha_A}]). \lambda(\text{alg}_2 : s[\overline{\alpha_B}]). \overline{\{l = [\overline{\alpha_A} \& \alpha_B / \overline{\alpha}] \text{gen}(l)\}}$

$\text{gen}(l) : \lambda(\overline{x} : \dots). \text{alg}_1.\overline{x}, \text{alg}_2.\overline{x}$.

$\text{gen2}(l)$: get the type from context $\Gamma(s).l$.

$\text{gen3}(l)$: for each case l , generate an auxiliary function for building structures. Only consider those with return type α_1 in **data** d from $s[\overline{\alpha_0}].\alpha_1$ in e .

$[\text{gen4}(d)] : [\overline{l}[\overline{\tau}]/\overline{l}]$. Only when $d \rightsquigarrow s[\overline{\alpha_0}].\alpha_1$, l is a constructor in s , and $\text{gen3}(l)$ exists.

3 Auxiliary Rules for Expanding Types

4 Notes

The rules should support both special syntax for algebras and common syntax.

- **sig**: (1) in the environment; (2) as a type synonym.
- **alg**: (1) in the environment; (2) as a function.
- **data**: (1) in the environment; (2) as a type synonym.

Each datatype has only one sort. And instantiation only works for datatypes.

Type and consistency check need. Like in the declaration of an algebra, the label l should be consistent. And in the instantiation $e[\overline{\tau}]/\langle \overline{x} \rangle$, it requires $x \multimap s[\overline{\tau}]$ with the same s .