


# Ch 5: Matrix and Tree using List

Matrix is any doubly subscripted array of elements arranged in rows and columns.



$$A = \begin{bmatrix} a_{11}, \dots, a_{1n} \\ a_{21}, \dots, a_{2n} \\ \dots\dots\dots \\ a_{m1}, \dots, a_{mn} \end{bmatrix} = \{A_{ij}\}$$

**m** rows  
**n** columns  
**m X n** matrix

Row Vector:  $[1 \times n]$  matrix  $\rightarrow$

$$A = [a_1 a_2, \dots, a_n] = \{a_i\}$$

Column vector:  $[m \times 1]$  matrix  $\rightarrow$

$$A = \begin{bmatrix} a_1 \\ a_2 \\ \dots \\ a_m \end{bmatrix} = \{a_i\}$$

# Basic Matrix Operations

- Addition, Subtraction, Multiplication: creating new matrices (or functions)

$$\begin{bmatrix} a & b \\ c & d \end{bmatrix} + \begin{bmatrix} e & f \\ g & h \end{bmatrix} = \begin{bmatrix} a+e & b+f \\ c+g & d+h \end{bmatrix}$$

**Just add elements**

$$\begin{bmatrix} a & b \\ c & d \end{bmatrix} - \begin{bmatrix} e & f \\ g & h \end{bmatrix} = \begin{bmatrix} a-e & b-f \\ c-g & d-h \end{bmatrix}$$

**Just subtract elements**

$$\begin{bmatrix} a & b \\ c & d \end{bmatrix} \begin{bmatrix} e & f \\ g & h \end{bmatrix} = \begin{bmatrix} ae+bg & af+bh \\ ce+dg & cf+dh \end{bmatrix}$$

**Multiply each row  
by each column**

# Matrix Addition and Subtraction

## Addition

- Commutative:  $\mathbf{A} + \mathbf{B} = \mathbf{B} + \mathbf{A}$
- Associative:  $(\mathbf{A} + \mathbf{B}) + \mathbf{C} = \mathbf{A} + (\mathbf{B} + \mathbf{C})$

$$\mathbf{A} + \mathbf{B} = \begin{bmatrix} 2 & 4 \\ 2 & 5 \end{bmatrix} + \begin{bmatrix} 1 & 0 \\ 3 & 1 \end{bmatrix} = \begin{bmatrix} 2+1 & 4+0 \\ 2+3 & 5+1 \end{bmatrix} = \begin{bmatrix} 3 & 4 \\ 5 & 6 \end{bmatrix}$$

## Subtraction

- By adding a negative matrix

$$\mathbf{A} - \mathbf{B} = \begin{bmatrix} 2 & 4 \\ 5 & 3 \end{bmatrix} - \begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix} = \begin{bmatrix} 2 & 4 \\ 5 & 3 \end{bmatrix} + \begin{bmatrix} -1 & -2 \\ -3 & -4 \end{bmatrix} = \begin{bmatrix} 1 & 2 \\ 2 & -1 \end{bmatrix}$$

# Matrix Multiplication

$$A \times B = C$$

2 x 2 matrix

$$A = \begin{bmatrix} \underline{a_{11} \ a_{12}} \\ a_{21} \ a_{22} \end{bmatrix}$$

2 x 3 matrix

$$B = \begin{bmatrix} b_{11} & b_{12} & b_{13} \\ b_{21} & b_{22} & b_{23} \end{bmatrix}$$

$$C = \begin{bmatrix} \underline{a_{11}b_{11} + a_{12}b_{21}} & a_{11}b_{12} + a_{12}b_{22} & a_{11}b_{13} + a_{12}b_{23} \\ a_{21}b_{11} + a_{22}b_{21} & a_{21}b_{12} + a_{22}b_{22} & a_{21}b_{13} + a_{22}b_{23} \end{bmatrix}$$

2 x 3 matrix

**Square Matrix:** Same number of rows and columns

$$B = \begin{bmatrix} 5 & 4 & 7 \\ 3 & 6 & 1 \\ 2 & 1 & 3 \end{bmatrix}$$

**Identity Matrix:** Square matrix with ones on the diagonal and zeros elsewhere

$$I = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

Worked example  
 $A I_3 = A$  for a 3x3 matrix:

$$\begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix} \times \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix} = \begin{bmatrix} 1+0+0 & 0+2+0 & 0+0+3 \\ 4+0+0 & 0+5+0 & 0+0+6 \\ 7+0+0 & 0+8+0 & 0+0+9 \end{bmatrix}$$

# Two Dimensional Arrays

- Some data can be organized efficiently in a **table** (also called a **matrix** or **2-dimensional array**)
- Each cell is denoted with two subscripts, a row and column indicator

$$B[2][3] = 50$$

B	0	1	2	3	4
0	3	18	43	49	65
1	14	30	32	53	75
2	9	28	38	50	73
3	10	24	37	58	62
4	7	19	40	46	66

$$B = \begin{bmatrix} 3 & 18 & 43 & 49 & 65 \\ 14 & 30 & 32 & 53 & 75 \\ 9 & 28 & 38 & 50 & 73 \\ 10 & 24 & 37 & 58 & 62 \\ 7 & 19 & 40 & 46 & 66 \end{bmatrix}$$

# 2D Lists in Python

```
data = [ [1, 2, 3, 4],  
         [5, 6, 7, 8],  
         [9, 10, 11, 12]  
        ]
```

```
>>> data[0]
```

```
[1, 2, 3, 4]
```

```
>>> data[1][2]
```

```
7
```

```
>>> data[2][5] index error
```

data[0] → [1, 2, 3, 4]

data[1] → [5, 6, 7, 8]

data[2] → [9, 10, 11, 12]

	0	1	2	3
0	1	2	3	4
1	5	6	7	8
2	9	10	11	12

$data = \begin{bmatrix} 1 & 2 & 3 & 4 \\ 5 & 6 & 7 & 8 \\ 9 & 10 & 11 & 12 \end{bmatrix}$



# 2D List Example in Python

- Find the sum of all elements in a 2D array

```
def sum_matrix(table):
```

```
    sum = 0
```

```
    for row in range(0, len(table)):
```

```
        for col in range(0, len(table[row])):
```


```
            sum = sum + table[row][col]
```

```
    return sum
```

number of rows in the table



number of columns in the  
given row of the table



In a rectangular matrix,  
this number will be fixed so we  
could use a fixed number for row  
such as len(table[0])

# Tracing the Nested Loop

```
def sum_matrix(table):  
    sum = 0  
    for row in range(0, len(table)):  
        for col in range(0, len(table[row])):  
            sum = sum + table[row][col]  
    return sum
```

```
>>> table = [ [ 1, 2, 3, 4 ],  
               [ 5, 6, 7, 8 ],  
               [ 9, 10, 11, 12 ]  
             ]
```

```
>>> sum_matrix(table)
```

```
len(table) = 3  
len(table[row]) = 4 for every row
```

row	col	sum
0	0	1
0	1	3
0	2	6
0	3	10
1	0	15
1	1	21
1	2	28
1	3	36
2	0	45
2	1	55
2	2	66
2	3	78

# 2D Array Creation using List [1/2]

## Static Allocation

```
# create a 2d list with fixed values (static allocation)
a = [ [ 2, 3, 4 ] , [ 5, 6, 7 ] ]
print(a)
```

## Dynamic Allocation (1)

```
# Create a variable-sized 2d list
rows = 3
cols = 2

a=[]
for row in range(rows): a += [[0]*cols]

print("This IS ok.  At first:")
print("  a =", a)

a[0][0] = 42
print("And now see what happens after a[0][0]=42")
print("  a =", a)
```

$[0]*2 \rightarrow [0, 0]$

$[] + [ [0] ]*2 \rightarrow [ [0, 0] ]$

$[ [0, 0] ] + [ [0]*2 ] \rightarrow [ [0, 0], [0, 0] ]$

$[ [0, 0], [0, 0], [0, 0] ]$

# 2D Array Creation using List [2/2]

## Dynamic Allocation (2)

```
rows = 3
cols = 2

a = [ ([0] * cols) for row in range(rows) ]

print("This IS ok.  At first:")
print("  a =", a)

a[0][0] = 42
print("And now see what happens after a[0][0]=42")
print("  a =", a)
```

```
[ [0, 0],
  [0, 0],
  [0, 0] ]
```

# Manipulating 2D-Array made by List [1/3]

## Getting 2d List Dimensions

```
# Create an "arbitrary" 2d List
a = [ [ 2, 3, 5] , [ 1, 4, 7 ] ]
print("a = ", a)


# Now find its dimensions
rows = len(a)
cols = len(a[0])
print("rows =", rows)
print("cols =", cols)
```

a → [ [ 2, 3, 5],  
[ 1, 4, 7] ]

a[0] → [ 2, 3, 5]

a[1] → [ 1, 4, 7]

# Manipulating 2D-Array made by List [2/3]



Nested Looping  
over 2d Lists

```
# Create an "arbitrary" 2d List
a = [ [ 2, 3, 5] , [ 1, 4, 7 ] ]
print("Before: a =", a)

# Now find its dimensions
rows = len(a)
cols = len(a[0])

# And now loop over every element
# Here, we'll add one to each element,
# just to make a change we can easily see
for row in range(rows):
    for col in range(cols):
        # This code will be run rows*cols times, once for each
        # element in the 2d list
        a[row][col] += 1

# Finally, print the results
print("After: a =", a)
```

# Manipulating 2D-Array made by List [3/3]

## Accessing a whole row

```
# alias (not a copy!); cheap (no new list created)
a = [ [ 1, 2, 3 ] , [ 4, 5, 6 ] ]
row = 1
rowList = a[row]
print(rowList)
```

a → 

## Accessing a whole column

```
# copy (not an alias!); expensive (new list created)
a = [ [ 1, 2, 3 ] , [ 4, 5, 6 ] ]
col = 1
colList = [ ]
for i in range(len(a)):
    colList += [ a[i][col] ]
print(colList)
```

colList → 

# Manipulating 3D-Array made by List

# 2d lists do not really exist in Python.  
# They are just lists that happen to contain other lists as elements.  
# And so this can be done for "3d lists", or even "4d" or higher-dimensional lists.  
# And these can also be non-rectangular, of course!

3D Matrix

2D Matrix

1D Matrix

```
a = [ [ [ 1, 2 ],  
        [ 3, 4 ] ],  
       [ [ 5, 6, 7 ],  
         [ 8, 9 ] ],  
       [ [ 10 ] ] ]
```

a[0]

```
[ [ 1, 2 ],  
  [ 3, 4 ] ]
```

a[1]

```
[ [ 5, 6, 7 ],  
  [ 8, 9 ] ]
```

a[2]

```
[ [ 10 ] ]
```

a[0][0]

```
[ 1, 2 ]
```

a[0][1]

```
[ 3, 4 ]
```

a[1][0]

```
[ 5, 6, 7 ]
```

a[1][1]

```
[ 8, 9 ]
```

a[2][0]

```
[ 10 ]
```

```
for i in range(len(a)):  
    for j in range(len(a[i])):  
        for k in range(len(a[i][j])):  
            print("a[%d][%d][%d] = %d" % (i, j, k, a[i][j][k]))
```

a[0][0][0] = 1

a[0][0][1] = 2

.




.



# Better Ways for 2D Array, 3D Array,.....

- Array Module
- NumPy Module


# Tree Structure using Python List



# Trees

- A **tree** is a hierarchical data structure.
  - Every tree has a **node** called the root.
  - Each node can have 1 or more nodes as children.
  - A node that has no children is called a leaf.
- A common tree in computing is a **binary tree**.
  - A binary tree consists of nodes that have at most 2 children.
- Applications: data compression, file storage, game trees

# Binary Tree



The root contains the data value 84.

There are 4 leaves in this binary tree: nodes containing 13, 37, 50, 98.


There are 3 internal nodes in this binary tree: nodes containing 41, 96, 24

This binary tree has height 3 – considering root is at level 0,  
the maximum level among all nodes is 3


# Trees and Python List Representations



[ 3 , [ ], [ ] ]





[ Bob , [ John, [ ], [ ] ] ,  
[ Sam, [ ], [Jim, [ ], [ ] ] ] ]



[ Bob , [ John, [ ], [ ] ] , [ Sam, [ ], [ ] ] ]

# Binary Trees: Implementation

- One common implementation of binary trees uses nodes like a linked list does.
  - Instead of having a "next" pointer, each node has a "left" pointer and a "right" pointer.



[ 45, [ 31, [ 19, [ ], [ ] ], [ 38, [ ], [ ] ], [ 70, [ ], [ 86, [ ], [ ] ] ]

# List Representation for Matrix or Tree

- List 는 Python의 대표 Data Type 이라 너무나 응용범위가 넓어서....
- List 로 Matrix or Tree 같은 복잡한 Data Structure 도 표현은 하지만
- Matrix 에 대한 다양한 Linear Algebra 작업을 한다면....
- Tree 에서 특정값을 search 한다면.....
- Tree 에서 특정 Node의 손자 Node들을 알고 싶다면...