Full product range / 20 models

Solar street lighting

Five series: JZ split, road, community, rural and industrial. Compare the existing model specifications and request a project-specific quotation.

JZ Split Series	5
Road Series	5
Community Series	4
Rural Series	3
Industrial Series	3

Selection reference, not a final engineering specification. Images may be shared series references. Runtime assumes a confirmed dimming schedule and solar yield. Warranty, certificate coverage, temperature limits and final structural drawings must be confirmed for each model and order. CE/ RoHS marks do not replace model-specific documents; ISO 9001 concerns the manufacturer’s quality system.

Model comparison

Page	Model	LED	Battery
3	JZ-HL0001	60 W	LiFePO4 · 3.2 V / 60 Ah · 192 Wh
5	JZ-AZ0001	60 W	LiFePO4 · 3.2 V / 60 Ah · 192 Wh
7	JZ-HW0001	60 W	LiFePO4 · 3.2 V / 60 Ah · 192 Wh
9	JZ-BG0001	60 W	LiFePO4 · 3.2 V / 60 Ah · 192 Wh
11	JZ-XQ0001	60 W	LiFePO4 · 3.2 V / 60 Ah · 192 Wh
13	Falcon Pro 60W	60W	40Ah LiFePO4 · 512Wh
14	Falcon Pro 90W	90W	60Ah LiFePO4 · 768Wh
15	Classic Split Solar Street Light 8m / 60W	60 W	LiFePO4 · 3.2 V / 60 Ah
17	ALCA Split 120W	120W	80Ah LiFePO4 · 1024Wh
18	PV Series 150W	150W	100Ah LiFePO4 · 1280Wh
19	Classic Split Solar Street Light 6m / 60W	60 W	LiFePO4 · 3.2 V / 60 Ah
21	Leaf AIO 30W	30W	24Ah LiFePO4 · 307Wh
22	Leaf AIO 40W	40W	30Ah LiFePO4 · 384Wh
23	Leaf AIO 60W	60W	40Ah LiFePO4 · 512Wh
24	Wall & Pole-Mount Solar Street Light 60W	60 W	LiFePO4 · 3.2 V / 60 Ah
26	Kmini Rural 20W	20W	15Ah LiFePO4 · 192Wh
27	Kmini Rural 30W	30W	24Ah LiFePO4 · 307Wh
28	Nova Industrial 100W	100W	70Ah LiFePO4 · 896Wh
29	Rifle Industrial 120W	120W	80Ah LiFePO4 · 1024Wh
30	ALCA Industrial 150W	150W	100Ah LiFePO4 · 1280Wh

Conch-arm solar street light

JZ-HL0001 / JZ Split Series



Style reference photo; final supply follows the confirmed configuration.

jiazun6888.com/en/products/jz-hl0001

LED power	60 W
Luminous efficacy	100–120 lm/W
Color temperature	5700–6000 K
Protection	IP65 (LED) / IP67 (battery)
Battery	LiFePO4 · 3.2 V / 60 Ah · 192 Wh
Battery cycles	≥2,000 cycles (sheet reference; test conditions to confirm)
Panel efficiency	19–21%
LED lifetime reference	30,000 h (sheet reference)
Mounting height	6–8 m
Nightly reference	8–10 h/night stated; depends on a verified dimming profile
Rainy-day reference	5–7 rainy days stated; conditional, not at continuous 60 W

Conch-arm solar street light

jz-hl0001 — Specifications continued

Solar panel	Mono-Si · 80 W / 6 V
Panel dimensions	800 × 670 × 25 mm
Pole construction	Q235 · hot-dip galvanized + powder coated. 6 m: Ø60/130 × 2.0 mm; 8 m: Ø60/140 × 2.5 mm.
Base flange	6 m: 250 × 250 × 10 mm; 8 m: 270 × 270 × 10 mm
Foundation cage	6 m: 260 mm diagonal / M16 / ≥400 mm; 8 m: 280 mm / M18 / ≥500 mm.
Installation note	Foundation excavation requires local soil, rainfall and wind-load design. Intermediate heights need a separate structural drawing.

The supplied sheet states 8–10 h/night and 5–7 rainy days. These are conditional references, not 60 W full-output guarantees. A 3.2 V × 60 Ah battery stores 192 Wh: about 3.2 h at 60 W before losses. Confirm dimming, usable capacity and local solar yield before ordering.

Warranty and compliance documents are confirmed for the selected model in the quotation.

A-arm solar street light

JZ-AZ0001 / JZ Split Series



Style reference photo; final supply follows the confirmed configuration.

jiazun6888.com/en/products/jz-az0001

LED power	60 W
Luminous efficacy	100–120 lm/W
Color temperature	5700–6000 K
Protection	IP65 (LED) / IP67 (battery)
Battery	LiFePO4 · 3.2 V / 60 Ah · 192 Wh
Battery cycles	≥2,000 cycles (sheet reference; test conditions to confirm)
Panel efficiency	19–21%
LED lifetime reference	30,000 h (sheet reference)
Mounting height	6–8 m
Nightly reference	8–10 h/night stated; depends on a verified dimming profile
Rainy-day reference	5–7 rainy days stated; conditional, not at continuous 60 W

A-arm solar street light

jz-az0001 — Specifications continued

Solar panel	Mono-Si · 80 W / 6 V
Panel dimensions	800 × 670 × 25 mm
Pole construction	Q235 · hot-dip galvanized + powder coated. 6 m: Ø60/130 × 2.0 mm; 8 m: Ø60/140 × 2.5 mm.
Base flange	6 m: 250 × 250 × 10 mm; 8 m: 270 × 270 × 10 mm
Foundation cage	6 m: 260 mm diagonal / M16 / ≥400 mm; 8 m: 280 mm / M18 / ≥500 mm.
Installation note	Foundation excavation requires local soil, rainfall and wind-load design. Intermediate heights need a separate structural drawing.

The supplied sheet states 8–10 h/night and 5–7 rainy days. These are conditional references, not 60 W full-output guarantees. A 3.2 V × 60 Ah battery stores 192 Wh: about 3.2 h at 60 W before losses. Confirm dimming, usable capacity and local solar yield before ordering.

Warranty and compliance documents are confirmed for the selected model in the quotation.

Meander-pattern solar street light

JZ-HW0001 / JZ Split Series



Style reference photo; final supply follows the confirmed configuration.

jiazun6888.com/en/products/jz-hw0001

LED power	60 W
Luminous efficacy	100–120 lm/W
Color temperature	5700–6000 K
Protection	IP65 (LED) / IP67 (battery)
Battery	LiFePO4 · 3.2 V / 60 Ah · 192 Wh
Battery cycles	≥2,000 cycles (sheet reference; test conditions to confirm)
Panel efficiency	19–21%
LED lifetime reference	30,000 h (sheet reference)
Mounting height	6–8 m
Nightly reference	8–10 h/night stated; depends on a verified dimming profile
Rainy-day reference	5–7 rainy days stated; conditional, not at continuous 60 W

Meander-pattern solar street light

jz-hw0001 — Specifications continued

Solar panel	Mono-Si · 80 W / 6 V (reference configuration)
Panel dimensions	800 × 670 × 25 mm
Pole construction	Meander-pattern pole; section, material, wall thickness and foundation to be agreed.

The supplied sheet states 8–10 h/night and 5–7 rainy days. These are conditional references, not 60 W full-output guarantees. A 3.2 V × 60 Ah battery stores 192 Wh: about 3.2 h at 60 W before losses. Confirm dimming, usable capacity and local solar yield before ordering.

Warranty and compliance documents are confirmed for the selected model in the quotation.

Clamp-mounted solar street light

JZ-BG0001 / JZ Split Series



Installation reference cropped from the supplied configuration sheet.

jiazun6888.com/en/products/jz-bg0001

LED power	60 W
Luminous efficacy	100–120 lm/W
Color temperature	5700–6000 K
Protection	IP65 (LED) / IP67 (battery)
Battery	LiFePO4 · 3.2 V / 60 Ah · 192 Wh
Battery cycles	≥2,000 cycles (sheet reference; test conditions to confirm)
Panel efficiency	19–21%
LED lifetime reference	30,000 h (sheet reference)
Mounting height	6–8 m (installation height)
Nightly reference	8–10 h/night stated; depends on a verified dimming profile
Rainy-day reference	5–7 rainy days stated; conditional, not at continuous 60 W

Clamp-mounted solar street light

jz-bg0001 — Specifications continued


Solar panel	Mono-Si · 60 W / 6 V
Panel dimensions	600 × 670 × 25 mm
Mounting arm	1,200 mm · Q235 galvanized + powder coated · Ø50 × 1.3 mm

The supplied sheet states 8–10 h/night and 5–7 rainy days. These are conditional references, not 60 W full-output guarantees. A 3.2 V × 60 Ah battery stores 192 Wh: about 3.2 h at 60 W before losses. Confirm dimming, usable capacity and local solar yield before ordering.

Warranty and compliance documents are confirmed for the selected model in the quotation.

Wall-mounted solar street light

JZ-XQ0001 / JZ Split Series



Style reference photo; final supply follows the confirmed configuration.

jiazun6888.com/en/products/jz-xq0001

LED power	60 W
Luminous efficacy	100–120 lm/W
Color temperature	5700–6000 K
Protection	IP65 (LED) / IP67 (battery)
Battery	LiFePO4 · 3.2 V / 60 Ah · 192 Wh
Battery cycles	≥2,000 cycles (sheet reference; test conditions to confirm)
Panel efficiency	19–21%
LED lifetime reference	30,000 h (sheet reference)
Mounting height	6–8 m (installation height)
Nightly reference	8–10 h/night stated; depends on a verified dimming profile
Rainy-day reference	5–7 rainy days stated; conditional, not at continuous 60 W

Wall-mounted solar street light

jz-xq0001 — Specifications continued

Solar panel	Mono-Si · 60 W / 6 V
Panel dimensions	600 × 670 × 25 mm
Mounting arm	1,200 mm · Q235 galvanized + powder coated · Ø50 × 1.3 mm

The supplied sheet states 8–10 h/night and 5–7 rainy days. These are conditional references, not 60 W full-output guarantees. A 3.2 V × 60 Ah battery stores 192 Wh: about 3.2 h at 60 W before losses. Confirm dimming, usable capacity and local solar yield before ordering.

Warranty and compliance documents are confirmed for the selected model in the quotation.

Falcon Pro 60W

falcon-pro-60w / Road Series



Model appearance reference; final configuration follows the quotation.

jiazun6888.com/en/products/falcon-pro-60w

LED power	60W
Solar panel	100W Monocrystalline 23%
Battery	40Ah LiFePO4 · 512Wh
Luminous flux	9,600 lm
Runtime reference	12–14 hrs · 3 rainy days
Charging reference	6–8 hrs
Protection	IP66 / IK10
Color temperature	4000K / 5700K
Mounting height	8–10 m
Controller	MPPT
Motion sensor	Optional PIR

Runtime and rainy-day figures are conditional, not continuous full-power guarantees. Confirm usable battery capacity, dimming, temperature limits and worst-month solar yield. Component lifetimes are not warranty periods.

Warranty and compliance documents are confirmed for the selected model in the quotation.

Falcon Pro 90W

falcon-pro-90w / Road Series



Shared series appearance reference. Confirm the model housing and dimensions.

jiazun6888.com/en/products/falcon-pro-90w

LED power	90W
Solar panel	150W Monocrystalline 23%
Battery	60Ah LiFePO4 · 768Wh
Luminous flux	14,400 lm
Runtime reference	12–14 hrs · 3 rainy days
Charging reference	6–8 hrs
Protection	IP66 / IK10
Color temperature	4000K / 5700K
Mounting height	9–11 m
Controller	MPPT
Motion sensor	Optional PIR

Runtime and rainy-day figures are conditional, not continuous full-power guarantees. Confirm usable battery capacity, dimming, temperature limits and worst-month solar yield. Component lifetimes are not warranty periods.

Warranty and compliance documents are confirmed for the selected model in the quotation.

Classic Split Solar Street Light 8m / 60W

classic-split-8m-60w / Road Series



Model appearance reference; final configuration follows the quotation.

jiazun6888.com/en/products/classic-split-8m-60w

LED power	60 W
Luminous flux	6,000–7,200 lm
Color temperature	5700–6000 K
Protection	IP65 / IP67
Luminous efficacy	100–120 lm/W
Solar panel	Mono-Si · 80 W / 6 V
Panel dimensions	800 × 670 × 25 mm
Panel efficiency	19–21%
Battery	LiFePO4 · 3.2 V / 60 Ah
Battery cycles	≥2,000 cycles
Rainy-day reference	5–7 rainy days

Classic Split Solar Street Light 8m / 60W

classic-split-8m-60w — Specifications continued

Nightly reference	8–10 hours
LED lifetime reference	30,000 hours (source-stated)
Mounting height	8 m
Pole construction	7.7 m Q235 pole · hot-dip galvanized + powder coated · Ø60/140 × 2.5 mm
Mounting arm	A-arm / shell arm
Base flange	270 × 270 × 10 mm
Foundation cage	280 mm diagonal · M18 bolts · ≥500 mm height
Installation note	Size the foundation pit for local rainfall, soil and wind conditions

The supplied sheet states 8–10 h/night and 5–7 rainy days. These are conditional references, not 60 W full-output guarantees. A 3.2 V × 60 Ah battery stores 192 Wh: about 3.2 h at 60 W before losses. Confirm dimming, usable capacity and local solar yield before ordering.

Warranty and compliance documents are confirmed for the selected model in the quotation.

ALCA Split 120W

alca-split-120w / Road Series



Shared series appearance reference. Confirm the model housing and dimensions.

jiazun6888.com/en/products/alca-split-120w

LED power	120W
Solar panel	200W Monocrystalline 23%
Battery	80Ah LiFePO4 · 1024Wh
Luminous flux	19,200 lm
Runtime reference	12–14 hrs · 3 rainy days
Charging reference	6–8 hrs
Protection	IP66 / IK09
Color temperature	3000K–6500K
Mounting height	11–14 m
Controller	MPPT
Motion sensor	Built-in PIR

Runtime and rainy-day figures are conditional, not continuous full-power guarantees. Confirm usable battery capacity, dimming, temperature limits and worst-month solar yield. Component lifetimes are not warranty periods.

Warranty and compliance documents are confirmed for the selected model in the quotation.

PV Series 150W

pv-series-150w / Road Series



Shared series appearance reference. Confirm the model housing and dimensions.

jiazun6888.com/en/products/pv-series-150w

LED power	150W
Solar panel	250W Monocrystalline 23%
Battery	100Ah LiFePO4 · 1280Wh
Luminous flux	24,000 lm
Runtime reference	12–14 hrs · 3 rainy days
Charging reference	6–8 hrs
Protection	IP66 / IK10
Color temperature	4000K / 5700K
Mounting height	12–15 m
Controller	MPPT
Motion sensor	Built-in PIR

Runtime and rainy-day figures are conditional, not continuous full-power guarantees. Confirm usable battery capacity, dimming, temperature limits and worst-month solar yield. Component lifetimes are not warranty periods.

Warranty and compliance documents are confirmed for the selected model in the quotation.

Classic Split Solar Street Light 6m / 60W

classic-split-6m-60w / Community Series



Model appearance reference; final configuration follows the quotation.

jiazun6888.com/en/products/classic-split-6m-60w

LED power	60 W
Luminous flux	6,000–7,200 lm
Color temperature	5700–6000 K
Protection	IP65 / IP67
Luminous efficacy	100–120 lm/W
Solar panel	Mono-Si · 80 W / 6 V
Panel dimensions	800 × 670 × 25 mm
Panel efficiency	19–21%
Battery	LiFePO4 · 3.2 V / 60 Ah
Battery cycles	≥2,000 cycles
Rainy-day reference	5–7 rainy days

Classic Split Solar Street Light 6m / 60W

classic-split-6m-60w — Specifications continued

Nightly reference	8–10 hours
LED lifetime reference	30,000 hours (source-stated)
Mounting height	6 m
Pole construction	5.7 m Q235 pole · hot-dip galvanized + powder coated · Ø60/130 × 2.0 mm
Mounting arm	A-arm / shell arm
Base flange	250 × 250 × 10 mm
Foundation cage	260 mm diagonal · M16 bolts · ≥400 mm height
Installation note	Size the foundation pit for local rainfall, soil and wind conditions

The supplied sheet states 8–10 h/night and 5–7 rainy days. These are conditional references, not 60 W full-output guarantees. A 3.2 V × 60 Ah battery stores 192 Wh: about 3.2 h at 60 W before losses. Confirm dimming, usable capacity and local solar yield before ordering.

Warranty and compliance documents are confirmed for the selected model in the quotation.

Leaf AIO 30W

leaf-aio-30w / Community Series



Shared series appearance reference. Confirm the model housing and dimensions.

jiazun6888.com/en/products/leaf-aio-30w

LED power	30W
Solar panel	50W Monocrystalline
Battery	24Ah LiFePO4 · 307Wh
Luminous flux	4,800 lm
Runtime reference	10–12 hrs
Charging reference	5–7 hrs
Protection	IP66
Color temperature	4000K / 5700K
Mounting height	5–6 m
Controller	MPPT
Motion sensor	Optional PIR

Runtime and rainy-day figures are conditional, not continuous full-power guarantees. Confirm usable battery capacity, dimming, temperature limits and worst-month solar yield. Component lifetimes are not warranty periods.

Warranty and compliance documents are confirmed for the selected model in the quotation.

Leaf AIO 40W

leaf-aio-40w / Community Series



Shared series appearance reference. Confirm the model housing and dimensions.

jiazun6888.com/en/products/leaf-aio-40w

LED power	40W
Solar panel	70W Monocrystalline
Battery	30Ah LiFePO4 · 384Wh
Luminous flux	6,400 lm
Runtime reference	10–12 hrs
Charging reference	5–7 hrs
Protection	IP66
Color temperature	4000K / 5700K
Mounting height	6–7 m
Controller	MPPT
Motion sensor	Optional PIR

Runtime and rainy-day figures are conditional, not continuous full-power guarantees. Confirm usable battery capacity, dimming, temperature limits and worst-month solar yield. Component lifetimes are not warranty periods.

Warranty and compliance documents are confirmed for the selected model in the quotation.

Leaf AIO 60W

leaf-aio-60w / Community Series



Shared series appearance reference. Confirm the model housing and dimensions.

jiazun6888.com/en/products/leaf-aio-60w

LED power	60W
Solar panel	100W Monocrystalline
Battery	40Ah LiFePO4 · 512Wh
Luminous flux	9,600 lm
Runtime reference	10–12 hrs
Charging reference	5–7 hrs
Protection	IP66
Color temperature	4000K / 5700K
Mounting height	8–10 m
Controller	MPPT
Motion sensor	Built-in PIR

Runtime and rainy-day figures are conditional, not continuous full-power guarantees. Confirm usable battery capacity, dimming, temperature limits and worst-month solar yield. Component lifetimes are not warranty periods.

Warranty and compliance documents are confirmed for the selected model in the quotation.

Wall & Pole-Mount Solar Street Light 60W

wall-pole-mount-60w / Rural Series



Model appearance reference; final configuration follows the quotation.

jiazun6888.com/en/products/wall-pole-mount-60w

LED power	60 W
Luminous flux	6,000–7,200 lm
Color temperature	5700–6000 K
Protection	IP65 / IP67
Luminous efficacy	100–120 lm/W
Solar panel	Mono-Si · 60 W / 6 V
Panel dimensions	600 × 670 × 25 mm
Panel efficiency	19–21%
Battery	LiFePO4 · 3.2 V / 60 Ah
Battery cycles	≥2,000 cycles
Rainy-day reference	5–7 rainy days

Wall & Pole-Mount Solar Street Light 60W

wall-pole-mount-60w — Specifications continued

Nightly reference	8–10 hours
LED lifetime reference	30,000 hours (source-stated)
Mounting arm	1,200 mm · Q235 hot-dip galvanized steel · Ø50 × 1.3 mm

The supplied sheet states 8–10 h/night and 5–7 rainy days. These are conditional references, not 60 W full-output guarantees. A 3.2 V × 60 Ah battery stores 192 Wh: about 3.2 h at 60 W before losses. Confirm dimming, usable capacity and local solar yield before ordering.

Warranty and compliance documents are confirmed for the selected model in the quotation.

Kmini Rural 20W

kmini-rural-20w / Rural Series



Shared series appearance reference. Confirm the model housing and dimensions.

jiazun6888.com/en/products/kmini-rural-20w

LED power	20W
Solar panel	40W Monocrystalline
Battery	15Ah LiFePO4 · 192Wh
Luminous flux	3,000 lm
Runtime reference	10–12 hrs
Charging reference	5–6 hrs
Protection	IP65
Color temperature	5700K
Mounting height	4–5 m
Controller	PWM
Motion sensor	No

Runtime and rainy-day figures are conditional, not continuous full-power guarantees. Confirm usable battery capacity, dimming, temperature limits and worst-month solar yield. Component lifetimes are not warranty periods.

Warranty and compliance documents are confirmed for the selected model in the quotation.

Kmini Rural 30W

kmini-rural-30w / Rural Series



Shared series appearance reference. Confirm the model housing and dimensions.

jiazun6888.com/en/products/kmini-rural-30w

LED power	30W
Solar panel	50W Polycrystalline
Battery	24Ah LiFePO4 · 307Wh
Luminous flux	4,500 lm
Runtime reference	10–12 hrs
Charging reference	5–7 hrs
Protection	IP65
Color temperature	4000K / 5700K
Mounting height	5–6 m
Controller	MPPT
Motion sensor	Optional PIR

Runtime and rainy-day figures are conditional, not continuous full-power guarantees. Confirm usable battery capacity, dimming, temperature limits and worst-month solar yield. Component lifetimes are not warranty periods.

Warranty and compliance documents are confirmed for the selected model in the quotation.

Nova Industrial 100W

nova-industrial-100w / Industrial Series



Shared series appearance reference. Confirm the model housing and dimensions.

jiazun6888.com/en/products/nova-industrial-100w

LED power	100W
Solar panel	160W Monocrystalline 23%
Battery	70Ah LiFePO4 · 896Wh
Luminous flux	16,000 lm
Runtime reference	12–14 hrs · 3 rainy days
Charging reference	6–8 hrs
Protection	IP66 / IK10
Color temperature	4000K / 5700K
Mounting height	10–12 m
Controller	MPPT
Motion sensor	Built-in PIR

Runtime and rainy-day figures are conditional, not continuous full-power guarantees. Confirm usable battery capacity, dimming, temperature limits and worst-month solar yield. Component lifetimes are not warranty periods.

Warranty and compliance documents are confirmed for the selected model in the quotation.

Rifle Industrial 120W

rifle-industrial-120w / Industrial Series



Shared series appearance reference. Confirm the model housing and dimensions.

jiazun6888.com/en/products/rifle-industrial-120w

LED power	120W
Solar panel	200W Monocrystalline 23%
Battery	80Ah LiFePO4 · 1024Wh
Luminous flux	19,200 lm
Runtime reference	12–14 hrs · 3 rainy days
Charging reference	6–8 hrs
Protection	IP66 / IK10
Color temperature	4000K / 5700K
Mounting height	11–14 m
Controller	MPPT
Motion sensor	Built-in PIR + Remote

Runtime and rainy-day figures are conditional, not continuous full-power guarantees. Confirm usable battery capacity, dimming, temperature limits and worst-month solar yield. Component lifetimes are not warranty periods.

Warranty and compliance documents are confirmed for the selected model in the quotation.

ALCA Industrial 150W

alca-industrial-150w / Industrial Series



Shared series appearance reference. Confirm the model housing and dimensions.

jiazun6888.com/en/products/alca-industrial-150w

LED power	150W
Solar panel	250W Monocrystalline 23%
Battery	100Ah LiFePO4 · 1280Wh
Luminous flux	26,400 lm
Runtime reference	12–14 hrs · 3 rainy days
Charging reference	6–8 hrs
Protection	IP66 / IK09
Color temperature	3000K–6500K
Mounting height	12–16 m
Controller	MPPT
Motion sensor	Built-in PIR + Remote

Runtime and rainy-day figures are conditional, not continuous full-power guarantees. Confirm usable battery capacity, dimming, temperature limits and worst-month solar yield. Component lifetimes are not warranty periods.

Warranty and compliance documents are confirmed for the selected model in the quotation.