

OS PRSET1

Syed Ahmed Farrukh

Make grade

```
syedahmedfarrukh@Hydrasdi x + v
make: 'kernel/kernel' is up to date.
== Test sleep, no arguments == sleep, no arguments: OK (2.1s)
== Test sleep, returns == sleep, returns: OK (1.2s)
== Test sleep, makes syscall == sleep, makes syscall: OK (1.0s)
== Test sixfive_test == sixfive_test: OK (0.9s)
== Test sixfive_readme == sixfive_readme: OK (1.8s)
== Test sixfive_all == sixfive_all: OK (2.0s)
== Test memdump, examples == memdump, examples: OK (1.2s)
== Test memdump, format ii, S, p == memdump, format ii, S, p: OK (1.0s)
== Test find, in current directory == find, in current directory: OK (1.1s)
== Test find, in sub-directory == find, in sub-directory: OK (1.2s)
== Test find, recursive == find, recursive: OK (1.6s)
== Test exec == exec: OK (1.2s)
== Test exec, multiple args == exec, multiple args: OK (1.2s)
== Test exec, recursive find == exec, recursive find: OK (1.6s)
== Test time ==
time: FAIL
    Cannot read time.txt
Score: 130/131
```

a)

```
syedahmedfarrukh@Hydrasdi x + v
xv6 kernel is booting

hart 1 starting
hart 2 starting
init: starting sh
$ sleep 50
$ QEMU: Terminated
```

```
make: 'kernel/kernel' is up to date.
== Test sleep, no arguments == sleep, no arguments: OK (2.5s)
    (Old xv6.out.sleep_no_args failure log removed)
== Test sleep, returns == sleep, returns: OK (1.0s)
== Test sleep, makes syscall == sleep, makes syscall: OK (1.1s)
    (Old xv6.out.sleep failure log removed)
```

b)

```
syedahmedfarrukh@Hydrasdi X + v
xv6 kernel is booting
hart 2 starting
hart 1 starting
init: starting sh
$ sixfive sixfive.txt
5
100
18
5
$ QEMU: Terminated
```

```
make: 'kernel/kernel' is up to date.
== Test sixfive_test == sixfive_test: OK (2.3s)
    (Old xv6.out.sixfive_test failure log removed)
== Test sixfive_readme == sixfive_readme: OK (2.6s)
== Test sixfive_all == sixfive_all: OK (2.8s)
```

c)

```
syedahmedfarrukh@Hydrasdi X + v
xv6 kernel is booting
hart 1 starting
hart 2 starting
init: starting sh
$ memdump
Example 1:
51810
2025
Example 2:
a string
Example 3:
another
Example 4:
880
1819438967
100
z
xyzyzy
Example 5:
hello
w
o
r
l
d
$ QEMU: Terminated
```

```
make: 'kernel/kernel' is up to date.
== Test memdump, examples == memdump, examples: OK (2.4s)
== Test memdump, format ii, S, p == memdump, format ii, S, p: OK (1.3s)
```

```
syedahmedfarrukh@Hydrasdi X + v
xv6 kernel is booting
hart 1 starting
hart 2 starting
init: starting sh
$ echo deadc0de | memdump hhccc
25956
25697
c
0
d
e
$ echo deadc0de | memdump p
64616564
```

d)

```
syedahmedfarrukh@Hydrasdi X + v
xv6 kernel is booting
hart 2 starting
hart 1 starting
init: starting sh
$ echo > b
$ mkdir a
$ echo > a/b
$ mkdir a/aa
$ echo > a/aa/b
$ find . b
./b
./a/b
./a/aa/b
$ QEMU: Terminated
```

e)

```
syedahmedfarrukh@Hydrasdi x + v
init: starting sh
$ echo > b
$ mkdir a
$ echo > a/b
$ mkdir a/aa
$ echo > a/aa/b
$ find . b
./b
./a/b
./a/aa/b
$ find . b -exec echo hi
hi ./b
hi ./a/b
hi ./a/aa/b
$ QEMU: Terminated
```

```
syedahmedfarrukh@Hydrasdi x
xv6 kernel is booting

hart 1 starting
hart 2 starting
init: starting sh
$ sh < findtest.sh
$ $ $ $ $ hello
hello
hello
$ $ QEMU: Terminated
```

```
make: 'kernel/kernel' is up to date.
== Test find, in current directory == find, in current directory: OK (2.6s)
== Test find, in sub-directory == find, in sub-directory: OK (1.1s)
== Test find, recursive == find, recursive: OK (1.6s)
== Test exec, recursive find == exec, recursive find: OK (1.8s)
```