

The diagram illustrates the electrical connections for a 123A-30M00 microcontroller. The power supply is +3.3 m2, and ground is GND. The microcontroller is labeled ZQ1. The pin list on the right includes: 2, 3.3V; 4, 3.3V; 12, 3.3V; 14, 3.3V; 16, 3.3V; 18, 3.3V; 70, 3.3V; 72, 3.3V; 74, 3.3V; 1, GND; 3, GND; 9, GND; 15, GND; 21, GND; 27, GND; 33, GND; 39, GND; 45, GND; 51, GND; 57, GND; 71, GND; 73, GND; 75, GND; M2, Корпус; S1, Корпус; S2, Корпус; 50, PERST; 52, CLKREQ; 54, PEWAKE; 49, PER_P_0; 47, PER_N_0; 43, PET_P_0; 41, PET_N_0; 37, PER_P_1; 35, PER_N_1; 31, PET_P_1; 29, PET_N_1; 25, PER_P_2; 23, PER_N_2; 19, PET_P_2; 17, PET_N_2; 13, PER_P_3; 11, PER_N_3; 7, PET_P_3; 5, PER_N_3; 38, DEVS LP; 53, REFCLK_P; 55, REFCLK_N; 10, LED; 69, PEDET; 68, SUSCLK.