

# Cryptography

Rosen Section 4.6

Tom Michoel

MNF130V2020 – Week 9

# Cryptography

- ▶ **Cryptography** is the subject of transforming information so that it cannot be easily recovered without special knowledge.

# Cryptography

- ▶ **Cryptography** is the subject of transforming information so that it cannot be easily recovered without special knowledge.
- ▶ **Encryption** is the process of making a message secret.

# Cryptography

- ▶ **Cryptography** is the subject of transforming information so that it cannot be easily recovered without special knowledge.
- ▶ **Encryption** is the process of making a message secret.
- ▶ **Decryption** is the process of determining the original message from the encrypted message.

# Cryptography

- ▶ **Cryptography** is the subject of transforming information so that it cannot be easily recovered without special knowledge.
- ▶ **Encryption** is the process of making a message secret.
- ▶ **Decryption** is the process of determining the original message from the encrypted message.
- ▶ Number theory is the basis of much of cryptography. Modern *ciphers* rely on *modular arithmetic* and the difficulty of the *prime factorization* problem.

# Shift cyphers

- ▶ A **shift cypher** shifts each letter  $k$  letters forward in the alphabet, sending the last  $k$  to the first  $k$ .

# Shift cyphers

- ▶ A **shift cypher** shifts each letter  $k$  letters forward in the alphabet, sending the last  $k$  to the first  $k$ .
- ▶ Mathematically it can be described as a function  $f$  on  $\mathbb{Z}_{26}$  (where each letter corresponds to an integer between 0 and 25) which maps  $n \in \mathbb{Z}_{26}$  to  $f(n) = (n + k) \bmod 26$ .

# Shift cyphers

- ▶ A **shift cypher** shifts each letter  $k$  letters forward in the alphabet, sending the last  $k$  to the first  $k$ .
- ▶ Mathematically it can be described as a function  $f$  on  $\mathbb{Z}_{26}$  (where each letter corresponds to an integer between 0 and 25) which maps  $n \in \mathbb{Z}_{26}$  to  $f(n) = (n + k) \bmod 26$ .
- ▶ If we know the *key*  $k$ , we can decrypt using the *inverse function*  $f^{-1}(n) = (n - k) \bmod 26$ .



# Shift cyphers

- ▶ A **shift cypher** shifts each letter  $k$  letters forward in the alphabet, sending the last  $k$  to the first  $k$ .
- ▶ Mathematically it can be described as a function  $f$  on  $\mathbb{Z}_{26}$  (where each letter corresponds to an integer between 0 and 25) which maps  $n \in \mathbb{Z}_{26}$  to  $f(n) = (n + k) \bmod 26$ .
- ▶ If we know the *key*  $k$ , we can decrypt using the *inverse function*  $f^{-1}(n) = (n - k) \bmod 26$ .

## Example

Julius Caesar made messages secret using a shift cypher with  $k = 3$ . For instance, to encrypt the message “THE ANSWER IS NO”, translate it to numbers, shift and translate back:

20	8	5	1	14	19	23	5	9	19	14	15
23	11	8	4	17	22	26	8	12	21	17	18

to obtain “WKH DQVZH LU QR”.

# Public vs. private key cryptography

- ▶ In **private key cryptography**, once you know an *encryption* key, you can quickly find the *decryption* key.

# Public vs. private key cryptography

- ▶ In **private key cryptography**, once you know an *encryption* key, you can quickly find the *decryption* key.
- ▶ In **public key cryptography**, knowing how to send encrypted messages does not help to decrypt them.

# Public vs. private key cryptography

- ▶ In **private key cryptography**, once you know an *encryption* key, you can quickly find the *decription* key.
- ▶ In **public key cryptography**, knowing how to send encrypted messages does not help to decrypt them.
- ▶ The **RSA cryptosystem** is a widely used *public key* cryptosystem.

# The RSA cryptosystem

- ▶ Each individual has a **public encryption key**  $(n, e)$ , and **private decryption key**  $d$ , where:

# The RSA cryptosystem

- ▶ Each individual has a **public encryption key**  $(n, e)$ , and **private decryption key**  $d$ , where:
  - ▶ The **modulus**  $n = pq$  is the product of two large primes  $p, q$ .

# The RSA cryptosystem

- ▶ Each individual has a **public encryption key**  $(n, e)$ , and **private decryption key**  $d$ , where:
  - ▶ The **modulus**  $n = pq$  is the product of two large primes  $p, q$ .
  - ▶ The **exponent**  $e$  is relatively prime to  $(p - 1)(q - 1)$ ,  
 $\gcd(e, (p - 1)(q - 1)) = 1$

# The RSA cryptosystem

- ▶ Each individual has a **public encryption key**  $(n, e)$ , and **private decryption key**  $d$ , where:
  - ▶ The **modulus**  $n = pq$  is the product of two large primes  $p, q$ .
  - ▶ The **exponent**  $e$  is relatively prime to  $(p - 1)(q - 1)$ ,  
 $\gcd(e, (p - 1)(q - 1)) = 1$
  - ▶ The **decryption key**  $d$  is an inverse of  $e$  modulo  $(p - 1)(q - 1)$ .
- ▶  $p$  and  $q$  can be found with relative ease using probabilistic primality tests, but factoring  $n$  into  $p$  and  $q$  is computationally infeasible.



# The RSA cryptosystem

- ▶ Each individual has a **public encryption key**  $(n, e)$ , and **private decryption key**  $d$ , where:
  - ▶ The **modulus**  $n = pq$  is the product of two large primes  $p, q$ .
  - ▶ The **exponent**  $e$  is relatively prime to  $(p - 1)(q - 1)$ ,  
 $\gcd(e, (p - 1)(q - 1)) = 1$
  - ▶ The **decryption key**  $d$  is an inverse of  $e$  modulo  $(p - 1)(q - 1)$ .
- ▶  $p$  and  $q$  can be found with relative ease using probabilistic primality tests, but factoring  $n$  into  $p$  and  $q$  is computationally infeasible.
- ▶ Messages *to* an individual are encrypted using that person's *public* encryption key.

# The RSA cryptosystem

- ▶ Each individual has a **public encryption key**  $(n, e)$ , and **private decryption key**  $d$ , where:
  - ▶ The **modulus**  $n = pq$  is the product of two large primes  $p, q$ .
  - ▶ The **exponent**  $e$  is relatively prime to  $(p - 1)(q - 1)$ ,  
 $\gcd(e, (p - 1)(q - 1)) = 1$
  - ▶ The **decryption key**  $d$  is an inverse of  $e$  modulo  $(p - 1)(q - 1)$ .
- ▶  $p$  and  $q$  can be found with relative ease using probabilistic primality tests, but factoring  $n$  into  $p$  and  $q$  is computationally infeasible.
- ▶ Messages *to* an individual are encrypted using that person's *public* encryption key.
- ▶ The current standard is to have keys of 2048 bits (617 digits) or primes with about 300 digits each.

# RSA in a nutshell

- ▶ A message  $m$  is encrypted using the encryption function

$$c = f(m) = m^e \bmod n$$

- ▶ An encrypted message  $c$  is decrypted using the decryption function

$$m = f^{-1}(c) = c^d \bmod n$$

# RSA encryption

- ▶ A message  $M$  is translated into strings of digits using the map

$$f : \{A, B, C, \dots, Z\} \rightarrow \{00, 01, 02, \dots, 25\}$$

and divided in blocks  $m_1, m_2, \dots, m_k$  each of length  $2N$ , where  $2N$  is the largest even integer such that  $\underbrace{2525 \dots 25}_{2N} \leq n$ .

# RSA encryption

- ▶ A message  $M$  is translated into strings of digits using the map

$$f : \{A, B, C, \dots, Z\} \rightarrow \{00, 01, 02, \dots, 25\}$$

and divided in blocks  $m_1, m_2, \dots, m_k$  each of length  $2N$ , where  $2N$  is the largest even integer such that  $\underbrace{2525 \dots 25}_{2N} \leq n$ .

- ▶ Each block  $m_i$  is encrypted using the function

$$c = f(m) = m^e \bmod n$$

## RSA decryption

- ▶ To decrypt an RSA encrypted message (recover  $m$  from  $c$ ), we use a **private decryption key**  $d$ , an inverse of  $e$  modulo  $(p-1)(q-1)$ .

# RSA decryption

- ▶ To decrypt an RSA encrypted message (recover  $m$  from  $c$ ), we use a **private decryption key**  $d$ , an inverse of  $e$  modulo  $(p-1)(q-1)$ .
- ▶ The decryption function is

$$m = f^{-1}(c) = c^d \bmod n$$

## RSA decryption

- ▶ To decrypt an RSA encrypted message (recover  $m$  from  $c$ ), we use a **private decryption key**  $d$ , an inverse of  $e$  modulo  $(p-1)(q-1)$ .
- ▶ The decryption function is

$$m = f^{-1}(c) = c^d \bmod n$$

- ▶ Decryption recovers the original message, if and only if

$$m = (m^e \bmod n)^d \bmod n$$



# RSA decryption

- ▶ To decrypt an RSA encrypted message (recover  $m$  from  $c$ ), we use a **private decryption key**  $d$ , an inverse of  $e$  modulo  $(p-1)(q-1)$ .
- ▶ The decryption function is

$$m = f^{-1}(c) = c^d \bmod n$$

- ▶ Decryption recovers the original message, if and only if

$$m = (m^e \bmod n)^d \bmod n$$

- ▶ That this result is true is based on the following results:
  - ▶ Existence of a decryption key
  - ▶ Fermat's little theorem
  - ▶ The Chinese remainder theorem

## Existence of a decryption key

- Recall that if integers  $a, m$  are relatively prime,  $\gcd(a, m) = 1$ , then there exists a unique inverse of  $a$  modulo  $m$ .

## Existence of a decryption key

- ▶ Recall that if integers  $a, m$  are relatively prime,  $\gcd(a, m) = 1$ , then there exists a unique inverse of  $a$  modulo  $m$ .
- ▶ By assumption, the exponent  $e$  is relative prime to  $(p - 1)(q - 1)$ . Hence an inverse  $d$  of  $e$  modulo  $(p - 1)(q - 1)$  exists.

## Existence of a decryption key

- ▶ Recall that if integers  $a, m$  are relatively prime,  $\gcd(a, m) = 1$ , then there exists a unique inverse of  $a$  modulo  $m$ .
- ▶ By assumption, the exponent  $e$  is relative prime to  $(p - 1)(q - 1)$ . Hence an inverse  $d$  of  $e$  modulo  $(p - 1)(q - 1)$  exists.
- ▶ Recall that this means

$$de \bmod (p - 1)(q - 1) = 1$$

and that there exists an integer  $k$  such that

$$de = 1 + k(p - 1)(q - 1)$$

## Existence of a decryption key

- ▶ Recall that if integers  $a, m$  are relatively prime,  $\gcd(a, m) = 1$ , then there exists a unique inverse of  $a$  modulo  $m$ .
- ▶ By assumption, the exponent  $e$  is relative prime to  $(p - 1)(q - 1)$ . Hence an inverse  $d$  of  $e$  modulo  $(p - 1)(q - 1)$  exists.
- ▶ Recall that this means

$$de \bmod (p - 1)(q - 1) = 1$$

and that there exists an integer  $k$  such that

$$de = 1 + k(p - 1)(q - 1)$$

- ▶ Hence we have

$$m^{de} = m(m^k)^{(p-1)(q-1)}$$

and

$$c^d \bmod n = (m^e)^d \bmod n = (m \bmod n)((m^k)^{(p-1)(q-1)} \bmod n) \bmod n$$

# Fermat's little theorem

## Theorem (Fermat's little theorem)

*If  $p$  is prime and  $a$  is an integer not divisible by  $p$  then*

$$a^{p-1} \equiv 1 \pmod{p}.$$

*Furthermore, for every integer  $a$  we have*

$$a^p \equiv a \pmod{p}.$$

# Fermat's little theorem

## Theorem (Fermat's little theorem)

*If  $p$  is prime and  $a$  is an integer not divisible by  $p$  then*

$$a^{p-1} \equiv 1 \pmod{p}.$$

*Furthermore, for every integer  $a$  we have*

$$a^p \equiv a \pmod{p}.$$

This theorem allows some modular exponentiations to be computed even more rapidly. Recall that we computed  $3^{67} \bmod 7 = 3$  by expressing 67 in its binary expansion. In fact, by Fermat's little theorem

$$3^{67} \bmod 7 = 3^{1+11 \cdot 6} \bmod 7 = (3 \bmod 7)((3^{11})^6 \bmod 7) = 3 \bmod 7 = 3$$

That  $3^{11}$  is not divisible by 7 follows from the fact that the *unique* prime number factorization of  $3^{11}$  is  $3 \cdot 3 \cdot \dots \cdot 3$  does not contain 7.

# RSA Decryption

- By Fermat's little theorem, we have

$$(m^k)^{(p-1)(q-1)} \equiv 1 \pmod{p}$$

$$(m^k)^{(p-1)(q-1)} \equiv 1 \pmod{q}$$



# RSA Decryption

- By Fermat's little theorem, we have

$$(m^k)^{(p-1)(q-1)} \equiv 1 \pmod{p}$$

$$(m^k)^{(p-1)(q-1)} \equiv 1 \pmod{q}$$

- Hence  $(m^k)^{(p-1)(q-1)}$  is a solution to the **system of linear congruences**

$$x \equiv 1 \pmod{p}$$

$$x \equiv 1 \pmod{q}$$

with  $\gcd(p, q) = 1$  (because  $p$  and  $q$  are primes).

# RSA Decryption

- By Fermat's little theorem, we have

$$(m^k)^{(p-1)(q-1)} \equiv 1 \pmod{p}$$

$$(m^k)^{(p-1)(q-1)} \equiv 1 \pmod{q}$$

- Hence  $(m^k)^{(p-1)(q-1)}$  is a solution to the **system of linear congruences**

$$x \equiv 1 \pmod{p}$$

$$x \equiv 1 \pmod{q}$$

with  $\gcd(p, q) = 1$  (because  $p$  and  $q$  are primes).

- By the Chinese remainder theorem,  $x \equiv 1 \pmod{pq}$ , and, using  $pq = n$ , we obtain

$$(m^k)^{(p-1)(q-1)} \equiv 1 \pmod{n}$$

► Hence

$$c^d \bmod n = (m \bmod n)((m^k)^{(p-1)(q-1)} \bmod n) \bmod n = m \bmod n = m$$

The last equality follows because the original message blocks  $m$  were constructed to be  $\leq n$ .

# Secure communication with RSA

- ▶ To **send** an encrypted message to your friend, use **her** public encryption key. She will be able to decrypt it using her private decryption key.

# Secure communication with RSA

- ▶ To **send** an encrypted message to your friend, use **her** public encryption key. She will be able to decrypt it using her private decryption key.
- ▶ To **receive** an encrypted message, share **your** public public encryption key. You will be able to decrypt it using your private decryption key.

## Digital signatures with RSA

Let your public key be  $(n, e)$  with private key  $d$ . To send a message  $M$  such that the recipient knows it came from you:

## Digital signatures with RSA

Let your public key be  $(n, e)$  with private key  $d$ . To send a message  $M$  such that the recipient knows it came from you:

- ▶ Divide  $M$  into integer blocks  $m_i$  such that  $0 \leq m_i \leq n$  for all  $i$ .

# Digital signatures with RSA

Let your public key be  $(n, e)$  with private key  $d$ . To send a message  $M$  such that the recipient knows it came from you:

- ▶ Divide  $M$  into integer blocks  $m_i$  such that  $0 \leq m_i \leq n$  for all  $i$ .
- ▶ Apply **your (private) decryption** function  $c = f^{-1}(m) = m^d \bmod n$  to each block.



# Digital signatures with RSA

Let your public key be  $(n, e)$  with private key  $d$ . To send a message  $M$  such that the recipient knows it came from you:

- ▶ Divide  $M$  into integer blocks  $m_i$  such that  $0 \leq m_i \leq n$  for all  $i$ .
- ▶ Apply **your (private) decryption** function  $c = f^{-1}(m) = m^d \bmod n$  to each block.
- ▶ The recipient applies **your (public) encryption** function  $f(c) = c^e \bmod n$  to the received message. By the same calculation as before

$$(m^d \bmod n)^e \bmod n = (m^{de}) \bmod n = m \bmod n = m$$

# Digital signatures with RSA

Let your public key be  $(n, e)$  with private key  $d$ . To send a message  $M$  such that the recipient knows it came from you:

- ▶ Divide  $M$  into integer blocks  $m_i$  such that  $0 \leq m_i \leq n$  for all  $i$ .
- ▶ Apply **your (private) decryption** function  $c = f^{-1}(m) = m^d \bmod n$  to each block.
- ▶ The recipient applies **your (public) encryption** function  $f(c) = c^e \bmod n$  to the received message. By the same calculation as before

$$(m^d \bmod n)^e \bmod n = (m^{de}) \bmod n = m \bmod n = m$$

- ▶ Only if the message was really sent by you (that is, if it was modified by *your* private decryption function), will this result in a readable message.

# Digital signatures with RSA

Let your public key be  $(n, e)$  with private key  $d$ . To send a message  $M$  such that the recipient knows it came from you:

- ▶ Divide  $M$  into integer blocks  $m_i$  such that  $0 \leq m_i \leq n$  for all  $i$ .
- ▶ Apply **your (private) decryption** function  $c = f^{-1}(m) = m^d \bmod n$  to each block.
- ▶ The recipient applies **your (public) encryption** function  $f(c) = c^e \bmod n$  to the received message. By the same calculation as before

$$(m^d \bmod n)^e \bmod n = (m^{de}) \bmod n = m \bmod n = m$$

- ▶ Only if the message was really sent by you (that is, if it was modified by *your* private decryption function), will this result in a readable message.
- ▶ The message itself is **not secure**: your public key is public and hence everyone will be able to reconstruct the original message.

## Encrypted messages with digital signatures

Let  $(n_s, e_s)$  and  $d_s$  be the public and private keys of the **sender**.

Let  $(n_r, e_r)$  and  $d_r$  be the public and private keys of the **recipient**.

To send an encrypted message  $M$  with the sender's digital signature:

# Encrypted messages with digital signatures

Let  $(n_s, e_s)$  and  $d_s$  be the public and private keys of the **sender**.

Let  $(n_r, e_r)$  and  $d_r$  be the public and private keys of the **recipient**.

To send an encrypted message  $M$  with the sender's digital signature:

- ▶ Divide  $M$  into integer blocks  $m_i$  such that  $0 \leq m_i \leq n$  for all  $i$ .

# Encrypted messages with digital signatures

Let  $(n_s, e_s)$  and  $d_s$  be the public and private keys of the **sender**.

Let  $(n_r, e_r)$  and  $d_r$  be the public and private keys of the **recipient**.

To send an encrypted message  $M$  with the sender's digital signature:

- ▶ Divide  $M$  into integer blocks  $m_i$  such that  $0 \leq m_i \leq n$  for all  $i$ .
- ▶ The sender applies her *private* decryption function  $c = m^{d_s} \bmod n_s$  to each block.

# Encrypted messages with digital signatures

Let  $(n_s, e_s)$  and  $d_s$  be the public and private keys of the **sender**.

Let  $(n_r, e_r)$  and  $d_r$  be the public and private keys of the **recipient**.

To send an encrypted message  $M$  with the sender's digital signature:

- ▶ Divide  $M$  into integer blocks  $m_i$  such that  $0 \leq m_i \leq n$  for all  $i$ .
- ▶ The sender applies her *private* decryption function  $c = m^{d_s} \bmod n_s$  to each block.
- ▶ The sender applies the recipient's *public* encryption function  $c' = c^{e_r} \bmod n_r$  to each block.

# Encrypted messages with digital signatures

Let  $(n_s, e_s)$  and  $d_s$  be the public and private keys of the **sender**.

Let  $(n_r, e_r)$  and  $d_r$  be the public and private keys of the **recipient**.

To send an encrypted message  $M$  with the sender's digital signature:

- ▶ Divide  $M$  into integer blocks  $m_i$  such that  $0 \leq m_i \leq n$  for all  $i$ .
- ▶ The sender applies her *private* decryption function  $c = m^{d_s} \bmod n_s$  to each block.
- ▶ The sender applies the recipient's *public* encryption function  $c' = c^{e_r} \bmod n_r$  to each block.
- ▶ The recipient first applies her *private* decryption and then the sender's *public* encryption function to reconstruct the message:

$$(c')^{d_r} \bmod n_r = c^{e_r d_r} \bmod n_r = c$$

$$c^{e_s} \bmod n_s = (m^{d_s e_s}) \bmod n = m$$



# Encrypted messages with digital signatures

Let  $(n_s, e_s)$  and  $d_s$  be the public and private keys of the **sender**.

Let  $(n_r, e_r)$  and  $d_r$  be the public and private keys of the **recipient**.

To send an encrypted message  $M$  with the sender's digital signature:

- ▶ Divide  $M$  into integer blocks  $m_i$  such that  $0 \leq m_i \leq n$  for all  $i$ .
- ▶ The sender applies her *private* decryption function  $c = m^{d_s} \bmod n_s$  to each block.
- ▶ The sender applies the recipient's *public* encryption function  $c' = c^{e_r} \bmod n_r$  to each block.
- ▶ The recipient first applies her *private* decryption and then the sender's *public* encryption function to reconstruct the message:

$$(c')^{d_r} \bmod n_r = c^{e_r d_r} \bmod n_r = c$$

$$c^{e_s} \bmod n_s = (m^{d_s e_s}) \bmod n = m$$

- ▶ Now only the recipient is able to reconstruct the message and she will still know it came from the sender.

# RSA DIY

- ▶ On unix(-like) systems, keys are stored in `~/.ssh/`:
  - ▶ `id_rsa`: private key (base64 format represented with ASCII characters)<sup>1</sup>
  - ▶ `id_rsa.pub`: public key
  - ▶ `known_hosts`: public keys of trusted servers
- ▶ `ssh-keygen` is the standard utility to generate RSA key pairs on unix(-like) systems.<sup>2</sup>
- ▶ OpenSSH offers more utilities to play with RSA keys<sup>3</sup>:
  - ▶ Generate 2048 bit keys:  
`> openssl genrsa -des3 -out private.pem 2048`
  - ▶ Extract public key:  
`> openssl rsa -in private.pem -outform PEM -pubout -out public.pem`
  - ▶ Extract public key modulus and exponent:  
`> openssl rsa -pubin -in public.pem -text -noout`

---

<sup>1</sup><https://www.cs.sfu.ca/~ggbaker/zju/math/int-alg.html>

<sup>2</sup><https://en.wikipedia.org/wiki/ssh-keygen>

<sup>3</sup><https://en.wikipedia.org/wiki/OpenSSH>