Compiler repeated work: profile, reduce, verify

Created-at: 2026-09-07 12:48 +02:00

Scope and ETA. Investigate cold source compilation, AST copying, reference resolution and repeated traversals. Approximately 45 minutes: 10 minutes instrumentation, 10 minutes profiles and baseline, 15 minutes implementation and correctness, 10 minutes repeat measurements and report. Generation, parsing, lowering, hashing, prepared compilation and destruction remain distinct measurement scopes. Do not remove validation or change hashes.

Authority and checkout. User requested optimization and investigation of repeated calls. Core fetched successfully at 12:42–12:45 using the existing origin with an SSH HostName override for 192.168.1.228; normal DNS failed. Base is freshly fetched origin/main f305ade; branch perf/compiler-repeated-work reuses the existing checkout. Former branch 2d43e82 has three unmerged diagnostic commits and is preserved. Untracked distributed-verification artifacts are preserved.

Discovery. Extend the existing interning Criterion benchmark and ModuleStore integration tests. ir_bench explicitly excludes parsing/lowering; ir_depth_probe measures depth failure, not compilation. Historical CPU optimization and CBOR reports contain no equivalent compiler profile. Ecosystem reader confirms Core owns compilation and is consumed by Graph, Transformation and Python.

Affected files. This four-format plan; `hymeko_core/benches/interning_bench.rs`; `hymeko_core/tests/mir` candidate production files `hymeko_core/src/module_store/module_store.rs`, `hymeko_core/src/ir/lower.rs` `hymeko_core/src/ir/canonical_hash.rs`, `hymeko_core/src/resolution/resolve.rs`; `reports/2026-09-07` and associated numerical, profile and figure evidence under `reports/compiler-repeated-work/`.

Core protection. User approved at the 2026-09-07 continuation: `APPROVED-CORE-EDIT: compiler-repeated` Instrumentation is allowlisted; candidate production files are lockdown-full. Apply the prepared root-AST/dependency-list borrow patch first, keeping imports, hashing and validation unchanged. Compare exact IR output (only timestamp normalized), then cold compilation and cached lookup. Preserve before/after binaries and PDBs. The user's runtime question also requires quoting the existing prepared Dijkstra results separately: compiler speedups are not traversal-kernel speedups.

Interfaces and invariants. Retain public signatures, cache behavior, resolution ambiguity/error order, import namespace order, IR contents and hash bytes. The legacy Merkle pass writes serialized decl_hash and is not redundant merely because another hash pass exists. No dependency changes. If borrowing ASTs requires an API change, keep the public owned-slice API and share the underlying lowering.

Measurement and tests. Criterion release, minimum five post-warmup iterations; save raw samples, median/IQR/worst. Windows samply CPU profile with symbols before selecting a hot spot. Read existing Graph campaign artifacts first. One large production-scale smoke precedes

repeated large runs. Record process peak working set, host and toolchain. Differential whole-IR checks normalize only metadata timestamps and pin both canonical and declaration hashes; import, constants, aliases, empty inputs and failure cases. Run relevant and workspace tests, fmt, clippy, symbols, duplication and preflight. Benchmark same machine and build settings.

Budgets and risk. Maximum 16 GiB RSS, 180 seconds per measured process; the existing 50,000-node source provides a quick discriminating workload, followed by the graph map512 source (30,032,345 bytes) if available through the existing harness. Target measurable reductions without greater than 10 percent time or memory regression. No claimed speedup without profile attribution. Nested imports and ambiguous reference paths can invalidate naive early return or memoization; tests must preserve them. Cloning may contribute memory rather than dominant CPU cost. Retaining cache entries may exchange speed for unbounded memory, so do not extend cache lifetime speculatively.


Rollback. Revert only this task's named changes. Preserve user files, previous branches, benchmark data and public hash/wire contracts.


Continuation, 2026-09-07 13:36. Under the same approved slug, strengthen source-to-IR compilation by reusing the canonical path table between validation and hashing. A crate-private CanonicalPaths view borrows the IR and owns just its derived paths; the IR cannot change during its lifetime. Public standalone APIs delegate to the same methods. Validation borrows index paths rather than cloning them, preserving the original index iteration and first-error order. Existing DerivedPathIndex also sorts a lookup table and is therefore inappropriate for this transient compile phase. Extend existing ModuleStore tests to compare compiled and standalone hashes, and to exercise namespace corruption. Frozen hashes and full serialized-IR goldens remain unchanged. Compare the already optimized root-borrow binary against this one change first; only then consider repeated leaf hashing. Expected additional work: 20 minutes including two bounded measurement pairs, tests, coverage and report. Retain the 50k baseline and add a larger existing frontend-generator scale if the smoke fits the declared 16 GiB / 180-second process budget. No second benchmark framework.

Continuation, 2026-09-07 13:59. Profile-guided compact Pruefer state: the resolved final profile puts 19.1 percent of compile-stack samples in prufer_from_forest. Replace its HashMap of dense declaration IDs with a dense vector and per-vertex adjacency lists with degree plus neighbor XOR. For degree one, the XOR equals the sole remaining neighbor, and removing an edge XORs out its endpoint. Preserve the existing heap key/order, labels, token sequence, super-root handling and hash domains. No public API or dependency change; same Core approval. Extend hymeko_core/tests/unified_ir/verification/frozen_hash.rs before production edits with deterministic chains, stars, balanced trees, multiple roots, empty and single-node forests, interleaved anonymous declarations and nondefault hash configuration. Freeze an aggregate digest against the current shared-path version before the rewrite. Reuse its archived binary as the immediate baseline. Measure cold compile and standalone canonical hashing at 50k, then cold compile at the already validated 500k scale in ABBA order; caps remain 180 seconds and 16 GiB per process. Capture a resolved after-profile, execute workspace tests, clippy and coverage, and append to the same report. ETA about 15 minutes: targeted parity/build 3, bounded A/B 6, profile plus checks/report 6. Roll back only this continuation if parity fails or investigation finds a regression. Existing root-borrow and shared-path edits remain.

Continuation, 2026-09-07 20:06. Remove duplicate annotation-value resolution in resolve_signed_refs under the existing `APPROVED-CORE-EDIT: compiler-repeated-work`. Fresh fetch confirms HEAD equals origin/main f305ade; preserve all earlier dirty changes. The exact current profile attributes

610 of 8070 compile samples to this function. Resolve the annotation once and clone its resolved value into the existing weights field; both owned wire fields must remain. Preserve list depth, absent versus empty, floating-point bits, symbol insertion order and first error. Extend existing test_ref_values.rs with mixed-value and error controls before editing production; extend the normalized-IR corpus for the real-parser path. Extend the existing Criterion generator with an explicit mixed-reference payload, retaining the numeric fixture and distinct benchmark identities. Archive matched binaries; compare lowering and cold compile in ABBA order, ten samples after warmup, with raw samples, IQR, worst and process peak. Existing 50k and 500k numeric fixture bounds apply; mixed 50k smoke must precede repeated runs. Each process capped at 180 seconds / 16 GiB. ETA approximately 20 minutes: tests and baseline 5, implementation and measured pairs 7, workspace gates and report/audit 8. No API or dependency changes. Bounded audit covers ModuleStore, intern/constant/reference resolution and lowering; record proven repeated work separately from unmeasured candidates and necessary semantic passes. Other candidates are not automatically bundled into this patch.





PERF-1 integration, 2026-09-09

Created-at: 2026-09-09T18:54:44+02:00. ETA: approximately 60–90 minutes, based on cached builds, existing 1-minute Core tests, 1–3 minute paired benchmark cells, SDK rebuild and browser tests; no complete historical campaign rerun. User approved saving the four-step strategy and executing step 1 in this turn. Existing authorization: `APPROVED-CORE-EDIT: compiler-repeated-work`; the course-module-compilation approval was the user's affirmative reply to that named scope, not a literal token. No new semantic or accelerator work.

Reuse the released course branches (Parser a528d98, Core 8623eb1) as bases. The original dirty performance checkouts remain the preserved source of the measured edits; independent integration worktrees hold the released control and candidate during A/B builds. Core main's independent sparse commit is not silently merged. Retire the temporary worktrees after evidence and publication.

Integrate only the existing grammar/string-scan optimizations, owned-record benchmark adapter, root borrowing/shared canonical paths, compact Pruefer state and single annotation-value resolution, plus their existing tests. Keep final course tests and diagnostics from the published branches. Affected additional paths: Parser grammar/lexer, existing benches/formats, tests/format_comparison.rs, scripts/format_*.py and their tests, Parser Cargo files and existing plan; Core canonical_hash.rs, module_store.rs, resolve.rs, existing interning benchmark and frozen/ref/module-store tests, Cargo pin/lock, generated SYMBOLS.md and docs/hymeko-platform-strategy.md; SDK Cargo pin/lock, existing changelog/package README and generated package. Root report exclusions remain. No Graph/Transformation/Tensor source change.

Use identical harnesses to build released control and integrated candidate. Run large-case smoke before bounded measurements: 50k linked/long-text parser and 50k mixed Core; 500k Core correctness/resource smoke where affordable. Minimum five post-warmup samples, retain raw values, median/IQR/worst and peak memory, binary/source/fixture hashes, affinity and environment. Reuse existing Campaign/ProcessRunner, Criterion and plotting tools. A/A or repeated control bounds ambient noise. More than ten percent stable regression requires investigation; inconclusive is not pass. Existing profiles justify the already-measured optimization mechanisms, not a fabricated combined speedup. No tests/builds overlap timed cells. Max process peak 16 GiB, timed process 180 seconds. Preserve full-IR and corpus hashes, signed-reference

diagnostics, source provenance; run Parser, Core, native/Node/browser/Worker parity and actual packed SDK installation. CPU tests only; no GPU performance claim.

Publication: provider before consumer, immutable Git revisions, one Core identity, no local path patches shipped; verify GitHub and LAN refs. Reuse current course branch without default-branch merge. Archive reports to Samba. Rollback uses previous published SHAs and retained original SDK; never reset or remove unrelated user work. PERF-2/3/4 remain planned at task completion.

Current full-IR characterization, 2026-09-13

Created-at: 2026-09-13 15:37 +02:00. ETA: about 15 minutes for existing target builds, correctness, bounded cells and report. User explicitly requests the full IR benchmark and the compiled library size. No circular-buffer remeasurement, profiler, production change or second compilation pipeline. Reuse ModuleStore::compile through the existing interning benchmark: 50k numeric and mixed sources, cold compile and cache hit reported separately. Reuse existing canonical-CBOR corpus encode/decode cells as independent boundary measurements; do not add phase medians to claim an end-to-end result. Ten or more post-warmup Criterion samples, median/IQR/worst of per-sample iteration averages, no per-call p99 claim. Run the exact public-facade corpus round-trip correctness test first. Use existing measure_peak_memory.ps1 Program mode with explicitly built targets, at most 16 GiB observed working set and 180 seconds per process. A single same-scale smoke precedes repeated cells. Build/check work never overlaps timing. Fresh release library build: default-empty features, no IPC/Arrow/GPU; report rlib versus cdylib/PDB and inspect DLL exports. A small DLL without callable Core exports is not the full linked Rust dependency footprint. Affected tracked files: this existing plan.tex and rebuilt plan.pdf only. Append results to reports/2026-09-07-compiler-repeated-work.md and reuse its compiler-repeated-work evidence directory for raw samples, resource records and plots. Preserve the other session's uncommitted circular-buffer bench, manifest and plan changes. Rollback: revert this plan addendum; no runtime migration.

Post-extraction audit and performance, 2026-09-23

Created-at: 2026-09-23 23:10 +02:00. ETA: 10–15 minutes including release builds. User explicitly requested duplication inspection followed by performance benchmarks. Reuse current dirty Core, Tensor and Nagare checkouts; no commits, worktrees, source backups or production optimizations. Fetch succeeded in all three. Pin the exact source hashes in the measurement record.

Audit the combined production sources of Core, WGPU, Tensor's numeric crate and Nagare HNN with the existing token detector, using the same scope for Git HEAD and current files. Report relocation separately from removed duplicates. Inspect the surviving clone groups and distinguish shared contract duplication from CPU/GPU strategies and different mathematical operators.

Artifact ledger: extend the existing interning benchmark with a semantic-digest characterization group (full digest, cached read, checked leaf update including clone/validation); reuse its deterministic source generator and public Core API. Verify equality against the full digest before timing. Reuse the existing CSR benchmark without copying its kernels or fixtures. Keep measurement opt-in. Write reports/2026-09-23-core-tensor-audit-performance.md and raw JSON/logs/plots under the existing reports/compiler-repeated-work directory, prefix cutover-. No new runner or plan directory. Existing peak-memory runner and Criterion own execution and sampling; no build/test overlaps measured cells.

Measure 50k-node cold/cached compilation and small/medium CSR SpMV/SpMM at 24 Rayon threads. Semantic digest uses a bounded 1000-node fixture with one editable value. Min-

imum 10 warmed-up samples; median, inclusive IQR and worst sample average (not per-call tail latency). Use historical same-host samples only where source/config match; absence is a new baseline, not evidence of speedup. Report OS, CPU, Rust version, flags, fixture digest and process peak working set. Userspace RSS guard: 16 GiB; stop an individual timed process at 180 seconds. A greater than 10 percent change is investigated before a causal claim. Retain raw results even if the host is noisy. CPU results only; no GPU/remote claims. Archive the report using the existing Samba synchronization tool. Rollback of benchmark-only changes uses Git; generated measurement evidence stays in reports.

Canonical incidence owner, 2026-09-24

Created-at: 2026-09-24 00:23 +02:00. ETA: 8–12 minutes for the focused refactor, cached targeted tests and report. User explicitly requested a struct/trait-oriented incidence API with hash() and bytes(); this authorizes the Core canonical hashing edit. No benchmark or dependency change.

Extend canonical_hash.rs with CanonicalIncidence, borrowing immutable IR, and a private output trait implemented by Vec¡u8¿ and the existing BLAKE3 hasher. One record iterator and encoder serve both methods. Normal hashing streams ordered edges. Duplicate paths or wrapped u16 positions require sorting lightweight records, using the same encoder without a byte arena or fallback pipeline. Preserve the existing byte order, domains and hash config. The existing public program-hash facade delegates to the owner; no old incidence free functions or forwarding aliases remain.

Affected files: canonical_hash.rs, existing frozen_hash.rs tests, generated SYMBOLS.md, this four-format plan and the existing Core/Tensor audit report. Fresh fetch of all Core remotes succeeded; HEAD 10138bf equals the task upstream and is three commits ahead of origin/main. Preserve all prior dirty work; no new checkout, backup, commit or publication.

Verification: fixed payload bytes and header-plus-payload digest equality; empty incidence, mixed signs, repeated targets, edge ordering, duplicate edge paths, u16 arc/slot wrapping and long path truncation. Existing frozen whole program vectors and generated forest/config corpus remain unchanged. Run only the affected correctness target, library lint and touched-file format checks. Worst input has many incidences with colliding paths: sorting holds record descriptors, never duplicate encoded payloads. No speed or memory improvement claim without measurement. Rollback is the scoped Git diff; no source backup. Archive the amended report through the existing shared report-sync tool.

Pruefer owner, 2026-09-24

Created-at: 2026-09-24 00:47 +02:00. ETA: 8–12 minutes for a focused source refactor, cached correctness checks and report. The user explicitly requests struct/trait orientation for Pruefer, authorizing the Core edit. Core fetch succeeded on origin and github; task HEAD/upstream remains 10138bf, three commits ahead of origin/main. Preserve existing uncommitted work.

Replace the tuple forest and free Pruefer orchestration with SkeletonForest methods, a prepared CanonicalPrufer owner, and PruferTraversal implementing Iterator. Store degree, neighbor XOR, live vertices and leaf heap in the traversal. Share the existing CanonicalSink trait for byte/hash output; one token iterator determines both. The canonical program hash uses this owner directly. No compatibility wrappers or duplicate algorithm remain. Preserve leaf priority (subtree hash, path tie, vertex), super-root handling, iterative subtree folding, token order, headers and malformed-input behavior.

Affected files: canonical_hash.rs, existing frozen_hash.rs tests, generated SYMBOLS.md, this four-format plan and the current Core/Tensor audit report. Update stale helper-name comments in coherence.rs and the existing hierarchy and test-oracle files; these edits do not change executable behavior. Extend fixed hash vectors with public byte/hash parity, empty/single/multiple

roots, interleaved anonymous declarations and generated forest shapes/configs. Exercise invalid cycle behavior explicitly. Run the frozen-hash and existing ordinary hierarchy correctness cases, excluding the ignored resource probe; library Clippy and touched-file formatting. No benchmark or dependency change. Worst-case deep trees remain heap-traversed; hashing streams fixed-size tokens, without constructing the full Pruefer payload. No measured speedup is claimed. Rollback is the scoped Git diff, preserving the preceding incidence change. No new checkout, source backup, commit or publication. Archive the final report.

Remaining canonical helpers, 2026-09-24

Created-at: 2026-09-24 00:57 +02:00. ETA: 6–10 minutes for the Core boundary; a public API migration may additionally require downstream checks. User requests remaining free functions to move into their responsible structs. Core fetched both remotes successfully; existing HEAD/upstream 10138bf remains.

CanonHashCfg owns domain-header initialization and chunk hashing. CanonicalPaths owns construction from IR, reverse paths for resolution-boundary validation and resolved strings. SkeletonForest owns its node-domain mapping. Reuse these owners from Pruefer, incidence, path-index construction and program hashing; remove their free helper bodies. No new struct solely to hold static utilities. The user explicitly approved public entrypoint removal with consumer migration. Promote CanonicalPaths::new/hash/validate; add DerivedPathIndex::new. Delete the three free public entrypoints and migrate Core, web, XR, Kawamirai, Transformation, Graph, the C++ Rust oracle and Nagare call sites. Keep manifest and lockfile pins unchanged; local verification uses command-line path patches. DerivedPathIndex is the existing owner for path-index construction. The XR check also reaches the existing simulator-xr-publish checkout. Migrate its callers and the primary simulator, Python binding and robot middleware found by the workspace-wide search. Exclude inactive alternative checkouts and the retired monorepo. Python's section-name adapter additionally requires the already-existing CanonicalIrCbor enum case to compile against current Core.

Discovery ledger: find canonical_hash.rs and existing consumer Rust files; grep the three public names and all private helpers across framework/Nagare; symbols confirm CanonHashCfg, CanonicalPaths, SkeletonForest and DerivedPathIndex already own these concerns; read implementations and callers. Verdict: EXTEND existing owners, remove free bodies, migrate callers in place.

Affected Core files: canonical_hash.rs and focused frozen/path/namespace tests; the existing plan bundle, symbol index and audit report. If public entrypoints are migrated, their Core consumers and downstream callers are also in scope. Keep canonical bytes, error variants and iteration behavior unchanged. Verify fixed hash vectors, byte/hash parity, namespace failures, duplicate paths and normal lookup behavior. No benchmark or dependency upgrade. Preserve prior edits; rollback is only this continuation's diff. No new checkout or source backup.

Namespace validator owner, 2026-09-24

Created-at: 2026-09-24 01:15 +02:00. ETA: 3–5 minutes. User requests a dedicated validator struct. Core fetch succeeded on both remotes; task HEAD 10138bf equals upstream and remains three commits ahead of main. Preserve the existing checkout and all preceding changes.

Discovery ledger: search IR/resolution for Validator and Validation owners finds none; CanonicalPaths in SYMBOLS.md and its implementation own the present validation. Read the method, namespace errors and all validation call sites. Verdict: EXTEND canonical_hash.rs with NamespaceValidator borrowing an existing CanonicalPaths, and MOVE validation plus reverse-index preparation into it. Remove CanonicalPaths::validate, with no forwarding method or free wrapper. Keep namespace errors and canonical hash bytes unchanged. Migrate lowering, CBOR vali-

dation and existing tests/bench call sites; retain shared path preparation. Run namespace/frozen-vector and lowering-boundary correctness tests, CBOR tests, compile the affected bench and run library lint. Update symbols and duplication gate, append the existing report and archive. No measurements or dependency edits. Rollback is the scoped diff; no backup or new checkout.

Subtree fold optimization, 2026-09-24

Created-at: 2026-09-24 01:21 +02:00. ETA: 4–6 minutes. User requests a more efficient subtree-hash implementation. Both Core remotes fetched; HEAD 10138bf still equals task upstream. Preserve current checkout and prior edits.

Discovery: SkeletonForest::new is the sole owner of parent/children/root construction; subtree_hashes is its sole fold. Each named declaration is inserted once under at most one valid named parent, or into roots. Therefore a root-reachable cycle or shared child is impossible even for malformed input; cycles and their descendants are disconnected from roots and retain zero hashes. Verdict: EXTEND the existing method, no additional module or production owner.

Build one root-first order, fold it backwards, and write directly into a dense zero-initialized HashId vector. Remove Enter/Exit frames, per-node Option state, on-stack flags and final conversion. Reuse one child-hash scratch buffer sized to maximum reachable fanout; skip it for leaves and single-child nodes. Use in-place unstable lexicographic sort: equal hashes contain identical bytes, so stability has no semantic effect. Cache the two configured named-leaf hashes within the fold, never across calls or configurations. Preserve all hash bytes and disconnected-component behavior. Complexity remains linear traversal plus sum of child-sort costs; no measured speedup is claimed.

Verify existing frozen vectors/configuration corpus, dense-ID permutations, deep/wide trees, mixed node/edge leaves, incidence multiplicity and malformed cycles. Extend the existing cycle regression to include a rooted component and a descendant of the disconnected cycle. Run only these correctness tests and library Clippy; no benchmark or profile was explicitly requested. Update the existing report, diagrams and symbol/duplication gates, then archive evidence. Rollback is the scoped diff; no backup, new checkout or dependency change.

Current Core performance, 2026-09-24

Created-at: 2026-09-24 01:30 +02:00. ETA: 3–5 minutes. The user explicitly asks about performance benchmarks. Measure the existing interning Criterion harness only: 50k canonical hash, cold/cached compile, and 1k full/cached digest plus checked leaf update. Reuse the existing memory runner and raw-sample summary machinery; no new benchmark implementation, source backup or worktree. Both Core remotes fetched, HEAD 10138bf equals the task upstream.

Discovery/cached evidence: the September 23 report has paired compiler/digest results. Its executable still exists and SHA256 matches 84f5f2261a8db3946b3d- afa17fd789ba589c038006d40f0ce7ec1d16c5de
Run it twice before rebuilding, then the current source twice, with explicit –bench, numeric 50k fixture, 24 Rayon threads, 1-second warmup and existing 10/20-sample groups. This compares the accumulated canonical refactors, not the isolated last subtree change. Verify source and canonical fixture hashes across binaries. Build time is excluded.

Budgets: each measured process below 16 GiB observed peak working set and 60 seconds wall time, expectation approximately 30 seconds from the prior 24.8-second five-cell run plus the hash cell. Preserve raw samples, report median/IQR/worst sample average and two-run drift. Memory polling uses the existing 100ms userspace cap; record its limits. Run sequentially without builds or tests during timing. The Windows/275HX interactive host has background GUI activity (largest observed process 0.156 CPU seconds per second); do not claim a quiet-host release gate or attribute every difference to the subtree fold. Investigate differences exceeding 10 percent within the measurement scope; profiling remains unrequested, and causal speedup claims require

separate evidence. Keep source/manifest/executable provenance, amend this report and archive results. No changes to production source, dependencies, public APIs or published pins.

Canonical hash batching, 2026-09-24

Created-at: 2026-09-24 01:45 +02:00. ETA: 6–10 minutes including archive. Continuation of the requested Core performance measurements and optimization. Owner: Core canonical hash; the existing user authorization covers this private implementation. Both remotes fetched; HEAD equals task upstream, three commits ahead of main. Preserve unrelated dirty work and all public contracts.

Discovery ledger: CanonicalSink is the sole output strategy in canonical_hash.rs; no buffered hash sink exists in Core. Extend that strategy with one private CanonicalHasher (configuration/header, fixed 16 KiB buffer, write, finish). Replace the direct Hasher sink, not the encoder. Existing frozen_hash tests, interning_bench, memory runner, report and plan bundle are reused. New measurement artifacts belong to reports/compiler-repeated-work with batching prefixes.

Evidence: the existing resolved Pruefer profile includes 463 Hasher::update samples, 255 ChunkState::update samples, and 371 path-string samples. These are historical inclusive observations, not current causal attribution. Current source issues per-field 1–32-byte updates. Test the bounded batching hypothesis against the just-measured current binary (canonical hash 78.743 ms); do not claim it explains the historical 6.6 percent regression without isolation. Batch the 24-byte header in CanonHashCfg and pass the existing sorted child-hash array as one contiguous slice. No alternate pipeline, dependencies or hash-version change. Fixed buffer memory is O(1), independent of model size.

Acceptance: identical frozen hashes, configured headers, long UTF-8 prefixes, wrapped incidence slots, empty streams, exact/full/partial buffer boundaries, and repeated calls. Existing targeted correctness gate and library Clippy. Two before and two after runs of only 50k canonical hash and cold compilation, existing warmup/sample counts, sequentially, no concurrent build or test. Expected 12–15 seconds per process, 40-second budget, 16 GiB observed peak cap. Record executable hashes, raw medians/IQR/worst, peak working set and fixture parity; interactive host remains a limitation. No fresh profiler run: reuse existing attribution and measure the scoped change. Retain only if parity passes and paired timings improve beyond ordinary run variation. Report and archive.

Remaining local duplication, 2026-09-24

Created-at: 2026-09-24 01:58 +02:00. ETA: 4–6 minutes including archive. User explicitly approved both identified cleanups and a fresh duplication audit. Owner: Core. Existing task checkout fetched both remotes; no upstream drift. Remove ir/common.rs and its module declaration; migrate the two integration-test consumers to SignedRefR::target/sign. Search found no external use in the framework/Nagare source trees. Public removal is intentional; no compatibility facade, replacement module, dependency change or extra checkout.

Discovery: TransactionAssembler already owns abandon and the seven staging-limit guards. Add one private staging_limit_exceeded method there; preserve guard order, counter updates, all diagnostic strings, committed version and replay position. Strengthen existing byte-limit, chunk-limit and superseded-drain tests to verify cleanup and preserved committed/sequence state. Run the assembler unit test module, the two migrated integration-test modules, library Clippy and fmt. No benchmark or profiler is requested for this cleanup.

Compare the same token detector and scope before/after: entry 462 marked runs, 9588 marked lines, 185 scanned files. Separate source and test contributions; inspect the remaining largest Core matches before calling any a duplicate pipeline. Existing candidate inventory, report, symbol index and diagrams are updated in place; report archived to the existing Samba destination.

Shared little-endian reader, 2026-09-24

Created-at: 2026-09-24 02:12 +02:00. ETA: 5–7 minutes including archive. User explicitly requests struct/trait/generic extraction of envelope readers. Owner: Core ir_stream. Both remotes fetched; existing task checkout is current. Discovery found no shared endian reader in common or ir_stream. New private reader.rs owns LittleEndianReader over a borrowed byte slice and a LittleEndianValue trait with associated fixed byte array. Generic read performs one shared bounds-checked copy, then statically dispatches the type conversion. A compact macro supplies primitive conversions for the four actual consumers: u16, u32, u64, f32. SnapshotVersion implements the same private trait by reusing its existing public conversion. No external reader API or dependency.

Migrate envelope fields, section-table fields, typed section-body copies and snapshot counters. Remove the old rd functions and per-version closure. Keep length/resource checks before reads/allocations, preserve exact validation order and wire errors; a private reader called outside validated bounds may panic, while public decoding must reject every truncated input. No pointer casts, unsafe code, dynamic dispatch or parallel decoding implementation.

Tests: independent known bytes at unaligned offsets and exact buffer ends; integer maxima, floating-point bit patterns, invalid offsets/short input; existing envelope/section/version/codec unit tests and stream-admission integration tests. Library Clippy, fmt, symbol-index and same-scope duplication checks. No performance measurement requested. Update existing candidate inventory/report, archive evidence.

Incidence and access surfaces; assembler cleanup, 2026-09-24

Created-at: 2026-09-24 02:39 +02:00. ETA: 6–8 minutes including archive. Owner: Core. User approved incidence consolidation and further access/assembler inspection. Both remotes fetched; existing task branch has no upstream drift. Discovery finds one numeric incidence implementation already in IncidenceIndexData. Share the 14 inherent delegating methods with a private declaration template, parameterized by data lifetime: owned results borrow self, view results retain the original data lifetime. Preserve Copy/two-pointer view layout, inherent call sites, operator arithmetic/order and all public signatures. A trait-only replacement would require consumer imports; a naive generic borrow shortens view lifetimes. No new runtime abstraction, dependency, module or compatibility API.

In access.rs share the four typed iteration/count/containment declaration families. Keep existing typed lookups and node/edge backlink checks, including the arc exception. Templates describe a repeated public surface; they do not create a second algorithm. Centralize transaction abandonment at public apply on every ResyncRequired outcome; retain diagnostic state captured before cleanup and replay bookkeeping rejection. Reset also reuses the existing abandon operation.

Extend existing incidence parity test with results surviving a short-lived view (slice, iterator, data reference and operator plan). Existing assembler test driver checks every resync preserves committed version/digest/sequence while clearing staged/draining state. Run focused incidence/access integration tests and assembler unit tests, library Clippy, formatting, symbol and duplication gates. No benchmark. Compare the same detector against 461 marked runs / 9546 marked lines / 185 files; separate declarations and test fixtures from actual pipeline duplication. Update existing inventory and report; archive to Samba.

Assembler test runner, 2026-09-24

Created-at: 2026-09-24 02:55 +02:00. ETA: 6–8 minutes: one test-only source refactor, targeted test compilation and archive. User requests runner structs for test duplication too. Owner: Core

ir_stream tests. Fresh fetch of both remotes; upstream 0/0. Existing dirty checkout and all production behavior preserved.

Extend existing tests_support with AssemblerRunner owning TransactionAssembler and the existing Producer. Move the free apply helper and its real wire validation and resync invariants into the runner. Reuse that path for step, expected outcome and ordinary complete-transaction execution. Migrate unit tests, ignored taxonomy probe and model tests; keep explicit bytes for exact/conflicting replay and expose producer controls for sequence gaps, stream changes and exhaustion. No alternate validator, test-only acceptance bypass, dependency or public production API.

Retain scenario-specific assertions and reference-model independence. Remove one byte-identical duplicate replay test only after confirming the surviving test covers all its assertions. Consolidate send/apply setup where bytes are used once; keep fixtures reused by replay tests. Preserve raw message fields/order for every migrated scenario. Existing correctness tests themselves prove runner behavior.

Affected: assembler.rs test modules, existing plan bundle, candidate inventory, report and generated symbol index if needed. Source is CORE-protected; the user's current runner request authorizes this test-only change. No production sections will change. Run the assembler unit and model-test modules (taxonomy stays ignored), Clippy for the library test target, rustfmt/diff checks, symbol and same-scope duplication gates. No performance measurement. Before: 459 marked runs / 9279 marked lines, assembler 663 of which 607 in test code. A smaller source count must not be bought by weakening tests or moving identical bodies into another file. Worst cases retained: u64 sequence boundary, zero replay capacity, staged/drain limits, randomized and exhaustive message streams. Restore only this task's patch through Git if needed; no backup checkout. Append report and archive to Samba.

WGPU preparation and declaration traversal, 2026-09-24

Created-at: 2026-09-24 03:08 +02:00. ETA: 10–15 minutes: eight backend builders, two AST passes, focused correctness and archive. User explicitly approved WGPU and traversal duplicate removal. Owner: Core checkout (hymeko_wgpu backend and hymeko_core resolution). Fresh origin/github fetch; upstream 0/0; reuse checkout. Existing roadmap invariants apply: canonical IR and numerical semantics unchanged.

WGPU: OperationFactory becomes the shared borrowed context for every builder, with one OperationLimits value replacing eight per-operation limit structs. Move typed uniform allocation/upload into that existing owner. GpuTensor owns its binding-entry construction. A private OperandCheck owns the operand diagnostic label and common required-value/shape-error construction. Remove six copies of each helper and the rotor-local uniform builder. Preserve each prepare method's validation order, diagnostics, kernel/layout binding positions, workgroup policy, resource usage flags, typestate and operand lifetimes. No new preparation-time collection, extra buffer, per-encode allocation, shader or numeric change.

AST: private DeclarationFields trait in existing sym_ast.rs exposes borrowed name/bases/optional children and mutable bases/children for NodeInner/EdgeInner. An AstInterner struct owns the interner borrow; one generic declaration method visits annotation/name/bases/body in existing order, with node/edge constructors preserving None versus Some(empty). ConstValues owns one generic mutable declaration walk. Arc ref-before-annotation substitution order remains explicit; error short-circuiting and constant arithmetic stay unchanged. Remove replaced free lowering/substitution helpers. Public entry points and parser dependency remain stable; no parser checkout modification or new module.

Files: eight operations/*.rs builders, operations/mod.rs, resources.rs; Core sym_ast.rs, resolution/intern_pass.rs and const_resolve.rs; focused tests in those owners as needed; existing plan/report/candidate/symbol artifacts. These source paths are CORE-protected; the current

user request authorizes them. No dependency, branch, worktree, commit or publication change. Rollback only this task's edits, preserving earlier dirty work.

Verification: Core intern/constant unit tests plus frozen identity/namespace integration fixtures; strengthen order/optional-body/error precedence checks. WGPU existing HSiKAN, entropy pooling, sparse scatter/highway/resident chain, rotor attention/spike tests plus targeted SpMM/activation preparation and dispatch cases. Inspect runners first; no profiling/benchmark opt-in. Execute GPU tests serially and require actual adapter execution when available. Clippy for both libraries, fmt/diff/symbol and duplicate gates. Before: 448 runs / 8996 marked lines / 185 files. No performance claim; shared buffers retain existing allocation sizes and ownership. Report actual results and any adapter skips; archive to Samba.

Incidence transpose row kernel, 2026-09-24

Created-at: 2026-09-24 03:24 +02:00. ETA: 6–8 minutes, one production owner, existing correctness fixtures, report and archive. User explicitly selected the remaining index/prepared-plan calculation overlap. Core-protected source changes are authorized by that request. Fresh origin/github fetch succeeded; upstream 0/0, existing dirty checkout retained. No dependency or public API change.

Introduce a private IncidenceCoefficients trait implemented by existing IncidenceView and IncidenceOperatorPlan. The live strategy resolves the canonical arc/ref coordinate; the prepared strategy reads its retained f64 coefficient. IncidenceIndexData owns one ordered transpose-row fold, shared by direct serial, prepared serial and Rayon applies. Share serial output traversal as well; preserve its initial zeroing, partial-write behavior and untouched output tail. Rayon keeps disjoint output partitioning and initial slice validation. Reuse the live coefficient strategy during preparation. Preserve coefficient multiplication and summation order, duplicate incidences, neutral references, signed zero and nonfinite policy. The direct path propagates nonfinite values; preparation rejects the first offending node in canonical node order. No dynamic dispatch, new retained array, per-apply allocation, IR copy, matrix materialization, reordered arithmetic or automatic cache. Bx and sparse topology construction remain in their existing owners.

Affected: incidence.rs, incidence_precompute_profile.rs correctness section, existing plan bundle, candidate inventory, symbol index if changed and report. Private trait and generic methods need no consumer migration. Restore only this task's patch if necessary, retaining earlier uncommitted work; no backup checkout.

Tests: reuse index/view/prepared and independent oracle fixtures. Add a compact runner covering cancellation-sensitive row order, duplicates, isolated nodes, empty graph/arc, repeat apply, output tails, overflow/neutral nonfinite coefficients and first-error node. Check bit parity including serial/Rayon; floating exceptional results by classification where NaN payloads are unspecified. Inspect aggregate selection first and keep ignored profiles disabled. Run incidence unit tests and specific incidence correctness integration filters, Clippy, scoped fmt/diff, symbol and duplication gates. Entry: 449 runs / 8543 marked lines / 185 files. No performance experiment or speed claim: current request is consolidation. Plan compile before source edit; write report and archive to Samba at completion.