WGPU forward kernels for canonical Slice 3

HyMeKo core/WGPU boundary

2026-09-06

1 Scope

Extend the existing `hymeko_wgpu` operation factory with two prepared forward kernels: sparse, single-head, untransported quaternion rotor attention, and star rotor-spike. They are the accelerated implementations consumed by a Nagare plan whose model authority remains the canonical `hymeko_core::Ir`. No parser, IR, graph, training, backward, CUDA, or temporal-spike semantics are added here.

2 Measured owners and restrictions

The CPU semantic owners already exist in Nagare. WGPU owns only independent WGSL execution. Attention consumes explicit CSR derived by Nagare from the canonical IR, four-wide query/key/value rows, one preferred quaternion, and one temperature. Rotor-spike consumes node rows, hyperedge centres, canonical membership rows, two projection columns, bin count, and concentration.

The restricted surface is intentional. Multi-head and frame-aware attention, backward, principal-plane extraction, spatial entropy and temporal membrane state require separate evidence and are rejected rather than approximated.

3 Implementation

Follow the established `HsikanBuilder`/`PreparedHsikan` pattern: typed builder validation, limit checks, pipeline/layout identity, uniform parameter buffer, sealed GPU operands, deterministic dispatch, and caller-owned output. Add no raw buffer escape and no host fallback.

4 Predeclared gates

1. CPU/WGPU full-output parity on non-vacuous irregular fixtures under $|g - c| \leq 5 \cdot 10^{-4} + 10^{-3}|c|$.
2. Empty attention neighbourhood produces the documented zero row; the double-cover sign control preserves attention output.
3. Invalid lengths, CSR, four-wide quaternion shape, bins, projections and device limits are rejected before dispatch.
4. Mutations of adjacency, preferred quaternion, concentration, incidence, or projection first alter the CPU result and then are detected by parity.
5. Prepared resources can be dispatched repeatedly without host re-upload; the output resource identity remains caller-owned.
6. Full core/WGPU tests, clippy and format gates pass before committing.

5 Stop conditions

Stop if the restricted kernels require changing canonical operator semantics, if a CPU fallback is needed to call the WGPU API, or if the bound fails at the first differing observable. CUDA is not introduced by this boundary.