Scope filter for template iteration (subsystem views)

Created 2026-10-07 00:18 CEST

Scope and estimate. Diagram templates iterate whole query results, so one view of a large model is too wide. Add a scope clause to {{`#each`}} that keeps only the matches reachable from a root along named edge results, so one template renders one view per subsystem (root as a config value). User decision 2026-10-07: engine extension *and* subsystem tags in the model, with a check that the two agree. ETA 90–120 minutes. No benchmark.

Syntax. {{`#each L [within|touching|outside S from R] [except X]`}}. `S`: comma-separated edge query labels, or the keyword `specializations`. `R`: comma-separated declaration names. In `S` and `R` an item `config:key` expands to the comma-separated config value, so one template renders every view (amended during implementation: several roots, configurable sources). `X`: a query label.

Semantics. The scope is the least set containing every declaration named `R` and closed under: for each match of an edge label in `S` with a + binding inside the scope, add its − binding targets (∼ is never followed); with `specializations`, add every declaration whose direct base is inside. A declaration is *inside* when it or an ancestor is in the set (ports go with their block). A node match qualifies for `within` when inside; an edge match when every ± binding is inside; `touching`: some ± binding is inside (node: inside); `outside`: not `within`. `except X` drops matches whose declaration is a match of `X`. Unknown labels and unresolved roots give an empty scope; a malformed clause is a template parse error.

Ownership. Query owns template semantics: `rewrite/template.rs` (parse and dispatch) and a new crate-private `rewrite/scope.rs` (closure, membership). No public symbol is added; `SYMBOLS.md` unchanged. Core read only (`Ir::parent`, `bases::bases`). View templates and the tag check live with the consumer model (`02_design/sze/halfarm/model/diagrams/`); upstreaming them as registered transforms is a separate decision.

Tests. Unit, in-memory model: `within` over composition (with ports via ancestors), `touching` vs `within` on a connector, `outside` as complement, `except`, `specializations`, multiple sources, `config:` root. Counter-tests: a ∼ binding is not followed; an unknown source label and an unresolved root render nothing; without the clause every match is emitted (the filter, not the query, removes them); a malformed clause is rejected. Consumer check: tags versus scope report empty; removing one tag and adding one wrong tag each produce exactly the expected line.

Budget and risks. Closure is O(iterations × edge matches), computed once per `#each` evaluation; specialization closure scans the declaration table per iteration. Literal roots are matched by name; a duplicated name yields all same-named declarations as roots (documented).

State and rollback. Checkout on `feat/material-lobes` with the uncommitted 2026-10-06 structural-template change and another worker's uncommitted files (not touched). No git writes from the Linux sandbox; the user branches and commits on Windows. Verification in the sandbox build copy. Rollback: delete `scope.rs`, revert the `template.rs` hunks.

