

“Arrays and Pointers”

Using Bloodshed Dev-C++

Heejin Park

Hanyang University



Introduction

- **Arrays**
- **Multidimensional Arrays**
- **Pointers and Arrays**
- **Functions, Arrays, and Pointers**
- **Pointer Operations**
- **Protecting Array Contents**
- **Pointers and Multidimensional Arrays**
- **Variable-Length Arrays (VLAs)**
- **Compound Literals**

Arrays

■ Arrays

- *declarations*

```
int main(void)
{
    float candy[365];      /* array of 365 floats */
    char code[12];         /* array of 12 chars  */
    int states[50];        /* array of 50 ints   */
    ...
}
```

Arrays

■ Initialization

```
int main(void)
{
    int powers[8] = {1,2,4,6,8,16,32,64}; /* ANSI only */
    ...
}
```

Arrays

■ The day_mon1.c Program

```
#include <stdio.h>
#define MONTHS 12


int main(void)
{
    int days[MONTHS] = {31,28,31,30,31,30,31,31,30,31,30,31};
    int index;

    for (index = 0; index < MONTHS; index++)
        printf("Month %d has %2d days.\n", index + 1,
               days[index]);

    return 0;
}
```

Arrays

■ The day_mon1.c Program



```
C:\WDev-Cpp\day_mon1.exe
Month 1 has 31 days.
Month 2 has 28 days.
Month 3 has 31 days.
Month 4 has 30 days.
Month 5 has 31 days.
Month 6 has 30 days.
Month 7 has 31 days.
Month 8 has 31 days.
Month 9 has 30 days.
Month 10 has 31 days.
Month 11 has 30 days.
Month 12 has 31 days.
계속하려면 아무 키나 누르십시오 . . .
```

Uninitialized array?

■ The no_data.c Program

```
#include <stdio.h>
#define SIZE 4


int main(void)
{
    int no_data[SIZE];  /* uninitialized array */
    int i;

    printf("%2s%14s\n",
           "i", "no_data[i]");
    for (i = 0; i < SIZE; i++)
        printf("%2d%14d\n", i, no_data[i]);

    return 0;
}
```

Uninitialized array?

■ The no_data.c Program



```
C:\WDev-CppW\no_data.exe
i    no_data[i]
0    2008985261
1    3014768
2    7864421
3    2293672
계속하려면 아무 키나 누르십시오 . . .
```


Partially initialized array

■ The somedata.c Program

```
#include <stdio.h>
#define SIZE 4


int main(void)
{
    int some_data[SIZE] = {1492, 1066};
    int i;

    printf("%2s%14s\n",
           "i", "some_data[i]");
    for (i = 0; i < SIZE; i++)
        printf("%2d%14d\n", i, some_data[i]);

    return 0;
}
```

Partially initialized array

■ The somedata.c Program



```
C:\WDev-Cpp\W\somedata.exe
i  some_data[i]
0      1492
1      1066
2         0
3         0
계속하려면 아무 키나 누르십시오 . . .
```

Omitting Array Size

■ The day_mon2.c Program

```
#include <stdio.h>


int main(void)
{
    const int days[] = {31, 28, 31, 30, 31, 30, 31, 31, 30, 31};
    int index;

    for (index = 0; index < sizeof days / sizeof days[0]; index++)
        printf("Month %2d has %d days.\n", index + 1,
               days[index]);

    return 0;
}
```

Omitting Array Size

■ The day_mon2.c Program



A screenshot of a Windows command window titled "C:\WDev-Cpp\Wday_mon2.exe". The window has a black background with white text. It displays the output of a program that lists the number of days in each month. The output is as follows:

```
Month 1 has 31 days.  
Month 2 has 28 days.  
Month 3 has 31 days.  
Month 4 has 30 days.  
Month 5 has 31 days.  
Month 6 has 30 days.  
Month 7 has 31 days.  
Month 8 has 31 days.  
Month 9 has 30 days.  
Month 10 has 31 days.  
계속하려면 아무 키나 누르십시오 . . .
```

Designated Initializers

■ Designated Initializers (C99)

- C99 has added a new capability: **designated initializers**.
- With traditional C initialization syntax, you also have to initialize every element preceding the last one:

```
int arr[6] = {0,0,0,0,0,212}; // traditional syntax
```

- With C99, you can use an index in brackets in the initialization list to specify a particular element:

```
int arr[6] = {[5] = 212}; // initialize arr[5] to 212
```

C99?

- **Use clang instead of gcc**
- **Use clang++ instead of g++**

Designated Initializers

■ The designate.c Program

```
#include <stdio.h>
#define MONTHS 12


int main(void)
{
    int days[MONTHS] = {31, 28, [4] = 31, 30, 31, [1] = 29};
    int i;

    for (i = 0; i < MONTHS; i++)
        printf("%2d  %d\n", i + 1, days[i]);

    return 0;
}
```

Designated Initializers

■ The designate.c Program



```
C:\WDev-Cpp\Wdesignate.exe
1 31
2 29
3 0
4 0
5 31
6 30
7 31
8 0
9 0
10 0
11 0
12 0
계속하려면 아무 키나 누르십시오 . . .
```


•Assigning Array Values

- Allowed
 - Yaks[0]=3;
- Assignments that are not allowed (unlike python):

```
#define SIZE 5
int main(void)
{
    int oxen[SIZE] = {5,3,2,8};           /* ok here      */
    int yaks[SIZE];

    yaks = oxen;                           /* not allowed */
    yaks[SIZE] = oxen[SIZE];               /* invalid     */
    yaks[SIZE] = {5,3,2,8};               /* doesn't work */
}
```

Index out of bound

■ The bounds.c Program

```
#include <stdio.h>
#define SIZE 4

int main(void)
{
    int value1 = 44;
    int arr[SIZE];
    int value2 = 88;
    int i;


    printf("value1 = %d, value2 = %d\n", value1, value2);
    for (i = -1; i <= SIZE; i++)
        arr[i] = 2 * i + 1;

    for (i = -1; i < 7; i++)
        printf("%2d  %d\n", i , arr[i]);
    printf("value1 = %d, value2 = %d\n", value1, value2);

    return 0;
}
```

Index out of bound

■ The bounds.c Program



```
C:\WDev-Cpp\Wbounds.exe
value1 = 44, value2 = 88
-1  -1
0   1
1   3
2   5
3   7
4   9
5   5
6  1245120
value1 = -1, value2 = 9
계속하려면 아무 키나 누르십시오 . . .
```

• Specifying an Array Size


- A `sizeof` expression is considered an integer constant, but a `const` value isn't.
- Also, the value of the expression must be greater than 0:

```
int n = 5;
int m = 8;
float a1[5];           // yes
float a2[5*2 + 1];     // yes
float a3[sizeof(int) + 1]; // yes
float a4[-4];          // no, size must be > 0
float a5[0];           // no, size must be > 0
float a6[2.5];         // no, size must be an integer
float a7[(int)2.5];    // yes, typecast float to int constant
float a8[n];           // not allowed before C99
float a9[m];           // not allowed before C99
```

Multidimensional Arrays


```
float rain[5][12]; // array of 5 arrays of 12 floats
```

Two-dimensional array



Multidimensional Arrays

■ The rain.c Program



```
C:\WDev-Cpp\Wrain.exe

YEAR      RAINFALL  <inches>
2000              32.4
2001              37.9
2002              49.8
2003              44.0
2004              32.9

The yearly average is 39.4 inches.

MONTHLY AVERAGES:

  Jan  Feb  Mar  Apr  May  Jun  Jul  Aug  Sep  Oct  Nov  Dec
  7.3  7.3  4.9  3.0  2.3  0.6  1.2  0.3  0.5  1.7  3.6  6.7
계속하려면 아무 키나 누르십시오 . . .
```

Multidimensional Arrays

■ The rain.c Program(1/2)

```
#include <stdio.h>
#define MONTHS 12    // number of months in a year
#define YEARS 5      // number of years of data

int main(void)
{
    // initializing rainfall data for 2000 - 2004
    const float rain[YEARS][MONTHS] =
    {
        {4.3,4.3,4.3,3.0,2.0,1.2,0.2,0.2,0.4,2.4,3.5,6.6},
        {8.5,8.2,1.2,1.6,2.4,0.0,5.2,0.9,0.3,0.9,1.4,7.3},
        {9.1,8.5,6.7,4.3,2.1,0.8,0.2,0.2,1.1,2.3,6.1,8.4},
        {7.2,9.9,8.4,3.3,1.2,0.8,0.4,0.0,0.6,1.7,4.3,6.2},
        {7.6,5.6,3.8,2.8,3.8,0.2,0.0,0.0,0.0,1.3,2.6,5.2}
    };

    int year, month;
    float subtot, total;

    printf(" YEAR      RAINFALL  (inches)\n");
```

Multidimensional Arrays


■ The rain.c Program(2/2)

```
for (year = 0, total = 0; year < YEARS; year++)
{
    for (month = 0, subtot = 0; month < MONTHS; month++)
        subtot += rain[year][month];
    printf("%5d %15.1f\n", 2000 + year, subtot);
    total += subtot;
}
printf("\nThe yearly average is %.1f inches.\n\n",
       total/YEARS);
printf("MONTHLY AVERAGES:\n\n");
printf(" Jan  Feb  Mar  Apr  May  Jun  Jul  Aug  Sep  Oct ");
printf(" Nov  Dec\n");


for (month = 0; month < MONTHS; month++)
{
    // for each month, sum rainfall over years
    for (year = 0, subtot = 0; year < YEARS; year++)
        subtot += rain[year][month];
    printf("%4.1f ", subtot/YEARS);
}
printf("\n");
return 0;
}
```


Multidimensional Arrays

■ Two methods of initializing an array



New:
`int sq[2][3] = {`
 `{5,6},`
 `{7,8}`
 `};`



`int sq[2][3]={5,6,7, 8};`

Multidimensional Arrays

■ More Dimensions

- ```
int box[10][20][30];
```

# Pointers and Arrays

## ■ Pointers and Arrays

- 1D array notation is simply a disguised use of pointers.
- That is, if `flizny` is an array, the following is true:

```
flizny == &flizny[0];
// name of array is the address of the first element
```

# Pointers and Arrays

## ■ The pnt\_add.c Program

```
#include <stdio.h>
#define SIZE 4


int main(void)
{
 short dates [SIZE];
 short * pti;
 short index;
 double bills[SIZE];
 double * ptf;

 pti = dates; // assign address of array to pointer
 ptf = bills;
 printf("%23s %10s\n", "short", "double");
 for (index = 0; index < SIZE; index ++){
 printf("pointers + %d: %10p %10p\n",
 index, pti + index, ptf + index);
 }

 return 0;
}
```

# Pointers and Arrays

## ■ The pnt\_add.c Program



```
C:\WDev-CppWpnt_add.exe

 short double
pointers + 0: 0x0064fd20 0x0064fd28
pointers + 1: 0x0064fd22 0x0064fd30
pointers + 2: 0x0064fd24 0x0064fd38
pointers + 3: 0x0064fd26 0x0064fd40
계속하려면 아무 키나 누르십시오 . . .
```

# Pointers and Arrays

## ■ The pnt\_add.c Program

- What?

0x0064fd20 + 1 is 0x0064fd22?

0x0064fd30 + 1 is 0x0064fd38?

Difference between


int \*

char \*

: addition/subtraction operator

# Pointers and Arrays

## ■ An array and pointer addition



```
int dates[y], *pti;
pti = dates; (or pti = & dates[0];)
```



pointer variable `pti` is assigned the  
address of the first element of the array `dates`

# Pointers and Arrays

## ■ An array and pointer addition

- As a result of C's cleverness, you have the following equalities:

```
dates +2 == &date[2] /* same address */

(dates + 2) == dates[2] / same value */
```



# Pointers and Arrays

## ■ An array and pointer addition

- Operator Precedence

```
(dates +2) / value of the 3rd element of dates */
dates +2 / 2 added to the value of the 1st element */
```

# Pointers and Arrays

## ■ The day\_mon3.c Program

```
#include <stdio.h>
#define MONTHS 12


int main(void)
{
 int days[MONTHS] = {31, 28, 31, 30, 31, 30, 31, 31, 30, 31, 30, 31};
 int index;

 for (index = 0; index < MONTHS; index++)
 printf("Month %2d has %d days.\n", index + 1,
 *(days + index)); // same as days[index]

 return 0;
}
```

# Pointers and Arrays

## ■ The day\_mon3.c Program



```
C:\WDev-Cpp\Wday_mon3.exe
Month 1 has 31 days.
Month 2 has 28 days.
Month 3 has 31 days.
Month 4 has 30 days.
Month 5 has 31 days.
Month 6 has 30 days.
Month 7 has 31 days.
Month 8 has 31 days.
Month 9 has 30 days.
Month 10 has 31 days.
Month 11 has 30 days.
Month 12 has 31 days.
계속하려면 아무 키나 누르십시오 . . .
```

# Functions, Arrays, and Pointers

## ■ Functions, Arrays, and Pointers

- Given an array

```
total = sum(marbles); // possible function call
```

# Functions, Arrays, and Pointers

## ■ Functions, Arrays, and Pointers

- What would the prototype be?
- 

```
int sum(int * ar); // corresponding prototype
```

# Functions, Arrays, and Pointers

## ■ Functions, Arrays, and Pointers

- 

```
int sum(int *ar) // corresponding definition
{
 int i;
 int total = 0;

 for(i = 0; i < 10; i++) // assume 10 elements
 total += ar[i]; // ar[i] the same as *(ar + i)
return total;
}
```

# Functions, Arrays, and Pointers

## ■ Functions, Arrays, and Pointers

- A more flexible approach is to pass the array size as a second argument:

```
int sum(int * ar, int n) // more general approach
{
 int i;
 int total = 0;

 for(i = 0; i < n; i++) // use n elements
 total += ar[i]; // ar[i] the same as *(ar + i)
return total;
}
```

```
int sum (int ar[], int n);
```

# Functions, Arrays, and Pointers

## ■ The `sum_arr2.c` Program

```
#include <stdio.h>
#define SIZE 10

int sump(int * start, int * end);
int main(void)
{
 int marbles[SIZE] = {20,10,5,39,4,16,19,26,31,20};
 long answer;
 answer = sump(marbles, marbles + SIZE);
 printf("The total number of marbles is %ld.\n", answer);

 return 0;
}
/* use pointer arithmetic */


int sump(int * start, int * end)
{
 int total = 0;

 while (start < end)
 {
 total += *start; /* add value to total */
 start++; /* advance pointer to next element */
 }
 return total;
}
```



# Functions, Arrays, and Pointers

## ■ The sum\_arr2.c Program



```
C:\WDev-Cpp\sum_arr2.exe
The total number of marbles is 190.
계속하려면 아무 키나 누르십시오 . . .
```

# Functions, Arrays, and Pointers

## ■ The sum\_arr2.c Program

- Uses

```
while (start < end)
```

```
total += *start++;
```

Instead of

```
for(i = 0; i < n; i++)
```

# Functions, Arrays, and Pointers

## ■ The `sum_arr2.c` Program

- Note that using this "past-the-end" pointer makes the function call neat:

```
answer = sump(marbles, marbles + SIZE);
```

# Functions, Arrays, and Pointers

## ■ The order.c Program

```
#include <stdio.h>

int data[2] = {100, 200};
int moredata[2] = {300, 400};


int main(void)
{
 int * p1, * p2, * p3;

 p1 = p2 = data;
 p3 = moredata;
 printf(" *p1 = %d, *p2 = %d, *p3 = %d\n",
 *p1, *p2, *p3);
 printf("*p1++ = %d, *++p2 = %d, (*p3)++ = %d\n",
 *p1++, *++p2, (*p3)++);
 printf(" *p1 = %d, *p2 = %d, *p3 = %d\n",
 *p1, *p2, *p3);

 return 0;
}
```

# Functions, Arrays, and Pointers

## ■ The order.c Program



```
C:\WDev-Cpp\Word.exe
*p1 = 100, *p2 = 100, *p3 = 300
*p1++ = 100, *++p2 = 200, (*p3)++ = 300
*p1 = 200, *p2 = 200, *p3 = 301
계속하려면 아무 키나 누르십시오 . . .
```

# Functions, Arrays, and Pointers

## ■ Comment: Pointers and Arrays

- the two expressions `ar[i]` and `* (ar+i)` are equivalent in meaning.
- However, using an expression such as `ar++` only works if `ar` is a pointer variable.

# Pointer Operations

## ■ The ptr\_ops.c Program(1/2)

```
#include <stdio.h>

int main(void)
{
 int urn[5] = {100,200,300,400,500};
 int * ptr1, * ptr2, *ptr3;

 ptr1 = urn; // assign an address to a pointer
 ptr2 = &urn[2]; // ditto

 printf("pointer value, dereferenced pointer, pointer address:\n");
 printf("ptr1 = %p, *ptr1=%d, &ptr1 = %p\n",
 ptr1, *ptr1, &ptr1);

 // pointer addition
 ptr3 = ptr1 + 4;
 printf("\nadding an int to a pointer:\n");
 printf("ptr1 + 4 = %p, *(ptr4 + 3) = %d\n",
 ptr1 + 4, *(ptr1 + 3));
 ptr1++; // increment a pointer

 printf("\nvalues after ptr1++:\n");
 printf("ptr1 = %p, *ptr1=%d, &ptr1 = %p\n",
 ptr1, *ptr1, &ptr1);
 ptr2--; // decrement a pointer
```

# Pointer Operations

## ■ The ptr\_ops.c Program(2/2)

```
printf("\nvalues after --ptr2:\n");
printf("ptr2 = %p, *ptr2 = %d, &ptr2 = %p\n",
 ptr2, *ptr2, &ptr2);

--ptr1; // restore to original value
++ptr2; // restore to original value


printf("\nPointers reset to original values:\n");
printf("ptr1 = %p, ptr2 = %p\n", ptr1, ptr2);
 // subtract one pointer from another
printf("\nsubtracting one pointer from another:\n");
printf("ptr2 = %p, ptr1 = %p, ptr2 - ptr1 = %d\n",
 ptr2, ptr1, ptr2 - ptr1);
 // subtract an integer from a pointer
printf("\nsubtracting an int from a pointer:\n");
printf("ptr3 = %p, ptr3 - 2 = %p\n",
 ptr3, ptr3 - 2);

return 0;
}
```



# Pointer Operations

## ■ The ptr\_ops.c Program



```
C:\WDev-Cpp\ptr_ops.exe

pointer value, dereferenced pointer, pointer address:
ptr1 = 0022FF50, *ptr1 = 100, &ptr1 = 0022FF4C

adding an int to a pointer:
ptr1 + 4 = 0022FF60, *(ptr4 + 3) = 400

values after ptr1++:
ptr1 = 0022FF54, *ptr1 = 200, &ptr1 = 0022FF4C

values after --ptr2:
ptr2 = 0022FF54, *ptr2 = 200, &ptr2 = 0022FF48

Pointers reset to original values:
ptr1 = 0022FF50, ptr2 = 0022FF58

subtracting one pointer from another:
ptr2 = 0022FF58, ptr1 = 0022FF50, ptr2 - ptr1 = 2

subtracting an int from a pointer:
ptr3 = 0022FF60, ptr3 - 2 = 0022FF58
계속하려면 아무 키나 누르십시오 . . .
```

# Pointer Operations

## ■ The ptr\_ops.c Program

- **Assignment**
  - You can assign an address to a pointer.
  - using an array name or by using the address operator (&).
- **Value finding (dereferencing)**
  - The \* operator

# Pointer Operations

## ■ The ptr\_ops.c Program(1/2)

```
#include <stdio.h>

int main(void)
{
 int urn[5] = {100,200,300,400,500};
 int * ptr1, * ptr2, *ptr3;

 ptr1 = urn; // assign an address to a pointer
 ptr2 = &urn[2]; // ditto

 printf("pointer value, dereferenced pointer, pointer address:\n");
 printf("ptr1 = %p, *ptr1=%d, &ptr1 = %p\n",
 ptr1, *ptr1, &ptr1);

 // pointer addition
 ptr3 = ptr1 + 4;
 printf("\nadding an int to a pointer:\n");
 printf("ptr1 + 4 = %p, *(ptr4 + 3) = %d\n",
 ptr1 + 4, *(ptr1 + 3));
 ptr1++; // increment a pointer

 printf("\nvalues after ptr1++:\n");
 printf("ptr1 = %p, *ptr1=%d, &ptr1 = %p\n",
 ptr1, *ptr1, &ptr1);
 ptr2--; // decrement a pointer
```

# Pointer Operations

## ■ The ptr\_ops.c Program

- **Taking a pointer address**
  - Like all variables, pointer variables have an address and a value.
  - The & operator tells you where the pointer itself is stored.
- **Adding an integer to a pointer**
  - You can use the + operator to add an integer to a pointer or a pointer to an integer.
- **Incrementing a pointer**
  - Incrementing a pointer (++) makes it move to the next element of the array.

# Pointer Operations

## ■ The ptr\_ops.c Program

- **Differencing (Subtraction)**

- You can find the difference between two pointers.
- Normally, you do this for two pointers to elements that are in the same array to find out how far apart the elements are.

- **Comparisons**

- You can use the relational operators to compare the values of two pointers, provided the pointers are of the same type.

# Protecting Array Contents

## ■ Protecting Array Contents

- Here's a function that adds the same value to each member of an array:

```
void add_to(double ar[], int n, double val)
{
 int i;
 for(i = 0; i < n; i++)
 ar[i] += val;
}
```

- Therefore, the function call

```
add_to(prices, 100, 2.50);
```

# Protecting Array Contents

## ■ Using const with Formal Parameters

- If a function's intent is that it not change the contents of the array,
- use the keyword `const`
- Ex) the prototype and definition for `sum()` should look like this:

```
int sum(const int ar[], int n); /* prototype */

int sum(const int ar[], int n) /* definition */
{
 int i;
 int total = 0;

 for(i = 0; i < n; i++)
 total += ar[i];
 return total;
}
```

# Protecting Array Contents

## ■ The arf.c Program(1/2)

```
#include <stdio.h>
#define SIZE 5

void show_array(const double ar[], int n);
void mult_array(double ar[], int n, double mult);
int main(void)
{
 double dip[SIZE] = {20.0, 17.66, 8.2, 15.3, 22.22};

 printf("The original dip array:\n");
 show_array(dip, SIZE);
 mult_array(dip, SIZE, 2.5);
 printf("The dip array after calling mult_array():\n");
 show_array(dip, SIZE);

 return 0;
}
```



# Protecting Array Contents

## ■ The arf.c Program(2/2)

```
/* displays array contents */
void show_array(const double ar[], int n)
{
 int i;


 for (i = 0; i < n; i++)
 printf("%8.3f ", ar[i]);
 putchar('\n');
}

/* multiplies each array member by the same multiplier */
void mult_array(double ar[], int n, double mult)
{
 int i;

 for (i = 0; i < n; i++)
 ar[i] *= mult;
}
```

# Protecting Array Contents

## ■ The arf.c Program



```
C:\WDev-Cpp\Warf.exe
The original dip array:
 20.000 17.660 8.200 15.300 22.220
The dip array after calling mult_array():
 50.000 44.150 20.500 38.250 55.550
계속하려면 아무 키나 누르십시오 . . .
```

# Protecting Array Contents

## ■ More About const

- Earlier, you saw that you can use `const` to create symbolic constants:

```
const double PI = 3.14159;
```

- Listing 10.4 showed how to use the `const` keyword to protect an array:

```
#define MONTHS 12
...
const int days[MONTHS] = {31, 28, 31, 30, 31, 30, 31, 31, 30, 31, 30, 31};
```

# Protecting Array Contents

## ■ More About const

- If the program code subsequently tries to alter the array, you'll get a compile-time error message:

```
days[9] = 44; /* compile error */
```

- Another example

```
double rates[5] = {88.99, 100.12, 59.45, 183.11, 340.5};
const double * pd = rates;
// pd points to beginning of the array
```

```
*pd = 29.89; // not allowed
pd[2] = 222.22; // not allowed
rates[0] = 99.99; // allowed because rates is not const
```

```
pd++; /* make pd point to rates[1] -- allowed */
```

# Protecting Array Contents

## ■ More About const

- A pointer-to-constant is usually used as a function parameter to indicate that the function won't use the pointer to change data.
- For example, the `show_array()` function from Listing 10.14 could have been prototyped as

```
void show_array(const double *ar, int n);
```

# Protecting Array Contents

## ■ Quiz

- ```
double rates[5] = {88.99, 100.12, 59.45, 183.11, 340.5};  
const double locked[4] = {0.08, 0.075, 0.0725, 0.07};  
const double * pc = rates;  
pc = locked;  
pc = &rates[3];
```

```
double rates[5] = {88.99, 100.12, 59.45, 183.11, 340.5};  
const double locked[4] = {0.08, 0.075, 0.0725, 0.07};  
double * pnc = rates;  
pnc = locked;  
pnc = &rates[3];
```

```
show_array(rates, 5);  
show_array(locked, 4);
```

```
mult_array(rates, 5, 1.2);  
mult_array(locked, 4, 1.2);
```

Protecting Array Contents

■ More About const

- Locking the pointer itself:
- The trick is the placement of the keyword `const`:

```
double rates[5] = {88.99, 100.12, 59.45, 183.11, 340.5};  
double * const pc = rates;      // pc points to beginning of the array  
pc = &rates[2];                // not allowed  
*pc = 92.99;                   // ok -- changes rates[0]
```

Protecting Array Contents

■ More About const

- Finally, you can use const twice to create a pointer that can neither change where it's pointing nor change the value to which it points:

```
double rates[5] = {88.99, 100.12, 59.45, 183.11, 340.5};  
const double * const pc = rates;  
pc = &rates[2];           // not allowed  
*pc = 92.99;              // not allowed
```


Pointers and Multidimensional Arrays

■ Pointers and Multidimensional Arrays

- How do pointers relate to multidimensional arrays?
- And why would you want to know?
- Functions that work with multidimensional arrays do so with pointers,
 - so you need some further pointer background before working with such functions.

Pointers and Multidimensional Arrays

■ Pointers and Multidimensional Arrays

- Suppose you have this declaration:

```
int zippo[4][2];  /* an array of arrays of ints */
```

- Then zippo, being the name of an array,
 - is the address of the first element of the array.

Pointers and Multidimensional Arrays

■ Pointers and Multidimensional Arrays

- Let's analyze that further in terms of pointer properties:
- Because `zippo` is the address of the array's first element, `zippo` has the same value as `&zippo[0]`.
- Adding 1 to a pointer or address yields a value larger by the size of the referred-to object.
- Dereferencing a pointer or an address yields the value represented by the referred-to object.

Pointers and Multidimensional Arrays

■ The zippo1.c Program

```
#include <stdio.h>


int main(void)
{
    int zippo[4][2] = { {2,4}, {6,8}, {1,3}, {5, 7} };

    printf("    zippo = %p,    zippo + 1 = %p\n",
           zippo,          zippo + 1);
    printf("zippo[0] = %p, zippo[0] + 1 = %p\n",
           zippo[0],       zippo[0] + 1);
    printf(" *zippo = %p,  *zippo + 1 = %p\n",
           *zippo,         *zippo + 1);
    printf("zippo[0][0] = %d\n", zippo[0][0]);
    printf(" *zippo[0] = %d\n", *zippo[0]);
    printf(" **zippo = %d\n", **zippo);
    printf("    zippo[2][1] = %d\n", zippo[2][1]);
    printf("*(*(zippo+2) + 1) = %d\n", *(*zippo+2) + 1));

    return 0;
}
```

Pointers and Multidimensional Arrays

■ The zippo1.c Program



```
C:\WDev-CppWzippo1.exe

zippo = 0022FF50,      zippo + 1 = 0022FF58
zippo[0] = 0022FF50,  zippo[0] + 1 = 0022FF54
*zippo = 0022FF50,    *zippo + 1 = 0022FF54
zippo[0][0] = 2
*zippo[0] = 2
**zippo = 2
      zippo[2][1] = 3
*(*zippo+2) + 1 = 3
계속하려면 아무 키나 누르십시오 . . .
```

Pointers and Multidimensional Arrays

■ The `zippo1.c` Program


- You probably should make the effort at least once in your life to break this down.
- Let's build up the expression in steps:

<code>zippo</code>	the address of the first two- <code>int</code> element
<code>zippo+2</code>	the address of the third two- <code>int</code> element
<code>*(zippo+2)</code>	the third element, a two- <code>int</code> array, hence the address of its first element, an <code>int</code>
<code>*(zippo+2)+1</code>	the address of the second element of the two- <code>int</code> array, also an <code>int</code>
<code>*(*(zippo+2)+1)</code>	the value of the second <code>int</code> in the third row (<code>zippo[2][1]</code>)

Pointers and Multidimensional Arrays

■ The zippo1.c Program

- An array of arrays



Pointers and Multidimensional Arrays

■ Pointers to Multidimensional Arrays

- `pz` must point to an array of two `ints`, not to a single `int`.

```
int (* pz)[2]; // pz points to an array of 2 ints
```

- This statement says that `pz` is a pointer to an array of two `ints`.
- Why the parentheses? Well, `[]` has a higher precedence than `*`.
 - Therefore, with a declaration such as

```
int * pax[2];
```


Pointers and Multidimensional Arrays

■ The zippo2.c Program

```
#include <stdio.h>


int main(void)
{
    int zippo[4][2] = { {2,4}, {6,8}, {1,3}, {5,7} };
    int (*pz)[2];
    pz = zippo;

    printf("    pz = %p,    pz + 1 = %p\n",
           pz, pz + 1);
    printf("pz[0] = %p, pz[0] + 1 = %p\n",
           pz[0], pz[0] + 1);
    printf("    *pz = %p,    *pz + 1 = %p\n",
           *pz, *pz + 1);
    printf("pz[0][0] = %d\n", pz[0][0]);
    printf("    *pz[0] = %d\n", *pz[0]);
    printf("    **pz = %d\n", **pz);
    printf("    pz[2][1] = %d\n", pz[2][1]);
    printf("*(* (pz+2) + 1) = %d\n", *(* (pz+2) + 1));

    return 0;
}
```

Pointers and Multidimensional Arrays

■ The zippo2.c Program



```
C:\WDev-CppWzippo2.exe
pz = 0022FF50,    pz + 1 = 0022FF58
pz[0] = 0022FF50, pz[0] + 1 = 0022FF54
*pz = 0022FF50,  *pz + 1 = 0022FF54
pz[0][0] = 2
*pz[0] = 2
**pz = 2
    pz[2][1] = 3
*(<*(pz+2) + 1) = 3
계속하려면 아무 키나 누르십시오 . . .
```

Pointers and Multidimensional Arrays

■ The zippo2.c Program

- you can represent individual elements by using array notation or pointer notation with either an array name or a pointer:

```
zippo[m][n] == * (* (zippo + m) + n)
```

```
pz[m][n] == * (* (pz + m) + n)
```

Pointers and Multidimensional Arrays

■ Pointer Compatibility

- The rules for assigning one pointer to another are tighter than the rules for numeric types.
- Ex) you can assign an int value to a double variable without using a type conversion, but you can't do the same for pointers to these two types:

```
int n = 5;
double x;
int * p1 = &n;
double * pd = &x;

x = n;           // implicit type conversion
pd = p1;         // compile-time error
```

Pointers and Multidimensional Arrays

■ Pointer Compatibility

- These restrictions extend to more complex types.
- Suppose we have the following declarations:

```
int * pt;  
int (*pa) [3];  
int ar1[2][3];  
int ar2[3][2];  
int **p2;    // a pointer to a pointer
```

Pointers and Multidimensional Arrays

■ Pointer Compatibility

- Then we have the following:

```
pt = &ar1[0][0];           // both pointer-to-int
pt = ar1[0];               // both pointer-to-int
pt = ar1;                  // not valid
pa = ar1;                  // both pointer-to-int[3]
pa = ar2;                  // not valid
p2 = &pt;                  // both pointer-to-int *
*p2 = ar2[0];             // both pointer-to-int
p2 = ar2;                  // not valid
```

Pointers and Multidimensional Arrays

■ Pointer Compatibility

- In general, multiple indirection is tricky. For instance, consider the next snippet of code:

```
int * p1;  
const int * p2;  
const int ** pp2;  
  
p1 = p2;    // not valid -- assigning const to non-const  
p2 = p1;    // valid      -- assigning non-const to const  
pp2 = &p1;  // not valid -- assigning non-const to const
```

Pointers and Multidimensional Arrays

■ Pointer Compatibility

- As you saw earlier, assigning a `const` pointer to a non-`const` pointer is invalid, because you could use the new pointer to alter `const` data.
- But assigning a non-`const` pointer to a `const` pointer is okay, provided that you're dealing with just one level of indirection:

```
p2 = p1; // valid -- assigning non-const to const
```


Pointers and Multidimensional Arrays

■ Pointer Compatibility

- But such assignments no longer are safe when you go to two levels of indirection.
- If it were allowed, you could do something like this:

```
const int **pp2;  
int *p1;  
const int n = 13;  
  
pp2 = &p1; // not allowed, but suppose it were  
*pp2 = &n; // valid, both const, but sets p1 to point at n  
*p1 = 10;  // valid, but changes const n
```

Pointers and Multidimensional Arrays

■ Functions and Multidimensional Arrays

- Let's write a function to deal with two-dimensional arrays.
- One possibility is to use a `for` loop to apply a one-dimensional array function to each row of the two-dimensional array.
- That is, you could do something like the following:

```
int junk[3][4] = { {2,4,5,8}, {3,5,6,9}, {12,10,8,6} };
int i, j;
int total = 0;

for (i = 0; i < 3 ; i++)
    total += sum(junk[i], 4);
    // junk[i]--one-dimensional array
```

Pointers and Multidimensional Arrays

■ Functions and Multidimensional Arrays

- You can declare a function parameter of this type like this:

```
void somefunction( int (* pt)[4] );
```

- Alternatively, if (and only if) `pt` is a formal parameter to a function, you can declare it as follows:

```
void somefunction( int pt[][4] );
```

Pointers and Multidimensional Arrays

■ The array2d.c Program(1/3)

```
#include <stdio.h>
#define ROWS 3
#define COLS 4

void sum_rows(int ar[][COLS], int rows);
void sum_cols(int [][COLS], int );    // ok to omit names
int sum2d(int (*ar)[COLS], int rows); // another syntax
int main(void)
{
    int junk[ROWS][COLS] = {
        {2,4,6,8},
        {3,5,7,9},
        {12,10,8,6}
    };

    sum_rows(junk, ROWS);
    sum_cols(junk, ROWS);
    printf("Sum of all elements = %d\n", sum2d(junk, ROWS));

    return 0;
}
```

Pointers and Multidimensional Arrays

■ The array2d.c Program(2/3)

```
void sum_rows(int ar[][COLS], int rows)
{
    int r;
    int c;
    int tot;

    for (r = 0; r < rows; r++)
    {
        tot = 0;
        for (c = 0; c < COLS; c++)
            tot += ar[r][c];
        printf("row %d: sum = %d\n", r, tot);
    }
}

void sum_cols(int ar[][COLS], int rows)
{
    int r;
    int c;
    int tot;

    for (c = 0; c < COLS; c++)
    {
        tot = 0;
        for (r = 0; r < rows; r++)
            tot += ar[r][c];
        printf("col %d: sum = %d\n", c, tot);
    }
}
```

Pointers and Multidimensional Arrays

■ The array2d.c Program(3/3)


```
int sum2d(int ar[][COLS], int rows)
{
    int r;
    int c;
    int tot = 0;

    for (r = 0; r < rows; r++)
        for (c = 0; c < COLS; c++)
            tot += ar[r][c];

    return tot;
}
```

Pointers and Multidimensional Arrays

■ The array2d.c Program



```
C:\WDev-CppWarray2d.exe
row 0: sum = 20
row 1: sum = 24
row 2: sum = 36
col 0: sum = 17
col 1: sum = 19
col 2: sum = 21
col 3: sum = 23
Sum of all elements = 80
계속하려면 아무 키나 누르십시오 . . .
```

Pointers and Multidimensional Arrays

■ The array2d.c Program

- Be aware that the following declaration will not work properly:

```
int sum2(int ar[][], int rows); // faulty declaration
```

- The declaration

```
int sum2(int ar[][4], int rows); // valid declaration
```

- says that `ar` points to an array of four ints,
 - so `ar+1` means "add 16 bytes to the address."

Pointers and Multidimensional Arrays

■ The array2d.c Program

- You can also include a size in the other bracket pair, as shown here, but the compiler ignores it:

```
int sum2(int ar[3][4], int rows);  
// valid declaration, 3 ignored
```

- This is convenient for those who use typedefs:

```
typedef int arr4[4];           // arr4 array of 4 int  
typedef arr4 arr3x4[3];       // arr3x4 array of 3 arr4  
  
int sum2(arr3x4 ar, int rows); // same as next declaration  
int sum2(int ar[3][4], int rows); // same as next declaration  
int sum2(int ar[][4], int rows); // standard form
```

Pointers and Multidimensional Arrays

■ The array2d.c Program

- In general, to declare a pointer corresponding to an N -dimensional array, you must supply values for all but the leftmost set of brackets:

```
int sum4d(int ar[][12][20][30], int rows);
```

- That's because the first set of brackets indicates a pointer,
- whereas the rest of the brackets describe the type of data object being pointed to, as the following equivalent prototype illustrates:

```
int sum4d(int (*ar)[12][20][30], int rows);
```

Variable-Length Arrays (VLAs)

■ Variable-Length Arrays (VLAs)

- You can describe the number of rows with a function parameter, but the number of columns is built in to the function.
- For example, look at this definition:

```
#define COLS 4

int sum2d(int ar[][COLS], int rows)
{
    int r;
    int c;
    int tot = 0;

    for (r = 0; r < rows; r++)
        for (c = 0; c < COLS; c++)
            tot += ar[r][c];
    return tot;
}
```

Variable-Length Arrays (VLAs)

■ Variable-Length Arrays (VLAs)

- Next, suppose the following arrays have been declared:

```
int array1[5][4];  
int array2[100][4];  
int array3[2][4];
```

- You can use the `sum2d()` function with any of these arrays:

```
tot = sum2d(array1, 5);    // sum a 5 x 4 array  
tot = sum2d(array2, 100);  // sum a 100 x 4 array  
tot = sum2d(array3, 2);    // sum a 2 x 4 array
```

Variable-Length Arrays (VLAs)

■ Variable-Length Arrays (VLAs)

- C is being positioned to take over from FORTRAN,
- so the ability to convert FORTRAN libraries with a minimum of fuss is useful.
- This need was the primary impulse for C99 introducing variable-length arrays, which allow you to use variables when dimensioning an array.
 - For example, you can do this:

```
int quarters = 4;  
int regions = 5;  
double sales[regions][quarters]; // a VLA
```

Variable-Length Arrays (VLAs)

■ Variable-Length Arrays (VLAs)

- Let's look at a simple example that shows how to write a function that will sum the contents of any two-dimensional array of `ints`.
- First, here's how to declare a function with a two-dimensional VLA argument:

```
int sum2d(int rows, int cols, int ar[rows][cols]); // ar a VLA
```

Variable-Length Arrays (VLAs)

■ Variable-Length Arrays (VLAs)

- Note that the first two parameters are used as dimensions for declaring the array parameter `ar`.
- Because the `ar` declaration uses `rows` and `cols`, they have to be declared before `ar` in the parameter list.
 - Therefore, the following prototype is in error:

```
int sum2d(int ar[rows][cols], int rows, int cols);  
// invalid order
```

Variable-Length Arrays (VLAs)

■ Variable-Length Arrays (VLAs)

- The C99 standard says you can omit names from the prototype.
- but in that case, you need to replace the omitted dimensions with asterisks:

```
int sum2d(int, int, int ar[*][*]);
```

- Second, here's how to define the function:

```
int sum2d(int rows, int cols, int ar[rows][cols])
{
    int r;
    int c;
    int tot = 0;

    for (r = 0; r < rows; r++)
        for (c = 0; c < cols; c++)
            tot += ar[r][c];
    return tot;
}
```


Variable-Length Arrays (VLAs)

■ The vararr2d.c Program(1/2)

```
#include <stdio.h>
#define ROWS 3
#define COLS 4

int sum2d(int rows, int cols, int ar[rows][cols]);
int main(void)
{
    int i, j;
    int rs = 3;
    int cs = 10;
    int junk[ROWS][COLS] = {
        {2,4,6,8},
        {3,5,7,9},
        {12,10,8,6}
    };
    int morejunk[ROWS-1][COLS+2] = {
        {20,30,40,50,60,70},
        {5,6,7,8,9,10}
    };
    int varr[rs][cs]; // VLA

    for (i = 0; i < rs; i++)
        for (j = 0; j < cs; j++)
            varr[i][j] = i * j + j;
```

Variable-Length Arrays (VLAs)

■ The vararr2d.c Program(2/2)

```
    for (i = 0; i < rs; i++)
        for (j = 0; j < cs; j++)
            varr[i][j] = i * j + j;


    printf("3x5 array\n");
    printf("Sum of all elements = %d\n",
           sum2d(ROWS, COLS, junk));
    printf("2x6 array\n");
    printf("Sum of all elements = %d\n",
           sum2d(ROWS-1, COLS+2, morejunk));
    printf("3x10 VLA\n");
    printf("Sum of all elements = %d\n",
           sum2d(rs, cs, varr));
    return 0;
}

// function with a VLA parameter
int sum2d(int rows, int cols, int ar[rows][cols])
{
    int r;
    int c;
    int tot = 0;

    for (r = 0; r < rows; r++)
        for (c = 0; c < cols; c++)
            tot += ar[r][c];
    return tot;
}
```

Variable-Length Arrays (VLAs)

■ The vararr2d.c Program



```
C:\WDev-Cpp\Wvararr2d.exe
3x5 array
Sum of all elements = 80
2x6 array
Sum of all elements = 315
3x10 VLA
Sum of all elements = 270
계속하려면 아무 키나 누르십시오 . . .
```

Variable-Length Arrays (VLAs)

■ The vararr2d.c Program

- The following snippet points out when a pointer is declared and when an actual array is declared:

```
    int thing[10][6];
    twoset(10,6,thing);
    ...
}
void twoset (int n, int m, int ar[n][m])    // ar a pointer to
                                           // an array of m ints
{
    int temp[n][m];    // temp an n x m array of int
    temp[0][0] = 2;    // set an element of temp to 2
    ar[0][0] = 2;      // set thing[0][0] to 2
}
```

Compound Literals

■ Compound Literals

- For arrays, a compound literal looks like an array initialization list preceded by a type name that is enclosed in parentheses.
- For example, here's an ordinary array declaration:

```
int diva[2] = {10, 20};
```

- And here's a compound literal that creates a nameless array containing the same two `int` values:

```
(int [2]){10, 20}      // a compound literal
```

Compound Literals

■ Compound Literals

- Just as you can leave out the array size if you initialize a named array,
- you can omit it from a compound literal, and the compiler will count how many elements are present:

```
(int []) {50, 20, 90} // a compound literal with 3 elements
```

- One way is to use a pointer to keep track of the location.
 - That is, you can do something like this:

```
int * pt1;  
pt1 = (int [2]) {10, 20};
```

Compound Literals

■ Compound Literals

- Another thing you could do with a compound literal is pass it as an actual argument to a function with a matching formal parameter:

```
int sum(int ar[], int n);  
...  
int total3;  
total3 = sum((int []){4,4,4,5,5,5}, 6);
```

- You can extend the technique to two-dimensional arrays, and beyond.
- Here, for example, is how to create a two-dimensional array of `ints` and store the address:

```
int (*pt2)[4];  
pt2 = (int [2][4]) { {1,2,3,-9}, {4,5,6,-8} };
```

Compound Literals

■ The flc.c Program(1/2)

```
#include <stdio.h>
#define COLS 4

int sum2d(int ar[][COLS], int rows);
int sum(int ar[], int n);
int main(void)
{
    int total1, total2, total3;
    int * pt1;
    int (*pt2)[COLS];

    pt1 = (int [2]) {10, 20};
    pt2 = (int [2][COLS]) { {1, 2, 3, -9}, {4, 5, 6, -8} };

    total1 = sum(pt1, 2);
    total2 = sum2d(pt2, 2);
    total3 = sum((int []){4, 4, 4, 5, 5, 5}, 6);
    printf("total1 = %d\n", total1);
    printf("total2 = %d\n", total2);
    printf("total3 = %d\n", total3);
    return 0;
}
```


Compound Literals

■ The flc.c Program(2/2)

```
int sum(int ar[], int n)
{
    int i;
    int total = 0;


    for( i = 0; i < n; i++)
        total += ar[i];
    return total;
}

int sum2d(int ar[][COLS], int rows)
{
    int r;
    int c;
    int tot = 0;

    for (r = 0; r < rows; r++)
        for (c = 0; c < COLS; c++)
            tot += ar[r][c];
    return tot;
}
```

Compound Literals

■ The flc.c Program



```
C:\WDev-CppWflc.exe  
total1 = 30  
total2 = 4  
total3 = 27  
계속하려면 아무 키나 누르십시오 . . .
```